



**GOVERNMENT OF PAKISTAN
FEDERAL BOARD OF REVENUE
CORPORATE TAX OFFICE, LAHORE
TAX HOUSE, SYED MAUJ DARYA ROAD, LAHORE**

TENDER NOTICE NO. 02 / 2023-24 3046

DATED:01.04.2024

Sealed bids are invited from firms which are registered with Inland Revenue Department as Income Tax / Sales Taxpayers and are also on Active Taxpayers List (ATL) for the for the supply / Installation of the following work:

Dry Gel Battery, Electric Light, Electric Circuit Breaker, Electric Power Cable & Filter Assembly: -

LOT No	EQUIPMENT / ITEMS	CATEGORY	SPECIFICATION
1	Dry Gel Battery	Ratings 12V - 40AH	Application: UPS, Technology: Gel (Pure Gel Technology), Voltage [V]: 12V Capacity: 40Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use, Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs), Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6-10years
		Ratings 12V - 26AH	Application: UPS, Technology: Gel (Pure Gel Technology) Voltage [V]: 12V, Capacity: 26Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use, Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs), Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6-10years
		Ratings 12V - 20AH	Application: UPS, Technology: Gel (Pure Gel Technology), Voltage [V]: 12V Capacity: 20Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use, Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs), Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6-10years
		Battery Extension Cable	Parallel cable for battery extension with copper thimble crimped round crimp terminals at both ends with nut bolts. According to the rating of batteries (12V - 40AH), (12V - 26AH), (12V - 20AH).
Batteries installation, configuration and Commissioning. (Before installing all batteries, the UPS and battery bank must be serviced)			
2	Electric Light	SMD Panel Light	Lighting Technology: SMD, Ceiling Panel Light Size: 2x2, Voltage: AC ~ 165 – 265V, Color: White, Wattage: 72, Color Temperature: 6500K Cool White, Cut Size: 595x595mm / 600x600mm, Surge Protection: 2.5KV, Life Time: Minimum 30,000 Hours.
		SMD Panel Light Slim Panel (Round)	Lighting Technology: SMD, Ceiling Panel Square Size: 6"-inch, Voltage: AC ~ 165 – 265V, Color: White, Wattage: 18, Color Temperature: 6500K Cool White, Cut Size: 595x595mm / 600x600mm, Surge Protection: 2.5KV, Life Time: Minimum 30,000 Hours. Material: Aluminum
		LED Bulb	Cap-Base: E27, Wattage: 13, Nominal lifetime: 25,000 hour(s), Switching Cycle: 50,000, Lighting Technology: LED, Color Temperature: 6500K Cool White.
		LED Bulb	Cap-Base: E27, Wattage: 13, Nominal lifetime: 25,000 hour(s), Switching Cycle: 50,000, Lighting Technology: LED, Color Temperature: 3000K Warm White.
3	Electric Circuit Breaker	MCCB Electric Circuit Breaker 400Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 400A, Number of Pole: 4, Breaking Capacity: 50 kA at 415 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
		MCCB Electric Circuit Breaker 250Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 250A, Number of Pole: 3, Breaking Capacity: 50 kA at 265 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
		MCCB Electric Circuit Breaker 200Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 200A, Number of Pole: 3, Breaking Capacity: 50 kA at 215 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
		MCCB Electric Circuit Breaker 125Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 125A, Number of Pole: 3, Breaking Capacity: 50 kA at 135 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed

		MCB Electric Circuit Breaker 32Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 32A, Number of Pole: 3, Breaking Capacity: 15 kA at 47 VAC, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
		MCB Electric Circuit Breaker 20Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 20A, Number of Pole: 2, Breaking Capacity: 4.5KA-20KA, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
		MCB Electric Circuit Breaker 16/20Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 16/20A, Number of Pole: 1, Breaking Capacity: 07 kA at 27 VAC, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed
4	Electric Power Cable	Electric Power Cable 40x76	Electric Power Cable Size: 40x76, Core: 2-Core, Color: Red, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall
		Electric Power Cable 7x36	Electric Power Cable Size: 7x36, Core: 1-Core, Color: Red, Black, Green Earth Wire, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall
		Electric Power Cable 7x29	Electric Power Cable Size: 7x29, Core: 1-Core, Color: Red, Green Earth Wire, Yellow, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall
		Electric Power Cable 3x29	Electric Power Cable Size: 3x29, Core: 1-Core, Color: Red, Green Earth Wire, Yellow, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall
		Coaxial cable RG7	Coaxial cable Size: RG7, Inner Conductor: Copper Wire, Gauge 100% Copper, Dielectric: Gas Injected Foamed, Foil Shield Screen-1: Tape Aluminum / Polyester / Bonding Layer, Braid Shield (Screen-2): Copper Braid, Jacket: Outside insulation (PVC) Flame retardant PVC sheathed overall
		Coaxial cable RG11	Coaxial cable Size: RG11, Inner Conductor: Copper Wire, Gauge 100% Copper, Dielectric: Gas Injected Foamed, Foil Shield Screen-1: Tape Aluminum / Polyester / Bonding Layer, Braid Shield (Screen-2): Copper Braid, Jacket: Outside insulation (PVC) Flame retardant PVC sheathed overall
5	Filter Assembly	Genset Complete Filter Assembly	Complete Filter Assembly: 10929, 10930, 10931 Complete Filter Assembly of Perkins Generator 550 KVA Installation (Commissioning) of Genset Complete Filter Assembly.

TERMS & CONDITIONS

1. The bids will be received on or before **11.00 A.M.** by **22.04.2024** and will be opened on the same date at **02:00 PM** in the presence of the bidders or their representatives. Tender documents may be obtained from the office of the undersigned during office hours by **19.04.2024**.
2. Every bidder shall submit the samples of items at the time of opening the bids. Successful bidder will provide all items as per approved samples. Tender documents may be obtained from the office of the undersigned during office hours or may be downloaded from the PPRa Website www.ppra.org.pk. Successful bidder will provide all items as per approved samples.
3. All items are to be supplied at the office premises within 2 weeks after issuance of supply order.
4. Every bidder shall submit Earnest / Bid money @ 2% of the quoted price in the shape of deposit-at-call, bid guarantee issued by any scheduled bank of Pakistan valid for 120 days from the opening date of tender in favour of Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore.
5. All due taxes will be deducted as per government rules.
6. The Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore reserves the right to reject all bids or any part of the bids at any time prior to acceptance of the bids.



(TANVEER IQBAL)

Additional Commissioner (Hqrs)
Corporate Tax Office, Lahore
Ph: 99211717, Fax: 99211816



**GOVERNMENT OF PAKISTAN
FEDERAL BOARD OF REVENUE
CORPORATE TAX OFFICE, LAHORE
TAX HOUSE, SYED MAUJ DARYA ROAD, LAHORE**

TENDER DOCUMENT

SUPPLY & INSTALLATION OF

- 1) DRY GEL BATTERY**
- 2) ELECTRIC LIGHT**
- 3) ELECTRIC CIRCUIT BREAKER**
- 4) ELECTRIC POWER CABLE**
- 5) FILTER ASSEMBLY**

TENDER ISSUANCE DATE 01.04.2024

BID SUBMISSION DATE 22.04.2024

CORPORATE TAX OFFICE, LAHORE
TAX HOUSE, SYED MAUJ DARYA ROAD, LAHORE

No. Bud / CCIR / 3047

Dated: 01 APR 2024

SUBJECT: TENDER FOR THE PROVISION & INSTALLATION OF DRY GEL BATTERY, ELECTRIC LIGHT, ELECTRIC CIRCUIT BREAKER, ELECTRIC POWER CABLE & FILTER ASSEMBLY IN CORPORATE TAX OFFICE, LAHORE

Organization Name	Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore
Address	Tax House, Syed Mauj Darya Road
City	Lahore
Tele No.	99211717
Fax No.	99211816
Tender document No.	02 / 2023-24

Description & Instructions:

The Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore Federal Board of Revenue (hereinafter called CCIR, Corporate Tax Office, Lahore / Purchaser invites sealed tenders for the supply and installation of Dry Gel Battery, Electric Light, Electric Circuit Breaker, Electric Power Cable & Filter Assembly as per detail given in Schedule of Requirement:

- 1) If you have doubt as to the meaning of any portion of the specifications or other terms and conditions you may seek clarification from Mr. Liaqat Ali, Drawing & Disbursing Officer, **042-99210317, 0321-4538936.**
- 2) The Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore reserves the right to reject all bids at any time prior to award of Contract (s) without thereby incurring any liability to the affected bidder or bidders or any obligation to inform the affected bidder or of the grounds for Chief Commissioner's action.
- 3) Income / Withholding Taxes will be deducted in accordance with the law. The Sales Tax shall also be deducted in accordance with the law.

4) **DELIVERY SCHEDULE:**

The provision and installation of **Dry Gel Battery, Electric Light, Electric Circuit Breaker, Electric Power Cable & Filter Assembly** mentioned in Schedule of Requirement Annexure "B" is required within 2 weeks (in Lahore at the premises) after award of the contract (s) to be issued against this tender inquiry. So, the successful bidder may be in a position to complete delivery and installation with the given time frame.

5) **INSTALLATION AND IMPLEMENTATION:**

5.1 **LOT-1 Dry Gel Battery: -**

After delivery of LOT-1, the following processes must be carried out before installation, configuration and commissioning.

- a) The Bidder / contractor shall first verify that all UPS and battery banks are operational and thereafter shall cleaning and service of all UPS and battery banks.
- b) The Bidder / contractor shall ensure that all UPS and all battery banks are cleaned / serviced before installation of batteries.
- c) The Bidder / contractor shall provide commissioning certificate after installation, configuration of all batteries.

5.2 LOT-5 FILTER ASSEMBLY: -

After delivery of LOT-5, the Bidder / contractor shall install the complete filter assembly of the generator and ensure that the filter assembly is functioning properly after installation.

6) PENALTY:

For failure to comply with delivery schedule of Supply Order (s) to be issued against this tender document, penalty will be imposed on defaulting Supplier as under:

- 6.1 1% of the cost of entire supply order of such supply order(s) as remains un-supplied / un-completed for every day up to maximum of 5% for 10 days exceeding the supply period.
- 6.2 If the **Dry Gel Battery, Electric Light, Electric Circuit Breaker, Electric Power Cable & Filter Assembly** is not supplied even after payment of penalty for 10 consecutive days the Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore reserves the right to cancel the supply order and to purchase required items elsewhere at the risk and cost of the defaulting Supplier.

7) Quoted rates must be inclusive of all taxes (Sales Tax etc.) & in **Pak Rupees**.

8) Rates must be quoted including all charges like installation, configuration, travelling & transportation of the supply of **Dry Gel Battery, Electric Light, Electric Circuit Breaker, Electric Power Cable & Filter Assembly**.

9) Bidding Form Annexure "A" must also be duly filled in, stamped and signed by authorized representative of the bidder.

10) Quoted rates shall be valid for at least one (1) year from the opening date of the bid. However, any subsequent change in taxes and duties as notified by Federal Board of Revenue will be given due consideration.

11) The Bidder shall furnish as part of his bid, a call deposit / Pay Order equivalent to 2% of the total value of the bid in favour of Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore. Any bid not accompanied by Earnest Money shall be rejected without any right of appeal. In case of cancellation of Purchase Order as default of the Supplier the earnest money shall be forfeited in favour of "Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore".

12) WARNING:

There will be no compromise on quantity, quality, originality and required specifications. So, mention clearly brand name, quantity, quality and original specifications of the product.

13) PAYMENT:

100% payment of the total value of the bill / supply order will be released subject to:

- 13.1 Payment will be made on submission of bill in accordance with the terms & conditions mentioned in this tender document.
- 13.2 2% earnest money will be released to the bidder after 30 days of the successful completion of contract / supplies and best satisfaction by this office.

14) SEALING AND MARKING OF BIDS:

The bid shall be submitted in sealed envelope marked as under:

(TANVEER IQBAL)

Additional Commissioner (Hqrs)
Corporate Tax Office, Lahore
Ph: 99211717, Fax: 99211816

15) DEADLINE FOR SUBMISSION OF BIDS:

All bids must be delivered in the Office of the undersigned on or before the prescribed deadline i.e. before **11.00 AM on 22.04.2024**.

16) OPENING OF BIDS:

- 16.1 The Purchaser will open the bids in the presence of bidder / representatives who choose to attend at **02.00 PM on 22.04.2024** at the below mentioned address.
- 16.2 Address: Office of the Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore 1st Floor, Tax House, Syed Mauj Darya Road, Lahore.

17) WARRANTY

- 17.1 The Supplier shall warrant that all equipment supplied against the Purchase Order (s) shall have no defect arising from design, materials or workmanship or from any act or omission of the Supplier that may develop under normal use of the supplied equipment under the conditions prevailing at final destination.
- 17.2 The supplier shall warrant/responsible that all items of supply order(s) shall have original, quantity & quality wise and according to the required specification.
- 17.3 LOT-2, LOT-3 & LOT-5 related period of warranty and maintenance with labour and material cost shall be "One (1) year comprehensive".
- 17.4 The supplier shall be responsible for minimum 3 years' service & maintenance of the LOT-1 but the warranty of equipment/parts thereof provided by the manufacturer exceeding 3 years will also apply.
- 17.5 During warranty period the supplier will be responsible to repair / replace the faulty equipment on **installation** place free of cost within 24 hours after occurrence of fault. During warranty period due to any reason, if the Supplier failed to rectify the problem, Corporate Tax Office shall repair the equipment or replace the defective parts thereof and forfeit the Bank Guarantee / retained values.

18) All bids must include:

- 18.1 Company's profile, list of clients with their telephone numbers.
- 18.2 Copies of Income Tax and Sales Tax Registration Certificates.
- 18.3 A call deposit being @ 2% of the total bid value as Earnest Money in favour of Chief Commissioner Inland Revenue, Corporate Tax Office, Lahore.
- 18.4 Brochures and other technical material of the quoted items.
- 18.5 Companies / agencies will produce capability, relevant experience certificate from the principal that the Vendor is Sole Distributor / Authorized Dealer /Authorized Re-Seller etc.
- 18.6 Affidavit (on legal paper) that the Supplier / Company is neither blacklisted nor in litigation with any of its clients.



(TANVEER IQBAL)
Additional Commissioner (Hqrs)
Corporate Tax Office, Lahore
Ph: 99211717, Fax: 99211816

Signature & Stamp of the Bidder on every Page of the Bid

**GOVERNMENT OF PAKISTAN
FEDERAL BOARD OF REVENUE
CORPORATE TAX OFFICE, LAHORE
TAX HOUSE, SYED MAUJ DARYA ROAD, LAHORE**

PARTICULARS	DESCRIPTION	ATTACHMENTS (Page Nos. or Annexure Nos.)
Name of the Firm		
Address (Telephone, Fax & E-mail)		
Year of Establishment (Attached any documentary evidence or furnish a statement on Oath)		
Whether Pay Order as Earnest Money equal to 2% of the total value of bid is enclosed in proposal)		
Banker's related to the similar assignments		
Experience related to the similar assignments		
Annual Turnover Supported by Sales or Income Tax Return		
Enlistment Certificate (Copy of Certificate enlisted with Govt. / Semi Govt. or Organization if any)		
Assignments in Hand (Current)		
Clientele attached as separate Annexure (if necessary)		
Affidavit (that the firm has not been blacklisted by private, Govt. Semi Govt./Autonomous body)		
Managerial / Technical Capability (Manpower attach if necessary)		
Name of Contact Person Telephone, Fax & Mobile No.		

**GOVERNMENT OF PAKISTAN
FEDERAL BOARD OF REVENUE
CORPORATE TAX OFFICE, LAHORE
TAX HOUSE, SYED MAUJ DARYA ROAD, LAHORE**

SCHEDULE OF REQUIREMENT & FINANCIAL PROPOSAL

LOT-1: DRY GEL BATTERIES

EQUIPMENT / ITEMS	SPECIFICATION	UNIT	QTY	RATE	TOTAL
Dry Gel Batteries Ratings (12V - 40AH)	Application: UPS, Technology: Gel (Pure Gel Technology), Voltage [V]: 12V, Capacity: 40Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs) Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6~10years	Nos.	160		
Dry Gel Batteries Ratings (12V - 26AH)	Application: UPS, Technology: Gel (Pure Gel Technology), Voltage [V]: 12V, Capacity: 26Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs) Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6~10years	Nos.	338		
Dry Gel Batteries Ratings (12V - 20AH)	Application: UPS, Technology: Gel (Pure Gel Technology), Voltage [V]: 12V, Capacity: 20Ah @ 20hr-rate to 1.75V per cell @25°C (77°F), Discharge Rate: Self-discharge Rate of Less than 2% Per Month, Standby: 3 – 5 Years Expected Life in Standby Use Terminal Type: Nut & Bolt, Terminal: L terminal: B8 (M5 bolt) or Recessed type (M6 bolt), Container Material: ABS(UL94-HB) & Flammability resistance of (UL94-V0) can be available upon request. Electrolyte: Pure Gel electrolytes / Gel polymer electrolytes (GPEs) Sealed Type: Sealed, Container Material: ABS Battery, Long Life: Floating lifespan 6~10years	Nos.	96		
Battery Cable Extension Wire	Parallel cable for battery extension with copper thimble crimped round crimp terminals at both ends with nut bolts. According to the rating of batteries (12V - 40AH), (12V - 26AH), (12V - 20AH).	Nos.	600		

Note: Batteries installation, configuration and Commissioning. (Before installing all batteries, the UPS and battery bank must be serviced)

LOT-2: ELECTRIC LIGHT

S.No	EQUIPMENT / ITEMS	SPECIFICATION	UNIT	QTY	Rate	Total
•	SMD Panel Light	Lighting Technology: SMD, Ceiling Panel Light Size: 2x2, Voltage: AC ~ 165 – 265V, Color: White, Wattage: 72, Color Temperature: 6500K Cool White, Cut Size: 595x595mm / 600x600mm, Surge Protection: 2.5KV, Life Time: Minimum 30,000 Hours.	Nos.	480		
•	SMD Panel Light Slim Panel (Round)	Lighting Technology: SMD, Ceiling Panel Square Size: 6"-inch, Voltage: AC ~ 165 – 265V, Color: White, Wattage: 18, Color Temperature: 6500K Cool White, Cut Size: 595x595mm / 600x600mm, Surge Protection: 2.5KV, Life Time: Minimum 30,000 Hours. Material: Aluminum	Nos.	200		
•	LED Bulb	Cap-Base: E27, Wattage: 13, Nominal lifetime: 25,000 hour(s), Switching Cycle: 50,000, Lighting Technology: LED, Color Temperature: 6500K Cool White.	Nos.	100		
•	LED Bulb	Cap-Base: E27, Wattage: 13, Nominal lifetime: 25,000 hour(s), Switching Cycle: 50,000, Lighting Technology: LED, Color Temperature: 3000K Warm White.	Nos.	100		

LOT-3: ELECTRIC CIRCUIT BREAKER

S.No.	EQUIPMENT / ITEMS	SPECIFICATION	UNIT	QTY	Rate	Total
•	MCCB Electric Circuit Breaker 400Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 400A, Number of Pole: 4, Breaking Capacity: 50 kA at 415 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	1		
•	MCCB Electric Circuit Breaker 250Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 250A, Number of Pole: 3, Breaking Capacity: 50 kA at 265 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	20		
•	MCCB Electric Circuit Breaker 200Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 200A, Number of Pole: 3, Breaking Capacity: 50 kA at 215 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	20		
•	MCCB Electric Circuit Breaker 125Amp	Electric Circuit Breaker Type: Mold Case Circuit Breaker, Amperage Rating: 125A, Number of Pole: 3, Breaking Capacity: 50 kA at 135 VAC, Voltage Rating: 690 V, Operating Temperature: 25°C To +70°C, Rated Current: optional 30, 40, 60, 100 (must write), Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	20		
•	MCB Electric Circuit Breaker 32Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 32A, Number of Pole: 3, Breaking Capacity: 15 kA at 47 VAC, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	25		
•	MCB Electric Circuit Breaker 20Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 20A, Number of Pole: 2, Breaking Capacity: 4.5KA-20KA, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	50		
•	MCB Electric Circuit Breaker 16/20Amp	Electric Circuit Breaker Type: Miniature Circuit Breaker, Amperage Rating: 16/20A, Number of Pole: 1, Breaking Capacity: 07 kA at 27 VAC, Voltage Rating: 220-440V, Operating Temperature: 25°C To +70°C, Frequency: 50/60 Hz, Breaker Type: Fixed, Mounting Mode: Fixed	Nos.	400		

LOT-4: ELECTRIC POWER CABLE

S.No.	EQUIPMENT / ITEMS	SPECIFICATION	UNIT	QTY	Rate	Total
•	Electric Power Cable 40x76	Electric Power Cable Size:40x76, Core: 2-Core, Color: Red, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall	Coil.	10		
•	Electric Power Cable 7x36	Electric Power Cable Size:7x36, Core: 1-Core, Color: Red, Black, Green Earth Wire Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall	Coil.	15		
•	Electric Power Cable 7x29	Electric Power Cable Size:7x29, Core: 1-Core, Color: Red, Green Earth Wire, Yellow, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall	Coil.	20		
•	Electric Power Cable 3x29	Electric Power Cable Size: 3x29, Core: 1-Core, Color: Red, Green Earth Wire, Yellow, Black, Conductor: copper conductors, full Gauge 100% Copper, Rated Temperature: 90°C, Rated Voltage: 220/440V, insulated: PVC, Flame retardant PVC sheathed overall	Coil.	32		

•	Coaxial cable RG7	Coaxial cable Size: RG7, Inner Conductor: Copper Wire, Gauge 100% Copper, Dielectric: Gas Injected Foamed, Foil Shield Screen-1: Tape Aluminum / Polyester / Bonding Layer, Braid Shield (Screen-2): Copper Braid, Jacket: Outside insulation (PVC) Flame retardant PVC sheathed overall	Coil.	5		
•	Coaxial cable RG11	Coaxial cable Size: RG11, Inner Conductor: Copper Wire, Gauge 100% Copper, Dielectric: Gas Injected Foamed, Foil Shield Screen-1: Tape Aluminum / Polyester / Bonding Layer, Braid Shield (Screen-2): Copper Braid, Jacket: Outside insulation (PVC) Flame retardant PVC sheathed overall	Coil.	3		

LOT-5: FILTER ASSEMBLY

S.No.	EQUIPMENT / ITEMS	SPECIFICATION	UNIT	QTY	Rate	Total
•	Genset Complete Filter Assembly	Complete Filter Assembly:10929, 10930, 10931 Complete Filter Assembly of Perkins Generator 550 KVA	Nos.	1		
	Installation (Commissioning) of Genset Complete Filter Assembly.					

Dated: _____

Authorized Signature with Stamp

Name: _____

Land Line Number: _____

Mobile Number: _____