

TENDER BULLETIN

TENDER CLOSING/OPENING DATE 10/02/2025

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S.N o	LPR No	PART NO	NSN / Description	P/Equipmen t	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
1	DNF737 91	FE-01-C	6665015587743 / SENSING ELEMENT (1 Box contains 10 small boxes)	FIDO EXPLOSIVE DETECTOR PORTABLE.	4 / BOX		Fido sales@fir.com 405-372-9535 (USA)	TECHNICAL SPECIFICATION - OEM: NOMADICS INC. DBA ICX NOMADICS 1024 S INNOVATION WAY STILLWATER OK UNITED STATES 74074-1508 405-372-9535 405-372-9537 DUNS 879735579 MINH.BINGHAM@ICXT.COM HTTP://WWW.NOMADICS.COM/ GENERAL SPECIFICATION - OEM: NOMADICS INC. DBA ICX NOMADICS 1024 S INNOVATION WAY STILLWATER OK UNITED STATES 74074-1508 405-372-9535 405-372-9537 DUNS 879735579 MINH.BINGHAM@ICXT.COM HTTP://WWW.NOMADICS.COM/
2	DN0735 93	TACWIP: SE/W02 / CLH100- 80-13- 01(Z)	4320FP1420002 / IMPELLER		2 / EACH/ NUMBE R	CLH100- 80-13- 01(Z)		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
3	DNS690 27	03101- 104	5315715188660 / LINK PIN	WOODWAR D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI
4	DNS690 11	03101-27	312071518862	WOODWAR D MAIN ENGINE	1 / EACH/ N	TYPE 3161 PNO	WOODWARD PO Box 1519, Fort Collins CO	TECHNICAL SPECIFICATION -

			2 / BEARING .827 X .312	GOVERNOR 3161 USA	UMBER	8540652	80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TPI</u> GENERAL SPECIFICATION - TPI
5	DNS690 19	03101- 115	4820715188662 / LOADING SPRING	WOODWAR D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPI</u> GENERAL SPECIFICATION - TPI
6	DNS690 13	03101- 119	4810715188672 / PILOT VALVE NUT	WOODWAR D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPI</u> GENERAL SPECIFICATION - TPI

7	DNS690 24	03101-43	5305715188714 / SHUTDOWN NUT	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPI</u> <u>GENERAL SPECIFICATION - TPI</u>
8	DNS690 12	03101- 127	4810715188666 / NEEDLE VALVE	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www	<u>TECHNICAL SPECIFICATION -</u> <u>TPI</u> <u>GENERAL SPECIFICATION - TPI</u>
9	DNJ717 15	990003- 45292 /31135- 94900	5360765222416 / SPRING	SUZUKI DF300AP 300 HP OBM	6 / EACH/ NUMBE R	SUZUKI DF300AP 300 HP OBM	SUZUKI MOTOR CO LTD JAPAN	<u>TECHNICAL SPECIFICATION -</u> <u>NIL</u> <u>GENERAL SPECIFICATION - NIL</u>
10	DNF737 91	FE-01 C	6665015587743 / SENSING ELEMENT (1 Box contains 10 small boxes)	FIDO EXPLOSIVE DETECTOR PORTABLE.	4 / BOX		OEM: NOMADICS INC. DBA ICX NOMADICS 1024 S INNOVATION WAY STILLWATER OK UNITED STATES 74074-1508 405-372-9535 405-372-9537 DUNS 879735579 MINH.BINGHA M@ICXT.COM HTTP://WWW.N OMADICS.COM /	<u>TECHNICAL SPECIFICATION -</u> OEM: NOMADICS INC. DBA ICX NOMADICS 1024 S INNOVATION WAY STILLWATER OK UNITED STATES 74074-1508 405-372-9535 405-372-9537 DUNS 879735579 MINH.BINGHAM@ICXT.COM HTTP://WWW.NOMADICS.COM/ <u>GENERAL SPECIFICATION - OEM:</u> NOMADICS INC. DBA ICX NOMADICS 1024 S INNOVATION WAY STILLWATER OK UNITED STATES 74074-1508 405-372-9535 405-372-9537 DUNS 879735579 MINH.BINGHAM@ICXT.COM HTTP://WWW.NOMADICS.COM/

11	SNJ732 42	241217B	4810765220488 / VALVE BLOCK (COUNTER BALANCE VALVE)	480 HP YANMAR 6LY-ETP	5 / EACH/ NUMBE R	6LY3- ETP	ROLLS-ROYCE OY AB P.O BOX 579 FIN- 67701 KOKKOLA FINLAND TELEPHONE +358 6 832 4500 TELEFAX +358 6 832 4512 EMAIL info.kokkola@rol ls-royce.com	TECHNICAL SPECIFICATION - FITTED ONBOARD ANACONDA BOAT WITH HYDRAULIC SYSTEM. ITEM AVAILABLE ON PAGE 36 AT S NO 01. GENERAL SPECIFICATION - FITTED ONBOARD ANACONDA BOAT WITH HYDRAULIC SYSTEM. ITEM AVAILABLE ON PAGE 36 AT S.NO 01.
12	DNJ737 74	AE01102 010B	2930765075941 / MECHANICAL SEAL 0305 FOR COOLING WATER PUMP	COOLING WATER PUMP (6DSM 22)	1 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
13	DNJ737 10	AE01102 010B	2930765075941 / MECHANICAL SEAL 0305 FOR COOLING WATER PUMP	COOLING WATER PUMP (6DSM 22)	3 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
14	DNG719	200100	533077509615	S.H PUMP	20 /			TECHNICAL SPECIFICATION - NO
	96		5 / GLAND PACKING	FIRE MAIN PUMP	EACH/ NUMBE R			DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAIL ABLE
15	DNF559 62	10.371.1 51.00	6240755093366 / INDICATION LAMP 230VAC	MOD CM60- 4FT COOKING RANGE OEM:BARAT TA	50 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
16	DNF732 11	KFAE- 55C	6105705044236 / BLOWER EXHAUST 1.5KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	EXHAUST BLOWER STEERING COMPART	1 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE

17	DNF712 06	ctb-20	5995535302617 / Control Unit		2 / EACH/ NUMBE R	CTB-20	<p>TECHNICAL SPECIFICATION - MATERIAL / FINISH ALUMINIUM / BLACK MOUNTING FLUSH WITH 4 X 4MM SCREWS. OPTIONAL BACK BOX FOR BULKHEAD MOUNTING TERMINALS PLUGABLE SCREW TERMINALS FOR CABLE MAX 2.5MM² CABLE GLAND 2 X PG-16 DIMENSION (MM) 240W X 144H X 100D CUT OUT DIMENSION 224 X 132 WEIGHT APPROX. 1.2 KG MICROPHONE INPUT SOCKET FOR HANDHELD AND ELECTRET GOOSENECK MICROPHONE EXTERNAL CONNECTIONS CENTRAL UNIT, EXTERNAL MICROPHONES, EXTERNAL LOUDSPEAKER FRONT PANEL GRAPHIC FRONT FILM SWITCHES PUSH BUTTON TYPE WITH LED INDICATION LOUDSPEAKER 3 W / 16 OHM IP RATING IP-22 TEMPERATURE OPERATING -15 TO +55 °C OPERATOR PANEL CTB- 20 WITH 20 LINES SELECTION OPERATES WITH CU-20 OR CU-200 CENTRAL UNIT SINGLE CALL / GROUP CALL / ALL CALL FACILITY SOCKET FOR GOOSENECK OR HANDHELD MICROPHONE DIMMABLE PANEL</p>
----	--------------	--------	---------------------------------	--	----------------------------	--------	---

							BACKGROUND LIGHT EXTENSION BUTTONS WITH ON LIGHT BUZZER INDICATION OF INCOMING CALLS STEP VOLUME CONTROL CALL SIGNAL OUTPUT FOR EXTRA SIGNAL DEVICE ALL <u>LINE GENERAL SPECIFICATION -</u> MATERIAL / FINISH ALUMINIUM / BLACK MOUNTING FLUSH WITH 6 X 4MM SCREWS, OPTIONAL BACK BOX FOR BULKHEAD MOUNTING TERMINALS PLUGABLE SCREW TERMINALS FOR CABLE MAX 2.5MM ² CABLE GLAND 2 X PG-16 DIMENSION (MM) 240W X 144H X 100D CUT OUT DIMENSION 224 X 132 WEIGHT APPROX 1.2 KG MICROPHONE INPUT SOCKET FOR HANDHELD AND ELECTRET GOOSENECK MICROPHONE EXTERNAL CONNECTIONS CENTRAL UNIT, EXTERNAL MICROPHONES, EXTERNAL LOUDSPEAKER FRONT PANEL GRAPHIC FRONT FILM SWITCHES PUSH BUTTON TYPE WITH LED INDICATION LOUDSPEAKER 3 W / 16 OHM IP RATING IP-22 TEMPERATURE OPERATING -15 TO +55 °C OPERATOR PANEL CTB- 20 WITH 20 LINES SELECTION OPERATES WITH CU-20 OR CU-200
18	DN0735 81	7620.740 002.6 /	2815FP303024	17 / EACH/ N	TBD620 V12		<u>TECHNICAL SPECIFICATION -</u>
		IL23091 1	6 / LUBE OIL FILTER CATRIDGE	UMBER			null <u>GENERAL SPECIFICATION - null</u>
19	DNF739 02	GXT- 10000MT PLUSC2 30	7025795258792 / UPS 10 KVA with battery Pack for 17 mints Back Up Emerson with accessories	1 / EACH/ NUMBE R	LiebertIT A10KVA/ 9KW UPS 230V/400 V		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
20	DNS711 08	CAST- HV- 6510/13	4810735264190 / GLOBE VALVE 1- 5/8"(6512/13)	18 / EACH/ NUMBE R	CAST- HV- 6510/13		<u>TECHNICAL SPECIFICATION -</u> Dimensions (mm) height = 199 Length = 141 a = 138 q = 88 (diagram also attached in documents) <u>GENERAL</u> <u>SPECIFICATION -</u> Dimensions (mm) height = 199 Length = 141 a = 138 q = 88 (diagram also attached in documents)

21	DNN745 00	990807	5305795231855 / HOLLOW SCREW	MST BOAT D3-190IC	1 / EACH/ NUMBE R	D3-190IC	MARINE SPECIALISED TECHNOLOGY LIMITED, 44(0) 1517084112 UNIT 1, ATLANTIC WAY, BRUNSWICK BUSINESS PARK LIVERPOOL, L3 4BE, UNITED KINGDOM	TECHNICAL SPECIFICATION - Make: MST BOAT OF f22p Model MST620WB-TF D3 ENGINE Brand Volvo Penta Sweden brochures enclosed GENERAL SPECIFICATION - Make: MST BOAT OF f22p Model MST620WB-TF D3 ENGINE Brand Volvo Penta Sweden brochures enclosed
22	DNF491 06	ST895	6625785204896 / LCD CCTV CAMERA VIDEO TESTER	ST895 Camera Video Tester Set	1 / SET	ST895	Wanglu Tech Co Ltd 5/F.No.3building He GuangWu Heng Road, Shangsha, TianH e district, Guang Zhou, China Overseas Market Tel: +86-(0)20- 87586118 Fax: +86-(0)20- 38075108 E-mail: cctvtester@wan glu.com.cn	TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables GENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables
23	DNO647 54	5226130/ R522613 0	2910011956720 / INJECTOR	DETROIT SSDD MODEL	6 / ASSEM		OLM: SUPERIOR DIESEL INC.	TECHNICAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881
			ASSEMBLY FUEL	16V149TI,10 00KW,1605A MPS,3PHAS E	BLY		6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUP ERIORDIESEL NGINES.COM	BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553- 7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGI NES.COM HTTP://WWW.SUPERIORDIESELENG GINES.COM GENERAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGI NES.COM HTTP://WWW.SUPERIORDIESELENG GINES.COM
24	DNO755 46	A6ZKNR A	8415002687859 / GLOVES WELDERS	DC & FF	100 / PAIR		USA	TECHNICAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET GENERAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET

25	DNN755 24	990807	5305795231855 / HOLLOW SCREW	MST BOAT D3-190IC	2 / EACH/ NUMBE R	D3-190IC	MARINE SPECIALISED TECHNOLOGY LIMITED, 44(0) 1517084112 UNIT 1, ATLANTIC WAY, BRUNSWICK BUSINESS PARK LIVERPOOL, L3 4BE, UNITED KINGDOM	TECHNICAL SPECIFICATION - Make: MST BOAT OF I22p Model MST620WB-TF D3 ENGINE Brand: Volvo Penta Sweden brochures enclosed GENERAL SPECIFICATION - Make: MST BOAT OF I22p Model MST620WB-TF D3 ENGINE Brand: Volvo Penta Sweden brochures enclosed
26	DNF748 05	AF-5G34 S45 / RD- 5G34	5985715225071 / ROCKET DISH ANTENNA	MICRO WAVE COMM	1 / ASSEM BLY	RG-5G34	SHENZHEN DINSTAR 9TH FLOOR OF GOUXING BUILDING,CHA NGXING ROAD NANSHAN DISTRICT,SHE NZHEN PR. CHINA,5180 52 e-mail - sales@dinstar.c om Phone +86-755- 26456664	TECHNICAL SPECIFICATION - TO USE WITH MICRO WAVE TX/RX THE SIGNAL GENERAL SPECIFICATION - TO USE WITH MICRO WAVE TX/RX THE SIGNAL
27	DNF744 37	457-6114	6625715195285 / CA3/DATA LINK CABLE ASSEMBLY	CATERPILL AR 466-6258 USA	1 / EACH/ NUMBE R	466-6258	M/S CATERPILLAR	TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL
28	DNF758 20	LP 12- 100 AH /	6625785149878 / 12 V 100 AH	ZTE INTERNAT(I P	4 / EACH/ N UMBER	LEOCH FT12- 100	CH	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -
		LEOCH FT12-100 /0505235 00092	BATTERY LEOCH FT12-100	MOLS)				
29	DNF758 92	CMOT 391 K-SL / CMAS10 0-SL / 3215050 C-EN.	5905715141324 / SKF MACHINE CONDITION ADVISOR	SKF MACHINE CONDITION ADVISOR	1 / EACH/ NUMBE R	CMAS10 0-SL	US	TECHNICAL SPECIFICATION - OEM ADD:M/S RELIABILITY SYSTEMS,5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA,USA TEL#+1 8584963400,FAX#+1 8584963531 GENERAL SPECIFICATION - OEM ADD M/S RELIABILITY SYSTEMS 5271 VIEW BRIDGE COURT,SAN DIEGO CALIFORNIA,USA.TEL#+1 8584963400,FAX#+1 8584963531
30	DNZ706 54	WTZK 50 C(PRES SURE)	6620785149508 / PRESSURE SENSER / switch AC 380V 3A	MAIN ENGINE	2 / EACH/ NUMBE R	G6300 19B,18B	M/S MC GAUGE MANUFACTURI NG CO LTD CHINA.	TECHNICAL SPECIFICATION - AC 380V 3A DC 220V 2.5A PRESSURE 0.1-0.4 Mpa GENERAL SPECIFICATION - AC 380V 3A DC 220V 2.5A PRESSURE 0.1-0.4 Mpa

31	DNO755 46	ABZKNR A	8415002687859 / GLOVES WELDERS	DC & FF	100 / PAIR		FED COMMERCIAL ITEM DESCRIPTION PROMULGATE D BY GENERAL SERVICES ADMIN WASHINGTON DC	TECHNICAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET GENERAL SPECIFICATION - KNITTED LINING CUFF TYPE GUANTLET
32	DNF736 95	XT-46C	3540785223172 / AUTOMATIC SHOES COVER MACHINE	AUTOMATIC SHOES COVER MACHINE XT-46C CHINA	1 / EACH/ NUMBE R	XT-46C	8th Floor, 12th Building, Longjun Industrial zone Bujiuwo, Heping West Road, Dalang Street, Longhua, Shenzhen, China Tel: +86-755- 27830663	TECHNICAL SPECIFICATION - Capacity of shoes cover: 1000 pcs Design use ful life: 300000 times Pre Heating Time: 120s File Delivery Time: 3s File Shaping Time 3s GENERAL SPECIFICATION - Capacity of shoes cover: 1000 pcs Design use ful life: 300000 times Pre Heating Time: 120s File Delivery Time: 3s File Shaping Time 3
33	DNS710 91	2751200 I/MRN- 102-051/ CODE25 7, CODE: 288	4510FT1008599 / Muslim Shower	MRN Shower Wet Unit (with Wall Model Vacuum Toilet)	10 / EACH/ NUMBE R	MERCAN MRN Shower Wet Unit	DERI ORGANIZE SANAYI BOLGESI 7/ YOL F 7 PARSEL TUZLA	TECHNICAL SPECIFICATION - likely supplier: SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312- 2633855, 0321-3240447. GENERAL SPECIFICATION - likely supplier SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi Mob# 0346-2120960, 0312-2633855, 0321-3240447.
34	DNF593 59	S4600- 28P-SI /J9775A	7025145837789 / SWITCH UNIT 24 PORT WITH 4SFP & Accessories	Local Area Network (LAN) (Intranet)	2 / EACH/ NUMBE R	S4600- 28P-SI /CSS326- 24G- 2SRM	1 AV DU CANADA LES ULIS LES ULIS	TECHNICAL SPECIFICATION - DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP GENERAL SPECIFICATION - DCN S4600-28P- SI LAYER-2 24 PORT WITH 4SFP

35	DNF755 53	SUA 10001 APC	6130725140393 / APC UPS 1KVA 230VAC WITH 2X BATTERIES 12V 12AH	BERQ PROJECT	1 / EACH/ NUMBE R	APC BRAND	GE	<p>TECHNICAL SPECIFICATION - ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AH</p> <p>GENERAL SPECIFICATION - ONE PC average voltage consumption in 250 Watts Battery backup time of said UPS is: Backup Time = AH *12V*N*Efficiency of Battery / Load in watts Where: AH= Ampere hour Capacity of battery (12AH) N= Number of 12 batteries attached (2) Efficiency of Battery = 0.8 12AH*12v*2*0.8/250 = 0.9216 hours Approx. : 30 minutes 230VAC WITH@X BATTERIED 12V 12AH</p>
35	DNF706 06	AT- GS950/2 4	1430015862275 / 24 PORT SWITCH AT- GS950/24	NETWORK AT- GS950/24 USA	2 / EACH/ NUMBE R	AT- GS950/2 4	ALLIED TELESIS INC. 19800 NORTH CREEK PARKWAY SUITE 100 BOTHIEL WA 98011 USA TEL : +1 800 424 4284 FAX : +1 425 481 3895	<p>TECHNICAL SPECIFICATION - 24 port 10/100/1000TX Websmart switch with 4x100/1000 SFP bays (Eco version) Model : AT-GS950/24-30</p> <p>GENERAL SPECIFICATION - 24 port 10/100/1000TX Websmart switch with 4x100/1000 SFP bays (Eco version) Model : AT-GS950/24-30</p>
37	DNF553 39	MD3003 B1 / BS- HH-D7	6665705208217 / HAND HELD METAL DETECTOR	METAL DETECTOR DESTO PAK	2 / EACH/ NUMBE R	MD3003 B1/BS- HH-D7	DESTO (HQ)CHAKLALA cant, Rawalpindi 46200, Pakistan	<p>TECHNICAL SPECIFICATION - a. Operating Frequency 25/27/93 KHz b. Length c. Weight d. Tuning e. Battery f. Maximum Detection Depth at 70 KHZ Paper Pin: 2-3 cm Razor Blade/Knife: 9-15 cm Pistol: 15-18 cm g. Normal Operation duration: 12 hrs</p> <p>GENERAL SPECIFICATION - a. Operating Frequency 25/27/93 KHz b. Length c. Weight d. Tuning e. Battery f. Maximum Detection Depth at 70 KHZ Paper Pin: 2-3 cm Razor Blade/Knife: 9-15 cm Pistol: 15-18 cm g. Normal Operation duration: 12 hrs</p>

38	DNV700 43	AHU 36000 BTU-SS / 2613000 B7	4130505217843 / AIR HANDLING UNIT 36000 BTUS (AT36HVZ)	Air Handling Unit AT36HV PAKISTAN	2 / EACH/ NUMBE R	AHU 36000 BTU-SS	77-78, St 10, Sector I-9 Industrial Area, Islamabad Tel: 051-111- 888-786 021- 2826584 - 051- 2824090 Fax: 051- 4430508- 4430103	<p>TECHNICAL SPECIFICATION - A Materials Spec: Tube material: Copper Fins: Aluminum (Acrylic Coated) Body: Stainless Steel-316 Fan material: Aluminum b. Technical Spec: 1. Dimensions: As per Annex 2. Collong (Bth/hr/kcal/hr): 36000/9072 3. Voltage @ 50- 60hz/1ph: 230 4. Amperage (fla) cost: 1.6 5. Water flow (gpm/lpm): 9.0/34.1 6. air flow (cfm/m3/hr) nominal: 676/1149 7. height excluding blower: (in/mm): 19.50/495 8. Height to blower: (in/mm): 19.50/495 9. width (in/mm)(3): 26.63/676 10. Depth (in/mm)(3): 18.00/457 11. Supply air duct diameter (in/mm): 8/203 12. remote mount electric box (in/mm): 8.00/203 High x 6.13/156</p>
								<p>Wide x 2. 00/51 deep 13. return air inlet (sq in/sq cm): 360/2323 14. supply air outlet (sq in / sq cm): 196/1265 15 water connections: (a) Drain : 1/2" fpt with pvc hb (b). Chilled water: 1/2" fpt on 4-24k, 1" fpt on 36k with brass hb on all. 16. Net weight(lb/kg)(4): 60.0/27.2 17. Gross Weight (lb/kg)(4): 60.0/29.2</p> <p>GENERAL SPECIFICATION - A. Materials Spec: Tube material: Copper Fins: Aluminum (Acrylic Coated) Body: Stainless Steel-316 Fan material: Aluminum b. Technical Spec: 1. Dimensions: As per Annex 1 2. Collong (Bth/hr/kcal/hr): 36000/9072 3. Voltage @ 50- 60hz/1ph: 230 4. Amperage (fla) cost: 1.6 5. Water flow (gpm/lpm): 9.0/34.1 6. air flow (cfm/m3/hr) nominal: 676/1149 7. height excluding blower: (in/mm): 19.50/495 8. Height to blower: (in/mm): 19.50/495 9. width (in/mm)(3): 26.63/676 10. Depth (in/mm)(3): 18.00/457 11. Supply air duct diameter (in/mm): 8/203 12. remote mount electric box (in/mm): 8.00/203 High x 6.13/156 Wide x 2. 00/51 deep 13. return air inlet (sq in/sq cm): 360/2323 14. supply air outlet (sq in / sq cm): 196/1265 15 water connections: (a), Drain : 1/2" fpt with:</p>

39	DNF586 34	ONL6000 VA- STABIM ATIC / APC BRAND / P- 0154000 / APC SRT5KX LI	6130785166753 / UPS 6KVA-2H O/P 220V 6000VA	PSS (CCTV SYS)	2 / EACH/ NUMBE R	APC BRAND	M/s CETC Mansion, No. 5 Wulutong North Street, Xicheng Distric, Beijing, China	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>
40	DNF755 95	N-120 / 6- QA-120. N-150 / n- 150 12v 120.ah.	6130785173196 / 12V 120 A/H BATTERY EXIDE	D/G KABOTA 20KVA	2 / EACH/ NUMBE R	N-120 VOLTA	SAIL FENGFAN BATTERY CO LTD CHINA	<u>TECHNICAL SPECIFICATION - SAIL</u> <u>FENGFAN BATTERY CO LTD CHINA</u> H=200 mm W=180 mm L=490 mm <u>GENERAL SPECIFICATION -</u> <u>SAIL FENGFAN BATTERY CO LTD</u> <u>CHINA H=200 mm W=180 mm L=490</u> mm
41	DNS690 21	03101-76	4820715188735 / SPRING SEAT	WOODWAR D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TP</u> <u>GENERAL SPECIFICATION - TP</u>
42	DNF755 50	SWTG DS-6.3 /ZA3000 E	6350705220323 / SMART WALK THROUGH GATE	SWTG	1 / EACH/ NUMBE R	DS-6.3 /ZA3000 E	DEFENCE SCIENCE AND TECHNOLOGY ORGANIZATIO N CHAKLALA CANTT RAWALPINDI	<u>TECHNICAL SPECIFICATION -</u> DIMENSIONS H: 2210MM W: 810MM D: 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD <u>GENERAL SPECIFICATION -</u> DIMENSIONS H: 2210MM W: 810MM D: 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD

43	DNS689 96	03101- 102	2990715188632 / CONNECTING LINK	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPIGENERAL SPECIFICATION - TPI</u>
44	DNS690 15	03101- 100	4810715188675 / PILOT VALVE PLUNGER	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA	<u>TECHNICAL SPECIFICATION -</u> <u>TPIGENERAL SPECIFICATION - TPI</u>
			(LIMIT SHUT DOWN)				Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	
45	DNS690 28	03101- 106	5315715188677 / PIN	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	2 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525, USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPIGENERAL SPECIFICATION - TPI</u>

46	DNS690 29	03101-107	5315715188690 / ROLL PIN .250 x .750	WOODWARD D MAIN ENGINE GOVERNOR 3161 USA	1 / EACH/ NUMBE R	TYPE 3161 PNO 8540652	WOODWARD PO Box 1519, Fort Collins CO 80522-1519, USA 1000 East Drake Road, Fort Collins CO 80525 USA Phone +1 (970) 482-5811 ? Fax +1 (970) 498- 3058 Email and Website?www.w oodward.com	<u>TECHNICAL SPECIFICATION -</u> <u>TPIGENERAL SPECIFICATION - TPI</u>
47	DNS709 12	3818543- 5/388/26 0	6145735159585 / CABLE HARNESS	ELECTRICA L SYSTEM	1 / EACH/ NUMBE R	D5-D16	WARTSILA FINLAND OY, SHIP POWER	<u>TECHNICAL SPECIFICATION -</u> <u>WARTSILA FINLAND OY, SHIP</u> <u>POWER GENERAL SPECIFICATION</u> <u>- WARTSILA FINLAND OY, SHIP</u> <u>POWER</u>
48	DNN750 25	6033.143 3.02	5820FP9011040 / EE DISPLAY ADAPTION DISPLAY ADAPTION	EK2000 VLF- HF RECEIVER	1 / EACH/ NUMBE R	N/A	Muhldorfstraße 15,81671, Munchen, Germany	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>
49	DNF187 36	HUAWEI CLOUD LINK BAR 310 / BOX- 300 /TE40- 720P30- P-07/ 2358531/ CLOUD LINK BAR 300	5895785197516 / HUWAEI VTC TE- 40/ TE-50 / CLOUD BOX-300	VTC Equipment	1 / EACH/ NUMBE R	BOX-300 /TE40- 720P30- P	HUAWEI Saudi Pak Towers, Blue Area , Islamabad VCale@huawei. com huawei technologies co ltd.	<u>TECHNICAL SPECIFICATION -</u> <u>HUAWEI VTC Equipment TE-40</u> <u>including HD Codec, Remote Control,</u> <u>Power Supply and optional HD</u> <u>Camera & MicrophoneGENERAL</u> <u>SPECIFICATION - HUAWEI VTC</u> <u>Equipment TE-40 including HD</u> <u>Codec, Remote Control, Power</u> <u>Supply and optional HD Camera &</u> <u>microphone</u>
50	DNF743 43	KR703/7 10VV / DR670 (B&D)	0565794119172 / DRILLING MACHINE ELECTRIC 1/2IN 220V/250V 6 AMP (BLACK&DECKE R)	SELF END USE	1 / EACH/ NUMBE R	710W / DR670 (B&D)		<u>TECHNICAL SPECIFICATION -</u> <u>650WATT 13MM KEYEDCHUCK</u> <u>MODEL NO.KR653KGENERAL</u> <u>SPECIFICATION - 650WATT 13MM</u> <u>KEYEDCHUCK MODEL NO.KR653K</u>
51	DNF730 01	1001- 8049-01 (LOCAL Y)	0561UK5061887 / RADIATOR WIRE 3 CORE ASSEMBLY 2.1MM IRON GALVONIZED (FR)	HLP/LP ANTENNA (NTS LANDHI)	762 / METER			<u>TECHNICAL SPECIFICATION -</u> <u>2.1mm Iron GalvanizedGENERAL</u> <u>SPECIFICATION - 2.1mm Iron</u> <u>Galvanized</u>

52	SNG686 61	B85	3030005290472 / BELT-V B85	WASHER EXTRACTO R L DRY CMRL 60LB CAP 360	20 / EACH/ NUMBE R			<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
53	DNG754 04	2501049 5	2940011977106 / FILTER,ELEMEN T,FLUID.	GM DETROIT D/E FOR GRP BOATS	24 / EACH/ NUMBE R			<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
54	DNG755 06	2501049 5	2940011977106 / FILTER,ELEMEN T,FLUID.	GM DETROIT D/E FOR GRP BOATS	2 / EACH/ NUMBE R			<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
55	DNG758 29	2350564 8	2815705088882 / ELEMENT AIR CLEANER	DETROIT DG	2 / EACH/ NUMBE R			<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
56	DNJ458 20	6331321 0A/63313 210C	2815765022885 / MAIN BEARING B (1300-6)		10 / EACH/ NUMBE R			<u>TECHNICAL SPECIFICATION - 125</u> mm <u>GENERAL SPECIFICATION - 125</u> mm
57	DNZ635 21	112603	4130785026770 / SPRING SUCTION VALVE C/HC 75 (2) AA009	AIR CONDITION PLANT NASR	36 / EACH/ NUMBE R	112603		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
58	DNF715 9	220V- 45W-	343478100185		1 /			<u>TECHNICAL SPECIFICATION - NO</u>
	5	162MM	8 / SOLDERING IRON 220V45W 162 MM 5123/MB21		EACH/ NUMBE R			DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
59	DNF748 02	1105	5825705118323 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V(12X4) 20A WITH ACCE		1 / EACH/ NUMBE R	GZL30A- 6/48V		<u>TECHNICAL SPECIFICATION -</u> Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC. OEM: Nanchang Shuguang Electric Equipment Factory <u>GENERAL</u> <u>SPECIFICATION -</u> Picture of equipment is enclosed. Input 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Electric Equipment Factory

60	DNF540 93	1106	5825705118323 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V(12X4) 20A WITH ACCE		1 / EACH/ NUMBE R	GZL30A- 6/48V		TECHNICAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC OEM: Nanchang Shuguang Eledricd Equipment Factory GENERAL SPECIFICATION - Picture of equipment is enclosed. input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC OEM: Nanchang Shuguang Eledricd Equipment Factory
61	DNF694 48	NEC SL2100 BE11649 4 /PABX KX- 1DA100 D	5830705056173 / TELEPHONE EXCHANGE WITH 96 LINE,12 LINE EXT	TELEPHONE EXCHANGE PANASONIC	1 / SET	NEC SL2100		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
62	DNF716 15	158- 51010	5961995580307 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
63	DNF738 21	158- 51010	5961995580307 / DIODE	MAIN RECTIFIER	3 / EACH/ N UMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL
			25AMPS 600VOLT.	ASSY	UMBER			SPECIFICATION - NO DATA AVAILABLE
64	DNF716 16	158 51020	5961995580314 / REVERSE DIODE	D/GENERAT OR (PNS RAJSHAH)	3 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
65	DNF738 15	158- 51020	5961995580314 / REVERSE DIODE	D/GENERAT OR (PNS RAJSHAH)	3 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
66	DNF755 52	2000VA STABIM ATIC/AP C	6130715117506 / UPS 2KVA	SELF END USE	2 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - "back up time of subject UPS" is required for 15 TO 20 minuit back up time GENERAL SPECIFICATION - "back up time of subject UPS" is required for 15 TO 20 minuit back up time
67	DNF694 19	AS PER DES- PTCL CABLE	6145705056673 / CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM	INTERCOME	60 / METER	PTCL CABLE		TECHNICAL SPECIFICATION - CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM country of origin pakistan (PTCL CABLE) GENERAL SPECIFICATION - CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM country of origin pakistan (PTCL CABLE)

68	DNF705 94	AS PER DES- PTCL CABLE	6145705056673 / CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM	INTERCOME	140 / METER	PTCL CABLE		TECHNICAL SPECIFICATION - CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM country of origin pakistan (PTCL CABLE) GENERAL SPECIFICATION - CABLE 50 CORE INTERCOM O/D 9MM CORE-DIA 1MM STRAIN DIA .5MM country of origin pakistan (PTCL CABLE)
69	DNF696 19	040349- 00	6230999427885 / TORCH COMPLETE WITH BULB	FIRE & REPAIR PARTY LOCKERS.	4 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
70	DNF708 39	040349- 00	6230999427885 / TORCH COMPLETE WITH BULB	FIRE & REPAIR PARTY LOCKERS.	2 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
71	DNF716 17	VPX715/ TZ-201	5965765013591 / Pro Sound	PUB ADDRE SS	1 / EACH/ N UMBER			TECHNICAL SPECIFICATION - 15- inch two-way full-range More powe
			speaker Electro- voice ELX115 15" Two Way passive loud Speaker (peak power1600 watt)	SYSTEM,TO A JAPAN	UMBER			fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz - 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak GENERAL SPECIFICATION - 15-inch two-way full-range More powe fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz - 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak.
72	DNF719 15	VPX715/ TZ-201	5965765013591 / Pro Sound speaker Electro- voice ELX115 15" Two Way passive loud Speaker (peak power1600 watt)	PUB.ADDRE SS SYSTEM,TO A JAPAN	4 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - 15- inch two-way full-range More powe fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz - 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak GENERAL SPECIFICATION - 15-inch two-way full-range More powe fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz - 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak.

73	DNF707 94	VPX715/ TZ-201	5965765013591 / Pro Sound speaker Electro- voice ELX115 15" Two Way passive loud Speaker (peak power1600 watt)	PUB.ADDRE SS SYSTEM,TO A JAPAN	4 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - 15- inch two-way full-range More powe fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz - 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak GENERAL SPECIFICATION - 15-inch two-way full-range More powe fuller sound for larger rooms EVS-15K woofer1.5-inch DH1K titanium HF compression driver 50Hz
								- 20 KHz frequency range 90x 50 coverage pattern waveguide Power handling 400W continues, 1600W peak.
74	DNF749 17	DML 1X8"	6240705088396 / BED LIGHT ASSEMBLY WITH LAMP 220V 40 WATTS	MESS BED LIGHT,ACCA MODATION OF FEMALE OFFICERS.	33 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - LOCAL ADDRESS:DIGI TECH SHOP NO2 NEW MEMON CHAMBERS,ALTAF HUSSAIN ROAD,DENSO HALL KARACHI- 7400.TEL:021-2639514 GENERAL SPECIFICATION - LOCAL ADDRESS:DIGI TECH,SHOP NO2 NEW MEMON CHAMBERS,ALTAF HUSSAIN ROAD,DENSO HALL KARACHI-7400.TEL:021-2639514.
75	DNG755 47	8112 or A A-1685	8415002688330 / GLOVES,MEN'S		6 / PAIR			TECHNICAL SPECIFICATION - cotton gloves w.r.t eligibility criteria: a. Anti-slip and breathable - Better grip comprising of dotted or plain cotton at palm side. b. Heat resistance - Quality of material should withstand temperature around 100-150 degree without any affect on texture quality. c. Excellent dexterity. d. Wear resistant GENERAL SPECIFICATION - cotton gloves w.r.t eligibility criteri a. Anti-slip and breathable - Better grip comprising of dotted or plain cotton at palm side. b. Heat resistance - Quality of material should withstand temperature around 100-150 degree without any affect on texture quality. c. Excellent dexterity. d. Wear resistant.
76	DNF728 38	CAT6 E/CAT 5E	7010705118996 / STP CAT 5E/CAT6E NETWORK CABLE (4 PAIR) AMP/AVAYA(100 0 FEET)	FAWMIS NETWORKI NG CABLE	2 / ROLL			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
77	DNF755 42	8136/1E Q	6145795023724 / CABLE TIE NYLON BLACK	TX/RX VRM	100 / PACKE T			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA

78	DNF759 14	913671F Q	6145795023724 / CABLE TIE NYLON BLACK	TX/RX VRM	500 / PACKE T		<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
79	DNF758 11	913671E Q	6145795023724 / CABLE TIE NYLON BLACK	TX/RX VRM	120 / PACKE T		<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
80	DNF742 78	IEC 1010 1	6625795100770 / DIGITAL CLAMP METER TONG TESTER 1000AMP=600V WITH ACCESSORIE	TEST EQUIPMENT 337 (USA)	2 / SET	model no 337	<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE
81	DNF742 17	CX-405 SONY	6710765085708 / VIDEO CAMERA RECORDER 8 HANDY CAM VIDEO 8		1 / EACH/ NUMBE R	CCDTR4 10E/TR4 20E/TR4 40E	<u>TECHNICAL SPECIFICATION - a 4K</u> video capturing feature. b. Alongwith motion stabilizer equipment. c. Alongwith standard size stand for placing the video camera. d. At least 1 TB memory space. e. Alongwith long range lenses. f. Alongwith additional batteries and chargers. g. Night video capturing feature. h. Go Pro Mode feature (optional). <u>GENERAL</u> <u>SPECIFICATION - a. 4K video</u> capturing feature. b. Alongwith motion stabilizer equipment. c. Alongwith standard size stand for placing the video camera. d. At least 1 TB memory space. e. Alongwith long range lenses. f. Alongwith additional batteries and chargers. g. Night video capturing feature. h. Go Pro Mode feature (optional).
82	DNF755 40	KFAE- 55C	6105705044236 / BLOWER EXHAUST 1.5KW 380-420V 5AMP RPM 2950 50HZ 3phase	EXHAUST BLOWER STEERING COMPART	2 / EACH/ NUMBE R		<u>TECHNICAL SPECIFICATION -</u> 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE <u>GENERAL</u> <u>SPECIFICATION - 1.5KW 380-420V</u> 5AMP RPM 2950 50HZ 3 PHASE
83	DNF755 90	ep- 1000t/b/a zer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	2 / EACH/ NUMBE R	BLAZER VISTA 1000/Aur ora	<u>TECHNICAL SPECIFICATION -</u> backup time: 10 minutes Product Name: AURORA Input: 220V <u>ACGENERAL SPECIFICATION -</u> backup time: 10 minutes Product Name: AURORA Input: 220V AC

84	DNF752 18	SMT3000 IC/SURT D3000X1 I/3000VA APC	6130715063823 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	2 / EACH/ NUMBE R	MODEL ESP-808 (E)/SYST EK PVT.		TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL
85	DNF755 55	16X50 ACULON A211/DP SI 8- 16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	4 / EACH/ NUMBE R	16X50 ACULON A211/DP SI AND MAKE OLYMPU S		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
86	DNS738 65	73637	5331171027165 / O RING (SEE COMD F8)	ALPHA LEVEL	1 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
87	DNF619 94	MD6.200 100.B	6135775118754 / MARINE	MARINE STARTER	12 / EACH/ N	MUTLU MD6.		TECHNICAL SPECIFICATION - S&A, DEFENCE TRADERS TOOBA
		(12 D3- M)	BATTERIES 12 V 200AH		UMBER	200.100. B		APARTMENT ,KARACHI CEL: 0300- 2811770 OEM,MUTLU TURKEY GENERAL SPECIFICATION - S&A, DEFENCE TRADERS TOOBA APARTMENT ,KARACHI CEL: 0300-2811770 OEM,MUTLU TURKEY.
88	DNN758 85	DC08.30 0.0761	1730FP3020058 / WIND SOCK		1 / EACH/ NUMBE R	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
89	DNN711 94	DC08.30 0.0761	1730FP3020058 / WIND SOCK		2 / EACH/ NUMBE R	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

90	DNF732 03	MINI- GBIC-LX- SM1310	5340785289364 / OPTICAL TRANCEIVER MODULE (SFP 1310nm 1000Base-LxSM 1GbB, LC single mode 10Km)	8 / NUMBE RS	MINI- GBIC-LX- SM1310	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
91	DNF750 01	EVR- 415V / MK-2015- E-7013	5920505267280 / ELECTRONICS VOLTAGE RELAY SCHNEIDER	2 / EACH/ NUMBE R	EVR- 415V	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
92	DNF750 19	mk-2015- e-7042	5999505264127 / thermostat - sensor built in scr	2 / EACH/ NUMBE R	na	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
93	DNF749 92	SKT 1200/16 / mk-2015- e-7029	5999505266910 / silicon control rectifier scr- 1600v	2 / EACH/ NUMBE R	skt 1200/16	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
94	DN0700 39	aczb- 0172- saw/CLD- 6-0107	4120FP1060165 / ANTI CORROSION ZINC ROD	6 / EACH/ NUMBE R	Type CLD- 4SCU Type CLD- 6SCU Type CLD- 8SCU Type CLD- 12SCU Type CLD- 17PSCU Type CLD- 17PSCU Type CLD-22P	TECHNICAL SPECIFICATION - ANTI CORROSION ZINC RODGENERAL SPECIFICATION - ANTI CORROSION ZINC ROD
95	DNO733 21	450-8213	2910715234014 / injector	1 / EACH/ NUMBE R	N/A	TECHNICAL SPECIFICATION - InjectorGENERAL SPECIFICATION - Injector
96	DNF749 89	Mk-2015- e-7044	5998505263131 / dc controller pcb electronic card	2 / EACH/ NUMBE R	mkes-dc- 001	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
97	DNF750 12	mk-2015- e-7048	5998505266902 / dc power supply i/p230vac	2 / EACH/ NUMBE R	MK-2015- E-7048	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
98	DNF750 11	CBB 55 / mk-2015- e-7041	5999505266906 / capacitor 400v 50UF C-1	2 / EACH/ NUMBE R	cbb65	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null

99	DNF749 96	LDP3-AV / MK 2015-E- 7017	5920505267278 / DC DIGITAL VOLT METER (RANGE 0 TO 500 VDC	2 / EACH/ NUMBE R	LDP3-AV	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
100	DNF750 15	mk-2015- e-7047	5999505264128 / blower fan 24vdc bkv-301	2 / EACH/ NUMBE R	BKV-301	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
101	DNN735 22	DH-IPC- HFW344 1E-SA	6780785327163 / CAMERA (DAHUA 4MP IR FIXED FOCAL BULLET WIZESENSE NETWORK CAMERA)	6 / EACH/ NUMBE R	HFW344 1E-SA	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
102	DNZ750 38	KTP 400	5999785237696 / SIEMENS	1 / EACH/ N	(KTP 400 COMFO R	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION -
			SIMATIC HMI (KTP 400 Comfort)	UMBER T		null
103	DNF758 24	HTS-jck- sebs-9524	5330705246098 / jack seals	6 / EACH/ NUMBE R	JCK- SEI S- 9524	TECHNICAL SPECIFICATION - SNIDS SURFACE MOUNT ROAD BLOCKER Raised Obstacle K-3 Crash Rated Height: 26-30 Inches (approx) 3000PSI (approx) Reinforced Civil WorkGENERAL SPECIFICATION - SNIDS SURFACE MOUNT ROAD BLOCKER Raised Obstacle K-3 Crash Rated Height: 26- 30 Inches (approx) 3000PSI (approx) Reinforced Civil Work
104	DNF749 87	MK 2015- E 7005	5998505266915 / push button with light (n/o)	2 / EACH/ NUMBE R	fbp-ea	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
105	DNF749 91	MC310A MZ202 / mk-2015- e 7023	5920505266923 / breaker mcb with alarm	2 / EACH/ NUMBE R	mc310a mz202	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
106	DNF750 08	3mk- 2015-e- 7035	5999505266905 / relay 2n/o, 2n/c2	2 / EACH/ NUMBE R	pak- 8js22	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
107	DNF750 13	mk-2015- e-7043	6625505263980 / thermostat TH 1.2	2 / EACH/ NUMBE R	dm01140	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
108	DNF750 14	mk-2015- e-7045	5998505264129 / rc network, Electronic card	2 / EACH/ NUMBE R	rc-001	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null

109	DNF750 02	MK-2015- E-7012	5920505267279 / CURRENT TRANSFORMER CT 1200 camscoo	2 / EACH/ NUMBE R	NA	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
110	DNF739 73	45MG-EI E EN U820071	5220735280647 / ULTRASONIC THICKNESS GAUGE	1 / EACH/ NUMBE R	45MG	TECHNICAL SPECIFICATION - NAGENERAL SPECIFICATION - NA
111	DNF749 98	MK-2015- E-7010	5998505266921 / CONTACTOR KM1 WITH AUX32A	2 / EACH/ NUMBE R	NA	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
112	DNF749 95	Mk-2015- e-7007	5998505266916 / On/off switch (Rotary switch)	2 / EACH/ NUMBE R	ca-026	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
113	DNO717 91	905948-2	5915715280586 / CABLE ASSEMBLY STAVE	36 / EACH/ NUMBE R	N/A	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
114	DNF742 19	GXT- 1000MT PLUSC2 30	7025795258792 / UPS 10 KVA with battery Pack for 17 mints Back Up Emerson with accessories	1 / EACH/ NUMBE R	LiebertIT A10KVA/ 9KW UPS 230V/400 V	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
115	DNF750 00	MK-2015 P-7011	5920505266926 / POWER CONTACTOR KM2 4 POLE 1000A	2 / EACH/ NUMBE R	11B630- 1000-400	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
116	DNF749 85	MK-2015- E-7008	5998505266919 / RESET PUSH BUTTON (N/C)	2 / EACH/ NUMBE R	LMB-ES5	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
117	DNF750 03	MK-2015- E-7015	6625505266922 / AC DIGITAL VOLTMETER range 0-500vac	2 / EACH/ NUMBE R	U ALPHA +V	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
118	DNF749 86	MK-2015- e-7001	5999505266913 / hrc fuse with holder cartrige 6amp	2 / EACH/ NUMBE R	eli-ch-10	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
119	DNF748 12	05-00 3395-00	5810715300651 / PC AVATAR - PC Based with Windows OS 7, Intel Core i7	1 / EACH/ NUMBE R	XIS- 100XD	TECHNICAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212 MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM GENERAL SPECIFICATION - MACHINE LENGTH: 1524 MM, WIDTH: 770 MM, HEIGHT: 1212

							MM, TUNNEL WIDTH: 506 MM, HEIGHT: 306 MM, MAX BAG WEIGHT: 165 KG, RESOLUTION: 38 AWG, PENETRATION IN STEEL: 244 MM
120	DNF749 94	MC316A MZ202 / mk-2015- e-7024	5920505266929 / breaker mcb with alarm 16AMP 3POL		2 / EACH/ NUMBE R	mc316a mz202	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
121	DNF758 96	WP7-12- LONG	5935705249028 / Dry Battery 12V 7AH		64 / EACH/ NUMBE R	China	<u>TECHNICAL SPECIFICATION -</u> M/FREE BATTERY 12V 7AH FOR UPS OEM, kung long batteries industrial co., ltd. <u>GENERAL</u> <u>SPECIFICATION -</u> M/FREE BATTERY 12V 7AH FOR UPS OEM. kung long batteries industrial co., ltd.
122	DNF750 23	mk-2015- e-7003	5920705264124 / hrc fuse with holder cartirage 6a, 3 pole		2 / EACH/ NUMBE R	pmf	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
123	DNF750 09	mk-2015- e-7037	5999509415536 / Wire wound resistor 400w, 26000 RP-3		2 / EACH/ NUMBE R	na	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
124	DNF746 53	DGS- 1510- 28X,DEM- 310GT,	5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS- 1510-28X & DEM- 310GT)		1 / EACH/ NUMBE R	dgs-1510- 28x,DEM- 310GT,	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
125	DNF749 90	mk-2015- e-7028	5925505263130 / mccb breaker 1250 amps, 4- pole		2 / EACH/ NUMBE R	t7h1250	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
126	DNF749 88	mk-2015- e-7004	5999505266912 / semi conductor fuse 630a		2 / EACH/ NUMBE R	iec60269- 4	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
127	DNF750 06	mk-2015- e-7038	5905505264131 / Variable resistor with knobw wire wound 10kO VR- 1.2		2 / EACH/ NUMBE R	na	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null
128	DNF750 07	mk-2015- e-7030	5999505264125 / diode 1200v		2 / EACH/ NUMBE R	d2209n2 0	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null

129	DNF749 99	Mk-2015- e-7009	5998505266920 / emergency stop (n/c)		2 / EACH/ NUMBE R	mpb-ec2		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
130	DNF750 22	mk-2015 e-7034	5999505266904 / relay octal base 8pin		2 / EACH/ NUMBE R	60.12		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
131	DNF750 24	MK-2015- e-7002	5920705264123 / hrc fuse with holder cartirage 2a, 1 pole		2 / EACH/ NUMBE R	ch-10		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
132	DNO710 17	AZCUE 4810. 1-2	5330735291514 / O - Ring		6 / EACH/ NUMBE R	Azcue BR41 20 Hydropho re Set		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
133	DNF749 93	MC210A /mk- 2015-e- 7025	5920505266927 / breaker mcb with alarm 10amp 2pol		2 / EACH/ NUMBE R	mc210a		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
134	DNF750 04	MK-2015- E 7014	5945505266925 / ELECTRONICS OVER CURRENT RELAY SCHNEIDER		2 / EACH/ NUMBE R	EOCR- SS-N		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
135	DNF750 05	mk-2015- E-7040	5999505266903 / exhaust fan 230vac		2 / EACH/ NUMBE R	ors- 4350ysa		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
136	DNJ746 48	701- 48320-70	5820765170579 / CABLE REMOTE CONTROL 20 FEET	OBM 90 HP YAMAHA	2 / EACH/ NUMBE R		JAPAN	<u>TECHNICAL SPECIFICATION -</u> STANDARD SPECIFICATION <u>GENERAL</u> <u>SPECIFICATION - STANDARD</u> SPECIFICATION
137	DNO500 57	8N-8455	2930270561085 / IMPELLER- PUMP		1 / EACH/ NUMBE R	3516E		<u>TECHNICAL SPECIFICATION -</u> IMPELLER-PUMP <u>GENERAL</u> <u>SPECIFICATION - IMPELLER-PUMP?</u>
138	DNC759 95	ELEC- 0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	500 / EACH/ NUMBE R	H/CRAF T8100TD	GRIFFON HOVER WORK UK	<u>TECHNICAL SPECIFICATION -</u> LENGTH: 24 INCHES COLOUR: BLACK <u>GENERAL SPECIFICATION -</u> LENGTH: 24 INCHES COLOUR: BLACK
139	DNJ746 81	701 48320-70	5825765216166 / CABLE END REMOTE CONTROL L=20F	150 AET OBM ENGINE	2 / EACH/ NUMBE R	150AET 07 (6G 47) 1024899	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438- 8501 JAPAN PHONE 0081- 538-37-1688 FAX 0081-538- 37-1954	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>

140	DNJ750 28	64E- 43897-00	5330765189341 / O-RING	YAMAHA SMALL BOAT ENGINE F100B JAPAN	12 / EACH/ NUMBE R	F100B	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@sea- quest.biz	<u>TECHNICAL SPECIFICATION -</u> <u>IPC</u> <u>GENERAL SPECIFICATION - IPC</u>
141	DNJ756 00	17400- 98J01- 000 & 17400- 98J05- 000	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	2 / EACH/ NUMBE R	DF300AP	SUZUKI MOTOR CO LTD JAPAN	<u>TECHNICAL SPECIFICATION -</u> WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416- 93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473 98J00 PANEL, WATER PUMP 09420- 05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER <u>GENERAL</u> <u>SPECIFICATION - WATER PUMP</u> REPAIR KIT ACCESSORIES 17461- 93J00 IMPELLER, WATER PUMP 17416-
								93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473 98J00 PANEL, WATER PUMP 09420- 05009 KEY 17471-98J01 PANEL PUMP CASE UNDER
142	DNJ750 30	8C11- 11194-00	5330765203499 / GASKET, HEAD COVER 2	YAMAHA OBM	13 / EACH/ NUMBE R	NO DATA AVAILAB LE	YAMAHA MOTOR CO. LTD JAPAN	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>

143	DNF760 24	N1537	6110705155260 / ENERGY SAVER 220V-240V ,11W.(screw type)	SELF, FOR DISTRIBUTI ON SYS.	100 / EACH/ NUMBE R		SOURCE OF AVAILABILITY: P HILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE: RS140 PKR. REQ: 1000. FOR GENERAL LIGHTING. SPECS 220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K- 2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi ' GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI PRICE: RS140 PKR. REQ: 1000. FOR GENERAL LIGHTING. SPECS 220- 240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K- 2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi '
144	DNJ746 47	6E5- 24410-04 / 6E5- 24410-03	2915765217955 / FUEL PUMP ASSY	200 AET 18(60JK) OBM ENGINE	2 / EACH/ NUMBE R	L200AET 18(60JK)	2500 SHINGAI LWATA SHIZUOKA 438- 8501 JAPAN PHONE 0081- 538-37-1660 FAX 0081-538- 37-1954	TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A
145	DNJ750 29	6CB- 11193-00	5330765203495 / GASKET, HEAD COVER 1	YAMAHA OBM	3 / EACH/ NUMBE R	NO DATA AVAILAB LE	YAMAHA MOTOR CO. LTD JAPAN	TECHNICAL SPECIFICATION - COUNTRY OF ORIGIN JAPAN GENERAL SPECIFICATION - COUNTRY OF ORIGIN JAPAN
146	DNF642 43	BSENG0 317-8 / CW1-18	0561795198751 / WIRE, WINDING	FOR WINDING.	60 / KILOG RAMM E			TECHNICAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue GENERAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2
147	DNF647 44	BSENG0 317-8 / CW1-18	0561795198751 / WIRE, WINDING COPPER ELECT COND DIA : 1.180MM O/ DIA : 1.308MM	FOR WINDING.	66.14 / KILOG RAMM E			TECHNICAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue GENERAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2
148	DNG755 03	5228725	2910008486764 / FUEL INJECTOR		16 / EACH/ NUMBE R			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

149	DNF760 37	A-1724	5830765120710 / 240WATT POWER AMPLIFIER INTER MPA- 600		1 / EACH/ NUMBE R		<p>TECHNICAL SPECIFICATION - 6 Input 95 x 3 pin XLR, 1 x stereo phono0. Telephone input (screw terminates). priority-telephone, mic 1, mic 2. 5 Band graphic equalizer. Line in / Line out. 5 Zone speaker selection. Chime 7 Siren 19" rack Mount Bracket Option: BKT-PA2000A/ PA6000A Model; PA2000A PA4000A PA6000A output power 240W 2 make : toa corporation model: a 1724 description: 240 w power amplifier inter mpa. 600</p> <p>GENERAL SPECIFICATION - 6 Input 95 x 3 pin XLR, 1 x stereo phono0. Telephone input (screw terminates). priority-telephone, mic 1, mic 2. 5 Band graphic equalizer. Line in / Line out. 5 Zone speaker selection. Chime 7 Siren 19" rack Mount Bracket Option: BKT-PA2000A/ PA6000A Model; PA2000A PA4000A PA6000A output power 240W 2 make : toa corporation model: a 1724 description: 240 w power amplifier inter mpa. 600.</p>
150	DNF617 91	A-1724	5830765120710 / 240WATT		1 / EACH/ N		<p>TECHNICAL SPECIFICATION - 6 Input 95 x 3 pin XLR, 1 x stereo</p>
			POWER AMPLIFIER INTER MPA- 600		UMBER		<p>phono0. Telephone input (screw terminates) priority-telephone, mic 1, mic 2. 5 Band graphic equalizer. Line in / Line out. 5 Zone speaker selection. Chime 7 Siren 19" rack Mount Bracket Option: BKT-PA2000A/ PA6000A Model; PA2000A PA4000A PA6000A output power 240W 2 make : toa corporation model: a 1724 description: 240 w power amplifier inter mpa. 600</p> <p>GENERAL SPECIFICATION - 6 Input 95 x 3 pin XLR, 1 x stereo phono0. Telephone input (screw terminates). priority-telephone, mic 1, mic 2. 5 Band graphic equalizer. Line in / Line out. 5 Zone speaker selection. Chime 7 Siren 19" rack Mount Bracket Option: BKT-PA2000A/ PA6000A Model; PA2000A PA4000A PA6000A output power 240W 2 make : toa corporation model: a 1724 description: 240 w power amplifier inter mpa. 600.</p>
151	DNF760 26	913671E Q	6145795023724 / CABLE TIE NYLON BLACK	TX/RX VRM	300 / PACKE T		<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>

152	DNO755 14	511-7975	4310715701972 / PUMP GP-FUEL INJECTION		1 / EACH/ NUMBE R	C9.3		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - Full</u>
153	DNO747 99	326-2041	5331715683465 / SEAL (FUEL SYSTEM)		6 / EACH/ NUMBE R	C9.3		<u>TECHNICAL SPECIFICATION - Not</u> Known <u>GENERAL SPECIFICATION -</u> Not Known
154	DNO747 98	467-1475	4730775269643 / HOSE AS		1 / EACH/ NUMBE R	C9.3		<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION - null</u>
155	DNO747 95	447-5663	2915715177086 / TUBE AS-FUEL		2 / EACH/ NUMBE R	C9.3		<u>TECHNICAL SPECIFICATION - Not</u> Known <u>GENERAL SPECIFICATION -</u> Not Known
156	DNJ746 85	60H- W0090- 02-1S	2010765210656 / CRANK CYLINDER ASSY	OEM ENGINE L200AET,18(60JK)JAPAN	1 / EACH/ NUMBE R	L200AET ,18(60JK	YAMAHA MOTOR CO. LTD ADDRESS: 2500 SHINGAI, LWATA, SHIZUOKA 438- 8501, JAPAN PHONE NO 0081-538-37- 1668 FAX.0081-538- 37-1954	<u>TECHNICAL SPECIFICATION -</u> SPARE REQUIRED FOR SAT OPS REQUIRMENT L200AET <u>GENERAL</u> <u>SPECIFICATION - SPARE</u> <u>REQUIRED FOR SAT OPS</u> <u>REQUIRMENT L200AET</u>

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

478

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 24 dt 02/12/2024	300000.00
Bank A/c No PK17HABB0004540013100701	300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A
(Signature of Offr Signing the cheque)

Initial
Supdt Audit Sec

Initial
Officer OI/C Audit Sec

To HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD
P.P.R.A
PPRA 1st Floor FBC Building, Near State Bank S.ctor G-5/2, Islamabad

Copy To LP Division
2. LAO (LAO (NAVY) NSD KARACHI)