

TENDER BULLETIN

DATE & TIME 2/10/25 11:34 AM INVITATION TO TENDER TO BE OPENED ON 22/4/2 10:00 AM AND ITEM REQ BY

- CONDITIONS**
1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
 2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
 3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNZ7347 1	6FE-50	413073522550 1 / AC COMPRESSO R ALONGWITH ACCESSORIE S	AC Compressor	2 / EACH/N UMBER	6 FE-50	6 FE-50	SABRO Technologies (PVT)Ltd, Plot No 77778, Street no 10, I-9/2 Islamabad	SABRO		TECHNICAL SPECIFICATION -As per attached Technical Specification Documents,GENERAL SPECIFICATION -As per attached Technical Specification Documents.	
2	DNZ7415 6	CXH3- 101P- 01/200-011	621072000606 5 / MAST HEAD LIGHT (WHITE)		1 / EACH/N UMBER	3NM 225 VERTICA L MOUNT			JIANGLI N TURBO CHARGE R PLANT. UNDER LICENCE OF ABB TURBO SYSTEM LTD. MADE IN CHINA PH#0086 (23) 47221135 E-MAIL: JTMAIL@ CTA.CO. CN		TECHNICAL SPECIFICATION - JIANGLIN TURBO CHARGER PLANT. UNDER LICENCE OF ABB TURBO SYSTEM LTD MADE IN CHINA PHONE NO 0086(23) 47221135 E-mail:jtmali@cta.cn. GENERAL SPECIFICATION - JIANGLIN TURBO CHARGER PLANT. UNDER LICENCE OF ABB TURBO SYSTEM LTD MADE IN CHINA PHONE NO 0086(23) 47221135 E-mail:jtmali@cta.cn	
3	DNZ7094 2	VTR251- 382	203078514288 6 / INNER BEARING BUSH (TURB END) OF T/C VTR251		40 / EACH/N UMBER	NO DATA AVAILAB LE	18B/19B	CH				

S. No	LP/R No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Remarks
4	DNN767 61	3883257	803073518059 3 / SEALING	engine gearbox	1 / EACH/IN UMBER			AB volvo penta, Gropogardsgatan, 405 08 Gote borg, Sweden	AB volvo penta, gote borg, sweden		TECHNICAL SPECIFICATION - Item required for the rectification of OPDEF of MST boat gear box GENERAL SPECIFICATION - item required for the rectification of OPDEF of MST boat gear box	
5	DNN767 65	184867	311073518059 7 / BEARING	engine gearbox	2 / EACH/IN UMBER			AB volvo penta, Gropogardsgatan, 405 08 Gote borg, Sweden	AB volvo penta, gote borg, sweden		TECHNICAL SPECIFICATION - Item required for the rectification of OPDEF of MST boat gear box UK GENERAL SPECIFICATION - item required for the rectification of OPDEF of MST boat gear box UK	
6	DNF7697 9	J9776A / J9772A+14 859c	589578520783 3 / NETWORK SWITCH HP 2530 24G/48G WITH 2/4 SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/IN UMBER	RG- NBS5200- 48G14x8/ R8N88A- HP/J9776 A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED	
7	DNF7460 9	BM7500 / IMEI: 358419070 009444	653070520521 6 / SVAS TAB	SVAS SYSTEM BM7500 PAKISTAN	1 / SET	BM7500	NY- SVAS-08	M/S C Digital, House No 275-C, Street No 13, Chaklala Scheme III, Rawalpindi Tel 051- 5155790-92, Fax 051- 51333789	INDIGEN OUS PAK		TECHNICAL SPECIFICATION - SVAS TAB (Customized with NADRA compliant bar code reader and biometric scanner module, software and hardware included) with secure date SIM including one year date charges, service, warranty configuration and installation. OEM, ARATEK BIOMATRIC CO LTD TAIWAN E-MAIL SALES@ARATEK CO TEL:886-5-2501-0001 GENERAL SPECIFICATION - SVAS TAB (Customized with NADRA compliant bar code reader and biometric scanner module, software and hardware included) with secure date SIM including one year date charges, service, warranty configuration and installation. OEM, ARATEK BIOMATRIC CO LTD TAIWAN E- MAIL SALES@ARATEK.CO TEL: 886-5-2501-0001	
8	DNF7435 3	169191937 10 (EXPRESS SERVICE CODE)	743578520521 9 / SVAS WEB TERMINAL (LAPTOP DELL/HP C13)	SVAS SYSTEM NY-SVAS-08 CHINA	1 / SET	NY- SVAS-08	NA	DELL INC 1 DELL WAY. ROUND ROCK, TEXAS CHINA 78682. TEL 1-866- 931-3355	CHINA		TECHNICAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15 GENERAL SPECIFICATION - SVAS WEB	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
9	DNF7688 8	ODS- AGM6M/ 9750N702 5	614001485147 2 / 12VDC 120AH LEAD ACID BATTERY	25 MM GUN	2 / EACH/N UMBER	HASP- FT/6TAG M		ENERSYS ENERGY PRODUCTS INC UK TEL 877-485-1472 WWW.HAWKERAPLUS. COM	ENERSYS ENERGY PRODUC TS INC UK		Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15	
10	DNF7412 0	TFBLL2002 /LPB-G3E- 17	611570520756 8 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAKISTAN	1 / EACH/N UMBER	2017	NA	M/S SOFT INOVATIVE SYSTEM 34-A2, 1ST FLOOR, OPP LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI TEL. +922135610429 +9221385610277	M/S SOFT INNOVAT IVE SYSTEM S		TECHNICAL SPECIFICATION - NOMINAL CAPACITY = 4 AH NOMINAL VOLTAGE = 20V DC BATTERY SIZE = 135X60X60 mm +/- 10% DISCHARGE CUTOFF VOLTAGE = 16 V DC CHARGING CONNECTOR = OPEN WIRE WIRE LENGTH = 300mm SHORT CIRCUIT PROTECTION = AVAILABLE OVER LOAD PROTECTION = AVAILABLE GENERAL SPECIFICATION - NOMINAL CAPACITY = 4 AH NOMINAL VOLTAGE = 20V DC BATTERY SIZE = 135X60X60 mm +/- 10% DISCHARGE CUTOFF VOLTAGE = 16 V DC CHARGING CONNECTOR = OPEN WIRE WIRE LENGTH = 300mm SHORT CIRCUIT PROTECTION = AVAILABLE OVER LOAD PROTECTION = AVAILABLE	
11	DNF7657 9	DH- SD6CE445 XA-HNR/ DH- SD5A445X A-HNR/ DH- SD6AL240 -HNI	582078520788 6 / NETWORK PTZ CAMERA 4MP WITH ACCESSORIE S	CCTV System DH-SD6AL240- HNI CHINA	1 / EACH/N UMBER	DH- SD6AL24 0-HNI	NA	No. 1199 Bir'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-87688883	M/s Dahua		TECHNICAL SPECIFICATION - mage Sensor 1/2.8" CMOS Effective Pixels 1920(H) x 1080(V), 2 Megapixels RAM/ROM 512M/32M Scanning System Progressive Electronic Shutter Speed 1/1s-1/30, 000s S/N Ratio More than 56dB IR Distance Distance up to 500m (1640f) IR On/Off Control Auto/Manual IR LEDs Laser module GENERAL SPECIFICATION - mage Sensor 1/2.8" CMOS Effective Pixels 1920(H) x 1080(V), 2 Megapixels RAM/ROM 512M/32M Scanning System Progressive Electronic Shutter Speed 1/1s-1/30,000s S/N Ratio More than 56dB IR Distance	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
12	DNF7412 1	TFBL12002 ALPB- MPSE-17	611570520759 3 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAK	1 / EACH/IN UMBER	2017	NA	M/S SOFT INNOVATION SYSTEM 34-A2, 1st FLOOR LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVAT IVE SYSTEM S		TECHNICAL SPECIFICATION- BATTERY REQUIRED FOR SIMULATOR GENERAL SPECIFICATION - BATTERY REQUIRED FOR SIMULATOR	
13	DNF7412 2	TFBL2002 ALPB- SMGE-17	611770520758 9 / BATTERIES (20V4AH) LITHIUM POLYMER	G-3 SIMULATOR 2017 PAK	1 / EACH/IN UMBER	2017	NA	M/S SOFT INNOVATION SYSTEM 34-A2, 1st FLOOR LUXURY HOTEL, LALAZAR OFF. MT KHAN ROAD KARACHI +9221385610277	M/S SOFT INNOVAT IVE SYSTEM S		TECHNICAL SPECIFICATION- Nominal Capacity = 4AH Nominal Voltage = 20V Battery Size = 135x60x60 mm = - 10% Discharge Cutoff Voltage = 16V Charging Connector = Open Wire Wire Length = 300 mm Short Circuit Protection = Available Over Load Protection = Available	
14	DNJ7549 8	90155- 10006	530576518084 4 / SCREW FLAT FILLISTER	YAMAHA OUTBOARD ENGINE 150HP	64 / EACH/IN UMBER	F150BET		YAMAHA MOTOR COMPANY LIMITED, JAPAN	YAMAHA MOTOR COMPAN Y		TECHNICAL SPECIFICATION- YAMAHA MOTOR COMPANY LIMITED, JAPAN GENERAL SPECIFICATION - YAMAHA MOTOR COMPANY LIMITED, JAPAN	
15	DNN761 98	GB91	5315FP004006 1 / Pin	NG16-1 SINGLE BARREL 76MM NAVAL GUN	10 / EACH/IN UMBER	N/A		FU LA ER JI, P.R.C.			TECHNICAL SPECIFICATION- GENERAL SPECIFICATION-	
16	DNN761 97	GB91	5315FP004006 2 / Pin	NG16-1 SINGLE BARREL 76MM NAVAL GUN	10 / EACH/IN UMBER	N/A		FU LA ER JI, P.R.C.			TECHNICAL SPECIFICATION- GENERAL SPECIFICATION-	
17	DNF7698 8	E95 (D)	613571517943 4 / 1.5 V +D SIZE ENERGIZER	CTD.SV PROBE	196 / EACH/IN UMBER	SNI 04- 205-2- 2004	SNI 04- 205-2- 2004	Energizer Holding Inc st Louis MO 63141 UNITED STATES OF	ENERGIZ ER . USA		TECHNICAL SPECIFICATION - 1.5 VOLT PILE ALKALINE BATTERY. USEFUL FOR SURVEY OPERATION. D SIZE CELL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
18	DNF7698	E93 (C)	613571517943 3 / 1.5 V +C SIZE ENERGIZER PILE ALKALINE BATTERY	CTD,SV PROBE	144 / EACH/IN UMBER	SNI 04- 205-2- 2004	SNI 04- 205-2- 2004	energizer Holding Inc st Louis MO 63141 UNITED STATES OF AMERICA	ENERGIZ ER, USA		Classification: alkaline chemical systems: zinc-manganese dioxide, no added mercury or cadmium designation: ans-13a, inc-120 nominal voltage: 1.5 volts, nominal lr: 200 to 400 milliohms operating temp: -18c to 55c typical weight: 139 gms -18c to 55c typical volume: 3.4 cubic inch jacket plastic label shelf life: 10 yrs at 21c terminal: flat contact GENERAL SPECIFICATION: 1.5 VOLT PILE ALKALINE BATTERY, USEFUL FOR SURVEY OPERATION, D SIZE CELL Classification: alkaline chemical systems: zinc-manganese dioxide, no added mercury or cadmium designation: ans-13a, inc-120 nominal voltage: 1.5 volts, nominal lr: 200 to 400 milliohms operating temp: -18c to 55c typical weight: 139 gms typical volume: 3.4 cubic inch jacket plastic label shelf life: 10 yrs at 21c terminal: flat contact	
6	DNF7698	E93 (C)	613571517943 3 / 1.5 V +C SIZE ENERGIZER PILE ALKALINE BATTERY	CTD,SV PROBE	144 / EACH/IN UMBER	SNI 04- 205-2- 2004	SNI 04- 205-2- 2004	energizer Holding Inc st Louis MO 63141 UNITED STATES OF AMERICA	ENERGIZ ER, USA		Classification: alkaline chemical systems: zinc-manganese dioxide, no added mercury or cadmium designation: ans-13a, inc-120 nominal voltage: 1.5 volts, nominal lr: 200 to 400 milliohms operating temp: -18c to 55c typical weight: 139 gms -18c to 55c typical volume: 3.4 cubic inch jacket plastic label shelf life: 10 yrs at 21c terminal: flat contact GENERAL SPECIFICATION: 1.5 VOLT PILE ALKALINE BATTERY, USEFUL FOR SURVEY OPERATION, D SIZE CELL Classification: alkaline chemical systems: zinc-manganese dioxide, no added mercury or cadmium designation: ans-13a, inc-120 nominal voltage: 1.5 volts, nominal lr: 200 to 400 milliohms operating temp: -18c to 55c typical weight: 139 gms typical volume: 3.4 cubic inch jacket plastic label shelf life: 10 yrs at 21c terminal: flat contact	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
19	DNF7688 1	CAT-6	783070519365 0 / d link 24 AWG 4 pair CAT-6 sftp CABLE ROLL (305M / 1000ft)	DAWN NETWORK	3 / ROLL	D-LINK				M/S MICROTECH INC 184, CO-OPERATIVE MARKET SADDAR KARACHI	M/S MICROTE CH INC	
20	DNF5377 7	DCC/HFB M/HW/119	705070521567 7 / HDMI CABLE 25MTR FIBER OPTIC	OPERATOR CONSOLE DCC-2016 PAKISTAN	4 / EACH/IN UMBER	NA	NA	Commercially Of The Shelf (COTS)Local Market	COTS		TECHNICAL SPECIFICATION - DISPLAY CABLEGENERAL SPECIFICATION - DISPLAY CABLE	
21	DNST63 48	120013	462000722419 2 / Valve guide	WARTSILA MAIN ENGINE 9L20C3 FINLAND	4 / EACH/IN UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243	Wartsila Finland Oy Vaasa Factory Tarttuajantie 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tlx 74251 wa sf	Wartsila Finland Oy		TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
22	DNC761 81	CL002283/ WBCL009 390	283572513298 2 / SCROOL COMPRESSOR 60000 BTU 400V R407C	AIR CONDITIONIN G SYSTEM	1 / EACH/N UMBER	NO DATA AVAILAB LE	PAAE084 244	Fax (Service) .358 6 356 7355 Fax (Spare parts) +358 10 709 1380	CONTRA CT NO. 1347/202/ DGDP/PC -4 DT. 28/06/200 6 &HCG/ZK /IDC/351 DT 24/07/08		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
23	DNS738 12	961663	473027037435 8 / HOSE CLAMP	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	25 / EACH/N UMBER	D9A2A		VOLVO AB GOETEBORG SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
24	DNF7265 4	BSEN6031 7-8 / CW1- 18	056179519875 1 / WIRE, WINDING COPPER ELECT COND DIA : 1.180MM O/DIA : 1.308 MM	FOR WINDING.	80 / KILOGR AMME						TECHNICAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2 GENERAL SPECIFICATION - Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue	
25	DNF7265 2	BSEN 60317-8	056179519875 6 / WIRE WINDING ELECT COPPER POLYESTER ENAMEL COND DIA 0.850 O/DIA 0.964MM (GRADE-3 CLASS-180)	FOR WINDING.	15 / KILOGR AMME						TECHNICAL SPECIFICATION - DATA AVAILBLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DNF7265 5	BSEN6031 7-8	056170525356 9 / WIRE, WINDING COPPER ELECT COND DIA- 0.710MM		15 / KILOGR AMME	GHAZILE X					TECHNICAL SPECIFICATION - DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 PURITY: 99.95 % COPPER CLASS: CLASS- 180GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			O/ DIA : 0.790 MM (CLASS 180)								DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4685 PART-1 BSEN60317-9 GRADE-2 PURITY: 99.95 % COPPER CLASS: CLASS-180	
27	DNF7673 B	0662-402044	056279428310 1 / BATTERY SECONDARY ACID TYPE 12V 64AH 14.875X6.812X9.750IN	GENERAL USE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
28	DNF7307 2	BSEN6031 7-8 / W0-63	056179525360 4 / WIRE, WINDING COPPER ELECT COND DIA 0.630MM O/A DIA 0.730 (CLASS-180)	WIRE WINDING	20 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DNA752 75	SN 02-06	281573508919 9 / FERRULE SIZE 3/8"	MACHINERY ON TYPE-21 & MCMVS	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DNA752 76	MS 00-24	281573508920 3 / FERRULE SIZE 1 1/2 (LENTH:86 mm, WIDTH 85mm, THICKNESS 43.5mm)	MACHINERY ON TYPE-21 & MCMVS	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM: SUNWAY HYDRAULIC INDUSTRIES SDN BHD MALAYASIA EMAIL: LOOBS@SUNWAY.COM.MY WEBSITE: WWW.SUNWAY.COM GENERAL SPECIFICATION - OEM: SUNWAY HYDRAULIC INDUSTRIES SDN BHD MALAYASIA EMAIL: LOOBS@SUNWAY.COM.MY WEBSITE: WWW.SUNWAY.COM	
31	DNG754 97	5117005	281500735420 2 / WASHER THURUST CRANK (THURUST PLATE CRANKS) 5117005 (USA MAKE)		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
40	DNF6769 3	SMT3000I C/SURTD3 000XLR30 00VA APC	613071506382 3 / UPS 3KVA APC/1P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEM PVT.					TECHNICAL SPECIFICATION:- APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL, GENERAL SPECIFICATION.-APC SMART- UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL.	
41	DNF767Z 3	650 VA APC USA	613070509060 4 / APC (BACK UPS650)	COMPUTER	2 / EACH/N UMBER						TECHNICAL SPECIFICATION.-A Load 650VA/ 520 Wats b. Backup Time 13 - 15 Min GENERAL SPECIFICATION.-A. Load 650VA/ 520 Wats b. Backup Time 13 - 15 Min	
42	DNF7617	XS100NB	562576512319	AIR	4 /						TECHNICAL SPECIFICATION.-NO	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilly	Tender Remarks	TECH / GEN SPECS	Dimension
32	DNA75274	SN 02-04	281573508919 7 / FERRULE SIZE 1/4"	MACHINERY ON TYPE-21 & MCMVS	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DNA73504	0350- 2N379A	432099558527 5 / MECHANICAL SEAL	AIR CONDITION PLANT	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
34	DNF76815	158-51010	596199558030 7 / DIODE 25AMPS 800VOLT.	MAIN RECTIFIER ASSY	6 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
35	DNF76816	158-51020	596199558031 4 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAH)	33 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DNF76725	TTB3450S	791070505097 5 / MACHINE FLOOR POLISHER 120/220V AC 50/60HZ 1000W 150RPM	SELF	2 / EACH/N UMBER	UPDATE MODED TT 3450 NUMATIC . UK.					TECHNICAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK.GENERAL SPECIFICATION - UPGRADED MODEL : TT3450S, NUMATIC, UK.	
37	DNF75291	210883-1	865500162247 9 / EXPENDABLE BATHY PROBE TT	LEANDER CLASS DEPOT PACKAGE	24 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DNF76982	ep- 1000/biaz er vista 1000	703570505992 7 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	3 / EACH/N UMBER	BLAZER VISTA 1000/Auto ra					TECHNICAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V ACGENERAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
39	DNF76892	SMT3000I C/SURTD3 000XL/30 00VA APC	613071506382 3 / UPS 3KVA APC/PP220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEM PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFC PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA9300041	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	S/R NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
4			4 / MINIATURE CIRCUIT BREAKER 220V 20AMP 2POLE	CONDITIONIN G SYSTEM	EACH/N UMBER						DATA AVAILBLEGENERAL SPECIFICATION - NO DATA AVAILBLE	
43	DNF7258 2	04150550	599578528426 6 / Diesel Control Cable, 10m, 24AWG		3 / EACH/N UMBER	EN2CPO WERC01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
44	DNF7651 6	wp7-12 (28w)	614078523833 3 / KLUNG LONG BATTERY 12V 7 AH 28W/CELL/15 MIN		128 / EACH/N UMBER	wp7-12 (28w)					TECHNICAL SPECIFICATION - RECHARGEABLE SEALED LEAD ACID BATTERY DC POWER CONSTANT VOLTAGE CHARGE CYCLE USE 14.4 -15.0V (25C) STANDBY USE 13.5-13.8V (25C) INITIAL CURRENT 2.1a MAX make: vietnamGENERAL SPECIFICATION - RECHARGEABLE SEALED LEAD ACID BATTERY DC POWER CONSTANT VOLTAGE CHARGE CYCLE USE 14.4 -15.0V (25C) STANDBY USE 13.5-13.8V (25C) INITIAL CURRENT 2.1a MAX make: vietnam	
45	DNF7619 6	XCK+ZCK	593078528974 7 / Switch		2 / EACH/N UMBER	NPT10DC					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
46	DNO767 67	8C-3080	533101454307 7 / SEAL-O-RING		3 / EACH/N UMBER	C 9.3					TECHNICAL SPECIFICATION - SEAL-O-RING GENERAL SPECIFICATION - null	
47	DNF7619 9	100237	491079533282 8 / calibration unit FOR NIFTY LIFT		1 / EACH/N UMBER	120t (tm34t)					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
48	DNF7698 0	gxt mt + cx 3 kva	599970524633 0 / vertiv ups 3kva/2400w		1 / EACH/N UMBER	GXT MT + CX 3 KVA					TECHNICAL SPECIFICATION - Input voltage : 220V IL Frequency : 50Hz III. Phase : Single Phase IV. Rating: 3000VA (2700V) v. Output Voltage : 230 Volt v. Frequency: 50Hz vII. Phase : Single Phase. vIII. Operating temp: 0-40°C cx. Battery (external battery bank): 6x 12v 200ah maintenance free BACKUP TIME 30-45 MINUTESGENERAL SPECIFICATION - I. Input voltage :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
49	DNF7142 4	6226d	341378529236 4 / cordless driver drill		2 / EACH/N UMBER	MAKITA 6226d					220V 5. Frequency : 50Hz Ill. Phase : Single Phase W. Rating: 3000VA (2700W) v. Output Voltage : 230 Volt v. Frequency: 50Hz vll. Phase : Single Phase. vll. Operating temp: 0- 40°C W. Battery (external battery bank): 6x 12v 200ah maintenance free BACKUP TIME 30-45 MINUTES	
50	DNF7681 0	WP7-12 / GP-1272- F2	613501608940 3 / SEALED LEAD BATTERY 12V 7.2AH (Maintenance Free)		131 / EACH/N UMBER	CSB GP- 1272-FF 7.2 AH					TECHNICAL SPECIFICATION:- muGENERAL SPECIFICATION:- null	
51	DNF6930 1	amp 001	611076528923 8 / dc comparator (amp 001) (SIGNAL AMPLIFIER PCB)		2 / EACH/N UMBER	amp-001					TECHNICAL SPECIFICATION:- muGENERAL SPECIFICATION:- null	
52	DNF7450 3	807290	590578527927 4 / microdige pro cnc		1 / EACH/N UMBER	MICROE DGE PRO CNC MACHINE					TECHNICAL SPECIFICATION:- MICRODGE PRO CNC MACHINE part no: 807290muGENERAL SPECIFICATION:- MICRODGE PRO CNC MACHINE part no: 807290	
53	DNV765 95	MBS3100- 060G3917	666572526418 0 / PRESSURE SENSOR		2 / EACH/N UMBER	0659.064. S36					TECHNICAL SPECIFICATION:- muGENERAL SPECIFICATION:- null	
54	DNF7540 5	PAM16451	599673526191 2 / AMPLIFIER MODULE 200VDC-50A		2 / EACH/N UMBER	IF-6M MARINE					TECHNICAL SPECIFICATION:- MuGeneral LmgeneRAL SPECIFICATION:- Indian Marine LMA	
55	DNNT736 59	G203 ZZR	311014224149 2 / BEARINGS (DRIVE END)	HVAC SYSTEM(F- ZPP)	1 / EACH/N UMBER	NO DATA AVAILAB LE		US	LIKELY SUPPLIE R OEM BRONSON		TECHNICAL SPECIFICATION:- muGENERAL SPECIFICATION:-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									ERK MARINE INC.3755 C BOUL. MATTE BROSSA RD, Q.C. J 4Y 2P CANADA, TEL. +4506596 571, FAX: +4506591 035, ROB. DEWERK @BRONS WERKGR OUP. COM			

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

478

Pakistan Military Accountst DepartmentOffice of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 24 dt 02/12/2024	300000.00
Bank A/c No PK17HABB0004540013100701	300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank S.ctor G-5/2, Islamabad

Copy To LP Division

2. LAO (LAO (NAVY) NSD KARACHI)