

TENDER BULLETIN

DATE & TIME 3/11/25 11:01 AM INVITATION TO TENDER TO BE OPENED ON 3/26/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE775 87		046250220180 3 / TUBING PLASTIC POLYETHLEN E LAY FLAT WD.48	DC/FF	60 / KILOGR AMME						TECHNICAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317GENERAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317	
2	DGB741 13		027459910485 1 / FILE ENGINEER HALF ROUND D-CUT FACES BASTARD 4.00 IN		9 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DGB739 40	WEIGHT OF HOOK 2 LB 8 OZ	026259001889 5 / HOOK BOAT LARGE ML-STEEL LG 11.75"DP.1.75" W/B/H5- 3/8WT2LB8OZ		50 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
4	DGE748 64	13213E54 56-12	422000275315 6 / LIFE BOUY (RING BOUY LIFE SAVING) ROUND ORANGE OUTER (COMD8)		24 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
5	DGB742 36	220V 7A 50/80H257 0WSNO35 961-2E	513070503602 4 / ELECTRIC GRINDER PORTABLE HEAVY DUTY 3"DISC 100MM220V 1200/M	FOR GENERAL USE	2 / EACH/N UMBER	BLAR-42					<p>TECHNICAL SPECIFICATION - Cable Length: 2m Weight: 2.9Kg Disc Diameter: 100 mm No Load Speed: 1200/min Axis: 5/8"-11/M14 Frequency: 50/60Hz Power: 650W Speed: 1200/ min(rpm) Voltqge: 220-220 Volt/ 50Hz</p> <p>GENERAL SPECIFICATION - Cable Length: 2m Weight: 2.9Kg Disc Diameter: 100 mm No Load Speed: 1200/min Axis: 5/8"-11/M14 Frequency: 50/60Hz Power: 650W Speed: 1200/ min(rpm) Voltqge: 220-220 Volt/ 50Hz</p>	
6	DGE763 71	CM6538- 000	597070504435 2 / TAPE INSULATING RAYCHEM HVB HEAT SHRINKABLE		50 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes</p> <p>GENERAL SPECIFICATION - Material System: Polyolefin Busbar Insulation Technology: Heat Shrink Busbar Insulation Voltage Class: = 36kV Color: Red Busbar Insulation Tape Width: 100mm (3.93 inch) Length of roll: 10 m Operating Temperature Range: -40 to 90 °C Low Halogen: Yes</p>	
7	DGE773 17	NO DATA AVAILABL E	653070504454 5 / HOSPITAL WARD BED ADJUSTABLE WITH UNDERCARRI AGE COMPLETE		4 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - material dimensions colour type of coating grade of steel Specification: a. I.C.U Bed Three Crane Adjustable b. Main frame 18 G pipes, sub frame & foot side & head side bow 18 SWG pipe. c. Height Adjustable pipe use 2 1/4 x 1 "20 gauge. d. Crane Pipe 18 Gauge. e. Top Size 3 x 6 1/4 Include Drip Rod Stand. f. Both sides FIBER side (Made in China) g. Wheel 4" (Made in China) h. Side railing set (Made in China) j. Titling system (head/knee/foot) is required along</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>with adjustable handles. k. Two screw clanks one for Head side and other for foot side. l. Urine bag hooks with smooth clips-02 in Nos. m. White Powder paint color as per international standard. 1. LG 210CM 2. WD 91 CM 3. Height 57</p> <p>CMGENERAL SPECIFICATION - material dimensions colour type of coating grade of steel Specification: a. I.C.U Bed Three Crane Adjustable b. Main frame 18 G pipes, sub frame & foot side & head side bow 18 SWG pipe. c. Height Adjustable pipe use 2 1/2 x 1 "20 gauge. d. Crane Pipe 18 Gauge. e. Top Size 3 x 6 1/4 include Drip Rod Stand. f. Both sides FIBER side (Made in China) g. Wheel 4" (Made in China) h. Side railing set (Made in China) j. Tilting system (head/knee/foot) is required along with adjustable handles. k. Two screw clanks one for Head side and other for foot side. l. Urine bag hooks with smooth clips-02 in Nos. m. White Powder paint color as per international standard. 1. LG 210CM 2. WD 91 CM 3. Height 57 CM</p> <p>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per</p>	
8	DGB757 68	NO DATA AVAILABL E	024850000001 5 / SAFE- STEEL-WITH- COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		1 / EACH/N UMBER	NO DATA AVAILAB LE						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RWIMs record	
9	DGE74869	NO DATA AVAILABLE	041378000045 5 / HOSE RUBBER 70X80X1000MM	DIESEL ENGINE 485	3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DGE75571	NO DATA AVAILABLE	046150000015 6 / MOP WHITE POLOSHING QUALITY FINE 10"		6 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - DIAMETER= 10 INCH THICKNESS= 1.5 INCH CLOTH LAYERS = 100 IN NO CLOTH MATERIAL= COTTON CLOTH GENERAL SPECIFICATION - DIAMETER= 10 INCH THICKNESS= 1.5 INCH CLOTH LAYERS = 100 IN NO CLOTH MATERIAL= COTTON CLOTH	
11	DGE72407	NO DATA AVAILABLE	043350000001 3 / FINS RUBBER FOR DIVERS.		14 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
12	DGE76309	R	834570504262 9 / Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter)	ITEM REQUIRED FOR MAKING OF GIFT BOXES	35 / METER						TECHNICAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes GENERAL SPECIFICATION - Cloth Suede (Velvet) Color Blue With 40 Inch (01 meter) oem: Pakistan PN Dockyard/Timber Craft Shop (C No 107) Item required for making of gift boxes	
13	DGE69307	Is219004pk	841576100337 8 / HELMET CRASH VIP ESCORT RIDER W/SUN VISER, NYL/BELT FOAM COAT		3 / EACH/NUMBER	ff353 rapid single mono					TECHNICAL SPECIFICATION - colour: gloss white (2) Serial No 1003378 size: xxl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm) GENERAL SPECIFICATION - colour: gloss white (2) Serial No 1003378 size: xxl carton no. 102-57 W/Sun Viser, Size 23.23"-23.62" NYL/Belt Foam (56-60 cm)	
14	DGE77754		711070511488 8 / master AURA LOW BACK	MASTER OFFICE CHAIR	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			REVOLVING CHAIR								<p>(3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240</p> <p><u>GENERAL SPECIFICATION</u> - Specification Of Item: (1) Lockable revolving and tilting mechanism. (2) Lockable at three different positions. (3) Extra torsion adjustment control. (4) Sleek and Stylish PP Arm set. (5) Adjustable Seat Height, gas lift and swivel. (6) 5 x prong pressure die-cast Aluminum/Nylon with reinforced fiberglass base for added seating support. (7) Twin wheel Castors, which meet requirement of BIFMA and DIN Standards. (8) High frequency compression process on multi-layer veneer shell, automatically designed for posture care. (9) Guaranteed pure excel foam of highest density. (10) Scotch guard</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											protected fabric. (11) Customization of arm set, base upholstery should be offered. b. OEM/COUNTRY OF ORIGIN/MANUFACTURE: DETAIL OF OEM IS AS UNDER: (1) M/S MASTER PAKISTAN (TECHNICAL COLLABORATION WITH BAYER, GERMANY) (2) BRANCH OFFICE: ARAM BAGH FURNITURE MARKET KARACHI (3) EMAIL: SALE@MASTERHOUSE.COM.PK (4) PHONE: +923009223440, +923212625240	
15	DGE744 92	NO DATA AVAILABL E	650350502490 7 / WHEEL CHAIR HOSPITAL STAINLESS STEEL PIPE (UN FOLDING)	FOR HOSPITAL	22 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DCD751 66		845670390179 3 / BADGE ARM BLUE FOR NI BRANCH LINTT		200 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	Item requird for tander sample
17	DGB755 58	NO DATA AVAILABL E	566070514847 6 / CONCER TINA WIRE	FOR BOUNDARY PROTECTION	25 / ROLL			SOURCE OF AVALIBILTY: PAKISTAN WIRE SITE AREA KARACHI .Mr WASEEM CONTRACT NO 0333-2112465.	PAKISTA N WIRE		TECHNICAL SPECIFICATION - Country of origin pakistan BLADE SIZE:22MML, 14MMW BLADE THIKNESS:0.5MM LINE WIRE:2.6 /3MM 10-12 GAUGE SIZE:36INCH DIA MATERIAL:(MILD STEEL&GALVANIZED GENERAL SPECIFICATION - Country of origin pakistan BLADE SIZE:22MML, 14MMW BLADE THIKNESS:0.5MM LINE WIRE:2.6/3MM 10-12 GAUGE SIZE:36INCH DIA MATERIAL:(MILD STEEL&GALVANIZED	
18	DGE762 80	L-4" Dia 1"	046170514204 1 / REFILE PAINT ROLLER WITH HANDLE	HULL PAINT SCHEME	64 / EACH/N UMBER	NO DATA AVAILAB LE	PK		M/S AJAZ PAINT HOUSE MARRIOT ROAD		TECHNICAL SPECIFICATION - Refille Paint Roller With Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan description: complete paint roller with handle SOURCE OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LENGTH 4 INCH DIA 1 INCH						KARACHI PHON NO.021 32412531		AVAILABILITY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work <u>GENERAL SPECIFICATION -</u> Refille Paint Roller With Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan description: complete paint roller with handle SOURCE OF AVAILABILITY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work	
19	DGH76110	WMS1.5 TON	2590785205060 / MANUAL STACKER	MANUAL STAC KER WMS 1.5 TON CHINA	2 / EACH/NUMBER	WMS 1.5 TON	NIL	CNMHE MATERIAL HANDLING COMPANY LTD. 2F, MAIN BUILDING NO.888, JINDU ROAD, YINHOU DISTRICT, NINGBO, CHINA 315000	STAXX CHINA		<u>TECHNICAL SPECIFICATION -</u> LIFTING CAPACITY= 1.5 TON LIFTING HEIGHT= 1.6 M <u>GENERAL SPECIFICATION - LIFTING CAPACITY= 1.5 TON LIFTING HEIGHT= 1.6 M</u>	
20	DGH75843	LCKHB1081182B	3020705202580 / BEAM PR 2740X240	RACKS	30 / EACH/NUMBER			OFFICE:3RD FLOOR 83 C, PHASE2, EXT, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726	HABIB & SONS		<u>TECHNICAL SPECIFICATION -</u> Profile: Step Beam Size: 118mm x 50mm Surface Finish: Rai 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5 <u>GENERAL SPECIFICATION -</u> _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Rai 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
21	DGE72285	4279	4240TY5202554 / REUSABLERE SPIRATORS 3M 7502 HALF MASK WITH 6059 CARTRIDGE+502	SAFETY	47 / SET	NIL		3M	3M		<u>TECHNICAL SPECIFICATION - a.</u> Size: 7502 b. Cartridge: 6059 ABEK1 c. Adopter: 502 d. Filter: 2135 ORGANIC VAPOUR PARTICULATES VAPOURS ACID GAS AMMONIA FFABEK1P3 <u>GENERAL SPECIFICATION - a.</u> Size: 7502 b. Cartridge: 6059 ABEK1 c. Adopter: 502 d. Filter: 2135	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ADOPTER+213 5 FILTER								ORGANIC VAPOUR PARTICULATES VAPOURS ACID GAS AMMONIA FFABEK1P3 RD	
22	DGE757 91		046150461008 7 / GOGGLE- GLASS		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
23	DGE723 02	NO DATA AVAILABL E	055979002055 2 / INSULATION TAPE ELECTRICAL SHRINKABLE WD 2IN RUBBER	GENERAL ELECTRIC USE	181 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
24	DGE762 66	NO DATA AVAILABL E	041459923091 4 / PACKING MATERIAL BRADED TYPE FOR FURNACE FUEL DIESEL OIL, LUBRICATING OIL AND LOW PRESSURE 5/8	SEA WATER PUMP	18 / METER						TECHNICAL SPECIFICATION - PACKING MATERIAL BRADED TYPE FOR FURNACE FUEL DIESEL OIL, LUBRICATING OIL AND LOW PRESSURE HYDRAULIC VALVE GLANDS, COIL FORM 5/8 GENERAL SPECIFICATION - PACKING MATERIAL BRADED TYPE FOR FURNACE FUEL DIESEL OIL, LUBRICATING OIL AND LOW PRESSURE HYDRAULIC VALVE GLANDS, COIL FORM 5/8	
25	DGE762 70	NO DATA AVAILABL E	046159000098 0 / CLOTH ABRASIVE 9		134 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DGE776 86		045159451009 4 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS		100 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
27	DGB749 44		027779001236 3 / SPANNER OPEN JAW FIXED BSW 0.6875"		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
28	DGE763 18	0413-8553,	041359923892 6 / RUBBER SHEET SOLID NATURAL, LENGTH= 72", WIDTH= 43"		30 / KILOGR AMME						TECHNICAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"GENERAL SPECIFICATION - SPECS= BS 1154 OF 1992 LENGTH= 72" WIDTH= 48" THICKNESS=0.188" TENSILE STRENGTH= NO. OF PLYS=2, APPROX WEIGHT PER SQ FT= 1.5 LBS, COMPUND Y2, HARDNESS RATING= 42-50"	
29	DGB724 82		021259571070 1 / BAR STEEL CORROSION RESISTING HOT ROLLED ROUND		18 / METER						TECHNICAL SPECIFICATION - minimum running length: 06 meter BS970/ EM58J, L42H35, DIA 7/8", 18% CHROMIUM 8% NICKLGENERAL SPECIFICATION - minimum running length: 06 meter BS970/ EM58J, L42H35, DIA 7/8", 18% CHROMIUM 8% NICKL	
30	DGB739 47	(FLUTE LG 2.250 INCH)	027279923788 4 / DRILL- TWIST- MORSE TAPER SK-1 (H/S/STEEL) DIA 15/64"- O/LG-5.438		15 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DGE721 95	CTLCS150 11016	534073526741 2 / CROSS (1500 X 1100 X 1.6MM)		138 / EACH/N UMBER	CROSS CTLCS15 011016					TECHNICAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
32	DGE753 55	565665	534070524611 1 / leatherite for wallpaper		650 / SQ FEET	565665					TECHNICAL SPECIFICATION - leatherite wallpaper sheetsGENERAL SPECIFICATION - leatherite wallpaper sheets	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
33	DGE721 82	CTLBS122 02003	534073526740 9 / BASE 4' (1220 X 200 X 3MM)		384 / FOOT RUN	BASE 4' CTLBS12 202003					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
34	DGE765 68		933070530065 4 / telic sheet (TRANSPARE NT sheet) THICKNESS: 0.35MM WIDTH:54 INCH LENGTH: 25-30 meter		1000 / SQ FEET	sheet					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
35	DGB754 69	BS 3628 &K0851& DEFSTAN 47-11	025470420308 8 / CLAMP HOSE TERRY BRAND SZ 2.750 TO 3.500"WD . 505"XTHK 0.038"		40 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DGB750 72	(SIM)	025770941150 4 / NUT-PLAIN- HEXAGON (BRASS) THREAD UNF SZ .375"LH . 350"		8 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DGB756 66		026259000627 4 / RAT GUARD DIAMETER OF ROPE 5-6 1/2 INCH		86 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGH760 74	BSEN 10025 GRADE S275JR	021259571072 2 / M/S ANGLE LG 6100mm, SIZE 40 X 40 X 5mm		31 / METER						TECHNICAL SPECIFICATION - BSEN 10025 of 2004 GRADE S275JR GENERAL SPECIFICATION - BSEN 10025 of 2004 GRADE S275JR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
39	DGB75668	NTER SUNK SLOT DRIVE SPEC BS1210	028659000022 6 / SCREW WOOD BRASS27 TONS/SQUARE FALT CSK SLOT IN MTS DRIVE HD 7G LG 0.750 IN		600 / DOZEN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
40	DGE72377	530300/T 41114/RCS 56000	422050508458 9 / KNIFE DIVER,S (SEAHWK/ AQUAL UNG KNIFE) WITH LEG CLASP BLADE LENGTH APPROXI. 180MM/ SEAHWK/ AQUAL UNG KNIFE		154 / EACH/NUMBER	/Cressi orca, black					TECHNICAL SPECIFICATION - BRAND: AQUA LUNG 7 1/2" POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE : BLACK CONTOURED RUBBER HANDLE. GENERAL SPECIFICATION - BRAND: AQUA LUNG 7 1/2" POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE : BLACK CONTOURED RUBBER HANDLE.	
41	DGE74505	MD231 (CROWN) /EH1504 /EH1418	444079510254 4 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIERS	3 / EACH/NUMBER	MD231 (CROWN) /EH1504/ EH1418					TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
42	DGB76103	NO DATA AVAILABLE	343971504503 2 / WET WELDING ELECTRODE UW-CS-1 (1/8"	UNDERWATER WELDING DURING SALVAGE OPS/TRAINING	1000 / PACKAGE						TECHNICAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OR 3.2 MM)	G							Vertical, Overhead Type of Arc: Medium, Moderate, Penetration <u>GENERAL SPECIFICATION - Wet Welding Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia: 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration</u>	
43	DGB74602		512079502193 2 / SPANNER ADJUSTABLE 8 INCH		12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
44	DGB74732		521079508743 2 / SCALE STEEL 12"(UK)		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
45	DGE72352	1756654	597000184200 2 / TAPE-INSULATION		105 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
46	DGE76327	0413-2184	597099923966 4 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u> <u>GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details: 10-12 in each packing</u>	
47	DGE76330	RT876-3/4-0	5970UK507293 5 / TUBING (HEAT SHRINK SLEEVE) FOR HARNESS EQUIPMENT		10 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
48	DGE72466	NO DATA AVAILABLE	041478000021 0 / INSULATING RUBBER GLOVES 309MS	MSI	5 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
49	DGE77300	NO DATA AVAILABLE	042250000002 7 / IMPROVED VERSION PVC TILES		50 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			MAROON SIZE 300X300X3MM									
50	DGE763 14	NO DATA AVAILABL E	04135000019 0 / TUBING PLASTIC TRANSPAREN T(G/USE) O/D 32MM I/D 27MM TH.2.5 MM, LENGTH (MIN) 50 METER, MATERIAL: PLASTIC GRADE-1		650 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Size Wall Thick: 2.5MM Length of Tube: 50FT O/D: 32MM I/D: 27MM Spec: 5039 PG 99 Material: Plastic Grade-1 GENERAL SPECIFICATION - Size Wall Thick: 2.5MM Length of Tube: 50FT O/D: 32MM I/D: 27MM Spec: 5039 PG 99 Material: Plastic Grade-1	
51	DGE739 57	SIZE- MERIOUS FREE SIZES	840570504642 3 / AIRCRAFT- MARSHALLER S GLOVES BRIGHTS ORANGE WASHABLE- MATERIAL	TO USED BY PERSONNE L DEPLOYED	4 / PAIR						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DGB754 58	NO DATA AVAILABL E	026550000151 7 / NAIL- STEEL- LENGTH-2-1/2- INCH		25 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DGE759 30	NO DATA AVAILABL E	933070505204 3 / PLASTIC SHEET BLACK SIZE 4.X 4.X 1/8	FOR CNS STATE BOARD	5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
54	DGE749 19		933070100331 8 / PERPEX SHEET 6MMX8FEETX 4FEET		5 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DGB757 11	NO DATA AVAILABL E	027450000013 4 / HAMMER HAND ENGINEER 4LBS 14IN		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
56	DGE754 99		047654600478 6 / GLOVES		35 / EACH/N						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LEATHER LEFT HAND LTR NO E-14927/A/845 DT 28092000		UMBER						SPECIFICATION - NO DATA AVAILABLE	
57	DGE725 12	2822-025-00051	802017101264 4 / SOFT BRUSH		15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
58	DGE763 68		9330PK512425 6 / PLASTIC COVER TRANSPARENT FOR MODLES OF 18' (SEE COMD F8)	N	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
59	DGT767 17	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	13 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 TO 14 INCH THICKNESS: 6 TO 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 TO 14 INCH THICKNESS: 6 TO 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%	
60	DGE748 56	100-65F	792099300899 7 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	470 / EACH/NUMBER	NO DATA AVAILAB LE		UK		MEMO HCG/MS D/03/336 DT 2/7/08	TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy). GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Material: 100% polyester made with continuous filament yarn for lowest possible particle generation. Type: Knitted Pattern: Line structure Weight: (250-270) GSM (Calculated with the help of GSN cutting and measuring scale). Colour: White, Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gelbo test method). Cutting: Laser cut sealed edges (+/- 3mm accuracy).	
61	DGE75058	GGG-H-142	8415009351901 / HELMAT, SAFETY	HELMET SFTYCONSTR UCTION TY	35 / EACH/NUMBER			FEDERAL SPECIFICATION CAGE CODE 81348		FEDERAL SPECIFICATION CAGE CODE 81348	TECHNICAL SPECIFICATION - GARMET SIZE 6-3/4, INCHES ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000, COLOUR BLUE MAIN BODY GENERAL SPECIFICATION - GARMET SIZE 6-3/4, INCHES ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000, COLOUR BLUE MAIN BODY	
62	DGE76267	P1000C	5350705160645 / WATER PROOF PAPER 166 SIZE 1000MM	WTER PROOF PAPER	10 / SHEET			LOCAL SOURCE: PRIME BUSINESS SYNDICATE SHOP#2. GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969, 32624690) FAX: 32623828		PRIME BUSINESS SYNDICATE	TECHNICAL SPECIFICATION - LOCAL SOURCE: PRIME BUSINESS SYNDICATE SHOP#2. GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969, 32624690) FAX: 32623828 GENERAL SPECIFICATION - LOCAL SOURCE: PRIME BUSINESS SYNDICATE SHOP#2. GROUND FLOOR ABID CHAMBER SHAH0E-LIAQUAT KARACHI (TEL: 32213969, 32624690) FAX: 32623828	
63	DGE76662	GGG-H-142	8415TY5202563 / SAFETY HELMET YELLOW	BV	29 / EACH/NUMBER			VHKMHMN		-	TECHNICAL SPECIFICATION - GARMET SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000 GENERAL SPECIFICATION - GARMET SIZE 6-3/4 TO 7-1/2; ELECTRICAL SHOCK RESISTANCE IN VOLTS 20000	
64	DGH78105	LCKHB1081182B	3020705202580 / BEAM PR	RACKS	30 / EACH/NUMBER			OFFICE: 3RD FLOOR 83 C, PHASE2, EXT, MAIN		HABIB & SONS	TECHNICAL SPECIFICATION - Profile: Step Beam Size: 118mm x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			2740X240		UMBER			NATIONAL HIGHWAY, DEFENCE KARACHI 021-5388726			50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5GENERAL SPECIFICATION _Profile: Step Beam Size: 118mm x 50mm Surface Finish: Ral 2004/ Powder Coated Material: SS400 strength:245mpa16mm Tensile strength:400-510mpa Locking pin: l- type x2 Load capacity/level:2000kg Lugs/nut bolt:4 Load safety factor: 01:01.5	
65	DGH781 04	HRKT4012 - SEW/LCK GI100304 H	494070520260 4 / TRAY Size 40"x12"x1" (SET OF 09 TRAYS)	RACKS	15 / SET			OFFICE 3RD FLOOR 83-C, PHASE-II EXTENSION, MAIN NATIONAL HIJGHWAY, DEFENCE, KARACHI		HABIB & SONS	TECHNICAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MMGENERAL SPECIFICATION - Profile: Type-L, MATERIAL Galvanized, TRAY SIZE: 40" X12 THICKNESS 1.5 MM	
66	DGE772 41	30DB	8415TY520257 5 / 3M PELTOR OPTIME EARMUFFS 3M PELTER H 10A NRR 30DB		40 / EACH/N UMBER	-SAFETY		JUOOTG		PAK	TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
67	DGB742 71		027750277003 3 / SPANNER 09X11MM A/F		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DGB747 31		027750277150 6 / SPANNER D.E D.J BSW 0.25X0.3125"		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DGB757 29		027779910597 0 / SPANNER RING DOUBLE ENDED 69X75 A/F 1/100 THS OF AN IN		4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
70	DGE750 56	0559- 15270	055979444490 0 / INSULATION-		65 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SLEEVING-ELECTRICAL-5.0MM - THICK.0.500/0.750MM								AVAILABLE	
71	DGE754 91	NO DATA AVAILABL E	047659943474 3 / TUFF GRADE 1" PAINT BRUSH	HANGAR DOOR	36 / EACH/N UMBER						TECHNICAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch GENERAL SPECIFICATION - 1. Bristle material: China bristle 2. Bristle colour: White 3. Bristle width: 25mm 4. Bristle thickness: 10mm 5. Handle material: Popular wood spec: bs2992 stock thickness:0.625 inch exposed length. 2 inch	
72	DGE761 29		055979001502 6 / SYNTHETIC- RESIN- BONDED- PAPER-SHEET		1 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DGE755 09	NO DATA AVAILABL E	041359923879 0 / TUBING RUBBER NATURAL INTERNAL DIA 1.00" HARDNESS RATING 42-50 DEGREE WALL THICKNESS 0.313"		12 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DGE762 68	NIL	047659943055 8 / BRUSH, VARNISH, TYNEX, FLAT SQUARE EDGE WD:3", STOCK THICKNESS		117 / EACH/N UMBER						TECHNICAL SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			0.875 INCH, EXPOSED LENGTH 3 INCH.								SPECIFICATION - bs 2992TABLE8, MATERIAL: POLYSTER / NYLON SIZE: 3 INCHES HANDLE TYPE: BEAVERTAIL MAKE/BRAND: CORONA/PURDY DIMENSIONS: 1x3x14 INCHES ITEM WEIGHT: 6.1 OUNCES	
75	DGE750 46	C-268	047659943055 9 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		140 / EACH/N UMBER						TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3.25 inch specs bs2992 table 8	
76	DGE724 70		041559923142 7 / GLASS TUBING ROUND LENGTH 20" O. DIA 5/8"		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DGB742 64	NO DATA AVAILABL E	027770000347 7 / SPANNER OPEN JAW ADJ 0.50" X 0.57"		22 / EACH/N UMBER						TECHNICAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy SteelGENERAL SPECIFICATION - Brand: Bahco Overall Length: 257 mm Wrench type: Adjustable Spanner Jaw Capacity: 33 mm Handle Type : Plastic/ Steel Material: Alloy Steel	
78	DGB759 58		028359571144 8 / ROD NAVAL BRASS RD DIA 1-1/8,	SERVICE PUMP	2 / METER						TECHNICAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M)GENERAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF1998 GRADE CW719R (M)	
79	DGB759 67		028359571145 9 / ROD NAVAL BRASS RD DIA.2.50 INCH WT PER MTR 27.49 KG		3 / METER						TECHNICAL SPECIFICATION - BS EN-12163 DESIGNATION: CW- 719R, R-340 SYMBOL: CU zN 39 SN 1GENERAL SPECIFICATION - BS EN-12163 DESIGNATION: CW- 719R, R-340 SYMBOL: CU zN 39 SN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											1	
80	DGE755 72	0413-4603	041359923891 5 / SHEET RUBBER SOLID BLACK, LENGTH: 06- FOOT, WIDTH: 48-INCH, THICKNESS: 0.125 INCH.		15 / KILOGR AMME						TECHNICAL SPECIFICATION - Approx. wt per sq ft (Lbs) 1, Spec: BS-1154 of 1992 Compound Z70, T259 BR-320-D of 1975 GENERAL SPECIFICATION - Approx. wt per sq ft (Lbs) 1, Spec: BS-1154 of 1992 Compound Z70, T259 BR-320-D of 1975	
81	DGE724 58	0414-2846	041459923097 5 / GASKET COPPER & ASBESTOS I. DIA 33/64" E. DIA 7/8"THICK 3/32".		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGE724 16	T-8802	043472000000 5 / DIVING GOGGLES WITH SAFETY GLASS DOUBLE SEALING FRAME.	PL-70	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	DGE724 67		041559923140 8 / PLASTIC SHEET METHYL METHACRYLA TE TRANSPAREN T 48"X36"X0. 0625		16 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DGE732 17		041559923141 2 / SHEET PLASTIC METHYL METHACRYLA TE PLAIN TRANSPAREN T L X W X THIC 48"X48"X0.		215 / SHEET						TECHNICAL SPECIFICATION - Manfr/Tech.Sponcer Code reference: DTD 5592 GENERAL SPECIFICATION - Manfr/Tech. Sponcer Code reference:DTD 5592	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			250"									
85	SGB398 25	NO DATA AVAILABL E	026759923510 0 / ELBOW ROUND BLACK 1.50 INCH		250 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - ID: 1.5 INCH OD: 48.3 MM WALL THICKNESS: 3.7 MM GRADE. ASTM 106 GRADE B. SCHEDULE: 40 Material: mild steel Specs: (galvanized) BS 1740/71,1387, grade: corrosion resisting ferrous alloy Nominal bore= 40mm/ 1.50" without internal thread, wall thickness: 6mm, external dia: 52mm Running length: 5.5 inch Origin: Pakistan / China</p> <p>GENERAL SPECIFICATION - ID: 1.5 INCH OD: 48.3 MM WALL THICKNESS: 3.7 MM GRADE. ASTM 106 GRADE B. SCHEDULE:40 Material: mild steel Specs:(galvanized) BS 1740/71, 1387, grade: corrosion resisting ferrous alloy Nominal bore= 40mm/ 1.50" without internal thread, wall thickness: 6mm, external dia: 52mm Running length: 5.5 inch Origin: Pakistan / China</p>	
86	DGB757 30	NO DATA AVAILABL E	027379910575 8 / BLADE HAND HACKSAW LTS FLEXIBLE NOMINAL LG 12IN TEETH 24		54 / DOZEN						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
87	DGB739 46	THT53321	027379910589 7 / CUTTER PIPE HAND OPERATED TYPE WHEEL 3-32MM CUTTING RANGE		2 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - Cutting Range: 1-3 inch (25-80mm) OLD RANGE: 1.5TO03IN</p> <p>GENERAL SPECIFICATION - Cutting Range: 1- 3 inch (25-80mm) OLD RANGE: 1.5 TO03IN</p>	
88	DGB754 65	BS 1421	027570910547 4 / PICK HEAD DIGGING TYPE CHISEL AND POINT		10 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</p> <p>GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN. SPECS	Dimension
			07LBS EYE 3" X3"									
89	DGB747 44		0274799104717 / HAMMER HAND TINMAN ROUND AND SQUARE 1.25 LBS LG 12.00 IN		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
90	DGB742 75	1B1783	0275599105514 / PLIERS NOSE FLATE 06" SINGLE JOINT, TO SPEC. BS 3087 TABLE 6	GENERAL USE (BR 320 D/76)	38 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 3087 GENERAL SPECIFICATION - BS 3087	
91	DGB754 71		0271799101887 / TAP THREAD CUTTING HS BSW P/S16. 0TPI0.375X1. 240X0.294X2. 937"		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGB754 66		0276799105870 / SCREW DRIVER RATCH, DOUBLE SPIRAL, AUTO RETURN, 250MM LG, 3 BITS		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China GENERAL SPECIFICATION - Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China	
93	DGB747 60		0277799106237 / SPANNER OPEN JAW FIXED D.E BS 0.500X0.563 W 0.431X0.500		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Double Open Ended Spanner Double Open Ended Spanner Chrome Plated 150 angle, Size: 14x15 GENERAL SPECIFICATION - Double Open Ended Spanner Chrome Plated 150 angle, Size: 14x15	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
94	DGB757 12	NO DATA AVAILABL E	028559423325 5 / PAD-LOCK- BRASS-1.50 INCH WITH 02 KEYS		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DGB754 57	NO DATA AVAILABL E	026550000148 4 / NAIL- STEEL- LENGTH-2- INCH		26 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DGB742 63		027179910172 7 / TAP THREAD CUTTING HS BSF T/S20. 0TPI0.373X1. 250X0.293X2. 937"		20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DGP782 33	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN					TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel @ Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAr or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.

98	DGP78224	NO DATA AVAILAB LE	0051PK506118 7 / BINDER SMALL SIZE 8	FOR STATIONERY.	6 / EACH/ UMBER						TECHNICAL SPECIFICATION - Required Size of title cover for printing of Hazard Identification and Risk Management (HIRM) Guide Book is 9.25 x 6 inches Cover binder small without steel clip √ Size 10.30 x 8 inches √ Best quality rexine with golden foil printing (Data for printing of title will be provided by PNCPP A. Complete item / store description: Cover binder small without steel clip Size of cover binder: 10.30 x 8 inches Quality / Thickness of straw board with rexine: 4mm Golden steel corners at the edges of the cover binders Color of rexine: Black Best quality imported rexine with golden foil printing (Data for printing of title	
----	----------	-----------------------	--	--------------------	-----------------------	--	--	--	--	--	---	--

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>will be provided by PN Central Printing Press. NAVCOM: 56050 / 021- 48506050) b. Detailed Specifications / Technical Data / Testing / Acceptance Criteria be mentioned As Above Sample has been provided. Supply will be accepted according to the approved sample. <u>GENERAL SPECIFICATION</u> - Required Size of title cover for printing of Hazard Identification and Risk Management (HIRM) Guide Book is 9.25 x 6 inches Cover binder small without steel clip √ Size 10.30 x 8 inches √ Best quality rexine with golden foil printing (Data for printing of title will be provided by PNCPP A. Complete item / store description: Cover binder small without steel clip Size of cover binder: 10.30 x 8 inches Quality / Thickness of straw board with rexine: 4mm Golden steel corners at the edges of the cover binders Color of rexine: Black Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021- 48506050) b. Detailed Specifications / Technical Data / Testing / Acceptance Criteria be mentioned As Above Sample has been provided. Supply will be accepted according to the approved sample.</p>	
99	DGP782 14	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: i5)		3 / SET	CORE I5 12 GEN					<p><u>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</u> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>(preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.</p>	
100	DGP781 86	CORE I5	702570524609		3 / SET	CORE I5 12 GEN					TECHNICAL SPECIFICATION -	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025	300000.00
Bank A/c No PK17HABB0004540013100701	300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To

LP Division

2. LAO (LAO (NAVY) NSD KARACHI)