

TENDER BULLETIN

TENDER CLOSING/OPENING DATE 28/01/2025

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
1	SNM62500	100-3880	2815015067155 / PUSHROD-VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	16 / EACH/NUMBER	NA	CATERPILLAR, INC. 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	TECHNICAL SPECIFICATION - 0GENERAL SPECIFICATION - 0
2	SNM64505	057-6987	2910016114223 / KIT-ELEMENT (FUEL FILLTER)	DG CATTERPELLER	10 / EACH/NUMBER	C2-2 DE18E3/DE 22E2	CATTERPELLER USA CO 701 WATERFOLD WAY SIUT 200 MIAMI USA CONTACT NO 305-476-6800 FAX NO 305-476-6801	TECHNICAL SPECIFICATION - FUEL FILLTER USE FOR PROVISION OF CLEAN FUEL TO DG FOR SMOOTH RUNNING OF ENGINEGENERAL SPECIFICATION - FUEL FILLTER USE FOR PROVISION OF CLEAN FUEL TO DG FOR SMOOTH RUNNING OF ENGINE
3	DNQ69832	HZ-PN-11	4720785177661 / HOZE 50MM,20M LONG WITH CHINESE CONNECTOR	FIXED FIREFIGHTING	10 / EACH/NUMBER		TIANBU INDUSTRY AREA, HAIMEN CITY,JIANGSU PROVINCE, P.R.CHINA TEL:0086-513-82330788,82330508 EMAIL:nthzcb@nthzcb.com	TECHNICAL SPECIFICATION - FIRE HOZE 50mm DIAMETER AND 20m LONG WITH STORZ50 FIRE HOZE COUPLINGGENERAL SPECIFICATION - FIRE HOZE 50mm DIAMETER AND 20m LONG WITH STORZ50 FIRE HOZE COUPLING
4	DNM69529	5110	5963715219687 / AUTOMATIC ENGINE CONTROL MODULE	DG 750 KVA DETROIT 92 SERIES 8183-7408 USA	1 / EACH/NUMBER	5110	DEEP SEA ELECTRONICS INC. 3230 WILLIAMS AVENUE ROCKFORD, ILLINOIS 61101-2688, U.S.A.alabapower@yahoo.com PHONE:+1(815)316-8708. FAX: +(815)316-8708. EMAIL: dsesales@deepseausa.com web: www.	TECHNICAL SPECIFICATION - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 18 Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60HzGENERAL SPECIFICATION - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 18 Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60Hz
	DPC72031	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/b)	DECK COVERING FOR CONCRETE SURFACE	20 / BAG		OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS. GENERAL SPECIFICATION - OEM ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.	
6	DPC68731	SIKAFLEX-290	8030795167621 / SIKA-FLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER-290DC	5 / EACH/NUMBER		SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 1BQ UK TELL:01707 394444, FAX: 01707 329129	TECHNICAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 1BQ UK TELL:01707 394444, FAX: 01707 329129GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 1BQ UK TELL:01707 394444, FAX: 01707 329129
7	DNM70919	225-8287	5330015277573 / GASKET	CAT GENERATOR CAT7.1 USA	2 / SHEET	CAT7.1	CATERPILLAR INC./DBA CATERPILLAR/DIV GOVERNMENTAL AND DEFENSE/PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353	TECHNICAL SPECIFICATION - ITEM USED IN CAT DG engine side for maintenance GENERAL SPECIFICATION - ITEM USED IN CAT DG engine side for maintenance
8	DNM71713	443-3226	4320715219506 / PUMP AS - FUEL INJECTION	CAT GENERATOR CAT7.1 USA	1 / UNIT	CAT7.1	CATERPILLAR INC./DBA CATERPILLAR/DIV GOVERNMENTAL AND DEFENSE/PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353	TECHNICAL SPECIFICATION - ITEM USED IN CAT DG in fuel system GENERAL SPECIFICATION - ITEM USED IN CAT DG in fuel system

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
9	DNM5956 9	85484	4330705172629 / SEPARATOR CARTRIDGE LPAC ALPINE	LPAC	3 / EACH/NU MBER	NK200	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	<u>TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102</u> <u>GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102</u>
10	DNM7091 6	277-3013	5330015878825 / SEAL,PLAIN ENCASED	CAT GENERATOR CAT7.1 USA	2 / UNIT	CAT7.1	CATERPILLAR INC.IDBA CATERPILLAR/DIV GOVERNMENTAL AND DEFENSE/PRODUCTS, 14009 OLD GALENA RD TC-A, MOSSVILLE, UNITED STATES, TEL: 3095782353	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR MAINTENANCE OF CATERPILLAR DGGENERAL SPECIFICATION - ITEM REQUIRED FOR MAINTENANCE OF CATERPILLAR DG</u>
11	DNM7094 3	1001434	5331715231067 / 7E129 O RING BUNA (PKG 3)	METAL 16E SPRAY GUN (ZINC)	2 / EACH/NU MBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163362414	<u>TECHNICAL SPECIFICATION - O RING BUNA (PKG 3)</u> <u>GENERAL SPECIFICATION - O RING BUNA (PKG 3)</u>
12	SNM70214 3	Y03/0003	5330795170097 / SEAL INJECTOR	PERKINS DIESEL GENERATOR 4006- 23TAG3A	32 / EACH/NU MBER	4006- 23TAG3A	PETER BOROUGH PE 15NA UNITED KINGDOM ENGLAND	<u>TECHNICAL SPECIFICATION - oem: perkins dg USED IN FUEL INJECTION SYSTEM</u> <u>GENERAL SPECIFICATION - oem: perkins dg USED IN FUEL INJECTION SYSTEM</u>
13	DNM7194 1	131323	6007715211154 / FILTER ELEMENT, 10 MICRON	SELF PROPELLED ARTICULATING BOOM	2 / EACH/NU MBER	ZX-135/70	GENIE UNITED STATE 18340 NE 76TH STREET REDMOND, WASHINGTON 98073- 9730 TELE+1(425)881- 1800 TOLL FREE IN USA/CANADA +1(800)- 536-1800 FAX+1(425)883-3475 www.genielift.com	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>
14	DNM7194 0	60857	6007715211157 / FILTER,ELEMENT, BETA(5)=1000	SELF PROPELLED ARTICULATING BOOM	2 / EACH/NU MBER	ZX-135/70	GENIE UNITED STATE 18340 NE 76TH STREET REDMOND, WASHINGTON 98073- 9730 TELE+1(425)881- 1800 TOLL FREE IN USA/CANADA +1(800)- 536-1800 FAX+1(425)883-3475 www.genielift.com	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>
15	DNM7193 9	101950	6007715211159 / FILTER ELEMENT, 10 MICRON	SELF PROPELLED ARTICULATING BOOM	2 / EACH/NU MBER	ZX-135/70	GENIE UNITED STATE 18340 NE 76TH STREET REDMOND, WASHINGTON 98073- 9730 TELE+1(425)881- 1800 TOLL FREE IN USA/CANADA +1(800)- 536-1800 FAX+1(425)883-3475 www.genielift.com	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>
16	DNM7194 2	60559	2990715210827 / BREATHER, RESERVOIR 3 MICRON	SELF PROPELLED ARTICULATING BOOM	2 / EACH/NU MBER	ZX-135/70	GENIE UNITED STATE 18340 NE 76TH STREET REDMOND, WASHINGTON 98073- 9730 TELE+1(425)881- 1800 TOLL FREE IN USA/CANADA +1(800)- 536-1800 FAX+1(425)883-3475 www.genielift.com	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>
17	DPC62753	H-300 HUX	8040735140710 / HARDNER (SET OF 2X1KG BOTTLE)	AC COMPRESSOR KALMAT GWADER	25 / SET	NO DATA AVAILABLE	00	<u>TECHNICAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner 6, Appearance, Brown , Flash point, 2000></u> <u>GENERAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 2000></u>
18	DNM7465 0	N7698	2940010820096 / FILTER ELEMENT(A/SUC FILTER)	RECOMPRESSION CHAMBER OR HPAC- K28.0	1 / EACH/NU MBER	N7698	GR	<u>TECHNICAL SPECIFICATION - OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY: M/S ALPINE INDUSTRIALCON(PVT)LTD 305/2 G.T. ROAD BAGHANPURA LAHORE PAKISTAN TEL:+92 42 6852313 FAX:+92 42 3674655</u> <u>GENERAL SPECIFICATION - OEM / BRAND : MS ALPINE SOURCE OF AVAILABILITY: M/S ALPINE INDUSTRIALCON(PVT)LTD 305/2 G.T. ROAD BAGHANPURA LAHORE PAKISTAN TEL:+92 42 6852313 FAX:+92 42 3674655</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	MANUF ADD	TECH / GEN SPECS
19	DNM6417 1	874-090	5330725141391 / GASKET(B/W VALVE HEAD CYLINDER)	RECOMPRESSION CHAMBER	1 / EACH/NUMBER	NO DATA AVAILABLE	GR	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: M/S ALPINE INDUSTRIALCON(PVT)LTD 305/2 G.T. ROAD BAGHANPURA LAHORE PAKISTAN TEL:+92 42 6852313 FAX:+92 42 3674655 GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: M/S ALPINE INDUSTRIALCON(PVT)LTD 305/2 G.T. ROAD BAGHANPURA LAHORE PAKISTAN TEL:+92 42 6852313 FAX:+92 42 3674655
20	SNM71974	90680300 40000	5133735225042 / RF 100 DIVER (4-FLUTE)	NSN#340872518689 0 CNC VERTICAL MACHINING CENTER	10 / EACH/NUMBER	FLUTE	Guhring, Inc. Main Office 1445 Commerce Avenue Brookfield, WI 53045 Tel (262) 784-8730 (800) 776-8170 Fax (262) 784-9086	TECHNICAL SPECIFICATION - MAKE: GUHRING INC GERMANY OUTSIDE DIA: 4MM. LENGTH OF CUT: 15MM. SHANK DIA: 6MM, OVERALL LENGTH : 54 MM. NOS OF FLUTES: 4 GENERAL SPECIFICATION - MAKE: GUHRING INC GERMANY OUTSIDE DIA: 4MM. LENGTH OF CUT: 15MM. SHANK DIA: 6MM, OVERALL LENGTH : 54 MM. NOS OF FLUTES : 4.
21	DNM7094 5	1028532	5331715231208 / K 180 O RING BUJA (PKG OF 3)	16E SPRAY GUN	4 / EACH/NUMBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	TECHNICAL SPECIFICATION - OEM & MAKE: CLEMCO US GENERAL SPECIFICATION - OEM & MAKE: CLEMCO USA
22	DNM7086 6	3937743 / 3912020 / 3924540 / LF3868	2940014971469 / FILTER ELEMENT,FLUID / LUBRICATING OIL FILTER CARTRIDGE	CUMMINS QSX15	2 / EACH/NUMBER	6BT5.9G1	Registered Office Cummins Ltd 49-51 Gresham Road, Staines, Middlesex TW18 2BD, England Registration 573951 England	TECHNICAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR GENERAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR
23	DNM7177 6	4093730/ FS1280	4330795193201 / SEPARATOR FUEL WATER	CUMMINS D/G 6BTAA5.9-G5	1 / EACH/NUMBER	6BTAA5.9-G5	CUMMINS UK	TECHNICAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTAN GENERAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTAN
24	DNQ74950	484748 ABN.	4730014355106 / REPAIR KIT,PIPE,EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL PIPE REPAIR KIT.	2 / KIT		OEM:3355 WEST ALABAMA ST STE 110HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM c IT PIPE REPAIR SYSTEM	TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM
25	DNQ73715	06973009	6140FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	2 / EACH/NUMBER	583210B.0 006	KINGSWAY DUNMURRY BELFAST ?RLANDA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
26	DNQ73714	06317009	5640FT1019337 / Termal Protection Aid (TPA)	Emergency Pack - 1	6 / EACH/NUMBER	583210B.0 006	KINGSWAY DUNMURRY BELFAST ?RLANDA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
27	DPK66976	71010010 02	9150736232473 / REFRIGERATION LUB OIL DHB-002 (19 Liters Packing)	HARD FORD AC COMPRESSOR.	19 / LITER	DHB-002	DUNHAM-BUSH INDUSTRIES SND.BHD. LOT 5755- 6,KIDMAL INDUSTRIAL PARK,BUKIT ANGKAT,43000 KAJANG,SELANGOR PH:+603-86249000 FAX:+603-86395020	TECHNICAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT (ASTM D-92,COC)-30 C GENERAL SPECIFICATION - FLASH POINT (ASTM D-92,COC)190C,MELTING POINT (ASTM D-92,COC)-30 C
28	SNM70862	2656F823	2915795171906 / FUEL FILTER	60 KVA PERKINS	4 / EACH/NUMBER	DK 51280	PERKINS UK	TECHNICAL SPECIFICATION - FUEL SYSTEM GENERAL SPECIFICATION - FUEL SYSTEM

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
29	SNM70430	3P-0647/2284947	5331003675650 / SEAL-O-RING	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	6 / EACH/NUMBER	135 KVA (C7.1)	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0910 COUNTRY USA	TECHNICAL SPECIFICATION - MAKE: CATERPILLAR AUTHORIZED DEALER M/S ALLIED GENERAL SPECIFICATION - MAKE: CATERPILLAR AUTHORIZED DEALER M/S ALLIED
30	DNM71025	380-1882	6625716228830 / SENSOR GP-PRESSURE (ENGINE OIL)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
31	DNM70866	3937743 / 3912020 / 3924540 / LF3959	2940014971469 / FILTER ELEMENT,FLUID / LUBRICATING OIL FILTER CARTRIDGE	CUMMINS QSX15	2 / EACH/NUMBER	6BT5.9G1	EAST ASIA CUMMINS POWER GENERATION NO.2,RONGCHANG EAST STREET,BEIJING ECONOMIC-TECHNOLOGICAL DEVELOP AREA BEIJING CHINA	TECHNICAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,8 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR GENERAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR
32	DNM74971	SEV551F/4	2940993807131 / FILTER ELEMENT, INTAKE AIR CL (MAIN AIR FILTER)	MOBILE DG	4 / EACH/NUMBER	2806A-E18TAG2/JGBF5119U16285U	PERKINS ENGINES CO LTD, FRANK PERKINS WAY, EASTFIELD, PETERBOROUGH, CAMBS, UK PH: 01733 582386 FAX: 01733 582947	TECHNICAL SPECIFICATION - Make: Perkins 2010 (UK) Model/ Serial No: 2806A-E18TAG2/JGBF5119U16285U GENERAL SPECIFICATION - Make: Perkins 2010 (UK) Model/ Serial No: 2806A-E18TAG2/JGBF5119U16285U
33	DPC71446	3315459	6860013871529 / SUPPLEMENTAL COOLANT ADDITIVES (DCA 4 coolant) OEM MS FLEETGUARD) Packing = 3.785 LTRs	DIG	1656 / LITER		FLEETGUARD INC A CUMMINS CO 2931 ELM HILL PIKE NASHVILLE TN UNITED STATES 37214-3719 615-367-0040 615-399-3850 PATT VIDE KARSAZ LTR NO:KAR/ARC DATED 12 JAN 2011	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
34	DNQ71135	5F CLASS (F EXTINGUISHER)	4210705212244 / 02 LTRS WET CHEMICAL 5F P/ABLE FIRE EXTINGUISHER	DC &FF	23 / EACH/NUMBER	BA25F.	PRIME BUSINESS SYNDICATE SHAHRA-E-LIAQUAT,KARACHI PAKISTAN PHONE: +92-21-32624690, 32213969 FAX: +92-21-32623828 E-MAIL: INFO@PRIME-FIRE.COM SUITE NO 2, GROUND FLOOR, ABID CHAMBER,	TECHNICAL SPECIFICATION - WORKING PRESSURE 10 BAR SPECS ATTACH Elite Fire and Safety Solutions Plot no 79-C 2nd Floor Suite No 4, Main Khayaban eJami, DHA Phase VII Karachi PH: 0213586699 PH: 042 35311453 GENERAL SPECIFICATION - WORKING PRESSURE 10 BAR SPECS ATTACH Elite Fire and Safety Solutions Plot no 79-C 2nd Floor Suite No 4, Main Khayaban e Jami, DHA Phase VII Karachi PH: 0213586699 PH: 042 35311453
35	DNQ71198	5F CLASS (F EXTINGUISHER)	4210705212244 / 02 LTRS WET CHEMICAL 5F P/ABLE FIRE EXTINGUISHER	DC &FF	8 / EACH/NUMBER	BA25F.	PRIME BUSINESS SYNDICATE SUITE NO 2, GROUND FLOOR, ABID CHAMBER, SHAHRA-E-LIAQUAT, KARACHI PAKISTAN PHONE: +92-21-32624690, 32213969 FAX: +92-21-32623828 E-MAIL: INFO@PRIME-FIRE.COM	TECHNICAL SPECIFICATION - WORKING PRESSURE 10 BAR SPECS ATTACH Elite Fire and Safety Solutions Plot no 79-C 2nd Floor Suite No 4, Main Khayaban e Jami, DHA Phase VII Karachi PH: 0213586699 PH: 042 35311453 GENERAL SPECIFICATION - WORKING PRESSURE 10 BAR SPECS ATTACH Elite Fire and Safety Solutions Plot no 79-C 2nd Floor Suite No 4, Main Khayaban e Jami, DHA Phase VII Karachi PH: 0213586699 PH: 042 35311453
38	DNM70866	3937743 / 3912020 / 3924540 / LF3959	2940014971469 / FILTER ELEMENT,FLUID / LUBRICATING OIL FILTER CARTRIDGE	CUMMINS QSX15	2 / EACH/NUMBER	6BT5.9G1	WWW.CUMMINS.COM CUMMINS INC. LTD 49-51 Gresham Road Staines,Middlex TW18 2BD ENGLAND Box 3005	TECHNICAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,8 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR GENERAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
37	DNM71101	FG-K2-002-KW	6630014989908 / TBN	LUB OIL TESTING KIT KITTIWAKE	4 / LITER	NO DATA AVAILABLE	UK	<u>TECHNICAL SPECIFICATION - -GENERAL SPECIFICATION - -</u>
38	DNM71950	151-7737	2940015368368 / FILTER ELEMENT,INTAKE AIR CLEANER	caterpillar C-13 USA	2 / EACH/NUMBER	C-13	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLLinois 61552 USA	<u>TECHNICAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u> <u>GENERAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u>
39	DNM74973	151-7737	2940015368368 / FILTER ELEMENT,INTAKE AIR CLEANER	caterpillar C-13 USA	2 / EACH/NUMBER	C-13	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLLinois 61552 USA	<u>TECHNICAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u> <u>GENERAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u>
40	SNM70861	419-8702	3030715223058 / BELT DRIVE	caterpillar DG C-13 USA	4 / EACH/NUMBER	C-13	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLLinois 61552	<u>TECHNICAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u> <u>GENERAL SPECIFICATION - FOR OPERATIONAL REQUIREMENT</u>
41	DNM74972	CH10929	2940795160207 / LUB OIL FILTER	DIESEL GENERATOR	4 / EACH/NUMBER	2806-E14TAG3	PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND	<u>TECHNICAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND</u> <u>GENERAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 1 5NA ENGLAND</u>
42	DPC70614	CON-EDDC-1PP1-P30	8010705204660 / EZIKLEAN DE-GREASER, CARBON AND SURFACE CLEANER CO	KACRHER MACHINE	50 / LITER	1PP1	HEAD OFFICE: NURISTAA B BUILDING NO 85, BLOCK DD CCA, PHASE 4, DHA LAHORE PH.+92 322-388-888-2 www.nuristaa.com E-mail:sales@nuristaa.com	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marbale ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR all metal surfaces (ferrous and no ferrous) stainless steel surface brass and chrome surface, glass surface, marbale ceramic, procelain, plastic and wooden floor, kitchen equipment, plastic, rubber and leather surface</u>
43	SNM56548	067-6095	2815795229656 / ROD	33KVA CATER PILLER DG DEO33EO UK	12 / EACH/NUMBER	DEO33EO	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	<u>TECHNICAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel</u> <u>GENERAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel</u>
44	DPC61199	KBA402	8010795221375 / INTERGARD 403 (ALUMINIUM GREY)	WATER BALLAST TANKS KBA402 UK	100 / LITER	KBA402	International Paint Pvt Ltd,STONEYGATE LANE, FELLING,GATESHEAD, UK. Ph.01914696111	<u>TECHNICAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET</u> <u>GENERAL SPECIFICATION - TECHNICAL DETAILS INCLUDED IN DATA SHEET</u>
45	DNQ69378	SOLO A10-001	1290735226270 / SOLO A10 150ML (SMOKE DETECTOR TESTER)	SMOKE DETECTOR	2 / EACH/NUMBER	SOLO A10	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	<u>TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u> <u>GENERAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u>
46	DNQ68644	SOLO A10-001	1290735226270 / SOLO A10 150ML (SMOKE DETECTOR TESTER)	SMOKE DETECTOR	4 / EACH/NUMBER	SOLO A10	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	<u>TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u> <u>GENERAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION</u>
47	SNM67788	234-0387	2910795230156 / NOZZLE	33KVA CATER PILLER DG DEO33EO UK	3 / EACH/NUMBER	DEO33EO	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	<u>TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOT SET</u> <u>GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOT SET</u>
48	DNM71944	289-2012	2920795229504 / ALTERNATOR GP - CHARGING	33KVA CATER PILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	<u>TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOT SET</u> <u>GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOT SET</u>
49	DNM73074	3583963/21407026	3030332067804 / BELT,POSITIVE DRIVE(COMPRESSOR)	MAIN ENGINE VOLVO PENTA(NAVY OR)	1 / EACH/NUMBER	NO DATA AVAILABLE	33	<u>TECHNICAL SPECIFICATION - -GENERAL SPECIFICATION - -</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
50	DNM7094 4	1004714	5331715230223 / O RING BLAKCK VITON (PKG 2)	16E SPRAY GUN	3 / EACH/NUMBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	TECHNICAL SPECIFICATION - O Ring Blcak viton (pkg 2) GENERAL SPECIFICATION - O Ring Blcak viton (pkg 2)
51	DPK67511	R 141b	6810715225084 / OIL FLUSHING AGENT R 141B	MAIN AC	28 / KILOGRAMME	R 141b	COMSTAR INTERNATIONAL INC 20-45 128TH STREET COLLEGE POINT, NY 11356 +1 (800) 328-0142 USA www.comstarproducts.com	TECHNICAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing agent GENERAL SPECIFICATION - Transport package: Disposable cylinder RS-141b oil flushing agent
52	SPK58312	SAE 90 (80W90)	9150251145135 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	60 / LITER	NO DATA AVAILABLE	US	TECHNICAL SPECIFICATION - SAE 90 (80W90) GENERAL SPECIFICATION - SAE 90 (80W90)
53	SNM51624	2WB250-25	4810785195851 / SOLENOID VALVE	FIRE MAIN SYSTEM	1 / EACH/NUMBER	2WB250-25	YUEQING RIGHTEIGHT PNEAMATIC CO LTD CHINA	TECHNICAL SPECIFICATION - Valve Body Material: Brass Function: 2/2 Way Normally Closed Port Size: 1", DN25 Voltage: AC110V, AC220V, DC24V, DC12V Action Type: Semi Direct Operated Orifice Size: 25mm Fluid Temperature: -5°C - +80°C Diaphragm Material: NBR, Viton, EPDM Working Pressure: 0-7 Bar Medium: Water, Oil, Gas, Air SOLENOID VALVE DIA 1 INCH ,OPERATED BY 220 V AC SUPPLY INSTALLED IN FIREMAIN MAGAZINE SPRINKLING SYSTEM GENERAL SPECIFICATION - Valve Body Material: Brass Function: 2/2 Way Normally Closed Port Size: 1", DN25 Voltage: AC110V, AC220V, DC24V, DC12V Action Type: Semi Direct Operated Orifice Size: 25mm Fluid Temperature: -5°C - +80°C Diaphragm Material: NBR, Viton, EPDM Working Pressure: 0-7 Bar Medium: Water, Oil, Gas, Air SOLENOID VALVE DIA 1 INCH ,OPERATED BY 220 V AC SUPPLY INSTALLED IN FIREMAIN MAGAZINE SPRINKLING SYSTEM
54	DPC67226	PILOT-II	8010795171839 / MAMMUT PRIMER WHITE	Tall ship	40 / LITER		Jotun Paints (Europe) Ltd, Stather Road Flixborough, Southorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDS.Jotun@jotun.com	TECHNICAL SPECIFICATION - undercoat primer white GENERAL SPECIFICATION - undercoat primer white
55	DNH63137	N/A	5410706232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/NUMBER	LOCAL	ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	TECHNICAL SPECIFICATION - Item Specification : a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2'x2' False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure GENERAL SPECIFICATION - Item Specification : a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2'x2' False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
56	DNH63112	N/A	5410708232583 / PORTABLE	PORTABLE TOILET	10 / EACH/N	LOCAL	ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	TECHNICAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, g. colour coated sheet. d. 27x27 False (Gypsum) ceiling at roof, e. 01 x Eastern commode with Faisal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure GENERAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, g. colour coated sheet. d. 27x27 False (Gypsum) ceiling at roof, e. 01 x Eastern commode with Faisal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for
57	DPC62993	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLON		MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744897	TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS GENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS
58	DPC57474	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLON		MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744897	TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS GENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS
59	DNM56038	NC1-121(110V)	6110785211676 / MAGNETIC CONTACTOR	MOBILE AC PLANT	1 / EACH/NUMBER	NC1-121(110V)	COOL POINT	TECHNICAL SPECIFICATION - BACOLYTE/PLASTIC GENERAL SPECIFICATION - BACOLYTE/PLASTIC
60	DNM71805	1000661	5331715230196 / O RING BUNA	16E SPRAY GUN	3 / EACH/NUMBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414 UK	TECHNICAL SPECIFICATION - OEM & MAKE: CLEMCO USA GENERAL SPECIFICATION - OEM & MAKE: CLEMCO USA
61	SNM70432	996-809/PK-CH10724	6760795189954 / VALVE GUIDE	PERKINS D/G 2306C-E14TAG3 UK	48 / EACH/NUMBER	2306C-E14TAG3		TECHNICAL SPECIFICATION - M/S S.M JAFFER & COMPANY KARACHI GENERAL SPECIFICATION - M/S S.M JAFFER & COMPANY KARACHI
62	DNM70866	3937743 / 3912020 / 3924540 / LF3959	2940014971469 / FILTER ELEMENT,FLUID / LUBRICATING OIL FILTER CARTRIDGE	CUMMINS QSX15	2 / EACH/NUMBER	6BT5.9G1	CUMMINS ENGINE COMPANY, INC BOX 3005 COLOMBUS INDIANA USA 47202	TECHNICAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR GENERAL SPECIFICATION - CUMMINS DG 70 KVA MODLE NO 6BT5.9-G1 S.NO 87426844 CONFIGURATION CAST IRON,IN-LINE,6 CYLINDER GOVERNOR TYPE MECHANICAL STARTING VOLTAGE 24V FUEL SYSTEM DIRECT INJECTION LUBE OIL CAPACITY 16 LTR
63	DNM70946	1000359	5365705230965 / O RING BLACK VITON	16E SPRAY GUN	8 / EACH/NUMBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	TECHNICAL SPECIFICATION - O RING BLACK VITON GENERAL SPECIFICATION - O RING BLACK VITON

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
64	DPK63858	SAPPHIRE LO TEMP 2	9150223091607 / LUBRICANT GREASE (ROCOL SAPPHIRE LO TEMP 2) (18KG packing)	LLADR ANTENA	20 / KILOGRAMME		ITW CHEMICAL PRODUCTS SCANDINAVIA APS FORMELY: KEMA A/S ST1: PRIORSVEJ 36 CIT: SILKEBORG CTR: DENMARK PSC: 8600 TEL: 88826444 FAX: 88826484	<u>TECHNICAL SPECIFICATION - LUBRICATING GREASE</u> <u>GENERAL SPECIFICATION - LUBRICATING GREASE</u>
65	DNM7143 0	CPMU-16	5945705218443 / SOLENOID VALVE	MOBILE AC CVM-2C75-PN	4 / EACH/NUMBER	SN TYPE HM2 220-50HZ (8WATT)	ADDA PLOT, SHARAIZ AVENUE, JATTI UMRA ROAD, RAJWIND ROAD, LAHORE	<u>TECHNICAL SPECIFICATION - SN TYPE HM2 220-50HZ (8WATT) INLET: 7/8" OUTLET: 7/8"</u> <u>GENERAL SPECIFICATION - SN TYPE HM2 220-50HZ (8WATT) INLET: 7/8" OUTLET: 7/8"</u>
66	DPC73912		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	180 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING</u> <u>PURPOSE</u> <u>GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE</u>
67	DPK63529		0475509429213 / LINSEED OIL BOILED ACID NO8 SP GR 0.935-0.955 AT 15.5DEG C.		60 / LITER			<u>TECHNICAL SPECIFICATION - BS6900</u> <u>GENERAL SPECIFICATION - BS6900</u>
68	DPC73642		0474504740087 / SOAP TEEPOL LIQUID (detergent general pupose)	SSDG	900 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4.5</u> <u>GENERAL SPECIFICATION - defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4.5</u>
69	DPC71339		0474504740082 / CUPREX 1 BLOCK (PACKING 1 KG)	4FI SSDG SEA WATER PUMP	46 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - packing 1 kg</u> <u>GENERAL SPECIFICATION - packing 1 kg</u>
70	DPC67392		0473504730146 / ZINC OXIDE WHITE	FWT TAKE OFF DR	20 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX5O3R. GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES : THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETTED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS. REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) IGNITED BASIS 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D407S CADMIUM (CD) * 0.002 MAX 0.0003 ASTM D407S IRON (RE) 0.002 MAX 0.0003 ASTM D407S COPPER (CU) 0.001 MAX 0.0001 ASTM D4075O LOSS AT 110°C (MOISTURE) 0.25 MAX 0.1S ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2.500 LB</u> <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
71	DPC72638		0473504730004 / FLUXITE SOLDDERING PASTE (ZINC CHLORIDE)		1 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
72	DPK64099	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		50 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
73	DPK63527	XG-250	0474509424829 / XG-250 (Silicon Compound DM-3) (18KG Packing)		36 / KILOGRAMME			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
74	SPC68649		0442504420069 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		300 / LITER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
75	DPC73889		0442509423539 / PAINT MARKING BRUSH STENCILLING AMMUNITION (AZURE BLUE), Flash Point 32C (04 LTR TIN) packing: 04 ltr tin gauge of drum 26 to 28 awg		40 / LITER			TECHNICAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996 GENERAL SPECIFICATION - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996
76	SPC59059		0442504420094 / VARNISH FINISHING ARR DRY (packing 4liter tin)		84 / LITER			TECHNICAL SPECIFICATION - S.NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE) GENERAL SPECIFICATION - S.NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE)
77	DPC70041		0442504420094 / VARNISH FINISHING ARR DRY (packing 4liter tin)		64 / LITER			TECHNICAL SPECIFICATION - S.NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE) GENERAL SPECIFICATION - S.NO INFORMATION REMARKS 01 NAME= SYNTHETIC CLEAR VARNISH (ELECTRIC VARNISH) 02 SPECIFIC GRAVITY= 0.87-0.91 03 COLOR= CLEAR HOMOGENEOUS DRAK BROWN 04 FLASH POINT= >30 °C 05 SURFACE DRY TIME= 5-6 HOURS 06 HARD DRY TIME= 24 HOURS 07 PACKAGING= 04 LITER (TIN PACKAGE)
78	DPC73405	NO DATA AVAILAB LE	0443509422226 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap		135 / KILOGRAMME			TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformity Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas
79	DPC67712	00084	0443GR5085142 / CLEANER C IRON REMOVER	SEA WATER DESALINATION UNIT ROCHEM GERMA	20 / PACKET			TECHNICAL SPECIFICATION - OEM ROCHEM RO-WASSERBEHANDLUNG, GMBH KNICKBERG LA, D-21077 HAMBURG GERMANY. VIDE IM (MSG) MEMO CICI/MSG/10770 DATED 9 OCT 12 GENERAL SPECIFICATION - OEM ROCHEM RO-WASSERBEHANDLUNG, GMBH KNICKBERG LA, D-21077 HAMBURG GERMANY. VIDE IM (MSG) MEMO CICI/MSG/10770 DATED 9 OCT 12.

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
80	SNQ37530	BS876(51 20-99- 255- 7816)	0274709104652 / HAMMER HAND ENGINEER 2.000LBS LG 16.000IN IL31ENGS PEIN		30 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
81	DNQ61421	BS - EN - 3	0243591295833 / FIRE EXTINGUISHER CO2 5.5 KGS RED	FIRE FIGHTING EQUIPMENT	141 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - SPECS: BS - EN - 3</u> NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150-160mm CYLINDER HIGH (mm): 800-840mm CYLINDER WEIGHT (Kg) 6-8KG EXTINGUISHER WEIGHT(kg) 11-13kg <u>GENERAL SPECIFICATION - SPECS: BS - EN - 3</u> NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150-160mm CYLINDER HIGH (mm): 800-840mm CYLINDER WEIGHT (Kg) 6-8KG EXTINGUISHER WEIGHT(kg)11-13kg
82	DNQ63433		0243591295834 / FIRE EXTINGUISHER CO2 (CARBON DIOXIDE) 2 1/2LB C /W DISHARGE HORN ASSM	FOR FIRE FIGHTING	79 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - BS EN -3</u> <u>GENERAL SPECIFICATION - BS EN -3</u>
83	DNQ73807		0243591295834 / FIRE EXTINGUISHER CO2 (CARBON DIOXIDE) 2 1/2LB C /W DISHARGE HORN ASSM	FOR FIRE FIGHTING	6 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - BS EN -3</u> <u>GENERAL SPECIFICATION - BS EN -3</u>
84	DNQ65552	G4A1H01 21CMOD	0243995316927 / FIRE HOSE DURALINE/GOMTE X I/D2 LENGTH: 40 FEET (1+1M)/FEMALE COUPLING	FOR FIRE FIGHTING EQUIPMENT	3 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - length: 40 feet (1+1m)/female coupling</u> <u>GENERAL SPECIFICATION - length: 40 feet (1+1m)/female coupling</u>
85	DPC67391		0473504730064 / MBT RUBBER ACELEATOR		20 / KILOGRA MME			<u>TECHNICAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u> <u>GENERAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u>
86	SPC59383		0473504730064 / MBT RUBBER ACELEATOR		20 / KILOGRA MME			<u>TECHNICAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u> <u>GENERAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u>
87	DPC56266		0473504730064 / MBT RUBBER ACELEATOR		40 / KILOGRA MME			<u>TECHNICAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u> <u>GENERAL SPECIFICATION - mBT POWDER PACKING: 20 KG NET PACKED BAGS</u>
88	DPC59036		0474504740012 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		10 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
89	SPC61234		0474504740012 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		70 / EACH/NU MBER			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
90	DPC70811	0474- 7041	0474502242642 / CEMENT PORTLAND (50 KG BAG)		300 / KILOGRA MME			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
91	DNQ47867	69217065 / 0	3040725091524 / TOP HEAD DRIVE SHAFT	DOCK BILGE PUMP GERMANY	4 / EACH/NUMBER			TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 2680 mm GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 2680 mm
92	SNM70216	CV2473(9 9-796-8199)	2940UK5071778 / FILTER LUB OIL LG 190 O/D-343MM FLEET GUARD	D/G MOBILE INTER POWER 600 KVA 480 KW	20 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
93	DNM7299 2	2654407	2940010803861 / OIL FILTER	PERKIN D/E 806/YE-102 OEM ADAMJEE D/ENGG	8 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
94	DNQ46495	ITSHFD4-SEW / 69217065 8	3040725094058 / INTERMEDIATE DRIVE SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	4 / EACH/NUMBER			TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MArTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MArTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar
95	SNM70219	CV20948	2815795091215 / AIR FILTER ELEMENT	D/G INTER POWER (UK) 3012TAGIA	8 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
96	SNM70207	6180250	2815731002991 / PIN PISTON RETAINER GMD 600W D/G	FG WILSON DIESEL GENERATOR 600W	14 / EACH/NUMBER	GMD/600W		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
97	SNM64028	801-115	2910795113057 / OIL FILTER	FG KEY DG PERKIN 1308-E87T 215	20 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
98	DNQ46494	PSDF4-SEW / 64710020 5	4320725084081 / PUMP SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	2 / EACH/NUMBER			TECHNICAL SPECIFICATION - TECHNICAL DATA , Drawing No. D008 MArTERIAL/ GRADE, Stainless Steel 304 PRODUCTION METHOD, Drawn from solid bar GENERAL SPECIFICATION - TECHNICAL DATA , Drawing No. D008 MArTERIAL/ GRADE, Stainless Steel 304 PRODUCTION METHOD, Drawn from solid bar
99	DNQ46496	1907-ISFT-FD4-SEW / 64710020 8	4320725094062 / INTERMEDIATE DRIVE SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	4 / EACH/NUMBER			TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 1907 mm TECHNICAL DATA , Drawing No. D005 MArTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 1907 mm TECHNICAL DATA , Drawing No. D005 MArTERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar
100	DNH61499	DV-200N	4310795113468 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
101	DNQ58140	54.107.00	4210995413550 / INLINE INDUCTOR,2.5" BSPF COUPLING,445MM LG,160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	5 / EACH/NUMBER			TECHNICAL SPECIFICATION - Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8 GENERAL SPECIFICATION -Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8
102	DNM7201 0	5P1260/3 718124	4720011033697 / HOSE 7.62 CM(3") (HOSE NON MATELIC)	3304PC,CATERPILLER D/GEN.USA	1 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
103	DNQ73706	LOCAL	4210705007917 / NOZZLE FOR HOSE CANVAS		3 / EACH/NUMBER	SL-138P SHILA FIRE		TECHNICAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy GENERAL SPECIFICATION - Series: W2500 Model: Pwr 1 & 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide & light aluminium alloy
104	DNM66499	EBH 12 OR 215412400/215612400/215613405	4130US6065503 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	2 / EACH/NUMBER	TVE12		TECHNICAL SPECIFICATION - Make: USA Model: E58977 Brand: DOMETIC Equivalent: Nil 215612400 FOR 115V/1/60HZ, 215613405 FOR 230/1/60HZ GENERAL SPECIFICATION - Make: USA Model: E58977 Brand: DOMETIC Equivalent: Nil 215612400 FOR 115V/1/60HZ, 215613405 FOR 230/1/60HZ
105	DNM69344	E24FDZ/1	4130715091891 / EVAPORATOR 24000BTU	AIR CONDITIONING UNIT OF MARINE AIR SYSTEM USA	2 / EACH/NUMBER	MARINE AIR/E24FDZ/1		TECHNICAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILITY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32 GENERAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILITY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32
106	DNH74952	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
107	DNH74347	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		4 / EACH/NUMBER	WDF-318		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
108	DNM71889	6712-666	4940795061957 / HOSE W/ADAPTOR 16M LG10MM I/D 17.50MM O/D W/PRESSURE=400 BAR	AIR POWERED PORTABLE AIRLESS HYDRA SPRAY	5 / EACH/NUMBER			TECHNICAL SPECIFICATION - LENGTH : 15METER ID: 10MM OD: 17.50MM PRESSURE:400BAR LOCAL ADD:ASHI ENTERPRISES ROOM NO:48 3RD FLOOR MOOSA MARKET OPP SINDH MADERSSEA SHAHRAH-E-LIAQAT KARACHI 74000 CELL: 0334-3500149 VIDE GM(SR&C)LETTER SRC/HE/131/349 DT 24 JAN 13. GENERAL SPECIFICATION - LENGTH : 15METER ID: 10MM OD: 17.50MM PRESSURE:400BAR LOCAL ADD:ASHI ENTERPRISES ROOM NO:48 3RD FLOOR MOOSA MARKET OPP SINDH MADERSSEA SHAHRAH-E-LIAQAT KARACHI 74000 CELL: 0334-3500149 VIDE GM(SR&C)LETTER SRC/HE/131/349 DT 24 JAN 13.
109	DPC69191	BS 2451, DEFSTAN 80-73/1 OF 1977	8010701004136 / PAINT NON SLIPING PREMIXED (LIGHT GREY) BS2451,DEFSTAN 80-73/1	FINISHING NON SLIP	307 / LITER			TECHNICAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0mm GENERAL SPECIFICATION - Grit Aggregate Size = 0.5mm to 1.0mm Thickness Level = 2.0mm to 3.0mm
110	DPC58482		8030000660967 / CORROSION RESISTANT		30 / QUART			TECHNICAL SPECIFICATION - MIL-DTL-81706 GENERAL SPECIFICATION - MIL-DTL-81706
111	DPC68732	NO DATA AVAILABLE	8010706112537 / SOLIGNUM WOOD LACOUER	FOR WOOD WORK	5 / LITER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
112	DPC67060	1107	8030785033978 / SEALING PASTE THREE BOND CF-161	MAIN ENGINE BRLB 66 FOR PNS NASR	5 / UNIT			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
113	DPC67211	0473-473157	6850992248070 / CAPSULE WATER DETECTION	MAINTENANCE, INSTRUMENT MEASURE, RECORD	12 / TUBE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
114	DPC71448	0473-473157	6850992248070 / CAPSULE WATER DETECTION	MAINTENANCE, INSTRUMENT MEASURE, RECORD	12 / TUBE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
115	DPC73536	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK5075658 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU, ARGOS-73 RADAR	204.12 / KILOGRAMME			TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)
116	DPC73537	R-502	6830705110669 / GAS REFRIGRENT R-502 (packing = 13.6kg)	COLD STORAGE & BLASTFREEZER	27.24 / KILOGRAMME			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
117	DPC67943	NO DATA AVAILAB LE	9160715016388 / COMPOUND HONEY WAX MOULD RLSE (Packing 14OZ Tin)	BEST TRADE PRODUCT.	5 / TIN			TECHNICAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP GENERAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP
118	DNM71429	RDH-710K	4140755126477 / EVAPORATOR BLOUER (NICOTRA) (ITLY)	MOBILE A/C PLANT	2 / EACH/NUMBER	CVM-2C70-PN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
119	DPK68486	CORENA P68, ISO 6743-3	9150705095666 / SHELL CORENA S4 P68 (CAN 20 LTR)	AIR COMPRESSOR HL2/90, PNT RUSTOM	20 / LITER			TECHNICAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P68 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/S ASTM D445 68 KINEMATIC VISCOSITY @100°C TIM'/S ASTM D445 8.5 DENSITY @15PC KG/M ASTM DI 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C ASTM D97 -51 SULPHATED ASH %M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM DI30 LB WATER SEPARABILITY @54°C MIN ASTM DI401 30 GENERAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P66 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/S ASTM D445 68 KINEMATIC VISCOSITY @100°C TIM'/S ASTM D445 8.5 DENSITY @15PC KG/M ASTM DI 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C ASTM D97 -51 SULPHATED ASH %M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM DI30 LB WATER SEPARABILITY @54°C MIN ASTM DI401 30
120	DPC70674	NO DATA AVAILAB L	6810705007848 / ACTIVATOR RESIN (ISOCYANATE COMONENT A) OEM = LOGSTOR/		220 / KILOGRAMME			TECHNICAL SPECIFICATION - ACCEPTANCE CRITERIA: ACCEPTANCE OF THE LOCAL ORIGIN ITEM WILL BE BASED ON END USER'S PERFORMANCE TESTING/ GENERAL SPECIFICATION - ACCEPTANCE CRITERIA:

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
121	DPC69121	NO DATA AVAILAB LE	6810705007848 / ACTIVATOR RESIN (ISOCYANATE COMONENT A) OEM = LOGSTOR/ Polyurethane Foam Comp A (OEM = ICI) Packing 220 Kg Drum		220 / KILOGRA MME			TECHNICAL SPECIFICATION - ACCEPTANCE CRITERIA: ACCEPTANCE OF THE LOCAL ORIGIN ITEM WILL BE BASED ON END USER'S PERFORMANCE TESTING/ ACCEPTANCE GENERAL SPECIFICATION - ACCEPTANCE CRITERIA: ACCEPTANCE OF THE LOCAL ORIGIN ITEM WILL BE BASED ON END USER'S PERFORMANCE TESTING/ ACCEPTANCE.
122	DPC58408	EPOVIAT H-350T OR EQUIVAL ANT LLOYDS APPROV EDPROD UCT	6810731001001 / CRYTIC GELCOAT 66 E (BRUSH) NON- ACCELERATED UNSATURATED OR EQUIVALANT LLOYDS APPROVED PRODUCT	USE BY BOAT SHOP FOR ANTICORROSION	260 / KILOGRA MME			TECHNICAL SPECIFICATION - Gel coat polyester resin unsaturated unprompted thixotropic suitable for hand and spray lay up in tropical conditions Material should be preferable of USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register. The material specifications are given below: a. Governing Reference/ Specifications NES -167 b. Viscosity, 20 °C Poise 30-35 - c. Appearance - pale - d. Tensile strength (unfilled resin) MPa 60 (Min) e. Flexural strength (unfilled resin) MPa 110 (Min) f. Typical gel time,30oC with accelerator & MEKP Minutes 25 (Min) g. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) h. Stability in dark at 25oC without initiator Months 6-8 - j. Water absorption (24 hours) mg 30 (Max) GENERAL SPECIFICATION - Gel coat polyester resin unsaturated unprompted thixotropic suitable for hand and spray lay up in tropical conditions Material should be preferable of USA West Europe, Japan make. Material should have valid Type Approval certificate of Lloyds's Register. The material specifications are given below: a. Governing Reference/ Specifications NES -167 b. Viscosity, 20 °C Poise 30-35 - c. Appearance - pale - d. Tensile strength (unfilled resin) MPa 60 (Min) e. Flexural strength (unfilled resin) MPa 110 (Min) f. Typical gel time,30oC with accelerator & MEKP Minutes 25 (Min) g. Cure time at 30oC accelerator & MEKP Minutes 35 (Min) h. Stability in dark at 25oC without initiator Months 6-8 - j. Water absorption (24 hours) mg 30 (Max)
123	SPC43409	24137	6810002270410 / ISOPROPYL ALCOHOL (SIGMA ALDRICH 24137) (2.5 Liter Packing)		15 / GALLON			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
124	DNH74794	NO DATA AVAILAB LE	1308500530125 / REFRIG 12CUFT DOUBLE DR 220V(DLT.NSSD/H M/PATT/467 DT.121093)	12 CUF	2 / EACH/NU MBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
125	DNM7140 7	CCG-3	1010705126482 / CONDENSER COIL GUARD	MOBILE A/C PLANT	4 / EACH/NU MBER	CWM-2C70- PN		TECHNICAL SPECIFICATION - Brand:locally fabricated by OEM Make: M/s CoolPoint (Pvt.) Ltd. Material of subject item is Galvanized Iron of 01 mm thickness and size: 65" x 39" GENERAL SPECIFICATION - Brand:locally fabricated by OEM Make: M/s CoolPoint (Pvt.) Ltd. Material of subject item is Galvanized Iron of 01 mm thickness and size: 65" x 39".
126	DNM7140 9	AEL-210 (SKF/NT N)	3120705126479 / EVAPORATOR FAN BEARING (SELF ALIGN)	MOBILE A/C PLANT	2 / EACH/NU MBER	CWM-2C70- PN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
127	DNM7141 0	CPMU-25	4330705126468 / OIL SEPARATOR	AIR COND SYS CWM 2C70-PN	2 / EACH/NU MBER	CWM-2C70- PN		TECHNICAL SPECIFICATION - Model No: CPMU-25 Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point GENERAL SPECIFICATION - Model No: CPMU-25 Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point
128	DNM7386 4	260104- 91	5331013262904 / O RING (SEE COMD F8)	ALPHA LEVEL	4 / EACH/NU MBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
129	DNM6891 4	260104- 91	5331013262904 / O RING (SEE COMD F8)	ALPHA LEVEL	2 / EACH/NU MBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
130	DNM71432	CPMU-27	4710705126489 / VIBRATION ABSORBER (DISCHARGE LINE)	MOBILE A/C PLANT	4 / EACH/NUMBER	CWM-2C70-PN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
131	DPK68228	FLUGEN E113BOM BEAERO SOL(UFI) PMU 1-ROPD-8007-P2DQ	6860143440904 / CLEANING SOLVENT FOR ELECTRIC/ELECTRONIC EQUIPMENT		20 / EACH/NUMBER	UFI:PMU 1-ROPD-8007-P2DQ		TECHNICAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate. GENERAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate.
132	DPK73798	PATEAR ODERGR AIN240	5350143407964 / PATE-RODER-CARBURE-SILJ-N		10 / KILOGRAMME	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
133	DPK56035		9150FP0020002 / GREASE SHELL GADUS S2 V 100 2 (18 KG Packing)		108 / KILOGRAMME	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
134	SNM70431	277-2823	5330015677967 / gasket		5 / EACH/NUMBER	C7-1502-117		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
135	DPC71447	MP4-2020TX	6850705281909 / MARINE ORTHOPHTHALIC UNSATURATED POLYESTER RESIN 225 KG Drum for underwater repairs		225 / KILOGRAMME	matpol		TECHNICAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value:35-40 mg KOH/g, solid content:60-65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature:165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250) GENERAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value:35-40 mg KOH/g, solid content:60-65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature:165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250)
136	DPC70673	MP4-2020TX	6850705281909 / MARINE ORTHOPHTHALIC UNSATURATED POLYESTER RESIN 225 KG Drum for underwater repairs		225 / KILOGRAMME	matpol		TECHNICAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value:35-40 mg KOH/g, solid content:60-65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature:165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250) GENERAL SPECIFICATION - Appearance:clear slightly pale, styrene content:30-35%, acid value:35-40 mg KOH/g, solid content:60-65%, mass density:1.12-1.19g/cm3, viscosity@300 in Din cup-4:80-90 seconds Gel time @300:10-12 Min, exothermic temperature:165-1700 C, Exothermic time: 13-20 Min, storage: 250, shelf life:03 months (reduces shelf life above 250)
137	DNM71799	ch11656	5330796320042 / seal oil		6 / EACH/NUMBER	na		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
138	SNM70646	198586050	3110785235514 / MAIN BEARING KIT		10 / EACH/NUMBER	SDG15PS		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
139	DNM71585	216061	4720715233360 / sensor angle 180 deg cw		2 / EACH/NUMBER	zx-135/70		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
140	SNM70645	7351577	4710735245481 / 25, pipe		1 / EACH/NUMBER	CLASSIC V		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
141	DNM7179 4	ch10732	2815795320033 / valve seat insert		12 / EACH/NU MBER	na		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
142	SNM70640	7351576	4710735245480 / 25, pipe		1 / EACH/NU MBER	CLASSIC V		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
143	DNQ69976	0841- 3009	8040735300637 / REPAIR ADHESIVE 70 ML TUBE		114 / EACH/NU MBER	n/a		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
144	DNQ69756	0841- 3009	8040735300637 / REPAIR ADHESIVE 70 ML TUBE		6 / EACH/NU MBER	n/a		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
145	DNQ69857	0841- 3009	8040735300637 / REPAIR ADHESIVE 70 ML TUBE		9 / EACH/NU MBER	n/a		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
146	DNM7091 8	4367781/ 317-5483	3120715265978 / BEARING		6 / EACH/NU MBER	C7.1		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
147	SNM70427	4367781/ 317-5483	3120715265978 / BEARING		18 / EACH/NU MBER	C7.1		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
148	DNM7112 9	13.57.321	2815745327007 / PUMP ASSY, OIL		1 / EACH/NU MBER	MOTEURS BAUDOUIIN, MAIN ENGINE, MODEL 12P15E		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
149	DNM6942 1	3134203	4730735281293 / HYDRALIC HOSE		1 / EACH/NU MBER	KESLA 204T		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
150	DPC66530	407A	6830795293018 / REFRIGERANT GAS 407A (in non returnable cylinder of 40 kg net)		90 / KILOGRA MME	407A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
151	DNM7132 5	7X-2542	5306715327076 / HEX HEAD BOLT 150MM		30 / EACH/NU MBER	1500F		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
152	DNM7179 6	ch11654	5330795320046 / seal oil		6 / EACH/NU MBER	na		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
153	DNM7179 5	krp1529	5330795320044 / gasket		1 / EACH/NU MBER	na		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
154	DNM7091 5	4367781/ 317-5482	3110785235438 / BEARING		6 / EACH/NU MBER	C7-1502- 117		<u>TECHNICAL SPECIFICATION - caterpillar</u> <u>GENERAL SPECIFICATION - caterpillar</u>
155	SNM70641	7651923	4710735269815 / 3/8"X1050 SAE 100 R2 HOSE		1 / EACH/NU MBER	CLASSIC V		<u>TECHNICAL SPECIFICATION - 3/8"X1050 SAE 100 R2 HOSE</u> <u>GENERAL SPECIFICATION - 3/8"X1050 SAE 100 R2 HOSE</u>
156	DPK59578		0930930237881 / ABCITE X1060 Thermoplastic Powder coating (RAL 9005-2 BLACK)		3 / CAN	NO DATA AVAILABLE		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
157	DNM7179 3	ch11311	2815795320039 / sleeve		6 / EACH/NU MBER	na		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
158	DNQ69747	06742009	4220795312158 / PRV CAPS (THANNER ONLY)		12 / EACH/NU MBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
159	DNQ73402	30-2062	4220785289433 / FLARE SET (06 RED HAND FLARE MK8+04 PARA RED ROCKET MK8A +02 LIFE SMOKE MK9) FOR SURVIVAL PACK OF 25 X MEN LIFE RAFT		18 / PACKET	life raft		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
160	DNQ69748	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		6 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
161	DNQ74696	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		15 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
162	DNQ73716	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		2 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
163	DNQ69862	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		4 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
164	DNQ70508	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		16 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
165	SNM70643	7351077	4720735283601 / 3/8"X1150 SAE 100 R2 HOSE		1 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
166	DPK57358	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100		<u>TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = 42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.08 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u> <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = 42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u> <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = 42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u>
167	DPK61572	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100		<u>TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = 42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u> <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = 42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A - FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A - REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES</u>
168	SNM70638	4001588	4730735269996 / 3/4"X2000 SAE100 R12 HOSE		1 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION - 3/4"X2000 SAE100 R12 HOSE</u> <u>GENERAL SPECIFICATION - 3/4"X2000 SAE100 R12 HOSE</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
169	DNM7139 4	ch12341	2915994989345 / NOZZLE,FUEL INJECTION		8 / EACH/NUMBER	na		<u>TECHNICAL SPECIFICATION</u> - engine fuel sys part no ch12341 country of origin uk <u>GENERAL SPECIFICATION</u> - engine fuel sys part no ch12341 country of origin uk
170	SNM70425	138-3097	4930014715268 / SEPARATOR GP-WATER		1 / EACH/NUMBER	C7.1		<u>TECHNICAL SPECIFICATION</u> - FUEL WATER SEPARATOR <u>GENERAL SPECIFICATION</u> - FUEL WATER SEPARATOR
171	SNM70642	7650356	4730735245544 / 3/8"x1300 SAE 100 R2 hose		1 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
172	SNM70636	7350736	4730735245324 / 3/4"x630 SAE 100 R12 hose		1 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
173	DNM7179 2	ch10731	2805997260776 / valve seat insert		12 / EACH/NUMBER	na		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
174	SNM70434	380-2055	2815715240080 / KIT-PISTON RINGS) (0.5-MM OS)(INCLUDES PISTON RINGS)		3 / EACH/NUMBER	C7.1		<u>TECHNICAL SPECIFICATION</u> - NOT KNOWN <u>GENERAL SPECIFICATION</u> - NOT KNOWN
175	DPC68169	code s154	6850725279747 / SALTESMO (LUB OIL TEST KIT AGENT)PACKING 100 PIECES		8 / BOTTLE	CODE S154		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
176	SNM70644	8716884	5340735269781 / 3/8"X1170 SAE 100 R2 HOSE		1 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION</u> - 3/8"X1170 SAE 100 R2 HOSE <u>GENERAL SPECIFICATION</u> - 3/8"X1170 SAE 100 R2 HOSE
177	DNH75021	mk-2015-e-7039	4140705263183 / exhaust fan 23vac w2e		2 / EACH/NUMBER	w2e200		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
178	SNM71442	2915330	5331735283579 / S Ø140X 2.5 70SH O-RING		6 / EACH/NUMBER	CLASSIC V		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
179	SNM70424	486-4849	2815715240073 / KIT-PISTON RING (1-MM OS) (INCLUDES ONE SET RINGS)		3 / EACH/NUMBER	C7.1		<u>TECHNICAL SPECIFICATION</u> - NOT KNOWN <u>GENERAL SPECIFICATION</u> - NOT KNOWN
180	SNM70650	19658608 D/T40262 1	3110785235515 / BIG END BEARING KIT		19 / EACH/NUMBER	SDG15PS		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
181	DNH71425	at-3291	5130755292387 / coil nailer		2 / EACH/NUMBER	AT-3291		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
182	DPC70298	006154Z0 3885	9350775274168 / REFRACTORY MORTAR READY MIX		20 / KILOGRAMME	FIBERSTIC K 1600		<u>TECHNICAL SPECIFICATION</u> - FIBER STICK1600 is a wet air setting mortar and because of the choice of raw material usable upto 1550 c <u>GENERAL SPECIFICATION</u> - FIBER STICK1600 is a wet air setting mortar and because of the choice of raw material usable upto 1550 c
183	SNM70435	380-4849	2815715301705 / KIT-PISTON (0.5-MM OS)		7 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
184	DPC73849	100	5340715160688 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 R2/b)	DECK COVERING FOR CONCRETE SURFACE	15 / BAG		OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:588-771-6500/FAX:588-771-6501.	<u>TECHNICAL SPECIFICATION</u> - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:588-771-6500/FAX:588-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS,RESINOUS FLOORING SYS <u>GENERAL SPECIFICATION</u> - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:588-771-6500/FAX:588-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS,RESINOUS FLOORING SYS.
185	DNQ74414	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		2 / EACH/NUMBER	N/A		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
186	DNM74284	JB/T9755-1999	2940785163960 / AIR CLEANER ELEMENT	20 KW DIESEL GENERATOR LLADR CUMMINS	2 / EACH/NUMBER	KW1524	M/S POLY TECHNOLOGIES BEIJING CHINA	<u>TECHNICAL SPECIFICATION - OEM: CUMMINS M/S POLY TECHNOLOGIES BEIJING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI.</u> <u>GENERAL SPECIFICATION - OEM: CUMMINS M/S POLY TECHNOLOGIES BEIJING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI.</u>
187	DNM74501	FTXN50JXV1	4120766222676 / AIR CONDITIONAR 1.5 TON INVERTOR/REVERSABLE	AC	1 / EACH/NUMBER	FTXN50JXV1	DAIKIN, JAPAN	<u>TECHNICAL SPECIFICATION - NAGENERAL SPECIFICATION - NA</u>
188	DPC74724	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
189	DPC74575	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
190	DPC74460	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
191	DPC75098	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
192	DPC73776	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
193	DPC74891	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIIEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
194	DPC74947	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIIEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
195	DPC74525	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIIEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
196	DPC74355	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIIEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
197	DPC74269	0443-443003	0443502240439 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPIIEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER			<u>TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u> <u>GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I</u>
198	DPC74914		0443705054896 / GAS HELIUM 99.995% PURE (CYLIDER 9.40 CUBIC M)		18.8 / CUBIC METER			<u>TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u> <u>GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM</u>
199	DPC73071	DEFSTAN 80-59/1 OF 1976. Shade no 221 of BS 381-C	0442504420101 / PAINT SYNTHETIC ENAMEL (BRILLIANT GREEN) (20 LTR DRUM) Flash point 32C	USED FOR CNS BARGE	340 / LITER			<u>TECHNICAL SPECIFICATION - 1. defstan 80-59/1 of 1976 2. colour shade no 221 of bs 381 c of 1996 3. stage inspection prescribed 4. flash point 32c (min)</u> <u>GENERAL SPECIFICATION - 1. defstan 80-59/1 of 1976 2. colour shade no 221 of bs 381 c of 1996 3. stage inspection prescribed 4. flash point 32c (min)</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
200	DPC73965	60194	0442504420168 / READY MADE BAIT CONTROL (Rat & mouse killer Racumin) TLON@ WEATHER BLOK @ XT		10 / KILOGRAMME			<u>TECHNICAL SPECIFICATION - ILON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight</u> <u>GENERAL SPECIFICATION - ILON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight</u>
201	DNH74386	NO DATA AVAILAB LE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL MITSUBUSHI / DAKEN/ GENERAL, GENERAL, LG.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>
202	DNH74623	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318		<u>TECHNICAL SPECIFICATION - NO DATA AVAILAB</u> <u>GENERAL SPECIFICATION - NO DATA AVAILAB</u>
203	SPK75170	S2 MX68	9150505035103 / SHELL TELLUS S2 MX68 (Packing 209 Liters Drum)	AIR COMPRESSOR	209 / LITER			<u>TECHNICAL SPECIFICATION - NO DATA AVAILAB</u> <u>GENERAL SPECIFICATION - NO DATA AVAILAB</u>
204	DPK73597	S2 MX68	9150505035103 / SHELL TELLUS S2 MX68 (Packing 209 Liters Drum)	AIR COMPRESSOR	209 / LITER			<u>TECHNICAL SPECIFICATION - NO DATA AVAILAB</u> <u>GENERAL SPECIFICATION - NO DATA AVAILAB</u>
205	DPK73503	90790-BS455	9150218770478 / OIL SAE 10W40 API SJ for YAMALUBE 4 STROKE MOTOR (01 Liter Packing)	RADAR-DA08	215 / LITER			<u>TECHNICAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached</u> <u>GENERAL SPECIFICATION - BASE NUMBER, D2896,mgKOH/g:6.9 D4739,mgKOH/g:6.0 part no 90790-bs455 updated against old part no FCW NMMA vide im direction on bases of oem quotation attached</u>
206	DNQ70971	005101010	8415991304874 / HOOD,ANTIFLASH.	DC LOCKER	71 / EACH/NUMBER			<u>TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0)2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.</u> <u>GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0)2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.</u>
207	SPK74562	ALBA ABP-8	6850TY6720908 / ETCHING SOLUTION (PCBA ABP-8) 6850TY6/20908		50 / KILOGRAMME	NO DATA AVAILAB		<u>TECHNICAL SPECIFICATION - (PACKING 30 KG PLASTIC CAN)</u> <u>GENERAL SPECIFICATION - (PACKING 30 KG PLASTIC CAN)</u>
208	DPK73670	SHELL OMALA S4 GX 220	9150705312134 / advanced synthetic industrial gear oil		8 / LITER	HIZIR TCMS		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
209	DPK73668	SHELL GADUS S3 A1000XD 2	9150715312357 / PREMIUM GREASES WITH EXTRA SOLIDS		6 / KILOGRAMME	NA		<p><u>TECHNICAL SPECIFICATION</u> - SHELL GADUS S3 A1000XD 2 IS A HEAVY DUTY CALCIUM GREASE FORMULATED WITH A HIGH LEVEL OF SOLID ADDITIVES FOR ENHANCED LOAD CARRYING CAPABILITY. THE HIGH SOLIDS CONTENT AND HEAVY BASE OIL UTILIZED IN THIS PRODUCT ARE DESIGNED TO PROVIDE AN EFFECTIVE LUBRICANT FILM UNDER THE HIGH LOADS AND CONSTANT SLIDING CONTACT. A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains 3% (w/w) DMSO extract, according to IP346.</p> <p><u>GENERAL SPECIFICATION</u> - SHELL GADUS S3 A1000XD 2 IS A HEAVY DUTY CALCIUM GREASE FORMULATED WITH A HIGH LEVEL OF SOLID ADDITIVES FOR ENHANCED LOAD CARRYING CAPABILITY. THE HIGH SOLIDS CONTENT AND HEAVY BASE OIL UTILIZED IN THIS PRODUCT ARE DESIGNED TO PROVIDE AN EFFECTIVE LUBRICANT FILM UNDER THE HIGH LOADS AND CONSTANT SLIDING CONTACT. A lubricating grease containing highly-refined mineral oils and additives. The highly refined mineral oil contains 3% (w/w) DMSO extract, according to IP346.</p>
210	DNQ74381	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		12 / EACH/NUMBER	N/A		<p><u>TECHNICAL SPECIFICATION</u> - null</p> <p><u>GENERAL SPECIFICATION</u> - null</p>
211	DNH74345		1680715206946 / AIR CONDITIONER (FLOOR STANDING) 2 TONS	UPGRADING OF MARITIME SAFETY INFORMATION MANAGEMENT	1 / EACH/NUMBER	GF-24TF	M/S Skill Orbit using ESIR GIS software orig USA	<p><u>TECHNICAL SPECIFICATION</u> - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.</p> <p><u>GENERAL SPECIFICATION</u> - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.</p>

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

478

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 24 dt 02/12/2024	300000.00
Bank A/c No PK17HABB0004540013100701	300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A
(Signature of Offr Signing the cheque)

Initial
Supdt Audit Sec

Initial
Officer OI/C Audit Sec

To HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD
P.P.R.A
PPRA 1st Floor FBC Building, Near State Bank S.ctor G-5/2, Islamabad

Copy To LP Division
2. LAO (LAO (NAVY) NSD KARACHI)