

HBL

HABIB BANK

حیب بینک

Deposit Slip

Customer Copy

Branch: _____ Date: _____

Account Title: اکاڈمیٹ ہولڈنگز کا نام

IBAN: PK17HABB0004540013100701

Currency: PKR USD EURO GBP JPY Others

Credit Card No. _____ Intercity Within city Same Branch

CASH نقد

BANK / BRANCH	CHEQUE/INSTRUMENT NO. چیک نمبر	AMOUNT رقم
	<u>Cash</u>	<u>15,000/-</u>
TOTAL AMOUNT		<u>5000/-</u>

Total Amount in Words: Fifteen Thousand only

Depositor's Name: Ashraf ulah Commission (if any) _____

Contact No.: 03450769922

Depositor's CNIC No.: 1101-1944489-3

Depositor's Account No.: _____

Online Cash Deposit

Branch: 0016-K.P.T. KARACHI

Account: PUBLIC PROCUREM Date: 2024-11-04

IBAN: PK17HABB0004540013100701

Amount: *****15,000.00 PKR

Charges: *****575.00

Teller BR30 179 Time 16.23.02.271000

Received By: موسلمہ کاندھلوی Depositor's Signature: [Signature]

17377616

(As per Terms & Conditions on reverse) (Not official unless validated)

TENDER BULLETIN

DATE & TIME 11/6/24 8:46 AM INVITATION TO TENDER TO BE OPENED ON 11/18/ 10:00 AM AND ITEM REQ BY

CONDITIONS

- NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
- FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
- LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGE211 92		041450823171 0 / LINING MATERIAL FOR USE IN CRANES LG 4 WD 12" THICKNESS 1/4" DENOMINATION SO FT		100 / SO FEET						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: DESCRIPTION=LINING MATERIAL FOR USE IN CRANE,WIDTH=12", THICKNESS=1/4", DENOMINATION SO FT MATERIAL= DENSELY WOVEN, SEMI-FLEXIBLE FRICTION MATERIAL (YARN SPUN FROM MIXTURE OF GLASS &SYNTHETIC FIBERS REINFORCED WITH FINE COPPER WIRE TO IMPROVE STRENGTH AND HEAT DISSIPATION CHARACTERISTICS) GENERAL SPECIFICATION - ITEM SPECIFICATION: DESCRIPTION=LINING MATERIAL FOR USE IN CRANE,WIDTH=12", THICKNESS=1/4", DENOMINATION SO FT MATERIAL= DENSELY WOVEN, SEMI-FLEXIBLE FRICTION MATERIAL (YARN SPUN FROM MIXTURE OF GLASS &SYNTHETIC FIBERS REINFORCED WITH FINE COPPER WIRE TO IMPROVE STRENGTH AND HEAT DISSIPATION CHARACTERISTICS)	
2	DGR400 48	Gate valve on 350	482070505115 2 / GATE VALVE 14 inch (DN 350)	GENERAL USE	3 / EACH/NUMBER						TECHNICAL SPECIFICATION: INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES:	

Generated By Re-Engineered WIMS

Page 1 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											22MM Inner dia: 14 inch (DN 350) GENERAL SPECIFICATION - INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES: 22MM Inner dia: 14 inch (DN 350)	
3	DGD298 33	NO DATA AVAILAB LE	003550000056 0 / COOKER PRESSURE-10 LITRES COMPLETE		1 / SET	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Aluminum Food Grade (Lead Free) GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free)	
4	DGE387 46	NO DATA AVAILAB LE	834050503826 2 / QANAT COMPLETE SIZE 18.X 7., OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length 18 feet, Width 7 feet. Bumbo in single piece of Qanat. 05 Pockets. Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Salt and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED GENERAL SPECIFICATION - Length 18 feet, Width 7 feet. Bumbo in single piece of Qanat. 05 Pockets. Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report:Salt and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED &TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
5	DCD658 99		844050390085 6 / CAP ROUND WHITE SIZE 7"		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - CAP ROUND WHITE SIZE 7" GENERAL SPECIFICATION - CAP ROUND WHITE SIZE 7"	

Generated By Re-Engineered WIMS

Page 2 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
6	DGE65365	NIL	5670705047303 / nomex paper-12		4 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
7	DGB54034		0275709105937 / SHOVEL HAND ROUND MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"		10 / EACH/NUMBER					OEM, COC/AUTHORIZED DEALER CERTIFICATE REQUIRED	TECHNICAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg. GENERAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg.	
8	DGP59111		3610705049342 / DUPLICATOR ELECTRICAL GESTETNER HEAVY DUTY		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGB54891	NO DATA AVAILABLE	0268500000047 / WEIGHING MACHINE 50 KG - 300 kg		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g GENERAL SPECIFICATION - a. Make Model: OMEGA TAIWA/KINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g	
10	SGB49081	BS 1740, UI27880267-10666	0267599235094 / ELBOW ROUND BLACK 0.75IN		250 / EACH/NUMBER						TECHNICAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b GENERAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b	
11	SGB54880	BS 1769	0214502140795 / BOLT ROOFING STEEL WITH NUT FULL THD TPI 20 SZ 2.0		200 / GROSS						TECHNICAL SPECIFICATION - MATERIAL GRADE EN 4140 Item Specification: OEM-KSF, FRANCE, PARENT EQUIPMENT - GENERAL SERVICE PUMP MOTOR NO.1 AND 2 GENERAL SPECIFICATION - MATERIAL GRADE EN 4140 Item Specification: OEM-KSF, FRANCE,	

Generated By Re-Engineered WIMS

Page 3 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PARENT EQUIPMENT - GENERAL SERVICE PUMP MOTOR NO.1 AND 2	
12	DGE57376	B5815758	4710715177961 / FLEXIBLE PIPE DIA 1.5 INCH	CNA LAN NETWORK	120 / METER	CAT 6 RJ45		3M USA		3M USA	TECHNICAL SPECIFICATION - pipe dia 1.5 inch GENERAL SPECIFICATION - pipe dia 1.5 inch	
13	DGB54581	BS 1740, UI27880267-10666	0267599235094 / ELBOW ROUND BLACK 0.75IN		92 / EACH/NUMBER						TECHNICAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b GENERAL SPECIFICATION - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade b	
14	DGP66796	NO DATA AVAILABLE	0461594638443 / TARGET PAPER GREY-50YDS		1400 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
15	SGB49409		0277702770041 / SPANNER FIXED DOUBLE ENDED OPEN JAW 16MM & 19MM	PAK PATTERN (GENERAL USE)	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
16	DGB54584		0267599235335 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		152 / EACH/NUMBER						TECHNICAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE 1/2 INCH. GENERAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE 1/2 INCH.	
17	SGB41223		0267599235092 / ELBOW ROUND		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp	

Generated By Re-Engineered WIMS

Page 4 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BLACK 0.50IN								pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n a GENERAL SPECIFICATION - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n a TECHNICAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm GENERAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm	
18	SGB56146		026759923534 9 / TEE PIPE EQUAL (GALVANISED) 03.00IN		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	SGB44817		026259000627 4 / RAT GUARD DIAMETER OF ROPE 5-6 1/2 INCH		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
20	SGB49412		021450214065 1 / BOLT AND NUT M 5 HEX HEAD SZ 2.00X0.187 IN		400 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 2.000 X 0.187 INCHES BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT GRADE: M 12 NUT THICKNESS: 12-14 MM GENERAL SPECIFICATION - SIZE: 2.000 X 0.187 INCHES BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT GRADE: M 12 NUT THICKNESS: 12-14 MM	
21	DGP60275		046150000845 3 / TARGETS PAPER BROWN SIZE 660 MM X1270 MM		1873 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE60223	GMS-38BA-07	491072513831 4 / ESD SHOES COVER WITH CONDUCTIVE STRAP	ESD LABORATORY EQUIPMENT	6 / EACH/NUMBER	NO DATA AVAILABLE		GR		ROHDE & SCHWARZ 2 INTL GMBH MUHLDO RFATRBE 15-81671 MUNICH	TECHNICAL SPECIFICATION - A. Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c. ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5 _Ω / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE	

Generated By Re-Engineered WIMS

Page 5 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL GENERAL SPECIFICATION - A. Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c. ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5 _Ω / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 _Ω to 108 _Ω GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 33% (± 1%) COTTON + 3% (± 1%) CONDUCTIVE FILAMENT c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 106 _Ω to 108 _Ω	
23	DGE38148	FEC 1735511	653270517259 3 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	6 / EACH/NUMBER			M/sDF Technologies & Services (Pvt)Ltd Building No 2-K,4th Floor, P.E.C.H.S Block-6,Shara-e-Faisal Karachi Tele No.021-34302153-4		GERMANY		
24	SGB62886	PVCSRH-0050 /SH2IN-SEW	472070529232 8 / spring hose 2" dia		51 / METER	PVCSRH-0050					TECHNICAL SPECIFICATION - Internal Dia: 2 Inch (50 mm) Outer Dia: 61 mm Working Pressure: 5 bar Bursting Pressure: 16 bar GENERAL SPECIFICATION - Internal Dia: 2 Inch (50 mm) Outer Dia: 61 mm Working Pressure: 5 bar Bursting Pressure: 16 bar	
25	DGD64538		003550000052 0 / UTENSILS COOKING		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND	

Generated By Re-Engineered WIMS

Page 6 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALUMINUM WITHOUT COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)								CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT	
26	DGD64535		003550000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG)		18 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT	
27	DGE13797	GGGH142	8415009353137 / HELMET SAFTY		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 brochure attached as document GENERAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 brochure attached as document	
28	DGE61553		8340705067915 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3-4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent & Iron Poles (Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY	

Generated By Re-Engineered WMS

Page 7 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											& FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3-4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent & Iron Poles (Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN	
29	DGE58501		8340705067915 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3-4 Ozs per m2. Inner: Inner Fold made of colored	

Generated By Re-Engineered WMS

Page 8 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADC	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent & Iron Poles (Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color, Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2, Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent & Iron Poles (Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN	
30	DGE57003		533070500725 2 / 04 PLY RUBBER BLANKETS		4 / EACH/UMBER						TECHNICAL SPECIFICATION - Size 53.5 cm x 48.5 cm 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36	

Generated By Re-Engineered WIMS

Page 9 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADC	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 53.5 CM X 48.5 CM								inches (for Roland Offset Printing Machine) GENERAL SPECIFICATION - Size 53.5 cm x 48.5 cm 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine)	
31	SGB43666	NO DATA AVAILABLE	5310PK506589 5 / NUT SZ- 16MM A/F 24MM HIGHT 13MM		150 / EACH/UMBER						TECHNICAL SPECIFICATION - MATERIAL: STAINLESS STEEL 316 GENERAL SPECIFICATION - MATERIAL: STAINLESS STEEL 316	
32	DGE13648		047659943040 1 / BRUSH WHITE WASH 2KNOT		5 / EACH/UMBER						TECHNICAL SPECIFICATION - a. Size : 8" b. Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market GENERAL SPECIFICATION - a. Size : 8" b. Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market	
33	SGB42547	0760 002 500	343971509837 8 / ELECTRODE HOLDER SAMPSON 500 C/P500AMP @ 60% PART#0760 002 500 APPROVED 2 EN-80874-11	WELDING GENERATOR	13 / EACH/UMBER						TECHNICAL SPECIFICATION - LOCAL SOURCE OF AVAILABILITY. BASE WELDING COMPANY STEEL HOUSE, WEST WHARF ROAD KARACHI, POST CODE 74000. PH: 021-32314531, 3220112, 32313132. FAX: 21-32310976, 32202931. E-mail: info@basewelding.com GENERAL SPECIFICATION - LOCAL SOURCE OF AVAILABILITY. BASE WELDING COMPANY STEEL HOUSE, WEST WHARF ROAD KARACHI, POST CODE 74000. PH: 021-32314531, 3220112, 32313132. FAX: 21-32310976, 32202931. E-mail: info@basewelding.com	
34	DGP66002		361070500723 7 / PAGE CORD TWIN COMPOSING		20 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items, 2. Acceptance Criteria Acceptable as	

Generated By Re-Engineered WIMS

Page 10 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection GENERAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers. set of forms, books and miscellaneous stationary items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection	
35	SGE600 85		531099124047 4 / NUT PLAIN HEX 3/8INBSW AFD.600THKO. 312		32 / TEN						TECHNICAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C) GENERAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C)	
36	SGE479 53	FP6F3	56400237482 8 / INSULATION SLEEVING TUBE		25 / EACH/NUMBER 1						TECHNICAL SPECIFICATION - SLEEVE SIZES: LENGTH: 06 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPECS.PICT ARE ATTACHED WITH WIMS NOTE: LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGASINT FOREIGN NSN OEM: FORTE PAKISTN GENERAL SPECIFICATION - SLEEVE SIZES: LENGTH: 06 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPECS.PICT ARE ATTACHED WITH WIMS NOTE: LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGASINT FOREIGN NSN OEM: FORTE PAKISTN	
37	SGE493 63	NO DATA AVAILAB LE	041350000013 2 / EAR DENFENDER-SMALL SIZE		1000 / PAIR	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	SGE495 30		813570508488 2 / TAPE TRANSPARENT ADHESIVE WATER	GENERAL USE.	180 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

Generated By R-Engineered WIMS

Page 11 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension	
			PROOFED WD. 12 MM LG. 06 MTR.										
39	DGE408 79	O/FLY 23X19FT, I/FLY 20X19FT	8340PK509784 1 / 400 LBS TENT/TP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANZOOR SONS KARACHI PAKISTAN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 08 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : mvs M BILAL textiles Mrs Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cinsuser. complete accessories to be incorporated to avoid complicationS at later stage GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR		

Generated By R-Engineered WIMS

Page 12 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
40	DGE21530	O/FLY 23X19FT. I/FLY 20X19FT	8340PK509764 1 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN. WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANZOOR SONS KARACHI PAKISTAN	2 / EACH/N UMBER						<p>POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s</p>	

Generated By Re-Engineered WIMS

Page 13 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
41	DGE61557	NO DATA AVAILABLE	834070501408 4 / TENT FOR CPOS AND SAILORS WT. 120 LBS		4 / EACH/N UMBER						<p>H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p>GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p>TECHNICAL SPECIFICATION - ons observation and annex b is enclosed as document a. Tent for CPOs and Sailors WT. 120 LBS along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2</p>	

Generated By Re-Engineered WIMS

Page 14 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall. Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.</p> <p>GENERAL SPECIFICATION - cins observation and annex b is enclosed as document a Tent for CPOs and Sailors WT. 120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.</p> <p>TECHNICAL SPECIFICATION - cins observation and annex b is enclosed as document a Tent for CPOs and Sailors WT. 120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also</p>	
42	DGE61822	NO DATA AVAILABLE	834070501408 4 / TENT FOR CPOS AND SAILORS WT. 120 LBS		9 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - cins observation and annex b is enclosed as document a Tent for CPOs and Sailors WT. 120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also</p>	

Generated By Re-Engineered WIMS

Page 15 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>required/compliance by seller.</p> <p>GENERAL SPECIFICATION - cins observation and annex b is enclosed as document a Tent for CPOs and Sailors WT. 120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.</p>	
43	SGE47952	4800	831289139716 0 / GLASS SEWING THREAD 03 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)	E&H VOL BELLOWS	6 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
44	SGD52128		027560000002 5 / MEASURING TAPE STEEL 1/2" x 300'		3 / EACH/NUMBER	NO DATA AVAILABLE					<p>TECHNICAL SPECIFICATION - Crescent Lufkin 1/2" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure - Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition GENERAL SPECIFICATION - Crescent Lufkin 1/2" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure - Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition</p>	
45	DGD583	NO DATA	003550000056		3 / SET	NO DATA					<p>TECHNICAL SPECIFICATION -</p>	

Generated By Re-Engineered WIMS

Page 16 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
	83	AVAILABLE	0 / COOKER PRESSURE-10 LITRES COMPLETE			AVAILABLE					Aluminum Food Grade (Lead Free) GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free)	
46	DGE48654	2822-025-00051	8020171012844 / SOFT BRUSH		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DGD26118	NO DATA AVAILABLE	0032500000133 / Fork Table Medium Common S/Steel		150 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest. GENERAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest	
48	DGP66078	727055-621	5908016641137 / HPE Ethernet 10Gb 2-port SFP+ Adapter		1 / EACH/NUMBER	HPE ETHERNET 10GB 2-PORT					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
49	DGP56620	C5-WDC09-855-BAA/CMW 9U	7125705141418 / 9U WALL MOUNT 19" CABINET	NET WORKING	1 / EACH/NUMBER	NO DATA AVAILABLE		CH		M/S RAISECOM SUITE NO.401A PANURAMA CENTRE 2 RAJA GHAZAN FAR ALI ROAD SADDAR KARACHI PHON NO. 021-35681550 -1	TECHNICAL SPECIFICATION - CONTECH BRAND GENERAL SPECIFICATION - CONTECH BRAND	
50	DGT34983	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI)	WOOD WORKS SHIPS&ESTABLISHMENT	8 / SHEET	NO DATA AVAILABLE		PK		SOURCE: M/S MEHRAN ART WOOD	TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL	

Generated By Re-Engineered WIMS

Page 17 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			TEAK COLOUR LAMINATION ONE SIDE, DENSITY 750 KG/CUB TO 850 KG/CUB. METER SIZE L:8 W: 4 TH: 8MM. MOISTURE RESISTANT							SHOP NO 9, PANJETANI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +02-21-32775064 .MOBILE 0322-2578654.	SPECIFICATION - SIZE Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
51	DGE58504	096-0240-004C	4020795152987 / ROPE NAVY FLEX 24 MM BROWN 3 STRAND POLYPROPYLENE (HAWSERLAID)	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL: +4589111213 FAX: +4589111212 E-MAIL: RANDERS.ROPE@RANDERS-REB.DK.	UK		TECHNICAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL: +4589111213 FAX: +4589111212 E-MAIL:RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS:TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE. GENERAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL: +4589111213 FAX: +4589111212 E-MAIL:RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS:TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.	

Generated By Re-Engineered WIMS

Page 18 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
52	DGP58350	12U	5995715208945 / RACK (12U)	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	1 / EACH/NUMBER	Aunet	AU12UB	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA		TECHNICAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix. GENERAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.	
53	SGE49515	2058051	8415145557607 / HAND GLOVES ALUMINIZED WITH PALM LEATHER HEAT	GLOVE	30 / PAIR	NIL	NA	HONEYWELL INTERNATIONAL INS 115 TABOR ROAD MORRIS PLAINS NJ 07950 USA NEW JERSEY	UK		TECHNICAL SPECIFICATION - DESCRIPTION CE CATEGORY: II INTERMEDIARY RISKS IN ACCORDANCE WITH STANDARDS: EN 420-2003 BASIC standards EN 388-2003 MECHANICAL HAZARDS EN 407-2004 HEAT HAZARDS EN 12 477-2000 TYPE A PROTECTION FOR WELDERS CHARACTERISTICS : COWHIDE SPLIT LEATHER GLOVE. GUNN CUT, WINGED THUMB, GAUNTLET TYPE. ALUMINISED KEVLAR BACK OF THE HAND WITH COTTON FLEECE LINER. HEAT RESISTANT SPLIT LEATHER PALM WITH COTTON FLEECE LINING. SPLIT LEATHER CUFF WITH COTTON FLEECE LINER ON PALM SIDE. ALUMINISED KELVAR CUFF WITH COTTON FLEECE LINER ON BACK SIDE. PRODUCT TECHNOLOGY: cut and sewn length: 35.5 cm thickness: leather only 1.1/1.3 mm harmlessness: in conformity with the european standards. GENERAL SPECIFICATION - DESCRIPTION CE CATEGORY: II INTERMEDIARY RISKS IN ACCORDANCE WITH STANDARDS: EN 420-2003 BASIC standards EN 388-2003 MECHANICAL HAZARDS EN 407-2004 HEAT HAZARDS EN 12 477-2000 TYPE A PROTECTION FOR WELDERS CHARACTERISTICS : COWHIDE SPLIT LEATHER	

Generated By Re-Engineered WIMS

Page 19 of 158

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
54	DGE67634	VE-ST-ALB-4211	1560705208750 / ANTI SKID STAIR STEP (42IN X 11IN)	STAIR CASES	60 / EACH/NUMBER	NIL	N/A	259, A-4, Akhtar Colony, Karachi 021-35385382	M/S VISION ENGINEER RING		GLOVE. GUNN CUT, WINGED THUMB, GAUNTLET TYPE. ALUMINISED KEVLAR BACK OF THE HAND WITH COTTON FLEECE LINER. HEAT RESISTANT SPLIT LEATHER PALM WITH COTTON FLEECE LINING. SPLIT LEATHER CUFF WITH COTTON FLEECE LINER ON PALM SIDE. ALUMINISED KELVAR CUFF WITH COTTON FLEECE LINER ON BACK SIDE. PRODUCT TECHNOLOGY: cut and sewn length: 35.5 cm thickness: leather only 1.1/1.3 mm harmlessness: in conformity with the european standards.	
55	DGE64185		0461590004058 / HEAD SCREEN FOR ELECTRIC WELDING WITH GLASS BLACK.		31 / EACH/NUMBER						TECHNICAL SPECIFICATION - ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 42 IN X 11 IN material grade: aluminium alloy 600 series. GENERAL SPECIFICATION - ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 42 IN X 11 IN material grade: aluminium alloy 600 series.	
											TECHNICAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11). Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection, standards: en166, en169, en175, & ce make : delta plus, france / uee. GENERAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (8 upto 11).	

Generated By Re-Engineered WIMS

Page 20 of 158

Designed & Developed By MTC