

HBL

HABIB BANK

حیب بینک

Deposit Slip

Customer Copy

Branch:	Date:	D	D	M	M	Y	Y	Y	Y	
Account Title اکاؤنٹ ہولڈر کا نام Public Procurement Regulatory Authority										
IBAN: آئی بی این PK17HABB0004540013100701										
Currency: <input type="checkbox"/> PKR <input type="checkbox"/> USD <input type="checkbox"/> EURO <input type="checkbox"/> GBP <input type="checkbox"/> JPY <input type="checkbox"/> Others	<input type="checkbox"/> Intercity <input type="checkbox"/> Within city <input type="checkbox"/> Same Branch									
Credit Card No.										
<input type="checkbox"/> CASH نقد	AMOUNT رقم									
BANK / BRANCH	CHEQUE/INSTRUMENT NO. چیک نمبر									
	Cash	15000/-								
TOTAL AMOUNT کل رقم										
Total Amount in Words: Fifteen thousand only									ملین	
Commission (if any)										
Depositor's Name مخبر کا نام Ashraf ulhaq	Online Cash Deposit									
Contact No. تلفون نمبر 03450767922	Branch: 0016-K.P.T. KARACHI									
Depositor's CNIC No. مخبر کی شناختی کارڈ نمبر 1101-1944489-3	Account: PUBLIC PROCUREMENT Date: 2024-11-15									
Depositor's Account No. مخبر کا اکاؤنٹ نمبر (For non-HBL/Walk-in Customers. Also attach CNIC Copy)	IBAN PK17HABB0004540013100701									
(For HBL Customers / Account Holders)	Amount *****15,000.00 PKR									
	Charges *****575.00									
	Teller BR30 31 Time 12.14.28.504000									
Received By: وصول کنندہ	Depositor's Signature دستخطی کنندہ				(As per Terms & Conditions on reverse) (Not official unless validated)					

17897666

TENDER BULLETIN

DATE & TIME 11/13/24 3:39 PM INVITATION TO TENDER TO BE OPENED ON 11/27/ 10:00 AM AND ITEM REQ BY

- CONDITIONS**
 1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONG WITH THEIR BIDS.
 2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
 3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGD31682		003250003201 1 / Knives Table Small		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) PN Crest engraved on knife Stainless Steel W/Grade SS 316 (Food Grade) GENERAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) PN Crest engraved on knife Stainless Steel W/Grade SS 316 (Food Grade)	
2	DGT09870	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	108 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag. 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag. 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%	
3	DGO69888	JE-01	732070520968 4 / STAINLESS STEEL JUICE EXTRACTOR		4 / EACH/NUMBER	UDZZ-A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 GENERAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED	

Generated By Ra-Engineered WMS

Page 1 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension	
4	DGT70230	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag. 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag. 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%		
5	DGP68989	CS-WDC09-855-BAW/CMW 9U	712570514141 8 / 9U WALL MOUNT 19" CABINET	NET WORKING	2 / EACH/NUMBER	NO DATA AVAILABLE		CH			M/S RAISECO M SUITE NO.401A PANURA MA CENTRE 2 RAJA GHAZAN FAR ALI ROAD SADDAR KARACHI PHON NO. 021-35601550 -1	TECHNICAL SPECIFICATION - CONTECH BRAND GENERAL SPECIFICATION - CONTECH BRAND	
6	DGE88988	ASN2S 1718 P3, EN143: 2000 P3 R	845570518127 6 / DISC IDENTITY RED FOR RESPIRATION AND HAVERSACK	NIL	520 / EACH/NUMBER		NIL	LOCAL MARKET	NIL		TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015)		
7	SGE54837	metabo 000862500	513015006222 1 / ELECTRIC DRILL MACHINE	DRILL MACHINE	4 / EACH/NUMBER	metabo SBE-710 (Impact Drill)	600862500	METABO-ALLEE 1 D-72622 NUERTINGEN GERMANY	METABO	GERMANY	TECHNICAL SPECIFICATION - OEM: METABO SBE 710 (800862500) IMPACT DRILL (220-240 V / 50 - 60 Hz); PLASTIC		

Generated By Ra-Engineered WMS

Page 2 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			13MM								CARRY CASE DRILLING IN METAL 4 M/S ² UNCERTAINTY OF MEASUREMENT K 1.5 M/S ² IMPACT DRILLING CONCRETE 18 M/S ² UNCERTAINTY OF MEASUREMENT K 1.5 M/S ² CHUCK CAPACITY 1.5 - 13 MM // 1/16 - 1/2" COLLAR DIAMETER 43 MM / 1 11/16" DRILL SPINDLE WITH HEXAGONAL RECESS 6.35 MM / 1/4" GENERAL SPECIFICATION - OEM: METABO SBE 710 (600682500) IMPACT DRILL (220-240 V / 50 - 60 Hz); PLASTIC CARRY CASE DRILLING IN METAL 4 M/S ² UNCERTAINTY OF MEASUREMENT K 1.5 M/S ² IMPACT DRILLING CONCRETE 18 M/S ² UNCERTAINTY OF MEASUREMENT K 1.5 M/S ² CHUCK CAPACITY 1.5 - 13 MM // 1/16 - 1/2" COLLAR DIAMETER 43 MM / 1 11/16" DRILL SPINDLE WITH HEXAGONAL RECESS 6.35 MM / 1/4"	
8	SGE881 45	NIL	05597944489 8 / INSULATION SLEEVE ELEC INT DIA 3MM THICK 0.500 MATER CERAMIC	GENERAL ELECTRIC USE	800 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DGE565 42		042159942563 7 / FILING CABINET SIZE, 4- DRAWERS W/LOCK combination AND COMPRESSOR PLATES GREY GAUGE SWG-22 SIZE		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - GAUGE SWG-22 SIZE; Width: 18 INCH; Dia: 24 1/2 INCH; HEIGHT: 52 INCH; MPBW CODE: 01-18-114 REQUIRED MATERIAL: STEEL. REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user GENERAL SPECIFICATION - GAUGE SWG-22 SIZE; Width: 18 INCH; Dia: 24 1/2 INCH; HEIGHT: 52 INCH; MPBW CODE: 01-18-114	

Generated By Re-Engineered WIMS

Page 3 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			W18 INCH								REQUIRED MATERIAL: STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	
10	DGE888 13	NO DATA AVAILABLE	041569923141 0 / SHEET PLASTIC TRANSPARENT LG 48 WD 36TH 0.125 MATERIAL METHYL METHACRYLATE PLAIN REF DTD 5592		64 / SHEET						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
11	SOB891 55		021258571068 7 / BAR STEEL CORROSION RESISTING H/R RD 1.25" WT PER FT 4.172LBS		8 / METER						TECHNICAL SPECIFICATION - BS 970 GRADE: 316S31 br-320 br970 en 57 GENERAL SPECIFICATION - BS 970 GRADE: 316S31 br-320 br970 en 57	
12	SOB886 62		026769923533 8 / Tee pipe (three sides equal) black		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS 1740/71 nominal bore size 1.00 inch (dimension 25 mm), corrosion resisting steel/ferrous alloy, thread type BSP (TPI 11) oem coc: required GENERAL SPECIFICATION - BS 1740/71 nominal bore size 1.00 inch (dimension 25 mm), corrosion resisting steel/ferrous alloy, thread type BSP (TPI 11) oem coc: required	
13	DGB892 23	SPEC BS 1387 (SIM)	026759923526 3 / COUPLING PIPE NOM BORE 0.500" GALVANISED SPEC BS 1387		60 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
14	SGH548 29		023169571524 3 / WIRE ROPE STEEL EXTRA SPECIAL GALVA LAY		2000 / METER						TECHNICAL SPECIFICATION - Circular Dia: 3/8" Strands in Rope: 08. Wires in Strands: 19 and Minimum Breaking Load = 6.5 Tons. (Reference NS 3200 Table 39) GENERAL SPECIFICATION -	

Generated By Re-Engineered WIMS

Page 4 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			OF RCPE RH CIRC 3/8"								Circular Dia: 3/8" Strands in Rope: 06, Wires in Strands: 19 and Minimum Breaking Load = 0.5 Tons (Reference NS 3200 Table 3/1)	
15	SGB08653	Material Grade EN 4140	02145903581 5 / BOLT MACHINE STEEL BSW HEX HD SZ 2.000X0.250X1/4" TP1 20.		50 / TEN						TECHNICAL SPECIFICATION - METRIAL GRADE EN 4140 GENERAL SPECIFICATION - METRIAL GRADE EN 4140	
16	SGB08987	MATERIAL GRADE EN 4140	021459041638 8 / BOLT MACHINE STEEL UNC HEX HD 0.75 X12X2 INCH TP1 10 (LOCAL)		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mrc REQUIRED GENERAL SPECIFICATION - material specs: PD 970:2005 material GRADE 708M40/42CRM04 OEM COC/mrc REQUIRED	
17	DGD65145		024770511752 1 / STOVE/BURNER GAS OPERATED (1/2 18" VALVE DIA 2")SEE COM FB	STOVE BURNER (EGLE STAR)	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - STOVE/BURNER GAS OPERATED (1/2 18" VALVE DIA 2")SEE COM FB EGLE STAR GENERAL SPECIFICATION - STOVE/BURNER GAS OPERATED(1/2 18" VALVE DIA 2")SEE COM FB EGLE STAR	
18	SGH68095	B5EN 10025 GRADE S275 JR	021259571072 3 / ANGLE STEEL CARBON BLACK 1-1/2X1-1/2X1/4"		200 / METER						TECHNICAL SPECIFICATION - B5EN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - B5EN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED	
19	SGH6854	SAFFIRE MODEL NM250, PART NO. 116324	028150281166 6 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	150 / EACH/NUMBER						TECHNICAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed. GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.	
20	SGB08797	TP1 14	530571503890 6 / SCREW	REPAIR FOR GRP BOATS	175 / TEN						TECHNICAL SPECIFICATION - material: stainless steel grade: 316	

Generated By Re-Engineered WMS

Page 5 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SELF TAPPING S/STEEL CSK HD 14 TP1SZ 2.000X0.250" LOCAL								HD 14 Dimension: diameter: 14mm Thread per inch: 2.000x0.250" GENERAL SPECIFICATION - material: stainless steel grade: 316 HD 14 Dimension: diameter: 14mm Thread per inch: 2.000x0.250"	
21	SGB52788	NO DATA AVAILAB E	026850000004 7 / WERHINIG MACHINE 50 KG - 300 kg		5 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - a. Make Model: OMEGA TAIWAKINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g GENERAL SPECIFICATION - a. Make Model: OMEGA TAIWAKINLEE/JSA b. Maximum weight limit: 300 KG c. Minimum weight limit: 50g	
22	DGD69269		773070504803 7 / DISH FLAT RICE 38CM BLUE CRESTED		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - 38CM GOLD CRESTED , MATERIAL PORCELAIN FOOD GRADE, CERA-E-NOOR (LOCAL) Dimension (l a Length 38 cm, width 24 cm and depth 1.5 cm) and material ceramic with Blue shell and FN Blue Crested GENERAL SPECIFICATION - 38CM GOLD CRESTED , MATERIAL PORCELAIN FOOD GRADE, CERA-E-NOOR (LOCAL) Dimension (l a Length 38 cm, width 24 cm and depth 1.5 cm) and material ceramic with Blue shell and FN Blue Crested	
23	DGD69268	NO DATA AVAILAB E	773070504805 3 / PLATE DINNER 26CM GOLDEN CRESTED		124 / EACH/NUMBER						TECHNICAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden crested GENERAL SPECIFICATION - 26CM GOLDEN CRESTED , MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL) plate dinner o/a dia 26 cm golden crested	
24	DGD69267		773070504807 5 / plate Dinner 23cm blue crested (as per		124 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material:PORCELIN GENERAL SPECIFICATION - Material: PORCELIN	

Generated By Re-Engineered WMS

Page 6 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			stock sample)									
25	DGE88099	NO DATA AVAILABLE	042350000002 / HOSPITAL STANDARD WARD BED LG.210CM,WD.91 CM,HIGHT 57CM.		7 / EACH/NUMBER	NO DATA AVAILABLE					<p>TECHNICAL SPECIFICATION - A: Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 2 1/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 61/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handles. j. two screw clanks one for head side and other for foot side. k. Maturine bag hooks with smooth clips- 02 in Nos. l. white powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crd 1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever for up and down of patient head 5. feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head end should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)</p> <p>GENERAL SPECIFICATION - B: Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 2 1/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 61/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handles. j. two screw clanks one for head side and</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											other for foot side. k. Maturine bag hooks with smooth clips- 02 in Nos. l. white powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crd 1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever for up and down of patient head 5. feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head end should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)	
26	DGE88029	NO DATA AVAILABLE	042350000002 / HOSPITAL STANDARD WARD BED LG.210CM,WD.91 CM,HIGHT 57CM.		7 / EACH/NUMBER	NO DATA AVAILABLE					<p>TECHNICAL SPECIFICATION - A: Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 2 1/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 61/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handles. j. two screw clanks one for head side and other for foot side. k. Maturine bag hooks with smooth clips- 02 in Nos. l. white powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crd 1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever for up and down of patient head 5. feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head end</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)</p> <p>GENERAL SPECIFICATION - A</p> <p>Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 21/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 6 1/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handas. j. two screw disks one for head side and other for foot side. k. Maturino bag hooks with smooth clips-02 in Nos. l. with powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crc</p> <p>1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever for up and down of patient head & feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head and should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)</p> <p>TECHNICAL SPECIFICATION - 1</p> <p>Material: Specification PSG-248, 100% Cotton Cloth. 2. color: Cedar Green BCC 80. 3. Print: White (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 06 in Number Length 25 feet. 5. Iron Pin: 08 in Number. Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759. Qty 06 in Number. Min dia at bottom</p>	
27	DGE060 51	NO DATA AVAILABL E	634050503928 1 / SHAMIANA SIZE 18 X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		3 / EACH/N UMBER							

Generated By Ra-Engineered WIMS

Page 9 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spais . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissao or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhater : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p>GENERAL SPECIFICATION - 1</p> <p>Material: Specification PSG-248, 100% Cotton Cloth. 2. color: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 06 in Number Length 25 feet. 5. Iron Pin: 08 in Number. Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759. Qty 06 in Number. Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spais . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissao or Teak wood of 2.5 feet length. 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhater : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p>TECHNICAL SPECIFICATION - 1</p> <p>Length 18 feet. 1. Width 7 feet. 2. Bumbo in single piece of Qanat. 3. 05 Pockets. 4. Qanat Cloth 100% cotton green printed in Double Ply. Lab Test Report: Soil and color shop PN Dockyard. ITEM SPECIFICATION</p>	
28	DGE064 85	NO DATA AVAILABL E	834050503928 2 / QANAT COMPLETE SIZE 18 X 7. OUT SIDE GREEN PRINTED		15 / EACH/N UMBER							

Generated By Ra-Engineered WIMS

Page 10 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			CLOTH, 100% COTTON								ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED. GENERAL SPECIFICATION - 1. Length 18 feet. 2. Width 7 feet. 3. Bamboo in single piece of Canal. 4. 05 Pockets. 5. Canal Cloth 100% cotton green printed in Double Ply. Lab Test Report: Sail and color shop PN Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON, BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR,BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED.	
29	DGT70237	NO DATA AVAILABLE	6100500000018 / Ply Wood GD-1, 7 ply (core and inner plies of Poplar. SIZE: L=8', W=4', TH=12MM	SPECEFCATION JM-2581 (E)	2336 / SQ FEET						TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT. 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993. 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993. 5. GLUE= BS 1203 : 1979. 6. PRESERVATION= BS 4072 : 1999. 7. PHYSICAL EVALUATION= BS 6566-6 : 1985. 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985. PART 1-8. TYPE-INT. 2. WOOD PRESERVATION AS PER BS-6566,Part-7,appendex A. 3. MOISTURE CONTENT= BS EN 322 : 1993. 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993. 5. GLUE= BS 1203 : 1979. 6. PRESERVATION= BS 4072 : 1999. 7. PHYSICAL EVALUATION= BS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											6566-6 : 1985. 8. DENSITY= BS EN 323 : 1993	
30	DGE63236	NO DATA AVAILABLE	8415PK5067442 / CLOTH PARASHUTE GRAY		550 / METER						TECHNICAL SPECIFICATION : Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery. GENERAL SPECIFICATION : Width must be 5-6 feet Water proof Rot proof colour of item is gray end user acceptance required on delivery.	
31	SGE68778	BA111131/5931052	8465725022150 / BAG CARRYING FOR DIVING EQUIPMENT		7 / EACH/NUMBER						TECHNICAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x 35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder straps/ 2 screwed valves. GENERAL SPECIFICATION - (1) Volume : 130 Liters (2) Dimension : 85 cm x 35 cm x 45 cm (3) Made from : Bag made with Tarpolin (4) Shape : U shape for opening (5) Appearance : 2 handles and shoulder straps/ 2 screwed valves.	
32	DGE68412		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8 X4. XX.60 to 0.70 MM	GENERAL USE	91 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794. GENERAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794.	
33	DGD68085		7320706012428 / ELECTRIC MEAT SLICERS BERKEL MODEL-825		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.	
34	DGD69668		0034546000434 / DISHES VEGETABLE ROUND E W W O COVER B/C		4 / EACH/NUMBER	CERA-E-NOOR					TECHNICAL SPECIFICATION - dia; 6" material; porcelain blue crested with pn logo. GENERAL SPECIFICATION - dia; 6" material; porcelain blue crested with pn logo.	
35	DGD69867	NO DATA AVAILABLE	0034546000448 / JUGS MILK CHINA 1 PINT		8 / EACH/NUMBER	CERA-E-NOOR					TECHNICAL SPECIFICATION - material ; porcelain capacity : 1 pint. golden crested with pn	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											logo GENERAL SPECIFICATION : material ; porcelain capacity : 1 pint golden created with an logo	
36	DGT70240	NO DATA AVAILABLE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swant)		38 / CUBIC FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION : SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION : SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
37	DGP88511	CORE I5	702570524809 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5 12 GEN					TECHNICAL SPECIFICATION : SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradeation. GENERAL SPECIFICATION : SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5	

Generated By Rx-Engineered WMS

Page 13 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradeation.	
38	DGP89371	CORE I5	702570524809 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN					TECHNICAL SPECIFICATION : SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed	

Generated By Rx-Engineered WMS

Page 14 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	MSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.	
30	DGT899 54	NIL	551070519913 4 / KAIL WOOD SLEEPER (GRADE-A (LOCAL))	KAIL WOOD (TIMBER)	110 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 18 FEET WIDTH: 6 TO 14 INCH THICKNESS: 6 TO 6 INCHES SPECIFICATIONS: psg: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 18 FEET WIDTH: 8 TO 14 INCH THICKNESS: 6 TO 6 INCHES SPECIFICATIONS: psg: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%	

S. No	LPR No	PART NO	MSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
40	DSM613 94	CBK5CS	422013112222 4 / C965CS ELECTRO PUMP		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Pump nature : centrifugal pump type: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange : 80 mm (gun metal) GENERAL SPECIFICATION - Pump nature : centrifugal pump type: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange : 80 mm (gun metal)	
41	DRG704 42	CHOCKS	173020853251 1 / CHOCKS AND LASHING		10 / SET	DRALLIM MC1 WEBBIN G TIE DOWN					TECHNICAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED GENERAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED	
42	DRG703 11	7.50-16LT OR 750R16	261020656757 9 / TYRE WITH TUBE SIZE 7.50-16LT 14PR (BRIDGESTON E)		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE 7.50-16LT 16 PLY SIZE OR 7.50-16 16 PLY MAX SPEED/ LOAD RATING: a. 10 KMH ,PRESSURE 575 KPA, LOAD 8250KG APROX b. 50 KMH ,PRESSURE 400 KPA, LOAD 5000KG APROX a. 10 KMH ,PRESSURE 575 KPA, LOAD 8250KG APROX RATING b. 50 KMH ,PRESSURE 400 KPA, LOAD 5000KG APROX GENERAL SPECIFICATION - SIZE 7.50-16LT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											16 PLY SIZE OR 7.50-16 16 PLY MAX SPEED/ LOAD RATING: a.10 KMH ,PRESSURE 575 KPA, LOAD 8250KG APPROX b. 50 KMH , PRESSURE 400 KPA, LOAD 5000KG APPROX a.10 KMH , PRESSURE 575 KPA, LOAD 8250KG APPROX RATING b. 50 KMH ,PRESSURE 400 KPA, LOAD 5000KG APPROX	
43	DSB67653	FLX-7232986-VTX /GSM166-16F210	472014342258 8 / FLEXIBLE PIPE/FLX 5 A PE40 DN10 R AC L1M200		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 06 BAR GENERAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 06 BAR	
44	DRG60514	NSL 8475	8415Z0853091 1 / HELMET		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE 50 TO 62 CM CAN BE ADJUSTED BY STRAP AS SHOWN IN PICTURE. SAFETY HELMET LIGHT WEIGHT YELLOW COLOR, HAVING ADJUSTABLE CHIN STRAP AS SHOWN IN PICTURE. GENERAL SPECIFICATION - SIZE 50 TO 62 CM CAN BE ADJUSTED BY STRAP AS SHOWN IN PICTURE. SAFETY HELMET LIGHT WEIGHT YELLOW COLOR, HAVING ADJUSTABLE CHIN STRAP AS SHOWN IN PICTURE.	
45	DRG70445	NSL 8475	8415Z0853091 1 / HELMET		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE 50 TO 62 CM CAN BE ADJUSTED BY STRAP AS SHOWN IN PICTURE. SAFETY HELMET LIGHT WEIGHT YELLOW COLOR, HAVING ADJUSTABLE CHIN STRAP AS SHOWN IN PICTURE. GENERAL SPECIFICATION - SIZE 50 TO 62 CM CAN BE ADJUSTED BY STRAP AS SHOWN IN PICTURE. SAFETY HELMET LIGHT WEIGHT YELLOW COLOR, HAVING ADJUSTABLE CHIN STRAP AS SHOWN IN PICTURE.	
46	DRG704	CYLINDER	166Z0854298		1 /	NO DATA					TECHNICAL SPECIFICATION - Dia:	

Generated By Re-Engineered WMS

Page 17 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
46		HPN2	3 / CYLINDER FOR HIGH PRESSURE NITROGEN GAS (4500 PSI)		EACH/NUMBER	AVAILAB LE					25 cm Approx Height: 155 cm Approx Width: 21 cm Approx 4500 PSI GENERAL SPECIFICATION - Dia: 25 cm Approx Height: 155 cm Approx Width: 21 cm Approx 4500 PSI	
47	DSB60719	32 K4231	491014338341 1 / SOLENOID VV COIL (OIL PANEL)		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DRG60116	SINIG	2925Z0523848 8 / SINGLE IGNITION		20 / EACH/NUMBER	GREAT POWER					TECHNICAL SPECIFICATION - SINGLE IGNITION GENERAL SPECIFICATION - SINGLE IGNITION	
49	DSB68746		4730TY671500 4 / COPPER ELBOW DIA 42MF		20 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Material: Copper Dia: 42 mm Degree: 90 ° Thickness: 1.5 mm Type: M/F GENERAL SPECIFICATION - Material: Copper Dia: 42 mm Degree: 90 ° Thickness: 1.5 mm Type: M/F	
50	DRG70499	205/75 R16C 110/108R R402 - 2022 OR 195/75 R16C	261070515849 6 / TYRE TUBELESS		6 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. TECHNICAL PARAMETERS: Tyre Size: 205/75R16C Type of Tyre: Rear 2. RATING Tread: 2 Polyester. 2. Steel Piles 2 Nylon Side Wall: 2. Polyester GENERAL SPECIFICATION - 1. TECHNICAL PARAMETERS: Tyre Size: 205/75R16C Type of Tyre: Rear 2. RATING Tread: 2 Polyester. 2. Steel Piles 2 Nylon Side Wall: 2. Polyester	
51	DRG60168	Z08544083	1730Z0854408 3 / PLATFORM AIRCRAFT SERVICING SIZE 4X5X7FT HEIGHT(M)		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - STEEL PIPE DIA 3/4INC. STEEL ANGLE TH 01CM WD 05CM STEP 1 TO 8 130X30CM, STEP09 130X90CM.02XSHORT WHEEL DIA 06CM.02XLONG WHEEL DIA 10CM, MATERIAL WOOD TRESTLE HEIGHT 220CM, TRESTLE LAST STEP GUARD GENERAL SPECIFICATION - STEEL PIPE DIA 3/4INC. STEEL ANGLE TH 01CM WD 05CM STEP 1 TO 8 130X30CM, STEP09 130X90CM.02XSHORT WHEEL DIA 06CM.02XLONG	

Generated By Re-Engineered WMS

Page 18 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
70	DSB70339	DSE 10.4 /6 PB-4, DSE 4.2/4 PB10	663572516965 5 / PROBE FOR ULTRASONIC THICKNESS GAUGE		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC, Doc No 7413.076 Part Code Cable Plug Order No, Housing No, DSE 4.2/4 PB10 1 m Lemo 00 1465.671.56	

Generated By Re-Engineered WMS

Page 22 of 55

Designed & Developed By MTC

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - Germany/KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1075 TC Basic Data TC. Doc No. 7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10.1 m Lemp 00 1465.671.55	
71	DRG89113	885SR	5999Z0523847 9 / HALL SENSOR (OP-88)		10 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - 885SR GENERAL SPECIFICATION - 885SR	
72	DSA70199	HPAC-STAC123-VTX	431054530077 8 / Air Cooler 1st, 2nd & 3rd Stage (FAISCEAU TUBULAIRE 30907C)		4 / EACH/NUMBER	HPAC-STAC123-VTX					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
73	SS868153	semix223gd12vc	560874528922 5 / IGBT 40 KVA		1 / EACH/NUMBER	SEMIX223GD12VC					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
74	DSA64731	4812268B	597714372487 9 / BALAI ELECTRIQUE 4812268B		14 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
75	DSB69071	1426-1110	651072516845 1 / WET/DRY VACUUM CLEANER		4 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 220-240 Volt 50/60 Hz 1500 Watts 2 Years Warranty Features: Powerful Motor User Friendly Locking System Water Brush (For Wet) Floor Brush (For Dry) Combination Brush Extension Wands Flexible Hose GENERAL SPECIFICATION - 220-240 Volt 50/60 Hz 1500 Watts 2 Years Warranty Features: Powerful Motor User Friendly Locking System Water Brush (For Wet) Floor Brush (For Dry) Combination Brush Extension Wands Flexible Hose	
76	DSB67951	FLX-7236417-VTX /GSM106-016-H-F510	472014399641 7 / FLEXIBLE PIPE/FLX 2 B PE40 DN25 RU LOM500		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 15 BAR GENERAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 15 BAR	

Generated By Re-Engineered WIMS

Page 23 of 56

Designed & Developed By MTC

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
77	DRG88525	1250	2940Z0522499 1 / AIR FILTER FOR AIR CENTER		1 / EACH/NUMBER	KAESER SXC 9 6916 03 E					TECHNICAL SPECIFICATION - a. Item Name Air Filter b. Parent Equipment KAESER SXC 4 Air Center c. Parent Assembly Air Filter Housing d. Manufacturer KAESER KOMPRESSOREN (Germany) e. Installed Quantity 01 f. Interval Of Replacement 3000Hrs g. Part Number 1250 h. NSN/ ZO Z0522499 i. Picture Attached j. Technical Specification Attached k. Publication Attached GENERAL SPECIFICATION - a. Item Name Air Filter b. Parent Equipment KAESER SXC 4 Air Center c. Parent Assembly Air Filter Housing d. Manufacturer KAESER KOMPRESSOREN (Germany) e. Installed Quantity 01 f. Interval Of Replacement 3000Hrs g. Part Number 1250 h. NSN/ ZO Z0522499 i. Picture Attached j. Technical Specification Attached k. Publication Attached	
78	DSA64733	A0013-010119B	597714372487 6 / BALAI ELECTRIQUE 4508700E		16 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DSA70428	GSM141-08F5MLEC215CN17-03	530814329937 5 / VIS CSM 141-08 INOX		280 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DRG89111	815SR	5999Z0523849 4 / HALL SENSOR (GP-123)		10 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - 815SR HALL SENSOR GENERAL SPECIFICATION - 815SR HALL SENSOR	
81	DRG70322	6X120 (6X15)	6140Z0653809 8 / BATTERY LEAD ACID 12 VOLTS,105 AH		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - LENGTH: 367MM W:173MM HEIGHT: 228MM LEAD ACID 12V,105AH, EXIDE 8X15 GENERAL SPECIFICATION - LENGTH: 367MM W:173MM HEIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15	
82	DRG70343	7208223 (4737755)	292015101318 5 / STARTER MOTOR		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

Generated By Re-Engineered WIMS

Page 24 of 56

Designed & Developed By MTC

81	DSB70488	008a103	6850TY671534 0 / MAGNETIC PARTICLE INSPECTION INK		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - packing detail: 10 x 400ml tin-can in each box brand: Magnaflex GENERAL SPECIFICATION - packing detail: 10 x 400ml tin-can in each box brand: Magnaflex	
----	----------	---------	--	--	------------------	-------------------	--	--	--	--	--	--

Generated By Re-Engineered WIMS

Page 25 of 56

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AVAILABLE	
83	DSB87655	FLX-7232985-VTX /A0291-002GF4	4720143382005 / FLEXIBLE PIPE/FLX 5 A PES40 DN15 R U L0MS		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 06 BAR/GENERAL SPECIFICATION - SATISFACTORY PRESSURE TESTING UP TO 06 BAR	
84	DRG68528	ZX6867058	5965Z06567058 / PNEUMATIC PIPE ADAPTER		20 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - make: Local made SPECIFICATIONS - Pneumatic pipe adapter used to connect high pressure pneumatic pipes of 1/2 inch diameter. - Available in two parts, male & female. - Made of steel or iron to handle high pressures. - Item commercially available in local market/GENERAL SPECIFICATION - make: Local made SPECIFICATIONS - Pneumatic pipe adapter used to connect high pressure pneumatic pipes of 1/2 inch diameter. - Available in two parts, male & female. - Made of steel or iron to handle high pressures. - Item commercially available in local market	
85	DSB60381	ORB-SVM70/V1/24/5V/1281	4810705312163 / SERVO-PERFORMANCE PROPORTIONAL DIRECTIONAL VALVE		3 / EACH/NUMBER	ORB-SVM70/V1/24/1506					TECHNICAL SPECIFICATION - MOUNTING INTERFACE THE STANDARD INCLUDES DETAILED DIMENSION FOR THE MOUNTING HOLES, PORTS, SIZE AND SPACING BETWEEN PORTS/GENERAL SPECIFICATION - MOUNTING INTERFACE THE STANDARD INCLUDES DETAILED DIMENSION FOR THE MOUNTING HOLES, PORTS, SIZE AND SPACING BETWEEN PORTS	
86	DRG68527	1450	2940Z05224992 / OIL SEPARATOR CARTRIDGE		2 / EACH/NUMBER	KAESER SXC 9 0916 03 E					TECHNICAL SPECIFICATION - Interval Of Replacement 3000Hrs/ Upon Change of Cooling Oil Storage of Air Center Upon storage of Air Center for 1 Year Change Oil Separator Cartridge/GENERAL	

Generated By Re-Engineered WMS

Page 25 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - Interval Of Replacement 3000Hrs/ Upon Change of Cooling Oil Storage of Air Center Upon storage of Air Center for 1 Year Change Oil Separator Cartridge.	
87	DUB66149	PVCSRH-0050 /5H20H-SEW	4720705292328 / spring hose 2" dia		33 / METER	PVCSRH-0050					TECHNICAL SPECIFICATION - Internal Dia: 2 Inch (50 mm) Outer Dia: 61 mm Working Pressure: 5 bar Bursting Pressure: 16 bar/GENERAL SPECIFICATION - Internal Dia: 2 Inch (50 mm) Outer Dia: 61 mm Working Pressure: 5 bar Bursting Pressure: 16 bar	
88	DSX87140	2A0268	5305765043021 / F-H-ALLEN SCREW M-10X50-OAL-1/16X50NOM500 IA10 ROUND HEAD 16MM		50 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Diameter: 10mm Length: 50mm (typ: round headed (allen key type) head dia: 16 mm material: stainless steel/GENERAL SPECIFICATION - Diameter: 10mm Length: 50mm (typ: round headed (allen key type) head dia: 16 mm material: stainless steel)	
89	DNG63801	NO DATA AVAILABLE	4730001802614 / UNION STEEL		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL STEEL 350PSI WOG NOM SIZE=8MM(1/4 INCHES) LENGTH MIN=38.37MM(1.555 INCHES) NPT=1/4-18 DASH NO: 22TA COUNTRY: USA/GENERAL SPECIFICATION - MATERIAL STEEL 250PSI WOG NOM SIZE=8MM(1/4 INCHES) LENGTH MIN=38.37MM(1.555 INCHES) NPT=1/4-18 DASH NO:22TA COUNTRY: USA	
90	SOB62885	5H11N-SEW	4720705292330 / flexible/Spring hose 1" dia		36 / METER	PVCSRH 019					TECHNICAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT SYNTHETIC RUBBER COMPOLIND B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 38 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL PILES	

Generated By Re-Engineered WMS

Page 26 of 55

Designed & Developed By MTC

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS. GENERAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT SYNTHETIC RUBBER COMPOUND. B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 36 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL FILES OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS.	
91	DGB60150	SH11M-SEW	472070529233 0 / flexible/Spring hose 1" dia		14 / METER	PVCSRH 019					TECHNICAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT SYNTHETIC RUBBER COMPOUND. B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 36 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL FILES OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS. GENERAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT SYNTHETIC RUBBER COMPOUND. B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 36 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL FILES OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS.	
92	DGT703	NIL	551070519913	KAIL WOOD	80 /	NIL	NIL	LOCAL MARKET	LOCAL		TECHNICAL SPECIFICATION -	

Generated By Re-Engineered WIMS

Page 27 of 55

Designed & Developed By MTC

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
03			4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	(TIMBER)	CUBIC FOOT				MARKET		size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%	
93	DGH54432	GDSK159001445	4010FT1007953 / Steel Wire Rope	9M Deck Crane	1 / EACH/NUMBER	GD-5K-159	0	DILOVASI ORGANIZE SAN BOL 4 NCU KISIM. KOCael		GURDES AN GEM MAK. SAN TIC. A.S	TECHNICAL SPECIFICATION - LENGTH: 45M THICKNESS: 14MM NO OF WIRES: 01 SAFE WORKING LOAD: 04 TONS TENSILE STRENGTH (MPA): 1670 MINIMUM BREAKING LOAD (KN): 121 DIA (MM): 14 APPROX. WEIGHT (KG/100M): 92.1 GENERAL SPECIFICATION - LENGTH: 45M THICKNESS: 14MM NO OF WIRES: 01 SAFE WORKING LOAD: 04 TONS TENSILE STRENGTH (MPA): 1670 MINIMUM BREAKING LOAD (KN): 121 DIA (MM): 14 APPROX. WEIGHT (KG/100M): 92.1	
94	DGH54431	GDHBMK4071445	4010FT1007919 / Steel Wire Rope	9M Combined Boat Crane	1 / EACH/NUMBER	GD-HBM-KS-407-PG&409	0	DILOVASI ORGANIZE SAN BOL 4 NCU KISIM. KOCael		GURDES AN GEM MAK. SAN TIC. A.S	TECHNICAL SPECIFICATION - Length: 45m Thickness: 14mm No of Wires: 01 Safe Working Load: 04 Tons TENSILE STRENGTH (MPA): 1670 MINIMUM BREAKING LOAD (KN): 121 DIA (MM): 14 APPROX. WEIGHT (KG/100M): 92.1 GENERAL SPECIFICATION - Length: 45m Thickness: 14mm No of Wires: 01 Safe Working Load: 04 Tons TENSILE STRENGTH (MPA): 1670 MINIMUM BREAKING LOAD (KN): 121 DIA (MM): 14 APPROX. WEIGHT (KG/100M): 92.1	
95	DGP67901	NIL	703570521056 9 / HPE DL 380 GEN 10 85FF CTO SERVER	SERVER DL380 PAKISTAN	1 / EACH/NUMBER	DL380	NA	LOCALY		HP	TECHNICAL SPECIFICATION - HPE DL 380 GEN 10 85FF CTO SERVER 1. PROCESSOR: 2 x intel (R), xeon(R), gold-5218 (3.25ghz/16-	

Generated By Re-Engineered WIMS

Page 28 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(INTEL(R), XEON(R), GOLD-S418)								CORE(I25w), flo. 2, pPROCESSOR KIT FOR hpe pROLIANT d380 gEN10, 4 X HPE 16 GB Dual Rank x 8 DDR4-2933 Registered Smart Memory Kit 3.6 X HPE 1.2TB SAS 12G ENTERPRISES 10K SFF (2.5 IN) SC, P408-A-RAID, 0.1,5.6,10.00, 2X500 RAIL, 3, RAM: 256GM HDD 06XHP, 1.2TB SSD HPE SMART MEMORY 408-A Permanent Storage SAS 12TB with RAM 256 GB GENERAL SPECIFICATION - HPE DL 380 GEN 10 8SFF CTO SERVER 1, PROCESSOR: 2 x intel(R), xeon (R), gold-5218 (3.25ghz/16-CORE/I25w), flo. 2, pPROCESSOR KIT FOR hpe pROLIANT d380 gEN10, 4 X HPE 16 GB Dual Rank x 8 DDR4-2933 Registered Smart Memory Kit 3.6 X HPE 1.2TB SAS 12G ENTERPRISES 10K SFF (2.5 IN) SC, P408-A-RAID, 0.1,5.6,10.00, 2X500 RAIL, 3, RAM: 256GM HDD 06XHP, 1.2TB SSD HPE SMART MEMORY 408-A Permanent Storage SAS 12TB with RAM 256 GB	
96	DGB635 64		028370000160 8 / INGOT, BRASS		62 / KILOGRAMME						TECHNICAL SPECIFICATION - Specification: BSEN 1982 OF 1999, GRADE ENCC7615 Compositional Designation: CuZn1604-C Weight of Ingot Range from Min 10 kg to Max 20 kg GENERAL SPECIFICATION - Specification: BSEN 1982 OF 1999, GRADE ENCC7615 Compositional Designation: CuZn1054-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
97	DGB678 38		041359023383 9 / MAT, FLOOR		50 / ROLL						TECHNICAL SPECIFICATION - B5 921 AUTHORITY BR 3020 mm: 7220-89-823-3636, FABRICATION METHOD: SOLID, LENGTH: 168.00 INCHES NOMINAL, WIDTH: 36.00 INCHES NOMINAL, THICKNESS: 0.375 INCHES NOMINAL, SHAPE RECTANGULAR, MATERIAL	

Generated By Ra-Engineered WMS

Page 29 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RUBBER, corrugated surface ; asbestos free rubber mix, 65-75 ihd fire characteristic smoke index less than 50 for 2.5 mm sample , toxicity index less than 5 per 100 gm sample, oxygen index greater than 30 temp index term index greater than 200 deg c GENERAL SPECIFICATION - B5 921 AUTHORITY BR 3020 mm: 7220-89-823-3636, FABRICATION METHOD: SOLID, LENGTH: 168.00 INCHES NOMINAL, WIDTH: 36.00 INCHES NOMINAL, THICKNESS: 0.375 INCHES NOMINAL, SHAPE RECTANGULAR, MATERIAL RUBBER, corrugated surface ; asbestos free rubber mix, 65-75 ihd fire characteristic smoke index less than 50 for 2.5 mm sample , toxicity index less than 5 per 100 gm sample, oxygen index greater than 30 temp index term index greater than 200 deg c	
98	DGB635 78		028359571120 9 / ROD ALUMINIUM BRONZE RD DIA 2 INCHES, WT/FT 10.44 (LB) U-O A6 TO 30 FOOT	SOLUTION HEAT TREATED (UNIT OF AVAILABIL	27 / METER						TECHNICAL SPECIFICATION - delstan 02-833 part 2 and iso 428 standards QUALIFEGENERAL SPECIFICATION - delstan 02-833 part 2 and iso 428 standards QUALIFEG	
99	DGE664 80	32A94250 03,BS 2019	033059942500 3 / TWINE NYLON COD LINE 3 STRO MIN 5KG STRENGTH 320 LBS LG=220FT	PROPELLER HUB	4 / EACH/UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DGD579 10	S NO 32 MODEL 2018	003550000038 6 / MINCING MACHINE MEDIUM		3 / EACH/UMBER	2018					TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM= 1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01	

Generated By Ra-Engineered WMS

Page 30 of 55

Designed & Developed By MTC

S	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	SR NO	DF PR	MANUF ADO	Availabil	Remarks	TECH / GEN SPECS	Dimension
106	DGB570	15	031070508791 5 / HIGH QUALITY DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	8 / EACH							TECHNICAL SPECIFICATION: Length: 5 Meter Width: 3 Meter Height of Tent: 3.50 Meter Height of Water: 1.00 Meter Fabric Material: Outer: Fold: First fold of 50 Ozs per sq. yard, 1st. proof & tongue and waterproof, 1st. proof & tongue proof cotton canvas, natural grey color. Middle: Fold made of black dye cotton, weighing for protection of sun rays, weight 3rd Ozs per sq. yard, Inner: Fold made of colored weaving of 150 GSM (50 Ozs per sq. yard) Accessories: All accessories (are required with Tent, Iron Pole, Centre & Side, Iron Hammer, Iron Stick for wale, Iron pins & Iron pegs & Repair Kit, P.E Ground Sheet of 160-200 Gram Size: 23 X 15 FT FT, 6 FOLD WALL HEIGHT: 5 FT 8 INCH DETACHABLE MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR CAMP OCC AND	
107	DGB61	47	0310500001 NO DATA 0 / CANVAS WATER COVER PROOF		5 / EACH	NO DATA						TECHNICAL SPECIFICATION: Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage Multiple uses for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM. Local Manufacture (Pakistan) Stock Sample / Reference Sample Material as per sample (indicated by hand)	

TH 16

S	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	SR NO	DF PR	MANUF ADO	Availabil	Remarks	TECH / GEN SPECS	Dimension
101	DGB64	22	3110099100 0 / BEARINGS BALL SKF 6312 ANNULAR SIZE 60.00 X130.00X1 00MM		1 / EACH							TECHNICAL SPECIFICATION: PART NO. SKF 6312-22, SIZE 60.00 X130.00X1.00MM GENERAL SPECIFICATION - PART NO. SKF 6312-22, SIZE 60.00X130.00X1.00MM	
102	DGB20	36C	31397998602 0 / MUREX SAFIRE 36C WELDCUT MUREX SAFIRE ARRESTOR CYLINDER ROULATOR JACKET/ENGINE		30 / EACH							TECHNICAL SPECIFICATION: STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED) GENERAL SPECIFICATION - STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED)	
103	DGB66	88	34397010085 4 / CERAMIC SAF CUPS APFT (USA) APFT CUPS APFT (USA) or SIZE 7, DIA 16 #7A ID 8, 10 MM equivalent)		100 / EACH							TECHNICAL SPECIFICATION: Ceramic Shield (cup) Size No. 7, Part No 10487, Murex WELDCRAFT (USA) or equivalent, Packing: 10 Pieces, Pack GENERAL SPECIFICATION: Ceramic shield (cup) Size No. 7, Part No 10487, Murex WELDCRAFT (USA) or equivalent, Packing: 10 Pieces, Part.	
104	DGB570	6213ZZ	31100715630 8 / BEARING BALL ANNULAR SKF 6213ZZ 65.00X120.00 X22.00MM (USA MAKE)		8 / EACH							TECHNICAL SPECIFICATION: NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DGB54Z	43	473070505480 NO DATA ANNULAR SKF 6213ZZ 65.00X120.00 X22.00MM (USA MAKE)		16 / EACH	LINE ON UPPER DECK						TECHNICAL SPECIFICATION: NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DGB33	EN140	03555903033 MACHINE 3 / SCREW STEEL BSW HEX HD #7/8D SZ 1.00X 0.7500		100 / EACH	NO DATA						TECHNICAL SPECIFICATION: material grade EN140 GENERAL SPECIFICATION - material grade EN140	

RPN-1450

AMP-04 PHASE-01 V-220 &
TECH / GEN SPECS

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2, waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 GM2 (5/6 Ozs per m2) Accessories All accessories are required with Tent & Iron Poles (Centre & Side) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E. Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETACHABLE MATERIAL DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR DEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN	
100	DGE62 64	NO DATA AVAILABL E	834080503926 0 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIE S (COMPLETE SET)		26 / EACH/IN UMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02, FOLDS: 02, 05 MS POLE 1. TENT ROOF: MADE OUT OF 450G M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS	

Generated By Ra-Engineered WIMS

Page 33 of 56

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											WHICH IS ROT PROOF, WATER PROOF. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CINS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01 GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02, FOLDS: 02, 05 MS POLE 1. TENT ROOF: MADE OUT OF 450G M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF, WATER PROOF. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CINS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01	
110	DGE634 56	NO DATA AVAILABL E	8415PK606744 2 / CLOTH PARASHUTE GRAY		500 / METER						TECHNICAL SPECIFICATION - Width must be 5-8 feet Water proof Rot proof colour of item is gray and user acceptance required on delivery GENERAL SPECIFICATION - Width must be 5-8 feet Water proof Rot proof colour of item is gray and user acceptance required on delivery	
111	SQE493		933099224609	GENERAL	75 /						TECHNICAL SPECIFICATION -	

Generated By Ra-Engineered WIMS

Page 34 of 56

Designed & Developed By MTC

S. No	Lpr No	PART NO	NSN / Description	QTY / DEMO	Mode	SR NO	MANUF ADO	Availabl	Tankar	TECH / GEN SPECS	Dimension
115	6	DSAT001	DSM141-1 VIS-CARRE-B-20CN17-0 (SCREW)	700 / EACHN	NO DATA					TECHNICAL SPECIFICATION, NO DATA AVAILABLE	
116	17	DRG585	2 01270 102/V08 REGULATOR JTL1000	1 / EACHN	NO DATA					TECHNICAL SPECIFICATION, ALTERNATE PART VHS45-100-L COMPLETE DESCRIPTION, ALTERNATE PART VHS45-100-L COMPLETE DESCRIPTION, VOLTAGE REGULATOR DEMICOUNTRY OF ORIGIN BASLER ELECTRIC COMPANY 12570 STATE RTE 143 HIGHLAND IL USA TEL: 618542351 FAX: 618542351 EMAIL: MATHODOGE@BASLER.COM PARENT EQUIPMENT MODEL: GROUND POWER UNIT JTL1000 100KVA MAKE NORTHERN AIRCRAFT PARTS (NAP) Ground Support Equipment, Ontario, LST 1C1 CANADA OEM COC YES IIF APPLICABLE GENERAL	

S. No	Lpr No	PART NO	NSN / Description	QTY / DEMO	Mode	SR NO	MANUF ADO	Availabl	Tankar	TECH / GEN SPECS	Dimension
112	43	DDG528	0035006045 7 UTENSIL COOKING ALUMINUM ALLOY WITH COVER 10.25" HEIGHT 10.25" THICKNESS 8	2 / EACHN	NO DATA					TECHNICAL SPECIFICATION: FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (Pb) AND CADMIUM (Cd) ALUMINUM GRADE 3003, NO BREAKAGE/ BENT	
113	6	DSB874	DDCNPL 53014295877 8 / SEAL MAT128-PLAIN (FSPJNB) 000478 (MESMA) (LOCAL) TELON STEEL & O-RING	370 / EACHN	NO DATA					TECHNICAL SPECIFICATION: Make: No France, item locally available through Mts Sbr Engineering Specification, item is combination of Teflon Seal, Rubberized O-ring & Nitrile pack. Material inspection: Material inspection criteria not held. Acceptance Criteria: item can be accepted upon physical inspection. GENERAL	
114	31	DRG685	205/75 R16C 261070515048 8 / TYRE TUBELESS R16C 110/109R 2022 OR R16C	6 / EACHN	NO DATA					TECHNICAL SPECIFICATION: 1 TECHNICAL SPECIFICATION - 1 TECHNICAL SPECIFICATION - GENERAL	
115	6	DSAT001	DSM141-1 VIS-CARRE-B-20CN17-0 (SCREW)	700 / EACHN	NO DATA					TECHNICAL SPECIFICATION, NO DATA AVAILABLE	
116	17	DRG585	2 01270 102/V08 REGULATOR JTL1000	1 / EACHN	NO DATA					TECHNICAL SPECIFICATION, ALTERNATE PART VHS45-100-L COMPLETE DESCRIPTION, ALTERNATE PART VHS45-100-L COMPLETE DESCRIPTION, VOLTAGE REGULATOR DEMICOUNTRY OF ORIGIN BASLER ELECTRIC COMPANY 12570 STATE RTE 143 HIGHLAND IL USA TEL: 618542351 FAX: 618542351 EMAIL: MATHODOGE@BASLER.COM PARENT EQUIPMENT MODEL: GROUND POWER UNIT JTL1000 100KVA MAKE NORTHERN AIRCRAFT PARTS (NAP) Ground Support Equipment, Ontario, LST 1C1 CANADA OEM COC YES IIF APPLICABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
117	DSB67479		8020TY8719549 / PAINTING BRUSH ANGULAR 45MM		560 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Name Bristle Painting Brush 45 mm b. Material Synthetic Bristle Material c. Bristle Color White+ Brown d. Bristle Width 45 mm e. Bristle Thickness 13.5 mm f. Handle Material Maple Wood g. Handle Color Natural Material GENERAL SPECIFICATION - a. Name Bristle Painting Brush 45 mm b. Material Synthetic Bristle Material c. Bristle Color White+ Brown d. Bristle Width 45 mm e. Bristle Thickness 13.5 mm f. Handle Material Maple Wood g. Handle Color Natural Material	
118	DSB67698	WIENTEK EM T3120A	5630705200400 / HMI 12 INCH		1 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DSB67393	31851	5825144820639 / CIRCUIT BREAKER (115V 60HZ BREAKER)		5 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 180 to 200Amps Photo attached GENERAL SPECIFICATION - 115 Volt 60Hz AC Network (BF system) breaker NSX250F TP 200Amps Adjustable 180 to 200Amps Photo attached	
120	DSM65983	C325100	6625735180298 / REPLACEMENT BATTERY CARTRIDGE 12V 17AH		8 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DSB67147	N310900503	4820745185917 / GLASS PTFE SEAT (VENTILATION FLAPPER FC 049)		4 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - PTFE TEFLON GRAPHITE SEAT size: outer dia: 270mm thickness: 13 mm color: black Material: Germany GENERAL SPECIFICATION - PTFE TEFLON GRAPHITE SEAT size: outer dia: 270mm thickness: 13 mm color: black Material: Germany	
122	DSB64738	A0D19-003056D	5677143724680 / BRUSH ELECTRICAL		109 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CONTACT (BALAI ELECTRIQUE)								AVAILABLE	
123	DSB61233	5305A818-45-45	5305144002131 / SCREW		357 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Bolt DIA M16 x Length 45mm Bolt HM16 X 45 X 45 mm CL 8.8 GENERAL SPECIFICATION - Bolt DIA M16 x Length 45mm Bolt HM16 X 45 X 45 mm CL 8.8	
124	DSM68915		4810997231524 / VALVE THERMOSTAT IC. 480BB1803		2 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION: THERMOSTATIC VALVE - 480 (See Figure 01) Manufacture: Amtel Controls S.A Type: 480-MET.2 (MH 1 to 9) or 48-MET2- No - 180189 BRONZE (SAGITTAIRE) Flowrate: 80 m ³ /h Passage diameter: 100mm Pressure drop: 0.2bar Working pressure: 3.5 bars Test Pressure 15 bars Temperature Setting: 820 C Operating range - start of opening - 700 C - fully open: 880 C Shock resistance: 20 g vertically 10 g horizontally Weight: 88 Kg GENERAL SPECIFICATION: THERMOSTATIC VALVE - 480 (See Figure 01) Manufacture: Amtel Controls S.A Type: 480-MET.2 (MH 1 to 9) or 48-MET2- No - 180189 BRONZE (SAGITTAIRE) Flowrate: 80 m ³ /h Passage diameter: 100mm Pressure drop: 0.2bar Working pressure: 3.5 bars Test Pressure 15 bars Temperature Setting: 820 C Operating range - start of opening - 700 C - fully open: 880 C Shock resistance: 20 g vertically 10 g horizontally Weight: 88 Kg	
125	DR064891	MD1245 / BDC500-SEW	8115206551883 / PLASTIC COVER SIZE LARGE		500 / EACH NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION: DIMENSION Jute: L285mm X W271mm X Collar: 100mm (drawing noted) THICKNESS: 1mm (Tolerance +/- 5%) MATERIAL: Acrylic GENERAL SPECIFICATION: DIMENSION Jute: L285mm X W271mm X Collar: 100mm (drawing	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY /	Model	SR NO	MANUF ADO	Available	Tender Remarks	TECH / GEN SPECS	Dimension
129	0	OSB650	E2511258 530514441790 L / SCREW HMS-105-20		29 /	NO DATA					TECHNICAL SPECIFICATION - Length: 105mm Dia: 8mm GENERAL SPECIFICATION - Length: 105mm Dia: 8mm	
130	2	DSB6714	533014356877 15 / CHDET17 9 / WATER BAUERLE 533014356877		190 /	NO DATA					TECHNICAL SPECIFICATION - SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NO) GENERAL SPECIFICATION - SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NO)	
131	02	DRG688	47202065 472020650500 0 / PIPE HIGH PRESSURE		1 /	NO DATA					TECHNICAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES OD:15.6	
132	15	DGT711	55107518913 4 / MAIL WOOD SLEEPER GRADE-A (LOCAL)		70 /	CUBIC FOOT		NIL		LOCAL MARKET	TECHNICAL SPECIFICATION - SIZE: LENGTH 8 TO 18 FEET WIDTH: 8 TO 14 INCH THICKNESS 6 TO 8 INCHES SPECIFICATIONS PAGE: 69 (FOR VISUAL INSPECTION ONL V) moisture content: 12% to 18%	
133	45	DGP713	702571632643 2 / HP 1.2TB		8 /	EACH	872285				TECHNICAL SPECIFICATION - 1.2 TB 2.5 INCH 128GBS 10K	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY /	Model	SR NO	MANUF ADO	Available	Tender Remarks	TECH / GEN SPECS	Dimension
128	51	DGE679	454070524596 0 / grom Baucosmo e electronic drain mixure with padding device chrome m.		8 /	EACH	01042200				TECHNICAL SPECIFICATION - GORME BAUCOSMO e infra red electronic drain mixer with mixing device chrome. ITEM IS TO BE USED IN ALL WASH BASINS FOR economicsl PROVISION OF WATERGENERAL SPECIFICATION GORME BAUCOSMO e infra red electronic drain mixer with mixing device chrome. ITEM IS TO BE USED IN ALL WASH BASINS FOR economicsl PROVISION OF WATER	
127	7	DSB0473	59771437448 1 / BLM ELECTRIQUE 0001818		17 /	NO DATA					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
126	71	DRG686	41020654294 8 / COMPRESSO R L P MOBILE 220/230V 50HZ 03 PHASE		2 /	EACH					TECHNICAL SPECIFICATION - 3 stage L/P compressor with following specifications - Maximum pressure of 130-150 PSI - 3 HP electric motor - 220 V / 3 phase - Auto start shut off - Safety cover on running belt - Running wheels - Tank capacity 200 Ltrs with pressure indicator - Pressure relief valve on tank - Drain valve of tank - Main electric ON/ OFF switch with request fuse - Approximate cost 250,000 excluding GST - Brand/ OEM any suitable From origin: Taiwan GENERAL SPECIFICATION - 3 stage L/P compressor with following specifications - Maximum pressure of 130-150 PSI - 3 HP electric motor - 220 V / 3 phase - Auto start shut off - Safety cover on running belt - Running wheels - Tank capacity 200 Ltrs with pressure indicator - Pressure relief valve on tank - Drain valve of tank - Main electric ON/ OFF switch with request fuse - Approximate cost 250,000 excluding GST - Brand/ OEM any suitable	

S. No	LPR No	PART NO	NSN / Description	R/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			2.5-INCH 5FF SAS 12GB/S 10K RPM HARD DISK		UMBER	002					RPM GENERAL SPECIFICATION - 1.2TB 2.5 INCH 12GB/S 10K RPM	
134	DGE713 33	AS925 1718 P3 EN143 2000 P3 R	845370518127 6 / DISC IDENTITY RED FOR RESPIRATION AND HAVERSACK.	NIL	40E / EACH/UMBER		NIL	LOCAL MARKET		NIL	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3480 dated 30 March 2015) GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3480 dated 30 March 2015)	
135	DGH712 10		712570513412 0 / UPRIGHT FRAME SIZE 4270MMX500MM	RACKING MATERIAL	15 / EACH/UMBER	NO DATA AVAILABLE		PK			TECHNICAL SPECIFICATION - MATERIAL GRADE: ASTM A500 STEEL GAUGE: 14-18 GAUGE HEIGHT: 8 TO 12 FEET THICKNESS: 2-3 MIL (50-75 MICRONS) SIZE: 4270MMX500MM COLOR: PAINT COAT FINISH IN STANDARD COLORS (E.G BLACK, WHITE, GRAY) MADE OF C.R.C PROFILE SECTION MATERIAL GRADE: SS-400 GENERAL SPECIFICATION - MATERIAL GRADE: ASTM A500 STEEL GAUGE: 14-18 GAUGE HEIGHT: 8 TO 12 FEET THICKNESS: 2-3 MIL (50-75 MICRONS) SIZE: 4270MMX500MM COLOR: PAINT COAT FINISH IN STANDARD COLORS (E.G BLACK, WHITE, GRAY) MADE OF C.R.C PROFILE SECTION MATERIAL GRADE: SS-400	
138	DGP711 75	4003DN	743570513883 2 / PRINTER HP LASER JET 2035HP LASER JET 2095HP LASER JET Pro 400/M401D/HP 402D/M402DN	COMPUTER	7 / EACH/UMBER	NO DATA AVAILABLE		PK		PAKISTAN	TECHNICAL SPECIFICATION - Laser, 296 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm/print speed (bw), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both GENERAL SPECIFICATION - Laser, 296 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm/print speed (bw)	

Generated By Re-Engineered WMS

Page 41 of 58

Designed & Developed by MTC

S. No	LPR No	PART NO	NSN / Description	R/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			M404DN								Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both	
137	DGE711 72	5A9-27017	626001074422 9 / LIGHT, CHEMILUMINE SCENT GREEN	REPLENISHMENT LIGHT	300 / EACH/UMBER			CYALLUME TECHNOLOGIES SA 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 3 04 42 37 17 80 04 42 37 17 98 325985622 XFARCY@CYALLUME.COM WWW.CYALLUME.COM		CYALUM E TECHNOLOGIES	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
138	DGP712 91	MFP M130FW / mfp 137fw/42b 64e	743570512798 4 / PRINTER/SCANNER HP-2573 PHOTO SMART(3 IN ONE)	PRINTER/SCANNER	1 / SET	MFP M130fw/MFP 137FW4 ZB84A		PK		pakistan	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
139	DGP894 55		046159463944 2 / TARGET PAPER LIGHT GREEN FOR REVOLVER 20YDS		4000 / EACH/UMBER						TECHNICAL SPECIFICATION - If spec of item not showing full contact to it department Size: 25 x 35" Color: Light Green Material: Paper Sport Type: Field shooting GENERAL SPECIFICATION - If spec of item not showing full contact to it department Size: 25 x 35" Color: Green Material: Paper Sport Type: Field shooting	Light
140	DGB715 90		021459033121 0 / STUD. PLAIN-85W-THRED-0.75-INCH-2.50-INCH LTH OF THREAD METAL		400 / EACH/UMBER						TECHNICAL SPECIFICATION - 0.75 x 2.5 inch, 05-4140 GENERAL SPECIFICATION - 0.75 x 2.5 inch, 05-4140	
141	DGE895 81	NIL	036068923712 8 / ROPE	MIN BRKKG STRENGTH	480 / FATHO						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE	

Generated By Re-Engineered WMS

Page 42 of 58

Designed & Developed by MTC

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	SR NO	OF PR	MANUF ADO	Availabl	Tender Remarks	TECH / GEN SPECS	Dimension
44	DGP713		057569009492 2 / TP ROLL 2 PLY COMPLETE WITH ONE TIME CARBON PAPER COMPLETE		TELEPRINTER, 320 / 11000 SV / ROLL							8.25 INCH 11. END PROTECTION OF CORE SPOOL BY PLASTIC COVER ON BOTH END OF CORESPOOL. 14. END INDICATOR TO BE MARKED. END INDICATOR IN RED COLOUR OR GREEN COLOUR. 15. PACKING. EACH TP ROLL WRAPPED/ PACKED IN POLYTHENE BAG & FURTHER 12 TP ROLL ARE PACKED IN A CARO BOARD BOX. 16. TENDER SAMPLE AS PER SAMPLE TO BE APPROVED BY STATIONERY BOARD GENERAL SPECIFICATION. TECHNICAL DATA OF TP ROLL 2 PLY: PAPER. PEARL WHITE PRINTED PAPER. 2. QUALITY/ STRENGTH OF PAPER. HIGHWOOD STRENGTH OF PAPER. 3. GSM OF PAPER. 63 GSM ± 5%. 4. QUALITY OF CARBON PAPER. HIGH STRENGTH. INCLUSIVE OF COLOUR. CHEMICAL AND WAX QUALITY GIVEN GOOD PRINTING ON OTHER COPY. 5. NO. OF CARBON PAPER. ONE LAYER OF CARBON PAPER. 6. GSM OF CARBON PAPER. 22 GSM ± 5%. 7. OR EQUIVALENT BRAND. 8. WIDTH OF ROLL. 8.25 INCH 9. LENGTH OF ROLL. 35 METER 10.1 METER. IN ONE PLACE REQUIRED ONLY. 10. DIA OF INNER CORE SPOOL. 01 INCH 11. DIA OF OUTER CORE SPOOL. 1.20 INCH 12. LENGTH OF CORE SPOOL.	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	SR NO	OF PR	MANUF ADO	Availabl	Tender Remarks	TECH / GEN SPECS	Dimension
43	DGP713		057569009492 2 / TP ROLL 2 PLY COMPLETE WITH ONE TIME CARBON PAPER COMPLETE		TELEPRINTER, 320 / 11000 SV / ROLL							8.25 INCH 11. END PROTECTION OF CORE SPOOL BY PLASTIC COVER ON BOTH END OF CORESPOOL. 14. END INDICATOR TO BE MARKED. END INDICATOR IN RED COLOUR OR GREEN COLOUR. 15. PACKING. EACH TP ROLL WRAPPED/ PACKED IN POLYTHENE BAG & FURTHER 12 TP ROLL ARE PACKED IN A CARO BOARD BOX. 16. TENDER SAMPLE AS PER SAMPLE TO BE APPROVED BY STATIONERY BOARD GENERAL SPECIFICATION. TECHNICAL DATA OF TP ROLL 2 PLY: PAPER. PEARL WHITE PRINTED PAPER. 2. QUALITY/ STRENGTH OF PAPER. HIGHWOOD STRENGTH OF PAPER. 3. GSM OF PAPER. 63 GSM ± 5%. 4. QUALITY OF CARBON PAPER. HIGH STRENGTH. INCLUSIVE OF COLOUR. CHEMICAL AND WAX QUALITY GIVEN GOOD PRINTING ON OTHER COPY. 5. NO. OF CARBON PAPER. ONE LAYER OF CARBON PAPER. 6. GSM OF CARBON PAPER. 22 GSM ± 5%. 7. OR EQUIVALENT BRAND. 8. WIDTH OF ROLL. 8.25 INCH 9. LENGTH OF ROLL. 35 METER 10.1 METER. IN ONE PLACE REQUIRED ONLY. 10. DIA OF INNER CORE SPOOL. 01 INCH 11. DIA OF OUTER CORE SPOOL. 1.20 INCH 12. LENGTH OF CORE SPOOL.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ROLL WRAPPED/ PACKED IN POLYTHENE BAG & FURTHER 12 TP ROLL ARE PACKED IN A CARD BOARD BOX. 16. TENDER SAMPLE: AS PER SAMPLE TO BE APPROVED BY STATIONERY BOARD.	
143	DGH67703		056156521840 7 / CABLE ELECT ELASTOMER C.LFH. 02CORE COND30/250 440V 23AMP	NIL	240 / METER						TECHNICAL SPECIFICATION - DEFSTAN 02-527 AND DEFSTAN 61-12 PART 25 DEFSTAN 02-526 ISSUE-3/2006 T-67GENERAL SPECIFICATION - DEFSTAN 02-527 AND DEFSTAN 61-12 PART 25 DEFSTAN 02-526 ISSUE-3/2006 T- 67	
144	DGP70571		561070500685 7 / CARD ALABASTER GSM 290 ±5% SIZE 22X28 PKT 100 SHEETS		123 / PACKET						TECHNICAL SPECIFICATION - weight of alabaster card: (290 ± 5%) size: (22" x 28") each packet contains 100 sheets as per sample provided by pccpc card will accepted after test printingGENERAL SPECIFICATION - weight of alabaster card: (290 ± 5%) size: (22" x 28") each packet contains 100 sheets as per sample provided by pccpc card will accepted after test printing	
145	DGE71173	549- 27077PF	626001178555 0 / LIGHT, CHEMILUMINE SCENT Birch BLUE	REPLENISHM ENT LIGHT	200 / EACH NUMB						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DGE68527	NO DATA AVAILABL E	030050000013 6 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	585 / KLOGRAMME	NO DATA AVAILABL E					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREADCM: WARP = 24/25 . WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREADCM: WARP = 24/25 . WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX)	

Generated By Re-Engineered WMS

Page 45 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SCOURING LOSS: 1% (MAX)	
147	DGT71111	NO DATA AVAILABL E	010050000001 8 / Ply Wood GD-1, 7 ply (core and inner plies of Paper SIZE: L=8', W=4', TH=12MM)	SPECEFIGATI ON UM-2551 (E	2856 / SQ FEET	NO DATA AVAILABL E					TECHNICAL SPECIFICATION - 1. BS-6566 OF 1985, PART 1-8, TYPE- INT, 2. WOOD PRESERVATION AS PER BS-6566, Part 7, appendix A, 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 1979, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993 GENERAL SPECIFICATION - 1. BS-6566 OF 1985, PART 1-8, TYPE-INT, 2. WOOD PRESERVATION AS PER BS-6566, Part 7, appendix A, 3. MOISTURE CONTENT= BS EN 322 : 1993, 4. BONDING QUALITY= BS 314-1 : 2004 AND BS EN 314-2 : 1993, 5. GLUE= BS 1203 : 1979, 6. PRESERVATION= BS 4072 : 1999, 7. PHYSICAL EVALUATION= BS 6566-6 : 1985, 8. DENSITY= BS EN 323 : 1993	
148	DGT71113	NO DATA AVAILABL E	010050000081 5 / PLY WOOD GRADE-1, 5 PLY		800 / SQ FEET	NO DATA AVAILABL E					TECHNICAL SPECIFICATION - SIZE LENGTH=6 FEET, WIDTH=4 FEET, THICKNESS=06 MM±1MM) SPECIFICATION: 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVOLUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 GENERAL SPECIFICATION - SIZE LENGTH=6 FEET, WIDTH=4 FEET, THICKNESS=06 MM±1MM) SPECIFICATION: 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5.	

Generated By Re-Engineered WMS

Page 46 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend); 3. Hard Disk= 1TB SATA/SSD; 4. Keyboard= USB (3d Optical); 5. Mouse= USB (Optical LED); 6. LED= 18.5" (Min) or higher (same brand); 7. LAN= Yes (Built in 10/100/1000); 8. Warranty= Minimum 01 YEAR or as provided by OEM; 9. Operating System= Windows 10 Professional or Above Key Sticker only; 10. Miscellaneous requirements: a. OEM sealed genuine PC; b. Authorized Dealer/ OEM COC; c. Certificate of genuineness; d. Online PC verification; e. PC without modification/ upgradeation. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB; 4 Core or above); Intel® Graphic Card (Min 2GB shared/ dedicated); 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend); 3. Hard Disk= 1TB SATA/SSD; 4. Keyboard= USB (3d Optical); 5. Mouse= USB (Optical LED); 6. LED= 18.5" (Min) or higher (same brand); 7. LAN= Yes (Built in 10/100/1000); 8. Warranty= Minimum 01 YEAR or as provided by OEM; 9. Operating System= Windows 10 Professional or Above Key Sticker only; 10. Miscellaneous requirements: a. OEM sealed genuine PC; b. Authorized Dealer/ OEM COC; c. Certificate of genuineness; d. Online PC verification; e. PC without modification/ upgradeation.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
165	DGP715 31	CORE I5	702570524609 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5 12 GEN					<p>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB; 4 Core or above); Intel® Graphic Card (Min 2GB shared/ dedicated); 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend); 3. Hard Disk= 1TB SATA/SSD; 4. Keyboard= USB (3d Optical); 5. Mouse= USB (Optical LED); 6. LED= 18.5" (Min) or higher (same brand); 7. LAN= Yes (Built in 10/100/1000); 8. Warranty= Minimum 01 YEAR or as provided by OEM; 9. Operating System= Windows 10 Professional or Above Key Sticker only; 10. Miscellaneous requirements: a. OEM sealed genuine PC; b. Authorized Dealer/ OEM COC; c. Certificate of genuineness; d. Online PC verification; e. PC without modification/ upgradeation. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 8 MB; 4 Core or above); Intel® Graphic Card (Min 2GB shared/ dedicated); 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend); 3. Hard Disk= 1TB SATA/SSD; 4. Keyboard= USB (3d Optical); 5. Mouse= USB (Optical LED); 6. LED= 18.5" (Min) or higher (same brand); 7. LAN= Yes (Built in 10/100/1000); 8. Warranty= Minimum 01 YEAR or as provided by OEM; 9.</p>	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PAPER) WOOD FREE									
154	DGP706 32		751070504225 9 / PLAIN PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	STATIONERY NA105	3 / REAM						TECHNICAL SPECIFICATION - PLAIN PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES, VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE GENERAL SPECIFICATION - PLAIN PAPER (OFF SET)VRG SHEET 80GSM ± 5% SIZE 610X914MM OR 24X36 INCHES,VRG,COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	
155	DGP894 52		048154800451 8 / TARGET PAPER		2000 / EACH/NUMBER						TECHNICAL SPECIFICATION - size: 21 inches x 21 inches (width x length) GSM: 125 GSM GENERAL SPECIFICATION - size: 21 inches x 21 inches (width x length) GSM: 125 GSM	
156	DGP713 18	NO DATA AVAILAB E	005050000011 4 / PAPER, TYPING, LARGE, GSM40±5%, WHITE, REAMOF500G HEEL SIZEA-04 210X297MM		356 / REAM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB E GENERAL SPECIFICATION - NO DATA AVAILAB E	
157	DGE713 3x	NO DATA AVAILAB E	834570511938 2 / VELVET GREEN W=54" L=25 Yard Min	PRESENTATIO N VIP ITEM	410 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILAB E GENERAL SPECIFICATION - NO DATA AVAILAB E	
158	DGT711 14	NO DATA AVAILAB E	010050000004 3 / Timber Gurjan, Grade-1 (Red pine) SLEEPER seasoned (swan)		35 / CUBIC FOOT	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30%	

Generated By Re-Engineered WIMS

Page 49 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
159	DSB6609 0	MAT101-0002F65	868514511777 1 / REMOTE THERMOMETER DIAM100 TYPE EQ120 CAP15M		8 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB E GENERAL SPECIFICATION - NO DATA AVAILAB E	
160	DGP715 51	1685k 7500h	702570527485 2 / led tv 65"		1 / PCS	KD65X 7500H					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
161	DSB6360 3	201395	823014481901 2 / FPN TYPE PORTABLE LIGHT CELLS		22 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILAB E GENERAL SPECIFICATION - NO DATA AVAILAB E	
162	DSB6510 2	4X15FALU-LED	532012152783 1 / RIVET, GESIPA-TET-FRA-4X15		6408 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Standard Blind Rivet - ALU/Steel - Dome head Diameter 4mm Length 15mm GENERAL SPECIFICATION - Standard Blind Rivet - ALU/Steel - Dome head Diameter 4mm Length 15mm	
163	DSB6706 7	TAQ-700 AIR ANGLE GRINDER/ NKS - NK2201G1	009006807298 7 / PNEUMATIC ANGLE GRINDER K/L12 OR 700NA		9 / EACH/NUMBER	taq-700 q/INK228 1G1					TECHNICAL SPECIFICATION - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" GENERAL SPECIFICATION - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	
164	DGP695 54	780081-01	702501616726 1 / 1.2 TB SSD/ DISK DRIVE UNIT		1 / EACH/NUMBER	1.2 TB SSD					TECHNICAL SPECIFICATION - 1.2 TB SSD GENERAL SPECIFICATION - 1.2 TB SSD	
165	DGP713 14	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		1 / SET	CORE I5 12 GEN					TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/SUS/LENOVO): 1. CPU Technology: Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory: Minimum 8 GB	

Generated By Re-Engineered WIMS

Page 50 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Operating System= Windows 10 Professional or Above Key Sticker only. 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgrade.	
167	DGP71371	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 I2 GEN					TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only. 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgrade. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel ® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB	

Generated By Re-Engineered WMS

Page 53 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only. 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgrade.	
168	DSB67488	LW-PM-14-3KVTX/LW-PM-14-VTX (LOCAL)	5310T0525157 7 / lock washer dn14 (LOCAL)		2940 / EACH/ NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
169	DSX84237	2AFD48	530575506266 2 / H H SCREW 8X40MM STEEL		352 / EACH/ NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
170	DSA68094	TAG-400	5100TY673014 7 / PNEUMATIC GRINDER 4"		5 / EACH/ NUMBER	TAG-40FRH					TECHNICAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODER: TAG-40FRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN GENERAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODER: TAG-40FRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN	
171	DSA33812		094038656700 3 / RUBBER		500 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SIZE - LENGTH =50 FEET WIDTH = 1	

Generated By Re-Engineered WMS

Page 54 of 55

Designed & Developed By MTC

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PACKING (RUBBER) MOLTOPRENE 16X2 (ONE ROLL 50 FEET)			LE					inch THICKNESS =3MM GENERAL SPECIFICATION - SIZE: LENGTH =50 FEET WIDTH= 1 inch THICKNESS =3MM	
172	DGE713 32	YCR105 or 1260	630578516309 0 / CERAMIC FIBER CLOTH	GENERAL USE	372 / METER	YCR105		OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI 86-574-63531211.63531433.		PANASONIC SADDAR KARACHI TECHNO POWER SYSTEM	<p>TECHNICAL SPECIFICATION - size: width 60.00 in thickness: 48 mils length: 50.00 yards weight: 24.00 oz/ sq yd colour: white temperature resistance: 700 degree centigrade max thermal conductivity 0.16 w/m OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI NINGBO ZHEJIANG CHINA ZIA HOSPITAL CODE 315333 TEL: 86-574-63531211.63531433.</p> <p>GENERAL SPECIFICATION - size: width 60.00 in thickness: 48 mils length: 50.00 yards weight: 24.00 oz/ sq yd colour: white temperature resistance: 700 degree centigrade max thermal conductivity 0.16 w/m OEM:CHINA MANUFACTURERS NINGBO RUIFENG SEALING MATERIAL COMPANY LTD KUANGVAN TOWN CIXI NINGBO ZHEJIANG CHINA ZIA HOSPITAL CODE 315333 TEL:86-574-63531211.63531433.</p>	