

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 20/11/2024

225000.00

Bank A/c No PK17HABB30004540013100701

225000.00

In Words Rs TWO HUNDRED TWENTY-FIVE THOUSAND

For C N A
(Signature of Offr Signing the cheque)

Initial
Supdt Audit Sec

Initial
Officer OI/C Audit Sec

To HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD
P.P.R.A
PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To LP Division
2. LAO (NAVY) NSD KARACHI

TENDER BULLETIN

12/18/24 10:08 AM

TENDER CLOSING/OPENING DAE: 01/01/2025

CONDITIONS

- NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONG WITH THEIR BIDS
- FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS
- LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM

S.No	LPR No	PART NO	NSN / Description	IV/Equipm ent	QTY / DENO	Model	MANUF ADD	TECH/ GEN/ SPECS
1	SGE68778	BA111131 / 5931052	8465725022150 / BAG CARRYING FOR DIVING EQUIPMENT		7 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - (1) Volume - 130 Liters (2) Dimension - 85 cm x35 cm x 45 cm (3) Made from - Bag made with Tarpon (4) Shape - U shape for opening (5) Appearance - 2 handles and shoulder straps/ 2 screwed valves GENERAL SPECIFICATION - (1) Volume - 130 Liters (2) Dimension - 85 cm x35 cm x 45 cm (3) Made from - Bag made with Tarpon (4) Shape - U shape for opening (5) Appearance - 2 handles and shoulder straps/ 2 screwed valves
2	DGE69651	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		3 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - 1 Material: Specification PSG-248, 100% Cotton Cloth, 2. strap: Cedar Green BCC 80 3. Pin: 06 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759. Qty: 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle: qty 01 8. Handle material: Khatua/Sasoo or Teak wood of 2.5 feet length. 9. Eyesls brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather: Piece inset in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhalar: 06 in Nos Ropes: 06 in Nos Nails: 09 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1 Material: Specification PSG-248, 100% Cotton Cloth, 2. strap: Cedar Green BCC 80 3. Pin: 06 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759. Qty: 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle: qty 01 8. Handle material: Khatua/Sasoo or Teak wood of 2.5 feet length. 9. Eyesls brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather: Piece inset in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhalar: 06 in Nos Ropes: 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos
3	SGE69145	NIL	0559794444888 / INSULATION SLEEVE ELEC INT DIA 3MM THICK 0.500 MATER CERAMIC	GENERAL ELECTRIC USE	400 / METRE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
4	SGE49351		9330992246090 / PLASTIC SHEET LAMINATED COLOUR WHITE 8.X4.X0.80 to 0.70MM	GENERAL USE	78 / SHEET			TECHNICAL SPECIFICATION - Size: L: 8mm, w: 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 GENERAL SPECIFICATION - Size: L: 8mm, w: 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794
5	DGE71439	100-85F	7920993008997 / CLEANING LINT FREE CLOTH (GUC ITEM)	CLEANING CLOTH	106 / EACH/ NUMB ER	NO DATA AVAILABLE	UK	TECHNICAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible pilling generation. Type: Knitted Pattern. Line structure Weight: (200-270) GSM (Calculated with the help of GSM cutting and measuring scale). Colour: White. Blue absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gulbo test method). Cutting: Laser cut sealed edges (± 0.5mm accuracy). GENERAL SPECIFICATION - Material: 100% polyester made with continuous filament yarn for lowest possible pilling generation. Type: Knitted Pattern. Line structure Weight: (200-270) GSM (Calculated with the help of GSM cutting and measuring scale). Colour: White. Blue Absorption: 354.7 g/sqm in water Rate of Absorbency: below 1 second Lint Free: less than 30 counts of 25 micron above particles (Gulbo test method). Cutting: Laser cut sealed edges (± 0.5mm accuracy)
6	SGE47952	4820	8310991397160 / GLASS SEWING THREAD 03 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)	SEWING BELLOW S	6 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
7	DGE40879	OFLY 23X19FT / IFLY 23X19FT	8340PK5097641 / 400 LBS TENT/ IP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANZOO R SONS KARACHI PAKISTAN	2 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY - 20 X 19 FT INNER FLY - 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES: 01 IN NO 2. SCREEN WEATHER: 01 IN NO 3. TENT POLE STANDING FOR TENT: 400 LBS 4. TENT POLE RIDGE FOR TENT: 400 LBS 5. TENT SALTAH: 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS: 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOLUSISSO OR TEAK: 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT: 400 LBS ALONGWITH: 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT: 400 LBS ALONGWITH: 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT: 400 LBS manufacture/ LIKELY SUPPLIERS: (a) M BILAL textiles Pvt Paramount Tarpaun Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit at time of inspection. Inspection criteria: joint inspection by contractor. complete accessories to be incorporated to avoid complications at later stage GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY - 20 X 19 FT INNER FLY - 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES: 01 IN NO 2. SCREEN WEATHER: 01 IN NO 3. TENT POLE STANDING FOR TENT: 400 LBS 4. TENT POLE RIDGE FOR TENT: 400 LBS 5. TENT SALTAH: 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS: 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOLUSISSO OR TEAK: 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT: 400 LBS ALONGWITH: 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT: 400 LBS ALONGWITH: 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT: 400 LBS manufacture/ LIKELY SUPPLIERS: (a) M BILAL textiles Pvt Paramount Tarpaun Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit at time of inspection. Inspection criteria: joint inspection by contractor. complete accessories to be incorporated to avoid complications at later stage
8	DGE70457		59700054331154 / TAPE INSULATION WOVEN GLASS WIDTH 13MM, THICK 0.18MM, LG. 50MTR		24 / ROLL			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
9	SGP69143	NIL	5975705088579 / RJ 45 JACK BOOT (TO WEATHER SHIELD)	COMPUTER	20 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
10	SGE47953	FP6F3	5640002374828 / INSULATION SLEEVING TUBE		25 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - SLEEVE SIZES: LENGTH: 36 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPEC/SPECT ARE ATTACHED WITH WMS NOTE. LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGAINST FOREIGN NGN OEM FORTE PAKISTAN GENERAL SPECIFICATION - SLEEVE SIZES: LENGTH: 36 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPEC/SPECT ARE ATTACHED WITH WMS NOTE. LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGAINST FOREIGN
11	DGE50755	NIL	4020999237121 / ROPE NYLON, HAWSER/LAID, 3-STRD, CIR 1.00", DIA 0.3125" (8MM)	NGHT 1.330 TONS UNIT OF AVAILABILITY	780 / FATHOM			TECHNICAL SPECIFICATION - SPECS: BS-4928/74 PART-2 TABLE 1; BS-EN-856 ISO 1140 OF 2004 120 FAH-TAM PER COIL REQUIRED GENERAL SPECIFICATION - SPECS: BS-4928/74 PART-2 TABLE 1; BS-EN-856 ISO 1140 OF 2004 120 FAH-TAM PER COIL REQUIRED
12	SGE49300		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-FL, WIDTH: 1-FT, THICKNESS: 3/8-INCH	PENDER	100 / KILO GRAM			TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-80 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM: COUNTRY OF ORIGIN MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN LG COM (2) LONGMAN KAISER SAHITI 0321-2480174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32730550 GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-80 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM: COUNTRY OF ORIGIN MANUFACTURE: (1) ADD GIBSUN CORP GIRLUM LG COM (2) LONGMAN KAISER SAHITI 0321-2480174 (3) SALOGI MANSION JAMEELA ST. MA Specifications: ANSI 287 1 - 2003 also EN 179 Min Shore (0 upto 11) Min tens (2)mm Likely Source: Lincoln, Miller, Weldline, SACTI, Hobart etc. are all welding helmet manufacturers. ceusd3 headgear welding shield or all type of welding that require shade disc inspection standards: en166, en155, en175, 5 cr mass, data sub, hence GENERAL SPECIFICATION - Specifications: ANSI 287 1 - 2003 also EN 175 Min Shore (0 upto 11) Min tens (2)mm Likely Source: Lincoln, Miller, Weldline, SACTI, Hobart etc. are all welding helmet manufacturers. ceusd3 headgear welding shield or all type of welding that require shade disc inspection standards: en166, en155, en175, 5 cr
85			8 / HEAD SCREEN FOR ELECTRIC WELDING WITH GLASS BLACK.		EACH/ NUMB ER			

S.No	LPR No	PART NO	NSN / Description	VEquipment cat	QTY / DEMO	Model	MANUF ADD	TECH / GEN SPECS
32	DGP73393	CORE 15	7025705248091 / PERSONAL COMPUTER (CORE: 15)		3 / SET	CORE 15 12 GEN		TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/dedicated), 2. System Memory Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/Adapt/Transcend), 3. Hard Drive 1TB SATA/SSD, 4. Keyboard+ USB (3d Optical), 5. Mouse+ USB (Optical LED), 6. LED+ 18.5" (Min) or higher (same brand), 7. LAN+ Yes (Built in 10/100/1000), 8. Warranty+ Minimum 01 Year or as provided by OEM, 9. Operating System+ Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation. GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO): 1. CPU Technology Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/dedicated), 2. System Memory Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/Adapt/Transcend), 3. Hard Drive 1TB SATA/SSD, 4. Keyboard+ USB (3d Optical), 5. Mouse+ USB (Optical LED), 6. LED+ 18.5" (Min) or higher (same brand), 7. LAN+ Yes (Built in 10/100/1000), 8. Warranty+ Minimum 01 Year or as provided by OEM, 9. Operating System+ Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation.
33	DCW68038		8430701241010 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 11		185 / PAIR			TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
34	DCD73562		8455703009747 / SURFACE SHIP INSIGNIA GOLD FOR OFFICER		100 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - SURFACE SHIP INSIGNIA GOLD FOR OFFICER GENERAL SPECIFICATION - SURFACE SHIP INSIGNIA GOLD FOR OFFICER
35	DCW73525		8430500000029 / BOOT DMS (WITH FABRIC LACE 160CM)		100 / PAIR			TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7 GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 7
36	DGP66183	Q1414B	9310705292390 / chart / PLOTTER PAPER SIZE: 40" / 42" X 18 TO 25 M, GSM 120 TO 160 ± 5%		5 / ROLL			TECHNICAL SPECIFICATION - SIZE: 40" / 42" X 18 TO 25 M, GSM 120 TO 160 ± 5% GENERAL SPECIFICATION - SIZE: 40" / 42" X 18 TO 25 M, GSM 120 TO 160 ± 5%
37	DCD73811		8455501001568 / BADGE SUBMARINE OFFICER GOLD		100 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - BADGE SUBMARINE OFFICER GOLD GENERAL SPECIFICATION - BADGE SUBMARINE OFFICER GOLD
38	DCW73630		8430500000045 / BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L		100 / PAIR			TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 12L
39	DCW68034		8430701241007 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8		185 / PAIR			TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8 GENERAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 8
40	DCW73517		8430500000036 / BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L		100 / PAIR			TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9L
41	DGB73859	OUT/BOO Y 118"PLAT E INNER 16 GAUG	0248591296147 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	B2 710X635X 425 MM/27- 31X21- 115X16-	2 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" cut body: 1/8" plate inner gauge: 16 local Indigenous Steel or 3400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" cut body: 1/8" plate inner gauge: 16 local Indigenous Steel or 3400 Fire Proof Required
42	DGB71179		0242599420535 / GAUGE-PRESSURE-DIAL-INDICATING		2 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - a. Pressure Range: 0-100 PSI b. Material: Steel c. Connection Size: 1/4" GENERAL SPECIFICATION - a. Pressure Range: 0-100 PSI b. Material: Steel c. Connection Size: 1/4"
43	DGB71828	4 7525M MITH 048"X 21 92MMX11 2	0283705711633 / STRIP BRAZING ALLOY WIDTH 0.1875TH 0.048" AG NO 5 WIDTH 1875"		2200 / GRAM			TECHNICAL SPECIFICATION - a. Thickness: 02 - 04 mm ±1 mm d. Length: 100 - 600 mm ±50 mm c. Width: 02 - 05 mm ±2 mm d. Copper: 85 - 95 % ±5 % BS EN 1044 Grade AG 103 GENERAL SPECIFICATION - a. Thickness: 02 - 04 mm ±1 mm d. Length: 100 - 600 mm ±50 mm c. Width: 02 - 05 mm ±2 mm d. Copper: 85 - 95 % ±5 % BS EN 1044 Grade AG 103
44	SGB56149	BS 1210	0266599417324 / SCREW, WOOD		200 / HUND RED			TECHNICAL SPECIFICATION - NSN: 5305-99-941-7324, FASTENER LENGTH: 1.000 INCHES NOMINAL, HEAD STYLE: FLAT COUNTERSUNK, HEAD DIAMETER: 0.312 INCHES MINIMUM & 0.328 INCHES MAXIMUM GENERAL SPECIFICATION - NSN: 5305-99-941-7324, FASTENER LENGTH: 1.000 INCHES NOMINAL, HEAD STYLE: FLAT COUNTERSUNK, HEAD DIAMETER: 0.312 INCHES MINIMUM & 0.328 INCHES MAXIMUM
45	DGB72869		0277702770151 / METRIC SOCKET SET 10 TO 32MM CONSIST 24 PIECES WITH BOX		1 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
46	SGB49056	V 2061- DCH 1484 SZ T	0278790012838 / DRILL PNEUMATIC PORTABLE 0.5IN MEDIUM DRIVE REVERSIBLE	AIR DRILL MODEL AT-4041 MACE	3 / EACH/ NUMB ER	AT-4041 (1/2 INCH REVERE BLE)		TECHNICAL SPECIFICATION - CHUCK SIZE: 1/2 INCH FREE SPEED: 800 RMP AIR INTEL: 1/4 INCH PT(NPT) AIR HOSE (ID): 3/8 INCH WORKING PRESSURE: 6.3 KG/CM2 GENERAL SPECIFICATION - CHUCK SIZE: 1/2 INCH FREE SPEED: 800 RMP AIR INTEL: 1/4 INCH PT(NPT) AIR HOSE (ID): 3/8 INCH WORKING PRESSURE: 6.3 KG/CM2
47	DGP73741	4003DN	7435706138632 / PRINTER HP LASER JET 2035/HP LASER JET 2035/HP LASER JET Pro 400/M401D/HP402D/M402DN/M404DN	COMPUT ER	3 / EACH/ NUMB ER	NO DATA AVAILAB LE	PK	TECHNICAL SPECIFICATION - Laser, 200 MHz, RAM 18 MB, 1200 x 12 dpi, 12 ppm/print speed b/w, Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port. GENERAL SPECIFICATION - Laser, 200 MHz, RAM 18 MB, 1200 x 12 dpi, 12 ppm/print speed b/w, Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port. Both
48	DCW73528		8430500000034 / BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S		100 / PAIR			TECHNICAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S GENERAL SPECIFICATION - BOOT DMS (WITH FABRIC LACE 160CM) SIZE 9S
49	DCW68037		8430701241011 / SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12		185 / PAIR			TECHNICAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12 GENERAL SPECIFICATION - SANDAL BLACK PESHAWARI RUBBER SOLE SIZE 12
50	DCW73519		8430500001978 / BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE		100 / PAIR			TECHNICAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE GENERAL SPECIFICATION - BOOT DMS WITH FABRIC LACE 200 CM SIZE 14 LARGE
51	DGB70076	NO DATA AVAILAB LE	5690705148476 / CONCERTINA WIRE	FOR BOUNDAR Y PROTEC TION	480 / ROLL		SOURCE OF AVAILABILITY PAKISTAN YOMI SITE AREA KARACHI, Mr. WASSEM CONTRACT NO 3335-2024MPS	TECHNICAL SPECIFICATION - Country of origin pakistan BLADE SIZE 20MM, 14MMW BLADE THICKNESS 0.5MM LINE WIRE 2.07MM 15-12 GAUGE SIZE 36INCH DIA MATERIAL (MILD STEEL/CALVANIZED) GENERAL SPECIFICATION - Country of origin pakistan BLADE SIZE 20MM, 14MMW BLADE THICKNESS 0.5MM LINE WIRE 2.07MM 15-12 GAUGE SIZE 36INCH DIA MATERIAL (MILD STEEL/CALVANIZED)
52	DGE70481	NA	9330705181279 / PLASTIC SHEET	GENERAL ITEM	48 / ROLL		LOCAL MARKET	TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / GEND	Model	MANUF ADD	TECH / GEN SPECS
53	DNM70059	SAP-27015PF	6260011969753 / LIGHT CHEMICAL BINCH ORANG/CYALUME CHEMLIGH ORANGE		50 / EACH NUMB ER		CYALUME TECHNOLOGI ES-3A 295 R MAYOR DE MONTRICHER AIX EN PROVENCE FRANCE AIX EN PROVENCE CEDEX 3 13961 04 42 37 17 80 04 42 37 17 80 KFAHCYALU ME.COM WWW.CYAL	TECHNICAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume Technologies GENERAL SPECIFICATION - Make/ Model / Brand Equivalent : Cyalume Technologies
54	DNH73755	OWR-528 / NWO2001 con-2(ORIEN T)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENSER	2 / EACH NUMB ER	OWR-528(Ow-2001)	ORIENT WATER DISPENSER PAKISTAN	TECHNICAL SPECIFICATION - white colour only HASQAS WATER DISPENSER GENERAL SPECIFICATION - white colour only HASQAS WATER DISPENSER
55	DNH73903	OWR-528 / NWO2001 con-2(ORIEN T)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENSER	2 / EACH NUMB ER	OWR-528(Ow-2001)	ORIENT WATER DISPENSER PAKISTAN	TECHNICAL SPECIFICATION - white colour only HASQAS WATER DISPENSER GENERAL SPECIFICATION - white colour only HASQAS WATER DISPENSER
56	DGE71332	YCR100 or 1250	8305785163090 / CERAMIC FIBER CLOTH	GENERAL USE	372 / METE R	YCR100	GEN CHINA MANUFACTURERS NINGBO RUBING SEALING MATERIAL COMPANY LTD HUANGYU TOWN COO-86 314 655 211 8983 1433	TECHNICAL SPECIFICATION - size: width 60 00 in thickness: 48 mils length: 50 00 yards weight: 24 00 oz/ sq yd colour: white temperature resistance: 700 degree centigrade max thermal conductivity 0 18 wk/m GENERAL SPECIFICATION - size: width 60 00 in thickness: 48 mils length: 50 00 yards weight: 24 00 oz/ sq yd colour: white temperature resistance: 700 degree centigrade max thermal conductivity 0 18 wk/m
57	DGE38148	PEC 1735511	6532705172593 / LIGHTWEIGHT ESD COMPLAINT LAB COATS.	PCB FABRICATION	81 / EACH NUMB ER		WJOP Technologies & Services Private Limited Building No 2 K-40 Floor P.E.L.H.S Block-B,Phase-3 Faisalabad, Sindh, Pakistan. Phone No: 031-34302153-4	TECHNICAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 35% (a 1% COTTON + 3% (a 1% CONDUCTIVE FILAMENT) c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 10E 6 to 10E 9 GENERAL SPECIFICATION - a. Fabric Type: Broad Cloth (combination of material) b. MATERIAL: 65% POLYESTER + 35% (a 1% COTTON + 3% (a 1% CONDUCTIVE FILAMENT) c. Shape: Standard Laboratory Coats (white in color) d. Length: Knee Length e. Size: Medium f. Color: White g. ESD Symbol embossed Surface Resistance: 10E 6 to 10E 9
58	DGE70472	NIL	4230705181268 / BAG PAPER FOR CONTAMINATED CLOTHING	NIL	250 / EACH NUMB ER		PLASTIC MARKET	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3480 dated 30 March 2015) Dimensions: Height = 40 cm Width = 32 cm Depth = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 - 110 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have double padding at its bottom. PACKING: STANDARD GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3490 dated 30 March 2015) Dimensions: Height = 40 cm Width = 32 cm Depth = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 - 150 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have double padding at its bottom. PACKING: STANDARD
59	DGE71333	ASNZ5 1718 P3, EN143, 2000 P3 R	8455705181276 / DISC IDENTITY RED FOR RESPIRATION AND HAVERSACK	NIL	468 / EACH NUMB ER		LOCAL MARKET	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3490 dated 30 March 2015) GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3490 dated 30 March 2015)
60	DGE68968	ASNZ5 1718 P3, EN143, 2000 P3 R	8455705181278 / DISC IDENTITY RED FOR RESPIRATION AND HAVERSACK	NIL	520 / EACH NUMB ER		LOCAL MARKET	TECHNICAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3490 dated 30 March 2015) GENERAL SPECIFICATION - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICPPATT/1057/3490 dated 30 March 2015)
61	DGE70463	NIL	3510705181278 / TRAY BLEECH	NIL	8 / EACH NUMB ER		LOCAL MARKET	TECHNICAL SPECIFICATION - GENERAL ITEM GENERAL SPECIFICATION - GENERAL ITEM
62	DGD64476	152254 / E-6228	7320997594311 / VEGETABLE PEELING MACHINE,ELECTRIC	GALLEY	2 / EACH NUMB ER		NO DATA AVAILAB LE	UK TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V
63	DGD61884	152254 / E-6228	7320997594311 / VEGETABLE PEELING MACHINE,ELECTRIC	GALLEY	1 / EACH NUMB ER		NO DATA AVAILAB LE	UK TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V
64	DGD59076	152254 / E-6228	7320997594311 / VEGETABLE PEELING MACHINE,ELECTRIC	GALLEY	2 / EACH NUMB ER		NO DATA AVAILAB LE	UK TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V
65	DGD37955	152254 / E-6228	7320997594311 / VEGETABLE PEELING MACHINE,ELECTRIC	GALLEY	2 / EACH NUMB ER		NO DATA AVAILAB LE	UK TECHNICAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V GENERAL SPECIFICATION - Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/blade: L x B x H Body Stainless Steel 6x3 inch INPUT 440V
66	DNQ73715	00873000	61440FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	2 / EACH NUMB ER	563210B 0006	KINGSWAY DUNMURRY BELFAST IRLANDIA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
67	DNQ73714	06317000	5640FT1019337 / Tarmul Protection Aid (TPA)	Emergency Pack - 1	6 / EACH NUMB ER	553210B 0006	KINGSWAY DUNMURRY BELFAST IRLANDIA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
68	SGE56531	FRS-580G/W	4130705218303 / ROLL FILTER MEDIA	As less Spay Media (pH=7)	2 / ROLL	FRS-580G/W	Fun Wic Enterprise 0000 # 02 # 2 Spay-8-001 Pano. 54/100	TECHNICAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER EN 779 CLASS F5 FINAL RESISTANCE = 400 PH TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120C GENERAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER EN 779 CLASS F5 FINAL RESISTANCE = 400 PH TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120C

S.No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
83	SGE56141		0461592203878 / PAPER, ABRASIVE 9"X11" (OROCUS) MATERIAL EMERY GRADE 4/0		1600 / SHEET			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
84	DGE68471	31W-SILVER-DE	0476590000031 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		142 / EACH NUMBER	31W-SILVER-DE		TECHNICAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE - .06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X8J8 6. ITEM WEIGHT: 4.9 OUNCES 7. PRODUCT DIMENSION L: 200mm, W: 25mm, T: 8mm, Brush Dimension L: 78mm x W: 22mm x 15mm 8. MODEL: Wooden handle, Brass Steel Wire Brush- 6 inches/ Can be customized as per user requirement GENERAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE - .06 INCH 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X8J8 6. ITEM WEIGHT: 4.9 OUNCES 7. PRODUCT DIMENSION L: 200mm, W: 25mm, T: 8mm, Brush Dimension L: 78mm x W: 22mm x 15mm 8. MODEL: Wooden handle, Brass Steel Wire Brush- 6 inches/ Can be customized as per user requirement
85	DGE67056		0476590000062 / GLOVES LEATHER LEFT HAND.		822 / EACH NUMBER			TECHNICAL SPECIFICATION - Size: Large a. Material: leather b. Color: Natural c. Good fit w/ing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable GENERAL SPECIFICATION - Size: Large a. Material: leather b. Color: Natural c. Good fit w/ing thumb and straight finger d. 15 centimeter split cuff e. Flexible soft and durable
86	DPC73642		0474504740067 / SOAP TEEPOL LIQUID (detergent general purpose)	880G	909 / KILO GRAM			TECHNICAL SPECIFICATION - Defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4 GENERAL SPECIFICATION - Defstan 79-8/1 of 1972 TEEPOL LIQUID HAVING DETERGENT/GERMICIDE PROPERTIES SURFACE ACTIVE AGENT SHOULD BE NONIONIC AND AS PER DEFSTAN 79-8/1 OF 1972 ANNEX SERIAL 4-5
87	DGE67838	NO DATA AVAILABLE	0413599238755 / MAT FLOOR RUBBER LG. 18. WD.(LTR NO E-I4927-A/1082 DT221086)		27 / METRE			TECHNICAL SPECIFICATION - Size: Size 15' x 30' Thickness: 5mm Coated Mat Material: Synthetic rubber Performance: Antiskid non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Dimensions: Width: 1.5m Length (as per roll): Thickness: 4-6mm Feature: Weather resistant, impact resistant, Heat resistant, Corrosion resistant, Insulated, Cold resistant. Color: Blue/Black GENERAL SPECIFICATION - Size: Size 15' x 30' Thickness: 5mm Coated Mat Material: Synthetic rubber Performance: Antiskid non slippery, slide proof. Usage: Used on gangways, alleyways, floors, car mats. Dimensions: Width: 1.5m Length (as per roll): Thickness: 4-6mm Feature: Weather resistant, impact resistant, Heat resistant, Corrosion resistant, Insulated, Cold resistant. Color: Blue/Black.
88	DGE68487	DGS 8971	0413599238761 / HOSE RUBBER, LENGTH= 60-FEET, NOMINAL OVERALL INTERNAL DIA= 0.500 INCHES, OUTSIDE DIA= 0.875 INCHES		1000 / METRE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
89	DGE70483	0.75X0.007 INCH-50MTR	0559790015244 / INSULATION-TAPE-VARNISHED WOVEN GLASS-FIBRE-(STRAIGHT CUT)		46 / ROLL			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
90	SGE69146	NIL	0461599104733 / HANDLE FOR HAMMER-17INCH		32 / EACH NUMBER			TECHNICAL SPECIFICATION - nil GENERAL SPECIFICATION - nil
91	DGE65956		0474504740128 / SHAMIANA COMPLETE SZ. 18.00X36.00 FT		9 / EACH NUMBER			TECHNICAL SPECIFICATION - Option I Size 15x15 Feet Poles 04 with cover Ropes 04 with cover Fill 04 (15 feet both) Killy 04 (15 feet rod) Option II Size 15x30 Feet Poles 06 with cover Ropes 06 with cover Fill 02 (15 feet) 02 (30 feet) Killy 04 (15 feet rod) MATERIAL: 100% COTTON, BAMBOO OF MATURE STEM, SOUND REASONABLY STRAIGHT & FREE FROM 100% BORER OR INSECT HOLES (GHOOON), SPLIT AND PRESERVED. Color: Item is covered in multicolor i.e (yellow, green) GENERAL SPECIFICATION - Option I Size 15x15 Feet Poles 04 with cover Ropes 04 with cover Fill 04 (15 feet both) Killy 04 (15 feet rod) Option II Size 15x30 Feet Poles 06 with cover Ropes 06 with cover Fill 02 (15 feet) 02 (30 feet) Killy 04 (15 feet rod) MATERIAL: 100% COTTON, BAMBOO OF MATURE STEM, SOUND REASONABLY STRAIGHT & FREE FROM 100% BORER OR INSECT HOLES (GHOOON), SPLIT AND PRESERVED. Color: Item is covered in multicolor i.e (yellow, green)
92	DGE69854	NIL	0360595713126 / ROPE NYLON, HAWSERLAD WHITE, 3-STRAND, CIRC: 02-INCH, DIA: 16MM (5/8")		120 / FATHOM	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 8554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL, 3. OEM: COTESI UK GENERAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 8554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL, 3. OEM: COTESI UK
93	SGB56158		0293595711430 / ROD NAVAL BRASS HEX		16 / METRE			TECHNICAL SPECIFICATION - SIZE: A/F 0.82", WT PER FT 2.170 (LB), bs 2674 cf 112 m. Acceptance criteria: as per size and specifications, or item sample may be shared with Machine Shop (C. No. 205) for acceptance or otherwise GENERAL SPECIFICATION - SIZE: A/F 0.82", WT PER FT 2.170 (LB), bs 2674 cf 112 m. Acceptance criteria: as per size and specifications, or item sample may be shared with Machine Shop (C. No. 205) for acceptance or otherwise
94	DGE68964	D5651-3 (4220-99-923-5557)	0433599235557 / TROUSER DIVER-S SUIT, MEDIUM, (UK MADE)	FOR DIVING PURPOSE	22 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
95	DGE58431		0421599425637 / FILING CABINET SIZE, 4-DRAWERS W/LOCK combination AND COMPRESSOR PLATES GREY GAUGE SWG: 22 SIZE: W18 INCH		12 / EACH NUMBER			TECHNICAL SPECIFICATION - GAUGE SWG: 22 SIZE: Width 18 INCH, Dia: 24 1/2 INCH, HEIGHT: 52 INCH, MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS (completely available and accepted by end user) GENERAL SPECIFICATION - GAUGE SWG: 22 SIZE: Width 18 INCH, Dia: 24 1/2 INCH, HEIGHT: 52 INCH, MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS (completely available and accepted by end user)
96	DPC73889		0442509423539 / PAINT MARKING BRUSH STENCILLING AMMUNITION (AZURE BLUE), Flash Point 32C (04 LTR TIN) packing: 04 tin tin gauge of drum 26 to 28 swg		30 / LITER			TECHNICAL SPECIFICATION - 1. Defstan: 80-68/4 of 2009 2. nsp/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996 GENERAL SPECIFICATION - 1. Defstan: 80-68/4 of 2009 2. nsp/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996
97	DGE70482	DNE1-921-8996	0460599318996 / TAPE COTTON ADHESIVE COMPOUND WIDTH 3" THICK 0.038" LG. 10 MTR.	30 MM GUN	64 / ROLL			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
98	SGE49097	0414-9160	0414599230934 / SHEET, ASBESTOS, COMPRESSED TH 1/16", WD 54" X63" IN WT PER SHEET 22LBS		78 / KILO GRAM			TECHNICAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES) GENERAL SPECIFICATION - BS2815, GRADE A, FOR WATER, STEAM OIL, HYDROCARBONS AND AIR (COLOURED RED BOTH SURFACES)
99	SGE49098	0414-5162	0414599230935 / ASBESTOS SHEET COMPRESSED, LENGTH: 63-INCH, WIDTH: 54-INCH, THICKNESS: 0.125 INCH	GENERAL PURPOSE	90 / KILO GRAM			TECHNICAL SPECIFICATION - Dimension/Size: LENGTH: 63 INCH, WIDTH: 54 INCH, THICKNESS: 0.125 INCH COLOUR: RED, MATERIAL: ASBESTOS BS-2815 GENERAL SPECIFICATION - Dimension/Size: LENGTH: 63 INCH, WIDTH: 54 INCH, THICKNESS: 0.125 INCH COLOUR: RED, MATERIAL: ASBESTOS BS-2815

S.No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
100	SGE49522	NIL	0413599238936 / RUBBER STRIP WIDTH 0.375"HEIGHT 0.375".		118 / METRE			TECHNICAL SPECIFICATION - SPECIFICATIONS: BS-1135 MATERIAL: NATURAL, HARDNESS RATING: 42.0 MINIMUM AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, FABRICATION METHOD: SOLID, COLOUR: WHITE, CROSS SECTIONAL SHAPE STYLE: SQUARE, CROSS SECTIONAL WIDTH: 0.375 INCHES, CROSS SECTIONAL HEIGHT: 0.375 INCHES GENERAL SPECIFICATION - SPECIFICATIONS: BS-1135 MATERIAL: NATURAL, HARDNESS RATING: 42.0 MINIMUM AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, FABRICATION METHOD: SOLID, COLOUR: WHITE, CROSS SECTIONAL SHAPE STYLE: SQUARE, CROSS SECTIONAL WIDTH: 0.375 INCHES, CROSS SECTIONAL HEIGHT: 0.375 INCHES.
101	DPC73406	NO DATA AVAILABLE	0443509422228 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wght 01 to 45 kg with protection cap		139 / KILO GRAM			TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F, 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap, 3. Purity Certificate and OEM Conformity Certificate required, 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Date GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F, 2. Gas Carbon Di Oxide (99.5% purity) in Buyer's Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap, 3. Purity Certificate and OEM Conformity Certificate required, 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Date
102	SGB69155		0212596710687 / BAR STEEL CORROSION RESISTING H/R RD 1.25"WT PER FT 4.172LBS		8 / METRE			TECHNICAL SPECIFICATION - BS 970 GRADE: 316L31 IN-320 8970 en 57 GENERAL SPECIFICATION - BS 970 GRADE: 316L31 IN-320 8970 en 57
103	SGB44945		0267599236335 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		180 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE: 1/2 INCH, GENERAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE: 1/2 INCH
104	DGB69223	SPEC BS 1387 (SMM)	0267599236263 / COUPLING PIPE NOM BORE 0.500" GALVANISED SPEC BS 1387		60 / EACH/ NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
105	DGB51416	G267, 13538	0267599235347 / TEE PIPE EQUAL GALVANISED NOM BORE SZ 2.50		50 / EACH/ NUMBER			TECHNICAL SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENING, NOMINAL BORE SIZE: 2.5" (63MM), PROTECTION: GALVANIZED GENERAL SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENING, NOMINAL BORE SIZE: 2.5" (63MM), PROTECTION: GALVANIZED
106	DGB54585		0267599235349 / TEE PIPE EQUAL (GALVANISED) 03.00IN		50 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Material: G I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm GENERAL SPECIFICATION - Material: G I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm
107	DGB34410	SKF N 312	0269799502091 / BEARING PARALLEL ROLLER SKF N 312 060X130X31MM		1 / EACH/ NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
108	DGB71590		0214590331210 / STUD-PLAIN-BSW-THRED 0.75-INCH-2.50-INCH LTH OF THREAD METAL		400 / EACH/ NUMBER			TECHNICAL SPECIFICATION - 0.75 x 2.5 inch, en-1740 GENERAL SPECIFICATION - 0.75 x 2.5 inch, en-1740
109	DGE61230	DEPSTA N 45-3	0330595713253 / TWINE HEMP 3-STRAND, MIN BKG STRENGTH 810 LBS, DIA: 7mm		17 / EACH/ NUMBER			TECHNICAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM Material: Jute Process: Twist Colour: Natural, Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT: CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE: SPECIFICATION BS 2019 C-1557, CONSTRUCTION STYLE: 3 PLY 3 STRANDS GENERAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM Material: Jute Process: Twist Colour: Natural, Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT: CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE: SPECIFICATION BS 2019 C-1557, CONSTRUCTION STYLE: 3 PLY 3 STRANDS
110	DGE58529	NIL	0350599237130 / ROPE NYLON, HAWSERLAD, 3-STRND, Z-LAY, NOM DIA: 28 MM, CIRC: 3.50 INCH, TYPE-1, MIN BRKG STRENGTH 15.500 TONS	MIN BRKG STRENGTH 15.500 TONS UNIT OF	440 / FATHOM			TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005, 4. LENGTH PER COIL: 120 FATHOM, 5. OEM COC REQUIRED GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED, MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005, 4. LENGTH PER COIL: 120 FATHOM, 5. OEM COC REQUIRED.
111	SGB31664		0214700630838 / NUT PLAIN HEX BSF SIZE 3/4"x1.20"x0.687 INCH		700 / EACH/ NUMBER			TECHNICAL SPECIFICATION - SPECS PD 970 2005, GRADE 708M4042CR0M4, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75 INCHES), 12 TPI, NOMINAL LENGTH: 5/8 (0.625 INCHES), THICKNESS: (1 1/8") (1.125 INCHES) GENERAL SPECIFICATION - SPECS PD 970 2005, GRADE 708M4042CR0M4, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75 INCHES), 12 TPI, NOMINAL LENGTH: 5/8 (0.625 INCHES), THICKNESS: (1 1/8") (1.125 INCHES)
112	SGB68653	Material Grade EN 4140	0214590035015 / BOLT MACHINE STEEL BSW HEX HD SZ 2.000X0.250X1/4" TP1 20		90 / TEN			TECHNICAL SPECIFICATION - METRIAL GRADE EN 4140 GENERAL SPECIFICATION - METRIAL GRADE EN 4140
113	SGB49415		0214590035653 / BOLT MACHINE STEEL BSW HEX HD SZ 1.5X0.375"THD LG 3/4" TPI 10	TP1 BS 910	700 / TEN			TECHNICAL SPECIFICATION - MATERIAL GRADE: AISI 4140 / ANY RELEVANT GRADE # 0, BS 708M40 NOMINAL LENGTH: 1 1/2 inch OUTER DIA: 3/8 inch THREAD LENGTH: 3/4 inch TPI: 16 HEAT TREATMENT CONDITION: R GENERAL SPECIFICATION - MATERIAL GRADE: AISI 4140 / ANY RELEVANT GRADE # 0, BS 708M40 NOMINAL LENGTH: 1 1/2 inch OUTER DIA: 3/8 inch THREAD LENGTH: 3/4 inch TPI: 16 HEAT TREATMENT CONDITION: R
114	SGB56163	BS2451 (S350-99-923-3401)	0283709233461 / CHILLED-IRON-GRIT-TYPE-FINE-GD-24		1000 / KILO GRAM			TECHNICAL SPECIFICATION - STANDARD PARTICLE SIZE: G-24+0.6 TO 1.0 MM STANDARD ISO 11124-2, METALLIC BLAST-CLEANING ABRASIVE, GRIT PARTICLE SHAPE: HARDNESS: ROCKWELL B1 TO 64 HRC, ±3 HRC SHAPE: ANGULAR AND IRREGULAR, DENSITIES: 7g/cm3 (APPARENT DENSITY) 3.8 g/cm3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON Si: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.00 % SULFUR S: 0.07 % to 0.17 % GENERAL SPECIFICATION - STANDARD PARTICLE SIZE: G-24+0.6 TO 1.0 MM STANDARD ISO 11124-2, METALLIC BLAST-CLEANING ABRASIVE, GRIT PARTICLE SHAPE: HARDNESS: ROCKWELL B1 TO 64 HRC, ±3 HRC SHAPE: ANGULAR AND IRREGULAR, DENSITIES: 7g/cm3 (APPARENT DENSITY) 3.8 g/cm3 (BULK DENSITY) CHEMICAL
115	DGB54016		0276709105870 / SCREW DRIVER RATCH, DOUBLE SPIRAL, AUTO RETURN, 250MM LG, 3 BITS		87 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Drive specification: Screw Driver Ratch, Double Spiral, Auto Return Technical data: Screw Drive: Set Flexible 215MM, 30 Accessories by HOLZER Made in China GENERAL SPECIFICATION - Detail specification: Screw Driver Ratch, Double Spiral, Auto Return Technical data: Screw Drive Set Flexible 215MM, 30 Accessories by HOLZER Made in China
116	DGE57595	NO DATA AVAILABLE	0320599232703 / Coir Yarn Type Good Quality 112 LBS		140 / KILO GRAM			TECHNICAL SPECIFICATION - Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type = Coir/Roll Breaking Load = 50 Kg GENERAL SPECIFICATION - Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type = Coir/Roll Breaking Load = 50 Kg
117	DGB54104		0272502720046 / DRILL-PARALELL-SHANK-4MM		41 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Material: HSS, Hardness: HRC55-60 GENERAL SPECIFICATION - Material: HSS, Hardness: HRC55-60

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
118	DGE66480	32494250 03.BS- 2019	0330599425003 / TWINE NYLON COD LINE 3 STRD MIN BKG STRENGTH 320 LBS LG=220FT	PROPELL ER HUB	4 / EACH NUMB ER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
119	SGB66967	WATERIA L GRADE EN 4140	0214599416388 / BOLT MACHINE STEEL UNC HEX HD 0.75X12X2 INCH TPI 10 (LOCAL)		100 / EACH NUMB ER			TECHNICAL SPECIFICATION - material specs: PD 970-2005 material GRADE 108M40/42CRM04 OEM COC/mfg REQUIRED GENERAL SPECIFICATION - material specs: PD 970-2005 material GRADE 108M40/42CRM04 OEM COC/mfg REQUIRED
120	SGB51715	NO DATA AVAILAB LE	0263694149635 / THIMBLE, ROPE, PEAR SHAPED OPEN TYPE, FOR STEEL 16MM WIREROPES		45 / EACH NUMB ER			TECHNICAL SPECIFICATION - GALVANIZATION REQUIREMENT IN GRAM M2 OR MICRON Thimble Shape: Pear Shape Material: High carbon steel with galvanized coating Size: 16mm Uses: Used as Steel Wire Rope Eye MATERIAL STEEL TO BS 970-EN3A, GALVANISED, WEIGHT LBS 6.00 PER 12 FORMER NS CATALOGUE NP 0203/5085 SPEC NO: DGS 5031 NO 40 GENERAL SPECIFICATION - GALVANIZATION REQUIREMENT IN GRAM M2 OR MICRON Thimble Shape: Pear Shape Material: High carbon steel with galvanized coating Size: 16mm Uses: Used as Steel Wire Rope Eye MATERIAL: STEEL TO BS 970-EN3A, GALVANISED, WEIGHT LBS 6.00 PER 12 FORMER NS CATALOGUE NP 0203/5085 SPEC NO: DGS 5031 NO 40
121	SGB44959		0273789105759 / BLADE HAND MACKSAW FLEXIBLE PITCH FINE NOM LG 12 Inches TEETH 32/ inch		15 / DOZE N			TECHNICAL SPECIFICATION - Blade length: 12 inches. Blade material: Steel, Blade width: 0.5 inches. Teeth per inch 32. Handle material: Rubber GENERAL SPECIFICATION - Blade length: 12 inches. Blade material: Steel, Blade width: 0.5 inches. Teeth per inch: 32 Handle material: Rubber
122	DNQ73807		0243691295834 / FIRE EXTINGUISHER CO2 (CARBON DIOXIDE) 2 1/2LB C/W DISCHARGE HORN ASSM	FOR FIRE FIGHTIN G	8 / EACH NUMB ER			TECHNICAL SPECIFICATION - BS EN 3 GENERAL SPECIFICATION - BS EN 3
123	SGB60216		0257704195013 / NUT PLAIN HEX BSW BRASS THD 0.250 OVA LG 0.200 (FULL BEARING)	0.250" DI A HEIGHT 0 300" STY LE FULL BEA	8 / DOZE N			TECHNICAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM DR 0.25" GENERAL SPECIFICATION - MATERIAL GRADE: MILD STEEL INNER DIA: 6.5MM OUTER DIA: 11MM WIDTH: 7MM DR 0.25"
124	DGB72585		0258502501203 / COPPER-WIRE- 2-MM-DIA		30 / KILO GRAM ME			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
125	DGD65145		0247705117521 / STOVE/BURNER GAS OPERATED (1/8" VALVE DIA 2") SEE COM FB	STOVE BURNER (EGLE STAR)	8 / EACH NUMB ER			TECHNICAL SPECIFICATION - STOVE/BURNER GAS OPERATED (1/8" VALVE DIA 2") SEE COM FB EGLE STAR GENERAL SPECIFICATION - STOVE/BURNER GAS OPERATED (1/8" VALVE DIA 2") SEE COM FB EGLE STAR
126	DGD44348	S NO 32 MODEL 2018	0035500000386 / MINCING MACHINE MEDIUM		1 / EACH NUMB ER	2018		TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450
127	DGD57790	S NO 32 MODEL 2018	0035500000386 / MINCING MACHINE MEDIUM		2 / EACH NUMB ER	2018		TECHNICAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 GENERAL SPECIFICATION - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450
128	DGD70664		0032500032006 / KNIVES FISH EATING FOR OCRS		40 / EACH NUMB ER			TECHNICAL SPECIFICATION - Material 5/8 304 / 302 FOOD GRADE NON Magnetic (LOCAL) GENERAL SPECIFICATION - Material 5/8 304 / 302 FOOD GRADE NON Magnetic (LOCAL)
129	DGD67231	NO DATA AVAILAB LE	0033546000911 / Tumbler Glass for Soda Water		450 / EACH NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - Material: Glass (Crystal clear) Capacity: 250/300ml Brand: Toya Nasic / Nova (LOCAL) GENERAL SPECIFICATION - Material: Glass (Crystal clear) Capacity: 250/300ml Brand: Toya Nasic / Nova (LOCAL)
130	DGB54583	NO EACH PKT	0251704119610 / CLIP-FLAG- FIXED-EYE W/O SWIVEL DGS 002503348/01-OF 01 (10 IN	FOR FLAG FITTING	1620 / EACH NUMB ER			TECHNICAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material GENERAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material
131	SGB54863		0212700000440 / BAR-STEEL- HEXAGONAL-0.75-INCH		5 / METE R			TECHNICAL SPECIFICATION - Material Grade S8 316, Running Length: 1 meter GENERAL SPECIFICATION - Material Grade S8 316, Running Length: 1 meter
132	SGB66146	NO DATA AVAILAB LE	0266691362020 / SCREW MACHINE STEEL 28/323 TONS/SQ.IN.MTS.THREAD SERIES BSW FLAT CSK HD SIZE 1.50X0.375 INCH, LENGTH OF THREAD: 0.830"		100 / TEN			TECHNICAL SPECIFICATION - metal grade en 4140 28/323 TONS/SQ.IN.MTS THREAD SERIES BSW FLAT CSK HD SIZE 1.50X0.375 INCH, LENGTH OF THREAD: 0.830" cut will be provided by firm GENERAL SPECIFICATION - metal grade en 4140 28/323 TONS/SQ.IN.MTS THREAD SERIES BSW FLAT CSK HD SIZE 1.50X0.375 INCH, LENGTH OF THREAD 0.830" cut will be provided by firm
133	DGE70478	NO DATA AVAILAB LE	0330546004484 / HEAVING LINE 06MM L50MM 466MS	MSI	300 / METE R	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
134	DGE67376	811231- 0X-00	1670715081086 / RUCK SACK / MT MILITARY TACTICAL BACKPACKS ALICE PACK ARMY SURVIVAL COMBAT		25 / EACH NUMB ER			TECHNICAL SPECIFICATION - VIDE BDE HQ 85G LETTER PNBDE HQ 85G/GENERAL/237613 DATED 01.08.2007 GENERAL SPECIFICATION - VIDE BDE HQ 85G LETTER PNBDE HQ 85G/GENERAL/237613 DATED 01.08.2007
135	DGE67591	811231- 0X-00	1670715081086 / RUCK SACK / MT MILITARY TACTICAL BACKPACKS ALICE PACK ARMY SURVIVAL COMBAT		25 / EACH NUMB ER			TECHNICAL SPECIFICATION - VIDE BDE HQ 85G LETTER PNBDE HQ 85G/GENERAL/237613 DATED 01.08.2007 GENERAL SPECIFICATION - VIDE BDE HQ 85G LETTER PNBDE HQ 85G/GENERAL/237613 DATED 01.08.2007
136	DGH24705		0561595218334 / CABLE ELECT ELASTOMERIC,LFH, 1CORE COND276/40 440V 165AMP	DEFSTAN STANDA RD 02- 526	100 / METE R			TECHNICAL SPECIFICATION - DEFSTAN 02-526 OF 2008-TABLE B-2 OEM COC / authorized dealer certificate GENERAL SPECIFICATION - DEFSTAN 02-526 OF 2009-TABLE B-2 OEM COC / authorized dealer certificate: not used anymore
138	DNH73700	NL	1308760530119 / 2 TONS WINDOW A/C -220V (GENERAL USA)	NL	1 / EACH NUMB ER			TECHNICAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA) GENERAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA)

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPEC
139	DGE66466		0474504740019 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAXIMUM PLY 5 OZ. URPEER	4 / EACH NUMBER			TECHNICAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flats: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gsm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gsm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Side) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P/E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03 GENERAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flats: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gsm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gsm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Side) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P/E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03
140	DNM73751	NR-20550996	2920725089587 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35 FOR CONTROL (GERMAN)	1 / EACH NUMBER	TF-35		TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGESA
141	DNM73896	NR-20550996	2920725089587 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35 FOR CONTROL	1 / EACH NUMBER	TF-35		TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGESA
142	DNQ47866	(ISHF403) 8-SEW / 64710020 9	3040725094056 / INTERMEDIATE DRIVE SHAFT	DOCK (BLDG) TF-EVZ 400/300 PD-IV OVM	4 / EACH NUMBER			TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 3100 mm TECHNICAL DATA - Drawing No: D003 MATERIAL: GRACE 4140 or equivalent PRODUCTION METHOD: Drawn from solid bar GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 3100 mm TECHNICAL DATA - Drawing No: D003 MATERIAL: GRACE 4140 or equivalent PRODUCTION METHOD: Drawn from solid bar
143	DNQ73706	LOCAL	4210705007917 / NOZZLE FOR HOSE CANVAS		3 / EACH NUMBER	SL-13BF SHELVA FIRE		TECHNICAL SPECIFICATION - Series: W2500 Model: Part 1 & 1p OEM/Brand: per control: manual output: 130-23 bar per minute at 6 bar pressure material: polyamide & light aluminum alloy GENERAL SPECIFICATION - Series: W2500 Model: Part 1 & 1p OEM/Brand: per control: manual output: 130-23 bar per minute at 6 bar pressure material: polyamide & light aluminum alloy
144	DNH73963	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	3 / EACH NUMBER	GREE/ P.EL. MITSUBUSHI/ DAKEN/ GENERAL/ GENERAL LO		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - null
145	DNH73899	ref-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH NUMBER	WDF-318		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
146	DNH73696	NO DATA AVAILABLE	4110731001910 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/FRONT STEELBODY	WATER COOLER	2 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
147	DNH73809		4110735060828 / REFRIGERATOR 18-CUFT DOUBLE DOOR PEL/DAWLANCE		1 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
148	DNH73900		4110735060828 / REFRIGERATOR 18-CUFT DOUBLE DOOR PEL/DAWLANCE		1 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
149	DNH73756	MODEL NO 50-	4110705057701 / WATER COOLER 60 LTR STORAGE TYPE 220V50HZ SINGLE PHASE	USER SIM DIV PMS DOCKYARD	2 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
150	DGB71213	CH50-10	4030705039310 / CHAIN BLOCK 5TON CAPACITY WITH 45 FEET DRIFT LINE DIA 9MM-	FOR GENERAL PURPOSE	4 / EACH NUMBER	CH50-10		TECHNICAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 inch Weight: 84 LBS Type: Manual Acceptance CRITERIA - lifting OF 5 Tons Load GENERAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 inch Weight: 84 LBS Type: Manual Acceptance CRITERIA - lifting OF 5 Tons Load
151	DGB39396	MODEL P 40	5130705016394 / ELECTRIC PORTABLE PLANNER AND GROOVERS(CWD 136 MAX-C/D 3MM)	GENERAL USE	5 / EACH NUMBER			TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null
152	SGB56625		5120705066568 / SCREW DRIVER PHILIPS 8" LENGTH SMALL	FOR GENERAL USE	15 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
153	SGB54698	BR3013 SHEETS 12	4730995311379 / FLANGE PIPE STEEL ROUND 2		10 / EACH NUMBER			TECHNICAL SPECIFICATION - Specification: Range pipe steel must 2 bore 2 inch b. Dimension: inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm. GENERAL SPECIFICATION - a. Specification: Range pipe steel must 2, bore 2 inch b. Dimension: inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm.
154	DGB54243	NO DATA AVAILABLE	4730705054809 / FLANGE PIPE 2"(GUN METAL)	WATER SEPERATOR OR ON SUCTION DISCHARGE	15 / EACH NUMBER	LINE ON UPPER DECK		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE
155	SGB66985		5310991240474 / NUT PLAIN HEX 3/8INBSW AFD.600THK0.312		32 / TEN			TECHNICAL SPECIFICATION - PD 970 Material Grade 605 M306 (EN16C)GENERAL SPECIFICATION - PD 970 Material Grade 605 M306 (EN16C)
156	DGE72210		5350731002897 / PAPER GARNET SANDING DISC DIA 30" P-90 BONNIN MACHINE	FOR COMBINE D USE & BOBBIN MACHINE	25 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	PIEquipm ent	QTY / DENO	Model	MANUF ADD	TECH / GEN SPEC
151	DGE72205	A-A-1048	5350001925049 / CLOTH ABRASIVE (ALUMINUM OXIDE), LENGTH:11",WIDTH:09"		317 / SHEET			TECHNICAL SPECIFICATION - OVERALL WIDTH: 09 INCHES NOMINAL GENERAL SPECIFICATION - OVERALL WIDTH: 09 INCHES NOMINAL
158	DGE57003		5330705007252 / 04 PLY RUBBER BLANKETS SIZE 53.5 CM X 48.5 CM		1 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Size 53.5 cm x 48.5 cm 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 38 inches (for model Offset Printing Machine) GENERAL SPECIFICATION - Size 53.5 cm x 48.5 cm 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 38 inches (for Raining Office Room Machine)
150	DGT70245	NO DATA AVAILAB LE	5530705042933 / PLY WOOD NATURAL TEAK FINISH ONE SIDE(NOT ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=03mm to 04mm	PRESENTATION BOXES FOR VVIPS	124 / SQ FEET			TECHNICAL SPECIFICATION - 108 part 1 & 2 BE 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Tolerance in Thickness= 03mm to 04mm Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm GENERAL SPECIFICATION - 108 part 1 & 2 BE 4079 Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Tolerance in Thickness= 03mm to 04mm Core and back ply should of hard wood Thickness of face and back veneer = 0.6mm
150	DGE71434		6530605024908 / OVER BED TABLE ADJUSTABLE 805X405MM STAND 4 WHEEL S/S ROUND		17 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Item Specification: Height=30 Cm Length=28 Cm, Width=15 Cm, Steel brand Standard 18" Gauge, Adjustable Stand Handle, 04 Wheel plastic GENERAL SPECIFICATION - Item Specification: Height=30 Cm Length=28 Cm, Width=15 Cm, Steel brand Standard 18" Gauge, Adjustable Stand Handle, 04 Wheel plastic
151	SGE52941	NIL	5970705047303 / nomex paper-12		50 / KILO GRAM			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
152	SGB47556	CH50-10	0246500001085 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		1 / EACH/ NUMBER	CH50-10		TECHNICAL SPECIFICATION - MADE Brand: Elephant Japan Model: CH50-10, 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons, Load Maximum distance from Hook to Hook is 45" (when drawn), Maximum working load is 05 Ton, Height of lift is 40" GENERAL SPECIFICATION - MADE Brand: Elephant Japan Model: CH50-10, 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons, Load Maximum distance from Hook to Hook is 45" (when drawn), Maximum working load is 05 Ton, Height of lift is 40"
153	DGE62738	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	477 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)
154	DGE69657	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	367 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)
155	DGE58491	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	101 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)
156	DGE64165	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	494 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM, WARP = 24/25 , WEFT=17/18 COUNT OF YARN, 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)
157	DGE66812	III	7910UK5063470 / PVC HOSE PLASTIC,	SPARE PART ELECTRIC POWER MABLE	2 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Internal Dia: 4", Outer Dia: 5.5", Bend Radius: 18", Working Pressure: 150 PSI, LENGTH: 100 FT EACH, Weight LB/FT: 5.00 GENERAL SPECIFICATION - Internal Dia: 4", Outer Dia: 5.5", Bend Radius: 18", Working Pressure: 150 PSI, LENGTH: 100 FT EACH, Weight LB/FT: 5.00
158	DGD66148		7730705048075 / plate Dinner 23cm blue crested (as per stock sample)		58 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Material PORCELIN GENERAL SPECIFICATION - Material PORCELIN
159	SGE69144	NIL	8105011242645 / BAG ANTISTATIC WITH BUBBLE SHEET 406X508MM RS P/N 217-9451	STATIC SAFETY OF EQUIPME NT/COMP OMENTS GENERAL PURPOSE	360 / EACH/ NUMBER			TECHNICAL SPECIFICATION - ADD: Item name 1(A00DP)2 NAVAIR AND NAVSEAMINGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES 20376 215-897-1557 GENERAL SPECIFICATION - ADD: Item name 1(A00DP)2 NAVAIR AND NAVSEAMINGED ORIGINAL DESIGNED ACTIVITY DWG. NOT MATERIAL/PARTS SUPPLIER 13333 ISAAC HULL AVE AS WASHINGTON DC UNITED STATES 20376 215-897-1557
170	DGE58501		8340705087915 / HIGH QUALITY		2 / EACH/ NUMBER			TECHNICAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of
			KUWAITI DELUXE TENT 23 X 15 FT					Walls: 1.80 Meter Fabric Material, Outer Fabric: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton surplus natural gray color, Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 34 Ozs per m2, Inner: Inner Fold made of colored sheeting of 150 GM2 (5/8 Ozs perm2) Accessories All accessories are required with Tent: 4 Iron Poles (Centre & Side) 4 Iron Hammer 4 Iron Stick for walls 4 Iron pins 4 Iron pegs 4 Repair Kit 4 P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material, Outer Fabric: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton surplus natural gray color, Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 34 Ozs per m2, Inner: Inner Fold made of colored sheeting of 150 GM2 (5/8 Ozs perm2) Accessories All accessories are required with Tent: 4 Iron Poles (Centre & Side) 4 Iron Hammer 4 Iron Stick for walls 4 Iron pins 4 Iron pegs 4 Repair Kit 4 P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN

S.No	LPR No	PART NO	NSN / Description	PI/EQUIPMENT	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
171	DGE67015		8340705087916 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	8 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent. Iron Poles (Centre & Ridge) Iron Hammer Iron Stick for walls Iron pins Iron pegs Repair Kit P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETACHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN</p> <p>GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent. Iron Poles (Centre & Ridge) Iron Hammer Iron Stick for walls Iron pins Iron pegs Repair Kit P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETACHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN</p>
172	DGE66269	OUTER FLY & FOLD MADE OF COTTON CANVAS	8340705087916 / TENT MARQUEE UNIVERSAL G.S(SZ27X19.6FT)FOLD&FLY TWO(JGREEN)	GENERAL PURPOSE	10 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % COTTON CANVAS 2. WATER AND ROT RESISTANT FABRIC/LIVE GREEN 3. GROUND SHEET AND MUD FLAP 180 GSM(+/- 5% 4. ACCESSORIES 5. COMPLETE WITH METAL PLATES OFFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES 6 DIMENTION, LENGTH X WIDTH OUTER TENT (OPTION 1) USABLE AREA 6.5X8.2 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63 M WALL HEIGHT 1.63 (OPTION 2) 1 USABLE AREA 5.5 X8 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63</p> <p>GENERAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % COTTON CANVAS 2. WATER AND ROT RESISTANT FABRIC/LIVE GREEN 3. GROUND SHEET AND MUD FLAP 180 GSM(+/- 5% 4. ACCESSORIES 5. COMPLETE WITH METAL PLATES OFFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES 6 DIMENTION, LENGTH X WIDTH OUTER TENT (OPTION 1) USABLE AREA 6.5X8.2 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63 (OPTION 2) 1 USABLE AREA 5.5 X8 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63</p>
173	DGE61555	OUTER FLY & FOLD MADE OF COTTON CANVAS	8340705087916 / TENT MARQUEE UNIVERSAL G.S(SZ27X19.6FT)FOLD&FLY TWO(JGREEN)	GENERAL PURPOSE	2 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % COTTON CANVAS 2. WATER AND ROT RESISTANT FABRIC/LIVE GREEN 3. GROUND SHEET AND MUD FLAP 180 GSM(+/- 5% 4. ACCESSORIES 5. COMPLETE WITH METAL PLATES OFFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES 6 DIMENTION, LENGTH X WIDTH OUTER TENT (OPTION 1) USABLE AREA 6.5X8.2 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63 (OPTION 2) 1 USABLE AREA 5.5 X8 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63</p> <p>GENERAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % COTTON CANVAS 2. WATER AND ROT RESISTANT FABRIC/LIVE GREEN 3. GROUND SHEET AND MUD FLAP 180 GSM(+/- 5% 4. ACCESSORIES 5. COMPLETE WITH METAL PLATES OFFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES 6 DIMENTION, LENGTH X WIDTH OUTER TENT (OPTION 1) USABLE AREA 6.5X8.2 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63 (OPTION 2) 1 USABLE AREA 5.5 X8 MTRS CENTER HEIGHT 3.65 M WALL HEIGHT 1.63</p>
174	DGE72218		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG.66 MTR.	GENERAL USE	213 / ROLL			<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>
175	SGB31524	NO DATA AVAILABLE	0214790131012 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3.000X1.250 IN	TURBO DRIVEN FC PUMP	340 / EACH NUMBER	NO DATA AVAILABLE		<p>TECHNICAL SPECIFICATION - QGS 1000-A CLASS-1 MATERIAL, GRADE EN-4140 GENERAL SPECIFICATION - QGS 1000-A CLASS-1 MATERIAL, GRADE EN-4140</p>
176	DGE3869	OIFLY 23X19FT IIFLY 20X19FT	8340PK5097641 / 400 LBS TENT/MP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANUFACTURE KARACHI PAKISTAN	6 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY: 23 X 19 FT INNER FLY: 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES: 01 IN NO 2. SCREEN WEATHER: 01 IN NO 3. TENT POLE STANDING FOR TENT: 400 LBS 4. TENT POLE RIDGE FOR TENT: 400 LBS 5. TENT SALTATH: 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT (BAG FOR POLES/RIDGES & PINS: 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHLOUSISSO OR TEAK: 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH: 08 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH: 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT: 400 LBS manufacturer/LIKELY SUPPLIERS: M/s M BILAL textiles M/s Paramount Tarpaun Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria: joint inspection by customer. complete accessories to be incorporated to avoid completion of later stage</p> <p>GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY: 23 X 19 FT INNER FLY: 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES: 01 IN NO 2. SCREEN WEATHER: 01 IN NO 3. TENT POLE STANDING FOR TENT: 400 LBS 4. TENT POLE RIDGE FOR TENT: 400 LBS 5. TENT SALTATH: 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT (BAG FOR POLES/RIDGES & PINS: 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHLOUSISSO OR TEAK: 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH: 08 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH: 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT: 400 LBS manufacturer/LIKELY SUPPLIERS: M/s M BILAL textiles M/s Paramount Tarpaun Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria: joint inspection by customer. complete accessories to be incorporated to avoid completion of later stage</p>
177	DGE66264	NO DATA AVAILABLE	8340505039260 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIES (COMPLETE SET)		26 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02. FOLDS: 02. 05 MS POLE: 1. TENT ROOF: MADE OUT OF 450G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CDS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01</p> <p>GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02. FOLDS: 02. 05 MS POLE: 1. TENT ROOF: MADE OUT OF 450G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CDS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01</p>
178	DGE67047	NO DATA AVAILABLE	8340505039260 / TENT 180 LBS MILITARY PATTERN MK-4 WITH ALL ACCESSORIES (COMPLETE SET)		20 / EACH NUMBER			<p>TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02. FOLDS: 02. 05 MS POLE: 1. TENT ROOF: MADE OUT OF 450G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CDS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01</p> <p>GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS: LENGTH: 4.25 MTR. WIDTH: 4.25 MTR. CENTRAL HEIGHT: 2.40 MTR. WALL HEIGHT: 0.90 MTR. THICKNESS: 2 MM. DIA: 52-56 MM. FILES: 02. FOLDS: 02. 05 MS POLE: 1. TENT ROOF: MADE OUT OF 450G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 2. TENT WALL: MADE OUT OF 400G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 3. INNER LINING: MADE OUT OF 180G / M2 COTTON CANVAS WHICH IS ROT PROOF. WATER PROOF AND VAT DYED CANVAS. 4. PACKING COMPLETE TENT AND ACCESSORIES IN ONE BAG WITH RAW MATERIAL. 5. ADVANCE SAMPLE TO BE APPROVED BY CDS. LIST OF ACCESSORIES: 1. IRON PIN: 22 2. ROPE: 22 3. BAMBOO (STAND POLE): 03 4. PIG POLE: 02 5. HAMMER: 01</p>

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / OENO	Model	MANUF ADD	TECH / GEN SPEC
179	DGE59872	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		5 / EACH NUMBER			TECHNICAL SPECIFICATION - 1 Material: Specification PSG-248, 100% Cotton Cloth, 2. 6our: Cedar Green BCC 80 3. Print: White (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet, 5. Iron Pin: 06 in Number, Length 18 inch, dia 1 3/4 inch, 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spurs, 7. Hammer: 05 Lbs with handle, qty 01 & Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (ii) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening, 11. COMPLETE ACCESSORIES: Jhaveri: 06 in Nos Ropes: 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1 Material: Specification PSG-248, 100% Cotton Cloth, 2. 6our: Cedar Green BCC 80 3. Print: White (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet, 5. Iron Pin: 06 in Number, Length 18 inch, dia 1 3/4 inch, 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spurs, 7. Hammer: 05 Lbs with handle, qty 01 & Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (ii) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening, 11. COMPLETE ACCESSORIES: Jhaveri: 06 in Nos Ropes: 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos
180	DGE60011	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		5 / EACH NUMBER			TECHNICAL SPECIFICATION - 1 Material: Specification PSG-248, 100% Cotton Cloth, 2. 6our: Cedar Green BCC 80 3. Print: White (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet, 5. Iron Pin: 06 in Number, Length 18 inch, dia 1 3/4 inch, 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spurs, 7. Hammer: 05 Lbs with handle, qty 01 & Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (ii) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening, 11. COMPLETE ACCESSORIES: Jhaveri: 06 in Nos Ropes: 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos
181	DGE38746	NO DATA AVAILABLE	8340505039262 / QANAT		18 / EACH IN			TECHNICAL SPECIFICATION - Length: 18 feet, Width: 7 feet
		E	COMPLETE SIZE 18.X 7.OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		UMBER			COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED GENERAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED GENERAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED
182	DGE68855	NO DATA AVAILABLE	8340505039262 / QANAT COMPLETE SIZE 18.X 7.OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		33 / EACH NUMBER			TECHNICAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED GENERAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED
183	DGE66485	NO DATA AVAILABLE	8340505039262 / QANAT COMPLETE SIZE 18.X 7.OUT SIDE GREEN PRINTED CLOTH,100% COTTON.		19 / EACH NUMBER			TECHNICAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED GENERAL SPECIFICATION - Length: 18 feet, Width: 7 feet, COLOR OF QANAT: PREFERABLY WHITE NO OF Bumbo STICKS IN EACH QANAT: 05 (03" DIAMETER) NO OF ROPES: DOUBLE ROPE WITH OUTER BAMBOOS STICKS ONLY 1E (01 & 05). Qanat Cloth: 100% cotton green printed in Double Ply. Lab Test Report: Salt and color shop PH Dockyard. ITEM SPECIFICATION ROPE/CORD MADE OF COTTON/BAMBO MATURED & TREATED WITH PRESERVATIVE (INSERTED BETWEEN CLOTH)100% COTTON NIWAR BRASS EYELET WITH STRENGTHING PIECE. NOTE: RELEVANT SPECIFICATION REQUIRED/ENDORSED
184	DGE61622	NO DATA AVAILABLE	8340705014084 / TENT FOR CPQS AND SAILORS WT, 120 LBS		3 / EACH NUMBER			TECHNICAL SPECIFICATION - cns observation and annex b is enclosed as document a Tent for CPQs and Sailors WT 120 LBS along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller GENERAL SPECIFICATION - cns observation and annex b is enclosed as document a Tent for CPQs and Sailors WT 120 LBS along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller
185	DGE61557	NO DATA AVAILABLE	8340705014084 / TENT FOR CPQS AND SAILORS WT, 120 LBS		4 / EACH NUMBER			TECHNICAL SPECIFICATION - cns observation and annex b is enclosed as document a Tent for CPQs and Sailors WT 120 LBS along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller GENERAL SPECIFICATION - cns observation and annex b is enclosed as document a Tent for CPQs and Sailors WT 120 LBS along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller
186	DGE48885	NIL	8340715104294 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VERTICAL INSTALLATION	4 / EACH NUMBER	OPPERA INFRARED CAMOUFLAGE NET ANTI RADAR		TECHNICAL SPECIFICATION - Type: Net Material: Plastic Waterproof Yes Folded: Yes Colour: Woodland Green Standardized size 8.9m x 6.9m and 4 can be tailored according to the requirement of end user Transport Package: Inside PVC Bag or OPP Bag Outside Carton * fabric: 420D polyester plain weave weight: 200 g/m ² nylon printed woven pattern, jungle camouflage with a function if value: 0.88 0.89 0.89 size: 6.9 m x 6 meters packing: packed in polythene/paraffin bag and cotton bag GENERAL SPECIFICATION - Type: Net Material: Plastic Waterproof Yes Folded: Yes Colour: Woodland Green Standardized size 8.9m x 6.9m and 4 can be tailored according to the requirement of end user Transport Package: Inside PVC Bag or OPP Bag Outside Carton * fabric: 420D polyester plain weave weight: 200 g/m ² nylon printed woven pattern, jungle camouflage with a function if value: 0.88 0.89 0.89 size: 6.9 m x 6 meters packing: packed in polythene/paraffin bag and cotton bag
187	DGE72236	#800	8310991397160 / GLASS SEWING THREAD 93 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)	F&H VOLT BELLOW S	12 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
188	SGE69148	NIL	8415735098508 / SURGICAL GLOVES RUBBER SIZE=07	GENERAL USE	24 / PAIR	Safety Disposable Latex Gloves		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	REQUIREMENT FOR PMS	QTY / QEND	Model	MANUF ADO	TECH / GEN SPEC
189	DPC73452	NO DATA AVAILABLE	6890785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200ML CLEANER/UNIVERSAL DEGREASER(OEM = PERFECTS)	REQUIREMENT FOR PMS	288 / EACH NUMBER			TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 3930 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUIJNE BELGIUM TEL: 003256351723 FAX: 003256353069 VIDE PMS RAH NA WARD LETTER 300/RWD/1111 DATED 9 DEC 13 GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 3930 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUIJNE BELGIUM TEL: 003256351723 FAX: 003256353069 VIDE PMS RAH NA WARD LETTER 300/RWD/1111 DATED 9 DEC 13
190	DPC73536	DUPONT SUVA 134a / RFA-134a / R-134a	8830PK6075658 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACUARD OS-73 RADAR	204 / KILO GRAM			TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 °C (-15.0 °F) at 1.013 hpa 5. %Volume : 100% 6. VA pour Pressure : 6.661 tpa at 25 °C (77 °F) : 13,190 h pa at 50 °C (122 °F) 7. Density : 1.260 g/cm3 at 25 °C (77 °F) (in liquid) 8. Specific gravity : 1.205 in 25 °C (77 °F) 9. Water solubility : 1.5 g/l at 25 °C (77 °F) at 1.013 hpa 10. VA pour density : 306 at 25 °C (77 °F) (Air:1.0) 11. Evaporation rate : >1(CO2) 1.0/GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 °C (-15.0 °F) at 1.013 hpa 5. %Volume : 100% 6. VA pour Pressure : 6.661 hpa
191	DPC73537	R-502	6830705110569 / GAS REFRIGRENT R-502 (packing = 13.6kg)	COLD STORAGE B BLASTER	27.24 / KILO GRAM			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
192	SGE51704	NO DATA AVAILABLE	0451500000021 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		160 / METRE	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - a WIDTH:58 INCH(1.473MTR) b.WT/SQ MTR(GM):200 ± 05 c.NO OF THREAD(INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT:2/206 e. SHRINKAGE- WARP:2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) GENERAL SPECIFICATION - a WIDTH:58 INCH(1.473MTR) b.WT/SQ MTR(GM):200 ± 05 c.NO OF THREAD(INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT:2/206 e. SHRINKAGE- WARP:2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)
193	DGE68853	NO DATA AVAILABLE	0451500000021 / CLOTH TICKEN BLUE STRIPS WIDTH 58 INCHES		1280 / METRE	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - a WIDTH:58 INCH(1.473MTR) b.WT/SQ MTR(GM):200 ± 05 c.NO OF THREAD(INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT:2/206 e. SHRINKAGE- WARP:2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) GENERAL SPECIFICATION - a WIDTH:58 INCH(1.473MTR) b.WT/SQ MTR(GM):200 ± 05 c.NO OF THREAD(INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT:2/206 e. SHRINKAGE- WARP:2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)
194	DGD64532		7330705013203 / food hot case 11 tray		7 / EACH NUMBER			TECHNICAL SPECIFICATION - Size: 28" x 24" x 36" material stainless steel heavy duty construction steel (201) Gauge 20 Electric Element: 2500 watts Voltage 220 Double Door stainless steel (304-3201) 1.5mm (16 gauge) 1mm (19 gauge) with ss 316-18 electric welding all hot plates are of 12mm GENERAL SPECIFICATION - Size: 28" x 24" x 36" material stainless steel heavy duty construction steel (201) Gauge 20 Electric Element: 2500 watts Voltage 220 Double Door stainless steel (304-3201) 1.5mm (16 gauge) 1mm (19 gauge) with ss 316-18 electric welding all hot plates are of 12mm
195	SGE38542	NO DATA AVAILABLE	9320705056984 / RUBBER STRIP (FOAM TYPE) SIZE 30 X 20 INCH	GENERAL USE	340 / METRE			TECHNICAL SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPRM) GENERAL SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPRM)
196	DGE71435	NO DATA AVAILABLE	9330705054354 / PLASTIC SHEET BLACK LENGTH 1220MM WIDTH 610MM THICKNESS 12MM	FOR PMS CREST	40.5 / SHEET			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
197	DNQ73813	140501010	8415991304873 / GLOVES	FIRE FIGHTING	60 / PAIR			TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0)2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12 GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0)2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12
198	DNQ73409	005101010	8415991304874 / HOOD,ANTIFLASH...	DC LOCKER	40 / EACH NUMBER			TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0)2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12 GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0)2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12
199	DGB71881	LKR SIZEA	7125PK5104420 / SECURITY SAFE NON/MAGNETIC WITH COMBINATION LOCK 35"X20"X19"	LOCKER M/S KCI STEEL WORKS ARAMBA GH.034	3 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
200	DGB55182	LKR SIZEA	7125PK5104420 / SECURITY SAFE NON/MAGNETIC WITH COMBINATION LOCK 35"X20"X19"	LOCKER M/S KCI STEEL WORKS ARAMBA GH.034	3 / EACH NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
201	DGD57212	NO DATA AVAILABLE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		4 / EACH NUMBER			TECHNICAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market GENERAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market
202	DGD64266	NO DATA AVAILABLE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		1 / EACH NUMBER			TECHNICAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market GENERAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market
203	DGD48760	TS2254 / E-6225	7320705045236 / MINCING MACHINE NO 22 WITH 2HP MOTOR BASE FRAME RPM 1420		3 / EACH NUMBER	pakistan		TECHNICAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICAL ACCEPTENCE BY END USER GENERAL SPECIFICATION - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN TECHNICAL ACCEPTENCE BY END USER
204	DGE70464	NO DATA AVAILABLE	0413548003681 / TUBING PLASTIC TRANSPARENT(G/USE) O/D 32MM I/D 27MM TH.2.5MM		300 / METRE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
205	DGD64540	NO DATA AVAILABLE	0033500000452 / UTENSILS COOKINGALUM (O/D10.5", H 4.5", TH 12 SWG) WITH COVER		2 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Food Grade Aluminium Alloy 100% Free from Lead (Pb) and Cadmium (Cd) GENERAL SPECIFICATION - Food Grade Aluminium Alloy 100% Free from Lead (Pb) and Cadmium (Cd)

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	MANUF ADD	TECH / GEN SPEC
206	DGD70448		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG)		12 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT. GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT.
207	DGD64535		0035500000457 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG)		18 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT. GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT.
200	DGD66685	NO DATA AVAILABLE	0035500000507 / STRAINERS/RICE FOR POTS ALU 20X10 INCH		4 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg. GENERAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg.
209	DGD70441		0035500000520 / UTENSILS COOKING ALUMINUM WITHOUT COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)		26 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT. GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT.
210	DGD64538		0035500000520 / UTENSILS COOKING ALUMINUM WITHOUT COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)		5 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT. GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003, NO BREAKAGE/ BENT.
211	DGD59077	NO DATA AVAILABLE	0035500000385 / MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14		2 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14 WD 17 HT 25" LOCAL MADE MILD STEEL B/ ATTACHED. GENERAL SPECIFICATION - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14 WD 17 HT 25" LOCAL MADE MILD STEEL B/ ATTACHED.
212	DGD64264	NO DATA AVAILABLE	0035500000386 / MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14		1 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14 WD 17 HT 25" LOCAL MADE MILD STEEL B/ ATTACHED. GENERAL SPECIFICATION - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14 WD 17 HT 25" LOCAL MADE MILD STEEL B/ ATTACHED.
213	DGD70661	NO DATA AVAILABLE	0035500000362 / KETTLE TEA ALUMINIUM 2 GALL		4 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - ALUMINIUM (FOOD GRADE) PURITY 99.9% (LEAD FREE). GENERAL SPECIFICATION - ALUMINIUM (FOOD GRADE) PURITY 99.9% (LEAD FREE).
214	DGD66147	NO DATA AVAILABLE	0035500000362 / KETTLE TEA ALUMINIUM 2 GALL		15 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - ALUMINIUM (FOOD GRADE) PURITY 99.9% (LEAD FREE). GENERAL SPECIFICATION - ALUMINIUM (FOOD GRADE) PURITY 99.9% (LEAD FREE).
215	DGD70391	NO DATA AVAILABLE	0035500000454 / UTENSIL COOKING ALUMINIUM WITH COVER O/D 16-17", INNER WIDTH 14", HEIGHT 7" TO 8", THICKNESS 10 SWG		12 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Aluminum Grade 1100, 3003, 2024 and 5052 Aluminum Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD). GENERAL SPECIFICATION - Aluminum Grade 1100, 3003, 2024 and 5052 Aluminum Alloy Food Grade, 100% Free from lead (PB) and Cadmium (CD).
216	DGD70444	NO DATA AVAILABLE	0035500000456 / UTENSIL COOKING ALUMINIUM WITH COVER O/D: 18.5", H: 10", THICKNESS 10 SWG, Cover Thickness: 10 SWG		29 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE 100% FREE FROM LEAD (PB) AND CADMIUM (CD), Aluminum Grade 1100, 3003, 2024 and 5052. GENERAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD), Aluminum Grade 1100, 3003, 2024 and 5052.
217	DGD58383	NO DATA AVAILABLE	0035500000560 / COOKER PRESSURE-10 LITRES		2 / SET	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Aluminum Food Grade (Lead Free). GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free).
218	DGD29833	NO DATA AVAILABLE	0035500000560 / COOKER PRESSURE-10 LITRES		1 / SET	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Aluminum Food Grade (Lead Free). GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free).
219	DGE68391	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		28 / ROLL	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.No. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM, 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS; LUGS: a. Outer Diameter: 0.5cm-5mm b. Minimum storage temperature: 70C c. Full storage temperature: 110C d. Color: Black. GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.No. 5) 40MM, 32MM, 28MM, 22MM, 18MM, 12MM, 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS; LUGS: a. Outer Diameter: 0.5cm-5mm b. Minimum storage temperature: 70C c. Full storage temperature: 110C d. Color: Black. TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 50 inches. GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 50 inches.
220	DGE58538		8345705119862 / SATTON CLOTH WHITE	PRESENTATION VPI ITEM	265 / METRE			TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 50 inches. GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 50 inches.
221	DNM73864	200104-91	5331013262904 / O RING (SEE COMD F8)	ALPHA LEVEL	4 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.
222	DGD66688	NO DATA AVAILABLE	0032500000171 / SPOON TABLE MEDIUM S/STEEL		180 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - PN Crest is to be embossed. specs - stainless steel grade 316. GENERAL SPECIFICATION - PN Crest is to be embossed. specs - stainless steel grade 316.
223	DGD66687	NO DATA AVAILABLE	0032500000133 / Fork Table Medium Common S/Steel		477 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS 316 (Food Grade) & PN Crest. GENERAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS 316 (Food Grade) & PN Crest.
224	DGD26118	NO DATA AVAILABLE	0032500000133 / Fork Table Medium Common S/Steel		156 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS 316 (Food Grade) & PN Crest. GENERAL SPECIFICATION - PN Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS 316 (Food Grade) & PN Crest.
225	DGD67030	NO DATA AVAILABLE	0033500000205 / TUMBLER SODA WATER		99 / EACH	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - SIZE: HEIGHT 11CM WIDTH 7CM MATERIAL: CRYSTAL GLASS. GENERAL SPECIFICATION - SIZE: HEIGHT 11CM WIDTH 7CM MATERIAL: CRYSTAL GLASS.

S.No	LPR No	PART NO	NSN / Description	P/Equipm ent	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
228	DGD70662	NO DATA AVAILAB LE	003350000205 / TUMBLER SODA WATER.		48 / EACH/ NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - SIZE HEIGHT 11CM WIDTH 7CM MATERIAL: CRYSTAL GLASS GENERAL SPECIFICATION - SIZE: HEIGHT 11CM WIDTH 7CM MATERIAL: CRYSTAL GLASS
227	DGD67028	NO DATA AVAILAB LE	003350000208 / Tumbler Glass for Drinking Water		720 / EACH/ NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toys Basic / Nova (LOCAL) GENERAL SPECIFICATION - Material: Glass (Crystal Clear) Capacity: 280/300 ml Brand: Toys Basic / Nova (LOCAL)
228	DGE72185	BS 2992-TABLE B ITEM NO 95	8020999430557 / PAINT BRUSH 2 INCH		38 / EACH/ NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
229	DGE70470	1-401-47845	8305991252223 / COTTON CLOTH		85 / Kilo GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
230	DGE72275	IACD4210 B or CITECH 1140	4240995275965 / SAFETY HARNESS (100% POLYESTER WITH BUCKLES & D-RING	PPE	40 / EACH/ NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - MATERIAL: 100% POLYESTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH >=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah Iqbal Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: info@abdullahi-protection.com.pk b. Last Procurement date through registered supplier M/S ASHI Enterprises in Sep 18. Specification may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42100. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue stop. c. Article should be 1.4 kg in weight. User weight 150 Kg including Tools and equipment with max impact force of 6 KN. GENERAL SPECIFICATION - MATERIAL: 100% POLYESTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH >=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah Iqbal Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: info@abdullahi-protection.com.pk b. Last Procurement date through registered supplier M/S ASHI Enterprises in Sep 18. Specification may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42100. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue stop. c. Article should be 1.4 kg in weight. User weight 150 Kg including Tools and equipment with max impact force of 6 KN.
231	DCC68669		8415500358171 / RAINCOAT WHITE OFFICERS SMALL LENGTH 46 INCH		60 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - RAINCOAT WHITE OFFICERS SMALL LENGTH 46 INCH GENERAL SPECIFICATION - RAINCOAT WHITE OFFICERS SMALL LENGTH 46 INCH
232	DCW67191		8430500100532 / BOOT ANTI SKID BLACK SIZE 06		60 / PAIR			TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 06 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 06
233	DSB43232	VFD01-30KW RE-CNT	5935505268800 / VFD Contactor		2 / EACH/ NUMB ER	EVD-30KL		TECHNICAL SPECIFICATION - Operating Volt: 12 to 24VDC Current Rating: 200 Amp MAKE: TAYWAN SYSTEM 30KL VFD GENERAL SPECIFICATION - Operating Volt: 12 to 24VDC Current Rating: 200 Amp MAKE: TAYWAN SYSTEM 30KL VFD
234	DRQ57066	297SP1-011	5965142697247 / EAR MUFF (297SP1-011)		75 / EACH/ NUMB ER	C		TECHNICAL SPECIFICATION - Test Frequencies (Hz): 125 250 500 1000 2000 3150 4000 6300 8000 Mean Attenuation (dB): 21 0 26 0 30 6 40 6 30 0 41 8 42 7 41 7 41 3 Standard Deviation (dB): 1.9 2.3 2.3 2.4 2.5 2.7 1.8 2.1 2.3 NRR: 30 CSA CLASS: AL GENERAL SPECIFICATION - Test Frequencies (Hz): 125 250 500 1000 2000 3150 4000 6300 8000 Mean Attenuation (dB): 21 0 26 0 30 6 40 6 30 0 41 8 42 7 41 7 41 3 Standard Deviation (dB): 1.9 2.3 2.3 2.4 2.5 2.7 1.8 2.1 2.5 NRR: 30 CSA CLASS: AL
235	DCW67193		8430500100698 / BOOT ANTI SKID BLACK SIZE 8		60 / PAIR			TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8
236	DNM71799	011656	5330795320042 / seal oil		5 / EACH/ NUMB ER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
237	DNM71585	216061	4720715233360 / sensor angle 160 deg cw		2 / EACH/ NUMB ER	EX-130/70		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
238	DRQ65627	POLYTH ENENAT URAL	8330Z06529824 / POLYTHENE NATURAL (WIDTH 1.5 MR)		100 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - a. Maker/Model/Brand/ Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 FFL d. Parent equipment be INDICATED. Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing: (2) 500-1000 gauge Acceptance Criteria be: (3) Less Coaque mentioned. (4) water proof f. Requirement of F3 CERTIFICATE. N/A g. Requirement of minimum SHELF LIFE: No shelf life h. Application: Wrapping/ preservation of A/C components GENERAL SPECIFICATION - a. Maker/Model/Brand/ Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 FFL d. Parent equipment be INDICATED. Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing: (2) 500-1000 gauge Acceptance Criteria be: (3) Less Coaque mentioned. (4) water proof f. Requirement of F3 CERTIFICATE. N/A g. Requirement of minimum SHELF LIFE: No shelf life h. Application: Wrapping/ preservation of A/C components
239	DRQ65694	POLYTH ENENAT URAL	8330Z06529824 / POLYTHENE NATURAL (WIDTH 1.5 MR)		220 / KILO GRAM	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - a. Maker/Model/Brand/ Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 FFL d. Parent equipment be INDICATED. Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing: (2) 500-1000 gauge Acceptance Criteria be: (3) Less Coaque mentioned. (4) water proof f. Requirement of F3 CERTIFICATE. N/A g. Requirement of minimum SHELF LIFE: No shelf life h. Application: Wrapping/ preservation of A/C components
240	DCC70803		8440703801892 / T-SHIRT KHAKI HALF SLEEVES SIZE MEDIUM FOR PNP, FIRE BRIGADE AND BOAT POOL STAFF		700 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
241	DRG72002	018-260	6140Z06550740 / BATTERY LEAD ACID 24V (2 X 12V 220 AH) engine starter		2 / SET	018-260		TECHNICAL SPECIFICATION - Daweco Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH), BATTERY LEAD ACID (2V 220 AH) general Specs. PACKAGE INCLUDES 02 X 12V 220AH GENERAL SPECIFICATION - Daweco Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH), BATTERY LEAD ACID (2V 220 AH) general Specs. PACKAGE INCLUDES 02 X 12V 220AH
242	DRG71701	018-260	6140Z06550740 / BATTERY LEAD ACID 24V (2 X 12V 220 AH) engine starter		2 / SET	018-260		TECHNICAL SPECIFICATION - Daweco Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH), BATTERY LEAD ACID (2V 220 AH) general Specs. PACKAGE INCLUDES 02 X 12V 220AH GENERAL SPECIFICATION - Daweco Deep Cycle Technology Batteries, Dimension: (519x217x269) (LxWxH), BATTERY LEAD ACID (2V 220 AH) general Specs. PACKAGE INCLUDES 02 X 12V 220AH

S.No	LPR No	PART NO	NSN / Description	PREQUIP amt.	QTY / DENO	Model	MANUF ADD.	TECH / GEN SPECS.
243	DRG72870	(1) N80 (N80) (N70A/N8 GA) / (2) N-80 new nu -85 12 v85ah 11 plates	6140Z06510142 / BATTERY LEAD ACID		2 / EACH NUMB ER	N80		TECHNICAL SPECIFICATION - TYPE LEAD ACID BATTERY, MODEL: N80, VOLTS: 12, PLATES: 11 PLATES PER CELL, AMPERE 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GLE5 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD. OEM COCAUTHORIZED DEALER CERTIFICATE: NA, ITEM AVAILABLE IN LOCAL MARKET. GENERAL SPECIFICATION - TYPE LEAD ACID BATTERY, MODEL: N80, VOLTS: 12, PLATES: 11 PLATES PER CELL, AMPERE 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GLE5 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD. OEM COCAUTHORIZED DEALER CERTIFICATE: NA, ITEM
244	DRG71694	(1) N80 (N80) (N70A/N8 GA) / (2) N-80 new nu -85 12 v85ah 11 plates	6140Z06510142 / BATTERY LEAD ACID		3 / EACH NUMB ER	N80		TECHNICAL SPECIFICATION - TYPE LEAD ACID BATTERY, MODEL: N80, VOLTS: 12, PLATES: 11 PLATES PER CELL, AMPERE 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GLE5 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD. OEM COCAUTHORIZED DEALER CERTIFICATE: NA, ITEM AVAILABLE IN LOCAL MARKET. GENERAL SPECIFICATION - TYPE LEAD ACID BATTERY, MODEL: N80, VOLTS: 12, PLATES: 11 PLATES PER CELL, AMPERE 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GLE5 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD. OEM COCAUTHORIZED DEALER CERTIFICATE: NA, ITEM AVAILABLE IN LOCAL MARKET.
245	DSB67479		8020TY6719549 / PAINTING BRUSH ANGULAR 45MM		580 / EACH NUMB ER	NO DATA AVAILA BLE		TECHNICAL SPECIFICATION - a. Name Bristle Painting Brush 45 mm b. Material Synthetic Bristle Material c. Bristle Color White+ Brown d. Bristle Width 45 mm e. Bristle Thickness 13.5 mm f. Handle Material Maple Wood g. Handle Color Natural Material GENERAL SPECIFICATION - a. Name Bristle Painting Brush 45 mm b. Material Synthetic Bristle Material c. Bristle Color White+ Brown d. Bristle Width 45 mm e. Bristle Thickness 13.5 mm f. Handle Material Maple Wood g. Handle Color Natural Material
246	DSA66759	7141- 31200	3433TY6720321 / Grade T Single line Welding hose CGA E- 1,ARPM IP-7 Series 7141 (Red-Fuel Gas Line Series 7142 (Green-Oxygen Line		400 / METE R	NO DATA AVAILA BLE		TECHNICAL SPECIFICATION - Brand EXAMPLE: Series 7141 Parker 7141welding fuel Gas (G) Max WP 200 Psi ARMP/CGA IP7(Yeas) STD duty Grade T couple with One inch Ferrules Made in USA Series 7142 Parker 7142 welding Oxygen Gas (G) Max WP 200 Psi ARMP/CGA IP7(Yeas) STD duty Grade T couple with One inch Ferrules Made in USA. Firm quotation enclosed. 2. Tube Black chromopne 3. Reinforcement Multiple textile plies 4. Industry standard CGA E-1,ARPM IP-7. 5. Application of Series 7141(Red), Acetylene, Hydrogen, Natural Gas, propane. 6. Application of Series 7142 Green Welding Brazing, Cutting, gouging, Preheating, Post heating 7. Refer to ARPM IP-7 Specification for rubber welding hose and hose technical bulletin 11-5 Dimensional Specification and acceptance criteria Series 7141 (Red-Fuel Gas Line) Part ID: Ø ID Rein: ODI Ø OD Approx Min Min Max Max Std Number (in) Min Pies (in) (mm) Wt Wt Bend Bend Rec Rec Pack (lb/ft) (kg/ft) Rad Rad WP WP Qty (in) (mm) (Psi) (Psi) (ft) 7141-31200 3/16" 7.9 2 0.594" 15.1 0.14 0.06 3 0" 76 2 200 13.8 730 Series 7142 (Green-Oxygen Line) Part ID: Ø ID Rein: ODI Ø OD Approx Min Min Max Max Std Number (in) Min Pies (in) (mm) Wt Wt Bend Bend Rec Rec Pack (lb/ft) (kg/ft) Rad Rad WP WP Qty (in) (mm) (Psi) (Psi) (ft) 7142-31200 3/16" 7.9 2 0.594" 15.1 0.14 0.06 3 0" 76 2 200 13.8 730 GENERAL SPECIFICATION - Brand EXAMPLE: Series 7141 Parker 7141welding fuel Gas (G) Max WP 200 Psi ARMP/CGA IP7(Yeas) STD duty Grade T couple with One inch Ferrules Made in USA Series 7142 Parker 7142 welding Oxygen Gas (G) Max WP 200 Psi ARMP/CGA IP7(Yeas) STD duty Grade T couple with One inch Ferrules Made in USA. Firm quotation enclosed. 2. Tube Black chromopne 3. Reinforcement Multiple textile plies 4. Industry standard CGA E-1,ARPM IP-7. 5. Application of Series 7141(Red), Acetylene, Hydrogen, Natural Gas, propane. 6. Application of Series 7142 Green Welding Brazing, Cutting, gouging, Preheating, Post heating 7. Refer to ARPM IP-7 Specification for rubber welding hose and hose technical bulletin 11-5 Dimensional Specification and acceptance criteria Series 7141 (Red-Fuel Gas Line) Part ID: Ø ID Rein: ODI Ø OD Approx Min Min Max Max Std Number (in) Min Pies (in) (mm) Wt Wt Bend Bend Rec Rec Pack (lb/ft) (kg/ft) Rad Rad WP WP Qty (in) (mm) (Psi) (Psi) (ft) 7141-31200 3/16" 7.9 2 0.594" 15.1 0.14 0.06 3 0" 76 2 200 13.8 730
247	DNM71794	0110732	2815795320033 / valve seat insert		12 / EACH NUMB ER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
248	DCF69119		8345500000880 / FLAG NATIONAL STANDARD PAKISTAN FITTED		18 / EACH NUMB ER			TECHNICAL SPECIFICATION - FLAG NATIONAL STANDARD PAKISTAN FITTED GENERAL SPECIFICATION - FLAG NATIONAL STANDARD PAKISTAN FITTED
249	DSA68952	ORR- MC170V 218DES- 100	6126705218777 / DC-DC CONVERTOR		2 / EACH NUMB ER	NO DATA AVAILA BLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA
250	DCC70805		8440703801893 / T-SHIRT KHAKI HALF SLEEVES SIZE LARGE FOR PNP,FIRE BRIGADE AND BOAT POOL STAFF		700 / EACH NUMB ER			TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
251	DCF72670		8345500000442 / CAR FLAG COMDEP		8 / EACH NUMB ER			TECHNICAL SPECIFICATION - CAR FLAG COMDEP GENERAL SPECIFICATION - CAR FLAG COMDEP
252	DNM71796	0111654	5330795320046 / seal oil		6 / EACH NUMB ER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
253	DNM71795	0101520	5330795320044 / gasket		1 / EACH NUMB ER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
254	DSB67069	102034	3415725166877 / Flap Grinding Disk		478 / EACH NUMB ER	EN13743		TECHNICAL SPECIFICATION - OEM Rhodus Germany • Model No. EN13743 • Size 180x22 23 • Outer dia 180 mm • Inner hole dia 22 23 mm • Packing details (enclosed) - expiry date of Flap Grinding Disk is not mandatory. GENERAL SPECIFICATION - OEM Rhodus Germany • Model No. EN13743 • Size 180x22 23 • Outer dia 180 mm • Inner hole dia 22 23 mm • Packing details (enclosed) - expiry date of Flap Grinding Disk is not mandatory.
255	DSA70428	QSR141- SDF9ALE CF15CN1 7-03	5306143290375 / VIS CSM 141-08 INOX		288 / EACH NUMB ER	NO DATA AVAILA BLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
256	DRG72003	GP-88	2810Z05238478 / GP-88 Complete with Accessories		2 / EACH NUMB ER	GP-88 Engine		TECHNICAL SPECIFICATION - GP 88 Twin Cylinder 88cc Engine gen specs: Package include: • GP-88 Engine • Hub Set (Hub + Hub Screw) • Propeller Plate • Carburetor Set (Carburetor Throttle Arm (2Pieces)) • Reed Valve Set Combo • Muffler Kit (Muffler with Gasket • Single Igniter • Hot Sensor • NGK CWS Spark Plugs • Magnot GENERAL SPECIFICATION - GP-88 Twin Cylinder 88cc Engine gen specs: Package include: • GP-88 Engine • Hub Set (Hub + Hub Screw) • Propeller Plate • Carburetor Set (Carburetor Throttle Arm (2Pieces)) • Reed Valve Set Combo • Muffler Kit (Muffler with Gasket) • Single Igniter • Hot Sensor • NGK CWS Spark Plugs • Magnot
257	DSA70080	MS1-107	6605142694407 / GLACE MS1- 107 SAGEM		1 / EACH NUMB ER	NO DATA AVAILA BLE		TECHNICAL SPECIFICATION - Glace MS1-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 8.375 ±0.03 (APPROX) PRESSURE TEST: 45 BAR X 02-HOURS GENERAL SPECIFICATION - Glace MS1-107 Material: TEMPERED GLAS VISIBILITY: TRANSPARENT WEIGHT: 8.375 KG (APPROX) PRESSURE TEST: 45 BAR X 02 HOURS
258	DCW67199		8438500100531 / BOOT ANTISKID BLACK SIZE 12		60 / PAIR			TECHNICAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12 GENERAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / GEND	Mode	MANUF ADD	TECH / GEN SPECS
256	DSM68612	915-140-40	6135143231890 / BATTERY 12V (7AH)		1 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
260	DSA70941	504802	5340144175333 / AMORTISSEUR CONIFOR		14 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
261	DSM61394	C965CS	4320131122224 / C965CS ELECTRO PUMP		2 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Pump nature - centrifugal pump type: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange: 80 mm (gun metal) GENERAL SPECIFICATION - Pump nature - centrifugal pump type: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange: 80 mm (gun metal)
262	DCF69118		8345500000087 / FLAG JACK CERIMONIAL SZ 6.50X3.00FT		16 / EACH NUMBER			TECHNICAL SPECIFICATION - FLAG JACK CERIMONIAL SZ 6.50X3.00FT GENERAL SPECIFICATION - FLAG JACK CERIMONIAL SZ 6.50X3.00FT
263	DRG49399	Z09M7572	1560206867572 / WHEEL		20 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tyre Diameter 535 mm Tyre Ply Rating 4 ply Hub Type Locally Made Load Capacity Varies (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub GENERAL SPECIFICATION - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tyre Diameter 535 mm Tyre Ply Rating 4 ply Hub Type Locally Made Load Capacity Varies (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub
264	DNQ64387	334 36105	4240715269813 / 3m safety goggles		40 / EACH NUMBER	S34 6698		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
265	DRG70343	Z20R2234737785	2920151013185 / STARTER MOTOR		1 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
266	DNQ69658	RSFD-2	6140795300635 / LITHIUM BATTERY OF AUTOFLASHING LIFERAFT LIGHT		6 / EACH NUMBER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
267	DSB61297	MAT194-0343F02R EP07	0870071544730 / STEEL WELDING CURVE SIZE (ELBOW) DN - 48.3 x 2.6 mm		18 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - OUTER DIA: 48.3MM THICKNESS: 2.6MM BENDING RADIUS: R-57 COUNTRY OF ORIGIN: FRANCE MATERIAL: T1037C PLACED AT ENCL 1 DIMENSION: PLACED AT ENCL 2 GENERAL SPECIFICATION - OUTER DIA: 48.3MM THICKNESS: 2.6MM BENDING RADIUS: R-57 COUNTRY OF ORIGIN: FRANCE MATERIAL: T1037C PLACED AT ENCL 1 DIMENSION: PLACED AT ENCL 2
268	DRG68528	Z09M7058	5965Z06567058 / PNEUMATIC PIPE ADAPTER		28 / PAIR	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - make: Local made SPECIFICATIONS - Pneumatic pipe adapter used to connect high pressure pneumatic pipes of 1/2 inch diameter. Available in two parts, male & female. Made of steel or iron to handle high pressures. Item commercially available in local market GENERAL SPECIFICATION - make: Local made SPECIFICATIONS - Pneumatic pipe adapter used to connect high pressure pneumatic pipes of 1/2 inch diameter. Available in two parts, male & female. Made of steel or iron to handle high pressures. Item commercially available in local market
269	DSB61296	MAT194-0343F02R EP13	0870071544730 / Steel WELDING CURVE SIZE DN - 76.1 x 2.9 mm		36 / EACH NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - OUTER DIA: 76.1MM THICKNESS: 2.9MM BENDING RADIUS: R-95 COUNTRY OF ORIGIN: FRANCE Material: T1037C grade, placed at Encl 1. Dimension: placed at Encl 2 GENERAL SPECIFICATION - OUTER DIA: 76.1MM THICKNESS: 2.9MM BENDING RADIUS: R-95 COUNTRY OF ORIGIN: FRANCE Material: T1037C grade, placed at Encl 1. Dimension: placed at Encl 2
270	DNM71793	oh11311	2815795320039 / sleeve		6 / EACH NUMBER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
271	DCC66471		8405501900182 / DRESS KHAKI MALE SWEEPER SIZE SMALL		150 / PAIR			TECHNICAL SPECIFICATION - DRESS KHAKI MALE SWEEPER SIZE SMALL GENERAL SPECIFICATION - DRESS KHAKI MALE SWEEPER SIZE SMALL
272	DCW67198		8430500100833 / BOOT ANTI SKID BLACK SIZE 11		60 / PAIR			TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11
273	DSA69094	TAG-400	5130TY8730147 / PNEUMATIC GRINDER 4"		6 / EACH NUMBER	TAG 40PRH		TECHNICAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODEL: TAG-40PRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN GENERAL SPECIFICATION - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODEL: TAG-40PRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN
274	DCW67196		8430500100700 / BOOT ANTI SKID BLACK SIZE 10		60 / PAIR			TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 10 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 10
275	DNQ73716	11788009	6210795312162 / EXTERNAL LAMP UNIT (RL6)		2 / EACH NUMBER	NA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
276	DRQ71491	A-A-1985	84150026883308 / GLOVES		32 / PAIR			TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null
			COTTON (NATURAL IN COLOUR)					null

S.No	LPR No	PART NO	NSN / Description	Equipment	QTY / DEND	Model	MANUF ADO	TECH / GER SPECS
277	DCC70806		8440703801894 / T-SHIRT KHAKI HALF SLEEVES SIZE EX-LARGE FOR PNP,FIRE BRIGADE AND BOAT POOL STAFF		700 / EACH/ NUMBER			TECHNICAL SPECIFICATION : null GENERAL SPECIFICATION : null
278	DCC70802		8440703801891 / T-SHIRT KHAKI HALF SLEEVES SIZE SMALL FOR PNP,FIRE BRIGADE AND BOAT POOL STAFF		700 / EACH/ NUMBER			TECHNICAL SPECIFICATION : null GENERAL SPECIFICATION : null
279	DRP65027	11000244	1680Z05268861 / TRANSMISSION OIL		60 / LITER	Shell Spirax S4 CX 30		TECHNICAL SPECIFICATION : BRAND: Shell Spirax S4 CX 30 TYPE: High performance off highway transmission oil. MAKE: 100004 GENERAL SPECIFICATION : BRAND: Shell Spirax S4 CX 30 TYPE: High performance off highway transmission oil. MAKE: 100004
280	DRG71696	NS100/ N130P	6140Z06529183 / BATTERY LEAD		1 / EACH/ NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100. SIZE:367MMX173X226(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION : BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE:367MMX173X226(LXWXH)MADE IN PAKISTAN
281	DRG71690	6XNS25/ N150EXI DE N200	6140Z065388612 / BATTERY LEAD ACID 12 VOLT		1 / EACH/ NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : TYPE N150/N325/N125 CAPACITY:170/155 VOLTAGE 12. DIMENSION:502 X 222 X 252 MAKE EXIDE GENERAL SPECIFICATION : TYPE N150/N325/N125 CAPACITY:170/155 VOLTAGE 12. DIMENSION
								502 X 222 X 252 MAKE EXIDE
282	DCW67201		8430500100961 / BOOT ANTI SKID BLACK SIZE-14		65 / PAIR			TECHNICAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE-14 GENERAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE-14
283	DCW67192		8430500100897 / BOOT ANTI SKID BLACK SIZE 7		65 / PAIR			TECHNICAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE 7 GENERAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE 7
284	DNM71792	0110731	2805997260776 / valve seat insert		12 / EACH/ NUMBER			TECHNICAL SPECIFICATION : null GENERAL SPECIFICATION : null
285	DCC70807		8440703801895 / T-SHIRT KHAKI HALF SLEEVES SIZE EX-LARGE FOR PNP,FIRE BRIGADE AND BOAT POOL STAFF		700 / EACH/ NUMBER			TECHNICAL SPECIFICATION : null GENERAL SPECIFICATION : null
286	DRG59991	T400206/ 2873K021	6105715159630 / STARTER MOTOR		1 / EACH/ NUMBER			TECHNICAL SPECIFICATION : AS PER PUBLICATION GENERAL SPECIFICATION : AS PER PUBLICATION
287	DSA71788	38-017/ BFP-12- T213-VTX	0850886567213 / BATTERY FLEXIBLE HOSE		250 / METRE	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : NO DATA AVAILABLE GENERAL SPECIFICATION : NO DATA AVAILABLE
288	DCW67200		8430500100960 / BOOT ANTI SKID BLACK SIZE-13		60 / PAIR			TECHNICAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE-13 GENERAL SPECIFICATION : BOOT ANTI SKID BLACK SIZE-13
289	DSB61298		0870071514730 / steel WELDING CURVE SIZE: DIA 88.9 X 6.3MM		36 / EACH/ NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : OUTER DIA: 88.9MM THICKNESS: 6.3MM BENDING RADIUS: R-114 COUNTRY OF ORIGIN: FRANCE Material: TUS30 Technical Data acceptance criteria: placed at End 1. Dimension: placed at End 1 GENERAL SPECIFICATION : OUTER DIA: 88.9MM THICKNESS: 6.3MM BENDING RADIUS: R-114 COUNTRY OF ORIGIN: FRANCE Material: TUS30 Technical Data acceptance criteria: placed at End 1. Dimension: placed at End 1
290	DRG73276	7133019	6140016219168 / BATTERY 12V 95AH (MAINTENANCE FREE)		2 / EACH/ NUMBER	TLD EUROPE		TECHNICAL SPECIFICATION : 12V 95AH GENERAL SPECIFICATION : 12V 95AH
291	DRG70418	A5476/VP	2915Z06527526 / REGULATOR LP AIR		1 / EACH/ NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE 0-350 & 0-4000 PSI RANGE). TANAKA JAPAN GENERAL SPECIFICATION : AIR REGULATOR LOW PRESSURE (GAUGE DIA 2-3 INCHES) MAKE JAPAN SINGLE STAGE VENUS OXYG REGULATOR WITH TWIN GAUGES(RANGE:0-350 & 0-4000 PSI RANGE). TANAKA JAPAN
292	DRG72872	6X120(BX 15)	6140Z06538699 / BATTERY LEAD ACID 12 VOLTS,105 AH		3 / EACH/ NUMBER	NO DATA AVAILABLE		TECHNICAL SPECIFICATION : LENGTH: 367MM W:173MM HIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15 GENERAL SPECIFICATION : LENGTH: 367MM W:173MM HIGHT:228MM LEAD ACID 12V,105AH,EXIDE 6X15

S.No	LPR No	PART NO	NSN / Description	P/Equipm USE	QTY / DENO	Model	MANUF ADD	TECH / GEN SPEC
293	DCD65899		8440503900856 / CAP ROUND WHITE SIZE 7"		450 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 7" <u>GENERAL SPECIFICATION</u> - CAP ROUND WHITE SIZE 7"
294	DSB71178		4730TY6715006 / COPPER ELBOW DIA42MF		4 / EACH/ NUMB ER	NO DATA AVAILAB LE		<u>TECHNICAL SPECIFICATION</u> - MATERIAL: COPPER DIA: 42 MM DEGREE: 45 THICKNESS: 1.5 MM TYPE MALE & FEMALE <u>GENERAL SPECIFICATION</u> - MATERIAL: COPPER DIA: 42 MM DEGREE: 45 THICKNESS: 1.5 MM TYPE MALE & FEMALE
295	DCW67194		8430500100699 / BOOT ANTI SKID BLACK SIZE 9		80 / PAIR			<u>TECHNICAL SPECIFICATION</u> - BOOT ANTI SKID BLACK SIZE 9 <u>GENERAL SPECIFICATION</u> - BOOT ANTI SKID BLACK SIZE 9
296	DSA68913		0940388567003 / RUBBER PACKING (RUBAN MOLTOPRENE 16X2 (ONE ROLL 50 FEET)		90 / ROLL	NO DATA AVAILAB LE		<u>TECHNICAL SPECIFICATION</u> - SIZE: LENGTH =50 FEET WIDTH= 1 inch THICKNESS =3MM <u>GENERAL</u> <u>SPECIFICATION</u> - SIZE: LENGTH =50 FEET WIDTH= 1 inch THICKNESS =3MM
297	DSB71176		4730TY6715002 / COPPER ELBOW 22MM MALE& FEMALE		12 / EACH/ NUMB ER	NO DATA AVAILAB LE		<u>TECHNICAL SPECIFICATION</u> - MATERIAL: COPPER DIA: 22 MM DEGREE: 90 THICKNESS: 1 MM TYPE MALE & FEMALE <u>GENERAL SPECIFICATION</u> - MATERIAL: COPPER DIA: 22 MM DEGREE: 90 THICKNESS: 1 MM TYPE MALE & FEMALE
298	DSB67142	5330JA- BAGUER UCHDE 17 15 / (LOCAL) TR150RH REMANU	5330143668779 / WATER TIGHTNESS RING TEFLON, S/STEEL & O-RING		190 / EACH/ NUMB ER	NO DATA AVAILAB LE		<u>TECHNICAL SPECIFICATION</u> - SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) <u>GENERAL SPECIFICATION</u> - SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)