

**TENDER BULLETIN**

**TENDER CLOSING/OPENING DATE 08-01-2025**

**CONDITIONS**

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONG WITH THEIR BIDS
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
1	DGT74054	NO DATA AVAILABL E	0100500000049 / TEAK WOOD BURMESE GRADE- I SLEEPER	SPECE/IM.276 3 (A)	10 / CUBIC FOOT	NO DATA AVAILAB LE			<b>TECHNICAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH Moisture Content= 12%±02% GENERAL SPECIFICATION - P-SG/730 (B) SIZE: LENGTH=12-16 FT, WIDTH=09-18 INCH, THICKNESS=8-10 INCH Moisture Content= 12%±02%</b>
2	DGP74000	HP Scanner 20G05A/L 2747A	7490705218483 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	1 / EACH/N UMBER	HP Scanner 20G05A/ Pro 2500 F1	MS ORA- TECH SYSTEM ,FOUR SQUARE PLAZA 4TH FLOOR, BUILDIN G NO 21- A, H.H FAROO QI ROAD OFF TARIQ	HP	<b>TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF,UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF,UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297</b>
3	DGP73795	HP Scanner 20G05A/L 2747A	7490705218483 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	2 / EACH/N UMBER	HP Scanner 20G05A/ Pro 2500	MS ORA- TECH SYSTEM FOUR	HP	<b>TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF,UPTO 1200DPI, DUTY</b>
4	DGE72642	4-0076-9700	4240015274018 / SAFETY GLASSES,REVISI ON SAWFLY	OHP	50 / EACH/N UMBER		NAM: REVISIO N EYEWE AR LTD. CTR: UNITED STATES TEL: 802-999-999-	HASTIN GS FIBER GLASS PRODU CTS	<b>TECHNICAL SPECIFICATION - NAM REVISION EYEWEAR LTD. CTR UNITED STATES TEL: 802-999-4031 FAX: 802-879-7224 WWW: HTTP://WWW.REVISIONEYEWEAR.COM GENERAL SPECIFICATION - NAM: REVISION EYEWEAR LTD CTR: UNITED STATES TEL: 802-999-4031 FAX: 802-879-7224 WWW: HTTP://WWW.REVISIONEYEWEAR.COM</b>
5	DGE72306	CARE SURVIVAL I TEL- STAR 6 STROBE( MODEL HS-640-5	1095735231260 / CARE SURVIVAL ITEL ? STAR 6 STROBE IS FOR FUNCTION	CARE SURVIVAL ITEL ? STAR 6 STROBE IS FOR FUNCTION	25 / EACH/N UMBER	NIKON D 7200 24 MP 18-140MM DSLR CAMER A	TNVC TACTIC AL NIGHT VISION COMPA NY TEL:	TNVC TACTIC AL NIGHT VISION COMPA NY	<b>TECHNICAL SPECIFICATION - CARE SURVIVAL ITEL ? STAR 6 STROBE IS FOR FUNCTION HELMET MOUNTED LIGHT USED IN AT/ CT OPS GENERAL SPECIFICATION - CARE SURVIVAL ITEL ? STAR 6 STROBE IS FOR FUNCTION HELMET MOUNTED LIGHT USED IN AT/ CT OPS</b>
6	DGP74014	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP402 D/M402DN/M404D N	COMPUTER	3 / EACH/N UMBER	NO DATA AVAILAB LE	PK	PAKISTA N	<b>TECHNICAL SPECIFICATION - Laser 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages Paper Type A4/A5/B5/Legal/Envelope Connectivity Paraller and USB Port Both GENERAL SPECIFICATION - Laser 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</b>

N	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	MANUF ADDO	Availabil ity	TECH / GEN SPECS
7	DGP73823	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP402 D/M402DN/M404D N	COMPUTER	8 / EACH/N UMBER	NO DATA AVAILAB LE	PK	PAKISTA N	<u>TECHNICAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB . 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages. Paper Type A4/A5/B5/L egal/Envelope. Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB . 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages. Paper Type A4/A5/B5/L egal/Envelope. Connectivity Paraller and USB Port Both
8	DGP74004	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP402 D/M402DN/M404D N	COMPUTER	3 / EACH/N UMBER	NO DATA AVAILAB LE	PK	PAKISTA N	<u>TECHNICAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB . 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages. Paper Type A4/A5/B5/Legal/Envelope. Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB . 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages. Paper Type A4/A5/B5/Legal/Envelope. Connectivity Paraller and USB Port Both
9	DGE73635	NIL	7460705141092 / REVOLVING COMPUTER CHAIR	REVOLVING COMPUTER CHAIR	20 / EACH/N UMBER	NO DATA AVAILAB LE	PK	MASTER AUTHORIZED DEALER SHAHRA FAISAL KARACHI	<u>TECHNICAL SPECIFICATION</u> - OEM ADD:M/S TIME&TUNE,60 A-8,1ST FLOOR,KHAN CHAMBERS,CANNING ROAD,RAWALPINDI,PAKISTAN <u>GENERAL SPECIFICATION</u> - OEM ADD:M/S TIME&TUNE,60 A-8,1ST FLOOR,KHAN CHAMBERS,CANNING ROAD,RAWALPINDI,PAKISTAN
10	DGP70876	50DU7000 /50AU700 0/46EH50 00	7730705174391 / SAMSUNG LED TV 46/49/50 INCH	LED TV	3 / EACH/N UMBER	46EH500 0	SAMSU NG	SAMSU NG	<u>TECHNICAL SPECIFICATION</u> - SAMSUNG LED TV 46/49/50 INCH <u>GENERAL SPECIFICATION</u> - SAMSUNG LED TV 46/49/50 INCH
11	DGP73853	KLV32R30 2E/P- 0114000	7730785166767 / LED TV SONY 32 INCH	PSS VIGIL SYSYTEM	2 / EACH/N UMBER	SONY KLV32R 302E	M/s CETC Mansion, No. 5 Wulaton	M/s CETC Internatio nal CO., LTD	<u>TECHNICAL SPECIFICATION</u> - BRAVIA SONY 32BX350 or Equivelent <u>GENERAL SPECIFICATION</u> - BRAVIA SONY 32BX350 or Equivelent
12	DGP73996	LQ-2190	7025735150505 / EPSON LQ-2190 DOT MATRIX PRINTER	EPSON	1 / EACH/N UMBER	EPSON	EPSON	EPSON	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
13	DGP73875	T6B59A	7435735226856 / HP COLOR LASERJET PRO M254NW PRINTER	UFFFAQ	1 / EACH/N UMBER	M254nw	HP Inc., 1 Depot Close, Singapor e	HP, Singapor e	<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE
14	DGE73342	SA9- 27017	6260010744229 / LIGHT,CHEMILUMI NESCENT GREEN	REPLENISHM ENT LIGHT	300 / EACH/N UMBER		CYALUM E TECHN OLOGIE S SA 295 R MAYOR DE MONTRI CHER AIX EN	CYALUM E TECHNO LOGIES	<u>TECHNICAL SPECIFICATION</u> - GENERAL <u>SPECIFICATION</u> -

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
15	DGE72835	SA9-27017	6260010744229 / LIGHT,CHEMILUMINESCENT GREEN	REPLENISHMENT LIGHT	200 / EACH/NUMBER		CYALUM E TECHNOLOGIE S SA 295 R MAYOR DE MONTRICHER AIX EN	CYALUM E TECHNOLOGIES	<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>
16	DGP73854	32D2900	5820735208496 / 32 INCH LED DISPLAY WITH HDMI & VGA I/P	CCTV System	1 / EACH/NUMBER	32D2900	TCL Electronics Australia Pty Ltd, Address: 797 Springvale Rd, Mulgrave, VIC 3170	M/s TCL Australia	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
17	DGP73794	50AU7000	7730705132179 / TV LCD 46/49 INCH		1 / EACH/NUMBER	50AU7000	PK	AUTHORITY LETTER # NS-5/9205/S SC/NHQ/07 DT 24/05/08	<u>TECHNICAL SPECIFICATION - S.No</u> Technical Specification Technical Data a. View Angle 178" b. Brightness 500cd/m2 c. Size 46/49 Inch d. Response Time 5ms e. Brand Samsung f. Screen Type LED g. Smart TV Yes h. HDMI 3 j. USB 2 k. Operating System Tizen l. Width x Height x Depth (With stand) 46"= 71.64cm x 26.13 cm 49"= 110.28cm x 63.78cm x 5.91cm m. Warranty 01 Year n. Model 46 Inch LED HD TV(UA46F6100AR) 49 Inch LED HD TV(949N5300) p. Resolution (Pixels) 1920 x 1080 q. Color Black <u>GENERAL SPECIFICATION - S.No</u> Technical Specification Technical Data a. View Angle 178" b. Brightness 500cd/m2 c. Size 46/49 Inch d. Response Time 5ms e. Brand Samsung f. Screen Type LED g. Smart TV Yes h. HDMI 3 j. USB 2 k. Operating System Tizen l. Width x Height x Depth (With stand) 46"= 71.64cm x 26.13 cm 49"= 110.28cm x 63.78cm x 5.91cm m. Warranty 01 Year n. Model 46 Inch LED HD TV(UA46F6100AR) 49 Inch LED HD TV(949N5300) p. Resolution (Pixels) 1920 x 1080 q. Color Black
18	DGP73850	KD55X7000F/UHD 4K Smart TV AU7000	7730705214892 / SMART LED TV 55"	F-22P SIMULATOR	1 / EACH/NUMBER	LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000	PLOT NO.C-4/A, S.I.T.E., Karachi, Pakistan. Tel:+92921)3257 1111-2 Fax+92(21)3255 3111	SONY	<u>TECHNICAL SPECIFICATION - a</u> Item Smart LED b. Company Name: Haier/SONY c. Model No: LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size 55 x inches e. Resolution: 3840 x 2160 f. Digital TV system DVB S2 + T2 g. Aspect Ratio 16:9 <u>GENERAL SPECIFICATION - a</u> Item Smart LED b. Company Name: Haier/SONY c. Model No: LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size 55 x inches e. Resolution 3840 x 2160 f. Digital TV system DVB S2 + T2 g. Aspect Ratio 16:9

S.N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
19	DGP73792	KD55X7000F/UHD 4K Smart TV AU7000	7730705214892 / SMART LED TV 55"	F-22P SIMULATOR	2 / EACH/NUMBER	LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000	PLOT NO C-4/A, S.I.T E., Karachi, Pakistan, Tel.+92921)32571111-2 Fax:+92(21)32553111	SONY	<b>TECHNICAL SPECIFICATION</b> - a Item : Smart LED b. Company Name: Haier/SONY c Model No : LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e Resolution: 3840 x 2160 f. Digital TV system DVB S2 + T2 g. Aspect Ratio : 16.9 <b>GENERAL SPECIFICATION</b> - a. Item : Smart LED b Company Name: Haier/SONY c Model No LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e Resolution 3840 x 2160 f. Digital TV system DVB S2 + T2 g. Aspect Ratio : 16.9
20	DGE73340	0413-8532 80413_92 3_8899, BS1154	0413599238899 / RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50",TENSILE STRENGTH : 2500 PSI		200 / KILOGRAMME				<b>TECHNICAL SPECIFICATION</b> - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50",TENSILE STRENGTH : 2500 PSI packing requirement standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21 <b>GENERAL SPECIFICATION</b> - RUBBER SHEET,SOLID, NATURAL RUBBER,LG 72" CLR OFF WHITE TH 0.500" WD 48" APP WT 4LBS PER SQ FT, BS 1154 COPOUND 42, HARDNESS RATING 42-50",TENSILE STRENGTH : 2500 PSI packing requirement standard packing Updated vide PN/COMAUXMIN 9/PNS MOAWIN/03/10085084 dated 13 aug 21
21	DGE72171	NO DATA AVAILABLE	0413591430200 / O.RING (38.2 x 2.6 mm) (RUBBER)	Piping System	50 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION</b> - MATERIAL: RUBBER. SIZE: 38.2 x 2.6 mm <b>GENERAL SPECIFICATION</b> - MATERIAL: RUBBER
22	DGE72376	NIL	0413599238777 / Hose Rubber, 3-Ply (FLEXABLE), Internal Dia 0.750"		500 / METER				<b>TECHNICAL SPECIFICATION</b> - SPECS= BS 2860, Internal dia = 19 mm (Inch 0.750), MINIMUM Working Pressure= 20 Bar, Maximum Working pressure= 40 Bar (580psi), Temp Range = -35 to 80 °C, Packing = Plastic Paper, oem coc/document/dealer certificate= REQUIRED, PARENT EQUIP= ABRASIVE BLAST CLEANING MACHINE <b>GENERAL SPECIFICATION</b> - SPECS= BS 2860, Internal dia = 19 mm (Inch 0.750), MINIMUM Working Pressure= 20 Bar, Maximum Working pressure= 40 Bar (580psi), Temp Range = -35 to 80 °C, Packing = Plastic Paper, oem coc/document/dealer certificate= REQUIRED, PARENT EQUIP= ABRASIVE BLAST CLEANING MACHINE
23	DGE72234	BRUSH LEG 4.375"	0476599430411 / BRUSH PAINT SQARE EDGE ONE KNOT GROUND WD.2.500"		51 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
24	DGE72240		0476599430414 / BRUSH PAINT SQ EDGE S/TOOL 8 STCL MRKG EXP DIA 1.125"LG 2.8"		10 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
25	DGE72221		0476599242785 / BROOM PUSH W/O HANDLE		34 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE

S.No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availability	TECH / GEN SPECS
26	DGE72250	FIFA10771	0476599430451 / BRUSH ARTISTS STYLE IMPRINTING		15 / EACH/NUMBER				TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA
27	DGE72864	C-268	0476599430559 / BRUSH VARNISH TYNEX FLAT SQUARE EDGE WD.4		96 / EACH/NUMBER				TECHNICAL SPECIFICATION - stock thickness: 01 inch expose length: 3 25 inch specs bs2992 table 8 GENERAL SPECIFICATION - stock thickness: 01 inch expose length: 3 25 inch specs bs2992 table 8
28	DGE73181	0415-2502	0415599231450 / CORK AND RUBBER SHEET, LG.01 MTR WIDTH 01 MTR THICK 3.175MM.SYNTHETIC RUBBER DEF 22		4 / SHEET				TECHNICAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3 175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber GENERAL SPECIFICATION - CORK AND RUBBER SHEET,Item Specification: DEF-22,THIC=3 175mm,LG=01 MTR WIDTH 01 MTR Synthetic Rubber.
29	DGB72876		0276709106592 / VICE ENGINEERS WIDTH OF JAW 4.5", NOM OPENING 5-1/2",	JAW 3-1/4"PARALLEL, QUICK RELEASE	7 / EACH/NUMBER				TECHNICAL SPECIFICATION - Jaw Opening 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England GENERAL SPECIFICATION - Jaw Opening 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England
30	SGB73430		0283595711448 / ROD NAVAL BRASS RD DIA 1-1/8,	SERVICE PUMP	10 / METER				TECHNICAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft 3.70 lb authority: br320d BS EN/2163 OF 1998 GRADE CW719R(M) GENERAL SPECIFICATION - runing length: 2 METERS (minimum) weight/ft:3.70 lb authority: br320d BS EN/2163 OF 1998 GRADE CW719R(M)
31	DGE72852	1Q04 MIL	0413599239706 / HOSE RUBBER INTERNAL DIA: 3.00", EXTERNAL DIA: 3.50", BURST PRESSURE: 150PSI		60 / METER	PRF 11588 TYPE III			TECHNICAL SPECIFICATION - SPECIFICATIONS: 1 Synthetic rubber inner surface and outer covering, reinforced with rubber impregnated fabric 2 color black with longitudinal BLUE stripe, Use: for hot mineral oil & aviation fuel. 3. No of plies 4, length Aprox 20 ft. 4. Spec: BSF67 type1 5. AUTHORITY AS PER BR-320D. GENERAL SPECIFICATION - SPECIFICATIONS: 1. Synthetic rubber inner surface and outer covering, reinforced with rubber impregnated fabric. 2. color black with longitudinal BLUE stripe, Use: for hot mineral oil & aviation fuel 3 No of plies 4, length Aprox 20 ft 4 Spec BSF67 type1 5. AUTHORITY AS PER BR-320D.
32	DGE71396		0451591292989 / CLOTH COATED PVC FOR FURNITURE UPHOLSTERY COLOUR BLUE WD,50 INCH	FOR SPECS SEE CMD 8	425 / METER				TECHNICAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd 50 INCH GENERAL SPECIFICATION - ISO7617-2 OF 1994 colour blue wd 50 INCH

S N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
33	SGB70111		0214580001004 / NUT (Dia 10mm) WITH BOLT STEEL (Dia 10.00MM) 480TD	S/M	500 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION -</b> HEXAGON BOLT DIMENSION: OUT SIDE DIA: 10 MM PITCH THREAD: 1.5 MM LENGTH: 40 MM LENGTH WITHOUT HEAD: 35 MM HEAD WIDTH: 20 MM HEXAGON NUT DIMENSION: INSIDE DIA: 10 MM PITCH THREAD: 1.5 MM HEIGHT: 7 MM WIDTH: 20 MM MATERIAL GRADE EN 4140 <b>GENERAL SPECIFICATION -</b> HEXAGON BOLT DIMENSION: OUT SIDE DIA: 10 MM PITCH THREAD: 1.5 MM LENGTH: 40 MM LENGTH WITHOUT HEAD: 35 MM HEAD WIDTH: 20 MM HEXAGON NUT DIMENSION: INSIDE DIA: 10 MM PITCH THREAD: 1.5 MM HEIGHT: 7 MM WIDTH: 20 MM MATERIAL GRADE EN 4140
34	SGH63392		0212595710913 / CHANNEL MILD STEEL SZ 8X3 1/2X3 1/2, WEIGHT 20LBS/FT		24 / METER				<b>TECHNICAL SPECIFICATION -</b> DIMENSIONS: 8 INCH (WIDTH) X 3 1/2 INCH X 3 1/2 INCH (GAP OF U CHANNEL) X 8MM (TH), RUNNING LENGTH 6 RM SPECS BSEN 10025-2/2004, MATERIAL GRADE S-275JR <b>GENERAL SPECIFICATION -</b> DIMENSIONS: 8 INCH (WIDTH) X 3 1/2 INCH X 3 1/2 INCH (GAP OF U CHANNEL) X 8MM (TH), RUNNING LENGTH 6 RM SPECS BSEN 10025-2/2004, MATERIAL GRADE S-275JR
35	DGB71272		0274709104648 / HAMMER HAND ENGINEER 0.500LBS LG 12.00IN BALL PEIN		11 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION -</b> Grade: BS-876 (LOCAL MADE) <b>GENERAL SPECIFICATION -</b> Grade: BS-876 (LOCAL MADE)
36	DGB73124	1A1155	0274709104966 / FILE ENGINEER THREE SQUARE D-CUT SMOOTH 4" LG, 11 MM WIDTH		36 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION -</b> TRIANGLE FILE SIZE: 5 INCH <b>GENERAL SPECIFICATION -</b> TRIANGLE FILE SIZE: 5 INCH
37	DGE72175	NO DATA AVAILABLE	0413591881162 / O.RING (RUBBER, SIZE 11.8 MM x 3.6 MM)	PIPING SYSTEM	50 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION -</b> PARENT EQUIPMENT: PIPING SYSTEM MATERIAL: RUBBER. SIZE: 11.8 MM x 3.6 MM <b>GENERAL SPECIFICATION -</b> PARENT EQUIPMENT: PIPING SYSTEM. MATERIAL: RUBBER. SIZE: 11.8 MM x 3.6 MM.
38	DGB73198		0274502741418 / GUN GREASE		1 / EACH/NUMBER				<b>TECHNICAL SPECIFICATION -</b> NO DATA AVAILABLE <b>GENERAL SPECIFICATION -</b> NO DATA AVAILABLE
39	SGB69796	HH5010A (Nitchi Japan)	0246794633854 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO	5 / EACH/NUMBER	HE-50A			<b>TECHNICAL SPECIFICATION -</b> MAKE ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 75 LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up) Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed <b>GENERAL SPECIFICATION -</b> MAKE ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 75 LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up) Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
40	SGB67697		0265594233192 / NAILSTEEL-1.25INCHES-SWG15		80 / KILOGRAMME				TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
41	DGB73055	0265-6163	0265594233438 / PAD-LOCK,-1.500,"TRI CIRCLE,CHINA MADE WITH,THREE KEYS dgs.XCII/104/4001.		38 / EACH/NUMBER				TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
42	SGB52803	NO DATA AVAILABLE	0249725117797 / GREASE GUN	7.5/15 TON PORTAL CRANES PANDAT(GERMANY)	15 / EACH/NUMBER				TECHNICAL SPECIFICATION - ITEM IS USED ONBOARD FOR GREASING OF BEARINGS AND GENERAL USE EASILY AVAILABLE IN LOCAL MARKET. EUROPEAN BRAND CAN BE PROCURED DUE BETTER QUALITY GENERAL SPECIFICATION - ITEM IS USED ONBOARD FOR GREASING OF BEARINGS AND GENERAL USE EASILY AVAILABLE IN LOCAL MARKET. EUROPEAN BRAND CAN BE PROCURED DUE BETTER QUALITY
43	DGH72493	SAFFIRE MODEL NM250, PART NO 116324	0281502811666 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	2 / EACH/NUMBER				TECHNICAL SPECIFICATION - saffire a-nme SIZE 1/16", MODEL NM250, PART NO 116324, TDS enclosed GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.
44	DGE72856		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT, THICKNESS: 3/8-INCH	FENDER	94 / KILOGRAMME				TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND NR DARDNESS (SHORE A): 50*±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST MA JINNAH ROAD KARACHI 021-32720552 GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND NR DARDNESS (SHORE A): 50*±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST MA JINNAH ROAD KARACHI

S.N	LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
			Description		DENO		ADO	ity	SPECS
45	DGE72225		0476599430401 / BRUSH WHITE WASH 2KNOT		15 / EACH/N				<b>TECHNICAL SPECIFICATION</b> - a Size 8" b. Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market <b>GENERAL SPECIFICATION</b> - a. Size 8" b. Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market
46	DGE72833	NIL	0462592202403 / TUBING, PLASTICS, POLYETHYLENE, LAY FLAT, 0.005"TH, WD.9"		50 / KILOGR AMME				<b>TECHNICAL SPECIFICATION</b> - SPECIFICATION: 225MMX125MICRON. <b>DEFSTAN93-13</b> <b>GENERAL SPECIFICATION</b> - SPECIFICATION: 225MMX125MICRON, DEFSTAN93-13
47	DGE74006	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
48	DGE73971	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
49	DGE73891	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	5 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG

S.N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
45	DGE72225		0476599430401 / BRUSH WHITE WASH 2KNOT		15 / EACH/N				<b>TECHNICAL SPECIFICATION</b> - a Size 8" b Brand China c. Material Handle Grip Wood Color Brown/ White d. Commercial item available in local market <b>GENERAL SPECIFICATION</b> - a Size 8" b. Brand China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market
45	DGE72833	NIL	0462592202403 / TUBING, PLASTICS, POLYETHYLENE, LAY FLAT, 0.005"TH, WD.9"		50 / KILOGR AMME				<b>TECHNICAL SPECIFICATION</b> - SPECIFICATION. 225MMX125MICRON, DEFSTAN93-13 <b>GENERAL SPECIFICATION</b> - SPECIFICATION. 225MMX125MICRON, DEFSTAN93-13
47	DGE74006	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG
48	DGE73971	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	4 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG
49	DGE73891	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,3 00W,220/240V SIZE:350X452X275 MM	DEHUMIDIFIE RS	5 / EACH/N UMBER	MD231 (CROW N) /EH1504/ EH1418			<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight 10.5 KG

S.N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
50	DGE72156	81349. MIL-H- 15217	4720002036333 / HOSE RUBBER, NON-METTALIC, INTERNAL DIA 1", NO OF LAYERS= 4, (IMPREG.FAB), LENGTH= 50 FT		1000 / FOOT				<b>TECHNICAL SPECIFICATION</b> - tech specs Internal dia = 1 Inch. EQUILANT= 4-PLY RUBBER TYPE/FLEXIBLE. MINIMUM Working Pressure = 10 Bar. Maximum Working pressure = 30 Bar. Temp Range = -35 to 80 °C Packing = Plastic Paper oem coc/DOCUMENTS /dealer certificate= REQUIRED. PARENT EQUIP= CHIPPING MACHINE <b>GENERAL SPECIFICATION</b> - tech specs: Internal dia = 1 Inch. EQUILANT= 4- PLY, RUBBER TYPE/FLEXIBLE MINIMUM Working Pressure = 10 Bar. Maximum Working pressure = 30 Bar. Temp Range = -35 to 80 °C Packing = Plastic Paper oem coc/DOCUMENTS /dealer certificate= REQUIRED. PARENT EQUIP= CHIPPING MACHINE
51	DGE72055	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		5000 / EACH/N UMBER				<b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6- 1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 inches h. Tear Resistance 10-30 kg/m j Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <b>GENERAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 inches n Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF)
57	DGE73039	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		4000 / EACH/N UMBER				<b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6- 1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 inches h. Tear Resistance 10-30 kg/m j

S.N	LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
o			Description		DENO		ADO	ity	SPECS
53	DGE71638	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		2350 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <b>GENERAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 25*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF)</p>
54	DGE71971	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		4953 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 25*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <b>GENERAL</b></p>
55	DGE73577	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		3000 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <b>GENERAL</b></p> <p><b>SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched</p>

LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
		Description		DENO		ADO	ity	SPECS
DGE73726	NO DATA AVAILABL F	4240PK5078177 / GUNNY BAGS		3000 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b></p> <p>a Material Natural Jute Fiber b Color Brown(Natural Jute Color) c Weight 250-500 GSM( gram per square meter) d Thickness 0.6-1.2 mm e Length 30-60 Inch f Stitching Sewn or stitched with jute thread g Dimensions 26*40 Inches h Tear Resistance 10-30 kg/m j Moisture Content 10-15% k Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF) <b>GENERAL SPECIFICATION - GUNNY BAGS</b></p> <p>a Material Natural Jute Fiber b Color Brown(Natural Jute Color) c Weight 250-500 GSM( gram per square meter) d Thickness 0.6-1.2 mm e Length 30-60 Inch f Stitching Sewn or stitched with jute thread g Dimensions 26*40 Inches h Tear Resistance 10-30 kg/m j Moisture Content 10-15% k Jute Content 100% 1- material = jute 2- type of bags = hessian bag</p>
DGE73510	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		3000 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b></p> <p>a Material Natural Jute Fiber b Color Brown(Natural Jute Color) c Weight 250-500 GSM( gram per square meter) d Thickness 0.6-1.2 mm e Length 30-60 Inch f Stitching Sewn or stitched with jute thread g Dimensions 26*40 Inches h Tear Resistance 10-30 kg/m j Moisture Content 10-15% k Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF) <b>GENERAL SPECIFICATION - GUNNY BAGS</b></p> <p>a Material Natural Jute Fiber b Color Brown(Natural Jute Color) c Weight 250-500 GSM( gram per square meter) d Thickness 0.6-1.2 mm e Length 30-60 Inch f Stitching Sewn or stitched with jute thread g Dimensions 26*40 Inches h Tear Resistance 10-30 kg/m j Moisture Content 10-15% k Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF)</p>

S.N	LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
o			Description		DENO		ADO	ity	SPECS
58	DGE71478	NO DATA AVAILABL E	4240PK5078177 / GUNNY BAGS		4500 / EACH/N UMBER				<p><b>TECHNICAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <b>GENERAL SPECIFICATION - GUNNY BAGS</b> a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 Inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF).</p>
59	DGE72254	9-27054	4220PK5080360 / LIGHT,CHEMILUMI NESCENT RED FOR UNDER WATER-12HR		170 / EACH/N UMBER	Cyalume Chem light			<p><b>TECHNICAL SPECIFICATION - US MADE</b> ipc is enclosed <b>GENERAL SPECIFICATION - US MADE</b> ipc is enclosed</p>
60	DGE74003	621100/30 68.184	4220795229562 / FINS SWIM RUBBER BLACK	FOR DIVING	13 / PAIR				<p><b>TECHNICAL SPECIFICATION - Brand Name:</b> Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium <b>BRAND NAME:</b> SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE SCUBA-PRO,WEIGHT-4 95LBs(2.25Kg,MADE USA <b>GENERAL SPECIFICATION - Brand Name:</b> Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium <b>BRAND NAME:</b> SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE SCUBA-PRO,WEIGHT-4 95LBs(2.25Kg,MADE USA</p>
61	DGE74005	621100/30 68.184	4220795229562 / FINS SWIM RUBBER BLACK	FOR DIVING	11 / PAIR				<p><b>TECHNICAL SPECIFICATION - Brand Name:</b> Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium <b>BRAND NAME:</b> SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE SCUBA-PRO,WEIGHT-4 95LBs(2.25Kg,MADE USA <b>GENERAL SPECIFICATION - Brand Name:</b> Rocket Fins with Metal Buckles Color : Black Length : 51 cm Wide: 24 cm Size: Medium <b>BRAND NAME:</b> SCUBA-PRO ADJUSTABLE HEEL STRAP WITH METAL BUCKLES,COLOUR-BLACK, MANUFACTURE SCUBA-PRO,WEIGHT-4 95LBs(2.25Kg,MADE USA</p>

S.N	LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
o			Description		DENO		ADO	ity	SPECS
62	DGH72495	MUREX SAFFIRE 36EC	3439795094012 / MUREX SAFFIRE 36EC FLASHBACK ARRESTOR CYLINDER REGULATOR (OXYGEN)	WELD/CUTT APPRATUS MUREX SAFFIRE 36EC	20 / EACH/N UMBER	MUREX SAFFIRE 36EC (OXYGE N)			<u>TECHNICAL SPECIFICATION - MODEL</u> MUREX SAFFIRE 36EC, STANDARD EN730, MAX WORKING PRESSURE 10 BAR (TDS ENCLOSED) <u>GENERAL SPECIFICATION -</u> MODEL: MUREX SAFFIRE 36EC, STANDARD EN730, MAX WORKING PRESSURE 10 BAR (TDS ENCLOSED)
63	DGH72496	MUREX SAFFIRE 36EC	3439795095020 / MUREX SAFFIRE 36EC FLASH BACK ARRESTOR CYLINDER REGULATOR	WELD/CUTT MUREX SAFFIRE 36EC	20 / EACH/N UMBER	MUREX SAFFIRE 36EC (FUEL GAS)			<u>TECHNICAL SPECIFICATION - STANDARD</u> EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED) <u>GENERAL</u> <u>SPECIFICATION - STANDARD EN730, MAX</u> WORKING PRESSURE 1.5 BAR (TDS ENCLOSED)
64	DGP73852		3610705117912 / SHREDDING MACHINE (HEAVY DUTY)	SHREDDER MACHINE	1 / EACH/N UMBER	ST- 12C/ST- 12CD			<u>TECHNICAL SPECIFICATION - ST-12C/ST-</u> 12CD <u>GENERAL SPECIFICATION - ST-</u> 12C/ST-12CD
65	DGE72230	EJEETED AT 300M BURNS 40 SECOND	4220795055197 / ROCKET PARA RED (FOR USE AS SHIPS BRIDGE LIFE RAFT FLARE	SURVIVAL PACK USED IN 20MEN LIFERAFT	15 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE
66	SGB52797	NO DATA AVAILABL E	3439715045032 / WET WELDING ELECTRODE UW- CS-1 (1/8" OR 3.2 MM)	UNDERWATE R WELDING DURING SALVAGE OPS/TRAINING	1000 / PACKET				<u>TECHNICAL SPECIFICATION - Wet Welding</u> Electrode UW-CS-1 (1/8" or 3.2 mm) Size: Dia 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration <u>GENERAL</u> <u>SPECIFICATION - Wet Welding Electrode UW-</u> CS-1 (1/8" or 3.2 mm) Size, Dia 3.2mm Length: 13 inches Material Grade: Low Carbon Steel Position: Flat, Horizontal, Vertical, Overhead Type of Arc: Medium, Moderate, Penetration
67	DGB73531	6308ZZ	3110001588161 / BEARING BALL ANNUAL SIZE .40X90X23.		2 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - OEM, SKF</u> Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available <u>GENERAL SPECIFICATION -</u> OEM, SKF Model: AB SKF 6308ZZ, Origin USA/ Sweden, Locally available.
68	DGB72883	133009C1 7	3110001982417 / BEARING BALL ANNULAR SZ 25.00X62.00X25.30 MM	FOR COIL DRAM PUMP MOTOR	2 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE
69	DGB73435	NSK 6313ZZ	3110785033515 / BEARING BALL DEEP GROVE NSK 6313ZZ 065X140X33MM	CARGO JP-5 OIL PUMP	4 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE
70	DGB73458		5210705050053 / DIGITAL MICRO METER 0-25MM GRADE 0.01MM-	TO MEASURE OUT SIDE DIAMINISION THICKNE-	1 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE
71	SGB52801		5120731000583 / SPANNER D/END OPENJAW 6-32MM 12 PCS SET		5 / SET				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE
72	DGE72203	A-A-1201, P-P-121, ANSIB74- 18	5350001868820 / PAPER ABRASIVE 9"X11" WATER PROOF MATERIAL GLASS GRADE 110-A		223 / SHEET				<u>TECHNICAL SPECIFICATION - NO DATA</u> AVAILABLE <u>GENERAL SPECIFICATION - NO</u> DATA AVAILABLE

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	Availabil ity	TECH / GEN SPECS
73	DGE72245	NO DATA AVAILABL E	5620505042335 / TILES CERAMIC GLAZED COLOUR WHITE (SIZE LG 9" x WD 4.5" x TH 3/8")	DECK COVERING	2800 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>
74	DGE72309	NO DATA AVAILABL E	5935725077494 / RAYCHEM J.S.C.R HEAT SHRINK SLEEVE SZ 31/8 LG METER		10 / METER				<u>TECHNICAL SPECIFICATION - Sleeve sizes 48/16,31/8,95/29,35/12</u> <u>GENERAL SPECIFICATION - Sleeve sizes 48/16,31/8,95/29,35/12.</u>
75	DGE72235	0413-2184	5970999239664 / TAP INSULATION ELECT ADHESIVE PLASTIC RED W1	FOR RED PHASE	206 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - Brand OSAKA, NEETO c. Packing details 10-12 in each packing</u> <u>GENERAL SPECIFICATION - Brand: OSAKA, NEETO c. Packing details 10-12 in each packing</u>
76	DGE72239	RT876-1/4-0	5970UK5072933 / TUBING (HEAT SHRINK SLEEVE) FOR MARNESSE EQUIPMENT		10 / METER				<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
77	DGB71929	NO DATA AVAILABL E	0265500001588 / PAD LOCK TRI CIRCLE CHINA MADE 2-1/2" WITH THREE KEYS		80 / EACH/N UMBER	NO DATA AVAILAB LE			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
78	DGD72491		7730705048060 / CUP TEA GOLDEN CRESTED		36 / EACH/N UMBER				<u>TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> <u>GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u>
79	DGE72181	NO DATA AVAILABL E	0476500000005 / BRUSH SABLE HAIR NO-1		20 / EACH/N UMBER	NO DATA AVAILAB LE			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>
80	DGE72276	NO DATA AVAILABL E	0476780000105 / BRUSH PAINT 1		156 / EACH/N UMBER	NO DATA AVAILAB LE			<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>

S.N	LPR No	PART NO	NSN /	P/Equipment	QTY /	Model	MANUF	Availabil	TECH / GEN
o			Description		DENO		ADO	ity	SPECS
83	DGE72832	32R1296	8135992203363 / TUBING PLASTIC POLYETHYLENE TYPE -1 LAY FLAT WD.36 THICKNESS 0.010 INCH		85 / KILOGR AMME				TECHNICAL SPECIFICATION - AS AS PER ER-3200 LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2 DEF STAN 93- 116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available GENERAL SPECIFICATION - AS AS PER ER-3200 LENGTH PER ROLE=250 FEET WEIGHT PER ROLE=72 LBS 2 DEF STAN 93-116 ISSUE 2 OF 2007 normal roll(no need of packing) locally available
84	DGE72199	NO DATA AVAILABL E	0476500000117 / GLASS WHITE PLAIN FOR WELDING SCREEN LG.4"WD.2"THICK	HULL ABOVE U/W	32 / EACH/N UMBER	NO DATA AVAILAB LE			TECHNICAL SPECIFICATION - SCREEN LG.4"WD.2" THICK 1/8" GENERAL SPECIFICATION - SCREEN LG.4" WD 2" THICK 1/8"
85	DGP73649		7510705042257 / PLAIN PAPER(OFFSET) VRG SHEET 80 GSM SIZE 27X24 INCH		2 / REAM				TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
86	DGD74105	NO DATA AVAILABL E	7310012707127 / MICRO WAVE OVEN		1 / EACH/N UMBER	NO DATA AVAILAB			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA
87	DGD72553	NO DATA AVAILABL E	7320705012426 / MACHINE ATTA KNEADING100TO1 20KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/N UMBER	GSA/23/ AKM			TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)
88	DGD74107	NO DATA AVAILABL E	7320705012426 / MACHINE ATTA KNEADING100TO1 20KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/N UMBER	GSA/23/ AKM			TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)
89	DGD72504	NO DATA AVAILABL E	0035500000507 / STRAINERSRICE FOR POTS ALU 20X10 INCH		2 / EACH/N UMBER	NO DATA AVAILAB LE			TECHNICAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg GENERAL SPECIFICATION - Food Grade 6061 dimension 36" x 24" Thickness 6 mm Shape Round Size Capacity 20-25 kg
90	DGD72500	NO DATA AVAILABL E	0034500000263 / Saucer Tea Blue Crested and Blue Shell On Edge of saucer Size width 5.5" Depth 1cm.		12 / EACH/N UMBER	NO DATA AVAILAB LE			TECHNICAL SPECIFICATION - MATERIAL PORCELING GENERAL SPECIFICATION - MATERIAL: PORCELIN
91	DGE72280	NO DATA AVAILABL E	0477780000043 / HAMMER WOODEN SMALL 222 MB(NS/ID/21/312		10 / EACH/N UMBER	NO DATA AVAILAB LE			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
92	DGE72248		8345705119862 / SATTON CLOTH WHITE	PRESENTATIO N VIP ITEM	75 / METER				TECHNICAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches GENERAL SPECIFICATION - Length = 20 Meter/Yard Width = 48 to 60 Inches
93	DGE73196	NO DATA AVAILABL E	8345705119362 / VELVET GREEN W=54" L=25 Yard	PRESENTATIO N VIP ITEM	40 / METER				TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE



