

108

**MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)**

966

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

**Pakistan Military Accountst Department**Office of the **CNA Karachi** No & Date Of cheque \_\_\_\_\_ Serial No Of Cheque slip \_\_\_\_\_

In Payment Of bill No:- 1 dt 20/11/2024

225000.00

Bank A/c No PK17HABB0004540013100701

225000.00

In Words Rs TWO HUNDRED TWENTY-FIVE THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer OI/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To P.P.R.A  
PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To LP Division

2. LAO ( LAO (NAVY) NSD KARACHI )

## TENDER BULLETIN

OPENING/CLOSING DATE ON 26/12/2024

## CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONG WITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS: 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
1	DNQ70970	06973006	6140FT1019336 / Torch (Long Life) c/w Spares	Emergency Pack - 1	68 / EACH/ NUMBER	563210B 0006	KINGSWAY DUNMURRY BELFAST IRLANDA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
2	DNM70948	1099588	3439715231227 / COMPLETE UNIT 4GF GAS FLOW METER	16E SPRAY GUN	1 / EACH/ NUMBER	16E SPRAY GUN	SULZER METCO (US)INC.1101 PROSPECT AVENUE WESTBURY, NY 11590	TECHNICAL SPECIFICATION - COMPLETE UNIT 4GF GAS FLOW METER GENERAL SPECIFICATION - COMPLETE UNIT 4GF GAS FLOW METER
3	DNQ70799	06279006	6210795175762 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD.	43 / EACH/ NUMBER	UK (RFD BEAUFORT)	RFD BEAUFORT LTD (UK)	TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)
4	DGT73344	707	5530FM0360076 / 5 LAYERS PLYWOOD	WEAPON AND AMMUNITION STORAGE SYSTEM	20 / EACH/ NUMBER	NIL	FENGTAI DISTRICT YUNGANG NORTH WEST BEIJING CHINA. Tel: 86-13911121951 Fax: 86-010-68191140	TECHNICAL SPECIFICATION - AVAILABLE IN TP; GENERAL SPECIFICATION - AVAILABLE IN TP.
5	DGD69273	NO DATA AVAILABLE	003250000138 / KNIFE BUTTER PN CRESTED	RADAR 1006	20 / EACH/ NUMBER	LOCAL		TECHNICAL SPECIFICATION - Material Stainless steel grade 304, non magnetic & non reactive, food grade stainless steel SIZE - LENGTH: 06 INCH, WIDTH: 05 MM GENERAL SPECIFICATION - Material Stainless steel grade 304, non magnetic & non reactive, food grade stainless steel SIZE - LENGTH: 06 INCH, WIDTH: 06 MM
6	DGD69270		0031546000242 / CUPS TEA GOLDEN CRESTED		100 / EACH/ NUMBER	CERA-A-NOOR		TECHNICAL SPECIFICATION - MESS TRAPS ITEM MADE IN PAKISTAN LOCAL MADE BY OEM. CERA-A-NOOR SIZE - STANDARD GENERAL SPECIFICATION - MESS TRAPS ITEM MADE IN PAKISTAN LOCAL MADE BY OEM. CERA-A-NOOR SIZE - STANDARD
7	DNH73065	NIL	4110705111991 / REFRIGGERATOR 18/22 CUFT(W=90KG,CAP=478LT RS.UPLI220V,1.6AMP)	REFRIGERATOR	1 / EACH/ NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
8	DGE69256	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		1000 / EACH/ NUMBER			TECHNICAL SPECIFICATION - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or attached with jute thread g. Dimensions 26*40 inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% l- material = jute 2- type of bags =essian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- profer x stot/wends x picks per dm = 11x12/47x47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)/112 x 120 (KGF) 8- seam strength wft x wf (kgf) 34 x 36 (KGF) GENERAL SPECIFICATION - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or attached with jute thread g. Dimensions 26*40 inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% l- material = jute 2- type of bags =essian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- profer x stot/wends x picks per dm = 11x12/47x47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)/112 x 120 (KGF) 8- seam strength wft x wf (kgf) 34 x 36 (KGF)

S.N	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
9	DGD68986	NO DATA AVAILABLE	003550000378 / KNIFE TABLE MEDIUM		100 / EACH/ NUMBER	NO DATA AVAILABLE		<u>TECHNICAL SPECIFICATION</u> - Stainless Steel, M/Grade SS-316 (Food Grade) & PN Crest SIZE: LENGTH: 08 INCH WIDTH: 05 MM <u>GENERAL SPECIFICATION</u> - Stainless Steel, M/Grade SS-316 (Food Grade) & PN Crest SIZE: LENGTH: 08 INCH WIDTH: 05 MM
10	DNH73086	SPLIT TYPE A/C 01 TON MITSUBI MITSUBI	6962735142474 / SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE 12000 BTU	SPLIT TYPE A/C 01 TON	4 / EACH/ NUMBER	12PITH 00		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null
11	DGB89593	NO DATA AVAILABLE	5660705148476 / CONCERTINA WIRE	FOR BOUNDARY PROTECTION	536 / ROLL		SOURCE OF AVAILIBTY PAKISTAN WIRE SITE AREA KARACHI Mr WASEEM CONTRACT NO 0333 2112455	<u>TECHNICAL SPECIFICATION</u> - Country of origin pakistan BLADE SIZE 22MM 14MMW BLADE THIKNESS 0.5MM LINE WIRE 2.63MM 10-12 GAUGE SIZE 38 INCH DIA MATERIAL (MILD STEEL & GALVANIZED) <u>GENERAL SPECIFICATION</u> - Country of origin pakistan BLADE SIZE 22MM 14MMW BLADE THIKNESS 0.5MM LINE WIRE 2.63MM 10-12 GAUGE SIZE 38 INCH DIA MATERIAL (MILD STEEL & GALVANIZED)
12	DGT73334	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	150 / CUBIC FOOT	NIL	LOCAL MARKET	<u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%
13	DGT73552	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	105 / CUBIC FOOT	NIL	LOCAL MARKET	<u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%
14	DGT73216	NIL	5510705199134 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	LOCAL MARKET	<u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: pag: 89 (FOR VISUAL INSPECTION ONLY) moisture contents: 12% to 18%
15	ONM73066	3808093	4720270382129 / HOSE (HEAT EXCHANGER AND EXPANSION TANK)	HEAT EXCHANGER	1 / UNIT	D6-3700-E	AB VALVO PENTA SE 405 08 GOTHEN BURG SWEDEN	<u>TECHNICAL SPECIFICATION</u> - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA <u>GENERAL SPECIFICATION</u> - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA
16	DGH71843	STRDBL2 46860	3020PK5202652 / STRUCTURE DOUBLE 20' * 08'	RACK	1 / UNIT	NA	3RD FLOOR 83C PHASE 2, EXTENSION MAIN NATIONAL HIGHWADEFENCE KARACHI 021634229 PK	<u>TECHNICAL SPECIFICATION</u> - SHELF 1100 MM * 500 MM SECTION 40*40*1.2MM YIELD STRENGTH 245MPA 16MM MATERIAL M.S TENSILE STRENGTH 400-510MPA SURFACE FINISH: POWDER COATED LOAD CAP: LEVEL 250KG LOAD SAFETY FACTOR 01 01 5 <u>GENERAL SPECIFICATION</u> - SHELF 1100 MM * 500 MM SECTION 40*40*1.2MM YIELD STRENGTH 245MPA 16MM MATERIAL M.S TENSILE STRENGTH 400-510MPA SURFACE FINISH: POWDER COATED LOAD CAP: LEVEL 250KG LOAD SAFETY FACTOR 01 01 5
17	DGP73563	MODEL NO: LA40 A550P1	7730705133301 / TV SAMSUNG LCD 40" INCH	SAMSUNG	1 / EACH/ NUMBER	NO DATA AVAILABLE		<u>TECHNICAL SPECIFICATION</u> - Nil <u>GENERAL SPECIFICATION</u> - Nil

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
18	DGP73580		7535705133021 / LAPTOP COMPUTER (AS PER NHD APPROVED MODEL HP/DELL/LENOVO)	COMPUTER	1 / EACH/NUMBER	NO DATA AVAILABLE	PK	<b>TECHNICAL SPECIFICATION</b> - HP/DELL/LENOVO LAPTOP, 6 NO COMPONENTS SPECIFICATION: 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ); 2. SYSTEM MEMORY: 8 GB DDR3/DDR4; 3. DISPLAY: 15.6" LED; 4. HARD DISK: 500 gb ssd; 5. OPTICAL DISK DRIVE DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL® HDHD GRAPHICS; 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION); <b>GENERAL SPECIFICATION</b> - HP/DELL/LENOVO LAPTOP, 6 NO COMPONENTS SPECIFICATION: 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ); 2. SYSTEM MEMORY: 8 GB DDR3/DDR4; 3. DISPLAY: 15.6" LED; 4. HARD DISK: 500 gb ssd; 5. OPTICAL DISK DRIVE DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL® HDHD GRAPHICS; 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION)
19	DGP73583	NIL	7730705138906 / smart led 40 INCH	LCD 41 INCH SONY	2 / EACH/NUMBER	SONY/TCL/G	JP	<b>TECHNICAL SPECIFICATION</b> - android smart led tv <b>GENERAL SPECIFICATION</b> - android smart led tv
20	DGE72260	NIL	4230705181288 / BAG PAPER FOR CONTAMINATED CLOTHING	NIL	120 / EACH/NUMBER		PLASTIC MARKET	<b>TECHNICAL SPECIFICATION</b> - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/10573490 dated 30 March 2015) Dimensions: Height = 40 cm Width = 32 cm Depth = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material" (4) Each bag should have double padding at its bottom. <b>PACKING: STANDARD</b> <b>GENERAL SPECIFICATION</b> - REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/10573490 dated 30 March 2015) Dimensions: Height = 40 cm Width = 32 cm Depth = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material" (4) Each bag should have double padding at its bottom. <b>PACKING: STANDARD</b>
21	DGP73576	HP Scanner 20G05A/L 2747A	7490705218483 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	2 / EACH/NUMBER	HP Scanner 20G05A/ Pro 2500 F1	MS ORA-TECH SYSTEM FOUR SQUARE PLAZA 4TH FLOOR BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD,	<b>TECHNICAL SPECIFICATION</b> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME ADF UP TO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <b>GENERAL SPECIFICATION</b> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME ADF UP TO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297
							PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <b>GENERAL SPECIFICATION</b> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME ADF UP TO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297
22	DGP73740	HP Scanner 20G05A/L 2747A	7490705218483 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	3 / EACH/NUMBER	HP Scanner 20G05A/ Pro 2500 F1	MS ORA-TECH SYSTEM FOUR SQUARE PLAZA 4TH FLOOR BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ	<b>TECHNICAL SPECIFICATION</b> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME ADF UP TO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <b>GENERAL SPECIFICATION</b> - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR AND MONOCHROME ADF UP TO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENC	Model	MANUF ADD.	TECH / GEN SPECS
23	DGP73736	NIL	7435705140006 / MULTIMEDIA PROJECTOR (4000 LUMENS)	MULTIMEDIA PROJECTOR	1 / EACH/ NUMBER	PANASONIC PT-VW360 (4000 LUMENS PROJECTOR) OR ABOVE	PK	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
24	DGE72148		4620705131640 / U PVC SOCKET 1.5" DIA FOR PVC PIPE PLASTIC	SRE SYSTEM	50 / EACH/ NUMBER	NO DATA AVAILAB LE	PK	TECHNICAL SPECIFICATION - A) MATERIAL: POLY VINYL CHLORIDE B) DIAMETER 1.5 INCH C) ENVIRONMENTAL FRIENDLY MATERIAL D) HEAT RESISTANT E) FIRE RESISTANT F)
								REPUTABLE COMPANY. GENERAL SPECIFICATION - A) MATERIAL: POLY VINYL CHLORIDE B) DIAMETER 1.5 INCH C) ENVIRONMENTAL FRIENDLY MATERIAL D) HEAT RESISTANT E) FIRE RESISTANT F) REPUTABLE COMPANY.
25	DGP73732	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro	COMPUTER	2 / EACH/ NUMBER	NO DATA AVAILAB LE	PK	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both
26	DGP73729	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro	COMPUTER	2 / EACH/ NUMBER	NO DATA AVAILAB LE	PK	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both
27	DGP73570	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET	COMPUTER	3 / EACH/ NUMBER	NO DATA AVAILAB LE	PK	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type
			2055/HP LASER JET Pro 400/M401D/HP402D/M402DN /M404DN					A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB, 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Parallel and USB Port Both
28	DGP73569	50DU7000/50ALJ7000/A6EH5000	7730705174391 / SAMSUNG LED TV 46/49/50 INCH	LED TV	2 / EACH/ NUMBER	46EH5000	SAMSUNG	TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49/50 INCH GENERAL SPECIFICATION - SAMSUNG LED TV 46/49/50 INCH
29	DGP73730	50DU7000/50ALJ7000/A6EH5000	7730705174391 / SAMSUNG LED TV 46/49/50 INCH	LED TV	2 / EACH/ NUMBER	46EH5000	SAMSUNG	TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49/50 INCH GENERAL SPECIFICATION - SAMSUNG LED TV 46/49/50 INCH
30	DGH71847	LUKUF9010S2100M	7125705206257 / FRAME 10' X 3.5'	Reckling	10 / EACH/ NUMBER	NA	M/a Habib & Sons 3rd Floor, 83-C, Phase II Extension, Main National Highway, Defense	TECHNICAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 92 x 2150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated GENERAL SPECIFICATION - Size: 3050mm x 1050 mm type: OMEGA PLUS X-Section : 92 x 2150 mm X-Section thickness: 2mm Pitch: 75 mm Standard: SS400 Surface Finish: Powder Coated
31	DGP73743	LQ-2190	7025735150606 / EPSON LQ-2190 DOT MATRIX PRINTER	EPSON	1 / EACH/ NUMBER	EPSON	EPSON	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -
32	DPC68733	TUFF-BOND HANGER	8040010098001 / ADHESIVE TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLON		MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE	TECHNICAL SPECIFICATION - Material: RUBBER SYNTHETIC - FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS GENERAL SPECIFICATION - Material: RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS

S.N	LPR No	PART NO	NSN / Description	PEquipment	QTY / DEND	Model	MANUF ADD	TECH / GEN SPECS
33	DGB65837		4920PK5131794 / REPAIR AND MAINTENANCE TOOL KIT WITH ALL ACCESSORIES	TOOL KIT	4 / EACH/ NUMBER	NO DATA AVAILABLE	PK	TECHNICAL SPECIFICATION :- GENERAL SPECIFICATION :-
34	DGE72140	2895S	4240TY5202562 / 3M COMFORT LINE SAFETY GOGGLES 2890 SERIES	BV	50 / EACH/ NUMBER	NA	VHKMHMN	TECHNICAL SPECIFICATION :- a. Goggle Type Sealed b. Lens Color Clear c. Lens Coating Anti fog & Anti-scratch d. Lens Material Polycarbonate e. Product Series 2890s f. Size Universal g. Venting None GENERAL SPECIFICATION :- a. Goggle Type Sealed b. Lens Color Clear c. Lens Coating Anti fog & Anti-scratch d. Lens Material Polycarbonate e. Product Series 2890s f. Size Universal g. Venting None
35	DGE72271	G3000	8415TY6202563 / 3M SAFETY HELMET G3000 SERIES	BV	95 / EACH/ NUMBER	NA	VHKMHMN	TECHNICAL SPECIFICATION :- NIL GENERAL SPECIFICATION :- NIL
36	DGH71846	LCKHB10 51182B	3020705202580 / BEAM PR 2740X240	RACKS	24 / EACH/ NUMBER		OFFICE 3RD FLOOR 83 C, PHASE2, EXT MAIN NATIONAL HIGHWAY,DEFENCE KARACHI 021-5386726	TECHNICAL SPECIFICATION :- Profile: Step Beam Size: 118mm x 50mm Surface Finish: Rai-200µ Powder Coated Material: SS400 strength 245mpa16mm Tensile strength 400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/out bolt:4 Load safety factor: 01.01.5 GENERAL SPECIFICATION :- Profile: Step Beam Size: 118mm x 50mm Surface Finish: Rai-200µ Powder Coated Material: SS400 strength 245mpa16mm Tensile strength 400-510mpa Locking pin: I-type x2 Load capacity/level:2000kg Lugs/out bolt:4 Load safety factor: 01.01.5
37	DGH718	HRKT401	494070520260	RACKS	215 /		OFFICE 3RD FLOOR 83-	TECHNICAL SPECIFICATION :-
44		SEWILCK	4 / TRAY Size 40"x12"x1" (SET OF 09 TRAYS)		SET		PHASE-II EXTENSION MAIN NATIONAL	Profile: Type-I, MATERIAL: Galvanized, TRAY SIZE: 40" X12" THICKNESS 1.5 MM GENERAL SPECIFICATION :- Profile: Type-I, MATERIAL: Galvanized, TRAY SIZE: 40" X12" THICKNESS 1.5 MM
38	DGE72259	NIL	8415705228017 / PARACHUTE CLOTH FOR WEAPONS AND SENSORS	Cloth	300 / METER	NIL	AL MUSTAFA TRADERS F-41/F-42, Iqbal Center M.A Jinnah Road, Karachi- 74200	TECHNICAL SPECIFICATION :- Type of cloth: Parachute Cloth Code: D-15-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof, with good quality gauge to withstand humid and hot environment GENERAL SPECIFICATION :- Type of cloth: Parachute Cloth Code: D-15-80 Colour: Dark Grey Parachute cover should be water resistant/ water proof, with good quality gauge to withstand humid and hot environment
39	DGH71842	LVDPL60 95044	3020705202591 / LOUVERED PANEL 3' * 2' * 144	RACKING	60 / EACH/ NUMBER		OFFICE 3RD FLOOR 83- C, PHASE-II EXTENSION, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI	TECHNICAL SPECIFICATION :- SIZE: 1200H * 590L * 15S * 1.2T SECTION, EMBOSSED TYPE, AS PER SAMPLE MATERIAL, M/S PAINT FINISH: POWDER COATED LOUVERED: 192NDS * 50W * 20H STRUCTURE DOUBLE: 20X06 GENERAL SPECIFICATION :- SIZE: 1200H * 590L * 15S * 1.2T SECTION, EMBOSSED TYPE, AS PER SAMPLE MATERIAL, M/S PAINT FINISH: POWDER COATED LOUVERED: 192NDS * 50W * 20H STRUCTURE DOUBLE: 20X06
40	DGH71839	PPBNGR 118412	3020705202595 / BIN 295 * 280 * 175 * 700W	RACKING	240 / EACH/ NUMBER		OFFICE 3RD FLOOR 83- C, PHASE-II EXTENSION, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI	TECHNICAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS GENERAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS
41	DGH71840	PPBNRD 161184	3020705202596 / BIN 41* 295 * 175 * 1000W	RACKING	180 / EACH/ NUMBER		OFFICE 3RD FLOOR 83- C, PHASE-II EXTENSION, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI	TECHNICAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS 2. BIN MDI 390 41*295*175*1000W Size: L: 400"D, 275"H, 165MM Material/ Grade: P.Polymer / 2000N C Color: Red, Blue & Yellow Weight/Capacity: 1025 Gram/ 70 Kgs GENERAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS 2. BIN MDI 390 41*295*175*1000W Size: L: 400"D, 275"H: 165MM Material/ Grade: P.Polymer / 2000N C Color: Red, Blue & Yellow Weight/Capacity: 1025 Gram/ 70 Kgs
42	DGH61327	PPBNRD 161184	3020705202596 / BIN 41* 295 * 175 * 1000W	RACKING	20 / EACH/ NUMBER		OFFICE 3RD FLOOR 83- C, PHASE-II EXTENSION, MAIN NATIONAL HIGHWAY, DEFENCE KARACHI	TECHNICAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS 2. BIN MDI 390 41*295*175*1000W Size: L: 400"D, 275"H, 165MM Material/ Grade: P.Polymer / 2000N C Color: Red, Blue & Yellow Weight/Capacity: 1025 Gram/ 70 Kgs GENERAL SPECIFICATION :- SIZE: L: 400"D, 275"H, 165MM MATERIAL/ GRADE: P.POLYMER / 2000N C COLUR: RED, BLUE & YELLOW WEIGHT/CAPACITY: 1025 GRAM/ 70 KGS 2. BIN MDI 390 41*295*175*1000W Size: L: 400"D, 275"H: 165MM Material/ Grade: P.Polymer / 2000N C Color: Red, Blue & Yellow Weight/Capacity: 1025 Gram/ 70 Kgs
43	DGB72475		0283700001608 / INGOT-BRASS		1975 / KILOGRAM			TECHNICAL SPECIFICATION :- Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn1654-C Weight of Ingot Range from Min 10 kg to Max 20 kg GENERAL SPECIFICATION :- Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn1654-C Weight of Ingot Range from Min 10 kg to Max 20 kg

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADO	TECH / GEN SPECS
44	DPC70810		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	1208 / KILOGRAMME			TECHNICAL SPECIFICATION - BS 1613 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1613 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE
45	DGP67891		0461504610120 / TARGET-PAPER 25YD RANGE 6 1/4"X8"		3000 / EACH/NUMBER			TECHNICAL SPECIFICATION - GSM 6 1/4"X8" GENERAL SPECIFICATION - GSM 6 1/4"X8"
46	DPC70611		0473509423131 / PIGMENT AND OIL PASTE WHITE LEAD / KOLOR KUT WATER FINDING PASTE FOR		100 / EACH/NUMBER			TECHNICAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.9 cm GENERAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm
47	DGE72179	0413-2556	0413599237038 / HOSE POLYVINYL PVC INT 0.375 ET 0.77 L 14.5 3PSI WT 3LB		100 / METER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
48	DGE72256	04769430	0476599430557 / BRUSH VARNISH TYNEX FIBER	DR QI-PS HIN SE	104 / EACH/NUMBER			TECHNICAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately
		6/5	FLAT SQUIRE EDGE LENGTH 2.5 INCH THICK					packed/ wrapped/ any suitable GENERAL SPECIFICATION - 2. Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUIRE EDGE 4. Packaging Separately packed/ wrapped/ any suitable
49	DGE69555		0474504740126 / SHAMIANA COMPLETE SZ. 18.00X36.00 FT		8 / EACH/NUMBER			TECHNICAL SPECIFICATION - Option I Size 15x15 Feet Poles 04 with cover Ropes 04 with cover Frit 04 (15 feet each) Kily 04 (iron rod) Option II Size 15x30 Feet Poles 06 with cover Ropes 06 with cover Frit 02 (15 feet) 02 (30 feet) Kily 04 (iron rod) MATERIAL - 100% COTTON, BAMBOO OF MATURE STEM, SOUND REASONABLY STRAIGHT & FREE FROM 100% BORER OR INSECT HOLES (GHODIN) SPLIT AND PRESERVED. Color: Item is required in multicolor i.e (yellow, green) GENERAL SPECIFICATION - Option I Size 15x15 Feet Poles 04 with cover Ropes 04 with cover Frit 04 (15 feet each) Kily 04 (iron rod) Option II Size 15x30 Feet Poles 06 with cover Ropes 06 with cover Frit 02 (15 feet) 02 (30 feet) Kily 04 (iron rod) MATERIAL - 100% COTTON, BAMBOO OF MATURE STEM, SOUND REASONABLY STRAIGHT & FREE FROM 100% BORER OR INSECT HOLES (GHODIN) SPLIT AND PRESERVED. Color: Item is required in multicolor i.e (yellow, green)
50	SGB56869		02834985711457 / ROD NAVAL BRASS RD DIA 2.25" WT PER FT 14.73(LB)		5 / METER			TECHNICAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter GENERAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade CW 712R (M), Running Length (Min): 02 meter
51	SGB71455		0267595213285 / Piping		20 / METER			TECHNICAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161
			Galv 3050x4.0x0.250					IS3801, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable GENERAL SPECIFICATION - BS 3602, Standard: ASTM A53, IS 1161, IS3601, BS1387-85, GB/T3091-08, DIN2440, JIS-G3444, EN10240, EN10255 Grade: S235JR, S275JR (recommended), any other MS pipes also usable
52	DGB72603	NO DATA AVAILABLE	0265591282628 / SCREW MACHINE STEEL (zinc coated)		110 / TEN			TECHNICAL SPECIFICATION - Screw Machine Steel (MS Zinc coated) Length: 1 inch Dia: 4 mm Thread Type DA GENERAL SPECIFICATION - Screw Machine Steel (MS Zinc coated) Length: 1 inch Dia: 4 mm Thread Type DA
53	DGB65030	SPECIFICATION BS 887	0274599100077 / CALIPER VERNIER ENG&MM COMB IN&EXT W/CASE 0-T09" (D-TQ-225MM)	MEASURING TOOL	1 / EACH/NUMBER			TECHNICAL SPECIFICATION - SPECIFICATION BS 887 GENERAL SPECIFICATION - SPECIFICATION BS 887
54	SGB52791		0274709104648 / HAMMER HAND ENGINEER 0.500LBS LG 12.00IN BALL PEIN		1 / EACH/NUMBER			TECHNICAL SPECIFICATION - Grade: BS-876 (LOCAL MADE) GENERAL SPECIFICATION - Code: BS-876 (LOCAL MADE)
55	DGB65032	NO DATA AVAILABLE	0272592720072 / DRILL-TWIST-TAPER-SHANK-HSS-9MM		15 / EACH/NUMBER			TECHNICAL SPECIFICATION - size: 9 mm material: has Hardness HRC65-66 has jobber drill-general purpose GENERAL SPECIFICATION - size: 9 mm material: has Hardness HRC65-66 has jobber drill-general purpose a100 9.00mm
56	DGB73082		0214790130808 / BOLT,	BR 320 Q/78	88 / TEN			TECHNICAL SPECIFICATION - THREAD SIZE: 1/2 INCH, NOMINAL LENGTH: 2 INCH, LENGTH OF

S.N	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
			THREAD SERIES: BSF, HEX HD					THREAD: 1 INCH. MATERIAL SPECS PD970.2005 MATERIAL GRADE EN16(B45 M36) or EN100(B45 M36). HEAT TREATMENT CONDITION R as per BR-3200 (Catalog of Naval Stores) OEM COC/MTC REQUIRED REQUIRED GENERAL SPECIFICATION - THREAD SIZE: 1/2 INCH. NOMINAL LENGTH: 2 INCH. LENGTH OF THREAD: 1 INCH. MATERIAL SPECS PD970.2005 MATERIAL GRADE EN16(B45 M36) or EN100(B45 M36). HEAT TREATMENT CONDITION R as per BR-3200 (Catalog of Naval Stores) OEM COC/MTC REQUIRED
57	DGB73643		0283702015139 / ROD WELDING BRASS	0-630% COPPER SP C BS 1453-C2	14.5 / KILDG RAMME			TECHNICAL SPECIFICATION - BS 1453-C2 0-630% COPPER SIZE DIA: 1/8 INCH LENGTH: 36 INCH AUTHORITY AS PER BR 3200 GENERAL SPECIFICATION - BS 1453-C2 0-630% COPPER SIZE DIA: 1/8 INCH LENGTH: 36 INCH AUTHORITY AS PER BR 3200
58	SGB56629		0272502720048 / DRILL-PARALELL-SHANK-4.2MM		170 / EACH/NUMBER			TECHNICAL SPECIFICATION - Material: HSS, Dia: 4.2mm, OEM: Hico Co GENERAL SPECIFICATION - Material: HSS, Dia: 4.2mm, OEM: Hico Co
59	DGB66372		0265594233532 / LOCK-RIM-5INCH-FOUR-LEVER (LOCAL)		10 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
60	DGB67716		0263594149652 / SHACKLE BOW TO SCREW FOR RIGGING SHACKLE		14 / EACH/NUMBER			TECHNICAL SPECIFICATION - 1 material: forged carbon magnesium steel 2 safe working load (swl): 3.80 tones 3 bow dia: 01 inch (25 mm) 4 pin dia: 32 mm 5 inside height: 102 mm 6 jaw opening: 48 mm GENERAL SPECIFICATION - 1 material: forged carbon magnesium steel 2 safe working load (swl): 3.80 tones 3 bow dia: 01 inch (25 mm) 4 pin dia: 32 mm 5 inside height: 102 mm 6 jaw opening: 48 mm
61	DGB73399	OUT/BODY 1/8" PLATE INNER 16 GAUG	0248591296147 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21-1/16X16-3/4"	2 / EACH/NUMBER			TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body, 1/8" plate, inner gauge: 16 local indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body, 1/8" plate, inner gauge: 16 local indigenous Steel crs s400 Fire Proof Required
62	DGB69518	OUT/BODY 1/8" PLATE INNER 16 GAUG	0248591296147 / SAFE STEEL FITTED WITH COMB 6 LEVER EXT DIM SZ 28X21X16 5/8"	SZ 710X535X425 MM(27-3/4X21-1/16X16-3/4"	1 / EACH/NUMBER			TECHNICAL SPECIFICATION - Size: 28X21X16 5/8" out body, 1/8" plate, inner gauge: 16 local indigenous Steel crs s400 Fire Proof Required GENERAL SPECIFICATION - Size: 28X21X16 5/8" out body, 1/8" plate, inner gauge: 16 local indigenous Steel crs s400 Fire Proof Required
63	DGB62402		0248591296153 / CHEST-KEYLESS-COMBINATION STL 21.75X18.50X11.50 PLATE		2 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
64	DGB73561	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE DOOR NOT LESS THAN 3/8" THK	1 / EACH/NUMBER			TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 03
65	DGB73045	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE DOOR NOT LESS THAN 3/8" THK	2 / EACH/NUMBER			TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 03 GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 03
66	DGH724	BSEN	021269571072		114 /			TECHNICAL SPECIFICATION -
97		10026 GRADE	2 / M/S ANGLE LG 6100mm, SIZE 40 X 40 X 5mm		METER			BSEN 10026 of 2004 GRADE S275JR GENERAL SPECIFICATION - BSEN 10026 of 2004 GRADE S275JR
67	DGB72568	SKF 6303 Z	0265899501331 / BEARING BALL JOURNAL SKF 6303 Z 017X047X14MM		20 / EACH/NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / QENO	Model	MANUF ADD	TECH / GEN SPECS
68	DGE67440	811251-0X-00	1670715081086 / RUCK SACK / MT MILITARY TACTICAL BACKPACKS ALICE PACK ARMY		25 / EACH/ NUMBER			TECHNICAL SPECIFICATION - VIDE BDE HQ SSG LETTER PN/BDE HQ SSG/GENERAL/237613 DATED 01.08.2022 GENERAL SPECIFICATION - VIDE BDE HQ SSG LETTER PN/BDE HQ SSG/GENERAL/237613 DATED 01.08.2022
69	DGE67635	811251-0X-00	1670715081086 / RUCK SACK / MT MILITARY TACTICAL BACKPACKS ALICE PACK ARMY		25 / EACH/ NUMBER			TECHNICAL SPECIFICATION - VIDE BDE HQ SSG LETTER PN/BDE HQ SSG/GENERAL/237613 DATED 01.08.2022 GENERAL SPECIFICATION - VIDE BDE HQ SSG LETTER PN/BDE HQ SSG/GENERAL/237613 DATED 01.08.2022
70	DGE73319	NO DATA AVAILABLE	0472595237744 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	16 / EACH/ NUMBER			TECHNICAL SPECIFICATION - DGS-DNG 10/588 K-7356 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM - Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating 181N GENERAL SPECIFICATION - DGS-DNG 10/588 K-7356 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM - Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating 181N
71	DGP73739		0575590624922 / TP ROLL 2 PLY COMPLETE WITH ONE TIME CARBON PAPER COMPLETE	TELEPRINTERS	210 / ROLL			TECHNICAL SPECIFICATION - TECHNICAL DATA OF TP ROLL 2 PLY 1. PAPER: PEARL WHITE PRINTING PAPER. 2. QUALITY/STRENGTH OF PAPER: HIGH GOOD STRENGTH OF PAPER. 3. GSM OF PAPER: 63 GSM ± 5%. 4. QUALITY OF CARBON PAPER: HIGH STRENGTH, INCLUSIVE OF COLOUR, CHEMICAL AND WAX QUALITY GIVEN GOOD PRINTING ON OTHER COPY. 5. NO. OF CARBON PAPER: ONE LAYER OF CARBON PAPER. 6. GSM OF CARBON PAPER: 22 GSM ± 5%. 7. BRAND OF CARBON PAPER: KUR OR EQUIVALENT BRAND. 8. WIDTH OF ROLL: 8.25 INCH. 9. LENGTH OF ROLL: 35 METER ± 0.1 METER, IN ONE PLACE REQUIRED ONLY. 10. DIA OF INNER CORE SPOOL: 01 INCH. 11. DIA OF OUTER CORE SPOOL: 1.20 INCH. 12. LENGTH OF CORE SPOOL: 0.25 INCH. 13. END PROTECTION OF CORE SPOOL BY PLASTIC COVER ON BOTH END OF CORE SPOOL. 14. END INDICATOR TO BE MARKED: END INDICATOR IN RED COLOUR OR GREEN COLOUR. 15. PACKING: EACH TP ROLL WRAPPED/ PACKED IN POLYTHENE BAG & FURTHER 12 TP ROLL ARE PACKED IN A CARD BOARD BOX. 16. TENDER SAMPLE AS PER SAMPLE TO BE APPROVED BY STATIONERY BOARD GENERAL SPECIFICATION - TECHNICAL DATA OF TP ROLL 2 PLY 1. PAPER: PEARL WHITE PRINTING PAPER. 2. QUALITY/STRENGTH OF PAPER: HIGH GOOD STRENGTH OF PAPER. 3. GSM OF PAPER: 63 GSM ± 5%. 4. QUALITY OF CARBON PAPER: HIGH STRENGTH, INCLUSIVE OF COLOUR, CHEMICAL AND WAX QUALITY GIVEN GOOD PRINTING ON OTHER COPY. 5. NO. OF CARBON PAPER: ONE LAYER OF CARBON PAPER. 6. GSM OF CARBON PAPER: 22 GSM ± 5%. 7. BRAND OF CARBON PAPER: KUR OR EQUIVALENT BRAND. 8. WIDTH OF ROLL: 8.25 INCH. 9. LENGTH OF ROLL: 35 METER ± 0.1 METER, IN ONE PLACE REQUIRED ONLY. 10. DIA OF INNER CORE SPOOL: 01 INCH. 11. DIA OF OUTER CORE SPOOL: 1.20 INCH. 12. LENGTH OF CORE SPOOL: 0.25 INCH. 13. END PROTECTION OF CORE SPOOL BY PLASTIC COVER ON BOTH END OF CORE SPOOL. 14. END INDICATOR TO BE MARKED: END INDICATOR IN RED COLOUR OR GREEN COLOUR. 15. PACKING: EACH TP ROLL WRAPPED/ PACKED IN POLYTHENE BAG & FURTHER 12 TP ROLL ARE PACKED IN A CARD BOARD BOX. 16. TENDER SAMPLE AS PER SAMPLE TO BE APPROVED BY STATIONERY BOARD.
72	DGB68420	SKF 6312-2Z	3110009910920 / BEARINGS BALL ANNULLAR, Size 60.00X130.00X31.00MM		3 / EACH/ NUMBER			TECHNICAL SPECIFICATION - PART NO. SKF 6312-2Z, SIZE 60.00X130.00X31.00MM GENERAL SPECIFICATION - PART NO. SKF 6312-2Z, SIZE 60.00X130.00X31.00MM
73	DGE73491	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,300W,220V 240V SIZE 350X452X275MM	DEHUMIDIFIERS	5 / EACH/ NUMBER	MD231 (CROWN) /EH1504		TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V. Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V. Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
74	DGE72791	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,300W,220V 240V SIZE 350X452X275MM	DEHUMIDIFIERS	1 / EACH/ NUMBER	MD231 (CROWN) /EH1504 /EH1418		TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V. Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V. Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG

S/N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / QENO	Model	MANUF ADO	TECH / GEN SPECS
75	DGE73560	MD231 (CROWN) /EH1504 /EH1418	4440795102644 / PREMI-AIR DEHUMIDIFIERS,300W,220V 240V SIZE:350X452X275MM	DEHUMIDIFIER	4 / EACH/ NUMBER	MD231 (CROWN) /EH1504/ EH1418		<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
76	DGE73315	MD231 (CROWN) /EH1504 /EH1418	4440795102644 / PREMI-AIR DEHUMIDIFIERS,300W,220V 240V SIZE:350X452X275MM	DEHUMIDIFIER	4 / EACH/ NUMBER	MD231 (CROWN) /EH1504/ EH1418		<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
77	DGE73728	MD231 (CROWN) /EH1504 /EH1418	4440795102644 / PREMI-AIR DEHUMIDIFIERS,300W,220V 240V SIZE:350X452X275MM	DEHUMIDIFIER	1 / EACH/ NUMBER	MD231 (CROWN) /EH1504/ EH1418		<b>TECHNICAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <b>GENERAL SPECIFICATION</b> - Rated Voltage: 220-240 V; Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG
78	DGE71071	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		2000 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wt (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF) <b>GENERAL SPECIFICATION</b> - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wt (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF)
79	DGE70992	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		2900 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wt (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF) <b>GENERAL SPECIFICATION</b> - GUNNY BAGS a. Material Natural Jute Fiber b. Color Brown(Natural Jute Color) c. Weight 250-500 GSM( gram per square meter) d. Thickness 0.6-1.2 mm e. Length 30-60 inch f. Stitching Sewn or stitched with jute thread g. Dimensions 26*40 Inches h. Tear Resistance 10-30 kg/m j. Moisture Content 10-15% k. Jute Content 100% 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wt (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF)
80	DGE72257	9-27017	4220PK5080361 / LIGHT,CHEMILUMINESCENT GREEN FOR UNDER WATER 12HR	DC LOCKERS	200 / EACH/ NUMBER	Oyphume Chem light		<b>TECHNICAL SPECIFICATION</b> - IPD IS ENCLOSED <b>GENERAL SPECIFICATION</b> -IPD IS ENCLOSED
81	DNH73213	LS- R126AAL	4120705099317 / AIR CONDITIONER (SPLIT WALL MOUNTED 01 TON)	AIR COND. OEM LG ELECTRONIC S,NEW ALLIED	4 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / QENO	Model	MANUF ADD	TECH / GEN SPECS
82	SGB39832	MILE2220 0-2QA	3439008782154 / ELECTRODE WELDING AWS E308-16 DIA - 2.6MM	WELDING (STEEL)	100 / KILOG RAMM E			<b>TECHNICAL SPECIFICATION</b> - Ø 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition: C: 0.02 S: 0.01 Mn: 1.9 Ni: 10.0 Cr: 19.5 Tensile STRENGTH: 550 N/mm <sup>2</sup> Current RANGE: 60-90 Amps Area reduction: 50 % Elongation: 40.0% Packaging: 21 kg per bag. Final delivery with one  <b>GENERAL SPECIFICATION</b> - Ø 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition: C: 0.02 S: 0.01 Mn: 1.0 Ni: 10.0 Cr: 19.5 Tensile STRENGTH: 550 N/mm <sup>2</sup> Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 21 kg per bag. Final delivery with one Approval of any international classification i.e. LR, BV, ABS, DNV, GL, CE, JIS, ISO-9001:2015
			ODE: 300 MM)					<b>TECHNICAL SPECIFICATION</b> - Ø 2.6 mm Spec: AWS A5.4-81 E 308-16 Chemical Composition: C: 0.02 S: 0.01 Mn: 1.0 Ni: 10.0 Cr: 19.5 Tensile STRENGTH: 550 N/mm <sup>2</sup> Current RANGE: 60-90 Amps Area reduction: 50.0% Elongation: 40.0% Packaging: 21 kg per bag. Final delivery with one Approval of any international classification i.e. LR, BV, ABS, DNV, GL, CE, JIS, ISO-9001:2015
83	DGP73737		3610705117912 / SHREDDING MACHINE (HEAVY DUTY)	SHREDDER MACHINE	1 / EACH/ NUMB ER	ST- 12C/ST- 12CD		<b>TECHNICAL SPECIFICATION</b> - ST-12C/ST-12CD <b>GENERAL SPECIFICATION</b> - ST-12C/ST-12CD
84	DNH73325	NO DATA AVAILAB LE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL. 24000 BTU 220 V 50 HZ ANY BRAND AS PER HQ POLICY	SELF	1 / EACH/ NUMB ER	GREE/P EL. MITSBU SHI/ DAKEN/ GENERA L LG.		<b>TECHNICAL SPECIFICATION</b> - null <b>GENERAL SPECIFICATION</b> - null
85	SGB71454	SKF8317 ZZ	3110001556338 / BEARING BALL ANNULAR	DIESEL GENERATOR DORMAN (ENGLAND)	2 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - SZ 85X180X41MM SHIELD QTY2 STEEL OVERALL <b>GENERAL SPECIFICATION</b> - SZ 85X180X41MM SHIELD QTY2 STEEL OVERALL
86	DGB64857	MILH904	3950009650097 / HOIST CHAIN		1 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
87	SGB56870		3950505035336 / CHAIN	FOR GENERAL	4 / EACH/ N	ZL00340		<b>TECHNICAL SPECIFICATION</b> - HEAVY DUTY HAND CHAIN HOIST
			BLOCK 10 TONS CAPACITY WITH 45 FEET DRIFT MAKE JAPAN	USE	UMBE R			CHAIN DIAMETER: 10 MM HEADROOM: 29.52 IN HOOK OPENING WIDTH: 2.51 INCH LIFT LOAD EFFORT: 85.98 LBS LOAD CAPACITY: 10 TONS STANDARD LIFT: 20 FT WEIGHT: 260 LBS TESTING ACCEPTANCE: 150 % OF LOAD CAPACITY <b>GENERAL SPECIFICATION</b> - HEAVY DUTY HAND CHAIN HOIST CHAIN DIAMETER: 10 MM HEADROOM: 29.52 IN HOOK OPENING WIDTH: 2.51 INCH LIFT LOAD EFFORT: 85.98 LBS LOAD CAPACITY: 10 TONS STANDARD LIFT: 20 FT WEIGHT: 260 LBS TESTING ACCEPTANCE: 150 % OF LOAD CAPACITY
88	DNH73502	wdf-318	4110731001200 / DEEP FREEZER 16 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/ NUMB ER	WDF- 318		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
89	DGP73575	CP1515N HP COLOR LASER 150A PRINTER 42B94A	3610705081120 / HP COLOR LASER JET CP1515N PRINTER	SELF/ANY COMPUTER OR LAPTOP	2 / EACH/ NUMB ER	CP1515 N/HP COLOR LASER 150A PRINTE R 42B94A		<b>TECHNICAL SPECIFICATION</b> - SPECIFICATION: (A)TYPE: COLOR, (B)PRINT TECHNOLOGY: COLOR LASER, (C)PROCESSOR SPEED: 450 MHZ, (D)STANDARD RAM: 96 MB, (E)MAX RAM: 382 MB, (F)RESOLUTION: 600X600 dpi, (G)PRINT SPEED COLOR: 8ppm, (H)PRINT SPEED BW: 12 PPM. PRICE OF LASER JET CP1515 RS 45,490. <b>GENERAL SPECIFICATION</b> - SPECIFICATION: (A)TYPE: COLOR, (B)PRINT TECHNOLOGY: COLOR LASER, (C)PROCESSOR SPEED: 450 MHZ, (D)STANDARD RAM: 96 MB, (E)MAX RAM: 382 MB, (F)RESOLUTION: 600X600 dpi, (G)PRINT SPEED CO, OR 8ppm, (H)PRINT SPEED BW: 12 PPM. PRICE OF LASER JET CP1515 RS 40,480.

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	MANUF ADD	TECH / GEN SPECS
90	DGP73738	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHRED MASTER)		2 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5M/MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HxWxD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs <b>GENERAL SPECIFICATION</b> - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5M/MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HxWxD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs
91	DGP73171	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHRED MASTER)		2 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5M/MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HxWxD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs <b>GENERAL SPECIFICATION</b> - TECHNICAL
								SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5M/MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HxWxD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs
92	DGB58065	NDR-3	5110765016376 / BLADE JIG SAW THICKNESS 3 MM 24 TEETH STEEL	JIG SAW	50 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - a. Specification: Non-3 Blade Jig Saw Thickness 3mm & 24 Teeth Steel used for cutting of wood and GRP material b. Material: grade high carbon steel c. Accepted Criteria: Conformed req. to check physically d. Thickness 3mm e. OEM/ Country of Origin: England/ Germany f. Length: 3 1/2 inch <b>GENERAL SPECIFICATION</b> - a. Specification: Non-3 Blade Jig Saw Thickness 3mm & 24 Teeth Steel used for cutting of wood and GRP material b. Material: grade High carbon steel c. Accepted Criteria: Conformed req. to check physically d. Thickness 3mm e. OEM/ Country of Origin: England/ Germany f. Length: 3 1/2 inch
93	DGB49498		4730995311376 / FLANGE PIPE STEEL ROLL Nominal BORE 1.00 inch	FOR PIPE FITTING/AS&AS P-5 KHAIBER TARIQ	256 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - MATERIAL GRADE: MILD STEEL MILD STEEL STANDARD: BS-10 OF 2008, GRADE S235JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH <b>GENERAL SPECIFICATION</b> - MATERIAL GRADE: MILD STEEL MILD STEEL
								STANDARD: BS-10 OF 2009, GRADE S235JR FLANGE NOMINAL SIZE 1 INCH, INNER DIA: 1.00 INCH, PITCH CIRCLE DIA: 3-1/4 INCH, OUTER DIA: 4-1/2 INCH, BOLT HOLES: 04 X HOLES OF 1/2 INCH OR 12.7MM AS PER TABLE A OF BS-10 OF 2009, THICKNESS OF FLANGE 7/16 INCH
94	DGB67723		4730705038534 / ELBOW BAND PIPE 90 deg with out threads (welding purpose)	DUMP BARGE CONSTRUCTION	100 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - Mild Steel ASTM-106 Grade B inner dia. 76mm, Outer dia. 88mm, Wall thickness 6mm Application Fuel and sea water system <b>GENERAL SPECIFICATION</b> - Mild Steel ASTM-106 Grade B inner dia. 76mm, Outer dia. 88mm, Wall thickness 6mm Application Fuel and sea water system
95	SGB71456		5308991243628 / BOLT MACHINE ISO STEEL HEX HD SIZE 16X5X38 MM	FASTENINGS BOLTS AND STUDS	150 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - SIZE: 16X5X38 MM, MATERIAL: MS, Grade A/SI 4140, BOLT HEAD - HEXAGON <b>GENERAL SPECIFICATION</b> - SIZE: 16X5X38 MM, MATERIAL: MS, Grade A/SI 4140, BOLT HEAD - HEXAGON
96	DGB72871	BRANDS: TOKA FLEXOMIT AND BLACK	5345705060218 / GRINDING DISC SIZE: 125X7X22.23 MM	GENERAL PURPOSE	157 / EACH/ NUMBER			<b>TECHNICAL SPECIFICATION</b> - GRINDING OF METAL SHEETS/PIPES DIMENSION: 125X7X22.23 MM BRAND: RHODIUS/ ANY OTHER CERTIFIED BRAND Date of manufacturing and expiry should be mentioned on item. Shelf life: 03 Years <b>GENERAL SPECIFICATION</b> - GRINDING OF METAL SHEETS/PIPES DIMENSION: 125X7X22.23 MM BRAND: RHODIUS/ ANY OTHER CERTIFIED BRAND Date of manufacturing and expiry should be mentioned on item. Shelf life: 03 Years
97	DGE72200	NIL	5380001619715 / PAPER	GENERAL USE	120 / PACK			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
			OXIDE MATERIAL EMERY					
98	DGP73648		7530705007182 / WHITE OFFSET PAPER SIZE		12 / REAM			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
99	DGE72177	NIL	7920705101751 / BROOM NYLON SIZE: 1'X2' (BRUSH NYLON)		3 / DOZEN			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	MANUF ADD	TECH / GEN SPECS
100	DGB73122	NO DATA AVAILABLE	0248500000015 / SAFE-STEEL-WITH-COMBINATION-LOCK FOR CBs SZ 28X20X16 5/8		1 / EACH/NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> -A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum: 02 As per RWIMs record <b>GENERAL SPECIFICATION</b> -A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM: 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum: 02 As per RWIMs record
101	DGB67611	NO DATA AVAILABLE	0246500001066 / BLOCK CHAIN 5 TON 10METER (ORIGINAL MANUFACTURE LENGTH)		4 / EACH/NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model: C21. <b>GENERAL SPECIFICATION</b> - Make: Elephant Chain Block Co. Ltd. Japan. Model: Manually operated chain Hoist Model: C21.
102	DGD72998	MS-3443 /ADW.	7310705121904 /	MICROWAVE OVEN 34LTR	1 / EACH/	DW-138G		<b>TECHNICAL SPECIFICATION</b> - brand name: (i.e WESTPOINT/ LG /SHARP / TOSHIBA /DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLDWH # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI <b>GENERAL SPECIFICATION</b> - brand name: (i.e WESTPOINT/ LG /SHARP / TOSHIBA /DAWLANCE) local: POWERTECH PAKISTAN (PVT) LTD BANGLDWH # D-63, BLOCK-08 KDA-24 GULSHAN-E-IQBAL KARACHI
103	DGE72136	NO DATA AVAILABLE	0413500000132 / EAR DEFENDER-SMALL SIZE		543 / PAIR	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
104	DGE72162	NO DATA AVAILABLE	0413500000133 / EAR DEFENDER		672 / PAIR	PELTOR H10A/ OPTIME 105		<b>TECHNICAL SPECIFICATION</b> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model: peltor H10A/OPTIME 105 3M Ear Defender Broom Viking Medium Size (HAC Hardware & Industrial Safety Equip) <b>GENERAL SPECIFICATION</b> - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model: peltor H10A/OPTIME 105 3M Ear Defender Broom Viking Medium Size (HAC Hardware & Industrial Safety Equip)
105	DGE72139	NO DATA AVAILABLE	0413500000134 / EAR DEFENDER LARGE SIZE		1852 / PAIR	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
106	DGP73647		7630705045304 / REAL ART PAPER 20"		2 / REAM			<b>TECHNICAL SPECIFICATION</b> - Denomination: Ream Size: 20 x 30 ± 5 inches weight 90 gm <b>GENERAL SPECIFICATION</b> - Denomination: Ream Size: 20 x 30 ± 5 inches weight 90 gm
107	DGE71822	HB-101BS187C	0421500000011 / MANUAL STEEL IRON HOSPITAL BED X 2 CRANK	(FOR HOSPITAL USE)	9 / EACH/NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - 1. Drip Point/IV Stand: To be included on both side of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/Coating: Half White 4. Lever: Lever for up and down of patients head & feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks 6. Head End: Head end should be removable <b>GENERAL SPECIFICATION</b> - 1. Drip Point/IV Stand: To be included on both side of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/Coating: Half White 4. Lever: Lever for up and down of patients head & feet. 5. Wheels: The bed should have 4 x wheels with three stopper / breaks 6. Head End: head end should be removable <b>BED IRON STEEL HOSPITAL ALONGWITH DRIP</b>
108	DGE72180		8020994615973 / TRAY FOR PAINTS ROLLER.		16 / EACH/NUMBER			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
108	DGP73745	NO DATA AVAILABLE	0051500000667 / FORM F(NS)68 FILE COVER		6250 / EACH/NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - 1. GSM OF CARD: 300±5% 2. FILE COVER SIZE LENGTH: 355MM (MIN) WIDTH: 235MM (MIN) HEIGHT OF FILE: 15MM (MIN) 3. WIDTH OF FALPER FOLD 595 MM (MIN) 4. BINDING CLOTH 100% COTTON TO BE PASTED (EQUALITY) ON BOTH SIDE OF CARD. CLOTH COLOUR SHADE OXFORD BLUE NO 105 OF BS-381C   LENGTH: 355MM (MIN)    WIDTH: 75MM (MIN) 5. THICKNESS

S/N	LPR No	PART NO	NSN / Description	Pr/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
								OF TRANSPARENT PLASTIC LAMINATION INSIDE FILE CARD 10 MICRON (MIN) 6. 06 NO EYLETES TO BE FIXED ON CARD FOR (FILLING PURPOSE) PAPER FASTING 7. PACKING I. ONLY 200 FILE COVER TO BE PACKED IN A CARD BOARD BOX. II. EACH BUNDLE OF 50 FILE COVER WRAPPED IN POLYTHENE BAG, THEN FURTHER PACKED IN CARD BOARD BOX. AS PER SAMPLE TO BE APPROVED BY STATIONARY BOARD. <b>GENERAL SPECIFICATION</b> - 1. GSM OF CARD 300±5% 2. FILE COVER SIZE LENGTH: 355MM (MIN) WIDTH: 235MM (MIN) HEIGHT OF FILE: 15MM (MIN) 3. WIDTH OF FALPER FOLD 355 MM (MIN) 4. BINDING CLOTH 100% COTTON TO BE PASTED (EQUALITY) ON BOTH SIDE OF CARD. CLOTH COLOUR SHADE OXFORD BLUE NO 105 OF BS-381C. 1. LENGTH: 355MM (MIN) II. WIDTH: 70MM (MIN) 5. THICKNESS OF TRANSPARENT PLASTIC LAMINATION INSIDE FILE CARD 10 MICRON (MIN) 6. 06 NO EYLETES TO BE FIXED ON CARD FOR (FILLING PURPOSE) PAPER FASTING 7. PACKING I. ONLY 200 FILE COVER TO BE PACKED IN A CARD BOARD BOX. II. EACH BUNDLE OF 50 FILE COVER WRAPPED IN POLYTHENE BAG, THEN FURTHER PACKED IN CARD BOARD BOX. AS PER SAMPLE TO BE APPROVED BY STATIONARY BOARD.
110	DGP73011	NO DATA AVAILAB LE	0051500000567 / FORM EN5168 FILE COVER		12500 / EACH/ NUMB	NO DATA AVAILAB		<b>TECHNICAL SPECIFICATION</b> - 1. GSM OF CARD 300±5% 2. FILE COVER SIZE LENGTH: 355MM (MIN) WIDTH: 235MM (MIN) HEIGHT OF FILE: 15MM (MIN) 3.
								WIDTH OF FALPER FOLD 355 MM (MIN) 4. BINDING CLOTH 100% COTTON TO BE PASTED (EQUALITY) ON BOTH SIDE OF CARD. CLOTH COLOUR SHADE OXFORD BLUE NO 105 OF BS-381C. 1. LENGTH: 355MM (MIN) II. WIDTH: 70MM (MIN) 5. THICKNESS OF TRANSPARENT PLASTIC LAMINATION INSIDE FILE CARD 10 MICRON (MIN) 6. 06 NO EYLETES TO BE FIXED ON CARD FOR (FILLING PURPOSE) PAPER FASTING 7. PACKING I. ONLY 200 FILE COVER TO BE PACKED IN A CARD BOARD BOX. II. EACH BUNDLE OF 50 FILE COVER WRAPPED IN POLYTHENE BAG, THEN FURTHER PACKED IN CARD BOARD BOX. AS PER SAMPLE TO BE APPROVED BY STATIONARY BOARD. <b>GENERAL SPECIFICATION</b> - 1. GSM OF CARD 300±5% 2. FILE COVER SIZE LENGTH: 355MM (MIN) WIDTH: 235MM (MIN) HEIGHT OF FILE: 15MM (MIN) 3. WIDTH OF FALPER FOLD 355 MM (MIN) 4. BINDING CLOTH 100% COTTON TO BE PASTED (EQUALITY) ON BOTH SIDE OF CARD. CLOTH COLOUR SHADE OXFORD BLUE NO 105 OF BS-381C. 1. LENGTH: 355MM (MIN) II. WIDTH: 70MM (MIN) 5. THICKNESS OF TRANSPARENT PLASTIC LAMINATION INSIDE FILE CARD 10 MICRON (MIN) 6. 06 NO EYLETES TO BE FIXED ON CARD FOR (FILLING PURPOSE) PAPER FASTING 7. PACKING I. ONLY 200 FILE COVER TO BE PACKED IN A CARD BOARD BOX. II. EACH BUNDLE OF 50 FILE COVER WRAPPED IN POLYTHENE BAG, THEN FURTHER PACKED IN CARD BOARD BOX. AS PER SAMPLE TO BE APPROVED BY STATIONARY BOARD.
								BOARD BOX. AS PER SAMPLE TO BE APPROVED BY STATIONARY BOARD.
111	DGE69855	NO DATA AVAILAB LE	8340705014084 / TENT FOR CPOS AND SAILORS WT. 120 LBS		14 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - cina observation and annex b is enclosed as document a. Tent for CPOs and Sailors WT. 120 Lbs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller. <b>GENERAL SPECIFICATION</b> - cina observation and annex b is enclosed as document a. Tent for CPOs and Sailors WT. 120 Lbs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned. Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.
112	DGE69652	NO DATA AVAILAB LE	8340705014084 / TENT FOR CPOS AND SAILORS WT. 120 LBS		4 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - cina observation and annex b is enclosed as document a. Tent for CPOs and Sailors WT. 120 Lbs along with complete accessories. B. Details specifications/Technical data/ Testing

S.N g	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
								acceptance criteria be mentioned; Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, var dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories B. CoC. CoC is also required compliance by seller. <b>GENERAL SPECIFICATION</b> - this observation and annex b is enclosed as document a Tent for CPDs and Sailors WT 100 Lbs along with complete accessories. B. Details specifications/Technical data: Testing acceptance criteria be mentioned; Tent Proof: made out of 450G M2 cotton canvas which is rot proof, water proof, var dyed canvas. Tent wall: Made out of 400G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC. CoC is also required compliance by seller.
113	DGB73064	NO DATA AVAILAB LE	0264500001773 / JERRY- CAN-4-GALLON		26 / EACH/ NUMB ER	NO DATA AVAILAB LE		<b>TECHNICAL SPECIFICATION</b> - Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M. Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid Fuel and a Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating <b>GENERAL SPECIFICATION</b>
								Volume : 20 Liters Dimension : 345x165x470 mm Nominal aperture Opening : 30 MM DIA Empty Weight : 4.30 KG Pack Weight : 4.40 Kg Pack Size : 360x190x490 MM Body M. Steel 0.9 M Thick Usage : Suitable storage of petrol, diesel, liquid Fuel and a Material Grade: Polish finish grade 304 stainless steel Lock Specification: any suitable Color Shade and Coating: paint with any shade of olive drab Internal Paint Coating: Cream color coating
114	DGE72265	NO DATA AVAILAB LE	8415PKS067442 / CLOTH PARASHUTE GRAY		501 / METER			<b>TECHNICAL SPECIFICATION</b> - Width must be 5-5 feet Water proof Rot proof colour of tent is gray and user acceptance required on delivery <b>GENERAL SPECIFICATION</b> - Width must be 5-8 feet Water proof Rot proof colour of tent is gray and user acceptance required on delivery
115	DGE72208	T55642	4220731000362 / CLAYPSO AQUA LUNG 105100	T-50300	31 / EACH/ NUMB ER	NO DATA AVAILAB LE		<b>TECHNICAL SPECIFICATION</b> - LUNG DEMAND REGULATOR VALVE WITH EXTENDE <b>GENERAL SPECIFICATION</b> - LUNG DEMAND REGULATOR VALVE WITH EXTENDE
116	DGB61081	STEEL LARGE SZ WIKEY/K	8465994111267 / HAND CUFFS STEL ADJUSTABLE RATCHET TYPE CHROME PLATED BRIGHT	PNS NIGRAM	54 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - null <b>GENERAL SPECIFICATION</b> - null
117	DGP73742		7490705041308 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/ NUMB ER	CPM 25		<b>TECHNICAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>GENERAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO
								<b>COMPANY NAME</b> - TOSHIBA e-STUDIO <b>GENERAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO
118	DGP73571		7490705041308 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/ NUMB ER	CPM 25		<b>TECHNICAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO <b>GENERAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO
119	DGP73733		7490705041308 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/ NUMB ER	CPM 25		<b>TECHNICAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO <b>GENERAL SPECIFICATION</b> - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO
								DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A - (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By-Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). <b>COMPANY NAME</b> - TOSHIBA e-STUDIO

S.N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUP ADO	TECH / GEN SPECS
120	SGH56140		6145995218511 / CABLE ELECT 3 CORE CON 50/0.25MM 250V 13A	GENERAL USE	100 / METER			TECHNICAL SPECIFICATION - def - stan 02-625(2006) GENERAL SPECIFICATION - def - stan 02-625(2006)
121	DPC57394	BUTANO X M-50	6810731000994 / METHAII ETHYLE KETONE PER OXIDE		180 / LITER			TECHNICAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4 GENERAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4
122	DPC68131	BUTANO X M-50	6810731000994 / METHAII ETHYLE KETONE PER OXIDE		40 / LITER			TECHNICAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4 GENERAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4
123	DPC54241	BUTANO X M-50	6810731000994 / METHAII ETHYLE KETONE PER OXIDE		30 / LITER			TECHNICAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4 GENERAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4
124	DPC57950	BUTANO X M-50	6810731000994 / METHAII ETHYLE KETONE PER OXIDE		100 / LITER			TECHNICAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4 GENERAL SPECIFICATION - PACKING: 20.25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm <sup>3</sup> VISCOSITY 20 C: 25 mPa.s CAS NO 1338-23-4
125	DPC68135	AEROSIL Ø 200	6810705009686 / POWDER AEROSIL 200 (packing 10/15/20 kg)	EXPOSED DECKS	20 / KILOG. RAMM E			TECHNICAL SPECIFICATION - REQUIREMENT - FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA [m <sup>2</sup> /g] = 175-225 LBS ON DRYING [wt %] = 1.5 ph VALUE = 3.7-4.5 GENERAL SPECIFICATION - REQUIREMENT - FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA [m <sup>2</sup> /g] = 175-225 LBS ON DRYING [wt %] = 1.5 ph VALUE = 3.7-4.5
126	SPC43409	24137	6810002270410 / ISOPROPYL ALCOHOL (SIGMA ALDRICH 24137)		15 / GALLO N			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
127	DGE72404		7210705030537 / WATER COOLER PLASTIC 5 LTR (BRAND REHBAR/INDUSTRY/JOY	WATER CONTAINER	43 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
128	DGH63652		7125991297694 / ANGLE POSTS STORAGE SHELVING 123		60 / EACH/ NUMB ER			TECHNICAL SPECIFICATION - Material: Steel/Aluminum Length: 8 feet to 24 feet Width: 02" to 6" Angle: 90 Degrees (standard) Thickness: 1/4" to 1" Size: 2x2x 1/4" (50.8 x 50.8 x 6.35mm) 2x4x 1/4" (50.8 x 101.6 x 6.35mm) 3x3x 1/4" (76.2 x 76.2 x 12.7mm) MATERIAL GRADE SS 400 GENERAL SPECIFICATION - Material: Steel/ Aluminum Length: 8 feet to 24 feet Width: 02" to 6" Angle: 90 Degrees (standard) Thickness: 1/4" to 1" Size: 2x2x 1/4" (50.8 x 50.8 x 6.35mm) 2x4x 1/4" (50.8 x 101.6 x 6.35mm) 3x3x 1/4" (76.2 x 76.2 x 12.7mm) MATERIAL GRADE SS 400
129	DGD71589	NO DATA AVAILAB LE	7320705012426 / MACHINE ATTA KNEADING 100 TO 120 KG CAPACITY 440V 50HZ 3PHS		1 / EACH/ NUMB ER	GSA/23/ AKM		TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)
130	DGB64169		0268545002894 / WEIGHT		1 / EACH/ N			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
			WEIGHING MACHINE COST IRON 7 LBS		UMBE R			SPECIFICATION - NO DATA AVAILABLE
131	DNH73500	NO DATA AVAILAB LE	1308500530126 / DEEP FREEZER 12 CUFT 220 V AC WAVES		1 / EACH/ NUMB ER	NO DATA AVAILAB LE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE

S.N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
132	DGP73646	NO DATA AVAILABLE	005050000114 / PAPER,TYPING,LARGE,GS M4015%,WHITE,REAMOF50 05HCEL SIZEA24		78 / REAM	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
133	DGP73644	NO DATA AVAILABLE	005050000117 / PAPER PRINTING WHITE 56GSM +5% SIZEA2 420MMX594MM		4 / REAM	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - SPECIFICATION: 500 SHEETS IN EACH REAM. SPECS ADDED VIDE LETTER GSC/STY/GEN/1122 DT 05 OCT 14. GENERAL SPECIFICATION - SPECIFICATION: 500 SHEETS IN EACH REAM. SPECS ADDED VIDE LETTER GSC/STY/GEN/1122 DT 05 OCT 14.
134	DGP68144	NO DATA AVAILABLE	005050000217 / PAPER PRINTING COMPUTER WHITE FANFOL SPQR381X280MM		29070 / SHEET	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - SIZE LENGTH: 381 MM WIDTH: 280 MM WEIGHT: 60 GSM + 5% PACKING: 2000 SHEETS IN EACH BOX. GENERAL SPECIFICATION - SIZE LENGTH: 381 MM WIDTH: 280 MM WEIGHT: 60 GSM + 5% PACKING: 2000 SHEETS IN EACH BOX.
135	DGE72290	NO DATA AVAILABLE	0559780000187 / SLEEVE PLASTIC DIA 0.5CM		24 / ROLL	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.NO. 5) 40MM, 32MM, 25MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black. GENERAL SPECIFICATION - 1. FOLLOWING DIA SLEEVES DIMENSION ETC (S.NO. 5) 40MM, 32MM, 25MM, 22MM, 18MM, 12MM. 2. INSULATION HEAT SLEEVES USED FOR ELECTRICAL CABLE JOINTS AND TERMINALS/ LUGS a. Outer Diameter: 0.5cm/5mm b. Minimum shrinkage temperature: 70C c. Full shrinkage temperature: 110C d. Color: Black.
136	DGE72283	NO DATA AVAILABLE	055950000442 / MILINEX POLYSTER FILM TYPE TH 0.01 WD 12 INCH	FOR 3 PHASE PUMP MOTOR	57 / KILOGRAM	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
137	DGE72242	NO DATA AVAILABLE	8345705119362 / VELVET GREEN W=54" L=25 Yard Min	PRESENTATION VIP ITEM	90 / METER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
138	DGT73555	NO DATA AVAILABLE	0100500000043 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		70 / CUBIC FOOT	NO DATA AVAILABLE		TECHNICAL SPECIFICATION - SIZE LENGTH: 12 FEET TO 23 FEET, WIDTH: 08 INCH TO 12 INCH, THICKNESS: 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (+10%). GENERAL SPECIFICATION - SIZE LENGTH: 12 FEET TO 23 FEET, WIDTH: 08 INCH TO 12 INCH, THICKNESS: 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (+10%).
139	DGB73079	NO DATA AVAILABLE	4710705126486 / COPPER TUBE DIA 1/4 INCH	MARINE VERSION AIR CONDITIONER	30 / METER			TECHNICAL SPECIFICATION - a. Inner Dia: 4.67mm b. Wall Thickness: 0.94mm c. Outer Dia: 6.58mm d. Material Grade: Supper Copper e. Running Length/ Roll SIZE: 50ft material copper (alloy no c12200/c1220/cu-dhp) asfm b280/en 12735 / js 3300 as/nss 1571 shape (in form of coil). GENERAL SPECIFICATION - a. Inner Dia: 4.67mm b. Wall Thickness: 0.94mm c.
								Outer Dia: 6.58mm d. Material Grade: Supper Copper e. Running Length/ Roll SIZE: 50ft material copper (alloy no c12200/c1220/cu-dhp) asfm b280/en 12735 / js 3300 as/nss 1571 shape (in form of coil).
140	DGB68519	SKF 29420	0269546002945 / BEARING TAPER ROLLER SKF 29420 100X210X68MM		1 / EACH/ NUMBER			TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE
141	DCW73410		8430500900364 / SHOES BLACK LEATHER OXFORD STYLE WITH TOE L 20		200 / PAIR			TECHNICAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 07 FOR SAILOR. GENERAL SPECIFICATION - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 07 FOR SAILOR.
142	DCC73398		8440501890016 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48"		800 / EACH/ NUMBER			TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48". GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48".
143	DCW73092		8430700663685 / SAFETY SHOES FOR INDUSTRIAL		100 / PAIR			TECHNICAL SPECIFICATION - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 10. GENERAL SPECIFICATION - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 10.
144	DCD71651		8455503972702 / AVIATION WINGS AIRCREW MEN FOR UNIFORM		150 / EACH/ NUMBER			TECHNICAL SPECIFICATION - AVIATION WINGS AIRCREW MEN FOR UNIFORM. GENERAL SPECIFICATION - AVIATION WINGS AIRCREW MEN FOR UNIFORM.

S.N ID	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	MANUF ADO	TECH / GEN SPECS
145	DCD73329		8455500801152 / BADGE CAP CPO GOLD		1000 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - BADGE CAP CPO GOLD <u>GENERAL SPECIFICATION</u> - BADGE CAP CPO GOLD
146	DSB73564	CMY3003 07 / FMV2305 AS 11T	0870055905975 / VFD (VARIABLE FREQUENCY DRIVE)		1 / EACH/ NUMB ER	CMY300		<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE
147	DNZ39894	22694	4730705243378 / UNION DIA 1/2 INCH STAINLESS STEEL		17 / EACH/ NUMB ER	UNION		<u>TECHNICAL SPECIFICATION</u> - a. Standard: ASME A213 b. Material: SS 316 c. Specification: Straight Union 3/8 Inch d. Dimension Compatible with Tube Outer Dia 12.7 mm e. Working Pressure: 3000 Psi f. Fitting Type Female Fitting/ Compression fitting <u>GENERAL SPECIFICATION</u> - a. Standard: ASME A213 b. Material: SS 316 c. Specification: Straight Union 3/8 Inch d. Dimension Compatible with Tube Outer Dia 12.7 mm e. Working Pressure: 3000 Psi f. Fitting Type Female Fitting/ Compression fitting
148	DCD73442		8455501300437 / PAK MARINE INSIGNIA CPOs / SAILORS		1000 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - PAK MARINE INSIGNIA CPOs / SAILORS <u>GENERAL SPECIFICATION</u> - PAK MARINE INSIGNIA CPOs / SAILORS
149	DRG69168	Z065440 83	1730Z06544083 / PLATFORM AIRCRAFT SERVICING SIZE 4X5X7FT HEIGHT(M)		1 / EACH/ NUMB ER	NO DATA AVAILAB LE		<u>TECHNICAL SPECIFICATION</u> - STEEL PIPE DIA 3/4 INCH STEEL ANGLE TH 01CM WD 05CM STEP 1 TO 8 130X30CM, STEP 09 130X30CM, 02X SHORT WHEEL DIA 06CM, 02X LONG WHEEL DIA 10CM MATERIAL WOOD TRESTLE HEIGHT 220CM, TRESTLE LAST STEP GUARD <u>GENERAL SPECIFICATION</u> - STEEL PIPE DIA 3/4 INCH STEEL ANGLE TH 01CM WD 05CM STEP 1 TO 8 130X30CM STEP 09 130X30CM 02X SHORT WHEEL DIA 06CM, 02X LONG WHEEL DIA 10CM, MATERIAL
								WOOD TRESTLE HEIGHT 220CM, TRESTLE LAST STEP GUARD
150	DCD71636		8455501600751 / SSG(N) INSIGNIA FOR OFFICER AND CPO/SAILORS GOLD PLATED		1000 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - Material Description Yellow Brass Material Grade Cz 107 (BSI No) C26800 (I (UNS No) Material Composition - Insignia and Miniature Brass Copper 65 ± 5% S. b. Zinc 35 ± 5% The complete insignias shall be Gold Plated and finally Lacquered with two coats of air drying lacquer to protect the finish from tarnish. <u>GENERAL SPECIFICATION</u> - Material Description Yellow Brass Material Grade Cz 107 (BSI No) C26800 (UNS No) Material Composition - Insignia and Miniature Brass Copper 65 ± 5% S. b. Zinc 35 ± 5% The complete insignias shall be Gold Plated and finally Lacquered with two coats of air drying lacquer to protect the finish from tarnish.
151	DCC73397		8440501890014 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"		800 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44" <u>GENERAL SPECIFICATION</u> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"
152	DCC72696		8405500692579 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II		140 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II <u>GENERAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II
153	DCC72694		8405500692578 / OVERALL BLUE PANTONE COLOUR		140 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-I <u>GENERAL SPECIFICATION</u> - OVERALL BLUE
			SHADE 19-3920 TC 100%					PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-I
154	DSB67067	TAG-700 AIR ANGLE GRINDER	0099086072967 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		9 / EACH/ NUMB ER	tag-700 qj/NK22 61G1		<u>TECHNICAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m <sup>3</sup> /min Air Inlet 3/8" Hose Size 1/2" <u>GENERAL SPECIFICATION</u> - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m <sup>3</sup> /min Air Inlet 3/8" Hose Size 1/2"
155	SCP73332		8415502501550 / BLANKET OFFICER		35 / EACH/ NUMB ER			<u>TECHNICAL SPECIFICATION</u> - Color: Blue Weight: 2250g (+/-) 100g Material: 90% Imported Wool and 10% Soft Fabric Size: 60"x96" Side Cloth Piping <u>GENERAL SPECIFICATION</u> - Color: Blue Weight: 2250g (+/-) 100g Material: 90% Imported Wool and 10% Soft Fabric Size: 60"x96" Side Cloth Piping

S/N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
156	DGP73744	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous</p> <p>requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation.</p>
157	DGP73879	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation.</p>
158	DGP73349	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgradation.</p>

S/N	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
								requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.
159	DGP73151	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN		<b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB
								SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.
160	DGP73731	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5 12 GEN		<b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU
								Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.
161	DGP73674	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		4 / SET	CORE I5 12 GEN		<b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous
								requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation. <b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 GHz, 6 MB, 4 Core or above), Intel® Graphics Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC. b. Authorized Dealer/ OEM COC. c. Certificate of genuineness. d. Online PC verification. e. PC without modification/ upgradation.

S.N o.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
162	DGP73718	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		4 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p> <p><b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p>
163	DGP72867	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p> <p><b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p>
164	DGP73287	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5 12 GEN		<p><b>TECHNICAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p> <p><b>GENERAL SPECIFICATION - SPECIFICATION OF PC (BRANDED HP/DELL/ASUS/LENOVO):</b> 1. CPU Technology= Intel® Core i5 Processor (12th Generation or Above) (Minimum 3 Ghz, 6 MB, 4 Core or above), Intel® Graphic Card (Min 2GB shared/ dedicated), 2. System Memory= Minimum 8 GB DDR4 SDRAM (Pre-installed by OEM (preferable) or Lexar/ Adata/ Transcend), 3. Hard Disk= 1TB SATA/SSD, 4. Keyboard= USB (3d Optical), 5. Mouse= USB (Optical LED), 6. LED= 18.5" (Min) or higher (same brand), 7. LAN= Yes (Built in 10/100/1000), 8. Warranty= Minimum 01 YEAR or as provided by OEM, 9. Operating System= Windows 10 Professional or Above Key Sticker only, 10. Miscellaneous requirements: a. OEM sealed genuine PC, b. Authorized Dealer/ OEM COC, c. Certificate of genuineness, d. Online PC verification, e. PC without modification/ upgrade.</p>

S/N	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
165	DCC73398		8440501890013 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40"		800 / EACH / NUMBER			<b>TECHNICAL SPECIFICATION</b> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40" <b>GENERAL SPECIFICATION</b> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40"
166	DCC72698		8405500692581 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV		140 / EACH / NUMBER			<b>TECHNICAL SPECIFICATION</b> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV <b>GENERAL SPECIFICATION</b> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV
167	DSA71823	11916/HP-H-20"	4720TY6740238 / HP HOSE		4 / EACH / NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - Make/Model: M/s VerTEX Engineering <b>GENERAL SPECIFICATION</b> - Make/Model: M/s VerTEX Engineering
168	DGP73735	06170311	7022785241032 / thin client		1 / EACH / NUMBER	for Onqt52003		<b>TECHNICAL SPECIFICATION</b> - Processor Intel Baytrail J1800 x86 2.41GHz Dual Core Memory DDR3-2G Storage 16GB SSD Network port 10/100/1000 Ethernet (RJ-45) USB port One USB 3.0 standard port, Five USB 2.0 standard ports + USB keyboard + USB mouse + Devices with USB ports, such as USB storage devices and USB printers Display adapter 32bits true color The maximum resolution support + VGA: 1620x1200@60Hz + DVI: 1920x1200@60Hz Audio port Output: 3.5 mm small port Input: 3.5 mm small port Accessories Power line, Power adapter(12V/3A) DVI-I to VGA Stand and Mounting Option accessories DVI-I to DVI-D+VGA cable del-d to vga <b>GENERAL SPECIFICATION</b> - Processor Intel Baytrail J1800 x86 2.41GHz Dual Core Memory DDR3-2G Storage 16GB SSD Network port 10/100/1000 Ethernet (RJ-45) USB port One USB 3.0 standard port, Five USB 2.0 standard ports + USB keyboard + USB mouse + Devices with USB ports, such as USB storage devices and USB printers Display adapter 32bits true color The maximum resolution support + VGA: 1620x1200@60Hz + DVI: 1920x1200@60Hz Audio port Output: 3.5 mm small port Input: 3.5 mm small port Accessories Power line, Power adapter(12V/3A) DVI-I to VGA Stand and Mounting Option accessories DVI-I to DVI-D+VGA cable del-d to vga
169	DSA71584	TAG-400	5130TY6730147 / PNEUMATIC GRINDER 4"		8 / EACH / NUMBER	TAG-40FRH		<b>TECHNICAL SPECIFICATION</b> - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODEL: TAG-40FRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN <b>GENERAL SPECIFICATION</b> - DESCRIPTION: PNEUMATIC GRINDER 4 INCH MAKE: TOKU JAPAN MODEL: TAG-40FRH BRAND: JAPAN OEM: TOKU PNEUMATIC PRODUCTS JAPAN
170	DSB70339	DSE 10.4/6 PB 4, DSE 4, 2/4 PPA	6635725169655 / PROBE FOR ULTRASONIC THICKNESS GAUGE		2 / EACH / NUMBER	NO DATA AVAILABLE		<b>TECHNICAL SPECIFICATION</b> - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC, Doc No: 7413 076 Part Code Cable Plug Order No: Housing No: DSE 4 2/4 PB10 1 m Lemo 00 1465 671 56 <b>GENERAL SPECIFICATION</b> - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC, Doc No: 7413 076 Part Code Cable Plug Order No: Housing No: DSE 4 2/4 PB10 1 m Lemo 00 1465 671 56
171	DRG68787	1102584, or c26270	2940123967954 / FILTER ELEMENT,INTAKE AIR CLEANER (main)		2 / EACH / NUMBER	n/a		<b>TECHNICAL SPECIFICATION</b> - null <b>GENERAL SPECIFICATION</b> - null
172	DCW73414		8430500900367 / SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20		200 / PAIR			<b>TECHNICAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 10 FOR SAILOR <b>GENERAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 10 FOR SAILOR
173	DCC73395		8440501890012 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"		800 / EACH / NUMBER			<b>TECHNICAL SPECIFICATION</b> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36" <b>GENERAL SPECIFICATION</b> - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"
174	DCW73411		8430500900365 / SHOES BLACK LEATHER OXFORD (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR		200 / PAIR			<b>TECHNICAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR <b>GENERAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 08 FOR SAILOR
175	DSA71485	local dfg-747-m54-vix	4330705243221 / FILTER DEMINERALIZER (CHEMICAL RESIN: UPWMS4, PRESSURE: 100		1 / EACH / NUMBER	no data available		<b>TECHNICAL SPECIFICATION</b> - ACCESSORIES DETAIL: A. 02 X FLEXIBLE PIPE, B. 04 X JUBLES CLAMPS, C. 01 X VENT RISER ON THE TOP OF CAP, D. 02 X NIPPLES <b>GENERAL SPECIFICATION</b> - ACCESSORIES DETAIL: A. 02 X FLEXIBLE PIPE, B. 04 X JUBLES CLAMPS, C. 01 X VENT RISER ON THE TOP OF CAP, D. 02 X NIPPLES

S.N o	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
176	DCD73331		8455505038670 / BADGE CAP MINIATURE GOLDEN FOR CPOS		150 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - MATERIAL: BLAZER FABRIC COLOUR: PANTONE SHADE ANCHOR STAINLESS STEEL RING AROUND ANCHOR FIVE POINTED STAR <b>GENERAL SPECIFICATION</b> - MATERIAL: BLAZER FABRIC COLOUR: PANTONE SHADE ANCHOR STAINLESS STEEL RING AROUND ANCHOR FIVE POINTED STAR
177	DCW73089		8430700663883 / SAFETY SHOES FOR INDUSTRIAL		104 / PAIR			<b>TECHNICAL SPECIFICATION</b> - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 8 <b>GENERAL SPECIFICATION</b> - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 8
178	DGP73578	MFP M479	7435715234912 / HP COLOR LASER JET PRO MFP M479 SERIES		1 / EACH/ NUMB ER	HP COLOR LASER JET PRO MFP M479FD W		<b>TECHNICAL SPECIFICATION</b> - AS PER ATTACHEMETN <b>GENERAL SPECIFICATION</b> - AS PER ATTACHEMETN
179	DCD71639		8455703892473 / TECHNICAL INSIGNIA FOR AVIATION TECH/OFFICER		50 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - TECHNICAL INSIGNIA FOR AVIATION TECH/OFFICER <b>GENERAL SPECIFICATION</b> - TECHNICAL INSIGNIA FOR AVIATION TECH/OFFICER
180	DCW73413		8430500900366 / SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20		200 / PAIR			<b>TECHNICAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 09 FOR SAILOR <b>GENERAL SPECIFICATION</b> - SHOES BLACK LEATHER OXFORD STYLE (WITH TOE) 20 EYELETS SIZE 09 FOR SAILOR
181	DGE72141		0000888819152 / TAPE INSULATION SIZE 2" COLOUR BROWN ONE ROLL =50MTR		29 / ROLL	NO DATA AVAILA BLE		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
182	DCC72697		8405500692580 / OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III		140 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III <b>GENERAL SPECIFICATION</b> - OVERALL BLUE PANTONE COLOUE SHADE 19-3920 TC 100% COTTON SIZE-III
183	DCD71640		8455703138362 / ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE		1000 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE <b>GENERAL SPECIFICATION</b> - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE
184	DSA71838	GSM163- 02DETNG	4730142243898 / VIROLE-A- BRASER-NG		62 / EACH/ NUMB ER	NO DATA AVAILA BLE		<b>TECHNICAL SPECIFICATION</b> - Material = Copper Inner Dia = 10mm Outer Dia = 15 mm Height = 09 mm <b>GENERAL SPECIFICATION</b> - Material = Copper Inner Dia = 10mm Outer Dia = 15 mm Height = 09 mm
185	DSB73565	CMY3007 05 / MA1- 552-0076- C	6125TY6720781 / VFD (VARIABLE FREQUENCY DRIVE)		4 / EACH/ NUMB ER	CMY300		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
186	DSA73141	D-18677	5130765157117 / disc CUTTING 5 inch		312 / EACH/ NUMB ER	200611/ EN- 12413		<b>TECHNICAL SPECIFICATION</b> - OEM: RHODIUS GERMANY Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core (out side) Model No: 200611/ EN-12413 ALPHA LINE STEEL Web: www.modius abrasives.com OEM Address: SCHIEFWEKZEDUGA GMBH & CO KG BROHTSLSTR 2 56659 BURG BROH/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing <b>GENERAL SPECIFICATION</b> - OEM: RHODIUS GERMANY Technical details: Series : FTK33 Diameter: 125mm Thickness: 3.0mm Center hole: 22.23mm with steel core out side Model No: 200611/ EN- 12413 ALPHA LINE STEEL Web: www.modius abrasives.com OEM Address: SCHIEFWEKZEDUGA GMBH & CO KG BROHTSLSTR 2 56659 BURG BROH/ GERMANY SHELF LIFE OF DISC: 3 years from date of manufacturing
187	DCW73088		8430700663482 / SAFETY SHOES FOR INDUSTRIAL		102 / PAIR			<b>TECHNICAL SPECIFICATION</b> - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 7 <b>GENERAL SPECIFICATION</b> - SAFETY SHOES FOR INDUSTRIAL STAFF RUBBER SOLE SIZE 7
188	DSB73284	SR20	0870033265330 / SEALING RING OE-20 / TEFLON,BRASS & O-RING		84 / EACH/ NUMB ER	NO DATA AVAILA BLE		<b>TECHNICAL SPECIFICATION</b> : 1. ITEM IS COMBINATION OF TEFLON, METAL & O- RING WITH OUTER DIA 30MM/ 2. ITEM CAN BE TESTED IN WORKSHOP BY PLACING IN SYSTEM at 250 bar/A. Service life of Item

S.N o	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	MANUF ADD	TECH / GEN SPECS
		TR19DRH SEW						years for seals provided by different firms i.e. NG, Tripartite) be endorsed. b. Item is required to be properly preserved in packing to avoid moisture/environmental effects as the item pertains to rubberized O-rings nature. <b>GENERAL SPECIFICATION</b> - 1. ITEM IS COMBINATION OF TEFLON, METAL & O. RING WITH OUTER DIA 20MM 2. ITEM CAN BE TESTED IN WORKSHOP BY PLACING IN SYSTEM at 250 bar A. Service life of item (generally 06 x years for seals provided by different firms i.e. NG, Tripartite) be endorsed. b. Item is required to be properly preserved in packing to avoid moisture/environmental effects as the item pertains to rubberized O-ring nature.
189	DSB73283	CMY3009 D0 / MAT- 662-0076- C	6125TY6720782 / VFD (VARIABLE FREQUENCY DRIVE)		3 / EACH/ NUMB ER	CMY300		<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
190	DRG66802	4720Z06- 555500	4720Z06555500 / PIPE HIGH PRESSURE		1 / EACH/ NUMB ER	NO DATA AVAILAB LE		<b>TECHNICAL SPECIFICATION</b> - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES OD 15.6MM. <b>GENERAL SPECIFICATION</b> - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES OD 15.6MM
191	SGB61478		0214780131424 / BOLT MACHINE STEEL BSF HEX	BS 1083 THREAD SIZE	100 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - DIA: 7/8" LENGTH: 6" SPEC: PD 970,2005 MATERIAL GRADE 708M40/42 CRMO4 <b>GENERAL SPECIFICATION</b> - DIA: 7/8" LENGTH: 6" SPEC: PD
			SZ 0.875X5 000X1.750 IN					970,2005 MATERIAL GRADE 708M40/42 CRMO4
192	SGB28945		0265594233589 / HINGES BUTT MILD STEEL 4" MOD(DNC)SCH 25		1250 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - Length: 4 inch/ 100mm Width: 2.2 inch/ 55mm Hole size & Qty: 2 5mm with counter of 2 9mm & 4 holes one side. Distance btw holes: 20mm Distance from edge: 8mm Packing details enclosed Acceptance Criteria: Physical inspection by End User <b>GENERAL SPECIFICATION</b> - Length: 4 inch/ 100mm Width: 2.2 inch/ 55mm Hole size & Qty: 2 5mm with counter of 2 9mm & 4 holes one side. Distance btw holes: 20mm Distance from edge: 8mm Packing details enclosed Acceptance Criteria: Physical inspection by End User
193	SGB70126	FAG 62056 (3110001- 556197)	3110795035144 / BEARING BALL DEEP GROVE FAG 6205 025X052X15MM	DAIMLER BANZ D/GENERAT OR U K	5 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - NO DATA AVAILABLE <b>GENERAL SPECIFICATION</b> - NO DATA AVAILABLE
194	SGB69803	SKF 6314 Z (2DOT)	3110999500137 / BEARING BALL JOURNAL SINGLE ROW 70X150X35 MM	FOR GENERAL USE ONLY	6 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - SKF 6314 Z (2DOT) <b>GENERAL SPECIFICATION</b> - SKF 6314 Z (2DOT)
195	SGB70127	0254- 5672	0254784203203 / CLAMP HOSE TERRY BRAND SZ 0.875 TO 1.125X0.505X0.036IN	FUEL TANK	800 / EACH/ NUMB ER			<b>TECHNICAL SPECIFICATION</b> - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35 <b>GENERAL SPECIFICATION</b> - Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35