

TENDER BULLETIN

DATE & TIME 4/8/25 1:00 PM

INVITATION TO TENDER TO BE OPENED ON 4/22/2 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC797 01	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25- 200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	23 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771- 6500/FAX:586-771-6501.	ORIGNAL COLOR CHIPS,A DIVISION		<u>TECHNICAL SPECIFICATION -</u> OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX: 586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS* FLOORING SYS.GENERAL <u>SPECIFICATION - OEM:ORIGINAL</u> COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE: 586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.	
2	SNM756 91	276-7476	281578523543 9 / KIT-PISTON RING (KIT INCLUDES RINGS- PISTON)		10 / EACH/N UMBER	C7-1502- 117					<u>TECHNICAL SPECIFICATION -</u> nullGENERAL SPECIFICATION - null	
3	SNM757 03	3978822	312071517539 6 / BEARING THURST	DIESEL GENERATOR QSB7DM	4 / EACH/N UMBER			Cummins Inc South Carolina USA	Cummins Inc South Carolina USA		<u>TECHNICAL SPECIFICATION -</u> BEARING THURST IS A PART OF CRANKSHAFT AND BEARINGS FOR CUMMINS ENGINE QSB7DM. UPPER:STANDARDGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - BEARING THURST IS A PART OF CRANKSHAFT AND BEARINGS FOR CUMMINS ENGINE QSB7DM. UPPER STANDARD	
4	DNM79599	PW1700X / BXPW1700E	4940735137922 / HIGH PRESSURE WATER JET WASHING MACHINE	JET WASHING	2 / EACH/NUMBER	NO DATA AVAILABLE		TY		BLACK AND DECKER	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
5	DPC79737	SUVA 410a /HFC-410a/R-410a	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com		DOMESTIC MARINE	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
6	DPC78562	SUVA 410a /HFC-410a/R-410a	2590715160193 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L.2810 ENGLISH PN:0880269 www.domesticusa.com		DOMESTIC MARINE	TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
7	SNM75700	3244598/419-7640	5945015796764 / SOLENOID	D/G CATERPILLAR C2.2	2 / EACH/NUMBER		JAW00494	USA		CATERPILLAR	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
8	SNM75754	6N7174	2815011834649 / SHIELD OIL (SEAL VALVE GUIDE)	DG	48 / EACH/NUMBER			ALLIED ENGINEERING KORANGI SITE		USA	TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
9	SNM75698	1006374/138-3100	2910014542190 / FILTER ELEMENT FLUID	CATERPILLAR DG	12 / EACH/NUMBER			CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL:		CATERPILLAR	TECHNICAL SPECIFICATION - CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM			WWW: HTTP://WWW.CAT.COM GENERAL SPECIFICATION - CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM	
10	DNQ796 13	NITECH 800H/ NITECH 550/bmen-3-006	623099179696 7 / HAND LAMP PLASTIC RECHARGABLE NITECH 800/550H	FLOOD LIGHT LANTERNS	10 / EACH/NUMBER	NO DATA AVAILAB LE		UK		UK ENGLAND	TECHNICAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C. GENERAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C.	
11	SNM756 97	N013MU02 2	533077513710 2 / MECHANICAL SEAL P56	STERLING /FIRE MAIN	2 / EACH/NUMBER	NO DATA AVAILAB LE		NL		STERLING FLUID SYSTEM NETHERLAND	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
12	DNM795 88	HBC 139/HBC 52	513073522795 0 / BRUSH CUTTER	Bush Cutter	2 / EACH/NUMBER	HBC 139/HBC 52	NIL	Hyundai Power products, Korea		Hyundai	TECHNICAL SPECIFICATION - BBC 139/HBC 52 Engine Cylinder Displacement 31cm3 Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											carburettor Diaphragm type <u>GENERAL SPECIFICATION -</u> BBC 139/HBC 52 Engine Cylinder Displacement 31cm ³ Clinder bore 39 rpm Stronke 31 mm Idle Speed 3000 rpm Recommended max. Speed, 7000 rpm for grass trimmer and 8500 for brush cutter Max engine output acc to ISO 8893 KW 0.75/6500 RPM Fuel and lubrication system Type of carburettor Diaphragm type	
13	SNM757 62	FS1280	473078516572 4 / OIL-WATER SEPARATOR	LLADR	20 / EACH/NUMBER	2010		27/F NEW POLY PLAZA NO 1CHAOVANGMEN BEIDAJIE BEIJING CHINA	M/S POLY TECHNOLOGIES		<u>TECHNICAL SPECIFICATION -</u> 20 GT POWER STATION SPARES AND TOOLS. 27/F NEW POLY PLAZA NO 1CHAOVANGMEN BEIDAJIE BEIJING CHINAGENERAL SPECIFICATION - 20 GT POWER STATION SPARES AND TOOLS. 27/F NEW POLY PLAZA NO 1CHAOVANGMEN BEIDAJIE BEIJING CHINA	
14	SNM757 51	MPU 120	281570521630 0 / MPU	SSDG	2 / EACH/NUMBER	MPU 120		M/S SCENARIO INTERNATIONAL, KARACHI PH NO 0324-2636007	LOCAL		<u>TECHNICAL SPECIFICATION -</u> OEM : ICA RPM SENSER AMPLIFIERGENERAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER	
15	SNM757 02	127-2176	533101477196 1 / SEAL-INTEGRAL	CATTER PILLER GENSET 3512B USA	12 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
16	DPC795 83	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collor. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						<u>TECHNICAL SPECIFICATION -</u> CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
17	DPC797	0443-	044350224043		138 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
	36	443003	9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		CUBIC METER						CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
18	DPC798 80	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		120 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
19	DPC796 64	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
20	DPC797 92	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION -CGA G1.1 OF 1990 GRADE-H OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(96.6% Purty) in buYer/supPIEr returnable cylinder with protection cap/collor. Each Cylinder containing 5-7 Cum Acetylene.								TABLE-I	
21	DPC79706		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	16 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
22	DPC79904		0474502201711 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	360 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
23	DPC79905		0474502201738 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	340 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
24	DPC79833		0474502201738 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH	SKF COUPLING	190 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PACKING 25 LTR CARBUOY									
25	DPC797 03	0461-3951, CS2879	046159224056 2 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		15 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DPC798 32	0461-3951, CS2879	046159224056 2 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		32 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DPC797 04	NO DATA AVAILABL E	047350000537 0 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	45 / KILOGR AMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up. GENERAL SPECIFICATION - Silica Gel (Desiccaant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
28	DPC799 08		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		152 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
29	DPC797 02		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		72 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DPC789 36	NO DATA AVAILABL E	044350443000 6 / GAS COOKING		45.4 / KILOGR AMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(weight 40 to 50 KGs)								evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
31	DPC799 61	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
32	DPC799 11	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			50 KGs)								CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1, GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
33	DPC79705		047450224246 3 / SOAP SCRUBBING		80 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
34	DPC79834		047450224246 3 / SOAP SCRUBBING		322 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
35	SNM75752	7N0110	293001011267 4 / CORE ASSY, FLUID, COOLER	FOR CATERPILLER DIESEL GENERATOR (USA)	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	SNM75758	5F3106/175-7904	293071100377 2 / SEAL F/W/PP	CATERPILLER DIESEL ENGINE 50KW	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
37	DNH79598	NO DATA AVAILABLE	411073100191 0 / WATER COOLER 40/45 LITER	WATER COOLER	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECT220 AKS 40PW/FRONT STEELBODY									
38	SNM757 57	8S1606	533000437875 2 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA- 9MM TH-03MM	3304PC CATERPILLER D/GEN.USA	10 / EACH/N UMBER	3304 SSDG					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
39	SNM756 95	7N-8022	533001129254 5 / GASKET	CATTER PILLER DIESEL GENERATOR (USA)	10 / EACH/N UMBER	3304 SSDG					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
40	SNM756 89	8S8821	533000431713 7 / SEAL (COOLING SYSTEM WATER PUMP)	CATTER PILLER D/G (USA)	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DPC795 86	DUPONT SUVA 134a/ HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R- 134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS- 73 RADAR	108.96 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1. 0) 11. Evaporation rate : >1(CCL4=1. 0)GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
42	DPC79739	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERAN T GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	108.96 / KILOGR AMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
43	DPK55890	CORENA P68,ISO 6743-3	915070509556 6 / SHELL CORENA S4 P68 (CAN 20 LTR)	AIR COMPRESSO R HL2/90,PNT RUSTOM	100 / LITER						TECHNICAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P68 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/\$ ASTM D445 68 KINEMATIC VISCOSITY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH / GEN SPECS.	Dimension
											@100°C TIM/S ASTM D445 8.5 DENSITY @15PC KG/M' ASTM D1 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C ASTM D97 -51 SULPHATED ASH % M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM D130 LB WATER SEPARABILITY @54°C MIN ASTM D1401 30GENERAL SPECIFICATION - TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES METHOD S4P68 ISO VISCOSITY GRADE ISO 3448 68 PERFORMANCE STANDARD DIN 51506 R VDL 68 KINEMATIC VISCOSITY @40°C MM2/S ASTM D445 68 KINEMATIC VISCOSITY @100°C TIM/S ASTM D445 8.5 DENSITY @15PC KG/M' ASTM D1 298 990 FLASH POINT (COC) °C ASTM D92 250 POUR POINT °C ASTM D97 -51 SULPHATED ASH % M DIN 51575 0.02 RUST PREVENTION - DISTILLED WATER 24 HRS PASS ASTM D665A PASS COPPER CORROSION (100°C/3HR CC ASTM D130 LB WATER SEPARABILITY @54°C MIN ASTM D1401 30	
44	DNQ796 39	140501010	841599130487 3 / GLOVES	FIRE FIGHTING	35 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availablity	Tender Remarks	TECH / GEN SPECS	Dimension
											COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
45	DNQ796 40	005101010	841599130487 4 / HOOD, ANTIFLASH..	DC LOCKER	457 EACH/N UMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION</u> - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
46	DPC799 60	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
47	DPC798 63	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					TECHNICAL SPECIFICATION - Daily mopping purpose concentrated Zeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. GENERAL SPECIFICATION - Daily mopping purpose concentrated Zeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
48	DPC797 07	ZEEPER1 14	801070533284 9 / ZEEPER 114 CLEANER		1000 / KILOGR AMME	ZEEPER. 114					TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
49	DPC797 24	ZEEPER1 14	801070533284 9 / ZEEPER 114 CLEANER		1000 / KILOGR AMME	ZEEPER. 114					TECHNICAL SPECIFICATION - COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPOSITION: Contains a blend of phosphoric acid Appearance: Red PH-undiluted 1-2 Shull life 1 years	
50	SNM75698	1006374/138-3100	2910014542190 / FILTER ELEMENT FLUID	CATERPILAR DG	12 / EACH/NUMBER		CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 USA		CATERPILAR USA	TECHNICAL SPECIFICATION - CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM GENERAL SPECIFICATION - CATERPILLAR INC.IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 61552-7547 TEL: 309-578-6941 FAX: 309-578-3739 WWW: HTTP://WWW.CAT.COM	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025

300000.00

Bank A/c No PK17HABB0004540013100701

300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To

LP Division

2. LAO (LAO (NAVY) NSD KARACHI)