

TENDER BULLETIN

DATE & TIME 4/15/25 3:14 PM

INVITATION TO TENDER TO BE OPENED ON 4/29/2 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONG WITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DSB77551	07-0930	2815TY671994 4 / SLEAVE SUPPORT RING P 30/43		6 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
2	DPC57479	TS10268/ ZOK 27	685099225402 0 / COMPRESSO R CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSO R G.T.E. TYPE 21	60 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DPC80080	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
4	DPC80007		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING	SKF COUPLING	600 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MATTER OR BOTH WITH PACKING 25 LTR CARBUOY									
5	DPC80077	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. <u>GENERAL SPECIFICATION - CHARACTERISTICS:</u> SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
6	DNH79126	HDS 10/20-4M	432072511369 3 / KARCHER MACHINE (WITH 35 MTR HIGH PRESS HOSE ,400 bar 6.300-027.0).	KARCHER MACHINE FOR WASHING OF MAIN MAST&RADAR	1 / EACH/NUMBER	MODEL HDS10/20					<u>TECHNICAL SPECIFICATION - STANDARD ACCES:</u>TRIGGER GUN WITH SOFT GRIP,HIGH PRESS HOSE 20-35 METERS,POWER NOZZLE & SERVO NOZZLE <u>GENERAL SPECIFICATION - STANDARD ACCES:</u>TRIGGER GUN WITH SOFT GRIP,HIGH PRESS HOSE 20-35 METERS,POWER NOZZLE & SERVO NOZZLE	
7	DNH79914		414070504164 0 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
8	DNH800 94		414070504164 0 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
9	DSM797 94	068N2103	482014476279 1 / THERMO EXPANSION VALVE		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
10	DNM801 41	A/C REVERSIB LE MITSUBISHI 2TON	596273514247 5 / AIR CONDITIONER (REVERSEABLE) SPLIT TYPE 02 TON (HOT/COOLED) MITSUBISHI	A/C REVERSIBLE MITSUBISHI 2TON	1 / EACH/N UMBER	NO DATA AVAILAB LE		00			TECHNICAL SPECIFICATION - COUNTRY OF ORIGIN: THAILAND GENERAL SPECIFICATION - COUNTRY OF ORIGIN: THAILAND	
11	SNM295 57	996-742	431079518994 7 / CON ROD BOLT	PERKINS D/G 2306C-E14TAG3 UK	12 / EACH/N UMBER	2306C-E14TAG3	FGD0610 12U1888 K	UK	PERKINS DIESEL COMPAN Y		TECHNICAL SPECIFICATION - M/S S.M JAFFER & COMPANY KARACHI GENERAL SPECIFICATION - M/S S.M JAFFER & COMPANY KARACHI	
12	SPC6811 1	NO DATA AVAILAB LE	047450224245 8 / POWDER GRAPHITE DRY FLAKE	PORT MAIN ENGINE	50 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
13	DNM792 02	3823494/3 164067	804079515592 3 / SEALANT SILICONE	750KVA CUMMINS D/G	6 / EACH/N UMBER	QSK 23G CUMMIN S UK		CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC. BOX 3005.COLUMBUS. INDIANA.U.S.A	QSK 23G CUMMIN S UK		TECHNICAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC.BOX 3005.COLUMBUS. INDIANA.U.S.A GENERAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND. CUMMINS INC.BOX 3005. COLUMBUS INDIANA.U.S.A	
14	SNM769 89	462-1171/462-1171	294001563305 4 / FILTER, FLUID	DG CAT 7.1 USA	10 / EACH/N UMBER	CAT 7.1	CAT00C7 15GTU00 677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPI LLAR USA		TECHNICAL SPECIFICATION - OVERALL WIDTH (IN): 3.6 OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6 GENERAL SPECIFICATION - OVERALL WIDTH (IN): 3.6	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OVERALL HEIGHT (IN): 7.9 OVERALL LENGTH (IN): 3.6	
15	DPC776 92	SIKAFLEX -290	803079516762 1 / SIKAFLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTRIDGE	PRIMER- 290DC	11 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		TECHNICAL SPECIFICATION - ? 1- component formulation ? Non- corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129 GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
16	DNM787 38	112017	433070517262 8 / INTAKE FILTER CARTRIDGE MOBILE LPAC (ALPINE)	LPAC	2 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102 GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102	
17	DNM787 39	85484	433070517262 9 / SEPARATOR CARTRIDGE LPAC ALPINE	LPAC	2 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102 GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102	
18	DNM781 82	3393037	533071517706 5 / IMPELLER, PRIMING	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER	kta 50		CUMMINS Ins SOUTH CAROLINA USA.	CUMMIN S USA		TECHNICAL SPECIFICATION - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL. GENERAL SPECIFICATION - IMPELLER, PRIMING FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
19	DPC781 06	ZISE-15	685070519963 9 / SUPER INSULATION (LIQUID ELECTRICAL INSULATION) OEM = NANO	PCB PROTECTOR SPRAY ESTONIA	15 / BOTTLE	150 ML	NA	NANO PROTECH OU, Uus Sadama 21, Tallinn 10120, Estonia Phone +3726683242	NANO PROTEC H		TECHNICAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C GENERAL SPECIFICATION - Form: Liquid Colour: Green Ignition Point: 250 Degree C	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PROTECH, Packing = 150ML bottle									
20	SNM53858	032-9020	534001575067 2 / CLAMP, LOOP	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	8 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE, ENGINE DIVISION MOSSVILLE BLDG AC P.O. BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
21	DPK77237	MODEL NO.5023	668071513258 1 / HFE-7500 3M(TM) ENGINEERING FLUID/FLUKE		10 / LITER	NO DATA AVAILABLE	US		FLUKE CORPORATION P. O BOX 9090, EVERETT, WA, USA 98206		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
22	DNM79179	390-1557	281571522420 3 / PUMP AS FUEL TRANSFER	DGCAT7.1USA	1 / UNIT	CAT7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
23	DNM77612	OS-2353	530600426294 9 / BOLT (5 / 8 - 18X3.75 - IN)	33KVA CATERPILLER DG DEO33EO UK	8 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G04236	CATERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER U. K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
24	DNM79192	8M-4988	533100997723 0 / SEAL O-RING	SSDG	2 / EACH/NUMBER	N03306B		CATERPILLAR INC. IDBA CATERPILLAR DIV DEFENSE & FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE IL UNITED STATES 309-578-6941 309-578-3739 HTTP://WWW.CAT.COM	CATERPILLAR INC. IDBA CATERPILLAR DIV DEFENSE & FED		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
25	SNM77227	6V-0128	533001536980 1 / GASKET	DG 550 KVA	4 / EACH/NUMBER	C-18ACERT	CAT00C1 8LNB017	CATERPILLER SARL SSS/O EAMI POWER	Caterpillar		TECHNICAL SPECIFICATION - OVERALL WIDTH: 1.4 INCH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(SEAL CONNECTOR)		UMBER		38	SYSTEMBUILDING 21 MILLENIUM SPRINGVALE BUISNESSPARK BELFAST BT 12 AL NORTHREN IRLAND UK			OVERALL LENGTH: 1.8 INCH OVERALL DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED GENERAL SPECIFICATION - OVERALL WIDTH: 1.4 INCH OVERALL LENGTH: 1.8 INCH OVERALL DEPTH: 0.1 INCH ACCEPTANCE CRITERIA: GENUINE CATERPILLAR ITEM REQUIRED	
26	SNM708 48	26550005	291099175147 8 / FUEL FILTER ELEMENT KIT	60 KVA PERKINS D/G	3 / EACH/N UMBER			PERKINS UK	UK		TECHNICAL SPECIFICATION - SM JAFFER AT KEAMARY GENERAL SPECIFICATION - SM JAFFER AT KEAMARY	
27	DPC778 91	NO DATA AVAILABL E	044350044302 8 / GAS OXYGEN BREATHING (99.5% PURITY) WITH PROTECTION CAP WATER CAPACITY 40- 50 LTR		47.6 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G4.5 OF 1983 TABLE IGENERAL SPECIFICATION - CGA G4.5 OF 1983 TABLE I	
28	DPC800 05		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	630 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
29	SPC7872 4		047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	522 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE	
30	DPC776 31		047450000713 8 / VASELINE PARAFIN WHITE		45 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
31	DPC743 82		044250442004 8 / Paint	FINISHING INTERIOR	300 / LITER						TECHNICAL SPECIFICATION - To be tested against DEFSTAN: 80-78/2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Interior, (Pale Green) fire retardant Flash Point: 32 Degree C (Min) type: alkyd, Principal Component: Titanium, Method of application: brushing, type of coat finishing, thinner white spirit / turpentine.								of 1995. Stage Inspection Prescribed. Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. PACKING: 04 LTR TIN (GAUGE OF TIN 26 TO 28 SWG) 4. NS/P/002 of Apr 2013 (Revised) Except for Packing <u>GENERAL SPECIFICATION</u> - To be tested against DEFSTAN: 80-78/2 of 1995. Stage Inspection Prescribed. Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. PACKING: 04 LTR TIN (GAUGE OF TIN 26 TO 28 SWG) 4. NS/P/002 of Apr 2013 (Revised) Except for Packing	
32	DPC749 30		044250942353 9 / PAINT MARKING BRUSH STENCILLING AMMUNITION (AZURE BLUE), Flash Point 32C (04 LTR TIN) packing: 04 ltr tin gauge of drum 26 to 28 swg		98 / LITER						<u>TECHNICAL SPECIFICATION</u> - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996 <u>GENERAL SPECIFICATION</u> - 1. defstan 80-68/4 of 2009 2. ns/p/012 of 1976 3. stage inspection prescribed 4. colour shade no 104 of bs 381 c of 1996	
33	DPC749 31	NO DATA AVAILABL E	044250442015 1 / PAINT ZINC RICH EPOXY HARDENER (Component B)	BUXLY/BERGE R/ICI/KOSAR GRP-A VIDE NHQ LT	176 / LITER						<u>TECHNICAL SPECIFICATION</u> - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY: WITHIN 1 HRS (B) TACK FREE: WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ. METERS PER LITER PER COAT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(vii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXLY THINNER EP-TH-10 (xi) % OF ZINC IN AGENT 70% MIN GENERAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY: WITHIN 1 HRS (B) TACK FREE: WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ. METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXLY THINNER EP-TH-10 (xi) % OF ZINC IN AGENT 70% MIN	
34	DPC724 84	DGS 5961	044250442015 2 / PAINT COALTAR EPOXY COMPENENT- A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	300 / LITER						<u>TECHNICAL SPECIFICATION -</u> DGS 5961 <u>GENERAL</u> <u>SPECIFICATION - DGS 5961</u>	
35	DNQ773 72	FRP/E3S0 4	035099571318 9 / ROPE FIBROUS.	DIVING PANNEL	32 / COIL						<u>TECHNICAL SPECIFICATION -</u> NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
36	DNQ781 27	FRP/E3S0 4	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	10 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
37	DPC801 92	NO DATA AVAILABL E	044350443000 8 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. <u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
38	DPC754 07	60194	044250442016 8 / READY MADE BAIT CONTROL (Rat & mouse killer Racumin) TLON@ WEATHER BLOK @ XT		7.5 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> TLON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight <u>GENERAL SPECIFICATION -</u> TLON@ WEATHER BLOK @ XT (MANUFACTURED BY SYNGENTTA) 16 POUND X 20 GRAM (0.7 OUNCE) BLOCKS net weight	
39	DPC754 08	NO DATA AVAILABLE	044250442016 9 / BAYTEX 50% EC FOR INSECTICIDE.		12 / LITER						<u>TECHNICAL SPECIFICATION - a.i</u> FENTHION 50%WW .01LTR PLASTIC PACKING WITH REGISTERED LABEL. 1. Owner name: Muhammad Naveed 2. Contact No. 03218995233 3. Address: MTS pest control and garden, Shop # 6 & 7, Razzaq apptment, Al - Hilal housing society, old sabzi mandi road, opposite Askari Park, Gulshan e Iqbal, Karachi. <u>GENERAL SPECIFICATION - a.i</u> FENTHION 50%WW .01LTR PLASTIC PACKING WITH REGISTERED LABEL. 1. Owner name: Muhammad Naveed 2. Contact No. 03218995233 3. Address: MTS pest control and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											garden, Shop # 6 & 7, Razzaq aptment, Al - Hial housing society, old sabzi mandi road, opposite Askari Park, Gulshan e Iqbal, Karachi.	
40	DNQ78632		026599419526 4 / 6" STAPLE CLAMP		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DPC80008		047450224248 3 / SOAP SCRUBBING		252 / KILOGRAMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose. GENERAL SPECIFICATION - BS 1913 of 1990 Soap Type a: Soap Scrubbing TYPE A: Suitable for general toilet purpose.	
42	DPC72034	NO DATA AVAILABLE	421070506993 6 / CYLINDER CO2 (72KG) CO2 FIXED FIRE FIGHTING SYSTEM BOAT WAIN (EMPTY)	PNS GAWADAR	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 01 Fire Extinguisher Cylinder CO2: 72 KG (Empty Weight) 02 Capacity :50 KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05 Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel GENERAL SPECIFICATION - 01 Fire Extinguisher Cylinder CO2: 72 KG (Empty Weight) 02 Capacity : 50 KG 03 Total Weight: 122 KG 04 Operation Method: Store Pressure 05 Extinguishing Agent: Carbon Dioxide 06 Operating Temperature: 30c to 60c 07 Discharge Time: 7 Sec per KG 08 Discharge Distance: 4 Meter 09 Height: 1440 mm 10 Width: 650 mm 11 Depth :1400 mm 12 Working Pressure: 60 Bar 13 Testing Pressure: 250 Bar 14 Material: Iron Steel	
43	DNQ76730	11/454/3/10/2745	533099923890 5 / STRIP RUBBER	4.5" MK-8 GUN	9 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SHEET								AVAILABLE	
44	DNQ78652	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
45	DNQ76882	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	SPC77413	BELZONA 9341	8030705040916 / BELZONA RE-INFORCEMENT TAPE (BELZONA 9341) (Packing 10 Meters roll)	FOR BRIDGING CRACKS & FOR BELZONA METALS	20 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
47	DPC79171	NO DATA AVAILABLE	6830705041338 / GAS ARGON N56 HIGH PURITY 99.9996%	FOR MISTRAL AIR DEFENCE SYSTEM	61.2 / CUBIC METER						TECHNICAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes. GENERAL SPECIFICATION - 1. PURITY 99.9996% through lab testing or through verification of OEM COC as per standard format. 2. Packing as per available cylinder sizes.	
48	DPK76418	XG-279, G-403 (DEFSTAN 91-27 ISSUE 2 OF 2011)	9150992202418 / GREASE AUTOMOTIVE & ARTILLERY XG-279 (G-403) (Packing 3KG TIN)		20 / KILOGRAMME						TECHNICAL SPECIFICATION - Composition: low viscosity mineral Oil and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TINGENERAL SPECIFICATION - Composition: low viscosity mineral Oil and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TIN	
49	SPC70929	BUTANOX M-60	6810731000994 / METHYL ETHYLE KETONE PER OXIDE		60 / KILOGRAMME						TECHNICAL SPECIFICATION - PACKING: 20,25 OR 30 LTRS. SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NO 1338-23-4 <u>GENERAL SPECIFICATION</u> - PACKING: 20.25 OR 30 LTRS. SPECIFICATION APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4	
50	DNM79037	342419/385311822 (600342419)	2990715119916 / M PUMP DIAPHRAGM	VACUME PUMP	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
51	DPK73798	PATEARO DERGRAI N240	5350143407964 / PATE-RODER-CARBURE-SIL-N		10 / KILOGRAMME	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
52	SPC77655	BS 627 (F-8) (R 5123)	8010705128764 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	40 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
53	DPC80051	PINAX	8010705332824 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					<u>TECHNICAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION</u> - Daily mopping purpose concentrated Zeeper Pinax which Cleans \$ Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-om, House,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Hospitals and All Types of Commercial and Noncommercial Area.	
54	DPC80031	PINAX	801070533282 4 / CLEANER ZEEPER liquid PINAX		1000 / LITER	PINAX-A					<u>TECHNICAL SPECIFICATION -</u> Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area. <u>GENERAL SPECIFICATION -</u> Daily mopping purpose concentrated Zeeper Pinax which Cleans & Germ. No need to use additional powder cleaners, bleach or any detergent. Provides a clean and refresh fragrance to help overcome unpleasant odors St Table for use on all type of floors in Schools, Sick's Rooms, Nursing S-.om, House, Hospitals and All Types of Commercial and Noncommercial Area.	
55	DSM71005	MT80711P/JWEMCM V06	599870528492 0 / Weintek HMI (Duly Programmed) for Main AC		3 / EACH/NUMBER	MT80711P					<u>TECHNICAL SPECIFICATION -</u> FUNCTIONS PARAMETERS MODEL NO MT80711P DISPLAY 7" TFT LCD DISPLAY RESOLUTION 800X480 MEMORY FLASH 125 MB <u>GENERAL SPECIFICATION -</u> FUNCTIONS PARAMETERS MODEL NO MT80711P DISPLAY 7" TFT LCD DISPLAY RESOLUTION 800X480 MEMORY FLASH 125 MB	
56	DSM71009	FX3U 48MR/JWE MCMV01	599870528492 5 / Mitsubishi PLC CPU (Duly Programmed) for Main AC		3 / EACH/NUMBER	FX3U 48MR					<u>TECHNICAL SPECIFICATION -</u> POWER SUPPLY (V) 100-240 CURRENT TYPE AC PROGRAM MEMORY 64K STEPS PROGRAM MEMORY UNIT RAM INTEGRATED DIGITAL INPUTS 24 OUTPUT TYPE RELAY LOCAL I/O OINTS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											256GENERAL SPECIFICATION - POWER SUPPLY (V) 100-240 CURRENT TYPE AC PROGRAM MEMORY 64K STEPS PROGRAM MEMORY UNIT RAM INTEGRATED DIGITAL INPUTS 24 OUTPUT TYPE RELAY LOCAL I/O QINTS 256	
57	DSB72667	RPS-CAG-34M-VTX	9320705280803 / ROBIN PAW		555 / METER	cassing shoes of submarine					TECHNICAL SPECIFICATION - ISO BRUTENE- ISOPERENE RUBBER color black, THICKNESS 0.2/0.3/0.4MM NATURAL SYNTHETIC RUBBERGENERAL SPECIFICATION - ISO BRUTENE- ISOPERENE RUBBER color black, THICKNESS 0.2/0.3/0.4MM NATURAL SYNTHETIC RUBBER	
58	DSB75919	RPS-CAG-34M-VTX	9320705280803 / ROBIN PAW		15 / METER	cassing shoes of submarine					TECHNICAL SPECIFICATION - ISO BRUTENE- ISOPERENE RUBBER color black, THICKNESS 0.2/0.3/0.4MM NATURAL SYNTHETIC RUBBERGENERAL SPECIFICATION - ISO BRUTENE- ISOPERENE RUBBER color black, THICKNESS 0.2/0.3/0.4MM NATURAL SYNTHETIC RUBBER	
59	DSM71007	FX2N-16EYR/JW EMC/MV03	5963705284924 / Mitsubishi digital OUTput module (Duly Programmed) for Main AC		3 / EACH/NUMBER	FX2N-16EYR					TECHNICAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 CURRENT TYPE DC OCCUPIED I/O POINTS ON PLC 8 INPUT CURRENT RANGE mA -20-20:4 -20 MIN. AMBIENT TEMPERATUE CELCIUS DEGREE 0 MAX. AMBIENT TEMPERATUE CELCIUS DEGREE 55GENERAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 CURRENT TYPE DC OCCUPIED I/O POINTS ON PLC 8 INPUT CURRENT RANGE mA -20-20:4 -20 MIN. AMBIENT TEMPERATUE CELCIUS DEGREE 0 MAX. AMBIENT TEMPERATUE CELCIUS DEGREE 55	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
60	DSM71010	FX2N-4AD-PT/JWEM CMV05	596370528449 2 / Mitsubishi PT100 Module (Duty Programmed) for Main AC		6 / EACH/NUMBER	FX2N-4AD-PT					TECHNICAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 NUMBER OF INPUTS 4 INTEGRATED ANALOG INPUTS 4 MIN. AMBIENT TEMPERATURE CELSIUS DEGREE 0 MAX. AMBIENT TEMPERATURE CELSIUS DEGREE 55 GENERAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 NUMBER OF INPUTS 4 INTEGRATED ANALOG INPUTS 4 MIN. AMBIENT TEMPERATURE CELSIUS DEGREE 0 MAX. AMBIENT TEMPERATURE CELSIUS DEGREE 55	
61	DSB71784	B2SK-0350-9KAS-F001	432014520970 1 / MECHANICAL SEAL (MESMA)		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Size: 40 mm Inner Dia: 35mm (physically measured) Material : Face Silicone Carbide Stationary Silicone Carbide Body: Stainless Steel GENERAL SPECIFICATION - Size: 40 mm Inner Dia: 35mm (physically measured) Material : Face Silicone Carbide Stationary Silicone Carbide Body: Stainless Steel	
62	DSM71008	FX2N-16EX/JWE MCMV02	596370528492 3 / Mitsubishi digital input module (Duty Programmed) for Main AC		3 / EACH/NUMBER	FX2N-16EX					TECHNICAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N OCCUPIED I/O POINTS ON PLC INTEGRATED DIGITAL INPUTS GENERAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N OCCUPIED I/O POINTS ON PLC INTEGRATED DIGITAL INPUTS	
63	DSB74702		424070524744 1 / copper foils 0.22 MM		8 / SHEET	2020					TECHNICAL SPECIFICATION - As per OEM document material of the disk is gold plated phosphor bronze. The diameter of disk is 20mm and ROUND IN SHAP THICKNESS 0.22 MM DIAMETER 19.96 MM The item can hold CO2 Gas pressure till 264 bar and required to puncture/ burst	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											above 264 bar. Available sample dimensions: 20mm diameter and 0.30mm thickness The item is metal disc which can hold till CO2 Gas pressure till 264 Bar. It is required to puncture/ burst at pressure above 264 bar Packing REQUIRED to avoid physical damage to item Item is local substitute of item Disque Plein 19-8 X 0,24 Bronze (NSN 4210-14-254-0732) OEM COC/ Authorized Dealer Certificate/ Mil Test Certificate (MTC) Information not held with unit and, may be acquired from local source Locally sourced sample is available Make: Item was originally received from NG France. Item locally available with M/s Star Engineering. Specification: Reference B refers <u>GENERAL SPECIFICATION</u> - As per OEM document material of the disk is gold plated phosphor bronze. The diameter of disk is 20mm and ROUND IN SHAP THICKNESS 0.22 MM DIAMETER 19.96 MM The item can hold CO2 Gas pressure till 264 bar and required to puncture/ burst above 264 bar. Available sample dimensions: 20mm diameter and 0.30mm thickness The item is metal disc which can hold till CO2 Gas pressure till 264 Bar. It is required to puncture/ burst at pressure above 264 bar Packing REQUIRED to avoid physical damage to item Item is local substitute of item Disque Plein 19-8 X 0,24 Bronze (NSN 4210-14-254-0732) OEM COC/ Authorized Dealer Certificate/ Mil Test Certificate (MTC) Information not held with unit and may be acquired from local source Locally sourced sample is available Make: Item was originally received from NG France. Item locally available with M/s Star Engineering.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specification: Reference B refers	
64	DNM78140	4309459	281501662927 9 / UPPER ENGINE GASKET		3 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
65	DNM76101	bt-2wn40	412070531225 5 / condenser shell & tube		1 / EACH/NUMBER	BT-2WN40					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
66	DNM69231	ch11021	281579524594 4 / intake valve		12 / EACH/NUMBER	2806 a-e 18 tag1a					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
67	DSM71006	FX2N-4AD/JWE MCMV04	599870528492 1 / Mitsubishi Analogue Input Module (Duty Programmed) for Main AC		6 / EACH/NUMBER	FX2N-4AD					TECHNICAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 CURRENT TYPE DC OCCUPIED I/O POINTS ON PLC 8 INPUT CURRENT RANGE mA -20-20.4 -20 MIN. AMBIENT TEMPERATURE CELSIUS DEGREE 0 MAX. AMBIENT TEMPERATURE CELSIUS DEGREE 55 GENERAL SPECIFICATION - SERIES MELSEC-F SERIES TYPE FX2N POWER SUPPLY VOLTS 24 CURRENT TYPE DC OCCUPIED I/O POINTS ON PLC 8 INPUT CURRENT RANGE mA -20-20.4 -20 MIN. AMBIENT TEMPERATURE CELSIUS DEGREE 0 MAX. AMBIENT TEMPERATURE CELSIUS DEGREE 55	
68	DSB68716		4730TY673061 7 / EQUAL TEE 1/4		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Material: Copper 03 Side Equal Tee Size ; 06x06x06 mm Thickness: 01 mm GENERAL SPECIFICATION - Material: Copper 03 Side Equal Tee Size ; 06x06x06 mm Thickness: 01 mm	
69	DRG49400	Z06510148	2630Z0651014 8 / WHEEL TROLLEY SIZE 8 INCH		10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Metallic/ rubber wheel with dia of 8 inches & Wheel Diameter 8 inches (20.32 cm) & Load Capacity approx.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											300 lbs ∟ Bearing Type Ball Bearing ∟ Mounting Type Plate Mount ∟ Swivel Type 360-degree movement Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle. GENERAL SPECIFICATION - Metallic rubber wheel with dia of 8 inches ∟ Wheel Diameter 8 inches (20.32 cm) ∟ Load Capacity approx. 300 lbs ∟ Bearing Type Ball Bearing ∟ Mounting Type Plate Mount ∟ Swivel Type 360-degree movement Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle.	
70	DPC777 52	476385	421014449704 9 / TEST GAS MIXTURE, AUTOMATIC SMOKE ALARM		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DPC779 00	POLP9460 035MC2P K	683070524143 3 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
72	DNM784 91	A054G720	281579524787 7 / Kit,Radiator		1 / EACH/N UMBER	C275D5B/ C330D5B					TECHNICAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422- 00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins GENERAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins	
73	DNM746	0149-2883	294079523736		1 /	C110D5/					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	32		4 / ELEMENT FUEL FILTER		EACH/NUMBER	FS 1251					make: fleet card <u>GENERAL SPECIFICATION</u> - make: fleet card	
74	DSB67068	LOCAL 121FA	0870033225330 / Sealing Ring		117 / EACH/NUMBER	NO DATA AVAILABLE					parent equip: HP Air Production • specs: Set of Teflon, O-Ring & metal piece Item is used in HP Air system (with 250 Bar pressure) and complete item is combination of 03 parts: metallic ring, rubberized O-ring & Teflon ring. <u>GENERAL SPECIFICATION</u> - parent equip: HP Air Production • specs: Set of Teflon, O-Ring & metal piece Item is used in HP Air system (with 250 Bar pressure) and complete item is combination of 03 parts: metallic ring, rubberized O-ring & Teflon ring.	
75	DRG40399	ZO6567572	1580ZO6567572 / WHEEL		20 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tire Diameter 535 mm Tire Ply Rating 4 ply Hub Type Locally Made Load Capacity Varies (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub <u>GENERAL SPECIFICATION</u> - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tire Diameter 535 mm Tire Ply Rating 4 ply Hub Type Locally Made Load Capacity Varies (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub	
76	DNM71415	ch11022	4810998716542 / exhaust valve		12 / EACH/NUMBER	2806a-e 18tag2					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
77	SNM68162	61-0456	5306015293358 / BOLT (M8X1.25X45-		5 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION</u> - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX FLANGE HEAD •	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MM)								COATING: ZINC • GRIP LENGTH (IN): 0.908 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 898-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL: STEEL • ZINC PLATED GENERAL SPECIFICATION - BOLT LENGTH (IN): 1.772 • BOLT TYPE: HEX FLANGE HEAD • COATING: ZINC • GRIP LENGTH (IN): 0.908 • THREAD: COARSE • THREAD SIZE (IN-TPI)(IN): M8-1.25 • HAND OF THREAD: RH • HEX SIZE (IN): 0.39 • CLASS OR GRADE: ISO 898-1 CLASS 8.8 • MATERIAL DESCRIPTION: STEEL ACCEPTANCE CRITERIA: • THREAD SIZE: M8 • MATERIAL: STEEL • ZINC PLATED	
78	DSB73721	532300-19303-45-51	5340143059306 / SUPPORT-ELA-532300-19303A		222 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DSB72719	LW-PM-14-3KVTX/LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		512 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
80	DSB75894	LW-PM-14-3KVTX/LW-PM-14-VTX (LOCAL)	5310705251577 / lock washer dn14 (LOCAL)		488 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm GENERAL SPECIFICATION - a. Type - Double Tab b. Material - Mild Steel c. Thickness - 1.5mm, 1.6mm d. Inner - 16mm	
81	DRG49402	WHEEL DIA 6"	2630ZO6510147 / TROLLEY		30 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Metal/ rubber wheel with 360 degree	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WHEEL 6"DIA		UMBER	LE					movement and dia of 6 Inches 1 Wheel Diameter 6 inches (15.24 cm) 2 Load Capacity approx. 300 lbs 3 Bearing Type Ball Bearing 4 Mounting Type Plate Mount 5 Swivel Type 360-degree movement 6 Wheel Type Solid Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle. <u>GENERAL SPECIFICATION</u> - Metal/ rubber wheel with 360 degree movement and dia of 6 Inches 1 Wheel Diameter 6 inches (15.24 cm) 2 Load Capacity approx. 300 lbs 3 Bearing Type Ball Bearing 4 Mounting Type Plate Mount 5 Swivel Type 360-degree movement 6 Wheel Type Solid Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle.	
82	DSB74291	GSM 1487 DET-7 (39679)	473014305908 1 / PLANE FLANGE		284 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - a. Material - Mild Steel b. Dia - DE 76.1 mm c. Testing Pressure - less and equal to 70 bars <u>GENERAL SPECIFICATION</u> - a. Material - Mild Steel b. Dia - DE 76.1mm c. Testing Pressure - less and equal to 70 bars	
83	DSB71480	(LOCAL) TR080RA-SEW/TR05 5RH-SEW	087003325533 0 / SEALING RING DE-14 / TEFLON, BRASS & O-RING		35 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - COUNTRY NAME : USA SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) <u>GENERAL SPECIFICATION</u> - COUNTRY NAME : USA SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
84	DSB67142	5330JA-BAGUERU CHDE17, 15 / (LOCAL)	533014356877 9 / WATER TIGHTNESS RING TEFLON,		190 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SERVICE LIFE OF ITEMS TO BE 06 YEARS (GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG) <u>GENERAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		TR130RH-SEW/ (LOCAL) TR280RA-SEW	S/STEEL & O-RING								SERVICE LIFE OF ITEMS TO BE 06 YEARS TO GENERALLY 06 X YEARS FOR SEALS PROVIDED BY NG)	
85	DPC80086	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-8 PARTIAL 25- 200 fl2/lb)	DECK COVERING FOR CONCRETE SURFACE	14 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771- 6500/FAX:586-771-6501.		ORIGINAL COLOR CHIPS,A DIVISION	TECHNICAL SPECIFICATION - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX: 586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.GENERAL SPECIFICATION - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE: 586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.	
86	DSA73708	DLT21236	534014232787 8 / SUPPORT ELASTIQUE 532500 B60		32 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE.GENERAL SPECIFICATION - NO DATA AVAILABLE	
87	DSB67497		009908607292 5 / FRAISE- ATRAX (STEEL RIMER)		118 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
88	DSB60991	AV19990970045	087013170343 9 / Aluminum		56 / KILOGR	NO DATA AVAILAB					TECHNICAL SPECIFICATION - Aluminum Filter Metal AL-Mg 4.5 Mn	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Filter Metal AL-Mg 4.5 M		AMME	LE					Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183 <u>GENERAL SPECIFICATION -</u> Aluminum Filter Metal AL-Mg 4.5 Mn Diameter : 1.2 mm Welding Process: MIG Shielding Gas: Argon Classification: AWS A 5-10: ER 5183	
89	DSB61297	MAT164-0343F02R EP07	087007154473 0 / STEEL WELDING CURVE SIZE (ELBOW) DN - 48.3 x 2.6 mm)		16 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - a.</u> Outer Diameter : 48.3 mm b. Thickness : 2.6 mm c. Bending Radius : R-57° d. Material : TU37C f. Country Origin : France for More details see attachment <u>GENERAL SPECIFICATION - a.</u> Outer Diameter : 48.3 mm b. Thickness : 2.6 mm c. Bending Radius : R-57° d. Material : TU37C f. Country Origin : France for More details see attachment	
90	DRG49176	61SSR	5999Z0523849 4 / HALL SENSOR (GP-123)		10 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> 61SSR HALL SENSOR <u>GENERAL SPECIFICATION - 61SSR HALL SENSOR</u>	
91	DSA74720	SS-HYD-7865-VTX/33358 / 33358A	536014311786 5 / RESSORT 33358		3 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION -</u> SIZE: 15X11X1 MATERIAL: STAINLESS STEEL 316 <u>GENERAL SPECIFICATION - SIZE: 15X11X1 MATERIAL: STAINLESS STEEL 316</u>	
92	DSA70941	504802	534014417533 3 / AMORTISSEUR CONIFOR		164 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
93	DSB61298		087007151473 0 / steel WELDING CURVE SIZE: DIA 88.9 X 6.3 MM		36 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - a.</u> Outer Diameter : 88.9 mm b. Thickness : 6.3 mm Enclosure-2 c. Bending Radius : R-114° d. Material/Chemical Composition/Testing Criteria: Enclosure-3 Material: TU37C Technical Data acceptance criteria: placed at Encl 1. Dimension: placed at Encl 3 <u>GENERAL SPECIFICATION - a.</u> Outer Diameter : 88.9 mm b. Thickness : 6.3 mm Enclosure-2 c. Bending Radius : R-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											114" d. Material/Chemical Composition/Testing Criteria: Enclosure-3 Material: TU37C Technical Data acceptance criteria: placed at End 1. Dimension: placed at End 3	
94	DSA80004	BIS20MT27F	593514316389 6 / ISOLANT B1520M27F		6 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DSA64731	4812268B	597714372487 9 / BALAI ELECTRIQUE 4812268B		14 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DSK67135	C337AHE XAGONE3 2CUAL	953014298438 6 / HEXAGONE- DE-32CUPRO- ALU		84 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DNH80652	HPU-48CH03	413078515703 4 / A/C 4 TON FLOOR STANDING	4 TON A/C HPU-48CH03	1 / EACH/N UMBER	GF-48TF		HAIER CHINA LOCAL MARKET (TUBA INTER FIRM)		HAIER CHINA	TECHNICAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY: LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, ig, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE GENERAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY: LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND COMPRESSOR), LG, GREE	
98	DPC804 60	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
99	DPC803 92	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
100	DPC803 75	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGR AMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. <u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
101	DPC80459	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. <u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
102	DSB74170	RL830-C602/604	599873528196 3 / motherboard bcu		1 / EACH/NUMBER	rl830-c602/c604					<u>TECHNICAL SPECIFICATION -</u> processor: 2 lga 2011 sockets chipset: intel C602/C6024 express chipset memory: 16 ddr3 dimm upto 512gb expansion: 4pcie x 16/2 pcie x8 display outputs: 1 vga lan: 4 lan com: 2com usb: 8usb 2.0 <u>GENERAL SPECIFICATION -</u> processor: 2 lga	

No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2011 sockets chipset: intel C602/C6024 express chipset memory: 16 ddr3 dimm upto 512gb expansion: 4pcie x 16/2 pcie x8 display outputs: 1 vga lan: 4 lan com: 2com usb: 8usb 2.0	
103	DSB80090	BIS20M21M	5935143164110 / ISOLANT BIS20M21M		6 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DSB71864		0099086072925 / FRAISE-ATRAX (STEEL RIMER)		25 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
105	DSA70338	30143AREP2	5360143680358 / RESSORT PLAT F1295 30143AREP2		12 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Length : 68mm Width : 6mm Thickness : 0.05 mm Material : Stainless steel GENERAL SPECIFICATION - Length : 68mm Width : 6mm Thickness : 0.05 mm Material : Stainless steel	
106	DSA70337	14X29-5X15SA710	5365142353252 / MANCHON COAU 14X29, 5X15SA710		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DRG70421		1730ZO6549721 / TRESTLE AFT		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE 30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel 8inch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color) GENERAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE 30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel 8inch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color)	
108	DPC80237	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
109	DNM75395	441-1215	294071524014 1 / FILTER GP-		1 / EACH/N	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FUEL (WATER SEPARATOR)		UMBER						SPECIFICATION - NOT KNOWN	
110	DPC801 14		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		242 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DPC801 15	0461-3951 CS2879	046159224056 2 / WATER INDICATING PASTE FOR FUEL (03 OZ TUBE)		48 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
112	DPC800 88		047450220173 8 / SOAP TOILET IN LIQUID FORM (PERFUMED), NON-TOXIC COLOURING MATTER OR BOTH WITH PACKING 25 LTR CARBUOY	SKF COUPLING	699 / LITER						TECHNICAL SPECIFICATION - BS 1545 : 1990 GENERAL SPECIFICATION - BS 1545 : 1990	
113	DPC764 12	FG-K2- 005-KW	482079513257 9 / TAN-(0-6) LUB OIL TESTING KIT	LUB OIL TESTING KIT KITTIWAKE	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK	UK		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
114	DNM749 84	U6511673 0	151578523555 4 / TIMING CASE		1 / EACH/N UMBER	SDG15PS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
115	DNM763 51	7N4448	531001130061 1 / INSERT (INTAKE) (WASHER RECESSED)	3304PC, CATERPILLER D/GEN.USA	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
116	DNM725 75	12009	482014488289 6 / AFT PUSH FOR PUSH ROD	SHAFT ASSEMBLY	1 / EACH/N UMBER	NO DATA AVAILAB LE		DK	FABRIK A/S NORVAN GEN 12- DK-4220 KORSOR-		TECHNICAL SPECIFICATION - AS PER SAMPEL GENERAL SPECIFICATION - AS PER SAMPEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									DENMARK PHONE: 00455837 0934; FAX: 00455837 2434;E- MAIL: PROPEL @POST 7.TELE. DK. DENMARK			
117	DNH798 91	BD 50/50 C	791072528077 3 / KARCHER MACHINE (CLASSIC BP PACK SCRUBBER DRIER WITH SWEEPING FUNCTION)		1 / EACH/NUMBER	SCRUBBER DRIER BD 50/50C					TECHNICAL SPECIFICATION - Classic BP pack scrubber drier with sweeping function GENERAL SPECIFICATION - Classic BP pack scrubber drier with sweeping function	
118	DPC802 51	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPLiEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene.		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

779

Pakistan Military Accountst Department

Office of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 1 dt 13/01/2025

300000.00

Bank A/c No PK17HABB0004540013100701

300000.00

In Words Rs THREE HUNDRED THOUSAND

For C N A

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To

LP Division

2. LAO (LAO (NAVY) NSD KARACHI)