

TENDER BULLETIN

DATE & TIME 5/20/25 11:41 AM INVITATION TO TENDER TO BE OPENED ON 6/3/25 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNQ80607		473099533296 8 / CLAMP HOSE ZINC PLATED W12. 8MM I/D 55MMX70MM SZ 70MM 68/226	E16 MACHINERY SPACE DAMAGE CONTROL TOOLB	17 / EACH/IN UMBER			AB VALVO PENTA SWEDEN SE 405 08 GOTHENBURG SWEDEN	VALVO PENTA SWEDEN		TECHNICAL SPECIFICATION - ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226 GENERAL SPECIFICATION - ZINC PLATED W12.8MM I/D 55MMX70MM SZ 70MM 68/226	
2	DNM82537	3905375	471001234288 8 / TUBE FUEL SUPPLY	CUMMINS STANDBY EMERGENCY GENERATOR 4BT3-9D UK	1 / EACH/IN UMBER	4BT3-9D	MAD 46950895 RSD 46954407	CUMMINS LTD T/A CUMMINS UK RUTHERFORD DRIVE, PARK FARM INDUSTRIAL ESTATE, WELLINGBOROUGH, NORTHAMPTONSHIRE, UK Tel : 01933 672 200 Fax : 01933 403 200 Email/URL : www.cummins. com	CUMMIN S LTD UK		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
3	DNQ79611	SPL-1	623099991050 4 / FLOOD LIGHT ELECTRICAL (NITECH UK)	FLOOD LIGHT LIGHT ELECTRICAL	4 / EACH/IN UMBER			UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM 01424 852788 01424 851008 ACCOUNTS@NITECH.CO. UK WWW.NITECH.CO.UK	UK		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38 9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK GENERAL SPECIFICATION - SOURCE OF AVAILABILITY; UNIT 4-6, HIGHFIELD BUSINESS PARK ST LEONARDS-ON-SEA EAST SUSSEX UNITED KINGDOM TN38	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											9UB 01424 852788 01424 851008 ACCOUNTS@NITECH.CO.UK WWW.NITECH.CO.UK	
4	DNM82614	26438317	291099509739 8 / FUEL INJECTION PUMP	50KVA DG 330T UK	1 / EACH/NUMBER	330T	U48904B	PERKIN ENGINES COMPANY LIMITED FRANK PERKINS WAY PETERBOROUGH CAMBRIDGE PE1 5FO UNITED KINGDOM FAX NO. 1.309.578.7329 EMAIL www.perkins.com/en	UK		TECHNICAL SPECIFICATION - FUEL INJECTION PUMP FITTED WITH 50KVA DG.IPC OF THE SAME IS ENCLOSED <u>GENERAL SPECIFICATION</u> - FUEL INJECTION PUMP FITTED WITH 50KVA DG.IPC OF THE SAME IS ENCLOSED.	
5	DNH82513	OWR-528 / NWD200/Icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/Icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
6	DNO82168	NGO-PAC-IA	421001493489 4 / HOOD, ANTI-FLASH, FIREMENS	DC&FF	75 / EACH/NUMBER			280 CEDAR ST 388 BLACKFOOT, ID 83221-1600, USA	DAWN ENTERPRISES INC.		TECHNICAL SPECIFICATION - NFPA CERTIFIED ANTI-FLASH <u>GENERAL SPECIFICATION</u> - NFPA CERTIFIED ANTI-FLASH	
7	SNM70855	977938	531099551632 6 / FLANGE LOCK NUT	Z DRIVE	20 / EACH/NUMBER	DPH-AB VOLVO PENTA		M/S AB VOLVO PENTA GROPEGARDSGATAN GOTEBORG SWEDEN SE-405 08 GOTEBORG SE-417 15 TEL: +46 31 23 54 60 FAX: +46 31 22 89 37 WWW: HTTPS://WWW.VOLVO.COM/VOLVOPENTA	AB VOLVO SWEDEN		TECHNICAL SPECIFICATION - <u>GENERAL SPECIFICATION</u> - -	
8	DNM81300	3525199	281501509502 9 / HOUSING TUR BEARING	250 KVA CUMMINS DG	1 / EACH/NUMBER	LTA10	23157514	CUMMINS INC.BOX 3005. COLUMBUS INDIANA USA	CUMMINS INC. BOX 3005. COLUMBUS INDIANA USA		TECHNICAL SPECIFICATION - TURBO CHARGER BEARING HOUSING <u>GENERAL SPECIFICATION</u> - TURBO CHARGER BEARING HOUSING	
9	DNO82694	484748 ABN.	473001435510 6 / REPAIR KIT PIPE	EMERGENCY CONTROL PIPE REPAIR	3 / KIT			OEM: IT PIPE REPAIR SYSTEM	INDUMAR PRODUCTS INC		TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			EMERGENCY DAMAGE CONTROL	KIT.				3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	DBA STOP		SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM <u>GENERAL SPECIFICATION</u> - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
10	DNQ803 33	464748 ABN.	473001435510 8 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL . PIPE REPAIR KIT.	3 / KIT			OEM: c IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	INDUMAR PRODUC TS INC DBA STOP		<u>TECHNICAL SPECIFICATION</u> - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM <u>GENERAL SPECIFICATION</u> - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
11	DPC822 30	WD40	803001418900 8 / WD40 (PACKING 440ML SPRAY BOTTLE)		50 / EACH/NUMBER			1061 CUDAHY PL. SAN DIEGO, CA SAN DIEGO CA	WD-40 COMPAN Y		<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> -	
12	DPC826 52	SUVA 410a /HFC- 410a/R- 410a	259071516019 3 / DUPONT REFRIGERAN T R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV- 20100818 L2810 ENGLISH PN:0880269 www. domesticusa.com	DOMESTI C MARINE		<u>TECHNICAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min) <u>GENERAL SPECIFICATION</u> - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											99.9% min)	
13	DPC82839	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
14	DPC82294	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
15	DPC82223	SUVA 410a /HFC-410a/R-410a	259071516019 3 / DUPONT REFRIGERANT R410A	TEMPERED WATER SYS	102.15 / KILOGRAMME	MTD 72 EC	MTD 72 EC	DOMESTIC MARINE REV-20100818 L 2810 ENGLISH PN:0880269 www.domesticusa.com	DOMESTIC MARINE		TECHNICAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)GENERAL SPECIFICATION - AHRI STANDARD 700 OF 2019 Packing: 11.35 kg net disposable cylinder (in oem sealed cylinders with purity level 99.9% min)	
16	DNM77614	233-7231	281579522991 7 / RING GP - PISTON	33KVA CATERPILLER DG DEO33EO UK	3 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G04 236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATTERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SETGENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
17	DNM77611	243-4304	281579522992 5 / PUMP AS - ENGINE OIL	33KVA CATERPILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G04 236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATTERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SETGENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
18	DNM80495	CPMU-17	592578521159 6 / CONTACTOR	6 TON AC AIR COOLED CWFSC-	2 / EACH/NUMBER	NC1-3201 CHINT	NA	NO 1255, WHENE ROAD SONGJIANG DISTRICT SHANGHAI CHINA	CHINT ELECTRIC COY		TECHNICAL SPECIFICATION - 6 TON PACKAGE TYPE AIR COOLED ACGENERAL SPECIFICATION - 6	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3 POLE FOR COMPRESSOR	8+CWCU-108 CHINA					CHINA		TON PACKAGE TYPE AIR COOLED AC	
19	DNM776 16	5185886/3 53-7439	531079522959 1 / KIT-BEARING (STANDARD)	33KVA CATERPILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
20	DNM776 19	275-0885	281579522955 3 / KIT GASKET (BOTTOM)	33KVA CATERPILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
21	DNM794 76	456-4858 / 2740022	281579522954 8 / PUMP GP FUEL INJECTION	33KVA CATERPILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
22	DNM776 15	353-2748	531079522959 5 / KIT-BEARING (STANDARD)	33KVA CATERPILLER DG DEO33EO UK	1 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER U.K		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33EO GENERATOR SET	
23	DNM782 39	252-1466	291001539276 3 / INJECTOR AS FUEL	D/G CATERPILLAR C2.2	4 / EACH/NUMBER		JAW0049 4	USA	CATERPILLAR		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
24	DPC821 37	BIOCIDE-L250	685070522609 7 / BIOCIDE-L250 (CHEMICAL)	WATER COOLED FLOODED SCREW CHILLER PAKISTAN	40 / KILOGRAMME	BIOCIDE-L250	13001002 01709210 00101	SUITE 103, FORTUNE CENTRE, BLOCK-6, P.E.C. H.S., SHAHRAH-E-FAISAL, KARACHI, 75400. TELE: 021-34389923-25 FAX: 021-34389926 URL: w.w.w.arcopk.com E MAIL: rahman@arcopk.com	ARCO CHEMICAL WATER TREATMENT SALES & SERVICE S		TECHNICAL SPECIFICATION - BIOCIDE-L250 MICROBIOLOGICAL CONTROL CHEMICAL USED IN COOLING TOWER OF AC PLANTS. Packing 20 Kg Can. GENERAL SPECIFICATION - BIOCIDE-L250 MICROBIOLOGICAL CONTROL CHEMICAL USED IN COOLING TOWER OF AC PLANTS. Packing 20 Kg Can.	
25	DPC821 38	ARCOBURAG-380	685070522609 5 / ARCOBURAG-380 (CHEMICAL)	WATER COOLED FLOODED SCREW CHILLER PAKISTAN	30 / KILOGRAMME	ARCOBURAG-380	13001002 01709210 00101	SUITE 103, FORTUNE CENTRE, BLOCK-6, P.E.C. H.S., SHAHRAH-E-FAISAL, KARACHI, 75400. TELE: 021-34389923-25 FAX: 021-34389926 URL: w.w.w.arcopk.com E MAIL: rahman@arcopk.com	ARCO CHEMICAL WATER TREATMENT SALES & SERVICE S		TECHNICAL SPECIFICATION - ARCOBURAG-380 CORROSION CONTROL CHEMICAL USED IN CHILLER OF AC PLANTS. GENERAL SPECIFICATION - ARCOBURAG-380 CORROSION CONTROL CHEMICAL USED IN CHILLER OF AC PLANTS.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GE/1 SPECS	Dimension
26	DNH82627	HPU-48CH03	413078515703 4 / A/C 4 TON FLOOR STANDING	4 TON A/C HPU-48CH03	1 / EACH/NUMBER	GF-48TF		HAIER CHINA LOCAL MARKET (TUBA INTER FIRM)	HAIER CHINA		<u>TECHNICAL SPECIFICATION -</u> BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE <u>GENERAL SPECIFICATION -</u> BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HRS SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE	
27	DNM78489	1000152	343971523169 6 / SIPHON PLUG AND NOZZLE RESEAL KIT	16E SPRAY GUN	5 / EACH/NUMBER	16E-H SPRAY GUN	NA	SULZER METCO (US)INC, 1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	SULZER METCO USA		<u>TECHNICAL SPECIFICATION -</u> OEM: SULZER METCO US INC 1101 PROSPECT AVENUE WESTBURY NY 11590 USA MANUFACTURE SULZER METCO <u>GENERAL SPECIFICATION -</u> OEM: SULZER METCO US INC 1101 PROSPECT AVENUE WESTBURY NY 11590 USA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MANUFACTURE SULZER METCO	
28	DNM80441	9510227	599973516148 8 / CORROSION PROTECTION	IPS 500 (PROPULSION & STEERING SYSTEM)	4 / EACH/NUMBER			M/S VOLVO PENTA, GOTEBOG SWEDEN	M/S VOLVO PENTA		TECHNICAL SPECIFICATION - CORROSION PROTECTION GENERAL SPECIFICATION - CORROSION PROTECTION	
29	DNQ82288	08279009	621079517576 2 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	8 / EACH/NUMBER	UK (RFD BEAUFORT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFORT LTD (UK)		TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
30	DNM82640	FF9773	294001523005 3 / Fuel Filter	CUMMINS 200 KVA DG	3 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Toll (1-954) 431-5511 Fax (1-954) 433-5797	USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
31	DNM82626	FF9011	294001523005 0 / Fuel Filter	CUMMINS 200 KVA DG	3 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Toll (1-954) 431-5511 Fax (1-954) 433-5797	USA		TECHNICAL SPECIFICATION - MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE CUMMINS USA	
32	DNM78834	3921265	533001437384 2 / SEAL, OIL	100KVA CUMMINS DG	2 / EACH/NUMBER	4BTA3.9-G4		CUMMINS CUSTOMER ASSISTANCE CENTER 1-800-DIESELS(1-800-343-7357)USA	CUMMINS		TECHNICAL SPECIFICATION - ITEM REQUIRED FOR STOCKGENERAL SPECIFICATION - ITEM REQUIRED FOR STOCK	
33	DNM81571	SM185-4CAM	413073513717 4 / DANFOS COMERCIAL COMP SM185-4CAM 11 TON	MAIN A/C PLANT YORK INTERNATIONAL	1 / EACH/NUMBER	NO DATA AVAILABLE		OC	YORK INTERNATIONAL AUSTRALIA PTY LTD		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
34	DPC82389	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPlEr returnable cylinder with protection		120 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			cap/collar. Each Cylinder containing 5-7 Cum Acetylene									
35	DPC826 51	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
36	DPC822 98	0443- 443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		100 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
37	DPK8212 7	0474-7021 (0475-99- 224-2137)	047450224213 7 / TALLOW WHITE (GREASE) (200 KG DRUM)		12 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DPC822 32		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		13 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
39	DNQ80309	FRP/E3504	0350995713169 / ROPE FIBROUS.	DIVING PANNEL	10 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
40	DNQ82632	FRP/E3504	0350995713169 / ROPE FIBROUS.	DIVING PANNEL	10 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE,	

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
41	DNO80606	FRP/E3504	035099571316 9 / ROPE FIBROUS.	DIVING PANNEL	2 / COIL						<u>TECHNICAL SPECIFICATION -</u> NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION -</u> NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE IDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDO, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
42	DPC82225	NO DATA AVAILABL E	044350224522 7 / GAS ARCTON-12 (FORANE)	STBD MAIN A/C COMPRESSO R	95.2 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
43	DPC82302	NO DATA AVAILABL E	044350224522 7 / GAS ARCTON-12 (FORANE)	STBD MAIN A/C COMPRESSO R	108.8 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
44	DNO75364	NO DATA AVAILABL E	034059923624 3 / BAG CANVAS TOOL		8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5" <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SATCHEL W/WOODEN BOTTOM, CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5								CLOTH CONVAS,(F 8), WATER PROOF, DIA 10.5", DEPTH 1'-9.5"	
45	DPC82517	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
46	DPC82599	NO DATA AVAILABLE	0443504430006 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture,	

S. No	LPR No	PART NO	1/5N / Description	P. Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CU strip corrosion @ 100 oF. UNIT: - psi. oF. Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
47	DPC82571	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - psi. oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - psi. oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1.	
48	DPC82471	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - psi. oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. GENERAL SPECIFICATION - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											, psi, of, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1857, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1,	
49	DNQ77478		026599419526 4 / 6" STAPLE CLAMP		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
50	DNQ80748	DEVELOPED BY DTD	204099787817 3 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
51	DPC82351	LUSTRE EXPORT	047350473013 2 / Electro polishing chemical LUSTRE EXPORT (OEM VANA Corporation Pakistan) (Packing = 650 Grams)		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
52	DNQ81532	00012221	047259425980 7 / LIFE RAFT INFLATABLE COMPLETE SURVIVAL EQUIPMENT 20 MAN(U.K)	LIFE RAFT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NCAGE Information: RFD BEAUFORT LTD BEAUFORT ROAD BIRKENHEAD MERSEYSIDE UNITED KINGDOM CH41 1HQ 9151 0151 653 6639 INFO@RFDBEAUFORT.COM WWW.RFDBEAUFORT.COM GENERAL SPECIFICATION - NCAGE Information: RFD BEAUFORT LTD BEAUFORT ROAD	

S. No	LPR No	PART NO	NSN Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tendr. / Remarks	TECH / GEN SPECS	Dimension
											BIRKENHEAD MERSEYSIDE UNITED KINGDOM CH41 1HQ 9151 0151 853 8639 INFO@RFDBEAUFORT.COM WWW.RFDBEAUFORT.COM	
53	DNM783 66	14.2	301072506967 0 / FLEXIBLE COUPLING HATLAPA L P AIR COMPRESSO R M-12	L P AIR COMPRESSO R	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - HATLAPA GERMANY GENERAL SPECIFICATION - HATLAPA GERMANY	
54	DNM738 85	211	304072509671 4 / PUMP SHAFT	PUMP B6B DISCHARGE HEAD OEM: KSB PUMP CO	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
55	DNM783 67	5N9359 (3040-01- 203-0160)	304071503513 0 / SHAFT, SHOULDERED QA-LG168MM- COLLAR- DIA34.8MM SPLINED ENDED	INDUSTRIEL MARINE CATER PILLER D/G	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended GENERAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended	
56	SNM772 26	4L6473	261571503512 8 / PLATE OD- 90MM-ID- 45MM-THK- 3MM-BRASS		2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4 GENERAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4	
57	DNM795 95	5S5917	261500457161 5 / SCREW		12 / EACH/N UMBER						TECHNICAL SPECIFICATION - MAKE: CATERPILLAR USAGENERAL SPECIFICATION - MAKE: CATERPILLAR USA	
58	DNM826 23	3930942/F S1280	261571510996 6 / FUEL/WATER SEPERATOR FILTER	PROPULSION CUMMINS ENGINE FORSPDB-II 173HP.	2 / EACH/N UMBER	6CT8 3-P					TECHNICAL SPECIFICATION - ENGINE S NO.45225188. RATED HPAT2200 RPM 173HP. GENERAL SPECIFICATION - ENGINE S NO.45225188. RATED HPAT2200 RPM 173HP.	
59	DNM761 82	3930942/F S1280	261571510996 6 / FUEL/WATER	PROPULSION CUMMINS ENGINE	1 / EACH/N UMBER	6CT8 3-P					TECHNICAL SPECIFICATION - ENGINE S NO.45225188. RATED HPAT2200 RPM 173HP.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SEPERATOR FILTER	FORSPDB-II 173HP.							GENERAL SPECIFICATION - ENGINE S NO.45225188, RATED HPAT2200 RPM 173HP.	
60	DNM82077	757-10211	2815725095201 / OIL PRESSURE SENDER	GAUGES & METERS LPWT4,LPA-2	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. OEM/COUNTRY OF ORIGIN/ MANUFACTURE: LISTER PITTER/UK GENERAL SPECIFICATION - A. OEM/COUNTRY OF ORIGIN/ MANUFACTURE: LISTER PITTER/UK	
61	DNM82478	NO DATA AVAILABLE	4610715089590 / WATER FILTRATION SYSTEM MABZI - THREE STAGES		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER) QUANTITY 01 GENERAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER)QUANTITY 01	
62	DNM82284	A/C 1-1/2 TON 03 YEAR GUARANE E	4310731001978 / A/C COMP 50HZ 220-240V 18000BTU 1-PH COPLAND USA 52-68 LRA	A/C 1-1/2 TON	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
63	DNQ77391	M24506-150	4210011310249 / HOSE ASSY N/METL 1.5"X50.COUP BRASS US/STY R/T 180F T, P300PSI		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DNQ82479	en-1566 and imo 1312/med	4210992248369 / afft 6% foam concentrate (packing in 20 lt can)	FOR FIRE FIGHTING EQUIPMENT	10 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DNH82619		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL LG, MITSUBISHI,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SF NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
66	DNH82433	EAC-70/WP-1302	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	8 / EACH/NUMBER	EAC-70/WP-1302					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DNH82512	EAC-70/WP-1302	4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	1 / EACH/NUMBER	EAC-70/WP-1302					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
68	DNH82616	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL WAVES AND DAWLANCE		4 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DNM82653		3230731001865 / BLADE POWER HACKSAW HSS 18X1-1/4X1/16INX6TPI		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE GENERAL SPECIFICATION - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE	
70	DNH82245	9140	4110705041926 / REFRIGERATOR 8CUFT-283 LITERS DOUBLE DOOR 190/230 VOLTS SINGLE PHASE 50HZ	REFRIGERATOR 8CUFT (283LITRES)	1 / EACH/NUMBER	9140					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF. ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WITH OVER LOAD CIRCUIT									
71	DNM77396	NIL	5120705108098 / PIPE CUTTER (PORTABLE)	NIL	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DNO80475	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DNO82367	00779	4730995332961 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM:ALFA LAVAL ENGG. UK	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
74	DNM78373	04.3	5330725069647 / O RING HATLAPA LP AIR COMPRESSOR M-12	HATLAPA LP AIR COMPRESSOR R L-20 GERMANY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
75	DNM78374	04.5	5330725069649 / O RING HATLAPA LP AIR COMPRESSOR M-12	HATLAPA LP AIR COMPRESSOR R L-20 GERMANY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
76	DNM78375	04.9	5330725069653 / O RING HATLAPA LP AIR COMPRESSOR M-12	HATLAPA LP AIR COMPRESSOR R L-20 GERMANY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
77	DNO78556	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
78	DNO82692	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DNO82518	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	DNO80851	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
81	DNO80808	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DNM75316	NO DATA AVAILABLE	0262780001264 / WASHER LOCK 43X62MM	12V130ZC FPB	10 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	80779		8415701004793 / HELMET WITH SAFETY SCREEN		69 / EACH/NUMBER						TECHNICAL SPECIFICATION - specification: Firefighter's (F500CR) Helmets with safety screens (F404/5)/fc-40, size: 8" x 15 1/2" x 1 mm, Make: Cromwell HSL STRANREAR SCOTLAND.del: F 500CR, Manufacturer: Helmet Integrated System Ltd Unit 3, Focus 4 Fourth Avenue Letchworth SG6 2TU United Kingdom. It is Firefighter's helmet built as per European standard of EN443:1997. It ensures individual's protection in firefighting or similar paramedical and emergency rescue situations. GENERAL SPECIFICATION - specification: Firefighter's (F500CR) Helmets with safety screens (F404/5)/fc-40, size: 8" x 15 1/2" x 1 mm, Make: Cromwell HSL STRANREAR SCOTLAND.del: F 500CR, Manufacturer: Helmet Integrated System Ltd Unit 3, Focus 4 Fourth Avenue Letchworth SG6 2TU United Kingdom. It is Firefighter's helmet built as per European	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											standard of EN443:1997. It ensures individual's protection in firefighting or similar paramedical and emergency rescue situations.	
84	DPC81980	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	95.2 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
85	DPC82482	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	95.2 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ether-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	

S. No	LPR No	PART NO	NSI / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6.661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
86	DPC82655	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU.ARGOS-73 RADAR	95.2 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6.661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6.661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
87	DPC823 53	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	95.2 / KILOGRAMME						0) <u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1, 0) 11. Evaporation rate : >1(CCL4=1, 0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1, 0) 11. Evaporation rate : >1(CCL4=1, 0)	
88	DPC825 33	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	95.2 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1, 0) 11. Evaporation rate : >1(CCL4=1, 0) <u>GENERAL SPECIFICATION - 1.</u>	

Sl. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
89	DPC82630	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK507565 8 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU,ARGOS-73 RADAR	95.2 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
90	DPC78877	DUPONT SUVA	6830PK507565 8 /	ACU,ARGOS-73 RADAR	54.4 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		134a / HFA-134a / R-134a	REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)		AMME						colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1,260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0) <u>GENERAL SPECIFICATION - 1.</u> Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1,260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity :1.208 at 25 oC (77 OF) 9. Water solubility :1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
91	DPC822 26	NO DATA AVAILABLE	683070505999 2 / GAS MIXTURE HYDROGEN 2% 98% NITROGEN (PACKING 6.8 CM)	GALIBERATION OF GAS METERS SUBMARINES	20.4 / CUBIC METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DPC822 28	R-502	683070511056 9 / GAS REFRIGRENT R-502 (packing = 13.6kg)	COLD STORAGE & BLASTFREEZER	13.62 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
93	DPC822 29	SUBSTITUTE OF GAS FREON-12	683070504911 4 / GAS FORANE 134A DIHYDRO TETRA FLUORO		95.2 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	Pr Equipment	QTY DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ETHANE C2H2F4									
94	DNM820 95	7139-540	291089829433 9 / LINER, TRANSFER PUMP	FUEL INJECTION PUMP	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
95	DPC821 35		047354600470 3 / SODA CAUSTIC (PACKING 25 KG)		200 / KILOGR AMME						TECHNICAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments GENERAL SPECIFICATION - Soda Caustic (chemical nomenclature SODIUM HYDROOXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance: Colourless, odourless liquid free of sediments	
96	DNM794 92	EOCR	599976512645 4 / ELECTRONIC OVER LOAD I/P 220V 6A (GREEN POWER)	AIR COND SYS CWM- 2C70-PN JAPAN	6 / EACH/N UMBER	CWM- 2C70-PN FUJI JAPAN					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DNM803 65	HD 6/15 m	791072511890 4 / KARCHER COLD WATER HIGH PRESSURE CLEANER WITH		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - 220- 440V/ 60Hz GENERAL SPECIFICATION - 220-440V/ 60Hz	
98	DNM783 77	04.11	533172512106 9 / O RING 62X3	DIESEL DRIVEN COMPRESSO R W-30	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - Make: HATLAPA GmbH & parent equipment Co (Germany) (W30/40) Two Stages Water Cooled Air	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Compressor WP 30 Bar GENERAL SPECIFICATION - Make: HATLAPA GmbH & parent equipment Co (Germany) (W30/40) Two Stages Water Cooled Air Compressor WP 30 Bar	
99	DNM81721	MDR2/6	5930725128023 / LP HP SWITCH FOR FRESH WATER SERVICE PUMP (F8)	CONTROLLER	3 / EACH/NUMBER	CONDOR MDR 2/6					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	SNM70431	277-2923/6194764	5330015877967 / gasket		5 / EACH/NUMBER	C7-1502-117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
101	DNM81575	5402699	2930795264354 / PUMP WATER		1 / EACH/NUMBER	6CPAA8.3G7					TECHNICAL SPECIFICATION - PUMP WATER GENERAL SPECIFICATION - PUMP WATER	
102	DNO67727	887665	4810725293140 / VALVE B0481-B DN49 WITH INTEGRATED ELECTRICAL RELEASE MX 1230/200		1 / EACH/NUMBER	B0481-B					TECHNICAL SPECIFICATION - WORKING PRESSURE AT 21 DEGREE CENTIGRADE (69.8 F) 50 BAR (725 PSI). WEIGHT APPROX: 9.3 KG (20.5 BAR) GENERAL SPECIFICATION - WORKING PRESSURE AT 21 DEGREE CENTIGRADE (69.8 F) 50 BAR (725 PSI). WEIGHT APPROX: 9.3 KG (20.5 BAR)	
103	DNM76591	238-5081	5331715270242 / SEAL O RING FOR TURBO LINE		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - SEAL O RING FOR TURBO LINE GENERAL SPECIFICATION - SEAL O RING FOR TURBO LINE	
104	DNM82011	4854895/354-4754	4310705240165 / KIT WATER PUMP (KIT INCLUDING GASKET AND PUMP GP)		1 / EACH/NUMBER	C7-1502-117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
105	DNM80838	370-4617	6150016008656 / CABLE		1 / EACH/NUMBER	DE-660EO					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ASSEMBLY (USB)		UMBER	CATERPILLAR GENERATOR C18 600 KVA /480KW					null	
106	DNM76104	29010561	471073528147 4 / HYDRAULIC PIPE L=247		2 / EACH/NUMBER	KESLA 204T					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
107	DNM80461	5P-7277	662501594433 1 / VOLTAGE TESTER		4 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
108	DNM76520	4327370 / ts38280	294078528080 4 / fuel water separator		3 / EACH/NUMBER	qs213-g5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
109	DNM72000	1249601	533072531802 3 / sealing system cpl		1 / EACH/NUMBER	1249601					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
110	DNM82636	2645K016	291099903382 1 / INJECTOR		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
111	DNM71680	5240335602	312012378785 8 / CRANKSHAFT BEARING, ORTZ C/N 02, (POSITION NR 030134)		46 / BOX	16V4000 M70 MTU					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
112	DNO79080	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gomtex lg 100 ft id 2"		3 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMTEX X LG 100 FT ID 2"					TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN, LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE, oem/country of origin GOMTEX/ usa GENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL. HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
113	DNM79084	309-8037	254012125187 5 / BELT TENSIONER GP (FAN)		3 / EACH/NUMBER	cat c18					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
114	DNM76904	3094496	281571532749 1 / Aftercooler		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - 0 GENERAL SPECIFICATION - 0	
115	DNM78165	320-3064	662001706500 2 / SENSOR PRESSURE ENGINE OIL		1 / EACH/NUMBER	DE033EO					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
116	DNM76522	AF26433	294079528072 1 / AIR FILTER ELEMENT PRIMARY		2 / EACH/NUMBER	QSZ13-G5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
117	DNO82541	00-54007-96954-7	424071526961 2 / 3m gloves general use		20 / EACH/NUMBER	nil					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
118	DSB82281	246343	254078517235 8 / PORTABLE BLOWER VENTILATOR 12 INCH		5 / EACH/NUMBER	pvt-12 / PVT-30					TECHNICAL SPECIFICATION - Structure : Aluminum Alloy Shell - Good heat dispersion and low weight Number of Blades: 7 blades Blade: Aluminum Alloy Drive Type: Motor Drive Bearing: Adopts High Quality bearing and durable using Motor: High Efficient and special made motor ducting Size: 300 mm material: steel Power (w): 360 watts: 305w rmp low: 2308 Cm3 rpm High: 2800-2900 rmp Voltage: 220v-240v phase: single phase Air Volume (m³/Hour): 3400 Pressure (Pa): 350 Noise dB (A): 80 decibels: 71 db fan diameter: portable blower ventilator 12 inch Safety Guard: Both front side and rear side is installed MAKE: Deton CHINA Brand Equipement: msm china GENERAL SPECIFICATION - Structure : Aluminum Alloy Shell - Good heat dispersion and low weight	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Number of Blades: 7 blades Blade: Aluminum Alloy Drive Type: Motor Drive Bearing: Adopts High Quality bearing and durable using Motor: High Efficient and special made motor ducting Size: 300 mm material: steel Power (w): 380 watts: 305w rmp low: 2308 Cm3 rpm High: 2800-2900 rmp Voltage: 220v-240v phase: single phase Air Volume (m³/Hour): 3400 Pressure (Pa): 350 Noise dB (A): 80 decibels: 71 db fan diameter: portable blower ventilator 12 inch Safety Guard: Both front side and rear side is installed MAKE: Deton CHINA Brand Equipment: msm china	
119	DRG82315	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
120	DSB81151	PWR-RGD-AC-DC-H	613001651479 9 / IUCCS Network switch power supply		1 / EACH/NUMBER	PWR-RGD-AC-DC-H					TECHNICAL SPECIFICATION - Cisco IE-4010 Gigabit Switch 16 SFP-slots and 12 Gigabit Ethernet ports (RJ45) 16 SFP modules (electrical RJ45 Gigabit ports or fibre optic Gigabit ports) cisco ie-4010 power supply GENERAL SPECIFICATION - Cisco IE-4010 Gigabit Switch 16 SFP-slots and 12 Gigabit Ethernet ports (RJ45) 16 SFP modules (electrical RJ45 Gigabit ports or fibre optic Gigabit ports) cisco ie-4010 power supply	
121	DSB79998	30033529	596174520325 6 / CONDENSATOR 29014L11U32F		14 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	SGB73926	NO DATA AVAILABLE	021270571003 0 / STEEL-BAR-CARBON-RD-DIA-5-	SPECIFICATION BS970 GRADE EN4	3 / METER						TECHNICAL SPECIFICATION - BS970 GRADE EN4 GENERAL SPECIFICATION - BS970 GRADE EN4	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INCH BS970 GRADE EN4									
123	DRG82452	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
124	DSB67067	TAG-700 AIR ANGLE GRINDER/ NKS - NK2261G1	009908607296 7 / PNEUMATIC ANGLE GRINDER KL/12 OR 700NA		9 / EACH/NUMBER	tag-700 qll/NK2261G1					TECHNICAL SPECIFICATION - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2" GENERAL SPECIFICATION - Wheel Size 180 mm Free Speed 8400 rpm Net Weight 2.9 Kg Overall Length 252 mm Air Cons 1.30 m3/min Air Inlet 3/8" Hose Size 1/2"	
125	DNV76492		534070529317 7 / Union Adapter Type With Ferrule for Pipe 1 1/4" (ID 32 X OD 40 MM)		6 / EACH/NUMBER	WP 3232 AIR COOLED COMPRESSOR					TECHNICAL SPECIFICATION - UNION ADAPTER TYPE WITH FERRULE FOR PIPE 1 1/4" (ID 32 X OD 40 MM) GENERAL SPECIFICATION - UNION ADAPTER TYPE WITH FERRULE FOR PIPE 1 1/4" (ID 32 X OD 40 MM)	
126	DSB82242		5340TY673002 5 / TWINE ROLL		103 / ROLL	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - a. Cotton 12 yarn per strand 04. b. Item available in local market GENERAL SPECIFICATION - a. Cotton 12 yarn per strand 04. b. Item available in local market	
127	DRG82310	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
128	DSB74842	5330BA27-8X3-6-20A8	533014313548 9 / JOINT TORIQUE 27.8 X3,6-20A8		148 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DRG82508	315/70 R 15 TL (300 R 15)	261012400272 4 / TYRE TUBELESS		1 / EACH/NUMBER	CONTINENTAL					TECHNICAL SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR GENERAL	

S No	LPR No	PART NO	NSN / Description	P/Equipment	CTY / DENG	Model	SR NO OF PR	MANUF ADU	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE 315/70 R 15 TL (300 R 15) 22PR								SPECIFICATION - TYRE TUBELESS SIZE 315/70 R 15 TL (300 R 15) 22PR	
130	DSB82250		009908607292 5 / FRAISE- ATRAX (STEEL RIMER)		43 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop. GENERAL SPECIFICATION - Make/ Model: Size: Taper From 31 to 5 mm Mandrel Size : 40 MM Mandrel Dia : 6 MM Stock sample: Sample enclosed (upload) Acceptance Criteria: Concerned rep will inspect and practically test in workshop.	
131	DSB82248	E27411A1 000QVTL/ 0310 10	531014299910 7 / NUT 10MM		660 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - TECHNICAL SPECIFICATIONS: a. DIA: 10MM GENERAL SPECIFICATION - TECHNICAL SPECIFICATIONS: a. DIA: 10MM	
132	DNV76491		471070530063 3 / Pipe 1 1/4" (ID 32 X OD 40 MM)		2 / MTR	WP-3232 JP SAUER					TECHNICAL SPECIFICATION - Pipe 1 1/4" (ID 32 X OD 40 MM) GENERAL SPECIFICATION - Pipe 1 1/4" (ID 32 X OD 40 MM)	
133	DRG68525	1250	2940Z0522499 1 / AIR FILTER FOR AIR CENTER		1 / EACH/NUMBER	KAESER SXC 9.6916 03 E					TECHNICAL SPECIFICATION - a. Item Name Air Filter b. Parent Equipment KAESER SXC 4 Air Center c. Parent Assembly Air Filter Housing d. Manufacturer KAESER KOMPRESSOREN (Germany) e. Installed Quantity 01 f. Interval Of Replacement 3000Hrs g. Part Number 1250 h. NSN/ ZO ZO5224991 i. Picture Attached j. Technical Specification Attached k. Publication Attached GENERAL SPECIFICATION - a. Item Name Air Filter b. Parent Equipment KAESER SXC 4 Air Center c. Parent Assembly Air Filter Housing d. Manufacturer KAESER KOMPRESSOREN (Germany) e. Installed Quantity 01 f. Interval Of Replacement 3000Hrs g.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Part Number 1250 h. NSN/ ZO 5224991 i. Picture Attached j. Technical Specification Attached k. Publication Attached	
134	DSB81722	23TT4A	5990142081178 / SYNCHRO TRANSMET 23 TT 4.		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
135	DNH82754	NO DATA AVAILABLE	1308546012246 / DEEP FREEZER 12 CUFT 220 V AC PEL		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DNQ82755	DEVELOPED BY DTD	2040997878173 / DAMAGE REPAIR CLIMP STEEL BS 4360 LG 403 WD190 H60 6.5MM DIA		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber. GENERAL SPECIFICATION - EMMS Clamps are mild steel clamps used for shoring during Damage Control., General dimension of the clamp is 190mm x 403 mm used to support shoring spar of 150 mm timber.	
137	DNQ82752		0265994195264 / 6" STAPLE CLAMP		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
138	DNQ82753	FRP/E3S04	0350995713169 / ROPE FIBROUS.	DIVING PANNEL	2 / COIL						TECHNICAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMPTON, PLYMOUTH DEVON UNITED KINGDOM, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.myatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NCAGE: U4207 M/S SURVITEC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENG	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SERVICE & DISTRIBUTION LIMITED, DEFENCE SALES DEPARTMENT, UNIT 1 MEADOW CLOSE INDUSTRIAL ESTATE, PLYMTON, PLYMOUTH DEVON UNITED KINGDOM, PL7 5EX TEL 01752 697314, FAX 01752 335475 EMA alan.miyatt@survitec-sd.com WWW www.survitec-sd.com ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
139	DPC80152	NO DATA AVAILABLE	0473500005370 / SILICA GEL (grain size 2-3mm)	Transformers Humidity Control	40 / KILOGRAMME						TECHNICAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up. GENERAL SPECIFICATION - Silica Gel (Desiccant) in grain form for transformers Humidity Control. Grain size 2-3mm square. Capable to absorb moisture at room temperature and release moisture when heated up.	
140	DNH82758	NIL	4120735139117 / AIR CONDITIONER SPLIT 1.5 TONS	AIR CONDITIONING	2 / EACH/NUMBER	NO DATA AVAILABLE		OC		THAILAND	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
141	DNM77254	3584427	4820270382248 / PRESSURE RETAINING V (FUEL SYSTEM)	(FUEL SYSTEM)	1 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN		VALVO PENTA SWEDEN	TECHNICAL SPECIFICATION - PRESSURE RETAINING V (FUEL SYSTEM) GENERAL SPECIFICATION - PRESSURE RETAINING V (FUEL SYSTEM)	
142	DNM77255	885502	2815795149071 / COPPER SLEEVE EXTRACTOR	VOLVO MAIN ENGINE D6-370	1 / EACH/NUMBER	NO DATA AVAILABLE		UK		VOLVO PENTA UK LTD OTTERS POOL HOUSE, OTTERS POOL WAY WATFORD HERTS	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									UNITED KINGDOM WD2 HW8 01923 228544 01923 246700 VP. UK@MEMO. VOLVO. SE			
143	DNM78552	3931062/3 286503/FS 1251	291001502653 9 / FUEL FILTER WATER SEPERATOR	CUMMINS (6BT5.9D2(M)).	4 / EACH/NUMBER	6BT5.9D2 (M).	22066008	M/S CUMMINS INS CATENBERGSTRAAT 1-2840 RUMST BELGIUM	CUMMINS UK		TECHNICAL SPECIFICATION - Fuel Filter Water Separator (FS1251) 250 KVA 361 AMP/ Phase 400 Volts 50 HZ 0.8 Power Factor 1500 RPM Filter used in 250 KVA (Model C275D5B) Cummins DGGENERAL SPECIFICATION - Fuel Filter Water Separator (FS1251) 250 KVA 361 AMP/ Phase 400 Volts 50 HZ 0.8 Power Factor 1500 RPM Filter used in 250 KVA (Model C275D5B) Cummins DG	
144	DNQ62760	464748 ABN.	473001435510 6 / REPAIR KIT,PIPE, EMERGENCY DAMAGE CONTROL	EMERGENCY CONTROL PIPE REPAIR KIT.	2 / KIT			OEM: IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	INDUMAR PRODUCTS INC DBA STOP		TECHNICAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM GENERAL SPECIFICATION - OEM: INDUMAR PRODUCTS INC DBA STOP IT PIPE REPAIR SYSTEM 3355 WEST ALABAMA ST STE 110 HOUSTON TX UNITED STATES 77098-1799 713-977-4100 713-977-4174 DUNS 161788682 DON@INDUMAR.COM HTTP://WWW.STOPIT.COM	
145	DNM78552	3931062/3 286503/FS 1251	291001502653 9 / FUEL FILTER	CUMMINS (6BT5.9D2(M)).	4 / EACH/NUMBER	6BT5.9D2 (M).		OEM: CUMMINS INC. 500 JACKSON ST	CUMMINS INC.		TECHNICAL SPECIFICATION - Fuel Filter Water Separator (FS1251) 250 KVA 361 AMP/ Phase 400 Volts 50	

S. No	LPR No	PART NO	NCN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Te:icer Remarks	TECH / GEN SPECS	Dimension
			WATER SEPERATOR					COLUMBUS IN UNITED STATES 47201-6258 812-377-3920 812-377-1715 DUNS 008415160 STEVE A. HEWITT@CUMMINS.COM			HZ 0.8 Power Factor 1500 RPM Filter used in 250 KVA (Model C275D5B) Cummins DGGENERAL SPECIFICATION - Fuel Filter Water Separator (FS1251) 250 KVA 381 AMP/ Phase 400 Volts 50 HZ 0.8 Power Factor 1500 RPM Filter used in 250 KVA (Model C275D5B) Cummins DG	
146	DNH82775	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENSER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENSER	
147	DNH75021	mk-2015-e-7039	414070526318 3 / exhaust fan 230vac w2e		2 / EACH/NUMBER	w2e200					TECHNICAL SPECIFICATION - 1. sPECIFICATION: a. Input supply: (230+-10 VAC) B. PARENT EQUIPMENT BATTERY CHARGING RECTIFIER: 1000 AMP 500 VDCGENERAL SPECIFICATION - 1. sPECIFICATION: a. Input supply: (230+-10 VAC) B. PARENT EQUIPMENT BATTERY CHARGING RECTIFIER: 1000 AMP 500 VDC	
148	DNM78793	MS4SA-AP / MS4SA	664576512644 8 / STAR DELAY TIMER I/P 110-240VAC	AIR COND SYS	10 / EACH/NUMBER	CWM-2C70-PN FUJI JAPAN					TECHNICAL SPECIFICATION - Input: 100-240VAC 50/60Hz Time: 0.05s-60hGENERAL SPECIFICATION - Input: 100-240VAC 50/60Hz Time: 0.05s-60h	
149	DNM77411		6685US508084 7 / GAS CHARGING SET LOW SIDE 0 TO 250PSI HIGH SIDE 0 TO 500PSI		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
150	DNQ82762	11/454/3/10/2745	533099923890 5 / STRIP RUBBER SHEET	4.5" MK-8 GUN	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DNH82776		411073500716 0 / DEEP		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FREEZER 10 CUFT 220V AC SINGLE PHASE		UMBER						SPECIFICATION - NO DATA AVAILABLE	
152	DNH82757		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
153	DNO82846	11/454/3/10/2745	5330999238905 / STRIP RUBBER SHEET	4.5" MK-8 GUN	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	SNM70219	CV20948	2815795091215 / AIR FILTER ELEMENT	D/G INTER POWER (UK) 3012TAGIA	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	SNM75754	6N7174	2815011834649 / SHIELD OIL (SEAL VALVE GUIDE)	DG	48 / EACH/NUMBER			ALLIED ENGINEERING KORANGI SITE	USA		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DPC82857	DUPONT SUVA 134a / HFA-134a / R-134a	6830PK5075658 / REFRIGERANT GAS ACU R-134A (packing = 13.6kg) (Purity level 99.9%)	ACU, ARGOS-73 RADAR	95.2 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA pour Pressure : 6,661 hpa at 25 oC (77 OF) : 13,190 hpa at 50 oC (122 OF) 7. Density : 1,260 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1,208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1,013 hpa 10. VA pour density : 306 at 25 oC (77 OF) (Air=1,0) 11. Evaporation rate : >1(CCL4=1,0) GENERAL SPECIFICATION - 1. Form : Liquefied gas 2 Color : colorless 3. Odor : slight, ethe-Like 4. Boiling Point : -26.1 OC (-150 OF) at 1,013 hpa 5. %Volatile : 100% 6. VA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											pour Pressure : 6.861 hpa at 25 oC (77 OF) : 13,190 h pa at 50 oC (122 OF) 7. Density : 1.280 g/cm3 at 25 oC (77 OF) (as liquid) 8. Specific gravity : 1.208 at 25 oC (77 OF) 9. Water solubility : 1.5 g/l at 25 oC (77 OF) at 1.013 hpa 10. VA pour: density: 306 at 25 oC (77 OF) (Air=1.0) 11. Evaporation rate : >1(CCL4=1.0)	
157	DNM79599	PW1700X/BXPW1700E	494073513792 2 / HIGH PRESSURE WATER JET WASHING MACHINE	JET WASHING	2 / EACH/NUMBER	NO DATA AVAILABLE		TY		BLACK AND DECKER	<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
158	DPC77692	SIKAFLEX-290	803079516762 1 / SIKAFLEX 290 DC WOODEN DECK CAULKING 300ML OR 800ML CARTDG	PRIMER-290DC	11 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129		SIKA LIMITED	<u>TECHNICAL SPECIFICATION -</u> ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129 <u>GENERAL SPECIFICATION -</u> ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather-resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
159	DNH82931		130854601108 1 / REFRIGERATOR 10 CU FT-220V AC (NO FROST)		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
160	DNM82841	98262.1009	294599827575 6 / OIL FILTER	COMPRESSOR 5415	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL SPECIFICATION -</u> NO DATA AVAILABLE	
161	DPK81077		047450910052 4 / GREASE NAVAL	XG-460	65 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> <u>TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =</u> FIBROUS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GRAPHITE XG-460 3 KG PACK								GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) = 400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST = 34 FOUR BALL (IP 239) WELD LOAD KGS = 315 TIMKEN OK LOAD IBS = 45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460) <u>GENERAL SPECIFICATION -</u> TECHNICAL DATA (TYPICAL VALUES) APPEARANCE = FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) = 400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST = 34 FOUR BALL (IP 239) WELD LOAD KGS = 315 TIMKEN OK LOAD IBS = 45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)	
162	DPC827 02	NO DATA AVAILABL E	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated. Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 ft3, NIL, 1. <u>GENERAL SPECIFICATION -</u> CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated. Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum):	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Report, 208, 40 OF, 15 Grains/100 #3, NIL, 1.	
163	DNH82868	OWR-528 / NWD200/Icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only (WITH 19 LTR BOTTLE)	WATER DISPENSER	1 / EACH/NUMBER	OWR-528/Icon-2 (orient)	OWR-528	ORIENT WATER DISPENSER PAKISTAN	ORIENT		<u>TECHNICAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER <u>GENERAL SPECIFICATION</u> - white colour only NASGAS WATER DISPENSER	
164	DPC82739	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1362 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 #3, NIL, 1. <u>GENERAL SPECIFICATION</u> - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 #3, NIL, 1.	
165	DPC82834	NO DATA AVAILABLE	044350443000 6 / GAS COOKING (weight 40 to 50 KGs)		1589 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96% evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF, UNIT: - , psi, oF, Grains/100 cubic ft3, ppm, rating, METHOD ASTM/IP: D-1657, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF, 15 Grains/100 #3, NIL, 1. <u>GENERAL SPECIFICATION</u> - CHARACTERISTICS: SP Gravity @ 60/60 oF, R.V.P. @ 100 OF, 96%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											evaporated, Sulphur Total, Moisture, CU strip corrosion @ 100 oF. UNIT: - . psi, oF, Grains/100 cubic ft3, ppm, rating. METHOD ASTM/IP: D-1857, D-1267, D-1837, D-7551, NGPA, D-1838, SPECIFICATION (Maximum): Report, 208, 40 OF. 15 Grains/100 ft3, NIL, 1.	
166	DPC827 17	NO DATA AVAILABLE	044370505488 4 / GAS COOKING BURSHANE IN FIRM RETURNABLE CYLINDER OF 45.40 KG		1362 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DPC828 38	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
168	DPC827 42	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-IGENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
169	DPC827	0443-	044350224043		138 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	03	443003	9 / GAS ACETYLENE TECHNICAL (98.6% Purity) in buyer/supplier returnable cylinder with protection cap/collar. Each Cylinder containing 5-7 Cum Acetylene		CUBIC METER						CGA G1.1 OF 1990 GRADE-H OF TABLE-I GENERAL SPECIFICATION CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
170	DNH82930	MODEL NO-SS-60P (STEEL)	4110705057701 / WATER COOLER 60 LTR STORAGE TYPE 220V50HZ SINGLE PHASE	USER SIM DIV PNS DOCKYARD	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
171	SNM75697	NO13MU022	5330775137102 / MECHANICAL SEAL P58	STERLING /FIRE MAIN	2 / EACH/NUMBER	NO DATA AVAILABLE		NL	STERLING FLUID SYSTEM NETHERLAND		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
172	DNH82843	NO DATA AVAILABLE	4110731001910 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/FRONT STEELBODY	WATER COOLER	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
173	DNH82842		4110705111571 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	8 / EACH/NUMBER	WA60000514					TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											100 W	
174	DNH829 28	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
175	DNH828 92	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABLE TOILET		TECHNICAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with Falsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure GENERAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with Falsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS	

S. No	LPR No	PART NO	1:SN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system L. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan. Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure	
178	DSB71806	23TR4A	599000822545 1 / SYNCHRO RECEIVER ROTOR I/P- 115V 400HZ 7.8 WATT SIZE 23	MK73MOD1. INDICATOR. RECOMMENDED COURSE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MIL-S-20708-94</u> <u>GENERAL SPECIFICATION - MIL-S-20708-94</u>	

MEMORANDUM HOW THE TOTAL OF A CHEQUE IS MADE UP (CHEQUE SLIP)

Auth Sec III Para 80 Sub Para (iii) Office Manual Part-III

1276

Pakistan Military Accountst DepartmentOffice of the CNA Karachi No & Date Of cheque _____ Serial No Of Cheque slip _____

In Payment Of bill No:- 2 dt 07/03/2025

180000.00

Bank A/c No PK17HABB0004540013100701

180000.00

In Words Rs ONE HUNDRED EIGHTY THOUSAND

For CNA

(Signature of Offr Signing the cheque)

Initial

Supdt Audit Sec

Initial

Officer O/C Audit Sec

HBL 'A' BLOCK BRANCH PAK SECRETARIAT, ISLAMABAD ISLAMABAD

To

P.P.R.A

PPRA 1st Floor FBC Building, Near State Bank Sector G-5/2, Islamabad

Copy To

LP Division

2. LAO (LAO (NAVY) NSD KARACHI)