

TENDER BULLETIN

DATE & TIME 5/22/24 12:03 PM INVITATION TO TENDER TO BE OPENED ON 6/5/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF58857	KNK-5002-E18	6630735216283 / CAPILARY INJECTOR W/EPC	HRGC 5000B KNK-5002-E18 SPAIN	1 / EACH/NUMBER	KNK-5002-E18	NIL	S.A Av.Cerdanyola, 73,08172 Sant Cugat, Barcelona, Spain Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com	KONIK-TECH		<u>TECHNICAL SPECIFICATION - S.A Av.Cerdanyola,73,08172 Sant Cugat, Barcelona, Spain</u> Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com <u>GENERAL SPECIFICATION - S.A Av. Cerdanyola,73,08172 Sant Cugat, Barcelona, Spain</u> Phone (34) 93.590-28.40 FAX (34) 93.590-28.44 E.MAIL sat@konik-group.com	
2	DGP53089	NHQ APPROVED MODEL	7535705133021 / LAPTOP COMPUTER AS PER NHQ APPROVED MODEL (HP/DELL/LENOVO)	COMPUTER	1 / EACH/NUMBER	NO DATA AVAILAB LE		PK	VIDE NHQ LETTER ST-S/3200/8198 DT 23/07/08		<u>TECHNICAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION</u> 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ)). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION). <u>GENERAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION</u> 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ)). 2. SYSTEM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION).	
3	DNF60622	J9776A / J9772A+j4 859c	5895785207833 / NETWORK SWITCH HP 2530 24G/48G WITH SFP MODULES	NETWORK SWITCH J9772A CHINA	1 / EACH/NUMBER	R8N88A/J9776A/J9772A	NA	HP INC C/O INVENTEE (CHONGGING) CORP. NO. 66 WEST DISTRICT 2ND ROAD SHAPINGBA DISTRICT CHONGGING 401331 CHINA	HP CHINA		<u>TECHNICAL SPECIFICATION - ATTACHED GENERAL SPECIFICATION - ATTACHED</u>	
4	SNM47243	MPU 120	2815705216300 / MPU	SSDG	5 / EACH/NUMBER	MPU 120		M/S SCENARIO INTERNATIONAL, KARACHI PH NO 0324-2636007	LOCAL		<u>TECHNICAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER</u> <u>GENERAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER</u>	
5	SNF57086	7429766	5930735218570 / PRESSURE SWITCH	Azimuth Thruster	1 / EACH/NUMBER	7429766	66925,669226	Rolls Royce OY Ab PO BOX 220, FIN-26101 Roma Finland Phone + 358283791. FAX NO + 358283794804 Azimuth Thruster/Propulsion Aftermarket Fax + 358283794804 Home Page: ww.rolls ? Royce. com	Rolls Royce OY Ab, Rauma, Finland		<u>TECHNICAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.</u> <u>GENERAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.</u>	
6	DGP61488	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED)</p> <p>GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
7	DGB53948		4730002572163 / TEE EQUAL Dia 1/4 inch		10 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62</p> <p><u>GENERAL SPECIFICATION</u> - Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62</p>	
8	DRP292	011-	8040ZO520308		36 /	SCANEA					<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	90	110031-000	9 / TAPE, FILM, KAPTON SILICONE, ADHESIVE		EACH/NUMBER	GLE					<u>GENERAL SPECIFICATION -</u>	
9	DNF60951	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		5 / EACH/NUMBER	NA				PICTURE Attached	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
10	DNF61083	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		8 / EACH/NUMBER	NA				PICTURE ATTACHED	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
11	DGP56251	NO DATA AVAILABLE	057559002492 3 / TP ROLL 3PLY WHITE P-P 60GSM5% +-W 8.25	TELEPRINTER	524 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
12	DNC57923	884408A08	4810MB002038 5 / VALVE KIT CONTROL - ELECTRIC BOOST	PETROL MAIN ENGINE	1 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - VALVE KIT CONTROL - ELECTRIC BOOST</u> <u>GENERAL SPECIFICATION - VALVE KIT CONTROL - ELECTRIC BOOST</u>	
13	DNC57921	898907	4810MB002051 0 / VALVE INTAKE	PETROL MAIN ENGINE	12 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - VALVE INTAKE</u> <u>GENERAL SPECIFICATION - VALVE INTAKE</u>	
14	DNC57922	898908T01	4810MB002051 1 / VALVE EXHAUST-CHROME	PETROL MAIN ENGINE	12 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - VALVE EXHAUST-CHROME</u> <u>GENERAL SPECIFICATION - VALVE EXHAUST-CHROME</u>	
15	DNC57924	896880/8M0214986	5330MB002051 2 / SEAL VALVE	PETROL MAIN ENGINE	24 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - SEAL VALVE</u> <u>GENERAL SPECIFICATION - SEAL VALVE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
16	SNM45551	8159975-5	291033204861 1 / FUEL FILTER AND WATER SEPARATOR	DG VOLVO PENTA 210KVA	2 / EACH/NUMBER	NO DATA AVAILAB LE		FR	SIEMEN PAKISTA N ENGINEE RING CO LTD AUTOMA TION&DR IVE DIVISION BU SMALL&L ARGE B-72ESTAT E AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700		<u>TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTAGENERAL SPECIFICATION -OEM & MAKE: VOLVO PENTA</u>	
17	SNM56792	0103-100002	668572515686 4 / PRESSURE GAUGE STAGE 2 (0-25 BAR)	ALPINE HP COMPRESSO R	1 / EACH/NUMBER	0103-100002		GERMANY ALPINE INDUSTRIAICON (PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674	GERMAN Y		<u>TECHNICAL SPECIFICATION - OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674</u> <u>GENERAL SPECIFICATION - OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674</u>	
18	DGT62010	NIL	551070519913 4 / KAIL WOOD SLEEPER	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GRADE-A (LOCAL)								6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18% <u>GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%</u>	
19	DNM61100	3808093	4720270382129 / HOSE (HEAT EXCHANGER AND EXPANSION TANK)	HEAT EXCHANGER	1 / UNIT	D6-370D-E		AB VALVO PENTA SE 40508 GOTHEN BURG SWEDEN		SWEDEN	<u>TECHNICAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA</u> <u>GENERAL SPECIFICATION - HOSE (HEAT EXCHANGER AND EXPANSION TANK) OEM: VALVO PENTA</u>	
20	DPK56026	HA5430H	9150735164284 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858		TELEFLEX MARINE CANADA	<u>TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858</u> <u>GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858</u>	
21	DGP63618	MODEL NO. LA40A550 P1	7730705133301 / TV SAMSUNG LCD 40" INCH	SAMSUNG	1 / EACH/NUMBER	NO DATA AVAILABLE		PK		PAKISTAN	<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
22	DNM62711	3803851	4310735179263 / COMPRESSOR, EXCH (COMPRESSOR)	VOLVO PENTA	1 / EACH/NUMBER	D6-370D-E		AB VOLVO PENTA SE40508 GOTHENBURG SWEDEN		VOLVO PENTA	<u>TECHNICAL SPECIFICATION - COMPRESSOR, EXCH (COMPRESSOR)</u> <u>GENERAL SPECIFICATION - COMPRESSOR, EXCH (COMPRESSOR)</u>	
23	DGP63616	HP Scanner	7490705218483 / HP	HP SERVER Pro 2500 F1	1 / EACH/NUMBER	HP Scanner	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA		HP	<u>TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		20G05A/L2 747A	SCANNER PRO 2500 F1 FLATBED		UMBER	20G05A/P ro 2500 F1		4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441			SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 <u>GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297</u>	
24	DNG546 19	95602.152	533101415908 4 / O RING	MAIN AIR COMPRESSO R	2 / EACH/N UMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD. REAVELL 53-56 WHITE HOUSE ROAD IPSWICH ENGLAN D IPI 5PB		<u>TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .</u>	
25	DNZ5589 7	95602.140	533101415911 8 / O RING	MAIN AIR COMPRESSO R	6 / EACH/N UMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
26	SNM567 35	214-7568	533101513521 0 / SEAL O RING	MAIN ENGINE	64 / EACH/N UMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPI LLAR		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183- 632189</u>	
27	DNF6299 8	eos 7d slr / eos 250d slr	671076515845 3 / Digital	CAMERA DIGITAL CANON EOS-	1 / EACH/N UMBER			SOURCE OF AVALIBILITY: CANON LINK 15,HAKEEM CENTER SADDAR KCI	CANON LINK 15, HAKEEM		<u>TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			STILL Camera Canon eos 7d slr / 250 D along with Flash Gun canon 580exii / V860 III (GODOX)	7D					CENTER SADDAR KCI		null	
28	DGT63348	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	6000 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required</u>	
29	DGT63231	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	6000 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required</u>	
30	DNF47660	BRAPDU-C001	7125735223890 / RACK, PDU, Cables	C Band DVBS	1 / EACH/N UMBER	BayLan		M/S NSSL Technopolis building ROLFSBUKTVEIEN 4B, 1364 FORNEBU OSOLO NORWAY	M/S NSSL .		TECHNICAL SPECIFICATION - ζ PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ζ Single phase 220-240AV 50-60 Hz. ζ Maximum load 16 Amp/7840 Watts. <u>GENERAL SPECIFICATION - ζ PDU19" RM 1U 7 Way Multi Extension socket type Power Distribution Unit (PDU). ζ Single phase 220-240AV 50-60 Hz. ζ</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Maximum load 16 Amp/7840 Watts.	
31	SNM57044	2451364	5330995516412 / SEAL	MAIN ENGINE CATTER PILLAR C-18	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - ITEM IS REQUIRED FOR TOH / MOH OF DGs</u> <u>GENERAL SPECIFICATION - ITEM IS REQUIRED FOR TOH / MOH OF DGs</u>	
32	SNM58658	3227488	4820715186720 / GASKET (1.1 MM THK)	DG CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH(IN): 10 OVERALL LENGTH(IN): 24</u> <u>GENERAL SPECIFICATION - OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH (IN): 10 OVERALL LENGTH(IN): 24</u>	
33	SNM57039	3227487	4820010141893 / GASKET (1.2 MM THK)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u>	
34	SNM62690	326-1644	4330015302969 / FILTER ELEMENT, FLUID	CATERPILLAR DG 275 KVA C-9	5 / EACH/NUMBER	C-9	-	CATTERPILLER SARL.C/O POWER SYSTEM, BUILDING 2 SPRINGVALE BUSINESS PARK BELFATS 7A/L NORTHERN IRELAND UK		CATTRPILLER	<u>TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9</u> <u>GENERAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9</u>	
35	SNM57046	2172752	5330015390573 / GASKET (VALVE BRACKET)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u>	
36	SNM57284	1542427	5330998450295 / GASKET EXHAUST	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u>	
37	SNM57040	2305118	5330715186536 / GASKET	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs</u>	
38	DNV60134	FZ400R12KE3	5961785224756 / IGBT	FREQUENCY CONTROLLER	1 / EACH/NUMBER	INFINEON	-	ZHENG ZHOU ELECTROMECHANICAL REASERCH INSTITUTE NO-126 NING GUANG		ZHENG ZHOU ELECTR OMECHA	<u>TECHNICAL SPECIFICATION - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								ROAD ZHENG ZHOU CHINA TEL:0371-67132002 FAX:0371-68714149	NICAL REASER CH INSTITUTE		CONVERTORGENERAL SPECIFICATION - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY CONVERTOR	
39	DNS57637	471 081	3110580007127 / BALL BEARING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	2 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20 GENERAL SPECIFICATION - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20	
40	DNS57959	200 011	5310735185436 / NUT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	221 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
41	DNF62892	05-00-0882-00	6350715194465 / HARD DRIVE, 500GB	Luggage Scanning Machine size (40)	1 / EACH/NUMBER	XIS-100X	ASTVC180LL740	ASTROPHYSICS INC CTR UNITED STATES TEL 9095985488 FAX 9095985546	Astrophysics Manufactured		TECHNICAL SPECIFICATION - Security Equipment 6350016155690 GENERAL SPECIFICATION - Security Equipment 6350016155690	
42	DNF62872	03-00-0201-00 / 02-00-0159-00	6350715194454 / PCB, DCI	Luggage Scanning Machine size (40)	1 / EACH/NUMBER	XIS-100X	ASTVC180LL740	ASTROPHYSICS INC CTR UNITED STATES TEL 9095985488 FAX 9095985546	Astrophysics Manufactured		TECHNICAL SPECIFICATION - Security Equipment 40"X40" 6350-01-615-5690 GENERAL SPECIFICATION - Security Equipment 40"X40" 6350-01-615-5690	
43	SNM57036	7F7590	5330015954369 / GASKET	SSDG	4 / EACH/NUMBER	3304-B	2P6512	CATERPILLER INC.100 N. E ADAMS PEORIA, ILLINOIS 61629,USA	CATERPILLER		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
44	DNS56418	3CA80-5.0-S	4820775188083 / CHECK VALUE	WARTSILA STERN THRUSTER	1 / EACH/NUMBER	WART-LCT-CS250-	MADD MP/00675.M2T12	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O.	Wartsila Propulsion		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				PROP CS250-S/WO-K HOLLAND		S/WO-K	RASD MP/00675 .M2T11	Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Netherlands B.V.			
45	SNM59316	06NA660016S	5915151799286 / OIL FILTER	CARRIER AIR CONDITION	1 / EACH/NUMBER	30GX-092-A-901-EE		CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388	CARRIER FRANCE		TECHNICAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388GENERAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388	
46	DGT48549	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	10 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		TECHNICAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB GENERAL SPECIFICATION - SIZE Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
47	DNJ62759	6Y2-24360-60	4710765189660 / PRIMER PUMP ASSY	YAMAHA SMALL BOAT ENGINE F100B JAPAN	3 / EACH/NUMBER	F100B	60CL100410G	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@sea-request.biz	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32		TECHNICAL SPECIFICATION - IPCGENERAL SPECIFICATION - IPC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									1115 Fax : +81 538 32 1634 Email/URL : info@sea-quest.biz			
48	DGE58504	096-0240-004C	402079515298 7 / ROPE NAVY FLEX 24 MM BROWN 3 STRAND POLYPROPYLENE (HAWSERLAID)	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS- ROPE@RANDERS-REB.DK. PARENT/SYS;/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE. GENERAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS- ROPE@RANDERS-REB.DK. PARENT/SYS;/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.	
49	DGE58503	096-0320-004C	402079515298 9 / ROPE NAVY FLEX 32 MM BROWN 3 STRAND POLYPROPYLENE	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - 1. MANUFACTURED TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR GENERAL SPECIFICATION - 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MANUFACTURD TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR	
50	DNF56424	84873025 / MWUA	492078520881 1 / POWER PROTECTOR	Jiangsu Josun Main AC System China	1 / EACH/NUMBER	CJK-58, 31KW	JKY-50600	Jiangsu Josun Air Conditioner Co., Ltd 18-28, Tongjiang Rd, Taixing City, Jiangsu Tel:0523-7598753 Fax:0523-7599928 http: www.zhaoshenggroup.com Email: Josun@zhaoshenggroup.com	Jiangsu Josun Air Conditioner Co., Ltd, China		TECHNICAL SPECIFICATION - AS PER CATALOGUE GENERAL SPECIFICATION - AS PER CATALOGUE	
51	DNQ63318	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
52	SNJ45657	12892-93J00-240	536576522237 0 / SHIM, TAPPET (T: 2400)	SUZUKI DF300AP 300 HP OBM	16 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN	
53	DNQ62629	08279009	621079517576 2 / LIFE RAFT	UK RFD	6 / EACH/NUMBER	UK (RFD BEAUFO	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFO		TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT &	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			INTERNAL LIGHT & BATTERY		UMBER	RT)			RT LTD (UK)		BATTERY, RFD BEAUFORT LTD (UK)GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
54	DNJ61834	25141-93L00-0EP / 25141-93L01-OEP / 25141-93L00-YAY	5340765221937 / HOUSING, SHIFT ROD GUIDE (BLACK)	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - ENGINE MODEL: DF300AP GENERAL SPECIFICATION - ENGINE MODEL: DF300AP	
55	DPC57929	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	6 / GALLON			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLOE E INC		TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPSGENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS	
56	SNM62690	326-1644	4330015302969 / FILTER ELEMENT, FLUID	CATERPILLAR DG 275 KVA C-9	5 / EACH/NUMBER	C-9	CAT000C9LLX900927	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, UNITED STATES TELE NO 3095782353 FAX NO 3095783739 WWW.CAT.COM	ALLIED CAT		TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9GENERAL SPECIFICATION -_CATERPILLAR DG 275 KVA MODEL NO. C-9	
57	DNF61824	627-098	4140725172364 / BLOWER	FLASH POINT TESTER	2 / EACH/NUMBER	HFP 339		WALTER HERZOG GmbH Test Equipment for Mineral Oil Products BadstraBe 3-5 D-97912 Lauda-Konigshofen,Postfach 1241 Germany	GERMANY		TECHNICAL SPECIFICATION - Operating Manual (Flash Point Tester)GENERAL SPECIFICATION - Operating Manual (Flash Point Tester)	
58	DNM57290	2010TM-OR	2910013538540 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	3 / EACH/NUMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFIN		TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.GENERAL SPECIFICATION - 10 micron	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.	
59	SNM56734	3J-1907	5331013336444 / SEAL-O-RING	CATERPILLAR GENSET D3512B (YBB1) USA	2 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
60	DNF55503	T-130	7050785204828 / SERVER DELL POWER EDGE MODEL T-130 WITH 1 TB SSD HARD DISK AND 16 GB RAM	Call Centre T130	1 / UNIT	T130		2nd floor entrance A, Block 3, Crown Technology Park Tairan 9th Rd#21 Chegongmaio Futain, Shenzhen China	DELL CHINA		<u>TECHNICAL SPECIFICATION - Extra Spec; 1Tb SSD and with 16 GB RAM</u> <u>GENERAL SPECIFICATION - Extra Spec; 1Tb SSD and with 16 GB RAM</u>	
61	DNM56413	3067129	2815795207860 / Assembly, fuel pump	320 KVA DG	1 / EACH/NUMBER	NT-855-G6	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMINS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
62	DNC56246	8806621	3410MB0020689 / BEARING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350	2B614987, 2B612137, 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - BEARING</u> <u>GENERAL SPECIFICATION - BEARING</u>	
63	DNM58113	PROPELLER MICHIGAN GOLDLINE	2010715220349 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	MARINE GEAR BOX	3 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA		<u>TECHNICAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u> <u>GENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u>	
64	DNF5020	MIT1025	662579513211	BRIDGE	1 /	MIT1025		UK	M/S		<u>TECHNICAL SPECIFICATION - Max</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	0		8 / BRIDGE MEGGER	MEGGER	EACH/NUMBER				ALTAF & CO 93-B1 M.M. ALAM ROAD GULBERG LAHORE		Output Voltage 10 KV Max Resistance 20 TO <u>GENERAL SPECIFICATION</u> - Max Output Voltage 10 KV Max Resistance 20 TO	
65	DNF61835	SKU	055958000023 2 / FUZE GLASS 10A CLA-203 348TD/(B329-DELL FUSE)		25 / EACH/NUMBER	SIBA/B329-DELL FUSE					<u>TECHNICAL SPECIFICATION</u> - MAKE/ MODEL : SIBA/B329-DELL FUSE Current Rating 10A, Voltage Rating 250V AC, Fuse Speed F, Fuse Size 6x30mm, Diameter 6mm, Overall Length 30mm, Body Material Glass, Breaking Capacity at 100A @ 250 Maximum Voltage Rating VAC Series FSF 5x20 Maximum, perating Temp +150C, Minimum Operating Temp -55C <u>GENERAL SPECIFICATION</u> - MAKE/ MODEL : SIBA/B329-DELL FUSE Current Rating 10A, Voltage Rating 250V AC, Fuse Speed F, Fuse Size 6x30mm, Diameter 6mm, Overall Length 30mm, Body Material Glass, Breaking Capacity at 100A @ 250 Maximum Voltage Rating VAC Series FSF 5x20 Maximum, perating Temp +150C, Minimum Operating Temp -55C	
66	DGE60115		045159451009 4 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS)		57 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM. <u>GENERAL SPECIFICATION</u> - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM.	
67	SGB49409		027770277004 1 / SPANNER FIXED DOUBLE ENDED OPEN JAW 18MM & 19MM	PAK PATTERN (GENERAL USE)	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
68	DGT47852	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		672 / SQ FEET						<u>TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm</u> <u>GENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm</u>	
69	SGB31490		0214590130609 / BOLT MACHINE STEEL BSF HEX HD SZ 0.375X2.250X0.750 IN		65 / TEN						<u>TECHNICAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED</u> <u>GENERAL SPECIFICATION - material specs AISI 4140(PD 970: 2005 GRADE 708M40/42CRM04 OEM COC/mtc REQUIRED</u>	
70	DGB37525		0272502720040 / DRILL-PARALELL-SHANK-3MM CARBON STEEL		58 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material HSS, Hardness HRC65-66.</u> <u>GENERAL SPECIFICATION - Material HSS, Hardness HRC65-66.</u>	
71	DNG48794	DO38012-003-0360-0	0000LLTRR7135 / MORES CABLE 30FT	G.M DETROIT FOR GRP BOATS MAKE USA	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
72	SNM49684	7961447	1309794990023 / FILTER-ELEMENT		10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
73	DNF56014	BSEN 60317-8	0561795198756 / WIRE WINDING ELECT COPPER	FOR WINDING.	30 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			POLYESTER ENAMEL cOND DIA 0.850 O/DIA 0.964MM (GRADE-3 CLASS-180)									
74	SNF17015	PAKISTAN CABLE/ ALLIED CABLE	129078509085 6 / 04 CORE POWER CABLE ELECTRICAL 37V 4X1.0MM2	MFC ZJ1-23A	250 / METER	PAKISTA N CABLE/ ALLIED CABLE					TECHNICAL SPECIFICATION - 04 CORE POWER CABLE 37V 4X1.0MM2 GENERAL SPECIFICATION - 04 CORE POWER CABLE 37V 4X1.0MM2	
75	DGH61751		056159521853 7 / CABLE ELECT WELDING FLEX 1 CORE COND 1107/0.20 DIA 14.5MM		100 / METER						TECHNICAL SPECIFICATION - DEF STAN 61-12/1 PART 19 & BS 638 PART 4 OF 1996 GENERAL SPECIFICATION - DEF STAN 61-12/1 PART 19 & BS 638 PART 4 OF 1996	
76	DNF54779	BS EN 60317-8	056179525358 0 / WIRE, WINDING COPPER ELECT COND	WIRE FOR WINDING	160 / KILOGRAMME	GHAZILE X					TECHNICAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 GENERAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
77	DNF56018	BS EN 60317-8 Grade 2	056179439325 2 / WIRE, WINDING ELECT COPPER COND	MOTOR WINDING	160 / KILOGRAMME						TECHNICAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM GENERAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM	
78	DNA44334	0400-2998	299072500691 0 / STOP RING DEUTZ BA12H716 0400-2998	DEUTZ DIESEL GENERATOR 350KW	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
79	SNM52398	4L-9852	2940000743584 / AIR FILTER ELEMENT	CATERPILLER D/G (USA)	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
80	SNM51620	2656617	2940992147826 / FUEL FILTER	P60P1 PERKINS DG UK THERMOSTAT E W/PUMP	2 / DECAGRAME						TECHNICAL SPECIFICATION - OEM ADD ; PERKINS FRANCE 165 AV DU BOIS DE LA PIE ROISSY EN FRANCE 95700 43064 ROISSY CGD CEDEX 95913 01499 07171 01 49 90 71 90 5720 572065886 WWW.PERKINS-FR.COM GENERAL SPECIFICATION - OEM ADD ; PERKINS FRANCE 165 AV DU BOIS DE LA PIE ROISSY EN FRANCE 95700 43064 ROISSY CGD CEDEX 95913 01499 07171 01 49 90 71 90 5720 572065886 WWW.PERKINS-FR.COM	
81	SNM51650	0210-4881	2910725043288 / STRAINER	MAIN ENGIE DEUTZ PNS KALMAT	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DNJ62761	E225800010B	2815765047759 / EXHAUST VALVE STEEL LG 300MM SEAT 71MM TH 16MM		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
83	SNM56815	4L8473	2815715035128 / PLATE OD-90MM-ID-45MM-THK-3MM-BRASS		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4 GENERAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4	
84	DNM48385	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR					TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control <u>GENERAL SPECIFICATION - Technical Specifications:</u> Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
85	DNM52931	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR					<u>TECHNICAL SPECIFICATION - Technical Specifications:</u> Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control <u>GENERAL SPECIFICATION - Technical Specifications:</u> Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
86	DGE59852	81349 MIL-H-15217	4720002036333 / HOSE RUBBER N/METTALIC INTERNAL DIA 1" NO OF		1800 / FOOT						<u>TECHNICAL SPECIFICATION - equilant:</u> 4 PLY, Rubber Type/ Flexible, oem: KAISHAN Quzhou Refine machinery Equipment Co. Ltd end user: HE-SM Paint Shop parent equip: Chipping Machine sample:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LAYERS 4 (IMPREG.FAB) LG 50 FT								Available tech specs: Internal dia = 1 Inch Working Pressure = 10 Bar Maximum Working pressure = 30 Bar Temp Range = -35 to 80 °C Packing = Plastic Paper oem coc/DOCUMENTS /dealer cerificate: Yes <u>GENERAL SPECIFICATION</u> - equilant: 4 PLY, Rubber Type/ Flexible, oem: KAISHAN Quzhou Refine machinery Equipment Co. Ltd end user: HE-SM Paint Shop parent equip: Chipping Machine sample: Available tech specs: Internal dia = 1 Inch Working Pressure = 10 Bar Maximum Working pressure = 30 Bar Temp Range = -35 to 80 °C Packing = Plastic Paper oem coc/DOCUMENTS /dealer cerificate: Yes	
87	DNH61499	DV-200N	4310795113465 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
88	DNF54009	LL-01A10-230C	4240705114965 / EMERGENCY LAMP WITH 10 METER CABLE TYPE 60W EX GLS LEAD LAMP	SAFETY RELATED EQUIPMENT	1 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
89	DNM41574	EBH16 / TV16/tve-24	4130US5065504 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	921047473					<u>TECHNICAL SPECIFICATION</u> - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22 <u>GENERAL SPECIFICATION</u> - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22	
90	SNM56745	7E7997	3120012977501 / BEARING HALH SET	3512TA, CATERPILLER USA	24 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
91	DNH43913		3510725066457 / HEAVY DUTY SPIN DRYER(Z-20)	GENERAL USE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - MODEL: MNM-CSSD-022 GAUGE : 16MM LOAD CAPACITY: 20 KG EXTRACTION SPEED: 1450 RPM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			LOAD 1.6KW								DIAMETER OF DRUM: 635 MM HEIGHT OF DRUM: 320 MM <u>GENERAL SPECIFICATION -</u> MODEL: MNM-CSSD-022 GAUGE : 16MM LOAD CAPACITY: 20 KG EXTRACTION SPEED: 1450 RPM DIAMETER OF DRUM: 635 MM HEIGHT OF DRUM: 320 MM	
92	SNM56736	7N5246	312001322293 3 / BEARING WASHER THRUST	3516, CATERPILLAR D/G USA (JNB)	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
93	DNZ60340	1121237/12017	413078502675 4 / PACKING FOR SIDE COVER THICK 0.5MM ASBESTOS SHEET AA016	AIR CONDITIONER PLANT NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Material: Asbestos Sheet <u>GENERAL SPECIFICATION -</u> Material: Asbestos Sheet	
94	DNZ60229	112601	413078502677 4 / PLATE SUCTION VALVE 1/D 76 MM O/D 99 MM SWEDISH STEEL AA001	AIR CONDITIONER PLANT 6C75-EB NASR	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
95	DNM61875	E24FDZ/1	413071509189 1 / EVAPORATOR 24000BTU	AIR CONDITIONING UNIT OF MARINE AIR SYSTEM USA	1 / EACH/NUMBER	MARINE AIR/E24FDZ/1					<u>TECHNICAL SPECIFICATION -</u> OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32 <u>GENERAL SPECIFICATION -</u> OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 &	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32	
96	SNM567 95	4W5738	312001202589 4 / BEARING HALF SLEEVE	CATER PILLER D/G (BASIC ENGINE)	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
97	SGB570 63	A1226-1-9	311000227327 6 / BEARING BALL ANNULAR SZ 40.00X90. 00MMX1.4375 IN		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required</u> <u>GENERAL SPECIFICATION - OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required</u>	
98	DGP633 45		361070509130 4 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC DUO		11 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NEW SPECS UPDATED</u> <u>GENERAL SPECIFICATION - NEW SPECS UPDATED</u>	
99	DGP635 86		361070509130 4 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC DUO		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NEW SPECS UPDATED</u> <u>GENERAL SPECIFICATION - NEW SPECS UPDATED</u>	
100	SNG448 43	FAG/SKF 6309ZZ	311000155672 7 / BEARING BALL ANNULAR FAG 6309 SZ 45.00X100. 00X25.00MM		37 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM= NAVAL SHIP SYSTEMS COMMAND</u> <u>GENERAL SPECIFICATION - OEM= NAVAL SHIP SYSTEMS COMMAND</u>	
101	SNM567 48	8S4757	530601323414 0 / BOLT	3512TA, CATERPILLER USA	12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate + Oil offers corrosion protection up to the point of assembly (recommend painting for external</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in): 5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50</p> <p><u>GENERAL SPECIFICATION</u> - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate + Oil offers corrosion protection up to the point of assembly (recommend painting for external applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in): 5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50</p>	
102	DNJ51765	A31121200 / ITEM-NO3200-13	5310765043438 / NUT-STEEL-I/D-10MM-HEX-SIZE18MM-THICK-9MM	CYLINDER-HEAD-3200	33 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
103	DNZ60301	306	5306785039137 / COUPL BOLT WITH NUT&S. WASHER STEELU-352	AIR CONDITION SEA WATER PUMP PNS NASR	18 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - MATERIAL: SSG</p> <p><u>GENERAL SPECIFICATION</u> - MATERIAL: SS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SZ 53.00 . 00X14.00MM									
104	DNZ60333	501	5330785027789 / GLAND PACKING CARBONIZED FIBER (NSD/CSG-II/2/132 DT30-04-2002	M/E PISTON COOLING PUMP TOMG-125 NASR	2 / METER						<u>TECHNICAL SPECIFICATION - Material: Carbonized fibre</u> <u>GENERAL SPECIFICATION - Material: Carbonized fibre</u>	
105	DNZ60300	501	5330785029814 / PACKIING GLAND 10MM DIA47X28MM	M/E F-V COOLING WATER PUMP BH-40-2	1 / SET						<u>TECHNICAL SPECIFICATION - MATERIAL: SEMI METALLIC Size: dia 47 x 28 mm</u> <u>GENERAL SPECIFICATION - MATERIAL: SEMI METALLIC Size: dia 47 x 28 mm</u>	
106	SNM45573	1P1255	5330013675724 / GASKET JOINT WD-29MM LG-70MM TH-1MM HOLE DIA-11MM	FOR CATER PILLER DIESEL GENERATOR (USA)	4 / EACH/NUMBER	3304B					<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u>	
107	DNZ60358	YS-250	5330785039118 / OILED ASBESTES PACKING SIZE OD 05MM BF-47	PIPING PART NASR	16 / METER						<u>TECHNICAL SPECIFICATION - Material: Asbestos Sheet</u> <u>GENERAL SPECIFICATION - Material: Asbestos Sheet</u>	
108	DNZ60334	264004 (132356)	5330785041797 / PACKING COMMANION FLANGE (JOINT-FABRIC) 71X0.8MM AA-125	A.C COMPRESSOR FOR PNS NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material: Joint-Fabric</u> <u>GENERAL SPECIFICATION - Material: Joint-Fabric</u>	
109	DNF62756	P2240/VP-1240A	5835765013357 / AMPLIFIER 240W TOA JAPAN	P.A SYSTEM.	2 / EACH/NUMBER	P2240					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
110	DGT57758	NO DATA AVAILABL E	5530705042933 / PLY WOOD NATURAL TEAK FINISH ONE SIDE (NOT	PRESENTATIO N BOXES FOR VVIPs	416 / SQ FEET						<u>TECHNICAL SPECIFICATION - bs 1088 part 1 & 2 BS 4079</u> ; Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Thickness= 3mm ; Core and back ply should of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ARTIFICIAL), 3PLY, TYPE OF BOND WBP, L=8' W= 4' TH=3mm								hard wood ; Thickness of face and back veneer = 0.6mm <u>GENERAL SPECIFICATION</u> - bs 1088 part 1 & 2 BS 4079 ; Plywood natural teak finish one side (not artificial), 3ply, type of bond WBP, Length= 8 Ft Width= 4 Ft Thickness= 3mm ; Core and back ply should of hard wood ; Thickness of face and back veneer = 0.6mm	
111	DNF5755 1	1106	582570511832 3 / BATTERY CHARGER I/P220V 50HZ 1PH O/P 48V (12X4) 20A WITH ACCE		1 / EACH/N UMBER	GZL30A- 6/48V					<u>TECHNICAL SPECIFICATION</u> - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory <u>GENERAL SPECIFICATION</u> - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC: OEM: Nanchang Shuguang Eledricd Equipment Factory	
112	SNJ3769 5	792802	593576501688 0 / PLUG TYPE JIS F8832 FOR NAVIGATION LIGHT	EXTRA NAVIGATION LIGHT	6 / EACH/N UMBER	T-1MB					<u>TECHNICAL SPECIFICATION</u> - MAKE OF itEM: ZJHAIJI CHINA <u>GENERAL SPECIFICATION</u> - MAKE OF itEM: ZJHAIJI CHINA	
113	DNF5533 7	SP 500PS (SALTEE POWER LINK UPS) / SP- 166ER	614070510849 2 / UPS-750VA WITH 01 BATTERY BACUP BUILTIN STABLIZER (WET BATERY	SALTEE POWER LINK UPS	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
114	DNC582 57	ELEC- 2650 / IN 63047/ 2650	623079511027 2 / SEARCH LIGHT HAND HELD (24V DC&230 WATT)	GRIFFON HOVER CRAFT LTD UK	2 / EACH/N UMBER	GEEPAS ®					<u>TECHNICAL SPECIFICATION</u> - 1. Make/ Brand: GEEPAS ® 2. Model: GSL5706 - 30Watt <u>GENERAL SPECIFICATION</u> - 1. Make/ Brand: GEEPAS ® 2. Model: GSL5706 - 30Watt	
115	DNC540 98	ELEC- 2650 / IN	623079511027 2 / SEARCH	GRIFFON HOVER	35 / EACH/N	GEEPAS ®					<u>TECHNICAL SPECIFICATION</u> - 1. Make/ Brand: GEEPAS ® 2. Model:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		63047/2650	LIGHT HAND HELD (24V DC&230 WATT)	CRAFT LTD UK	UMBER						GSL5706 - 30Watt <u>GENERAL SPECIFICATION - 1. Make/ Brand: GEEPAS @ 2. Model: GSL5706 - 30Watt</u>	
116	DNF61504	HDR-XR200/XR150	6710765119366 / DIGITAL VIDEO CAMERA SONY	DIGITAL VIDEO CAMERA	1 / EACH/NUMBER	HDR-XR200/XR150					<u>TECHNICAL SPECIFICATION - DNSS LTR ST-S/3201/06229 DT 16JUN 06</u> <u>GENERAL SPECIFICATION - DNSS LTR ST-S/3201/06229 DT 16JUN 06</u>	
117	DGB59857	NO DATA AVAILABLE	0246500001066 / BLOCK CHAIN 5 TON 10METER (ORIGINAL MANUFACTURE LENGTH}		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
118	DGP63617	SONY/SAMSUNG/LG/TCL 20, 21,18, 32 INCH	7730705059182 / LED 32 INCH		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
119	DGE57608		8340705087914 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - PSG-600, SPECIFICATIONS: • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO</u> <u>SPECIFICATION OF CANVAS COTTON: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER PROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet</p> <p><u>GENERAL SPECIFICATION - PSG-600, SPECIFICATIONS:</u></p> <ul style="list-style-type: none"> • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO <p><u>SPECIFICATION OF CANVAS</u></p> <p>COTTON: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER pROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM <p>Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet</p> </p>	
120	DGE61622	NO DATA AVAILABLE	834070501408 4 / TENT FOR CPOS AND SAILORS WT. 120 LBS		9 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - cins observation and annex b is enclosed as document a. Tent for CPOs and Sailors WT.120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller. <u>GENERAL SPECIFICATION</u> - cins observation and annex b is enclosed as document a.Tent for CPOs and Sailors WT.120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.	
121	DGT61222	NO DATA AVAILAB LE	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		2848 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993 <u>GENERAL SPECIFICATION</u> - SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
122	DGT62156	NO DATA AVAILAB LE	010050000001 5 / PLY WOOD GRADE-1, 5 PLY		992 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993</p> <p><u>GENERAL SPECIFICATION -</u> SIZE LENGTH=8 FEET, WIDTH=4 FEET, THICKNESS=06 MM(±1MM) SPECIFICATION; 1. MOISTURE CONTENT: BS EN 322 : 1993 2. BONDING QUALITY: BS 314-1 : 2004 AND BS EN 314-2 : 1993 3. GLUE: BS 1203 : 1979 4. PRESERVATION: BS 4072 : 1999 5. PHYSICAL EVALUTION: BS 6566-6 : 1985 6. DENSITY: BS EN 323 : 1993</p>	
123	DGT62158	NO DATA AVAILAB LE	010050000002 8 / PLY WOOD marine all shesham DURABILITY REQUIRED STANDARD GD-I, 5 PLY (CORE INNER and outer PLIES OF shesham wood TYPE OF BOND wbp class iii TREATED WITH PRESERVATIV E AS PER SPECS BS EN 314-2.	2.440X1. 220MTRX6. 35MM) SPECE/BS- 1088	192 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION -</u> Size: L = 8' W = 4' DIMENSIONAL TOLERANCE Thickness = 06 MM to 07mm bs1088 part-1 &2 density of timber shesham as per international standard: 100% thickness 0.6 mm) shesham venier both sides thickness .70 mm</p> <p><u>GENERAL SPECIFICATION -</u> Size: L = 8' W = 4' DIMENSIONAL TOLERANCE Thickness = 06 MM to 07mm bs1088 part-1 &2 density of timber shesham as per international standard: 100% thickness 0.6 mm) shesham venier both sides thickness .70 mm</p>	
124	DGB576	NO DATA	026850000006		6 /	NO DATA					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	96	AVAILABL E	1 / SCALE-SPRING-BALANCE-20-STONE-280-LBS		EACH/N UMBER	AVAILAB LE					Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow	
125	DGE13594	NO DATA AVAILABL E	0476590000026 / BRUSH STEEL WIRE FLAT 1 3/4	LIFE RAFT	109 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Material: Steel wire with wooden handle Length with handle: 280mm Length without handle: 140mm <u>GENERAL SPECIFICATION</u> -Material: Steel wire with wooden handle Length with handle: 280mm Length without handle: 140mm	
126	DNF48291	HA7623-3-1 TERASAKI	9611750650023 / CIRCUIT BREAKER 100AMPS 220/500V	SWITCH BOARD	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> ITEM IS TO-100BA,AC 550V, DC250V,100 AMP,3 POLE(SHT-TRIP) TERASAKI AND 5433 RESPECTIVELY.. <u>GENERAL SPECIFICATION -</u> ITEM IS TO-100BA,AC 550V,DC250V,100 AMP,3 POLE(SHT-TRIP) TERASAKI AND 5433 RESPECTIVELY..	
127	DNQ62657	140501010	8415991304873 / GLOVES	FIRE FIGHTING	150 / PAIR						<u>TECHNICAL SPECIFICATION -</u> OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION -</u> OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FEB 12.	
128	DGB31351	XK-1000/Execel-40C	6670785116072 / DIGITAL WEIGHING SCALE FOR RATIONS WEIGHING		1 / EACH/NUMBER					MTC / COC ALSO REQUIRED	<p><u>TECHNICAL SPECIFICATION</u> - model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft</p> <p>The item is to used for weighing of ration <u>GENERAL SPECIFICATION</u> - model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft</p> <p>The item is to used for weighing of ration</p>	
129	DGP63615	NO DATA AVAILABLER	7435705114870 / PERSONAL COMPUTER CORE i7 (AS PER NHQ APPROVED SPEC)	SELF	1 / SET						<p><u>TECHNICAL SPECIFICATION</u> - specification of pc: HP/DELL CORE i7 SYSTEM OR HIGHER EQUIVALENT. 1. CPU Technology: Intel ® Core i7 (8th/9th/10th/11th/12th Generation or above) (Minimum 2.4 & 4.7 GHz or above), 2. System Memory: 8/16 GB RAM DDR3/DDR4 or (02 x 4GB OR 02X08 gm RAM ddr3/ddr4). 3. Hard Disk: 1 TB SATA 4. Optical Disk Drive: DVD RW 5. Keyboard: wired/usb 6. Mouse: wired/usb 7. LED: 18.5" HDMI Display 8. LAN: Ethernet Card: 10/100/1000 Mbps 9.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Warranty: 3 Years 10. Operating System: Windows (Licensed Version window-10 or above). 11. Graphics: Intel ® HD Graphics 750, (Minimum 2 GB shared/ dedicated GRAPHIC CARD)</p> <p><u>GENERAL SPECIFICATION - specification of pc: HP/DELL CORE i7 SYSTEM OR HIGHER EQUIVALENT.</u></p> <p>1. CPU Technology: Intel ® Core i7 (8th/9th/10th/11th/12th Generation or above) (Minimum 2.4 & 4.7 GHz or above), 2. System Memory: 8/16 GB RAM DDR3/DDR4 or (02 x 4GB OR 02X08 gm RAM ddr3/ddr4). 3. Hard Disk: 1 TB SATA 4. Optical Disk Drive: DVD RW 5. Keyboard: wired/usb 6. Mouse: wired/usb 7. LED: 18.5" HDMI Display 8. LAN: Ethernet Card: 10/100/1000 Mbps 9. Warranty: 3 Years 10. Operating System: Windows (Licensed Version window-10 or above). 11. Graphics: Intel ® HD Graphics 750, (Minimum 2 GB shared/ dedicated GRAPHIC CARD)</p>	
130	DNF63591	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	1 / EACH/NUMBER	BLAZER VISTA 1000/Aurora					<p><u>TECHNICAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC</u></p> <p><u>GENERAL SPECIFICATION - backup time: 10 minutes Product Name: AURORA Input: 220V AC</u></p>	
131	DNF62755	CAT-6	7035735114696 / 4 PAIR CAT-6 CABLE	LOCAL AREA NETWORK CABLE CAT-6	1220 / METER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
132	DNH61061	NO DATA AVAILABLE	7320701002276 / AUTOMATIC ROTI PLANT		2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - a. Production capacity upto 1000 chapaties per hour b. Mild Steel Structure c. Natural and LPG GAS fired 1: 10X4X6 FT W/MOTOR 50HZ AC22 BELT SIZE 12"X3", OVERALL BELT SIZE 110"X32 " CAPACITY</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											3000 ROTI/HR ELECTRICAL PLANT 2: 12X3 FT APPROX, BELT SIZE 110"X32" CPACITY 3000 ROTI/HR, CONSTRUCTION 22 GUAGE PARTED MSOR, 22 GUAGE GI DUCTING 18 GUAGE 304 SS, 1 HP RELIABLE BRAND MOTOR 2 HP EXHAUST FLOWER MOTOR <u>MOTORGNERAL SPECIFICATION</u> -a. Production capacity upto 1000 chapaties per hour b. Mild Steel Structure c. Natural and LPG GAS fired 1: 10X4X6 FT W/MOTOR 50HZ AC22 BELT SIZE 12"X3", OVERALL BELT SIZE 110"X32 " CAPACITY 3000 ROTI/HR ELECTRICAL PLANT 2: 12X3 FT APPROX, BELT SIZE 110"X32" CPACITY 3000 ROTI/HR, CONSTRUCTION 22 GUAGE PARTED MSOR, 22 GUAGE GI DUCTING 18 GUAGE 304 SS, 1 HP RELIABLE BRAND MOTOR 2 HP EXHAUST FLOWER MOTOR	
133	DGD48753	NO DATA AVAILAB LE	003550000056 0 / COOKER PRESSURE-10 LITRES COMPLETE		7 / SET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free) <u>GENERAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free)	
134	DNF44017	XR-800 FT/DC- CMS2200- 3-MIG	142071512071 1 / PRO AUDIO MIXER DYNACORD CMS- 1600/2200-3 16/22- CHANNEL	PA SYSTEM	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USAGENERAL SPECIFICATION - Main voltage 100 to 240VAC, 50/60 Hz, battery power supply 48 V DC, 12 Mic/Line +4 Mic/Stereo inputs. 15 Hz-70KHz Freq response. master EQ 11 Band. XR-800 FT/DC-CMS2200-3-MIG OEM: DYNACORD ORIGIN: USA	
135	SNM57288	4P5975/5B 4855 &	441072512783 8 /	HP COMPRESSO	2 / EACH/N	KAP-23- 40E					<u>TECHNICAL SPECIFICATION - NO DATA AVAILAB</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		7E9658	CONTACTOR GP WATER TEMP SHUTOFF 4P5975, 5B4855 Burning & 7E9658 Contractor A	R	UMBER	GERMANY					SPECIFICATION - NO DATA AVAILABLE	
136	DPK56355	FLUGENE 113B0MBE AER0S0L/ UFI:PMU 1-ROPD-8007-P2DQ	685014344090 4 / CLEANING SOLVENT FOR ELECTRIC/ ELECTRONIC EQUIPMENT		40 / EACH/NUMBER	UFI:PMU 1-ROPD-8007-P2DQ					TECHNICAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate. GENERAL SPECIFICATION - Perfects Universal Degreaser Spray is oil free and cleans dirty or corrosive material, electrical contacts, switches, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, potentiometer and others Features a. Can be used to clean dirty or corrosive material, electrical contacts, switches, spark plugs, voltage regulators, relays, telephone equipment, electronics circuits, PCBs. b. Should be very safe to use on Active/ Passive Components. c. Should have fast vaporization rate.	
137	DN053957	ZAUW-314/0-SEW , A21H-6	209070528070 5 / Under water zinc anodes 054A Ships (500*100*40 MM)		18 / EACH/NUMBER	500*100*40					TECHNICAL SPECIFICATION - MATERIAL COMPOSITION: NICKAL: 0.01 IRON: 0.08 MAGNESIUM: 1.00 SILCON: 0.01 TITANIUM: 0.04 ZINC: 5.10 ALUMINUM: REMAINDER IT IS ALLOY OF AL-ZN-IN-MG-TI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											METALS DIMENSIONS 500X100X40 MM <u>GENERAL SPECIFICATION - MATERIAL COMPOSITION:</u> NICKAL: 0.01 IRON: 0.08 MAGNESIUM: 1.00 SILCON: 0.01 TITANIUM: 0.04 ZINC: 5.10 ALUMINUM: REMAINDER IT IS ALLOY OF AL-ZN-IN-MG-TI METALS DIMENSIONS 500X100X40 MM	
138	DNZ51695	SC000872	9150785278480 / LUBE OIL CE 755		5 / EACH/NUMBER	MCH18-Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION - OIL CE 750 ISO VG 150/220 Synthetic OIL High Pressure Compressor For Breathing Air & Technical Gases NITROX upto 40% O2 MAX\ Packing details : 1 & ½ Ltr</u> <u>GENERAL SPECIFICATION - OIL CE 750 ISO VG 150/220 Synthetic OIL High Pressure Compressor For Breathing Air & Technical Gases NITROX upto 40% O2 MAX\ Packing details : 1 & ½ Ltr</u>	
139	DNF63098	T-1S01	5996705249070 / Mixer Pre-amplifer, 5 mic input, 3aux, AC 230V and DC 24V		1 / EACH/NUMBER	ITC					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
140	DNF58991	20 Pair 0.6mm Jelly Filled UG	7045705249625 / Copper Cable 20 Pair 0.6mm Jelly Filled UG Armoured Telephone Cable		500 / METER	20 Pair 0.6mm Jelly Filled UG					<u>TECHNICAL SPECIFICATION - Complete Details regarding all type of copper cables are avialable on the page no 9 to 12 in the provided Brochure named PTCL Product Catalogue -Copper Telecom Cables" NOTE: 0.6mm is the outer diameter size while 20, 50 & 100 present the number of pairs in the cable for further details kindly concern above mentioned Brocuher</u> <u>GENERAL SPECIFICATION - Complete Details regarding all type of copper cables are avialable on the page no 9 to 12 in the provided Brochure named PTCL Product Catalogue -Copper Telecom Cables" NOTE: 0.6mm is</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											the outer diameter size while 20, 50 & 100 present the number of pairs in the cable for further details kindly concern above mentioned Brocuher	
141	DNF63524	DS-6701HFHIV	589527068439 1 / HD ENDCODER (VIDEO COMPRATION DEVICE)		3 / EACH/NUMBER	N/A					<p><u>TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.</u></p> <p><u>GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.</u></p>	
142	DN063355	G860022-02 / ZRACR-065-SEW	6115FP105006 5 / ANTI-CORROSIVE ZINC ROD		2 / EACH/NUMBER	1FR6506-4SA42-2					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
143	DNF58862	RG-S5750C-28GT4XS-H	589578528071 1 / NETWORK SWITCH 28 SFP PORTS RUIJIE		1 / EACH/NUMBER	RG-s5750c-28sfp4xs-h					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
144	SNM47012	2656615	534070524601 9 / fuel filter head		2 / EACH/NUMBER	3-2500					<u>TECHNICAL SPECIFICATION - OEM:MILLAT TRACTOR LTD,</u> <u>LHR</u> <u>GENERAL SPECIFICATION - OEM:MILLAT TRACTOR LTD, LHR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
145	DNF56228	PE-LAP-SS (10 PAIRS)	599570524882 3 / SELF SUPPORTING ARIEL TELEPHONE CABLE SIZE 10 PAIRS 0.5 MM		100 / METER	10/0.5 MM SSAU					TECHNICAL SPECIFICATION - COMPANY NAME: PREMIER CABLES (PVT) LIMITED ADDRESS: 43-E, BLOCK-6, P.E.C.H.S, RAZI ROAD, SHAHRAH-E-FAISAL, KARACHI, PAKISTAN CONTACT NO: 02134397771 GENERAL SPECIFICATION - COMPANY NAME: PREMIER CABLES (PVT) LIMITED ADDRESS: 43-E, BLOCK-6, P.E.C.H.S, RAZI ROAD, SHAHRAH-E-FAISAL, KARACHI, PAKISTAN CONTACT NO: 02134397771	
146	DNF62891	SDPH62H-008T-NBAAD / 47519	702578523545 7 / HARD DRIVE STORAGE SYSTEM G-TECHNOLOGY G-DRIVE 8TB - USB THUNDERBOLT		1 / EACH/NUMBER	SKU: OG05375					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
147	DNM63000	4309459	281501662927 9 / UPPER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
148	SNM56657	243-5220	311001537069 0 / BEARING, BALL, ANNULAR		3 / EACH/NUMBER	C-18 DE605EO CATERPILLER					TECHNICAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8 GENERAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8	
149	DSB49874	27740	623071526809 0 / 12-v dc LED BLAST LIGHT with 50-ft cable		2 / EACH/N UMBER	27740 1					<u>TECHNICAL SPECIFICATION -</u> CLEMCO BLAST LIGHT IS A POWERFULL 860 LUMEN LED LIGHT SOURCE TO ILLUMIANTE THE WORK SYSTEM make usa <u>GENERAL SPECIFICATION -</u> CLEMCO BLAST LIGHT IS A POWERFULL 860 LUMEN LED LIGHT SOURCE TO ILLUMIANTE THE WORK SYSTEM make usa	
150	DNF54598	NCB- FS09D- LCLC-20	599570524636 0 / D-LINK LC- LC SINGLEMODE OS2 DUPLEX PATCH CORD 20M		4 / EACH/N UMBER	NCB- FS09D- LCLC-20					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
151	DNF61817	d701-592	6350CA527106 4 / vapor swabs (pack of 12 swabs)		1 / EACH/N UMBER	na					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
152	DNF56241	pE-LAP- SS (20 pairs)	599570524882 4 / self supporting aerial telephone cable size 20 pairs 0.5 mm		150 / METER	20/0.5 mm ssau					<u>TECHNICAL SPECIFICATION -</u> M/s Premier Cables (Pvt) Limited is the manufacturer of subject telephone cable, <u>GENERAL SPECIFICATION -</u> M/s Premier Cables (Pvt) Limited is the manufacturer of subject telephone cable,	
153	DNF56905	pE-LAP- SS (20 pairs)	599570524882 4 / self supporting aerial telephone cable size 20 pairs 0.5 mm		120 / METER	20/0.5 mm ssau					<u>TECHNICAL SPECIFICATION -</u> M/s Premier Cables (Pvt) Limited is the manufacturer of subject telephone cable, <u>GENERAL SPECIFICATION -</u> M/s Premier Cables (Pvt) Limited is the manufacturer of subject telephone cable,	
154	DPC63424	POLP9460 035MC2P	683070524143 3 / HELIUM		15.3 / CUBIC	not known					<u>TECHNICAL SPECIFICATION -</u> HELIUM OXYGEN (HELIOX)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		K	OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		METER						MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M) <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
155	DPC57841	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
156	DPC57992	POLP9460035MC2PK	6830705241433 / HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
157	SGB62685	SH11IN-SEW	4720705292330 / flexible/Spring hose 1" dia		36 / METER	PVCSRH019					<u>TECHNICAL SPECIFICATION - TEMP: -30C TO +80C PRESSURE 88 BAR DOUBLE FIBRE BRAID AND INNER TUBE IS MADE OF SYNTHETIC RUBBER DIA: 1 INCH LENGTH: 12M</u> <u>GENERAL SPECIFICATION - TEMP: -30C TO +80C PRESSURE 88 BAR DOUBLE FIBRE BRAID AND INNER TUBE IS MADE OF SYNTHETIC RUBBER DIA: 1 INCH LENGTH: 12M</u>	
158	DGP63291	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In</p> <p>10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
159	DGP634 64	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In</p> <p>10/100/1000 Warranty: MINIMUM 01</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
160	DGP63558	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION</u> - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
161	DNM62654	10000-97157	2815715289160 / WATER PUMP		2 / EACH/NUMBER	P/E 1106A-70TAG					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
162	DSA44850	ORB-TQT/70/V1 /18ERPM MS	6150705216871 / MAIN BOX		2 / EACH/NUMBER	m/s baig engineering					<u>TECHNICAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY SYSTEM (BD) OEM: M/S BAIG ENGINEERING</u> <u>GENERAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SYSTEM (BD) OEM: M/S BAIG ENGINEERING	
163	DPK59580	STM7610A B10L	685014352474 2 / SAFETY DAGREASING SOLVENT		10 / EACH/ NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
164	DSB57313	123	6625TY672008 2 / PROCESS CALIBRATOR		1 / EACH/ NUMBER	Calibrator Model 123					<u>TECHNICAL SPECIFICATION -</u> The main features of Calibrator (Multifunction Calibrator Model 123) are appended below a. 4-20 ma, 0-20ma, 0-24 ma with 1mamp Resolution. b. 0-100 mv with 10mv Resolution c. 0-12 V with 1mv Resolution d. Thermocouple k, J, E, T Type 1°C Resolution e. Frequency 1- 62,500 Hz <u>GENERAL SPECIFICATION -</u> The main features of Calibrator (Multifunction Calibrator Model 123) are appended below a. 4-20 ma, 0-20ma, 0-24 ma with 1mamp Resolution. b. 0-100 mv with 10mv Resolution c. 0-12 V with 1mv Resolution d. Thermocouple k, J, E, T Type 1°C Resolution e. Frequency 1- 62,500 Hz	
165	DNF57366	dem-310gt	593070524633 3 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510- 28X & DEM- 310GT)		2 / EACH/ NUMBER	dgs-1510- 28x					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
166	DNF59331	dem-310gt	593070524633 3 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS		1 / EACH/ NUMBER	dgs-1510- 28x					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)									
167	DNF55115	dem-310gt	5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		5 / EACH/NUMBER	dgs-1510-28x					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
168	SN060467	Flange DN65 L=500 / MELD-FLH-TG-SEW	4710785269856 / MAIN ENGINE LUB OIL FLEXIBLE HOSE		3 / EACH/NUMBER	16PA6V-280STC					<u>TECHNICAL SPECIFICATION - MAIN ENGINE LUB OIL FLEXIBLE HOSE</u> <u>GENERAL SPECIFICATION - MAIN ENGINE LUB OIL FLEXIBLE HOSE</u>	
169	DNM63001	4309460	5330016657611 / LOWER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE CM 2250					<u>TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u> <u>GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u>	
170	DRG58571	FTK50250/ SNAP NO (MODEL BRA10312H)	4310ZO6542946 / COMPRESSOR L.P.MOBILE 220/230V 50HZ 03 PHASE		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 3 stage LP compressor with following specifications • Maximum pressure of 130-150 PSI • 3 HP electric motor • 220 V/ 3 phase • Auto start/ shut off • Safety cover on running belt • Running wheels • Tank capacity 200 Ltrs with pressure indicator • Pressure relief valve on tank • Drain valve of tank • Main electric ON/ OFF switch with requisite fuses •</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Approximate cost 250, 000 excluding GST • Brand/ OEM any reputable firm origin Taiwan <u>GENERAL SPECIFICATION</u> - 3 stage LP compressor with following specifications • Maximum pressure of 130-150 PSI • 3 HP electric motor • 220 V/ 3 phase • Auto start/ shut off • Safety cover on running belt • Running wheels • Tank capacity 200 Ltrs with pressure indicator • Pressure relief valve on tank • Drain valve of tank • Main electric ON/ OFF switch with requisite fuses •</p> <p>Approximate cost 250, 000 excluding GST • Brand/ OEM any reputable firm origin Taiwan</p>	

INVITATION TO TENDER VSD I.T DATE 22-05-2024

The following item is required against local purchase. Suppliers are requested to quote by **05-06-2024** before 11:00 AM quotation are to be deposited in the quotation box.

<u>S.No</u>	<u>LPR NO & DATE</u>	<u>QTY</u>	<u>DELIVERY</u>
1.	VSD-LPR NO.12/2024 DATE 20 APRIL 2024 WHOLE DAY MREs	150 PACKETs	VSD AT KARACHI

NOTE:-

1. Non-registered firms/supplier are required to forward bank draft/pay order equal to 5% total value of quotation in favor of “**Commander Local Purchase**” division along with their bids.
2. For any amplified details interested firms may contact local purchase division in person.

NOTE:

SPECIFICATION OF ITEM IS ATTACHED

Group officer
Local Purchase





HUAWEI Product
E303

CE0682
HUAWEI TECHNOLOGIES CO., LTD.
MADE IN CHINA





