

## TENDER BULLETIN

DATE & TIME 5/27/24 2:47 PM INVITATION TO TENDER TO BE OPENED ON 6/10/2 10:00 AM AND ITEM REQ BY

### CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

| S. No | LPR No   | PART NO   | NSN / Description   | P/Equipment  | QTY / DENO             | Model | SR NO OF PR | MANUF ADO  | Availabili ty   | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------|---|--|------------------------|-------|-------------|--|---|----------------|---|-----------|
| 1     | SNM55104 | 215-9509  | 473001579602<br>5 / FITTING<br>(QUICK<br>DISCONNECT,<br>MALE) | 50KVA ALLIED<br>CAT DG 400<br>VOLTS 3<br>PHASE 50 HZ | 1 /<br>EACH/N<br>UMBER | N/A   | E3S01292    | CATERPILLAR INC<br>MANAGER ,CUSTOMER<br>SERVICE,ENGINE<br>DIVISION MOSSVILLE<br>BLDG AC P.O.BOX 610<br>MOSSVILLE,LLLINOIS<br>61552-0610 COUNTRY<br>USA     | ALLIED<br>CAT   |                | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>  |           |
| 2     | SNM55152 | 334-2319  | 289571522841<br>5 / KIT-PISTON<br>(0.5-MM OS)                 | 50KVA ALLIED<br>CAT DG 400<br>VOLTS 3<br>PHASE 50 HZ | 1 /<br>EACH/N<br>UMBER | N/A   | E3S01292    | CATERPILLAR INC<br>MANAGER ,CUSTOMER<br>SERVICE,ENGINE<br>DIVISION MOSSVILLE<br>BLDG AC P.O.BOX 610<br>MOSSVILLE,LLLINOIS<br>61552-0610 COUNTRY<br>USA     | ALLIED<br>CAT   |                | <u>TECHNICAL SPECIFICATION -</u><br>Length: 14.99 cm Width: 14.99 cm<br>Height: 2.03 cm Weight: 0.14<br>cm <u>GENERAL SPECIFICATION -</u><br>Length: 14.99 cm Width: 14.99 cm<br>Height: 2.03 cm Weight: 0.14 cm  |           |
| 3     | DNM58192 | 063976-KD | 132572515698<br>7 / PISTON<br>AND SLEEVE<br>ASSEMBLY          | ALPINE HP<br>COMPRESSO<br>R                          | 1 /<br>EACH/N<br>UMBER |       |             | GERMANY<br>ALPINE INDUSTRIAICON<br>(PRIVATE) LIMITED 305/2<br>G. T ROAD<br>BAGHBANPURA LAHORE<br>PAKISTAN<br>TEL:042-6852313,6862490<br>FAX:+92-42-6553674 | GERMAN<br>Y<br>/ALPINE<br>INDUSTR<br>IALCON<br>(PVT)LTD | newspaper      | <u>TECHNICAL SPECIFICATION -</u><br>SOURCE OF AVAILABILITY:ALPINE<br>INDUSTRIAICON(PRIVATE)<br>LIMITED 305/2 G. T ROAD<br>BAGHBANPURA LAHORE<br>PAKISTAN TEL:042-<br>6852313,6862490 FAX:+92-42-<br>6553674 <u>GENERAL</u><br><u>SPECIFICATION - SOURCE OF</u><br>AVAILABILITY:ALPINE<br>INDUSTRIAICON(PRIVATE)<br>LIMITED 305/2 G. T ROAD<br>BAGHBANPURA LAHORE<br>PAKISTAN TEL:042-<br>6852313,6862490 FAX:+92-42-<br>6553674 |           |

| S. No | LPR No   | PART NO           | NSN / Description  | P/Equipment                                      | QTY / DENO        | Model               | SR NO OF PR        | MANUF ADO  | Availabili ty  | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------|--|--|-------------------|---------------------|--------------------|--|--|----------------|--|-----------|
| 4     | DNH56498 | K1387-11/K 1387-3 | 3431715227928 / IDEALARC DC-1000 GOUGING RECTIFIER                     | SELF   | 2 / EACH/NUMBER   | IDEALARC DC-1000    | - IDEALARC DC-1000 | LINCOLN ELECTRIC COMPANY 22801 ST. CLAIR AVE CLEVELAND USA   | LINCOLN ELECTRIC   | newspaper      | TECHNICAL SPECIFICATION - INPUT V/PH/HZ (220/380/440/03/50/60), RATED OUTPUT CURRENT /VOLTAGE/DUTY CYCLE (1000A/44V/100%), OUTPUT RANGE (16-46V,150-1300A)<br>GENERAL SPECIFICATION - INPUT V/PH/HZ (220/380/440/03/50/60), RATED OUTPUT CURRENT /VOLTAGE/DUTY CYCLE (1000A/44V/100%), OUTPUT RANGE (16-46V,150-1300A) |           |
| 5     | SPK58337 | ARCTIC 32/146264  | 9150795170256 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)                  | COMPRESSOR                                       | 40 / LITER        |                     | 65703502           | Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Ermyn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000 | Mobil Oil Company Limited  |                | TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32<br>GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32   |           |
| 6     | SNS55074 | 0676006/067-6006  | 5365014715617 / Plug   | Caterpillar Emergency DG Marine Genset C 4.4 USA | 12 / EACH/NUMBER  | Marine Genset C 4.4 | N/A                | 14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A   | CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS |                | TECHNICAL SPECIFICATION -<br>GENERAL SPECIFICATION -   |           |
| 7     | DPC58414 | NO DATA AVAILABLE | 6810705007848 / ACTIVATOR RESIN (ISOCYANATE COMONENT A ) OEM = LOGSTOR |  | 1300 / KILOGRAMME |                     |                    |  |  | newspaper      | TECHNICAL SPECIFICATION - PROPERTY .....CREEN TIME detail information attached as documents tds-1 and tds-2<br>GENERAL SPECIFICATION - PROPERTY .....CREEN TIME detail information attached as documents tds-1 and tds-2   |           |
| 8     | SNM58024 | 1W3900            | 5330011554283 / GASKET   | CATERPILLAR DIESEL GENERATOR                     | 15 / EACH/NUMBER  | 3304 SSDG           |                    |  |  |                | TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304   |           |

| S. No | LPR No   | PART NO                          | NSN / Description  | P/Equipment | QTY / DENO      | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------------------|--|-------------|-----------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                                  |  | (USA)       |                 |       |             |           |              |                | SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG  |           |
| 9     | SNM45589 | 40207-00 (OLD) / 297000047 (NEW) | 5930US5062125 / PRESSURE SWITCH 40207-00 FOR MAIN A/C                        | MAIN A/C    | 4 / EACH/NUMBER |       |             |           |              |                | TECHNICAL SPECIFICATION - OEM & MAKE: SURE MARINE SERVICE USAGENERAL SPECIFICATION - OEM & MAKE: SURE MARINE SERVICE USA   |           |
| 10    | DGE62531 | NO DATA AVAILABLE                | 8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO |             | 5 / EACH/NUMBER |       |             |           |              |                | TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: |           |

| S. No | LPR No   | PART NO          | NSN / Description  | P/Equipment                          | QTY / DENO        | Model                           | SR NO OF PR         | MANUF ADO   | Availabili ty   | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|------------------|--|--------------------------------------|-------------------|---------------------------------|---------------------|---|-----------------|----------------|---|-----------|
|       |          |                  |  |                                      |                   |                                 |                     |   |                 |                | 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos  |           |
| 11    | DGP55345 | PT-VZ 585N WUXGA | 703070510439 3 / MULTIMEDIA PROJECTOR (PANASONIC MODEL PT-VZ 585N WUXGA) | MULTIMEDIA                           | 1 / EACH/NUMBER   | MODEL PT-VZ 585N WUXGA OR ABOVE |                     |   |                 |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 12    | DSB44573 | AI-9 8C 7C 6C    | 603078528089 7 / FIBER OPTIC SPLICING MACHINE                            |                                      | 1 / EACH/NUMBER   | AI-9                            |                     |   |                 |                | TECHNICAL SPECIFICATION - OEM: SOFTEL OPTIC CO. LTD ADDRESS: 708-709 HAIWEI BUILDING, NO.101 BINKANG ROAD, BINJIANG DISTRICT, HANGZHOU, ZHEJIANG CHINA PH# +86-13588723749 EMAIL: INFO@SOFTEL-OPTIC.<br>GENERAL SPECIFICATION - OEM: SOFTEL OPTIC CO. LTD ADDRESS: 708-709 HAIWEI BUILDING, NO.101 BINKANG ROAD, BINJIANG DISTRICT, HANGZHOU, ZHEJIANG CHINA PH# +86-13588723749 EMAIL: INFO@SOFTEL-OPTIC.COM |           |
| 13    | SNM63013 | 6J-2245          | 533101194610 5 / SEAL-O-RING   | CATERPILLAR GENSET D3512B (YBB1) USA | 34 / EACH/NUMBER  | NA                              | CAT3512 BEYBB00 583 | CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA  | CATERPILLAR USA |                | TECHNICAL SPECIFICATION - MAKE: CATERPILLAR<br>GENERAL SPECIFICATION - MAKE: CATERPILLAR  |           |
| 14    | DNZ63214 | 4101150          | 533001648073 1 / CONNECTION GASKET                                       | Cummins QSK 38 DM Main Engine        | 2 / EACH/NUMBER   | QSK38-DM                        | 33170174            | Cummins, Engine Co. Ltd   | Cummins         |                | TECHNICAL SPECIFICATION - N/A<br>GENERAL SPECIFICATION - N/A  |           |
| 15    | SNF51953 | 0102-034009-226  | 592578515447 8 / SINGLE POLE   | L/PAC                                | 120 / EACH/NUMBER | CHNT-C4 CHNT SINGLE             | 100-125 PSI         | ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE | CHINA           |                | TECHNICAL SPECIFICATION - SOURCE OF AVAILABIY:ALPINE INDUSTRIAL CON PVT LTD.305/2   |           |

| S. No | LPR No   | PART NO         | NSN / Description   | P/Equipment | QTY / DENO       | Model | SR NO OF PR | MANUF ADO   | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------|---|-------------|------------------|-------|-------------|---|---------------|----------------|--|-----------|
|       |          |                 | BREAKER<br>4AMP 220V AC   |             |                  | POLE  |             | PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674   |               |                | GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC.</u>  |           |
| 16    | SNF54637 | 0102-034006-226 | 599978515447<br>5 / OVER IOAD<br>SS3-120 (0-120 AMP)<br>Range 01 – 120 Amp (Adjustable) | L/PAC       | 30 / EACH/NUMBER |       | 100-125 PSI | ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674 | CHINA         |                | <u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR ( MAC ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR ( MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR ( MAC ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP</u> |           |

| S. No | LPR No   | PART NO         | NSN / Description                            | P/Equipment                   | QTY / DENO       | Model          | SR NO OF PR   | MANUF ADO  | Availability              | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------|--|-------------------------------|------------------|----------------|---------------|--|---------------------------|----------------|--|-----------|
|       |          |                 |  |                               |                  |                |               |  |                           |                | (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR ( MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known. |           |
| 17    | DNZ63244 | 3050944         | 5330014964338 / FLANGE GASKET                | Cummins QSK38 DM Main Engine  | 1 / EACH/NUMBER  | QSK38-DM       | 33170174      | Cummins, Engine Co. Ltd  | Cummins                   |                | TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A   |           |
| 18    | DNJ52898 | 94702-00400     | 2815765220582 / PLUG SPARK(NGK LFR6A-11)     | F115A,00 (68V) OBM ENGINE     | 4 / EACH/NUMBER  | F115A,00 (68V) | 68V-X-1162973 | YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954   | YAMAHA MOTOR CO LTD       |                | TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -  |           |
| 19    | DNF59976 | 0103-034021-250 | 6685785154496 / THERMOCOUPLE 5M              | H/PAC                         | 10 / EACH/NUMBER |                |               | ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674  | CHINA                     |                | TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.                                  |           |
| 20    | SNF53944 | ST895           | 6625785204896 / LCD CCTV CAMERA VIDEO TESTER | ST895 Camera Video Tester Set | 1 / SET          | ST895          | -             | Wanglu Tech Co.Ltd 5/F,No.3building,He GuangWu Heng Road, Shangshe,TianHe district, Guang Zhou,China Overseas Market Tel:+86-(0)20-87566118 Fax: +86-(0)20-38075108 E-mail: cctvtester@wanglu.com.cn | Wanglu Technology Co. Ltd |                | TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cablesGENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video                               |           |

| S. No | LPR No   | PART NO         | NSN / Description  | P/Equipment                   | QTY / DENO       | Model  | SR NO OF PR | MANUF ADO  | Availabili ty             | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------|--|-------------------------------|------------------|--------|-------------|--|---------------------------|----------------|--|-----------|
|       |          |                 |  |                               |                  |        |             |  |                           |                | monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables  |           |
| 21    | DNF58400 | ST895           | 662578520489<br>6 / LCD CCTV CAMERA VIDEO TESTER           | ST895 Camera Video Tester Set | 2 / SET          | ST895  | -           | Wanglu Tech Co.Ltd<br>5/F,No.3building,He GuangWu Heng Road, Shangshe,TianHe district, Guang Zhou,China Overseas Market<br>Tel:+86-(0)20-87566118<br>Fax: +86-(0)20-38075108<br>E-mail: cctvtester@wanglu.com.cn | Wanglu Technology Co. Ltd |                | <u>TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables</u><br><u>GENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables</u> |           |
| 22    | SNF48507 | 5025            | 056875520031<br>3 / ELECTRICAL SOCKET WITH WATER PROOF BOX | ELECTRICAL SOCKET 5025 ITALY  | 25 / EACH/NUMBER | 5025   | NIL         | MARLIN VILL, ITALY   | BTICINO MAGIC SYSTEM      |                | <u>TECHNICAL SPECIFICATION - OEM &amp; COUNTRY OF ORIGIN: BTICINO &amp; ITALY BTICINO SOCKET WITH WATER PROOF BOX MODEL NO 5025 15 AMPAR AND 250 VOLTS</u><br><u>GENERAL SPECIFICATION - OEM &amp; COUNTRY OF ORIGIN: BTICINO &amp; ITALY BTICINO SOCKET WITH WATER PROOF BOX MODEL NO 5025 15 AMPAR AND 250 VOLTS</u>   |           |
| 23    | DNF59977 | 0103-034021-249 | 668578515449<br>7 / THERMOCOUPLE 6M                        | H/PAC                         | 10 / EACH/NUMBER | FKE 6M |             | ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674  | CHINA                     |                | <u>TECHNICAL SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.</u><br><u>GENERAL SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.</u>   |           |

| S. No | LPR No   | PART NO              | NSN / Description                               | P/Equipment  | QTY / DENO       | Model               | SR NO OF PR       | MANUF ADO  | Availability               | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------|---|--|------------------|---------------------|-------------------|--|----------------------------|----------------|--|-----------|
| 24    | DNF59978 | 0103-034021-248      | 6685785154498 / THERMOCUPLE 7M                  | H/PAC  | 10 / EACH/NUMBER | FKC7M               |                   | ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674  | CHINA                      |                | <u>TECHNICAL SPECIFICATION - MAKE: ALPINE SOURCE OF AVAILABILITY: ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. GENERAL SPECIFICATION - MAKE: ALPINE SOURCE OF AVAILABILITY: ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.</u> |           |
| 25    | DNM62672 | 233-5182             | 2940015348709 / Filter Element As-Air (Primary) | Caterpillar Emergency DG Marine Genset C 4.4 USA   | 3 / EACH/NUMBER  | Marine Genset C 4.4 | CAT00C715GTY00677 | CATERPILLAR INC PEORIAL IL 61629 US  | CATERPILLAR USA            |                | <u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u><br><u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>   |           |
| 26    | SNF45530 | C60HC33232A          | 5925735228333 / BREAKER TRI POLE                | STEERING CONTROL                                   | 2 / EACH/NUMBER  |                     | NIL               | M/S FATEK AUTOMATION CORPORATION 26FL,No 29,Sec.2, jung,jeng E Road Danshuei Dist, New Taipei city 25170,Taiwan, R.O.C. TEL : +886-2-2808-2192 FAX : +886-2-2809-2618. | FATEK TAIWAN               |                | <u>TECHNICAL SPECIFICATION - SCHNIDER</u><br><u>GENERAL SPECIFICATION - SCHNIDER</u>   |           |
| 27    | DNM63515 | 5284228              | 2815715193133 / NOZZLE PISTON COOLING           | CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA | 6 / EACH/NUMBER  | QSB6.7-305MD        |                   | M/s Cummins Inc 500 Jackson Street Columbus IN, USA  | M/s IMPEX NINE INC         |                | <u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u><br><u>GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>   |           |
| 28    | DNF53510 | EZC250H3200          | 5925735177780 / 160A CIRCUIT BREAKER            | PORTAL CRANE                                       | 4 / EACH/NUMBER  |                     |                   | ISTANBUL AVRUPA VINC GEMI EKIMANLARI SAN. VETIC.LTD.STI. Guzelyali Mah. Manolya Sok. No:15/2 Pendik/Istanbul/TURKIYE. Tel: +90(216) 392 25 51, +90(216)392 29 83       | SCHNEIDER                  |                | <u>TECHNICAL SPECIFICATION - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER</u><br><u>GENERAL SPECIFICATION - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER</u>   |           |
| 29    | DGP63782 | CS-WDC09-655-BAA/CMW | 7125705141418 / 9U WALL MOUNT 19" CABINET       | NET WORKING  | 1 / EACH/NUMBER  | NO DATA AVAILABLE   |                   | CH   | M/S RAISECOM SUITE NO.401A |                | <u>TECHNICAL SPECIFICATION - CONTECH BRAND</u><br><u>GENERAL SPECIFICATION - CONTECH BRAND</u>   |           |



| S. No | LPR No   | PART NO                             | NSN / Description  | P/Equipment                | QTY / DENO       | Model                   | SR NO OF PR | MANUF ADO  | Availability   | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-------------------------------------|--|----------------------------|------------------|-------------------------|-------------|--|--|----------------|---|-----------|
|       |          | 9U                                  |  |                            |                  |                         |             |  | PANURAMA CENTRE 2 RAJA GHAZAN FAR ALI ROAD SADDAR KARACHI PHON NO. 021-35661550 -1 |                |   |           |
| 30    | SNF59933 | 32M50A                              | 5920795173071 / INPUT FUSE 32M50A (F1-F3)                    | TRANSFORMER RECTIFIER UNIT | 4 / EACH/NUMBER  |                         |             | Powerstax plc, Unit 5, Armstrong, Mall, South wood, Business Park, Farnborough, GU14 oNR, UNITED KINGDOM Website: www.powerstaxplc.com E-mail: sales@powerstaxplc.com UK/Europe: +44 1252 407800 | DP ENERGY SERVICE S LTD, WICKFORD (VALUE ADDITIONS L                               |                | <u>TECHNICAL SPECIFICATION</u> - Item Used In All (11 in No?s) Main Transformer Rectifier Units As Input Fuse (400VAC, ±5%, 32 Amps) <u>BUSSMANN GENERAL SPECIFICATION</u> - Item Used In All (11 in No?s) Main Transformer Rectifier Units As Input Fuse (400VAC, ±5%, 32 Amps) <u>BUSSMANN</u>  |           |
| 31    | SNF56589 | ML-1102S-A & B(2 RJ-45 PORTS)/ 4V1D | 6030705215937 / FIBER OPTIC MEDIA CONVERTER FOR IP CAMERAS   | CCTV SYSTEM 4V1D PAKISTAN  | 15 / PAIR        | ml-1102s-a & ml-1102s-b |             | Al-Sa'ee business Solutions Suit 30, 3rd Floor, Crown Centre Plot SB-1, Opp Bait-ul-Mukarram Masjid, Gulshan-e-Iqbal Karachi Tel & Fax (9221)3483-7233   | Al-Sa'ee/Pro Secure  |                | <u>TECHNICAL SPECIFICATION</u> - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. <u>GENERAL SPECIFICATION</u> - MODEL NUMBER: ML-1102S-A ML-1102S-B (2 RJ-45 PORTS) oem: MICROLINK Branded Fiber Optic Media Converter for IP Cameras-100mbps/ 1000mbps ? Gigabyte Transmission. |           |
| 32    | DNF53913 | 6-FMX-100B/cmbt-g-12-150            | 6140785221249 / MAINTENANCE FREE BATTERIES 12 VOLT 90-100 AH | Microwave                  | 25 / EACH/NUMBER | Crown Micro             |             | WAREHOUSE NO.CA02, Near R/A08, Jebel Ali Freezone, Dubai, UAE Phone(INTERNATIONAL) +971-4-883-9373 AX +971-4-883 9756  | CROWN MICRO AGM CHINA  |                | <u>TECHNICAL SPECIFICATION</u> - required for backup supply for microwave <u>GENERAL SPECIFICATION</u> - required for backup supply for microwave   |           |

| S. No | LPR No   | PART NO      | NSN / Description                                | P/Equipment      | QTY / DENO       | Model    | SR NO OF PR | MANUF ADO   | Availability   | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------|--|------------------|------------------|----------|-------------|---|--|----------------|--|-----------|
| 33    | DNF56271 | PATCH CHORDS | 599570522990<br>7 / PATCH CHORDS FIBER (SC - LC) | PSS SYSTEM       | 1 / EACH/NUMBER  | sm-sc-lc |             | LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN  | LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN |                | <u>TECHNICAL SPECIFICATION - PATCH CHORDS FIBER (SC - LC)</u><br><u>GENERAL SPECIFICATION - PATCH CHORDS FIBER (SC - LC)</u>   |           |
| 34    | DNA42656 | 34235        | 533070516433<br>4 / KIT VALVE                    | SEA WATER PUMP   | 2 / EACH/NUMBER  | 3535     |             | DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104 | DESTO ISLAMABAD                                      |                | <u>TECHNICAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104</u><br><u>GENERAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104</u> |           |
| 35    | DNA49890 | 34235        | 533070516433<br>4 / KIT VALVE                    | SEA WATER PUMP   | 2 / EACH/NUMBER  | 3535     |             | DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104 | DESTO ISLAMABAD                                      |                | <u>TECHNICAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104</u><br><u>GENERAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104</u> |           |
| 36    | SNM43441 | 6659861      | 433071517870<br>7 / FILTER ELEMENT               | AZIMUTH THRUSTER | 12 / EACH/NUMBER |          |             | ROLLS ROYCE OY AB, Rauma, Finland   | ROLLS ROYCE  |                | <u>TECHNICAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM</u><br><u>GENERAL SPECIFICATION - MAKE: ROLLS ROYS FILTER ELEMENT FOR AZIMUTH THRUSTER STEERING SYSTEM</u>   |           |
| 37    | SNF4133  | DILM65 /     | 611072518327                                     | HPAC             | 3 /              | DILM65   |             | JP SAUREC & SOHN  | JP   |                | <u>TECHNICAL SPECIFICATION -</u>   |           |

| S. No | LPR No   | PART NO                        | NSN / Description  | P/Equipment   | QTY / DENO        | Model                       | SR NO OF PR | MANUF ADO   | Availability                                       | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------------------|--|---|-------------------|-----------------------------|-------------|---|--|----------------|--|-----------|
|       | 2        | EATON XTCE065D00               | 8 / MAIN CONTRACTOR 380V 150 AMPARE  |   | EACH/NUMBER       | (MOELLER) /EATON XTCE065D00 |             | MASCHINEN GMBH GERMANY  | SAUREC & SOHN MASCHINEN GMBH                       |                | MAKE: (MOELLER) EATON HPAC WP5500, AUX CONTACTOR RELAY, DIL ER-40<br><u>GENERAL SPECIFICATION - MAKE:</u><br>(MOELLER) EATON HPAC WP5500, AUX CONTACTOR RELAY, DIL ER-40   |           |
| 38    | DPK63936 | 841GB                          | 9150795160135 / DEKS OLJE D.2 FLEXIBLE HIGH GLOSS FINISH (01 LITER Pack) OEM = OWATROL | SHIP WOODEN STRUCTURE, HULL                         | 30 / LITER        |                             |             | MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL: +33(0) 160 86 48 70, FAX: +38 (0) 160 88 84 84-LEQUAL | OWATROL-DURIEU GROUP-BP75-                         |                | <u>TECHNICAL SPECIFICATION - MANUFACTURE ADDRESS:</u><br>OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL:+33(0) 160 86 48 70, FAX:+38 (0) 160 88 84 84-LEQUAL<br><u>GENERAL SPECIFICATION - MANUFACTURE ADDRESS:</u><br>OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL:+33(0) 160 86 48 70, FAX:+38 (0) 160 88 84 84-LEQUAL   |           |
| 39    | SNF51787 | B 22 CDL                       | 6240785157419 / PHILPS TORNADO ENERGY SAVER(PIN TYPE)110V AC 6500                      | LIGHTING SYSTEM                                     | 400 / EACH/NUMBER |                             |             | MADE IN CHINA 2009 KONIN KLIJKE PHILPS ELECTRIC WWW.PHILPS.COM.   | MADE IN CHINA 2009 KONIN KLIJKE PHILPS ELECTRIC WW |                | <u>TECHNICAL SPECIFICATION - 24 WATT 110 V AC 6500K COOL DAYLIGHT 1450 LUMAN 63 1M/W PIN TYPE</u><br><u>GENERAL SPECIFICATION - 24 WATT 110 V AC 6500K COOL DAYLIGHT 1450 LUMAN 63 1M/W PIN TYPE</u>   |           |
| 40    | DNS52732 | MRN-102-051/ CODE257, CODE 269 | 4510FT1008599 / Muslim Shower  | MRN Shower Wet Unit (with Wall Model Vacuum Toilet) | 20 / EACH/NUMBER  | MERCAN, MRN Shower Wet Unit | 0           | DERI ORGANIZE SANAYI BOLGESI 7. YOL F 7 PARSEL TUZLA  | MERCAN GEMICILIK SAN. VE TIC. A.S.                 |                | <u>TECHNICAL SPECIFICATION - likely supplier: SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-3240447.</u><br><u>GENERAL SPECIFICATION - likely supplier: SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-3240447.</u> |           |
| 41    | SNF54655 | S.NO 58071                     | 6625795136599 / AMPERE METER RANGE 0-500AMPS (DC)                                      | 110VDC RECTIFIER                                    | 8 / EACH/NUMBER   | 44C4                        |             | GR  | SIEMENS GERMANY                                    |                | <u>TECHNICAL SPECIFICATION - -</u><br><u>GENERAL SPECIFICATION - -</u>   |           |

| S. No | LPR No   | PART NO          | NSN / Description   | P/Equipment  | QTY / DENO              | Model                                  | SR NO OF PR | MANUF ADO  | Availabili ty | Tender Remarks                  | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------|---|--|-------------------------|--|-------------|--|---------------|---------------------------------|--|-----------|
|       |          |                  | SHUNT RATIO:<br>45MV SIZE<br>96MM2<br>X96MM2  |  |                         |  |             |  |               |                                 |  |           |
| 42    | DNF57360 | S.NO 58071       | 662579513659<br>9 / AMPERE<br>METER<br>RANGE 0-<br>500AMPS (DC)<br>SHUNT RATIO:<br>45MV SIZE<br>96MM2<br>X96MM2 | 110VDC<br>RECTIFIER                                  | 5 /<br>EACH/N<br>UMBER  | 44C4                                   |             | GR   |               | SIEMENS<br>GERMAN<br>Y          | <u>TECHNICAL SPECIFICATION - -</u><br><u>GENERAL SPECIFICATION - -</u>   |           |
| 43    | SNM53815 | 298-3484         | 597571522872<br>4 / PLUG  | 50KVA ALLIED<br>CAT DG 400<br>VOLTS 3<br>PHASE 50 HZ | 24 /<br>EACH/N<br>UMBER | N/A                                    | E3S01292    | CATERPILLAR INC<br>MANAGER ,CUSTOMER<br>SERVICE,ENGINE<br>DIVISION MOSSVILLE<br>BLDG AC P.O.BOX 610<br>MOSSVILLE,LLLINOIS<br>61552-0610 COUNTRY<br>USA |               | ALLIED<br>CAT                   | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>   |           |
| 44    | DNJ47560 | 884408A08        | 291001562814<br>7 / VALVE,<br>FUEL SYSTEM   | Mercury OBM<br>Engine                                | 4 /<br>EACH/N<br>UMBER  | 300 HP<br>Mercury                      | 2B469929    | Murcery Marine W6250<br>Pioneer Road Fond du Lac<br>Wisconsin USA  |               | Murcery<br>Marine<br>USA        | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>   |           |
| 45    | DPK63856 | MOBILITH<br>AW-2 | 915001514873<br>3 / GREASE<br>GENERAL<br>PURPOSE/<br>MOBILITH AW-<br>2 (PACKING<br>18KG)                        | RHIB (DAVIT)   | 1 / CAN                 |  |             | MOBIL OIL CORP<br>AVIATION &<br>GOVERNMENT SALES<br>DIV 3225 GALLOWS RD<br>FAIRFAX VA UNITED<br>STATES<br>PSC: 22037-4872 TEL:<br>703-846-4090         |               | MOBIL<br>OIL<br>CORP            | <u>TECHNICAL SPECIFICATION -</u><br>HIGH PERFORMANCE LITHIUM<br>COMPLES GREASE COLOUR<br>GREEN ORDOR MILD NEGLIGIBLE<br>SUITABLE FOR LUBRICATING<br>CAMS WAYS AND OTHER SLIDING<br>ELEMENTSGENERAL<br>SPECIFICATION - HIGH<br>PERFORMANCE LITHIUM<br>COMPLES GREASE COLOUR<br>GREEN ORDOR MILD NEGLIGIBLE<br>SUITABLE FOR LUBRICATING<br>CAMS WAYS AND OTHER SLIDING<br>ELEMENTS |           |
| 46    | DNF47198 | SRV6KI           | 613071519494<br>3 / 06 KVA ON<br>LINE UPS   | SMART-UPS<br>ON-LINE5                                | 2 /<br>EACH/N<br>UMBER  | Smart-<br>UPS On-<br>Line SRC<br>230 V |             | Schneider Electric<br>Industries SAS<br>USA<br>www.schneider-electric.com<br>998-1269702_US<br>+ 971 4 7099333 USA                                     |               | APC by<br>Schneider<br>Electric | <u>TECHNICAL SPECIFICATION -</u><br>Power Rating : 06KVA/3500 W<br>Nominal Output Voltage : 220 Vac<br>singe-phase UPS Nominal Input<br>Voltage : 220/230 Vac singe-phase<br>UPS Input Frequency Range : 40 ?<br>70 Hz Output Frequency : 50/60 Hz   |           |

| S. No | LPR No   | PART NO      | NSN / Description  | P/Equipment                    | QTY / DENO       | Model              | SR NO OF PR | MANUF ADO   | Availabili ty                    | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------|--|--------------------------------|------------------|--------------------|-------------|---|----------------------------------|----------------|---|-----------|
|       |          |              |  |                                |                  |                    |             |   |                                  |                | Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES. <u>GENERAL SPECIFICATION</u> - Power Rating : 06KVA/3500 W Nominal Output Voltage : 220 Vac single-phase UPS Nominal Input Voltage : 220/230 Vac single-phase UPS Input Frequency Range : 40 ? 70 Hz Output Frequency : 50/60 Hz Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES.  |           |
| 47    | SNF56594 | CAT-6A U-FTP | 5995785207850 / CABLE NETWORK CAT-6A U-FTP 23AWG PE-0.36MM 4/U-FTP PVC/LSZH-0.5 MM AQUA/BLUE/G RAY7.47MM | CCTV System CAT-6A U-FTP CHINA | 2500 / FOOT      | CAT-6A U-FTP       | NA          | No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883  | CHINA                            |                | <u>TECHNICAL SPECIFICATION</u> - oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION</u> - oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 |           |
| 48    | DNO46374 | NPX-35       | 6140015237323 / SEALED LEAD ACID BATTERY 12V, 35W, 15 MIN  | UPS                            | 10 / EACH/NUMBER |                    |             | ENERSYS 1835 FOREST DR D4 ANNAPOLIS MD UNITED STATES PSC: 21401-4432 TEL: 800-820-4814 FAX: 410-268-1196 EMA: ENERSYS@VERIZON.NET | ENERSYS ANNAPO LIS, USA          |                | <u>TECHNICAL SPECIFICATION</u> - 12V, 35W, 15 MIN <u>GENERAL SPECIFICATION</u> - 12V, 35W, 15 MIN   |           |
| 49    | SNF18351 | 5SX4106-7    | 5925123535276 / MCB-SINGLE POLE 6A   | D/G                            | 2 / EACH/NUMBER  | NO DATA AVAILAB LE |             | PK  | SIEMEN PAKISTA N ENGINEE RING CO |                | <u>TECHNICAL SPECIFICATION</u> - -<br><u>GENERAL SPECIFICATION</u> - -  |           |

| S. No | LPR No   | PART NO                              | NSN / Description                                    | P/Equipment            | QTY / DENO        | Model              | SR NO OF PR | MANUF ADO  | Availabili ty   | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------------------------|--|------------------------|-------------------|--------------------|-------------|--|---|----------------|--|-----------|
|       |          |                                      |  |                        |                   |                    |             |  | LTD AUTOMA TION&DR IVE DIVISION BU SMALL&L ARGE B-72ESTAT E AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700 |                |  |           |
| 50    | SNF54183 | OK-12SW-103-EE                       | 5945715134550 / 24V RELAY                            | 60 TONS A/C PLANT      | 14 / EACH/N UMBER | NO DATA AVAILAB LE |             | US   | CARRIER USA   |                | <u>TECHNICAL SPECIFICATION - -</u><br><u>GENERAL SPECIFICATION - -</u>   |           |
| 51    | SNM56750 | 722300288                            | 5999715227677 / POWER LOGIC BOARD                    | AIR CONDITION          | 1 / EACH/N UMBER  | A-288D             | 52683139    | DOMETIC CORPORATION ENVIRONMENTAL SYSTEMS PO BOX 15299 RICHMOND, VA 23227-0699 USA www.cruisair.com 804 746 1313 | USA   |                | <u>TECHNICAL SPECIFICATION -</u><br>Power Logic Board is used to control the Parameters of the Air Conditioning Unit<br><u>GENERAL SPECIFICATION -</u> Power Logic Board is used to control the Parameters of the Air Conditioning Unit    |           |
| 52    | SNF51842 | CC-22                                | 6350705148004 / BELL ELECTRICAL 220 VAC 1 PHASE .25A | 12.7 MM GUN ALARM SYS. | 5 / EACH/N UMBER  |                    |             | DIGI-TECH NO2,NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482                                | DIGI-TECH   |                | <u>TECHNICAL SPECIFICATION -</u><br>DIGI-TECH NO2,NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482<br><u>GENERAL SPECIFICATION -</u> DIGI-TECH NO2, NEW MEMON CHAMBERS ALTAF HUSSAIN ROAD KARACHI, TEL: 2639514,2638482 |           |
| 53    | DNF58185 | APC BRAND / P-0154000 / APC SRT6KXLI | 6130785166753 / UPS 6KVA-2H O/P 220V 6000VA          | PSS (CCTV SYS)         | 1 / EACH/N UMBER  | APC BRAND          |             | M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China                                  | M/s CETC Internatio nal CO., LTD  |                | <u>TECHNICAL SPECIFICATION -</u><br>OEM & SOA:M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS<br><u>GENERAL SPECIFICATION -</u> OEM & SOA:M/S                                     |           |

| S. No | LPR No   | PART NO      | NSN / Description   | P/Equipment                         | QTY / DENO       | Model        | SR NO OF PR   | MANUF ADO  | Availabili ty | Tender Remarks      | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------|---|-------------------------------------|------------------|--------------|---|--|---------------|---------------------|--|-----------|
|       |          |              |   |                                     |                  |              |   |  |               |                     | CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . BACKUP TIME: 30-35 MINS   |           |
| 54    | DGP64041 | HP4000/cl11h | 7025715133409 / BIO METRIC TIME AND ATTANDANCE MACHINE HP-4000              | TIME AND ATTANDANCE MACHINE         | 2 / EACH/NUMBER  | HP4000/CL11H |   | US   |               | RSI(IR) USA         | <p><u>TECHNICAL SPECIFICATION</u> - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name &amp; Time of Thumb impression <u>GENERAL SPECIFICATION</u> - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name &amp; Time of Thumb impression</p> |           |
| 55    | DNS48157 | 145 015      | 5315145538066 / VALVE TAPPET ROLLER KIT (2)[TWO KITS REQUIRED PER CYLINDER] | WARTSILA MAIN ENGINE 9L20C3 FINLAND | 18 / EACH/NUMBER | 9L20C3       | MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244 | Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380 |               | Wartsila Finland Oy | <p><u>TECHNICAL SPECIFICATION</u> - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20 <u>GENERAL SPECIFICATION</u> - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20</p>   |           |

| S. No | LPR No   | PART NO          | NSN / Description                       | P/Equipment  | QTY / DENO       | Model              | SR NO OF PR  | MANUF ADO  | Availability                             | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------|---|--|------------------|--------------------|--|--|--|----------------|--|-----------|
| 56    | DNS47931 | 111 003          | 2815145537848 / NUT-9L20 CONNECTING ROD | WARTSILA MAIN ENGINE 9L20C3 FINLAND                      | 54 / EACH/NUMBER | 9L20C3             | MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244 | Wartsila Finland Oy<br>Vaasa Factory<br>Tarhaajantia 2, FIN-65101<br>Vaasa, Finland<br>Tel.<br>+358 10 708 0000, Tix<br>74251 wa sf<br>Fax (Service) ,358 6 356<br>7355<br>Fax (Spare parts) +358 10<br>709 1380 | Wartsila<br>Finland<br>Oy                |                | <u>TECHNICAL SPECIFICATION - TPI</u><br><u>GENERAL SPECIFICATION - TPI</u>   |           |
| 57    | DNM62734 | 981-482          | 5305795198597 / METRIC BOLT             | PERKIN DG P-275H-2 UK                                    | 6 / EACH/NUMBER  | P-275H-2           | WS55451614661  | PERKIN UK  | PERKIN<br>UK                             |                | <u>TECHNICAL SPECIFICATION - 250 KVA PERKIN DG</u><br><u>GENERAL SPECIFICATION - 250 KVA PERKIN DG</u>   |           |
| 58    | SNS41598 | 8148038          | 3120270354470 / BEARING SHELL           | VOLVO PENTA SSDG D9A2A MG HE SWEDEN                      | 15 / EACH/NUMBER | D9A MG HE          | SEE GEN SPECS  | AB Volvo Penta<br>SE-405 08 Göteborg,<br>Sweden<br>Tel: +46 31 23 54 60  | AB Volvo<br>Penta<br>Sweden              |                | <u>TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u><br><u>GENERAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>   |           |
| 59    | SNM29199 | 3583443/21718912 | 2910145458894 / FUEL FILTER             | PROPULSION AND STEERING SYSTEM/ MAIN ENGINE VOLVO D6-370 | 20 / EACH/NUMBER | NO DATA AVAILAB LE |  | OC   | VOLVO<br>PENTA<br>GOTEBU<br>RG<br>SWEDEN |                | <u>TECHNICAL SPECIFICATION - -</u><br><u>GENERAL SPECIFICATION - -</u>   |           |
| 60    | SNM51624 | 2WB250-25        | 4810785195851 / SOLENOID VALVE          | FIRE MAIN SYSTEM   | 1 / EACH/NUMBER  | 2WB250-25          | NIL  | YUEQING RIGHTEIGHT PNEAMATIC CO LTD CHINA  | CHINA                                    |                | <u>TECHNICAL SPECIFICATION - Valve Body Material: Brass Function: 2/2 Way Normally Closed Port Size: 1", DN25 Voltage: AC110V, AC220V, DC24V, DC12V Action Type: Semi Direct Operated Orifice Size: 25mm Fluid Temperature: -5°C - +80°C Diaphragm Material: NBR, Viton, EPDM Working Pressure: 0-7 Bar Medium: Water, Oil, Gas, Air SOLENOIED VALVE DIA 1 INCH , OPERATED BY 220 V AC SUPPLY INSTALLED IN FIREMAIN MAGAZINE SPRINKLING SYSTEM</u><br><u>GENERAL</u> |           |



| S. No | LPR No   | PART NO      | NSN / Description  | P/Equipment                | QTY / DENO             | Model                    | SR NO OF PR | MANUF ADO  | Availability | Tender Remarks                  | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------|--|----------------------------|------------------------|--------------------------|-------------|--|--------------|---------------------------------|---|-----------|
|       |          |              |  |                            |                        |                          |             |  |              |                                 | SPECIFICATION - Valve Body<br>Material: Brass Function: 2/2 Way<br>Normally Closed Port Size: 1", DN25<br>Voltage: AC110V, AC220V, DC24V,<br>DC12V Action Type: Semi Direct<br>Operated Orifice Size: 25mm Fluid<br>Temperature: -5°C - +80°C<br>Diaphragm Material: NBR, Viton,<br>EPDM Working Pressure: 0-7 Bar<br>Medium: Water, Oil, Gas, Air<br>SOLENOID VALVE DIA 1 INCH ,<br>OPERATED BY 220 V AC SUPPLY<br>INSTALLED IN FIREMAIN<br>MAGAZINE SPRINKLING SYSTEM |           |
| 61    | SNF51969 | DVP04ADS     | 702570517977<br>7 / PLC<br>EXTENSION<br>(ANALOG TO<br>DIGITAL) | PORTAL<br>CRANE FD-IV      | 2 /<br>EACH/<br>NUMBER | DVP-SV2                  | NIL         | DELTA ELECTRONICS<br>INS. TAOUYUAN<br>TECHNOLOGY CENTRE<br>NO.18 XINGLONG RD.<br>TAOUYUAN CITY<br>TAOUYUAN COUNTY<br>33068, TAIWAN TELE:886-<br>3-362-6301, FAX:886-3-<br>371-6301 |              | DELTA<br>ELECTR<br>ONIS<br>INC. | TECHNICAL SPECIFICATION -<br>INPUT VOLTAGE: 10 VAC TO +10<br>VAC, CURRNET : -20MA TO +20<br>MA, INPUT RESOLUTION : 14-BIT<br>BUILT-IN RS-485<br>INTERFACE<br>GENERAL<br>SPECIFICATION - INPUT<br>VOLTAGE: 10 VAC TO +10 VAC,<br>CURRNET : -20MA TO +20 MA,<br>INPUT RESOLUTION : 14-BIT<br>BUILT-IN RS-485 INTERFACE  |           |
| 62    | SNF51918 | DVPPS05      | 702570517977<br>9 / PLC<br>POWER<br>SUPPLY UNIT                | PORTAL<br>CRANE FD-IV      | 2 /<br>EACH/<br>NUMBER | DVP-SV2                  | N/A         | DITD CONTRACT<br>PD/2400/5/P CRANE FD-<br>IV/12/SR&C/1024  |              | DELTA<br>ELECTR<br>ONIS<br>INC  | TECHNICAL SPECIFICATION - 1-<br>PHASE, INPUT :100-240 VAC,<br>OUTPUT: 24 V DC, POWER<br>120W<br>GENERAL SPECIFICATION -<br>1-PHASE, INPUT :100-240 VAC,<br>OUTPUT: 24 V DC, POWER 120W  |           |
| 63    | DNQ61841 | B1<br>PRENEC | 597099522452<br>6 / TAPE<br>INSULATING<br>38MM                 | TAPE<br>INSULATING<br>(FF) | 3 /<br>ROLL            | NO DATA<br>AVAILAB<br>LE |             | UK   |              | UK<br>ENGLAN<br>D               | TECHNICAL SPECIFICATION -<br>NIMAGE:K4723 M/S DUNLOP<br>GREENGATE (STROMPROFING<br>LTD) MOSS ROSE MILL,<br>SPRINGFIELD ROAD KERSLEY,<br>BOLTON UNITED KINGDOM BL4<br>8JW TEL 01204 466 74, FAX 01204<br>861 333 EMA lesley.minton@john-<br>holden.com www www.JOHN-<br>HOLDEN.COM ITEMS REQUIRED<br>ON VALID PART NUMBER AS PER<br>NMCRL<br>GENERAL<br>SPECIFICATION - NIMAGE:K4723<br>M/S DUNLOP GREENGATE   |           |

| S. No | LPR No   | PART NO          | NSN / Description                                     | P/Equipment                        | QTY / DENO        | Model              | SR NO OF PR   | MANUF ADO   | Availabili ty | Tender Remarks               | TECH / GEN SPECS  | Dimension |
|-------|----------|------------------|---|------------------------------------|-------------------|--------------------|---------------|---|---------------|------------------------------|---|-----------|
|       |          |                  |   |                                    |                   |                    |               |   |               |                              | (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL  |           |
| 64    | DNQ62372 | B1 PRENEC        | 597099522452<br>6 / TAPE INSULATING 38MM              | TAPE INSULATING (FF)               | 2 / ROLL          | NO DATA AVAILAB LE |               |   | UK            | ENGLAN D                     | TECHNICAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL</u> |           |
| 65    | SNF51754 | ACC24 25BB-3     | 592572512913<br>9 / CIRCUIT BREAKER 24VDC, 25AMPS(F8) | CUMMUNICAT ION SYSTEM              | 2 / EACH/N UMBER  |                    |               |   | GR            | DIGI TECH DENSO HALL KARACHI | TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |           |
| 66    | SNJ54842 | 09160-10082      | 531076522250<br>9 / WASHER (105X19X2)                 | SUZUKI DF300AP 300 HP OBM          | 20 / EACH/N UMBER | DF300AP            | 30002P-712896 | SUZUKI MOTOR CO LTD JAPAN   | SUZUKI JAPAN  |                              | TECHNICAL SPECIFICATION - NIL <u>GENERAL SPECIFICATION - NIL</u>  |           |
| 67    | SNV51405 | MBS 33M/MBS 3000 | 668522269384<br>7 / PRESSURE TRANSMITTE R             | SSDG PRESSURE TRANSMITTE R MBS 33M | 3 / EACH/N UMBER  | MBS 33M            | NIL           | DANFOSS A/S, NORDBORGVEJ 81HAVNBJERG, NORDBORG DENMARK TEL;74882222 | DANFOS S A/S  |                              | TECHNICAL SPECIFICATION - TECHNICAL DETAILS OF THE ITEM ARE BEING ATTACHED. <u>GENERAL SPECIFICATION - TECHNICAL DETAILS OF THE</u>   |           |

| S. No | LPR No   | PART NO           | NSN / Description  | P/Equipment   | QTY / DENO             | Model                     | SR NO OF PR    | MANUF ADO  | Availability   | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------|--|---|------------------------|---------------------------|----------------|--|--|----------------|--|-----------|
|       |          |                   |  |   |                        |                           |                | FAX74490949  |  |                | ITEM ARE BEING ATTACHED.   |           |
| 68    | DNQ62018 | 08279009          | 621079517576<br>2 / LIFE RAFT<br>INTERNAL<br>LIGHT &<br>BATTERY                | UK RFD  | 6 /<br>EACH/N<br>UMBER | UK (RFD<br>BEAUFO<br>RT)  | 08279009       | RFD BEAUFORT LTD (UK)  | RFD<br>BEAUFO<br>RT LTD<br>(UK)  |                | <u>TECHNICAL SPECIFICATION -</u><br>LIFE RAFT INTERNAL LIGHT &<br>BATTERY, RFD BEAUFORT LTD<br>(UK) <u>GENERAL SPECIFICATION -</u><br>LIFE RAFT INTERNAL LIGHT &<br>BATTERY, RFD BEAUFORT LTD<br>(UK)  |           |
| 69    | DNF48045 | RES81042<br>BFSCR | 743570521666<br>6 / SERVER<br>RACK F<br>SERIES II<br>RACK 42U<br>800X 1090 C/W | HP SERVER<br>DL 380                                       | 1 /<br>EACH/N<br>UMBER | DL380                     | SGH830X<br>X1T | MS ORA-TECH SYSTEM,<br>FOUR SQUARE PLAZA<br>4TH FLOOR,BUILDING NO<br>21-A, H.H FAROOQI ROAD<br>OFF TARIQ ROAD,<br>PECHS, BLOCK-II,<br>KARACHI. TELEPHONE<br>NO 021-34535933 FAX NO<br>: 021-34536441 | EMERSO<br>N  |                | <u>TECHNICAL SPECIFICATION - F</u><br>Series II Rack 42U 800X 1090 C/W:<br>1. Perforated doors with lock and<br>key. 2. Split side panels .3. EIA<br>mounting rails. 4. levelling feet .5.<br>color black 6. Curved front door A<br>complete Rack includes all of the<br>followings: <u>GENERAL</u><br><u>SPECIFICATION - F Series II Rack</u><br>42U 800X 1090 C/W: 1. Perforated<br>doors with lock and key. 2. Split side<br>panels .3. EIA mounting rails. 4.<br>levelling feet .5. color black 6. Curved<br>front door A complete Rack includes<br>all of the followings: |           |
| 70    | SNS55064 | 8T-0337           | 530501430027<br>7 / Screw-<br>Machine<br>(M4X0.7X12-<br>mm)                    | Caterpillar<br>Emergency DG<br>Marine Genset<br>C 4.4 USA | 8 /<br>EACH/N<br>UMBER | Marine<br>Genset C<br>4.4 | N/A            | 14009 OLD GALENA RD<br>TC-A, MOSSVILLE, IL,<br>61552-7547, U.S.A   | CATERPI<br>LLAR<br>INC. DBA<br>CATERPI<br>LLAR DIV<br>GOVERN<br>MENTAL<br>AND<br>DEFENS<br>E<br>PRODUC<br>TS |                | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>   |           |
| 71    | SNS55056 | 6I-4012           | 530701471489<br>9 / Stud   | Caterpillar<br>Emergency DG<br>Marine Genset<br>C 4.4 USA | 3 /<br>EACH/N<br>UMBER | Marine<br>Genset C<br>4.4 | N/A            | 14009 OLD GALENA RD<br>TC-A, MOSSVILLE, IL,<br>61552-7547, U.S.A   | CATERPI<br>LLAR<br>INC. DBA<br>CATERPI<br>LLAR DIV<br>GOVERN<br>MENTAL<br>AND<br>DEFENS<br>E                 |                | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>   |           |

| S. No | LPR No   | PART NO          | NSN / Description   | P/Equipment                        | QTY / DENO        | Model              | SR NO OF PR | MANUF ADO  | Availabili ty   | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------|---|------------------------------------|-------------------|--------------------|-------------|--|---|----------------|--|-----------|
|       |          |                  |   |                                    |                   |                    |             |  | PRODUC TS   |                |  |           |
| 72    | SNF51783 | 039027           | 4140014847927 / FAN ASSEMBLY 120MM 220VAC                 | ELINT DZ 9000S                     | 6 / EACH/NUMBER   | NO DATA AVAILAB LE |             | CH   | SOUTHW EST CHINA RESEAR CH INSTITUT E OF ELECTR ONIC EQUIPME NT |                | TECHNICAL SPECIFICATION - OEM ADD:SOUTHWEST CHINA RESEARCH INSTITUTE OF ELECTRONIC EQUIPMENTGENERAL SPECIFICATION - OEM ADD: SOUTHWEST CHINA RESEARCH INSTITUTE OF ELECTRONIC EQUIPMENT  |           |
| 73    | SNF52120 | DCC/HFB M/HW/119 | 7050705215677 / HDMI CABLE 25MTR FIBER OPTIC              | OPERATOR CONSOLE DCC-2016 PAKISTAN | 5 / EACH/NUMBER   | NA                 | NA          | Commercially Of The Shelf (COTS)/Local Market  | COTS  |                | TECHNICAL SPECIFICATION - DISPLAY CABLEGENERAL SPECIFICATION - DISPLAY CABLE   |           |
| 74    | DNM54248 | MPU 120          | 2815705216300 / MPU                                       | SSDG                               | 1 / EACH/NUMBER   | MPU 120            |             | M/S SCENARIO INTERNATIONAL, KARACHI PH NO 0324-2636007   | LOCAL   |                | TECHNICAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIERGENERAL SPECIFICATION - OEM : ICA RPM SENSER AMPLIFIER   |           |
| 75    | DNM63133 | 3969562          | 3120015815885 / BEARING, CONNECTING ROD                   | DIESEL GENERATOR QSB7DM            | 6 / EACH/NUMBER   |                    |             | CUMMINS USA  | CUMMIN S  |                | TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARDGENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD   |           |
| 76    | SNF56583 | N1537            | 6110705155260 / ENERGY SAVER 220V-240V ,11W. (screw type) | SELF, FOR DISTRIBUTION SYS.        | 500 / EACH/NUMBER |                    |             | SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. | PHILIPS CO LTD.   |                | TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/1,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi |           |

| S. No | LPR No   | PART NO | NSN / Description                               | P/Equipment                         | QTY / DENO       | Model             | SR NO OF PR   | MANUF ADO  | Availability | Tender Remarks      | TECH / GEN SPECS  | Dimension |
|-------|----------|---------|---|-------------------------------------|------------------|-------------------|---|--|--------------|---------------------|---|-----------|
|       |          |         |   |                                     |                  |                   |   |  |              |                     | 'GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD,ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE:RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address; K-2/l,11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi ' |           |
| 77    | DNH64131 | NIL     | 4120735139117 / AIR CONDITIONER SPLIT 1.5 TONS  | AIR CONDITIONING                    | 2 / EACH/NUMBER  | NO DATA AVAILABLE |   | OC   |              | THILAND             | <u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>  |           |
| 78    | DNS47955 | 100017  | 3110735151601 / Main bearing screw M36          | WARTSILA MAIN ENGINE 9L20C3 FINLAND | 44 / EACH/NUMBER | 9L20C3            | MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244 | Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380 |              | Wartsila Finland Oy | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 79    | DNS47929 | 120021  | 2805735151611 / Valve seat Insert Inlet         | WARTSILA MAIN ENGINE 9L20C3 FINLAND | 72 / EACH/NUMBER | 9L20C3            | MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244 | Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380 |              | Wartsila Finland Oy | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 80    | DNZ63245 | 3635158 | 5330016184710 / THERMOSTAT HOUSING COVER GASKET | Cummins QSK38 DM Main Engine        | 1 / EACH/NUMBER  | QSK38-DM          | 33170174  | Cummins, Engine Co. Ltd  |              | Cummins             | <u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A</u>   |           |

| S. No | LPR No   | PART NO        | NSN / Description                               | P/Equipment                                      | QTY / DENO       | Model               | SR NO OF PR              | MANUF ADO  | Availabili ty  | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------|---|--|------------------|---------------------|--------------------------|--|--|----------------|--|-----------|
| 81    | DNM63778 | 168306         | 5305190044577 / SLOTTED SET SCREW               | Cummins QSK38 DM Main Engine                     | 18 / EACH/NUMBER | QSK38-DM            | 33170174                 | Cummins, Engine Co. Ltd  | Cummins  |                | <u>TECHNICAL SPECIFICATION - Dimension: Length 51mm Dia 12.5 mm</u><br><u>GENERAL SPECIFICATION - Dimension: Length 51mm Dia 12.5 mm</u>   |           |
| 82    | DNM62672 | 233-5182       | 2940015348709 / Filter Element As-Air (Primary) | Caterpillar Emergency DG Marine Genset C 4.4 USA | 3 / EACH/NUMBER  | Marine Genset C 4.4 | N/A                      | 14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A                               | CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS |                | <u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u><br><u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>   |           |
| 83    | DNJ46112 | 6CE-W0078-01   | 4320765203369 / WATER PUMP REPAIR KIT           | YAMAHA OBM                                       | 1 / EACH/NUMBER  | NO DATA AVAILAB LE  | 6CE-1029885, 6CF-1009814 | YAMAHA MOTOR CO. LTD JAPAN   | JAPAN  |                | <u>TECHNICAL SPECIFICATION -</u><br><u>GENERAL SPECIFICATION -</u>   |           |
| 84    | DNM58115 | imp/gp/stb/t01 | 2010715221033 / STERN TUBE FOR 50 MM SHAFT DIA  | SHAFTING ARRANGEMENT                             | 3 / EACH/NUMBER  | NA                  |                          | CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483 | CUMMINS USA  |                | <u>TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u><br><u>GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u> |           |
| 85    | DNM566   | imp/gp/stb/    | 201071522103                                    | SHAFTING   | 4 /              | NA                  |                          | CUMMINS ENGINE CO  | CUMMIN   |                | <u>TECHNICAL SPECIFICATION -</u>   |           |

| S. No | LPR No   | PART NO                                  | NSN / Description  | P/Equipment           | QTY / DENO       | Model       | SR NO OF PR | MANUF ADO  | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--|--|-----------------------|------------------|-------------|-------------|--|---------------|----------------|--|-----------|
|       | 23       | /t01                                     | 3 / STERN TUBE FOR 50 MM SHAFT DIA   | ARRANGEMENT           | EACH/NUMBER      |             |             | 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483 | S USA         |                | STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED<br><br>GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS. INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED |           |
| 86    | DNF56740 | 12X50 Aculon A211                        | 0552790019071 / BINOCULAR 12X50 BLACK  |                       | 10 / EACH/NUMBER | NIKON 12X50 |             |  |               |                | <u>TECHNICAL SPECIFICATION - Nikon 12x50 Black</u><br><u>GENERAL SPECIFICATION - Nikon 12x50 Black</u>   |           |
| 87    | SGE49369 |  | 0461590000976 / PAPER ABRASIVE 9" X11" WATER PROOF MATERIAL GLASS GRADE NO.0   |                       | 3600 / SHEET     | local       |             |  |               |                | <u>TECHNICAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0</u><br><u>GENERAL SPECIFICATION - Paper Abrasive 0"x9"x11" Size 0</u>   |           |
| 88    | SPC29583 | Ratio: brodifacoum 1: absolute alcohol 4 | 0473504730002 / Broadifacoum technical (2.5%) W/V with solubilizer of absolute alcohol (ethyl alcohol 100%) (01 ltr) | De-rating of PN Ships | 3 / BOTTLE       |             |             |  |               |                | <u>TECHNICAL SPECIFICATION - 1. Owner Name: Shahbaz Hussain 2. Contact No. 03458906728 3. Company Name: The IPM Services.</u><br><u>GENERAL SPECIFICATION - 1. Owner Name: Shahbaz Hussain 2. Contact No. 03458906728 3. Company Name: The IPM Services.</u>   |           |
| 89    | DPK5067  | 0474-7021                                | 047450224213   |                       | 50 /             |             |             |  |               |                | <u>TECHNICAL SPECIFICATION - NO</u>  |           |

| S. No | LPR No   | PART NO            | NSN / Description  | P/Equipment | QTY / DENO             | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|--|-------------|------------------------|-------|-------------|-----------|--------------|----------------|---|-----------|
|       | 5        | (0475-99-224-2137) | 7 / TALLOW WHITE (GREASE) (200 KG DRUM)  |             | KILOGR<br>AMME         |       |             |           |              |                | DATA AVAILABLE<br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |           |
| 90    | DPK63527 | XG-250             | 0474509424829 / XG-250 (Silicon Compound DM-3) (18KG Packing)                      |             | 36 /<br>KILOGR<br>AMME |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |           |
| 91    | DGE9015  | nil                | 0350595713121 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM |             | 1080 /<br>FATHO<br>M   |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - 1. MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 &amp; ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1. MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 &amp; ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.</u></u> |           |
| 92    | DGB49047 |                    | 0283595711440 / ROD NAVAL BRASS, RD DIA 0.25 inch, WT PER, FT 18LBS                |             | 110 /<br>METER         |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - BS 12163 &amp; CW719W ALONG WITH, MATERIAL CONDITION: R-340 (OR) Specifications: BSEN 12163 of 1998 Grade 712(M), Running Length (Min): 02 meter</u><br><u>GENERAL SPECIFICATION - BS 12163 &amp; CW719W ALONG WITH, MATERIAL</u>  |           |



| S. No | LPR No   | PART NO            | NSN / Description  | P/Equipment | QTY / DENO       | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------|--|-------------|------------------|-------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                    |  |             |                  |       |             |           |               |                | CONDITION: R-340 (OR)<br>Specifications: BSEN 12163 of 1998 Grade 712(M), Running Length (Min): 02 meter   |           |
| 93    | DGB53081 |                    | 028350283152<br>1 / CADMIUM ANODE ROLLED LG 12 WTH 8 TH 3/8                                      |             | 27 / EACH/NUMBER |       |             |           |               |                | TECHNICAL SPECIFICATION - IS 2602 – 1989, Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm<br>GENERAL SPECIFICATION - IS 2602 – 1989, Cadmium >99.94%. May also contain Copper 50ppm, Lead 250ppm, Thallium 35ppm, Zinc 350ppm   |           |
| 94    | DGB52203 |                    | 028359571145<br>5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)                              |             | 30 / METER       |       |             |           |               |                | TECHNICAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.<br>GENERAL SPECIFICATION - BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.   |           |
| 95    | DPC63746 | NO DATA AVAILAB LE | 044350942222<br>6 / GAS CARBON DIOXIDE TECH (Purity 99.5%) wight 01 to 45 kg with protection cap |             | 135 / KILOGRAMME |       |             |           |               |                | TECHNICAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test Date D. Water Capacity E. Cylinder Weight F. Design Gas<br>GENERAL SPECIFICATION - 1. CGA G-6.2 of 1994 Grade-F. 2. Gas Carbon DI Oxide (99.5% purity) in Buyer's/ Supplier's Returnable Cylinders of Net Weight 01 kg to 45 Kg with Protection Cap. 3. Purity Certificate and OEM Conformi ty Certificate required. 4. Cylinder Marking: A. Serial No B. Test Pressure C. Test |           |

| S. No | LPR No   | PART NO    | NSN / Description  | P/Equipment | QTY / DENO        | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------|--|-------------|-------------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |            |  |             |                   |       |             |           |              |                | Date D. Water Capacity E. Cylinder Weight F. Design Gas  |           |
| 96    | SGE49355 | NIL        | 0413599239287 / TUBING RUBBER LIGHT PRESSURE USE./D19. 5MM TH2. 778MM LG18. 2M |             | 50 / METER        |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - SPECS: BS 1155 (S-50)</u><br><u>GENERAL SPECIFICATION - SPECS: BS 1155 (S-50)</u>   |           |
| 97    | SGB56149 | BS 1210    | 0266599417324 / SCREW, WOOD  |             | 200 / HUNDRED     |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - NSN: 5305-99-941-7324. FASTENER LENGTH: 1.000 INCHES NOMINAL. HEAD STYLE: FLAT COUNTERSUNK. HEAD DIAMETER: 0.312 INCHES MINIMUM &amp; 0.328 INCHES MAXIMUM. GENERAL SPECIFICATION - NSN: 5305-99-941-7324. FASTENER LENGTH: 1.000 INCHES NOMINAL. HEAD STYLE: FLAT COUNTERSUNK. HEAD DIAMETER: 0.312 INCHES MINIMUM &amp; 0.328 INCHES MAXIMUM.</u> |           |
| 98    | DGB51416 | 0267-10598 | 0267599235347 / TEE PIPE EQUAL GALVANISED NOM BORE SZ 2.50                     |             | 50 / EACH/NUMBER  |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENINGS, NOMINAL BORE SIZE: 2.5" (65MM), PROTECTION: GALVANIZED</u><br><u>GENERAL SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENINGS, NOMINAL BORE SIZE: 2.5" (65MM), PROTECTION: GALVANIZED</u>   |           |
| 99    | DGB54585 |            | 0267599235349 / TEE PIPE EQUAL (GALVANISED) 03.00IN                            |             | 50 / EACH/NUMBER  |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm</u><br><u>GENERAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm</u>  |           |
| 100   | DGB53396 |            | 0214590331012 / Stud, Plain (Ends  |             | 390 / EACH/NUMBER |       |             |           |              |                | <u>TECHNICAL SPECIFICATION - DGS 8060 Class 1(B), BS 970, Material Grade: EN 16 (605 M36),</u>   |           |

| S. No | LPR No   | PART NO                       | NSN / Description  | P/Equipment           | QTY / DENO       | Model   | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------------------|--|-----------------------|------------------|---------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                               | Threaded Unequal Lengths), Thread Size: 5/8", Length: 3", Length of Thread: (a.) Metal End: 5/8", (b.) Nut End: 1 1/4" |                       |                  |         |             |           |               |                | Condition: R Thread Size: 5/8 inch, Length: 3 inch, Length of Thread: (a.) Metal End: 5/8 inch, (b.) Nut End: 1 1/4 inch<br><u>GENERAL SPECIFICATION - DGS 8060 Class 1(B), BS 970, Material Grade: EN 16 (605 M36), Condition: R Thread Size: 5/8 inch, Length: 3 inch, Length of Thread: (a.) Metal End: 5/8 inch, (b.) Nut End: 1 1/4 inch</u>  |           |
| 101   | DGB62739 |                               | 0283705711634 / BRAZING ALLOY, SILVER, STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1                         |                       | 5200 / GRAM      |         |             |           |               |                | <u>TECHNICAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u><br><u>GENERAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u> |           |
| 102   | SGB31389 | SPEC DGS/XC11 /103/45         | 0214590035952 / STUD PLAIN BSW DIA 0.625"LG 1.50"THREAD LG 0.875" TPI 11   | USE FOR DECK PLANKING | 50 / TEN         |         |             |           |               |                | <u>TECHNICAL SPECIFICATION - METRIAL GRADE EN 4140</u><br><u>GENERAL SPECIFICATION - METRIAL GRADE EN 4140</u>   |           |
| 103   | DGB63196 | BRAND (MADE IN WEST GERMANY ) | 0243702431004 / AGRICULTURAL SPRAYER MODEL GLORIA (172 RTG) CAPACITY 10 LITER  |                       | 7 / EACH/NUMBER  |         |             |           |               |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 104   | SNF54627 | R51d-12                       | 0584799951110 / LAMP FILAMENT CAP TYPE MESC6V 0.04A 11X23MM  |                       | 25 / EACH/NUMBER | R51D-12 |             |           |               |                | <u>TECHNICAL SPECIFICATION - MESC6V 0.04A 11X23MM CLEAR G SHP B,V (R51D-12)</u><br><u>GENERAL SPECIFICATION - MESC6V 0.04A 11X23MM CLEAR G SHP B,V (R51D-12)</u>   |           |

| S. No | LPR No   | PART NO                       | NSN / Description   | P/Equipment                  | QTY / DENO       | Model                         | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------------------|---|------------------------------|------------------|-------------------------------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                               | CLEAR G SHP B,V   |                              |                  |                               |             |           |              |                |  |           |
| 105   | DNF58527 | JPN-8840                      | 058379942788<br>5 / TORCH-HAND-ELECT  |                              | 9 / EACH/NUMBER  | SOGO HUNTER                   |             |           |              |                | TECHNICAL SPECIFICATION - INPUT 220-240V 50/60Hz RANGE: 1000M BATTERY: 6V 4Ah OUTPUT: 15W Rechargeable time : 20-24Hrs Dimension: 190x122x127mm.<br>GENERAL SPECIFICATION - INPUT 220-240V 50/60Hz RANGE: 1000M BATTERY: 6V 4Ah OUTPUT: 15W Rechargeable time : 20-24Hrs Dimension: 190x122x127mm.   |           |
| 106   | DNF63871 | PAK / GFC/MILL AT/EQUIVALENT  | 056570000004<br>8 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)               | END USE SELF                 | 2 / EACH/NUMBER  |                               |             |           |              |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 107   | DNG50074 | 25010495                      | 294001197710<br>6 / FILTER, ELEMENT, FLUID.                                     | GM DETROIT D/E FOR GRP BOATS | 43 / EACH/NUMBER |                               |             |           |              |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 108   | DNF63772 | MD231 (CROWN) /EH1504 /EH1418 | 444079510254<br>4 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM | DEHUMIDIFIERS                | 1 / EACH/NUMBER  | MD231 (CROWN) /EH1504/ EH1418 |             |           |              |                | TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG<br>GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG |           |
| 109   | DNH63863 |                               | 412070505191<br>9 / AIR CONDITIONER 1.5 TON SPLIT TYPE                          | SELF                         | 2 / EACH/NUMBER  |                               |             |           |              |                | TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)  |           |

| S. No | LPR No   | PART NO               | NSN / Description   | P/Equipment                       | QTY / DENO           | Model   | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------------|---|-----------------------------------|----------------------|---|-------------|-----------|--------------|----------------|---|-----------|
|       |          |                       | COMPLETE  |                                   |                      |   |             |           |              |                | GENERAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)  |           |
| 110   | DNH61798 | NO DATA AVAILAB<br>LE | 4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY | SELF                              | 1 / EACH/N<br>UMBER  | GREE/PE<br>L,<br>MITSBUS<br>HI/<br>DAKEN/<br>GENERA<br>L,<br>GENERA<br>L, LG, |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null  |           |
| 111   | DGB37893 | SKF6317Z<br>Z         | 3110001556338 / BEARING BALL ANNULAR  | DIESEL GENERATOR DORMAN (ENGLAND) | 1 / EACH/N<br>UMBER  |   |             |           |              |                | TECHNICAL SPECIFICATION - SZ: 85X180X41MM SHIELD QTY2, STEEL<br>OVERALL<br>GENERAL<br>SPECIFICATION - SZ: 85X180X41MM SHIELD QTY2, STEEL<br>OVERALL   |           |
| 112   | DGP63955 |                       | 3610705091304 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC DUO   |                                   | 12 / EACH/N<br>UMBER |   |             |           |              |                | TECHNICAL SPECIFICATION - NEW SPECS UPDATED<br>GENERAL<br>SPECIFICATION - NEW SPECS UPDATED   |           |
| 113   | DNJ45823 | 5901-19 (677532260)   | 4720765107645 / RUBBER HOSE   | NIGATA M/ENGINE, (AUTHORITY MRD)  | 4 / EACH/N<br>UMBER  |   |             |           |              |                | TECHNICAL SPECIFICATION - 3" diameter (approx)<br>GENERAL<br>SPECIFICATION - 3" diameter (approx)   |           |
| 114   | DGB54166 | BR3013-SHEET3.1.2     | 4730995311380 / FLANGE PIPE STEEL ROUND 2.500 X6.250X0.562IN  | GENERAL USE                       | 48 / EACH/N<br>UMBER |   |             |           |              |                | TECHNICAL SPECIFICATION - DIMENSION: 2.500 X 6.250 X 0.562 INCHES<br>MATERIAL: SS (316 GRADE)<br>GENERAL<br>SPECIFICATION - DIMENSION: 2.500 X 6.250 X 0.562 INCHES<br>MATERIAL: SS (316 GRADE) |           |
| 115   | DGB53400 | NO DATA AVAILAB<br>LE | 4730705038535 / band pipe m/s 2.5 inch  | DUMP BARGE COUNSTRUCT<br>ION      | 22 / EACH/N<br>UMBER |   |             |           |              |                | TECHNICAL SPECIFICATION - Material: Mild Steel Grade JR275<br>Size: 2.5 inch x 4.775 mm thick   |           |

| S. No | LPR No   | PART NO            | NSN / Description   | P/Equipment                               | QTY / DENO       | Model                | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks  | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|---|---|------------------|----------------------|-------------|-----------|---------------|---|---|-----------|
|       |          |                    |   |   |                  |                      |             |           |               |   | Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) <u>GENERAL SPECIFICATION</u> - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) |           |
| 116   | DNM27494 | 8S1606             | 5330004378752 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA-9MM TH-03MM | 3304PC, CATERPILLER D/GEN.USA             | 1 / EACH/NUMBER  | 3304 SSDG            |             |           |               | LOCAL SOURCE: RK AUTOS TIBBET CENTER M. A JINNAH ROAD KARACHI | <u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG   |           |
| 117   | DNM55656 | 7N8025/4N8087      | 5330012668826 / SEAL WATER NEW PART NO. 4N8087                              | CATTER PILLAR D/G                         | 36 / EACH/NUMBER |                      |             |           |               | .   | <u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR   |           |
| 118   | SNM55175 | CV21258            | 5306795102515 / CONROD BOLT   | 3012/CV12, PISTON & CONN & ROD, PERKIN,UK | 24 / EACH/NUMBER |                      |             |           |               | .   | <u>TECHNICAL SPECIFICATION</u> - MAKE: PERKINS (WXHXD 20mmx120mmx20mm) weight 0.07kg material: ss <u>GENERAL SPECIFICATION</u> - MAKE: PERKINS (WXHXD 20mmx120mmx20mm) weight 0.07kg material: ss   |           |
| 119   | SNF54232 | BS-1030 / BS-1030W | 5830765117020 / TOA WALL MOUNTED SPEAKER                                    |   | 9 / EACH/NUMBER  | BS-1030 / BS-1030W   |             |           |               | .   | <u>TECHNICAL SPECIFICATION</u> - MODEL: TOA JAPAN LOCALLY AVAILABLE AUTHARIZED DEALER CERTIFICATE: REQUIRED <u>GENERAL SPECIFICATION</u> - MODEL: TOA JAPAN LOCALLY AVAILABLE AUTHARIZED DEALER CERTIFICATE: REQUIRED   |           |
| 120   | SNF51852 | 63/19 EB 21105=21  | 5935725077496 / RAYSHEM (J.S.C.R)HEAT SHRINK SIZE                           |   | 60 / METER       | RMW-63/19-1200/ADH-0 |             |           |               | .   | <u>TECHNICAL SPECIFICATION</u> - Category: Cables/Wires: Type: Tubing/Semi Rigid Shrinkage Ratio: 3:1 Material: Polyelofin (PO,   |           |

| S. No | LPR No   | PART NO                       | NSN / Description  | P/Equipment            | QTY / DENO       | Model        | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------------------|--|------------------------|------------------|--------------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                               | 63/19 LG 1 METER   |                        |                  |              |             |           |               |                | irradiated Operation Temp: -40 °C to 110 °C<br><u>GENERAL SPECIFICATION -</u><br>Category: Cables/Wires: Type: Tubing/Semi Rigid Shrinkage Ratio: 3:1 Material: Polyelofin (PO, irradiated Operation Temp: -40 °C to 110 °C              |           |
| 121   | DNZ63194 | COMPACT C-160L                | 5925785034775 / CIRCUIT BREAKER 250V 150KA-380/415V COMPACT C-160L           | SERVICE PANNELS NASR   | 1 / EACH/NUMBER  |              |             |           |               |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 122   | DNQ58133 | 53531-241                     | 6350705089489 / HEAT DETECTOR APOLLO-INTRINSICALLY SAFE RATE OF RISE HEAT    | FOR FIRE ALARM SYSTEM  | 6 / EACH/NUMBER  |              |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>Country: APOLLO UK Make: Apollo Fire Detectors Ltd 8.5V to 33V 060418/P5<br><u>GENERAL SPECIFICATION -</u><br>Country: APOLLO UK Make: Apollo Fire Detectors Ltd 8.5V to 33V 060418/P5               |           |
| 123   | DNF59577 | SERVO COTROL STAC JAPAN       | 6110705045037 / STABLIZER 3KVA I/P50-130V/160-240VAC50/60HZ O/P110/220V STAC | ELECTRICAL GENERAL USE | 1 / EACH/NUMBER  |              |             |           |               |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 124   | DNF63865 | WP7-12 -LONG/LX7-12/ PR 12-70 | 6140CH5088427 / BATTERY 12VOLT 7AH LEAD ACID SEALED.                         | 1 KVA UPS NS-1000      | 19 / EACH/NUMBER | WP7-12 -LONG |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>SPECIFICATION: BATTERY 12V 7AH SEALED M/FREE. MODEL NO. PR12-7, ,WEIGHT 2.15KG.<br><u>GENERAL SPECIFICATION -</u><br>SPECIFICATION: BATTERY 12V 7AH SEALED M/FREE. MODEL NO. PR12-7, ,WEIGHT 2.15KG. |           |
| 125   | DNF58512 |                               | 5965765016701 / MICROPHONE ON/OFF SWITCHABLE MODLE 3049                      | SRE SYSTEM             | 1 / EACH/NUMBER  |              |             |           |               |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>   |           |
| 126   | SNF51747 | d72sd500v/v-001               | 6625UK5081632 / VOLT METER 0-500V  | MAIN SW/BB             | 2 / EACH/NUMBER  | hobut 0-500v |             |           |               |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA</u>   |           |

| S. No | LPR No   | PART NO                              | NSN / Description   | P/Equipment                           | QTY / DENO       | Model                        | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------------------------|---|---------------------------------------|------------------|------------------------------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                                      |   |                                       |                  |                              |             |           |               |                | AVAILABLE  |           |
| 127   | SNF51973 | DC-II                                | 6210785031276 / LAMP CEILING COMPLETE FITTING DECK LIGHT 24V 25W CQ0006     | GRP BOAT                              | 20 / EACH/NUMBER |                              |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - colour: black<br><u>GENERAL SPECIFICATION</u> - colour: black   |           |
| 128   | DNF62894 | 1165190/1165180/1165170 / AD10-2HHMD | 6350715088918 / TR HAND HELD METAL DETECTOR SUPPER SCAN                     | SELF (SECURITY EQUIP) OEM GARRETT USA | 1 / EACH/NUMBER  | 1165180/1165170 / AD10-2HHMD |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE   |           |
| 129   | SNF51834 | DM-1200                              | 5965765013593 / OMNI DIRECTIONAL MICROPHONE 600 OHMS                        | SRE                                   | 10 / EACH/NUMBER | MODEL DM-1200 TOA JAPAN      |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - broucher is attached for details<br><u>GENERAL SPECIFICATION</u> - broucher is attached for details   |           |
| 130   | SNF53945 | A.G.M                                | 6230PK5073096 / SEARCH LIGHT 500W 220V COMPLETE WITH ACCESSORIES COMMERCIAL | ELECTRICAL USE                        | 7 / EACH/NUMBER  |                              |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - Search Light 500W/220V 50/60Hz/PF>0.9/CCT 6500k/IP 66<br><u>GENERAL SPECIFICATION</u> - Search Light 500W/220V 50/60Hz/PF>0.9/CCT 6500k/IP 66 |           |
| 131   | DNF58186 | K138Y/ K-133                         | 6230JP5087449 / TORCH WATER PROOF (FOR UNDER WATER DIVING) TOSHIBA          | FOR DIVING                            | 8 / EACH/NUMBER  |                              |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE   |           |
| 132   | SNF57093 | PHILIPS/NATIONAL AS PER DESCRIPTION  | 6240705038479 / TUBE LIGHT 220V 18W LENGTH 18 INCH                          | PNT JANBAZ GENERAL USE                | 40 / EACH/NUMBER |                              |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE   |           |
| 133   | DNF56965 | HU953UV                              | 8040705009081 / ARALDITE AW 106   | EM LOG                                | 3 / EACH/NUMBER  |                              |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - Colour (visiual) Neutral Pale yellow<br>SPecific gravity ca.1.15 ca. 0.95 ca.   |           |



| S. No | LPR No   | PART NO                           | NSN / Description  | P/Equipment                       | QTY / DENO       | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------------------------|--|-----------------------------------|------------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                                   | HARDNER  |                                   |                  |       |             |           |              |                | 1.05 Viscosity at 25 C 30-50 20-35 30-45 Pot Life (100 gm at 25 C) ca. 100 minutes <u>GENERAL SPECIFICATION</u> - Colour (visual) Neutral Pale yellow S <sup>pecific</sup> gravity ca.1.15 ca. 0.95 ca.1.05 Viscosity at 25 C 30-50 20-35 30-45 Pot Life (100 gm at 25 C) ca.100 minutes |           |
| 134   | DPC62991 | IN70052                           | 8040795103434 / LOCTITE 638 50ML   | GRIFFON 2000TD(M), HOVERCRAFT ,UK | 10 / EACH/NUMBER |       |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE  |           |
| 135   | DPK63939 | H 572                             | 9150992203468 / OIL OM 65 (Packing = 05 liters)  | 30MM GUN                          | 428 / LITER      |       |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - bs-4475 of 2000 grade cs 68 defstan 01-5/issue 17 mar 11 200 Ltr drum <u>GENERAL SPECIFICATION</u> - bs-4475 of 2000 grade cs 68 defstan 01-5/issue 17 mar 11 200 Ltr drum  |           |
| 136   | DNF54931 | DA-1250-D/XLS2502/CS-2000/CS-1400 | 5821785120712 / PRO POWER AMPLIFIER ELECTRO-VOICE Q1212 /CROWN 2400 WATTS                            | PA SYSTEM                         | 1 / EACH/NUMBER  |       |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - turn on delay protections. <u>GENERAL SPECIFICATION</u> - turn on delay protections.  |           |
| 137   | SNF54321 | CAT6 E/CAT 5E                     | 7010705118996 / STP CAT 5E/CAT6E NETWORK CABLE (4 PAIR) AMP/AVAYA (1000 FFFT)                        | FAWMIS NETWORKING CABLE           | 3 / ROLL         |       |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE  |           |
| 138   | DPC63538 | CAT ELC TM (2056612 or 2056611)   | 6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 | CP AIR COMP                       | 200 / LITER      |       |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - TDS & IPC Enclosed <u>GENERAL SPECIFICATION</u> - TDS & IPC Enclosed  |           |

| S. No | LPR No   | PART NO                            | NSN / Description  | P/Equipment                     | QTY / DENO      | Model                          | SR NO OF PR | MANUF ADO | Availabilty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------------------------|--|---------------------------------|-----------------|--------------------------------|-------------|-----------|-------------|----------------|--|-----------|
|       |          |                                    | Liter Can)   |                                 |                 |                                |             |           |             |                |  |           |
| 139   | DNF63218 | DMM-FLUKE 87-V / 87-III            | 6625715110413 / DIGITAL MULTIMETER FLUKE 87-V / 87-III                   | TEST EQUIPMENT.                 | 2 / EACH/NUMBER | DMM-FLUKE 87-V / 87-III        |             |           |             |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 140   | DNF63869 | D3500 /D-3000                      | 6710765087447 / NIKON DIGITAL STILL CAMERA WITH FLASH GUN SB-900         | DIGITAL CAMERA                  | 1 / EACH/NUMBER |                                |             |           |             |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 141   | DNF59377 | KFAE-55C                           | 6105705044236 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE | EXHAUST BLOWER STEERING COMPART | 6 / EACH/NUMBER |                                |             |           |             |                | <u>TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE</u><br><u>GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE</u>  |           |
| 142   | SNF52116 | SMT3000I C/SURTD3000XLI/3000VA APC | 6130715063823 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES. | SELF                            | 1 / EACH/NUMBER | MODEL ESP-808 (E) /SYSTEK PVT. |             |           |             |                | <u>TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u><br><u>GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u> |           |
| 143   | SNH51648 | 61N-11631-00-                      | 2850546012631 / PISTON   |                                 | 5 / EACH/NUMBER |                                |             |           |             |                | <u>TECHNICAL SPECIFICATION - PISTON KIT STD PISTON</u>   |           |

| S. No | LPR No   | PART NO                      | NSN / Description                                      | P/Equipment | QTY / DENO      | Model              | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks   | TECH / GEN SPECS  | Dimension |
|-------|----------|------------------------------|--|-------------|-----------------|--------------------|-------------|-----------|---------------|--|---|-----------|
|       |          | 95                           |  |             | UMBER           |                    |             |           |               |  | DIAMETER: 72MM PISTON HIGHT: 72,75MM WRIST PIN: 20MM<br>GENERAL SPECIFICATION - PISTON KIT STD PISTON<br>DIAMETER: 72MM PISTON HIGHT: 72,75MM WRIST PIN: 20MM   |           |
| 144   | DNM55835 | 342419/385311822 (600342419) | 2990715119916 / M PUMP DIAPHRAGM                       | VACUME PUMP | 1 / EACH/NUMBER |                    |             |           |               |  | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null  |           |
| 145   | DGB48678 |                              | 0278546003470 / PENUMATIC DRILL MACHINE S 1" R.P.M-530 |             | 1 / EACH/NUMBER | INCGO / TOTAL      |             |           |               | MAKE / MODEL / COUNTRY : UK/ GERMANY/ CHINA<br>CONSIDER ONLY INCGO OR TOTAL & MANUFAC Turer<br>COC/AUTH OROZED | TECHNICAL SPECIFICATION - Forward / Reverse Drill Heavy duty 90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V<br>GENERAL SPECIFICATION - Forward / Reverse Drill Heavy duty 90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V  |           |
| 146   | DGD29833 | NO DATA AVAILAB LE           | 0035500000560 / COOKER PRESSURE-10 LITRES COMPLETE     |             | 1 / SET         | NO DATA AVAILAB LE |             |           |               |  | TECHNICAL SPECIFICATION - Aluminum Food Grade (Lead Free)<br>GENERAL SPECIFICATION - Aluminum Food Grade (Lead Free)  |           |
| 147   | DNF63426 | DPSI 8-16X40                 | 0552780000245 / BINOCULAR WITH CASE                    | SELF & USE  | 6 / EACH/NUMBER | DPSI OLYMPU S      |             |           |               |  | TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF |           |

| S. No | LPR No   | PART NO                          | NSN / Description  | P/Equipment                               | QTY / DENO         | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks   | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------------------|--|---|--------------------|-------|-------------|-----------|--------------|------------------|--|-----------|
|       |          |                                  |  |   |                    |       |             |           |              |                  | AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)                 |           |
| 148   | SNF38108 | 02 CORE KAUDIO                   | 599576512071<br>6 / SPEAKER STEREO cable Electro voice                             | PA SYSTEM (TOA)                           | 280 / METER        |       |             |           |              |                  | TECHNICAL SPECIFICATION - EV 2C X 14 AWG Pro Speaker Cable SSC-910, 2 X 1.5MM 2 Speaker cable OD 7.2MM (100 Mtr Roll)<br>GENERAL SPECIFICATION - EV 2C X 14 AWG Pro Speaker Cable SSC-910, 2 X 1.5MM 2 Speaker cable OD 7.2MM (100 Mtr Roll) |           |
| 149   | DPC62765 | BS 627 (F-8) (R 5123)            | 801070512876<br>4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)                          | PIGMENT IS USED TO ACHIEVE DERIVED COLOUR | 50 / KILOGRAMME    |       |             |           |              |                  | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 150   | DNM55091 | PH-55356-5                       | 662570512854<br>9 / LIMITORQUE CONTROL INDICATION METER (15V, 2000 OHMS) (F8)      | BLAST VALVE OPERATING MOTOR               | 3 / EACH/NUMBER    |       |             |           |              |                  | TECHNICAL SPECIFICATION - Dia / Size: Inner Dia 8.8 mm, Outer Dia 6.7 mm, Depth 3.6 mm (Picture enclosed)<br>GENERAL SPECIFICATION - Dia / Size: Inner Dia 8.8 mm, Outer Dia 6.7 mm, Depth 3.6 mm (Picture enclosed)                         |           |
| 151   | DGB54242 | WORKING 100PSI FLANGE CONNECTION | 024154600192<br>9 / VALVE-GATE-2" (5.08 CM)<br>MATERIAL: GUNMETAL (BRASS) PRESSING |   | 2 / EACH/NUMBER    |       |             |           |              |                  | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 152   | DCD63621 |                                  | 845550193866<br>9 / BADGE CAP MINIATURE GOLDEN FOR PETTY OFFICERS                  |   | 3000 / EACH/NUMBER |       |             |           |              | as per file spec | TECHNICAL SPECIFICATION - material blazer fabric colour pantone shade Anchor Stainless Steel Ring around Anchor Five pointed Star<br>GENERAL SPECIFICATION - material blazer fabric colour pantone shade Anchor Stainless Steel Ring         |           |

| S. No | LPR No   | PART NO                              | NSN / Description   | P/Equipment | QTY / DENO                | Model   | SR NO OF PR | MANUF ADO | Availability | Tender Remarks          | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------------------------|---|-------------|---------------------------|---|-------------|-----------|--------------|-------------------------|---|-----------|
|       |          |                                      |   |             |                           |   |             |           |              |                         | around Anchor Five pointed Star   |           |
| 153   | DCD63104 |                                      | 845570390175<br>5 / BADGE<br>ARM MEDICAL<br>(GN) LMT RED<br>EMBROIDRY                     |             | 300 /<br>EACH/<br>NUMBER  |   |             |           |              | AS PER<br>FILE<br>SPECS | <u>TECHNICAL SPECIFICATION</u> -<br>null<br><u>GENERAL SPECIFICATION</u> -<br>null  |           |
| 154   | DNQ53462 | GOMTEX<br>Ø<br>30310003800           | 473070526970<br>9 / hose assy<br>rubber duraline/<br>gometex lg 100<br>ft id 1-1/2"       |             | 8 /<br>EACH/<br>NUMBER    | HOSE<br>ASSY<br>RUBBER<br>DURALIN<br>E/<br>GOMETE<br>X LG 100<br>FT ID 1-<br>1/2" |             |           |              |                         | <u>TECHNICAL SPECIFICATION</u> -<br>specially formulated rubber, i<br>extruded through a circular woven.<br>low pressure drop thanks to its<br>smooth inner wall, high thermal<br>resistance.<br><u>GENERAL SPECIFICATION</u> - specially<br>formulated rubber, i extruded through<br>a circular woven. low pressure drop<br>thanks to its smooth inner wall, high<br>thermal resistance. |           |
| 155   | DNQ54618 | GOMTEX<br>Ø<br>30310003800           | 473070526970<br>9 / hose assy<br>rubber duraline/<br>gometex lg 100<br>ft id 1-1/2"       |             | 4 /<br>EACH/<br>NUMBER    | HOSE<br>ASSY<br>RUBBER<br>DURALIN<br>E/<br>GOMETE<br>X LG 100<br>FT ID 1-<br>1/2" |             |           |              |                         | <u>TECHNICAL SPECIFICATION</u> -<br>specially formulated rubber, i<br>extruded through a circular woven.<br>low pressure drop thanks to its<br>smooth inner wall, high thermal<br>resistance.<br><u>GENERAL SPECIFICATION</u> - specially<br>formulated rubber, i extruded through<br>a circular woven. low pressure drop<br>thanks to its smooth inner wall, high<br>thermal resistance. |           |
| 156   | DSB63516 | CMY30030<br>7 /<br>FMV2306A<br>S 11T | 087005590597<br>5 / 11T<br>FREQUENCY<br>VARIATOR -<br>VARIATEUR<br>DE<br>FREQUENCE<br>11T |             | 2 /<br>EACH/<br>NUMBER    | CMY300  |             |           |              |                         | <u>TECHNICAL SPECIFICATION</u> - NO<br>DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA<br>AVAILABLE  |           |
| 157   | DCD63619 |                                      | 845550130043<br>7 / PAK<br>MARINE<br>INSIGNIA<br>CPOs /<br>SAILORS                        |             | 1000 /<br>EACH/<br>NUMBER |   |             |           |              | as per file<br>spec     | <u>TECHNICAL SPECIFICATION</u> - PAK<br>MARINE INSIGNIA CPOs / SAILORS<br><u>GENERAL SPECIFICATION</u> - PAK<br>MARINE INSIGNIA CPOs / SAILORS  |           |
| 158   | DCD63597 |                                      | 844050410039<br>7 / CAP   |             | 800 /<br>EACH/<br>NUMBER  |   |             |           |              | AS PER<br>FILE          | <u>TECHNICAL SPECIFICATION</u> -<br>Color Pantone Shade BLACK: 19-  |           |

| S. No | LPR No   | PART NO         | NSN / Description  | P/Equipment | QTY / DENO        | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------|--|-------------|-------------------|-------|-------------|-----------|--------------|-------------------|---|-----------|
|       |          |                 | BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 7 INCH            |             | UMBER             |       |             |           |              | SPECS             | 4006 TCX Body: 100% Pure Merino Wool Lining: Artificial Silk Thread of Stitching: Polyester Dimension Stability (Wool Shrinkage): 2% Max Binding: Tape Textile Silk Corded 25 mm wide<br><u>GENERAL SPECIFICATION</u> - Color Pantone Shade BLACK: 19-4006 TCX Body: 100% Pure Merino Wool Lining: Artificial Silk Thread of Stitching: Polyester Dimension Stability (Wool Shrinkage): 2% Max Binding: Tape Textile Silk Corded 25 mm wide |           |
| 159   | DCC63513 |                 | 8405500692579 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II |             | 100 / EACH/NUMBER |       |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II<br><u>GENERAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-II  |           |
| 160   | DCC63511 |                 | 8405500692578 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-I  |             | 100 / EACH/NUMBER |       |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-I<br><u>GENERAL SPECIFICATION</u> - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-I  |           |
| 161   | DN057278 | A20107020104302 | 4620FP1050019 / 2205 Electric regulating ball valve                              |             | 1 / EACH/NUMBER   | N/A   |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - L-type G3/4 thread PN63 IP67 L=88 mm valve DN Size: DN20 Explosion proof<br><u>GENERAL SPECIFICATION</u> - L-type G3/4 thread PN63 IP67 L=88 mm valve DN Size: DN20 Explosion proof  |           |
| 162   | DCD63599 |                 | 8440504100425 / CAP BARRET BLACK FOR CPO/SAILOR SIZE 7.5 INCH                    |             | 800 / EACH/NUMBER |       |             |           |              | AS PER FILE SPECS | <u>TECHNICAL SPECIFICATION</u> - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL  |           |

| S. No | LPR No   | PART NO | NSN / Description                                | P/Equipment | QTY / DENO | Model   | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|---------|--|-------------|------------|---------|-------------|-----------|---------------|----------------|---|-----------|
|       |          |         |  |             |            |         |             |           |               |                | SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDEGENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE  |           |
| 163   | DGP63934 | CORE I5 | 702570524609<br>1 / PERSONAL COMPUTER (CORE: I5) |             | 2 / SET    | CORE I5 |             |           |               |                | <p>TECHNICAL SPECIFICATION -</p> <p>CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p>GENERAL SPECIFICATION</p> <p>_CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System:</p> |           |

| S. No | LPR No   | PART NO | NSN / Description                                      | P/Equipment | QTY / DENO | Model   | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------|--|-------------|------------|---------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |         |  |             |            |         |             |           |               |                | Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required   |           |
| 164   | DGP63630 | CORE I5 | 702570524609<br>1 / PERSONAL<br>COMPUTER<br>(CORE: I5) |             | 3 / SET    | CORE I5 |             |           |               |                | <p><u>TECHNICAL SPECIFICATION -</u><br/> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u><br/> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED)</p> |           |



| S. No | LPR No   | PART NO               | NSN / Description  | P/Equipment | QTY / DENO         | Model                 | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------------|--|-------------|--------------------|-----------------------|-------------|-----------|--------------|-------------------|---|-----------|
|       |          |                       |  |             |                    |                       |             |           |              |                   | <p>GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>  |           |
| 165   | DNF63531 | dse8610mkii           | 6625994114623 / synchronising auto start load sharing control module |             | 2 / EACH/NUMBER    | dse 8610mkii          |             |           |              |                   | <p><u>TECHNICAL SPECIFICATION - null</u><br/><u>GENERAL SPECIFICATION - null</u></p>  |           |
| 166   | DSB50369 | CUB5VB00              | 6625016039841 / Voltmeter  |             | 2 / EACH/NUMBER    | N/A                   |             |           |              |                   | <p><u>TECHNICAL SPECIFICATION - N/A</u><br/><u>GENERAL SPECIFICATION - N/A</u></p>  |           |
| 167   | DNF56448 | 04-Fiber SMF G. 652.D | 7045705249621 / Optical fiber cables CLT                             |             | 400 / METER        | 04-Fiber SMF G. 652.D |             |           |              |                   | <p><u>TECHNICAL SPECIFICATION - IITECH SINGLE mODE 04 FIBER g. 652.d clt type oPTICAL FIBER cABLE NOTE: SM G.652.D Is the common standard for all type of OFC just the number of fibers varries i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc</u><br/><u>GENERAL SPECIFICATION - IITECH SINGLE mODE 04 FIBER g.652.d clt type oPTICAL FIBER cABLE NOTE: SM G.652.D Is the common standard for all type of OFC just the number of fibers varries i.e. 2 Fiber, 4 Fiber, 8 Fiber, 24 Fiber etc</u></p> |           |
| 168   | DCD63600 |                       | 8405503501175 / CHEVRON WHITE FOR PN POLICE HEAD CONSTABLE           |             | 1000 / EACH/NUMBER |                       |             |           |              | AS PER FILE SPECS | <p><u>TECHNICAL SPECIFICATION - CLOTH WOOLEN COLOUR KHAKI ( AS PER STOCK SAMPLE) RANK SHADE WHITE Make , Shape , Design , Deamination as per Stock Sample</u><br/><u>GENERAL SPECIFICATION -CLOTH WOOLEN COLOUR KHAKI ( AS PER STOCK SAMPLE) RANK SHADE WHITE Make , Shape , Design , Deamination as per Stock Sample</u></p>   |           |

| S. No | LPR No   | PART NO      | NSN / Description  | P/Equipment | QTY / DENO        | Model     | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------|--|-------------|-------------------|-----------|-------------|-----------|--------------|-------------------|--|-----------|
| 169   | DCC63514 |              | 8405500692581 / OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV   |             | 100 / EACH/NUMBER |           |             |           |              | as per file specs | <u>TECHNICAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV</u><br><u>GENERAL SPECIFICATION - OVERALL BLUE PANTONE COLOUR SHADE 19-3920 TC 100% COTTON SIZE-IV</u>   |           |
| 170   | DCD63102 |              | 8455703901753 / BADGE ARM MEDICAL (GN) MT-II RED EMBROIDRY   |             | 300 / EACH/NUMBER |           |             |           |              | as per file spec  | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 171   | DNJ49050 | 68V-81800-02 | 2920765264989 / STARTING MOTOR ASSY  |             | 1 / EACH/NUMBER   | F90BETL   |             |           |              | .                 | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 172   | DNQ61643 | 30-2062      | 4220785289433 / FLARE SET (06 RED HAND FLARE MK8+04 PARA RED ROCKET MK8A +02 LIFE SMOKE MK9) FOR SURVIVAL PACK OF 25 X MEN LIFE RAFT |             | 15 / PACKETS      | life raft |             |           |              | .                 | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 173   | DNO50057 | 8N-8455      | 2930270561085 / IMPELLER-PUMP  |             | 2 / EACH/NUMBER   | 3516E     |             |           |              | .                 | <u>TECHNICAL SPECIFICATION - IMPELLER-PUMP</u><br><u>GENERAL SPECIFICATION - IMPELLER-PUMP</u>   |           |
| 174   | DCD63598 |              | 8440504100398 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 7.25 INCH   |             | 800 / EACH/NUMBER |           |             |           |              |                   | <u>TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE</u><br><u>GENERAL</u> |           |

| S. No | LPR No   | PART NO       | NSN / Description  | P/Equipment | QTY / DENO       | Model               | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------------|--|-------------|------------------|---------------------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |               |  |             |                  |                     |             |           |              |                | SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006<br>TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE                                   |           |
| 175   | DNF63455 | 010-017111-03 | 660571529297<br>4 / gps map 585 plus with fish finder tranducer  |             | 2 / EACH/NUMBER  | gpsmap 585 plus-sea |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |
| 176   | DNF61819 | AALR6         | 613573528152<br>4 / AA2 ENERGIZER LITHIUM BATTERY 1.5V RECHARGEABLE SIZE H: 145mm  |             | 250 / PAIR       | ENERGIZER LITHIUM   |             |           |              |                | TECHNICAL SPECIFICATION - (2 PACK)<br>GENERAL SPECIFICATION - (2 PACK)   |           |
| 177   | SNF59294 | DMC-820SSC    | 589571524110<br>4 / MEDIA CONVERTOR D-LINK 10/100/1000base-t Gigabit twisted pair to 1000base-lx fiber 1310 nm singlemode fiber (20km, sc) |             | 13 / EACH/NUMBER | DMC-820SSC          |             |           |              |                | TECHNICAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC)<br>GENERAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC) |           |
| 178   | SNF54668 | DMC-820SSC    | 589571524110<br>4 / MEDIA CONVERTOR D-LINK 10/100/1000base-t Gigabit twisted pair to 1000base-lx fiber 1310 nm singlemode fiber (20km, sc) |             | 10 / EACH/NUMBER | DMC-820SSC          |             |           |              |                | TECHNICAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC)<br>GENERAL SPECIFICATION - PORT 10/100/1000BASE-T RJ45 GIGABIT TWISTED PAIR TO 1000BASE-LX FIBER 1310 NM SINGLEMODE FIBER (20KM, SC) |           |

| S. No | LPR No   | PART NO                 | NSN / Description   | P/Equipment | QTY / DENO        | Model        | SR NO OF PR | MANUF ADO | Availabilty | Tender Remarks    | TECH / GEN SPECS  | Dimension |
|-------|----------|-------------------------|---|-------------|-------------------|--------------|-------------|-----------|-------------|-------------------|---|-----------|
| 179   | DNF63777 | DS-6701HFHIV            | 589527068439<br>1 / HD ENDCODER (VIDEO COMPRATION DEVICE)     |             | 1 / EACH/NUMBER   | N/A          |             |           |             |                   | <p><u>TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.</u></p> <p><u>GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.</u></p> |           |
| 180   | SNF52838 | HTS-MC100CM             | 591570524870<br>4 / MEDIA CONVERTER (1 PAIR)                  |             | 10 / EACH/NUMBER  | MC100CM      |             |           |             |                   | <p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>   |           |
| 181   | DNJ50367 | 952188                  | 531576523659<br>1 / PIN Dowel                                 |             | 8 / EACH/NUMBER   | E40XMHL      |             |           |             |                   | <p><u>TECHNICAL SPECIFICATION - Make/ Model: Mercury/ E40XMHL a. Length 11.50mm b. Dia 5.87 mm</u></p> <p><u>GENERAL SPECIFICATION - Make/ Model: Mercury/ E40XMHL a. Length 11.50mm b. Dia 5.87mm</u></p>  |           |
| 182   | DCD63103 |                         | 845570390175<br>4 / BADGE ARM MEDICAL (GN) MT-I RED EMBROIDRY |             | 300 / EACH/NUMBER |              |             |           |             | AS PER FILE SPECS | <p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>   |           |
| 183   | SNF52831 | HTS--LMS-4NP /LXW-511G2 | 593070524607<br>1 / LIMIT SWITCH (1                           |             | 8 / EACH/NUMBER   | HTS--LMS-4NP |             |           |             |                   | <p><u>TECHNICAL SPECIFICATION - Mechanism:Highly reliable design, self-centering and</u></p>  |           |

| S. No | LPR No   | PART NO | NSN / Description                       | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS   | Dimension |
|-------|----------|---------|---|-------------|------------|-------|-------------|-----------|--------------|-------------------|--|-----------|
|       |          |         | PAIR) snids                             |             |            |       |             |           |              |                   | <p>electromechanically operated Power fail operations: fail-lock or fail-safe is available Arms: • Three arm sections for 120 degrees of passage space. • Four arm sections for 90 degree of passage space. Material: • 304 Grade Stainless Steel • Mild Steel Dimensions: Height: 2165mm, Width: 1400mm Supply: 220-240VAC, 50 Hz Operational Voltage: 220-240VAC, 50 Hz Programmable Logic Controller: WECON brand (China) Limit Switches: 15A / 250V AC, Brand: C-Lin Relays: 24V DC / 220V AC (8 pins or 11 pins configuration) Brand: C-Lin Relay Base: Standard 8pins or 11 pins, Brand: C-Lin Power Adopter: Standard Power Adapter 24V DC, 5A, Output</p> <p><u>GENERAL SPECIFICATION - Mechanism:</u><br/>Highly reliable design, self-centering and electromechanically operated Power fail operations: fail-lock or fail-safe is available Arms: • Three arm sections for 120 degrees of passage space. • Four arm sections for 90 degree of passage space. Material: • 304 Grade Stainless Steel • Mild Steel Dimensions: Height: 2165mm, Width: 1400mm Supply: 220-240VAC, 50 Hz Operational Voltage: 220-240VAC, 50 Hz Programmable Logic Controller: WECON brand (China) Limit Switches: 15A / 250V AC, Brand: C-Lin Relays: 24V DC / 220V AC (8 pins or 11 pins configuration) Brand: C-Lin Relay Base: Standard 8pins or 11 pins, Brand: C-Lin Power Adopter: Standard Power Adapter 24V DC, 5A, Output</p> |           |
| 184   | DCD63136 |         | 8455500700467 / BADGE SHOULDER CRESCENT |             | 700 / PAIR |       |             |           |              | as per file specs | <p><u>TECHNICAL SPECIFICATION - BADGE SHOULDER CRESCENT AND STAR FOR MCPO DRESS 03</u><br/><u>GENERAL SPECIFICATION -</u></p>  |           |

| S. No | LPR No   | PART NO         | NSN / Description  | P/Equipment | QTY / DENO        | Model                         | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------|--|-------------|-------------------|-------------------------------|-------------|-----------|--------------|-------------------|--|-----------|
|       |          |                 | AND STAR FOR MCPO dress 03   |             |                   |                               |             |           |              |                   | BADGE SHOULDER CRESCENT AND STAR FOR MCPO DRESS 03   |           |
| 185   | DCD63105 |                 | 8455703901756 / BADGE ARM MEDICAL (GN) ARTIFICER -IV RED EMBROIDRY           |             | 300 / EACH/NUMBER |                               |             |           |              | AS PER FILE SPECS | <u>TECHNICAL SPECIFICATION</u> - null<br><u>GENERAL SPECIFICATION</u> - null   |           |
| 186   | SSM28233 | 068N2103        | 4820144762791 / THERMO EXPANSION VALVE                                       |             | 3 / EACH/NUMBER   | NO DATA AVAILABLE             |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE   |           |
| 187   | DNF57457 | 44C2 / M20967-1 | 6625705289212 / VOLT meter (DC PANEL) 0-100 v model 44c2 size (100x80x12 mm) |             | 5 / EACH/NUMBER   | 44C2                          |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - dc panel volt meter (60v) model 44c2 for welding ideal arc r3r 500-i & 600-i<br><u>GENERAL SPECIFICATION</u> - dc panel volt meter (60v) model 44c2 for welding ideal arc r3r 500-i & 600-i   |           |
| 188   | DNM63131 | 4309459         | 2815016629279 / UPPER ENGINE GASKET  |             | 1 / EACH/NUMBER   | QSB 6.7 300 HP CUMMINS ENGINE |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7<br><u>GENERAL SPECIFICATION</u> - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7   |           |
| 189   | DNN43568 | SCPF22-02-SEW   | 5340705281508 / MAIN BODY OF SHAFT COOLING PUMP F22P                         |             | 1 / EACH/NUMBER   | NA                            |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - MAIN BODY OF SHAFT COOLING PUMP PUMP USED FOR COOLING OF SHAFTING ONBOARD F22P SHIPS. DETAILS AS PER PART CATALOGUE<br><u>GENERAL SPECIFICATION</u> - MAIN BODY OF SHAFT COOLING PUMP PUMP USED FOR COOLING OF SHAFTING ONBOARD F22P SHIPS. DETAILS AS PER PART CATALOGUE |           |
| 190   | DNF63528 | DJI RC          | 5998765280434 / dji rc smart controller occui sync 2.0                       |             | 9 / EACH/NUMBER   | CP.MA.00000080.01             |             |           |              |                   | <u>TECHNICAL SPECIFICATION</u> - null<br><u>GENERAL SPECIFICATION</u> - null   |           |

| S. No | LPR No   | PART NO                    | NSN / Description  | P/Equipment | QTY / DENO        | Model       | SR NO OF PR | MANUF ADO | Availability | Tender Remarks    | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------------|--|-------------|-------------------|-------------|-------------|-----------|--------------|-------------------|--|-----------|
| 191   | DN055014 | 7620.740.013.5 / FIL230912 | 2815FP3030393 / FUEL DUPLEX FILTER   |             | 19 / EACH/NUMBER  | TBD620V12   |             |           |              |                   | <u>TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER</u> Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps<br><u>GENERAL SPECIFICATION - FUEL DUPLEX FILTER</u> Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps   |           |
| 192   | SGB62686 | SH2IN-SEW                  | 4720705292328 / spring hose 2" dia   |             | 51 / METER        | PVCSRH-0050 |             |           |              |                   | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 193   | DCD63596 |                            | 8440504100396 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 6.75 INCH |             | 800 / EACH/NUMBER |             |             |           |              | AS PER FILE SPECS | <u>TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE</u><br><u>GENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE</u> |           |
| 194   | DCD63595 |                            | 8440504100395 / CAP BARRET BLACK FOR CPOs/SAILOR S/FIRE BRIGADE AND PNP STAFF SIZE 6.50 INCH |             | 800 / EACH/NUMBER |             |             |           |              | AS PER FILE SPECS | <u>TECHNICAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006 TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE</u><br><u>GENERAL SPECIFICATION - COLOR PANTONE SHADE BLACK: 19-4006</u>  |           |

| S. No | LPR No   | PART NO                              | NSN / Description  | P/Equipment | QTY / DENO       | Model                                      | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------------------------|--|-------------|------------------|--|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                                      |  |             |                  |  |             |           |              |                | TCX BODY: 100% PURE MERINO WOOL LINING: ARTIFICIAL SILK THREAD OF STITCHING: POLYESTER DIMENSION STABILITY (WOOL SHRINKAGE): 2% MAX BINDING: TAPE TEXTILE SILK CORDED 25 MM WIDE |           |
| 195   | DNO19974 | 450-6496                             | 293071523402<br>1 / Core Aftercooler   |             | 1 / EACH/NUMBER  | N/A  |             |           |              |                | <u>TECHNICAL SPECIFICATION - Core Aftercooler</u><br><u>GENERAL SPECIFICATION - Core Aftercooler</u>   |           |
| 196   | DNF51173 | lx3v-0806mt-a1                       | 599870524611<br>6 / 1xplc  |             | 1 / EACH/NUMBER  | LX3V-0806MT-A1                             |             |           |              |                | <u>TECHNICAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA</u><br><u>GENERAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA</u>   |           |
| 197   | DNF62169 | RSFD-II                              | 613578528471<br>7 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY                                 |             | 12 / EACH/NUMBER | RSFD-II                                    |             |           |              |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 198   | DNF63532 | T7S 1250 PR231/PLS/IN=1250A 4P F F M | 592573530064<br>2 / MOUIded CASE Circuit Breaker (motorize 4 pole 1250 a (air circuit breaker) |             | 2 / EACH/NUMBER  | ABB T7S 1250 PR231/ PLS/IN=1250A -4P F F M |             |           |              |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>   |           |
| 199   | DNS47263 | 196 055                              | 533117126022<br>3 / O RING   |             | 8 / EACH/NUMBER  | 9L20C3                                     |             |           |              |                | <u>TECHNICAL SPECIFICATION - COUNTRY OF ORIGIN: FINLAND</u><br>Manufacturer: Wartsila<br><u>GENERAL SPECIFICATION - COUNTRY OF ORIGIN: FINLAND</u><br>Manufacturer: Wartsila     |           |
| 200   | DNM63135 | 4309460                              | 533001665761<br>1 / LOWER ENGINE GASKET  |             | 1 / EACH/NUMBER  | QSB 6.7 300 HP CUMMINS ENGINE CM 2250      |             |           |              |                | <u>TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u><br><u>GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u>               |           |