

TENDER BULLETIN

DATE & TIME 5/29/24 3:04 PM INVITATION TO TENDER TO BE OPENED ON 6/12/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGP637 71	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
2	DGP639 55	G2102560 EU	361070509130 4 / SHREDDING		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MACHINE, GBC DUO (SHERED MASTER)								SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
3	SNF54634	0102-034009-226	592578515447 8 / SINGLE POLE BREAKER 4AMP 220V AC	L/PAC	70 / EACH/NUMBER	CHNT-C4 CHNT SINGLE POLE	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILY;</u> ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. <u>SPEC;COIL VOLTAGE 220V AC.</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILY;</u> ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. <u>SPEC;COIL VOLTAGE 220V AC.</u>	
4	SNF51809	0102-034012-226	593078515448 1 / PHASE FAILURE IN	L/PAC	10 / EACH/NUMBER	IN PUT 380-415VAC	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILY;</u> ALPINE INDUSTRIAL CON PVT LTD.305/2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PUT 380-415VAC					PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674			GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC.</u>	
5	SNF57089	0103-034021-250	6685785154496 / THERMOCOUPLE 5M	H/PAC	5 / EACH/NUMBER			ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.</u>	
6	SNF57092	NZ-640210	5995705195584 / VGA CABLE 7 CORE	WARSHIP ELECTRONIC CHART DISPLAY AND INFORMATIWDIS	50 / METER	ugreen	NIL	HASSAN ABDAL PAKISTAN	PAKISTAN CABLES		<u>TECHNICAL SPECIFICATION - make/brand: ugreen /smart one technology cONSTRUCTION/ mATERIAL: 15 PINS STANDARD CONNECTOR FOR VIDEO OUTPUT WHICH CONTAINS COAXIAL WIRING. LENGTH: 10 METERS. GENERAL SPECIFICATION - make/brand: ugreen /smart one technology cONSTRUCTION/ mATERIAL: 15 PINS STANDARD CONNECTOR FOR VIDEO OUTPUT WHICH CONTAINS COAXIAL WIRING. LENGTH: 10 METERS.</u>	
7	SNM59314	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLARGENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
8	DNJ64016	8M0078858/817275A08	2930015618292 / REPAIR KIT WATER PUMP UPPER	MERCURY 300 HP OBM USA	6 / EACH/NUMBER	F300BETX	2B469929	MERCURY Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	MERCURY Marine USA		TECHNICAL SPECIFICATION - GEAR HOSE DRIVESHAFT, 4.80 TORPEDO REPAIR KIT WATER PUMP UPPER. GENERAL SPECIFICATION - GEAR HOSE DRIVESHAFT, 4.80 TORPEDO REPAIR KIT WATER PUMP UPPER.	
9	SNM61948	85484	4330705172629 / SEPARATOR CARTRIDGE LPAC ALPINE	LPAC	2 / EACH/NUMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTAN (LAHORE)		TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102 GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANUAL 0102	
10	SGB47306		0554705221347 / CARBON STEEL ELECTRODE ZODIAN E-6013 SIZE 2.5 MM	WELDING RECTIFIER YPK1511611 LINDE	200 / KILOGRAMME	AWS A/SFA 5.1-91, E 6013	R3R 500 i	Linde Pakistan LTd PO BOX N4845 Dockyard Road west wharf KARACHI 74000 PAKISTAN TEL 021111262725 FAX NO.+922132312968 E.Mail:customerservice.pk@linde.com	LINDE PVT LTD		TECHNICAL SPECIFICATION - DIA: 2.5 MM, SPECS: AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-600 N/mm2, Yield Power: 380 N/mm2, Elongation: 24.0%, Charpy V impact values at 0 degree Celsius: minimum 47 (joules) Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to 0.40 %, S 0.03 Max, P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range ac/dc and type of DCEP/DCEN, Welding all on positions, Welding arc, Spatter, Flow of welding, Penetration, Finishing of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013 GENERAL SPECIFICATION - DIA: 2.5 MM, SPECS: AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-600 N/mm2, Yield Power: 380 N/mm2, Elongation: 24.0%, Charpy V impact values at 0 degree Celsius: minimum 47 (joules) Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											0.40 %, S 0.03 Max, P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range ac/dc and type of DCEP/DCEN, Welding all on positions, Welding arc, Spatter, Flow of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013	
11	DNC573 81	(DOS3), N1115.	635022616408 4 / OPTICAL SMOKE DETECTOR HEAD	SALWICO CS4000 FIRE ALARM	1 / EACH/N UMBER	SALWICO DOS3	SG-1360	73	CONSIL UM MARINE ABSALS MASTAR EGATAN 21GOTEB ORGSWE DENSE- 40276876 3HISINGS BACKAS E-402 76+46 31 710 77 00+46 31 710 78 00556070 - 9353CON SILIUM@ CONSILI UM. SEHTTPS ://WWW. CONSILI UM. SE4669		<u>TECHNICAL SPECIFICATION -</u> NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILIUM MARINE AB SALSMASTAREGATAN 21 GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILIUM@CONSILIUM.SE HTTPS://WWW.CONSILIUM.SE 4669 <u>GENERAL SPECIFICATION -</u> NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILIUM MARINE AB SALSMASTAREGATAN 21 GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILIUM@CONSILIUM.SE HTTPS://WWW.CONSILIUM.SE 4669	
12	DNF5593 5	SRD-442	582073520694 7 / DVR	DVR	4 / EACH/N UMBER	SRD-442	SAMSUN G TECHWIN DVR KOREA	SAMSUNG TECHWIN CO LTD KOREA Samsungtechwin R & D Center, 701 Sampyeong- dong,Bundang-gu, Seongnam-si, Gyeonggi-do, Korea,463-400	SAMSUN G TECHWIN KOREA		<u>TECHNICAL SPECIFICATION -</u> DVR USES TO CCTV NETWORKING. <u>GENERAL</u> <u>SPECIFICATION - DVR USES TO</u> CCTV NETWORKING.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								TEL: +82-70-7147-8740-60 FAX: +82-31-8018-3745				
13	DNF50891	VCL-F850N/H-IR	585573515692 7 / NIGHT VISION IR CAMERA WITH 25 METER IR RANGE	CCTV CAMERA	2 / EACH/NUMBER			VISIONITE KOREA 4F, Yeolin Building, 487-12 Banghwa 1 Dong Gangseo Gu Seoul South Korea 157-849 Tel:+82(2)26610112 Fax:+82(2)26611505 E-mail:sales@visionite.com	VISIONITE KOREA		<u>TECHNICAL SPECIFICATION</u> - Sony 1/3" Super HAD CCD, High resolution of 550 TV lines, 25 IR LEDs, Maximum 25M IR distance, F=3.6/6/8/12mm board lens, Fixed IRIS IR corrective board lens, Weatherproof (IP65), Dimensions: 54Ø(mm) x 110mm <u>GENERAL SPECIFICATION</u> - Sony 1/3" Super HAD CCD, High resolution of 550 TV lines, 25 IR LEDs, Maximum 25M IR distance, F=3.6/6/8/12mm board lens, Fixed IRIS IR corrective board lens, Weatherproof (IP65), Dimensions: 54Ø(mm) x 110mm	
14	SNM61053	MSM GRFY 035F20D43	4820725177126 / MEGNIT SOLENOID	AGG HYDRO PP	1 / EACH/NUMBER	SRP-1010FP	NA	SCHOTTEL GmbH & Co KG D.56322 SPAY/RHEIN GERMANY	SCHOTTEL		<u>TECHNICAL SPECIFICATION</u> - oem: volvo penta schottel gmbh germany AMGNIT SOLENOID OPERATING VELVE 24VDC SUPPLY <u>GENERAL SPECIFICATION</u> - oem: volvo penta schottel gmbh germany AMGNIT SOLENOID OPERATING VELVE 24VDC SUPPLY	
15	SNO41175	NPX-35	6140015237323 / SEALED LEAD ACID BATTERY 12V, 35W, 15 MIN	UPS	20 / EACH/NUMBER			ENERSYS 1835 FOREST DR D4 ANNAPOLIS MD UNITED STATES PSC: 21401-4432 TEL: 800-820-4814 FAX: 410-268-1196 EMA: ENERSYS@VERIZON.NET	ENERSYS ANNAPOLIS, USA		<u>TECHNICAL SPECIFICATION</u> - 12V, 35W, 15 MIN <u>GENERAL SPECIFICATION</u> - 12V, 35W, 15 MIN	
16	SNF61941	OK-12SW-103-EE	5945715134550 / 24V RELAY	60 TONS A/C PLANT	10 / EACH/NUMBER	NO DATA AVAILABLE		US	CARRIER USA		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
17	DNS46873	196-013	4820735170611 / THERMOSTATIC VALVE FOR HT WATER	MAIN ENGINE	2 / EACH/NUMBER			WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	WARTSILA PAKISTAN		<u>TECHNICAL SPECIFICATION</u> - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821 <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	
18	DNF64024	WPS5-12	6140785223035 / LONG BATTERY 12 VOLT 5AH	10 KVA UPS WPS5-12	32 / EACH/NUMBER	WB5-12	APC	kung long batteries industrial co, ltd tel no +886-49-2254-777 FAX +886-19-2255-139 EMAIL SALES@MAIL.KIB.COM.TW	CHINA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
19	DPK58801	ISO VG 80	4320735157688 / SYNTHETIC COMPRESSOR OIL (Brand = VOLVO) ISO VG 80 (250 ML = Packing)	MAIN ENGINE VOLVO PENTA	90 / EACH/NUMBER		2006032390	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	VOLVO PANTA SWEDEN		TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY: AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY:AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	
20	DNM47835	2366057	4330715186669 / FILTER ELEMENT FUEL	D/G CATTER PILLAR C2.2	10 / EACH/NUMBER		JAW00494	USA	CATER PILLAR		TECHNICAL SPECIFICATION - oem : caterpillar GENERAL SPECIFICATION - oem : caterpillar	
21	SNF45837	225-230	6630795185146 / HD-TYPE 15 PIN FEMALE CONNECTORS	HF TX/RX XK2100L	10 / EACH/NUMBER	XK-2100L	NOT	FARNELL UK WAREHOUSE PHONE NO+448701200208	FARNELL UK WAREHOUSE PHONE NO+4487 01200208		TECHNICAL SPECIFICATION - HD-TYPE 15 PIN FEMALE CONNECTORS GENERAL SPECIFICATION - HD-TYPE 15 PIN FEMALE CONNECTORS	
22	SNM56579	2021196	3805995881286 / WASHER	D/G CATTER PILLAR C2.2	8 / EACH/NUMBER		JAW00494	USA	CATER PILLAR		TECHNICAL SPECIFICATION - Coating: None Overall Height (in): 0.05 Overall Width (in): 0.8 Overall Length (in): 0.8 GENERAL SPECIFICATION - Coating: None Overall Height (in): 0.05 Overall Width (in): 0.8 Overall Length (in): 0.8	
23	SNV56275	FZ400R12 KE3	5961785224756 / IGBT	FREQUENCY CONTROLLER	6 / EACH/NUMBER	INFINEON	-	ZHENG ZHOU ELECTROMECHANICAL REASERCH INSTITUTE NO-126 NING GUANG	ZHENG ZHOU ELECTR OMECHA		TECHNICAL SPECIFICATION - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								ROAD ZHENG ZHOU CHINA TEL:0371-67132002 FAX:0371-68714149	NICAL REASER CH INSTITUT E		CONVERTORGENERAL SPECIFICATION - POWER TRIGGING TO THE ELEVATION AND TRAINING FREQUENCY CONVERTOR	
24	SNM472 32	901-202	518079521555 0 / FUEL FILTER KIT	15 KVA DG	4 / EACH/N UMBER	SDG15PS	15403027	PERKINS ENGINES LTD! CENTRAL PARTS OPERATION UNITED KINGDOM	PERKINS ENGINE		TECHNICAL SPECIFICATION - AUTHROIZED DEALER perkins dg (S M JAFFER & CO KARACHI) GENERAL SPECIFICATION - AUTHROIZED DEALER perkins dg (S M JAFFER & CO KARACHI)	
25	DNF5735 4		601570522983 3 / OFC CABLE 48-FIBER (2X OFC CABLES ALONG PERIMTER)	PSS SYSTEM	1 / METER	PTCL- OFC -48	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL,PAKISTAN	LTE		TECHNICAL SPECIFICATION - OFC CABLE 48-FIBER FIBER TYPE: SINGLE MODE ITU-T G. 652D, G.655 & G.657GENERAL SPECIFICATION - OFC CABLE 48- FIBER FIBER TYPE: SINGLE MODE ITU-T G.652D, G.655 & G.657	
26	DNF5627 2	SC/UPC- SC/UPC	609970522981 9 / PATCH CHORDS FIBER (1.5 MTR) SC - LC	PSS SYSTEM	1 / EACH/N UMBER	SM-SC- LC	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL,PAKISTAN	LTE		TECHNICAL SPECIFICATION - PATCH CHORDS FIBER (1.5 MTR) SC - LCGENERAL SPECIFICATION - PATCH CHORDS FIBER (1.5 MTR) SC - LC	
27	DNS579 53	200 006	312073518541 4 / BELLOWS	WARTSILA MAIN ENGINE 9L20C3 FINLAND	6 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy	TECHNICAL SPECIFICATION - TPIGENERAL SPECIFICATION - TPI		
28	DNS576 34	471 066	534058000712 4 / PLATE	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy	TECHNICAL SPECIFICATION - TPIGENERAL SPECIFICATION - TPI		

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
29	DNS57633	471 584	201073518553 3 / FLUSHING CANAL SHAFT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	2 / EACH/ NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
30	DNS57635	471 062	534058000712 6 / PLATE	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/ NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
31	SGE48729	lc-08-ssp-01	562070522765 1 / DUST PRESSED, UNGLAZED PROCELAIN TILES (MASTER)	DECK	650 / EACH/ NUMBER	SSP-01- LL08	NIL	MASTER TILES PAKISTAN	MASTER TILES PAKISTA N		<u>TECHNICAL SPECIFICATION - AS PER LETTER ATTACH</u> <u>GENERAL SPECIFICATION - AS PER LETTER ATTACH</u>	
32	DNF57675	P-0113000	705078516678 9 / IPSAN HARDDISK_W D 2T	PSS	39 / EACH/ NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		<u>TECHNICAL SPECIFICATION - Harddisk_WD 2T</u> <u>GENERAL SPECIFICATION - Harddisk_WD 2T</u>	
33	SNF52110	DH-IPC- HD2231T- ZS-S2/ DH-IPC- HDBW223 1RP-ZS- S2/VFS / P-0123000	582078516679 9 / 2 MP WDR IR DOME NETWORK CAMERA	PSS VIGIL	8 / EACH/ NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
34	DPC48826	387 008	494073518627 2 / GLUE COMPOUND- LOCTITE 5399	WARTSILA MAIN ENGINE 9L20C3 FINLAND	4 / EACH/ NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel.	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
							AE084243 PAAE084 244	+358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380				
35	DNF6043 1	US/CHINA BRAND/ P- 0003	603078516496 3 / PREMIERE / PTCL OPTICAL FIBRE 6-CORE CABLE	PSS (CCTV SYS)	305 / METER			CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA. 100120	M/S CETC INTERNA TIONAL CO LTD		<u>TECHNICAL SPECIFICATION - DIAMETER 7.5MM Make: PREMIERE/PTCL cables</u> <u>GENERAL SPECIFICATION - DIAMETER 7.5 MM Make: PREMIERE/PTCL cables</u>	
36	DNQ580 81	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	53 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		<u>TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL</u> <u>GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL</u>	
37	SNJ4565 8	12892- 93J00-243	536576522237 1 / SHIM, TAPPET (T: 2425)	SUZUKI DF300AP 300 HP OBM	16 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
38	SNJ4565 9	12892- 93J00-245	536576522237 2 / SHIM, TAPPET (T: 2450)	SUZUKI DF300AP 300 HP OBM	16 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
39	SNJ4566 0	12892- 93J00-250	536576522237 4 / SHIM,	SUZUKI DF300AP 300	16 / EACH/N	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TAPPET (T: 2500)	HP OBM	UMBER						JAPANGENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN	
40	DNJ61109	09944-09820	5120705230990 / TILT CYLINDER CAP TOOL	300HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	M/S PAK SUZUKI MOTORS CO LTD, KARACHI TELEPHONE NO: 021-34723511		M/S PAK SUZUKI MOTORS	TECHNICAL SPECIFICATION - Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5 Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition GENERAL SPECIFICATION - Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5 Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition	
41	SNJ45663	12891-93J00	2895765222456 / TAPPET	SUZUKI DF300AP 300 HP OBM	12 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)	
42	SNJ52848	15440-93J00	2940765221800 / FILTER, FUEL (EPI)	SUZUKI DF300AP 300 HP OBM	25 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
43	DNF61134	S-100-12/YH-100-12 / P-0145000-A	6130785167249 / POWER SUPPLY 12V6A 119-239V	FIXED PTZ IP CAMERA	1 / EACH/NUMBER	YH-100-12		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120		M/S CETC INTERNATIONAL CO CETC CHINA	TECHNICAL SPECIFICATION - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664GENERAL SPECIFICATION - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664	
44	SNF51862	0702-004-00	5999795133797 / AUTO AND MANUAL START CONTROL	SSDG CATTERPILLAR	5 / EACH/NUMBER	NO DATA AVAILAB LE		UK		DEEP SEA ELECTRONICS PLC	TECHNICAL SPECIFICATION - oem, deep sea electronics (dse uk. local source. m/s pyramid automation 8-a/2 gulberg iii near hussain chowk lahore. tel: 92 42 35760910-2 fax 92	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MODULE (DSE 702)						HIGH FIELD HOUSE HUNMAN BY INDUSTRIAL ESTATE NORTH YORKSHIRE Y0114PH UK		42 35754944 e-mail: sales@PYRAMID AUTOMATION.com GENERAL SPECIFICATION - oem, deep sea electronics ()dse uk. local source. m/s pyramid automation 8-a/2 gulberg iii near hussain chowk lahore. tel: 92 42 35760910-2 fax 92 42 35754944 e-mail: sales@PYRAMID AUTOMATION.com	
45	SNM58651	2010TM-OR	2910013538540 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	20 / EACH/NUMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFIN		<u>TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u> GENERAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.	
46	DNF57683	VCNP-21OH-IR	5820705156826 / LONG RANGE IR CAMERA	CCTV CAMERA SYSTEM	1 / EACH/NUMBER			V SECURE VISION FIRE&SECURITY,OFFICE NO.16,CROWN CENTRE SB-1,BLOCK13-C, GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-34830466,34830392, FAX:+92-91-36832287.	V SECURE VISION FIRE&SECURITY		<u>TECHNICAL SPECIFICATION - V SECURE VISION FIRE&SECURITY, OFFICE NO.16,CROWN CENTRE SB-1,BLOCK13-C,GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-34830466,34830392,FAX:+92-91-36832287. OEM:VISION INC KOREA</u> GENERAL SPECIFICATION - V SECURE VISION FIRE&SECURITY,OFFICE NO.16, CROWN CENTRE SB-1,BLOCK13-C,GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-34830466,34830392,FAX:+92-91-36832287. OEM:VISION INC KOREA	
47	SNF54692	KX-2375MXW	5805735157736 / PHONE SET (PANASONIC)	PHONE SET	20 / SET			OEM:PANASONIC COMMUNICATION MALAYSIA SON-SENAI.	PANASONIC COMMUNICATION		<u>TECHNICAL SPECIFICATION - OEM:PANASONIC COMMUNICATION MALAYSIA SON-SENAI.</u> GENERAL SPECIFICATION - OEM: PANASONIC COMMUNICATION MALAYSIA SON-SENAI.	
48	SNF4682	c60hc206	592573522829	Steering	5 /	C60HC20	NIL	M/S Scenario International	Schneider		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	0	6A	5 / DOUBLE POLE CIRCUIT BREAKER	Control System	EACH/NUMBER	6 6A		Karachi Ph No 0324-2636007			OEM: SCHNIDER ELECTRIC FRANCE GENERAL SPECIFICATION - OEM: SCHNIDER ELECTRIC FRANCE	
49	DNC56249	8M0103373	2990MB0020692 / HEAD STEERING	PETROL MAIN ENGINE	1 / EACH/NUMBER	350	2B614987 2B612137 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		TECHNICAL SPECIFICATION - HEAD STEERING GENERAL SPECIFICATION - HEAD STEERING	
50	DNJ61144	6E5-14198-A2	5330765217948 / GASKET	200 AET 18 (60JK) OBM ENGINE	4 / EACH/NUMBER	L200AET18(60JK)	6K1-X-1012721X	2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
51	SNM59314	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
52	SNM56578	10000-46312	2915795175309 / LIFT PUMP KIT	45KVA PERKIN	1 / EACH/NUMBER		45KVA PERKIN	CATTER PILLER UK	UK		TECHNICAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX. RX1 GUARANTEED 144-148 MHZ RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 Ω) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLE ICOM) S BATTERY PACK ONLY CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK) GENERAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX. RX1 GUARANTEED 144-148 MHZ RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 Ω) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLE ICOM'S BATTERY PACK ONLY) CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK)</p>	
53	DNF64022	FSM-80S/90S+	6060765204977 / OPTICAL FIBER SPLICER FUJIKURA	Optical Fiber Splicer FSM-80S JAPAN	1 / EACH/NUMBER	FSM-80S/90S+		1-5-1, Kiba, Koto-ku, Tokyo 135-8512, Japan Phone:+81-3-5606-1164 Fax:+81-3-5606-1534 http://www.fujikura.co.jp		Fujikura Ltd JAPAN	<p>TECHNICAL SPECIFICATION - Optical Fiber Splicer Fujikura World's quickest splicing 7sec. / tube-heating 14sec. - Minimal manual operation. Splice in 4 steps. - Multifunctional carrying case with integrated work station. - Absolute robustness. Make FUSION, FUJIKURA RIBBON Parent</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											equipment Optical fiber splicer tool GENERAL SPECIFICATION - Optical Fiber Splicer Fujikura World? s quickest splicing 7sec. / tube-heating 14sec. - Minimal manual operation. Splice in 4 steps. - Multi-functional carrying case with integrated work station. - Absolute robustness. Make FUSION, FUJIKURA RIBBON Parent equipment Optical fiber splicer tool	
54	DNF60037	RX-M2700	5998785223199 / MAIN CONTROLLER	RX-2700 XP CONFERENCE SYSTEM RX-2700 XP CHINA	1 / SET	RX-2700 XP	NA	RESTMOMENT FACTORY ADDRESS:NO4-1,E BOROUGH, DONGAN INDUSTRIAL ESTATE ENPING CITY, GAUNGDONG, CHINA.		RESTMOMENT	TECHNICAL SPECIFICATION - AS PER ATTACHMENT ENCLOSED GENERAL SPECIFICATION - AS PER ATTACHMENT ENCLOSED	
55	SNF48508	ER 3215 TOA JAPAN/IN DONESIA	0512700060001 / APOLLO TRASISTOR MEGAPHONE MODEL PA-535S 12-18W 1.5VX6	USE END SELF	6 / EACH/NUMBER	ER-3215					TECHNICAL SPECIFICATION - BROUCHER ATTACHED GENERAL SPECIFICATION - BROUCHER ATTACHED	
56	DPC61632		0474504740079 / POWDER P.B.N		100 / KILOGRAMME						TECHNICAL SPECIFICATION - SPECIFICATION 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>SPECIFICATION - SPECIFICATION</u> 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG</p>	
57	DPC61200		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						<p><u>TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u> <u>GENERAL SPECIFICATION -1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg</u></p>	
58	DPC63466	NO DATA AVAILABL E	044450001055 1 / SOLUTION FOR SCALE REMOVING packing 20 or 25 ltr		50 / LITER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABL E</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABL E</u></p>	
59	DGB52205	SOEC.BS 2874, CZ112M	028359571144 2 / ROD NAVAL BRASS		28 / METER						<p><u>TECHNICAL SPECIFICATION - standard BSEN 12163 of 1998 Grade 712 (M)</u> <u>GENERAL SPECIFICATION</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			RD DIA.9.525 MM WT PER MTR 0.615 KG								- standard BSEN 12163 of 1998 Grade 712 (M)	
60	DPC611 93	Defstan 80-78 OF 1995	044250942119 3 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	500 / LITER						<u>TECHNICAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) <u>GENERAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
61	SGB487 25		026759521638 3 / PIPING STEEL SEAMLESS, GALVANIZED, L:6 M, E/DIA: 1.344", W/THICKNESS :0.128", N/BORE:1.0"	NIL	35 / METER						<u>TECHNICAL SPECIFICATION -</u> SPECS. FOR GALVANIZED SEAMLESS BS EN ISO 1461: 2022 GRADE P. 265 GH <u>GENERAL</u> <u>SPECIFICATION - SPECS. FOR</u> GALVANIZED SEAMLESS BS EN ISO 1461: 2022 GRADE P. 265 GH	
62	DGB408 16		026659136213 2 / SCREW COACH WOOD STEEL SQUARE HD point. gimlet	GIMLET	40 / TEN						<u>TECHNICAL SPECIFICATION - 1.</u> Screw Length 4.0 Inch 2. Screw Dia 0.625 (5/8) inch (15 mm) 3. Thread size 5 threads per inch 4. Material grade 42 CrMo4 or 708M40 AISI 4140 (PD 970:2005 Material Grade 708M40 or 42CrMo4) for clarity and quality inspection c. Packing detail As per standard d. Acceptance criteria Screw coach wood steel Square HD SIZE: POINT. GIMLET (As per sample attached C. COC / AUTHORIZED DEALER CERTIFICATE/ MILL TEST CERTIFICATE (MTC): OEM COC/AUTHORIZED DEALER CERTIFICATE/MILL TEST CERTIFICATE (MTC) IS REQUIRED TO PROVIDE BY SUPPLIER AT THE TIME OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>INPECTIONGENERAL SPECIFICATION - 1. Screw Length 4.0 Inch 2. Screw Dia 0.625 (5/8) inch (15 mm) 3. Thread size 5 threads per inch 4. Material grade 42 CrMo4 or 708M40 AISI 4140 (PD 970:2005 Material Grade 708M40 or 42CrMo4) for clarity and quality inspection c. Packing detail As per standard d. Acceptance criteria Screw coach wood steel Square HD SIZE: POINT. GIMLET (As per sample attached C. COC / AUTHORIZED DEALER CERTIFICATE/ MILL TEST CERTIFICATE (MTC): OEM COC/AUTHORIZED DEALER CERTIFICATE/MILL TEST CERTIFICATE (MTC) IS REQUIRED TO PROVIDE BY SUPPLIER AT THE TIME OF INPECTION</u></p>	
63	SGB56146		026759923534 9 / TEE PIPE EQUAL (GALVANISED) 03.00IN		50 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm <u>GENERAL SPECIFICATION -</u> Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm</p>	
64	SGB58592		021459013101 5 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3. 750X1.250 INCH		40 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable. <u>GENERAL SPECIFICATION -</u> Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable.</p>	
65	SGB31618	BS1769, 0214-941- 0019	021459941001 9 / BOLT MACHINE STEEL UNC class 2a HEX HD SZ 0.625 X3.000X1.500 IN	BR-320 D/78	300 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> SPECIFICATION : (PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC <u>REQUIREDGENERAL SPECIFICATION -</u> SPECIFICATION : (PD 970:2005, MATERIAL GRADE 708M40/ 42CRM04 AUTHORITY : AS PER BR-320D OEM COC/MTC</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											REQUIRED	
66	DGE57595	NO DATA AVAILAB LE	032059923270 3 / Coir Yarn Type Good Quality 112 LBS		140 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg end user: pnd w/shop 105 oem coc/certificate: n/a <u>GENERAL SPECIFICATION -</u> Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg end user: pnd w/shop 105 oem coc/certificate: n/a	
67	SGB51719	0254-5672	025478420320 3 / CLAMP HOSE TERRY BRAND SZ 0.875 TO 1.125 X0.505X0. 038IN	FUEL TANK	250 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35 <u>GENERAL SPECIFICATION -</u> Code Number: 442-035, Adjustment: 25-35mm (1" -1 3/8"), Acceptance Criteria: BS 5315 Standard, BS Code 35	
68	SGB56143		026659441325 5 / SCREW MACHINE C/ALLOY FLAT FILLISTER, SLOT DRIVE SZ 1X0.250"		200 / TEN						<u>TECHNICAL SPECIFICATION - a.</u> size: 1 x 0.250" b. Dimension: 52- TEN c. Material: Brass <u>GENERAL</u> <u>SPECIFICATION - a.</u> size: 1 x 0.250" b. Dimension: 52-TEN c. Material: Brass	
69	SGE46997		2040PK510105 2 / RUBBER SHEET SIZE WEIGHT: 10- KG, LENGTH: 7-ft, WIDTH: 1- FT, THICKNESS: 3/8-INCH	FENDER	16 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552 <u>GENERAL SPECIFICATION - MATERIAL:</u> NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
70	SNF52091	0585-67691	058579412852 3 / LAMP-HOLDER-PORCELAIN 3/4 IN FEMAL CONNECTION SCREW SEE 196		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
71	DNH64015	NO DATA AVAILABLE	130850053011 6 / AIR CONDITIONER 1.5 TON WINDOW TYPE		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
72	DPC52664	DSL 101/SOFNOLIME 2050	047350473005 0 / SODA LIME DSL 101 TYPE:		50 / TIN/PKT						<u>TECHNICAL SPECIFICATION - COLOUR WHITE, COLOUR ON SATURATION VIOLET, GRAINS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8 <u>GENERAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
78	SGB23328	MILE22200-2QA	343900865471 1 / ELECTRODE WELDING 3.25 MM	WELDING (STAINLESS STEEL)	30 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> AWS E309-16 STAINLESS STEEL size 3.25 MM <u>GENERAL SPECIFICATION -</u> AWS E309-16 STAINLESS STEEL size 3.25 MM	
79	SGB57071	SKF 6314 Z (2DOT)	311099950013 7 / BEARING BALL JOURNAL SINGLE ROW 70X150X35 MM	FOR GENERAL USE ONLY	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SKF 6314 Z (2DOT) <u>GENERAL SPECIFICATION -</u> SKF 6314 Z (2DOT)	
80	DGP57770		361070500723 7 / PAGE CORD TWIN COMPOSING		20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection <u>GENERAL SPECIFICATION -</u> 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection	
81	DNH63958	wdf-318	411073100120 0 / DEEP		1 / EACH/N	WDF-318					<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILABLE <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
82	DNH64018	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
83	SNM48967	1P 1111	3120012257648 / BEARING WASHER THRUST	CATTER PILLAR DIESEL GENERATOR (USA)	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - length:96mm high:5.1mm width:71.1 mm</u> <u>GENERAL SPECIFICATION - length:96mm high:5.1mm width:71.1 mm</u>	
84	DGP64072	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u> <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CDs.	
85	SNM52382	3915506	482071509827 7 / VALVE INTAKE	6CT,6CTA8.9, CUMMINS D/G USA	6 / EACH/N UMBER	6CT, 6CTA8.9					<u>TECHNICAL SPECIFICATION - BRAND: CUMMINS WEIGHT: 0.036 KG SIZE: 18X19X4 CM</u> <u>GENERAL SPECIFICATION - BRAND: CUMMINS WEIGHT: 0.036 KG SIZE: 18X19X4 CM</u>	
86	SGB44917		482070502618 8 / GATE VALVE 4 INCH FLANGE O/D 214MM I/D97.5 MM/12MM	DISCHARGE VALVE	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - c. Detail of Valve i. Outer Dia of Flange 225 mm ii. Inner dia 04" iii. Flange to Flange 230mm iv. No of Holes 08 v. Bolt Hole Size 18mm vi. PCD 192mm MS GRADE 40</u> <u>GENERAL SPECIFICATION - c. Detail of Valve i. Outer Dia of Flange 225 mm ii. Inner dia 04" iii. Flange to Flange 230mm iv. No of Holes 08 v. Bolt Hole Size 18mm vi. PCD 192mm MS GRADE 40</u>	
87	SNM52366	8S1963	533001069099 2 / GASKET	CATTER PILLER DIESEL GENERATOR (USA)	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
88	SNM45761	5S-6348	531000557938 9 / NUT	CATTER PILLER DIESEL GENERATOR (USA)	12 / EACH/N UMBER	7N3277 (3304 PC)					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
89	SNM52380	33415118	534099201964 6 / WASHER	P40,WATER PUMP THERMOSTAT E PERKINS DG UK	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - weight: 5g dimensions 4x4x1cm</u> <u>GENERAL SPECIFICATION - weight: 5g dimensions 4x4x1cm</u>	
90	DNF64032	LCIR127R 2PG1(SEE F8 FOR L/ADDRES	614576509185 7 / SEALED LEAD ACID BATTERY 7.2 AH/20HR12V SZ5.7"X3.5"X2. 3"L.H.W	UPS APC ASIS SYSTEM	49 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - dDESCRIPTION: a. Sealed lead Acid Dry battery 12 Volt 7.0 AH b. Sealed lead Acid Dry battery 12 Volt 7.0 AH c. Sealed lead Acid Dry battery 12 Volt 7.2 AH mAKE/MODEL: A. Ebaam 12HD7.0 b. Leoch DJW 12-7.0 c. VOLTA NP-7-12 oem: a. eBAAM USA B. LEOCH CHINA C. VOLTA PAKISTAN</u> <u>GENERAL SPECIFICATION - dDESCRIPTION: a.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Sealed lead Acid Dry battery 12 Volt 7.0 AH b. Sealed lead Acid Dry battery 12 Volt 7.0 AH c. Sealed lead Acid Dry battery 12 Volt 7.2 AH mAKE/MODEL: A. Ebaam 12HD7.0 b. Leoch DJW 12-7.0 c. VOLTA NP-7-12 oem: a. eBAAM USA B. LEOCH CHINA C. VOLTA PAKISTAN	
91	DNF45057	1354-01	625000299596 2 / STARTER FLUORESCEN T 2PINS 110/220V	TUBE LIGHTES	311 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
92	SNF57081	cs-154 /TC-154	596517110315 8 / LOUDSPEAKE R PERMANENT 10-15 w WITH MATCHIN TRANSFORMA R & ACCESS	SRC SYSTEM	3 / EACH/N UMBER	MODEL TC-154					<u>TECHNICAL SPECIFICATION - EXACT MAKE/BRAND/OEM: TOA CORPORATION. LTD, JAPAN SOURCE OF AVAILABILTY : [GIANT ENTERPRISES] ADDRESS: [A-87/3, 1ST FLOOR, GULSHAN-E-IQBAL KARACHI]</u> <u>GENERAL SPECIFICATION - EXACT MAKE/BRAND/OEM: TOA CORPORATION. LTD, JAPAN SOURCE OF AVAILABILTY : [GIANT ENTERPRISES] ADDRESS: [A-87/3, 1ST FLOOR, GULSHAN-E-IQBAL KARACHI]</u>	
93	SNF38102	ZS061B	596576508839 4 / BOX SPEAKER 10WATTS WITH MATCHING TRANSFORME R	SRE SYSTEM	6 / EACH/N UMBER	BS1034S					<u>TECHNICAL SPECIFICATION - BROUCHER ATTACHED: MAKE/BRAND:TOA JAPAN, MODEL:BS1034S WALL MOUNTED BOX SPEAKER</u> <u>GENERAL SPECIFICATION - BROUCHER ATTACHED: MAKE/BRAND:TOA JAPAN, MODEL:BS1034S WALL MOUNTED BOX SPEAKER</u>	
94	SNF51823	TC-154S	596576510216 7 / SPEAKER 15W HORN WITH MATCHING TFMR & VOLUME CONTROL	SRE SYSTEM , TOA JAPAN	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
95	SNC52813	ELEC-2650 / IN 63047/2650	6230795110272 / SEARCH LIGHT HAND HELD (24V DC&230 WATT)	GRIFFON HOVER CRAFT LTD UK	50 / EACH/NUMBER	GEEPAS®					TECHNICAL SPECIFICATION - 1. Make/ Brand: GEEPAS® 2. Model: GSL5706 - 30Watt GENERAL SPECIFICATION - 1. Make/ Brand: GEEPAS® 2. Model: GSL5706 - 30Watt	
96	SNF51846	sc-615/ sc-630m/ TC15ML/TC10ML TOA	9512700030004 / LOUD-SPEAKER HORN TYPE	PA SYSTEM/SRE SYSTEM	10 / EACH/NUMBER	TC15ML/TC10ML TOA sc-615					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	SGB12088		0214590530839 / NUT PLAIN HEXAGON, BSF MEDIUM CLASS 7/8 INCH		480 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - HEAD: HEXAGON, THREAD SERIES: BSF MEDIUM CLASS, STYLE: A, THREAD SIZE: 7/8 INCH (0.875"), DIMENSIONS: AF: 1.300 INCH, THICKNESS: 0.750 INCH Specifications: DEF STAN 02-862 Part 2 Issue 3 Class B, Material Grade: BSEN 10269 21CrMoV5-7 GENERAL SPECIFICATION - HEAD: HEXAGON, THREAD SERIES: BSF MEDIUM CLASS, STYLE: A, THREAD SIZE: 7/8 INCH (0.875"), DIMENSIONS: AF: 1.300 INCH, THICKNESS: 0.750 INCH Specifications: DEF STAN 02-862 Part 2 Issue 3 Class B, Material Grade: BSEN 10269 21CrMoV5-7	
98	DPK61621	ISO VG 460	9150701003321 / OIL-SHELL OMALA S2 G 460 (PACKING 209 LTR DRUM)	BHER-E-PAIMA	60 / LITER						TECHNICAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSURE GENERAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSURE	
99	SGB52128		0275500000026 / MEASURING TAPE STEEL ½" x 300'		3 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition GENERAL SPECIFICATION - Crescent Lufkin	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											½” x 300’ Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition	
100	SNF52103	ADAMJEE / bs-4678 (n)	5330705118843 / CHANNEL PATTI duraduct p/w 3m 01" INCH (16x25) adamjee	CHANNEL PATTE	350 / EACH/NUMBER	BS-4678 (N) adamjee					<u>TECHNICAL SPECIFICATION</u> - oem, adam jee karachi pakistan <u>GENERAL SPECIFICATION</u> - oem, adam jee karachi pakistan	
101	DNF58744	NO DATA AVAILABLE	5965705120723 / SINGLE CORE CABLEFOR HORN SPEAKER	PA SYSTEM	200 / METER						<u>TECHNICAL SPECIFICATION</u> - 1. PURE COPPER WIRE 2. ELECTRO-VOICE SINGLE CORE CABLE 3. INSULATION MATERIAL PVCA 4. IMPEDENCE 75 OHM <u>GENERAL SPECIFICATION</u> - 1. PURE COPPER WIRE 2. ELECTRO-VOICE SINGLE CORE CABLE 3. INSULATION MATERIAL PVCA 4. IMPEDENCE 75 OHM	
102	SNF52105	LOCAL A/P DESCRIPTION	0559780000402 / FUSE GLASS QUICK BLOW 10 AMP 12X39MM	MSI	350 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
103	DNH63932	APPROVED MODEL	1308500530109 / REFRIGERATOR-4-CU-FT-ANY COMMERCIAL BRAND		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
104	SNF54647	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	2 / EACH/NUMBER	DPSI OLYMPUS					<u>TECHNICAL SPECIFICATION</u> - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	
105	SNF51854	TH-652/TU-651M/650M	598576512072 2 / LOUD SPEAKER HORN TYPE WITH UNIT 50W. 250HZ-6KHZ (TOA)	PA SYSTEM TOA	2 / EACH/NUMBER	TH-652 TOA					TECHNICAL SPECIFICATION - dust,water,weather protected speaker. Maximum power 50W. 250Hz-6KHz frequency response. Built-in line transformer. TOA, DynacordGENERAL SPECIFICATION - dust,water, weather protected speaker. Maximum power 50W. 250Hz-6KHz frequency response. Built-in line transformer. TOA, Dynacord	
106	SNM47233	7E9658	471071512827 8 / CONTACTOR (WATER TEMPERATURE)	D/G	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - oem: catterpillar GENERAL SPECIFICATION - oem: catterpillar	
107	SNM57034	26561118	294099126340 8 / seFUEL FILTER OF PERKIN DIEI generator 153.5 kva		10 / EACH/NUMBER	26561118					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
108	SNF52839	MCTX-4PRT-SWTC	593070524871 2 / 4 PORT SWITCH		10 / EACH/NUMBER	MCTX-4PRT-SWTC					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
109	DN061062	7620.464.004.4	2815FP303038 3 / Hole-type nozzle		6 / EACH/NUMBER	tbd620v12					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
110	DNF58178	HST-cjx2-1810/HEP-600C-12	5935705246117 / magnetic connector		3 / EACH/NUMBER	CJX2-1810 C-LIN					TECHNICAL SPECIFICATION - as per enclosed GENERAL SPECIFICATION - as per enclosed	
111	DNZ58913	E-03-12	2815785277599 / THREE-STAGE PISTON		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
112	DNO61837	447-8230	2930715234012 / Seawaterpump Gp Aux		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Seawaterpump Gp Aux GENERAL SPECIFICATION - Seawaterpump Gp Aux	
113	DSB63553		0011041950216 / THERMOSTAT E T021 16(2)A-250/380V~50T O300C		2 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Part no: Not Available Make/ Model/ Brand/ Equivalent : DEST 0-300 °C KOREA Further information may be obtained from under mentioned supplier: HUMAYUN ELECTRIC HEATER Shop#, Aram Bagh Electric Market, Shahrah-e-Liaqat, Karachi. 0300-9200510,0324-3234032 GENERAL SPECIFICATION - Part no: Not Available Make/ Model/ Brand/ Equivalent : DEST 0-300 °C KOREA Further information may be obtained from under mentioned supplier: HUMAYUN ELECTRIC HEATER Shop#, Aram Bagh Electric Market, Shahrah-e-Liaqat, Karachi. 0300-9200510,0324-3234032	
114	DNM63933	0122-0922/LF16087	2940715267678 / ELEMENT LUBE OIL FILTER (FFL PART No. LF16087)		2 / EACH/NUMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
115	SNJ45509	16543-96J00	5331765265137 / O RING		2 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN) GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)	
116	DNM611	332-7865	597571523880		600 /	C7.1					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	43		5 / TIE-CABLE		EACH/NUMBER						NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
117	SNF57094	HTS-PB-3B /SUN433 2CH PB-3B	593070524688 3 / PUSH BUTTON		6 / EACH/NUMBER	SUN 433 2CH					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
118	DSB62174	YED0526/01 - A4E02596	6110FT102866 8 / Power Bridge		3 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
119	SNM56664	6I-0839	5306014715310 / BOLT (M8X1.25X70-MM)		10 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48 GENERAL SPECIFICATION - BOLT LENGTH (IN): 2X3/4 BOLT TYPE: HEX FLANGE HEAD COATING: ZINC PLATED GRIP LENGTH (IN): 1.89 THREAD: COARSE THREAD SIZE (IN - TPI) (IN): M8-1.25 NOTES: THREAD LENGTH (MM): 48	
120	SNF48719	04070916	591578527938 7 / hdmi usb slave cable (otg) cable		8 / EACH/NUMBER	D14581-01-03					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
121	SRP39050	TEXAMATIC 1888	9150ZO653196 7 / FLUID AUTOMATIC TRANSMISSION (PACK 01LI)		100 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPA.S @ 40 OC: 15000, VISCOSITY KINEMATIC, MM2/S@ 40OC: 35.8, MM2/S @ 10OC: 7.2, VISCOSITY INDEX: 168, FLASH: >190 (CLEVELAND OPEN-CUP). GENERAL SPECIFICATION - CALTEX TEXAMATIC 1888, MAKE: CALTEX, CHEVRON, COLOUR: RED, POUR POINT, OC: -51, VISCOSITY BROOK FIELD, MPA.S @ 40 OC: 15000, VISCOSITY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											KINEMATIC, MM2/S@ 40OC: 35.8, MM2/S @ 10OC: 7.2, VISCOSITY INDEX: 168, FLASH: >190 (CLEVELAND OPEN-CUP).	
122	DNZ5891 2	E-02-02	299078527763 6 / SECONDARY PISTON		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
123	DSB6215 1	CMY30070 5 / MAT- 662-0076- C	6125TY672078 1 / AEI AGOSTA VARIATOR-DT COMPLETE UNIT (HYDRAULIC PUMP)		2 / EACH/ NUMBER	CMY300					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
124	SNF5281 5	mctx-elct- pnl	597570524610 5 / electrical panel		6 / EACH/ NUMBER	MCTX- ELCT- PNL					<u>TECHNICAL SPECIFICATION - BROUCHER ATTACHED</u> <u>GENERAL SPECIFICATION - BROUCHER ATTACHED</u>	
125	DNF4685 5	9FN066- 008	702501599393 2 / SEAGATE HDD 15K.7 NCC/NMS SERVER DB SERVER		3 / EACH/ NUMBER	n/a					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
126	DNZ5891 7	E-02-11	481078527758 7 / SECONDARY EXHAUST VALVE		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
127	DNO474 01	545-9773	294077526649 7 / CIRCUIT BREAKER (20- AMPERE,2- POLE)		5 / EACH/ NUMBER	3516E					<u>TECHNICAL SPECIFICATION - CIRCUIT BREAKER (20-AMPERE,2-POLE)</u> <u>GENERAL SPECIFICATION - CIRCUIT BREAKER (20-AMPERE,2-POLE)</u>	
128	DNF6121	NI 2020	614070524600		5 /	NI 2020					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	5		1 / Lithium Ion Battery 10.8V OF 3D X-RAY SCANNER		EACH/NUMBER						nullGENERAL SPECIFICATION - null	
129	SNH56812	244862	5330785283914 / PACKING VEE, TUFFSTACK (PISTON)		10 / PACKING	70:1					TECHNICAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEAKAGE OF LUBRICANTS GENERAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEAKAGE OF LUBRICANTS	
130	SNF51959	lx3v-0806mt-a1	5998705246116 / 1xplc		2 / EACH/NUMBER	LX3V-0806MT-A1					TECHNICAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA GENERAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA	
131	SNF52835	cob 61	5930705246094 / push button		10 / EACH/NUMBER	COB 61					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
132	DNF49163	33010328	6685785240916 / TEMPERATURE AND HUMIDITY SENSOR FOR RDU-SIC		3 / EACH/NUMBER	2311720					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
133	SNJ45496	17400-87101 / 17400-96J03	2805705267440 / water pump repair kit		6 / EACH/NUMBER	df150 suzuki					TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN	
134	DSB62152	CMY300900 / MAT-662-0076-C	6125TY6720782 / AEI AGOSTA VARIATOR-DM COMPLETE UNIT (REGULATING PUMP)		2 / EACH/NUMBER	CMY300					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
135	SNF57080	EM-380-AS	5965785235026 / TOA GOOSENECK MICROPHONE		2 / EACH/NUMBER	EM-380-AS					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	