

TENDER BULLETIN

DATE & TIME 5/13/24 1:26 PM INVITATION TO TENDER TO BE OPENED ON 5/27/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	SCP62746		653250000025 1 / TOWEL OPERTING HOSPITAL SIZE 42 X 30		1000 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TOWEL OPERTING HOSPITAL SIZE 42 X 30</u> <u>GENERAL SPECIFICATION - TOWEL OPERTING HOSPITAL SIZE 42 X 30</u>	
2	DGE47200	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	26 / ROLL			LOCAL MARKET		GENERA L ITEM	<u>TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm</u> <u>GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm</u>	
3	DGD20681	NO DATA AVAILABL E	003550000038 8 / MACHINE POTATO CHIPPING (DLT VIDE LTR ST-V/1732 DT. 06-12-92		5 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
4	SGE22550	23-53-21- 17-01SA	047670520731 9 / SHOOTER GLOVES	GLOVE	60 / EACH/N UMBER	X-PRO by Alif	NA	M SADIQ ALI & SONS, 217/15,SALEH MARKET, ADAMJEE ROAD, SADDAR, RAWALPINDI. 051-5527252 051-5513958		M SADIQ ALI & SONS	<u>TECHNICAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stiching for heavy duty protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design (X-PRO by Alif).</u> <u>GENERAL SPECIFICATION - goatskin leather (abrasion resistant) reinforced palm and double stiching for heavy duty</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											protection from abrasion reinforced digital leather layer with antislip feature and grip for tactical applications durable, lightweight, breathable and comfortable adjustable wrist design (X-PRO by Alif).	
5	DNC60434	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	500 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK		GRIFFON HOVER WORK	<u>TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK</u> <u>GENERAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK</u>	
6	SGE56527		0422705158411 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 0.15 M.)	SELF	1200 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.		M/S ANWAR PLASTICS, SADDAR KARACHI	<u>TECHNICAL SPECIFICATION - SHEET LENGTH 18.5 M WIDTH 1.5 m THICKNESS 1.5 M</u> <u>GENERAL SPECIFICATION - SHEET LENGTH 18.5 M WIDTH 1.5 m THICKNESS 1.5 M</u>	
7	DNF57848	CAT-6A U-FTP	5995785207850 / CABLE NETWORK CAT-6A U-FTP 23AWG PE-0.36MM 4/U-FTP PVC/LSZH-0.5 MM AQUA/BLEU/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	700 / FOOT	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883		CHINA	<u>TECHNICAL SPECIFICATION - oem, contech solution USA. www.CONTECH SOLUTION.COM</u> Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION - oem, contech solution USA. www.CONTECH SOLUTION.COM</u> Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
8	DNS61701	1161231-4 / 1161231	5130735159441 / SEALANT	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	4 / EACH/NUMBER	D9A2A MG HE		WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR		WARSILA FINLAND	<u>TECHNICAL SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								+358 10 709 0000 OR ANY DIRECT DIAL NUMBER			SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND DURING OFFICE HOURS (7.30-16.30) CALL OPERATOR +358 10 709 0000 OR ANY DIRECT DIAL NUMBER	
9	DNS576 28	471 086	531058000712 2 / NUT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	8 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
10	DNS579 60	200 010	531073518548 3 / WASHER	WARTSILA MAIN ENGINE 9L20C3 FINLAND	248 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
11	DNS579 57	200 008	530573518546 5 / SEALING RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	38 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
12	DNS576 38	471 188	251073518555 3 / TENSION RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380				
13	DNS479 36	165 015	281573518568 7 / RETAINER RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	36 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
14	DNS564 15	1PS100-P- 5-S	482099297804 6 / SEQUENCE VALVE PILOT OPERATED	WARTSILA STERN THRUSTER PROP CS250- S/WO-K HOLLAND	1 / EACH/N UMBER	WART- LCT- CS250- S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsio n Netherlan ds B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
15	DNS564 16	3CA80- 0.2-S	482077518808 1 / CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250- S/WO-K HOLLAND	1 / EACH/N UMBER	WART- LCT- CS250- S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsio n Netherlan ds B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
16	DNS564 17	3CA80- 3.5-S	482077518808 2 / CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250- S/WO-K HOLLAND	1 / EACH/N UMBER	WART- LCT- CS250- S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsio n Netherlan ds B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
17	DNS576 36	471 601	310073518604 4 / BALL BEARING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	2 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20</u> <u>GENERAL SPECIFICATION - OEM: WARTSILA MAKE: FINLAND MODEL: 9L20</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
							PAAE084 244	74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380				
18	SNM455 65	8N6058	533001388242 2 / GASKET - TURBO OUT	CATERPILLAR DG 3304B	10 / EACH/N UMBER			CATERPILLAR INC.!DBA CATERPILLAR DIV DEFENSE &! FEDERAL PRODUCTS 14009 OLD GALENA RD TC-A MOSSVILLE UNITED STATES TEL:3095786941 FAX:3095783739 HTTP://WWW.CAT.COM	CATERPI LLAR		<u>TECHNICAL SPECIFICATION - OEM & MAKE:</u> <u>CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE:</u> CATERPILLAR	
19	SGE493 61	TIGER BRAND	046159000776 7 / SCREEN HAND FOR ELECTRIC WELDING WITH GLASS BLACK.		30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Material: High Density Polyethylene HDPE Size: 9 x 6 inch or any suitable size Color: BLACK Style: FULL FACE</u> <u>GENERAL SPECIFICATION - Material: High Density Polyethylene HDPE Size: 9 x 6 inch or any suitable size Color: BLACK Style: FULL FACE</u>	
20	DGE604 54	0413-2441	041359923877 6 / HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0. 875"X60 FT LG, 3PLY.		980 / METER						<u>TECHNICAL SPECIFICATION - 1.</u> HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0.875"X60 FT LG, 3-PLY. 2. TEST PRESSURE- 250 PSI, 3. NATURAL RUBBER, INNER SURFACE AND OUTER COVERING, REINFORCED WITH RUBBER IMPREGNATED FABRIC, COLOUR: NATURAL, 4. SPECIFICATION: BS2860, BR-1975, T-50 <u>GENERAL SPECIFICATION - 1.</u> HOSE RUBBER INTERNAL EXTERNAL DIA 0.500'X0.875"X60 FT LG, 3-PLY. 2. TEST PRESSURE- 250 PSI, 3. NATURAL RUBBER, INNER SURFACE AND OUTER COVERING, REINFORCED WITH RUBBER IMPREGNATED FABRIC, COLOUR: NATURAL, 4. SPECIFICATION: BS2860, BR-1975,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											T-50	
21	DGE38745		0474504740126 / SHAMIANA COMPLETE SZ. 18.00X36.00 FT		5 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)</u></p> <p><u>GENERAL SPECIFICATION - MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)</u></p>	
22	SGE47449	NO DATA AVAILABLE	0461590006480 / PAINT ROLLER 7 INCH,C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	550 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</u></p> <p><u>GENERAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</u></p>	
23	SGB56158		0283595711430 / ROD NAVAL BRASS HEX		16 / METER						<p><u>TECHNICAL SPECIFICATION - SIZE A/F 0.82", WT PER FT 2.170 (LB), bs 2874 cz 112 m. Acceptance criteria: as per size and specifications, or item sample may be shared with Machine Shop (C. No. 205) for acceptance or otherwise.</u></p> <p><u>GENERAL SPECIFICATION - SIZE A/F 0.82", WT PER FT 2.170 (LB), bs 2874 cz 112 m. Acceptance criteria: as per size and specifications, or item sample may be shared with Machine Shop (C. No. 205) for acceptance or otherwise.</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
24	DGE44803		0421599244635 / CHAIR-PEDESTAR		25 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DGE55542		0421599425637 / FILING CABINET SIZE, 4-DRAWERS W/LOCK combination AND COMPRESSOR PLATES GREY GUAGE SWG:22 SIZE; W18 INCH		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user GENERAL SPECIFICATION - GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	
26	SGB39775	FLUXITE PASTE	0283595711610 / FLUX SOLDERING PASTE FORM FLUXITE TYPE 4509 TIN (500GRAM TIN)		40 / TIN						TECHNICAL SPECIFICATION - Multi-purpose paste flux Well established product Quick and clean to use WRAS Approved Product Suitable for lead free and lead containing solder alloys Effective and reliable soldering flux broushers attached as document GENERAL SPECIFICATION - Multi-purpose paste flux Well established product Quick and clean to use WRAS Approved Product Suitable for lead free and lead containing solder alloys Effective and reliable soldering flux broushers attached as document	
27	SGB51524	0283-12512	0283595711433 / ROD NAVAL BRASS HEX SIZE A/F 1.10"WT PER FT 3.910(LB)		10 / METER						TECHNICAL SPECIFICATION - COMPOSITION OF MATERIAL IS: Cu 81%min 86%max, Al 0.7%min 1.2%max, Ni 0.8%min 1.4%max, Silicon 0.8%min 1.3%max Specs: BS 2874, CZ 112M GENERAL SPECIFICATION - COMPOSITION OF MATERIAL IS: Cu 81%min 86% max, Al 0.7%min 1.2%max, Ni 0.8%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											min 1.4%max, Silicon 0.8%min 1.3% max Specs: BS 2874, CZ 112M	
28	SGB448 55		028359571145 3 / ROD NAVAL BRASS RD DIA.1.75" LENGTH: 1 MTR WEIGHT PER MTR 13.45 (KG)		3 / METER						<u>TECHNICAL SPECIFICATION -</u> BSEN-12163 OF 2011, MATERIAL GRADE CW-712R, Material Condition: M, RUNING LENGTH MAX UPTO: 1 METER <u>GENERAL</u> <u>SPECIFICATION - BSEN-12163 OF</u> 2011, MATERIAL GRADE CW-712R, Material Condition: M, RUNING LENGTH MAX UPTO: 1 METER	
29	SGB412 16		028359571145 5 / ROD NAVAL BRASS DIA 2 INCH (WT PER FT 11.72 LB)		2 / METER						<u>TECHNICAL SPECIFICATION -</u> BSEN 12163 OF 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance. <u>GENERAL</u> <u>SPECIFICATION - BSEN 12163 OF</u> 2011 MATERIAL GRADE CW 712R, Runing length: 6 to 10 FT Advance sample to be provided by the firm for testing/ acceptance.	
30	DGB540 34		027670910593 7 / SHOVEL HAND ROUND MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - a.</u> Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg. <u>GENERAL SPECIFICATION - a.</u> Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg.	
31	SGB487 39		021259571069 9 / BAR STEEL CORROSION RESISTING H/R RD 0.50		100 / METER						<u>TECHNICAL SPECIFICATION -</u> material grade: SS316L <u>GENERAL</u> <u>SPECIFICATION - material grade:</u> SS316L	
32	SGB449 45		026759923533 5 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		150 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE 1/2 INCH,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE ½ INCH,	
33	SGB449 48		021470000067 2 / BOLT ROOFING WITH NUT GALV. SZ 0.750X0.250"	PAK PATT	300 / GROSS						TECHNICAL SPECIFICATION - steel with durable layer of zinc to protect against rust and corrosion GENERAL SPECIFICATION - steel with durable layer of zinc to protect against rust and corrosion	
34	SGB314 87	BS 1769 (5306-99-941-0015)	021459941001 5 / BOLT MACHINE, THD UNC CLASS 2A. HEX HD TPI 11 SZ 0.625X2X1.5"		300 / EACH/N UMBER						TECHNICAL SPECIFICATION - METRIAL GRADE EN 4140 steell grade aisi 4140(pd 970:2005 grade 708m40/42crm40 oem coc required GENERAL SPECIFICATION - METRIAL GRADE EN 4140 steell grade aisi 4140(pd 970:2005 grade 708m40/42crm40 oem coc required	
35	SGB449 59		027378910575 9 / BLADE HAND HACKSAW FLEXIBLE PITCH FINE NOM LG 12 INches TEETH 32/ inch		15 / DOZEN						TECHNICAL SPECIFICATION - Blade length: 12 inches, Blade material: Steel, Blade width: 0.5 inches, Teeth per inch: 32, Handle material: Rubber GENERAL SPECIFICATION - Blade length: 12 inches, Blade material: Steel, Blade width: 0.5 inches, Teeth per inch: 32, Handle material: Rubber	
36	DGB540 60	0246-4028 (BRAND-NICH) / c 21-1	024679463385 4 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	2 / EACH/N UMBER	HE-50A					TECHNICAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed GENERAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed	
37	SGB48733	SKF RMS 12 (31109995 01305)	0269599501305 / BEARING BALL DEEP GROVE SKF RMS 12 SZ 1-1/2X3-3/4X15/16"		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
38	SGB44817		0262590006274 / RAT GUARD DIAMETER OF ROPE 5-6 1/2 INCH		40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
39	SGB29914		0258702581204 / COPPER WIRE RD 19SWG FOR LAGGING PURPOSE (LOCAL)		39 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - material grade of wire: 99.9% PURE COPPER.</u> <u>GENERAL SPECIFICATION - material grade of wire: 99.9% PURE COPPER.</u>	
40	SGH51415	SAFFIRE MODEL NM250, PART NO. 116324	0281502811666 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	120 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u> <u>GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.</u>	
41	SGB54862		1325723250001 / TIP DIAMOND CUTTING TOOL A25MM ATDIN4966		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - GRADES: TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI</u> <u>GENERAL SPECIFICATION - GRADES:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											TUNGSTEN CARBIDE ULTRA-MET GRADES:Z60 ISO CODE:P20/M15 GRAIN SIZE:FINE APPLICATION: GENERAL PURPOSE (MACHINING STEEL) HARDNESS (HRA):92.1 RA DENSITY:12.95 G/CC TRANSVERSE RUPTURE (TRS): 325 KSI325000 PSI	
42	SGB294 30	10N47 (WELDCR AFT (USA) or equivalent)	343970100465 4 / CERAMIC SHEILD HI- AMP CUPS SIZE-7, O/A LG 47.4 I/D 9,10 MM		400 / EACH/N UMBER					CHINSE ORIGN NOT REQUIRED	TECHNICAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.GENERAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.	
43	DNQ464 97	3IBRCR- FD4-SEW / 647000283	312072509406 6 / BEARING CARRIER	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	7 / EACH/N UMBER	ZVZ 400/300					TECHNICAL SPECIFICATION - Material = Gun Metal TECHNICAL DATA , Drawing No. D001 MARTERIAL/ GRADE, BS-1400 (LG2/LG4) PRODUCTION METHOD, DRAWN FROM CASTING GENERAL SPECIFICATION - Material = Gun Metal TECHNICAL DATA , Drawing No. D001 MARTERIAL/ GRADE, BS-1400 (LG2/LG4) PRODUCTION METHOD, DRAWN FROM CASTING	
44	SGB566 25		512070505656 8 / SCREW DRIVER PHILIPS 8" LENGTH SMALL	FOR GENERAL USE	15 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
45	SGB566 22		512070505657 3 / SCREW DRIVER FLAT BLADE 8 1/4" TIP WIDTH	FOR GENERAL USE	15 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
46	SGB546 98	BR3013- SHEET3. 1.2	473099531137 9 / FLANGE PIPE STEEL ROUND 2		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											inch (125 mm) and d. thickness: 13 mm. <u>GENERAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch. b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm.</u>	
47	DNG61102	20648	5340011673961 / ZINC ANODE	HD-1079/SLQ-32(V), HEAT EXCHANGER, LIQUID	20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
48	SGE47446		5970705049690 / MASKING TAPE SizeZ: 2INCH	FOR P.P CENTER (USA)	160 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
49	DNC56749	ELEC-2650 / IN 63047/2650	6230795110272 / SEARCH LIGHT HAND HELD (24V DC&230 WATT)	GRIFFON HOVER CRAFT LTD UK	20 / EACH/NUMBER	GEEPAS®					<u>TECHNICAL SPECIFICATION - 1. Make/ Brand: GEEPAS® 2. Model: GSL5706 - 30Watt</u> <u>GENERAL SPECIFICATION - 1. Make/ Brand: GEEPAS® 2. Model: GSL5706 - 30Watt</u>	
50	DGB61201	NO DATA AVAILAB LE	0248500000015 / SAFE-STEEL-WITH-COMBINATION -LOCK FOR CBs SZ 28X20X16 5/8		3 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</u> <u>GENERAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 02 Safe Steel with Combination lock for CBS Size 28X20X16 5/8 a. Body: 16 Gauge b. Door: Not less than 3/8" thick c. NO OF LEVERS: Minimum. 02 As per RWIMs record</u>	
51	SGE49297	NO DATA AVAILAB LE	0461500000086 / GOGGLE CHIPPING		1700 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Acceptance criteria: Physically Inspection usage: Chipping and grinding work OEM: PAKISTAN</u> <u>GENERAL SPECIFICATION - Acceptance criteria: Physically</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
52	DGE11996	3PICES FRAME WID2" IN02IN-NO-R/SP	830570505568 3 / SCREEN MOVEABLE WITH CURTAIN WOODEN HIGHT 5.-6" WD.22".	FOR PNS SHIFA	3 / EACH/NUMBER						<p>Inspection usage: Chipping and grinding work OEM: PAKISTAN</p> <p><u>TECHNICAL SPECIFICATION - a.</u> Item should be moveable and having suitable number of wheels as shown in picture. b. There should be 03 x foldable stands with curtains; stands attached to each other. c. Height and width of single stand should be 06 ft and 2.5 ft respectively. Overall width not exceeding 08 ft. d. The curtains should be Opaque (non-see through) to ensure privacy of patient. e. Curtains should be of parachute cloth and of sky blue colour. f. Curtains should be moveable within each stand. g. Stand should be of stainless steel or of suitable material / metal with white colour. H Curtains should be of parachute cloth and of sky blue colour Material of curtain: a. The curtains should be Opaque (non-see through) to ensure privacy of patient. b. Curtains should be of parachute cloth and of sky blue colour.</p> <p><u>GENERAL SPECIFICATION - a.</u> Item should be moveable and having suitable number of wheels as shown in picture. b. There should be 03 x foldable stands with curtains; stands attached to each other. c. Height and width of single stand should be 06 ft and 2.5 ft respectively. Overall width not exceeding 08 ft. d. The curtains should be Opaque (non-see through) to ensure privacy of patient. e. Curtains should be of parachute cloth and of sky blue colour. f. Curtains should be moveable within each stand. g. Stand should be of stainless steel or of suitable material / metal with white colour. H Curtains should be of parachute cloth and of sky blue colour Material of curtain: a. The curtains should be Opaque (non-see</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											through) to ensure privacy of patient. b. Curtains should be of parachute cloth and of sky blue colour.	
53	DGE59872	NO DATA AVAILAB LE	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S 3 IN NO		5 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p><u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
54	SGB455 41		724050504072 4 / BUCKET KICK WITH FOUR RUBBER WHEEL, Capacity: 14L, MODEL NO WK530, Stainless Steel		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Model No: WK S30, Metallic: Stainless Steel, Size: 33x33x42cm, Castor: Dia 50mm, Capacity: 14L <u>GENERAL SPECIFICATION -</u> Model No: WK S30, Metallic: Stainless Steel, Size: 33x33x42cm, Castor: Dia 50mm, Capacity: 14L	
55	SGB485 16	NO DATA AVAILABL E	531070512632 1 / HEX NUT STAINLESS STEEL SIZE INNER DIA 1/2 OUTER DIA 3/4 INNER THREAD 12 T. P.I BSW	FITTING OF QSB 6.9 CUMMINS ENGINE FOUNDATION PLATES WITH BOAT HULL	400 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> MATERIAL: SS 316 <u>GENERAL</u> <u>SPECIFICATION - MATERIAL: SS</u> 316	
56	DGP586 72	NO DATA AVAILABL E	005050000022 5 / ROUGH PAD (100 PAGE) SIZE A- 5 148MM 210MM PAPER GSM 50+-5%		235 / PAD	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> <u>DATA AVAILABLEGENERAL</u> <u>SPECIFICATION - NO DATA</u> <u>AVAILABLE</u>	
57	SGB494 16		534070512426 1 / CABINET LOCK	WOODEN CABINET	160 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> material specifications grade: cp (metal key) length: 22mm dia of lock: 19mm make: khas <u>GENERAL</u> <u>SPECIFICATION - material</u> specifications grade: cp (metal key) length: 22mm dia of lock: 19mm make: khas	
58	DGE206 48	611-055	402079515314 3 / ROPE NYLON 16MM WHITE MULTIPLAIT	TAL SHIP SAILING RIG	1000 / METER			BASELINE MARINE PRODUCTS LTD 10 APPLE INDUSTRIAL ESTATE, WHITTLE AVENUE FAREHAM	UK		<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(FLEXABLE AND HIGH					HAMPSHIRE UNITED KINGDOM PO15 5SX 01489 576349 01489 578835 BASELINE. MARINE@BTCONNECT.			ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG" <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 220 MTR 5. PART NO 611-055 6. TALL SHIP SAILING RIG"</u>	
59	DGP62709	MODEL NO. LA40A550 P1	773070513330 1 / TV SAMSUNG LCD 40" INCH	SAMSUNG	1 / EACH/NUMBER	NO DATA AVAILAB LE		PK	PAKISTA N		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
60	DNF62283	NCB-FS09D-LCSC-5	599570524635 5 / D-LINK SC-LC SINGLEMODE Os2 DUPLEX PATCH CORD 5M		5 / EACH/NUMBER	NCB-FS09D-LCSC-5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
61	DGP63020	16919193710 (EXPRESS SERVICE CODE)	743578520521 9 / SVAS WEB TERMINAL (LAPTOP DELL/HP CI3)	SVAS SYSTEM NY-SVAS-08 CHINA	1 / SET	NY-SVAS-08	NA	DELL INC 1 DELL WAY. ROUND ROCK, TEXAS CHINA 78682. TEL 1-866-931-3355	CHINA		<u>TECHNICAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15</u> <u>GENERAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15</u>	
62	DNM62736	3588745	342617122729 7 / ANODE KIT ZINC ANODE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887</u> <u>GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6887</u>	
63	DGP63115	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET	COMPUTER	3 / EACH/NUMBER	NO DATA AVAILAB LE		PK	PAKISTA N		<u>TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN								A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
64	DGP631 11	50AU7000/ 46EH5000	773070517439 1 / SAMSUNG LED TV 46/49 INCH	LED TV	3 / EACH/N UMBER	46EH500 0		SAMSUNG	SAMSUN G		<u>TECHNICAL SPECIFICATION -</u> SAMSUNG LED TV 46/49 INCH <u>GENERAL SPECIFICATION -</u> SAMSUNG LED TV 46/49 INCH	
65	DGP631 14	KLV32R30 2E/ P- 0114000	773078516676 7 / LED TV SONY 32 INCH	PSS VIGIL SYSYTEM	3 / EACH/N UMBER	SONY KLV32R3 02E		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		<u>TECHNICAL SPECIFICATION -</u> BRAVIA SONY 32BX350 or Equivelent <u>GENERAL</u> <u>SPECIFICATION - BRAVIA SONY</u> 32BX350 or Equivelent	
66	DGE310 84	G3000	8415TY520256 3 / 3M SAFETY HELMET G3000 SERIES	BV	239 / EACH/N UMBER	NA		VHKMHMN	-	.	<u>TECHNICAL SPECIFICATION -</u> NIL <u>GENERAL SPECIFICATION -</u> NIL	
67	DNF6219 8	140000004 6	613078520917 7 / QUINT POWER SUPPLY, 24VDC (PRIMARY: 500VAC INPUT, POWER SUPPLY MODULE OUT. CURRENT 40A)	GS PS Control System for BA 700 Excavator Netherlands	1 / EACH/N UMBER	BACKAC TER 700	5082	Zudiwal 107, 4931DC Geertruidenburg, Netherlands, Tele: (+31) 653 984760, Email: omfp@gspartsandservices. nl	M/S GS Parts & Services		<u>TECHNICAL SPECIFICATION - AS</u> PER CATALOGUE <u>GENERAL</u> <u>SPECIFICATION - AS PER</u> CATALOGUE	
68	DNF6275 7	15 opzv 1500 (GFMJ. 1500 AH)	611750514525 5 / 2V 1500AH gfmj BATTERIES	SOLAR PANEL SYSTEM 10KVA	5 / EACH/N UMBER	15 opzv 1500 gfmj		GR	M/S CHENGY ANG ROAD QUFU 273100 PR CHINA TEL:+86		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILTY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858 <u>GENERAL</u> <u>SPECIFICATION - SOURCE OF</u> AVAILABILTY : M/S AKHTAR COMPUTERS PAKISTAN BULAND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									537-4438666 , 4411936 FAX: +86 537 4411936		MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858	
69	SGB412 23		026759923509 2 / ELBOW ROUND BLACK 0.50IN		30 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n.a <u>GENERAL SPECIFICATION</u> - material: black steel grade: bs1740 nominal dia: 1/2 inch treads: bsp pressure: 150 psi degree: 90 requirement of galvanization or heat treatment: n.a	
70	SGB448 52		021459033101 0 / Stud Plain (Ends threaded unequal LENGTH), THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END 1 1/4"		600 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - DGS.8060 A CLASS-1, EN 4140 DGS 8060 Class 1(B), BS 970, Material Grade EN16 (605 M36) or EN 100 (945 M38), Condition: R LENGTH), THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END 1 1/4" <u>GENERAL SPECIFICATION</u> - DGS.8060 A CLASS-1, EN 4140 DGS 8060 Class 1(B), BS 970, Material Grade EN16 (605 M36) or EN 100 (945 M38), Condition: R LENGTH), THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END 1 1/4"	
71	SGB316 64		021470053083 8 / NUT PLAIN HEX BSF SIZE 3/4"X1.20"X0.687 INCH		700 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - SPECS PD 970:2005, GRADE 708M40/42CRM04, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75 INCHES, 12 TPI), NOMINAL LENGTH: 5/8 (0.625 INCHES), THICKNESS: (1 1/8" (1.125 INCHES)) <u>GENERAL SPECIFICATION</u> - SPECS PD 970:2005, GRADE 708M40/42CRM04, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES, 12 TPI), NOMINAL LENGTH: 5/8 (0.625 INCHES), THICKNESS: (1 1/8" (1.125 INCHES)	
72	DGB63233		0283705711634 / BRAZING ALLOY, SILVER, STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1		4965 / GRAM						<u>TECHNICAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2% <u>GENERAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%	
73	SGB49060	0265-111	0265594233195 / NAIL STEEL WIRE ROUND, CHEQUERED HD, SWG 9 LG 3.0 IN (LOCAL)		300 / KILOGRAMME	local					<u>TECHNICAL SPECIFICATION</u> - nail steel wire round 3 inch <u>GENERAL SPECIFICATION</u> - nail steel wire round 3 inch	
74	DGD57790	S NO 32 MODEL 2018	0035500000386 / MINCING MACHINE MEDIUM		2 / EACH/NUMBER	2018					<u>TECHNICAL SPECIFICATION</u> - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450 <u>GENERAL SPECIFICATION</u> - MAX POWER ELECTRIC MOTOR, HP=01, AMP=04, PHASE=01, V=220 & RPM=1450	
75	DNH62758	NO DATA AVAILABLE	1308500530116 / AIR CONDITIONER 1.5 TON WINDOW TYPE		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
76	DGP59271	NO DATA AVAILABLE	0575590024923 / TP ROLL 3PLY WHITE P-P 60GSM5% +-W 8.25	TELEPRINTER	1394 / ROLL						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
77	DGE60455	2507000	4720US5071638 / HOSE RUBBER INTERNAL	ABRASIVE BLAST CLEANING MACHINE	15 / SET						<u>TECHNICAL SPECIFICATION</u> - Blast Hose with coupled nylon flange make/brand/ model: AIR BLAST B.V Specification: Reinforcement: High	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DIA: 1-INCH, EXT DIA: 1.57-INCH, LG-20 METER WITH COUPLED WITH Nylon flange								Strength Polyester/ Rayan Cord/ Textile Wrapped Cover: Antistatic NR/SBR Rubber, Black, Abrasion and weather resistant, Internal Diameter: 01-Inch (25MM), External Diameter: 1.57-INCH (39-mm), Weight: 0.75 KG/M, Standard Length: 20 Meter Working Pressure: 12 Bar & 175 PSI, Working Temperature: -350°C to + 700°C Testing: Abrasion resistance of tube 50 + 5mm according to DNI ISO 4649: 2006 <u>GENERAL SPECIFICATION - Blast Hose with coupled nylon flange make/brand/ model: AIR BLAST B.V</u> Specification: Reinforcement: High Strength Polyester/ Rayan Cord/ Textile Wrapped Cover: Antistatic NR/SBR Rubber, Black, Abrasion and weather resistant, Internal Diameter: 01-Inch (25MM), External Diameter: 1.57-INCH (39-mm), Weight: 0.75 KG/M, Standard Length: 20 Meter Working Pressure: 12 Bar & 175 PSI, Working Temperature: -350°C to + 700°C Testing: Abrasion resistance of tube 50 + 5mm according to DNI ISO 4649: 2006	
78	DGP63101		3610705117912 / SHREDDING MACHINE (HEAVY DUTY)	SHREDDER MACHINE	2 / EACH/NUMBER	ST-12C/ST-12CD					<u>TECHNICAL SPECIFICATION - ST-12C/ST-12CD</u> <u>GENERAL SPECIFICATION - ST-12C/ST-12CD</u>	
79	DNH62873	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		2 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
80	SNM63012	8N 8221	3110011848029 / BEARING CONNECTING ROD O.25	CATER PILLER (USA)	8 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
81	DNM62762	32GB500182EE	5999745118298 / PRODIALOG 4 BASIC BOARD	80 TON CARRIER A/C PLANT OFFICERS WARD (FRANCE)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
82	DGP62614		7530705054601 / FORM F (CP)-37 ATTENDANCE CARD (NEW)	STATIONARY	36900 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: LENGTH: 8.5 INCH WIDTH: 3.5 INCH WEIGHT: 240 GSM ± 5% CARD COLOUR: WHITE PRINTING INK: BLUE INK ON FRONT SIDE AND RED INK ON BACK SIDE PACKING: 1000 CARD IN EACH BOX GENERAL SPECIFICATION - SIZE: LENGTH: 8.5 INCH WIDTH: 3.5 INCH WEIGHT: 240 GSM ± 5% CARD COLOUR: WHITE PRINTING INK: BLUE INK ON FRONT SIDE AND RED INK ON BACK SIDE PACKING: 1000 CARD IN EACH BOX	
83	DGE61551	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	442 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
84	DGE12235	NO DATA AVAILAB LE	0421500000008 / PERSONAL LOCKER CUM STEEL ALMIRAH		14 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACEGENERAL SPECIFICATION - SIZES: hieght: 6 FEET, 2 INCH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACE	
85	SGE56506	NO DATA AVAILAB LE	03105000000 6 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		600 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: WATER PROOF AND ROT PROOF WIDTH: 36 INCH WEIGHT: 12 OZ PER SQ YARD COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY. <u>GENERAL</u> <u>SPECIFICATION -</u> SPECIFICATION: WATER PROOF AND ROT PROOF WIDTH: 36 INCH WEIGHT: 12 OZ PER SQ YARD COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
86	DGE3869	O/FLY 23X19FT, I/FLY 20X19FT	8340PK509764 1 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIE S	MANZOOR SONS KARACHI PAKISTAN	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD &	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>LINE MADE OF COTTON FOR TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p> <p>GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p>	
87	DGP63107		7490705041308 / PLAIN PAPER	OFFICE MACHINE	1 / EACH/NUMBER	CPM 25					TECHNICAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COPIER STANDARIZED MEDIUM DUTY								Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sor ng, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Mul ple Copying 1-999 & Zoom 25%-400%). cOMPANY nAME: tOSHIBA e sTUDIO GENERAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sor ng, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Mul ple Copying 1-999 & Zoom 25%-400%). cOMPANY nAME: tOSHIBA e sTUDIO	
88	DGP63106		702570505746 1 / TONNER FOR LASER JET III		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. HP 147A Black Original Laser Jet Toner Cartridge (P/N W1470A) for HP Laser Jet Enterprise M611 Printer 2. Average cartridge yield 10,500 pages 3. Dimensions (l x w x d) 380 x 180 x 270 mm 4. Weight 2.1 KG 5. UPC Code 194441304671GENERAL SPECIFICATION - 1. HP 147A Black Original Laser Jet Toner Cartridge (P/N W1470A) for HP Laser Jet Enterprise M611 Printer 2. Average cartridge yield 10,500 pages 3. Dimensions (l x w x d) 380 x 180 x 270 mm 4. Weight 2.1 KG 5. UPC Code 194441304671	
89	DGE13797	GGGH142	841500935313 7 / HELMET SAFTY		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as documentGENERAL SPECIFICATION - Certification No PP071002 SIRIM Certified to MS 183:2001 broucher attached as document	
90	DGD23851		733070502570 1 / PRESSURE COOKER		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			25LTR MAJECTIC BRAND								AVAILABLE	
91	DGD26118	NO DATA AVAILAB LE	003250000013 3 / Fork Table Medium Common S/Steel		150 / EACH/N UMBER	NO DATA AVILAB LE					<u>TECHNICAL SPECIFICATION - PN</u> Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest . <u>GENERAL SPECIFICATION - PN</u> Crest engraved on spoon Stainless Steel M/Grade SS 316 (Food Grade) Stainless Steel M/Grade SS-316 (Food Grade) & PN Crest .	
92	DGD55629	B-650	733070526967 5 / VEGETABLE CUTTER		2 / EACH/N UMBER	b-650					<u>TECHNICAL SPECIFICATION -</u> stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade <u>GENERAL SPECIFICATION -</u> stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade	
93	DNF61823	d701-537	613573527071 2 / LUMINAL CELL (PACK OF 6 CELLS)		2 / EACH/N UMBER	NA					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
94	DSM61369	UPAC- 832738	5999TY671972 8 / UP AC WEID MULLER		1 / EACH/N UMBER	NO DATA AVILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILAB <u>LE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
95	DGP63113	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required <u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
96	DNF53391	2810019	6160735244928 / battery 12v 170 ah		2 / EACH/NUMBER	CLASSIC V					<p><u>TECHNICAL SPECIFICATION - DRY BATTERY</u> Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KGGENERAL SPECIFICATION - DRY BATTERY Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KG</p>	
97	DSM61413		4810997231524 / VALVE, THERMOSTATIC, 4B0BB1803		1 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
98	DSM61394	C965CS	4320131122224 / C965CS ELECTRO PUMP		2 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - Pump nature : centrifugal pump tyPe: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange : 80 mm (gun metal) <u>GENERAL SPECIFICATION - Pump</u> nature : centrifugal pump tyPe: horizontal (single stage) intake head: 5 to 7 meters motor brand: siemens flow rate: 60 cubic meter per hour pressure: 4.5 to 7 bar max total pump head: 15 meter coupling: both ends gun metal pump material: tin bronze & stainless steel (304) usage: sea & fresh water suction and discharge flange : 80 mm (gun metal)</p>	
99	DSM599 86	3121- 0011WN14 310/fmp- ms-048	301013112427 3 / DIAPHRAGM 12EE000R1554 6 18M/H (FIRE PUMP)		183 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
100	DSM600 72	3121- 0011WN14 310/fmp- ms-048	301013112427 3 / DIAPHRAGM 12EE000R1554 6 18M/H (FIRE PUMP)		96 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
101	DSM601 36	0030D025 W	433012301249 8 / FILTERING ELEMENT		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
102	DNF6071 9	d1000-585	635073527106 6 / particulate swabs (pack of 250 swabs)		1 / EACH/N UMBER	na					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
103	DNM623 19	0402- 0968-04	289571526752 2 / ISOLATOR, VIBRATION		4 / EACH/N UMBER	C22 D5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
104	DSM613 96	27-37-AO	584574522500 7 / ACOUSTIC PINGER		2 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
105	DGD55616	MJ-DJ31	7330705270665 / PANASONIC JUICER BLENDER 3 IN 1		4 / EACH/NUMBER	MJ-DJ31					TECHNICAL SPECIFICATION - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY GENERAL SPECIFICATION - BRAND PANASONIC, CAPACITY: 1LTR, VOLTAGE: 800W, JAR MATERIAL TYPE GLASS, OPERAING MODE MANUAL, SKLI 227669609, PK-1447852121, 2 LTR CAPACITY	
106	DNF60720	d701-592	6350CA5271064 / vapor swabs (pack of 12 swabs)		1 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
107	DGP63116	H42D6FG	7730705292968 / HAIER LED 42 Inches		1 / EACH/NUMBER	H42D6FG					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
108	DSM60137	f600detecteur complet	6350143577346 / IONIC DETECTOR.		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Make/Model/ Brands/Equivalent be Endorsed/ OEM: OP-110 (Siemens, Switzerland) GENERAL SPECIFICATION - Make/Model/ Brands/Equivalent be Endorsed/ OEM: OP-110 (Siemens, Switzerland)	
109	DRG47266	BARREL JP	4320ZO6531217 / BARREL EMPTY FUEL JP1/JP4 EPOXY COATED REUSABLE		14 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - CAPICITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXIY COATED, TO BE USED FOR AVN FUEL GENERAL SPECIFICATION - CAPICITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXIY COATED, TO BE USED FOR AVN FUEL	
110	DNF62754	J9776A/r8n88a	7035715248832 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH	
111	DNF62732	WP1236W/ WP7-	6140795140462 / 12V7AH	FIRE ALARM / UPS 6KVA	6 / EACH/NUMBER	CP1270		UK	STABIMATIC CO		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		12/CP1270	LEAD ACID MAINTENANCE FREE BATTERY	STABMATIC	UMBER				LTD UK			
112	DNF62352	ABX-104 / P-0186000	6350785167632 / ALARM SYSTEM/INFRARED INTRUSION DETECTORS	PSS	27 / EACH/NUMBER	ZUDSEC -ABX SERIESE / BOSCH 4281		CETC mansion no 5 Wulutong North Street Xicheng District Beijing China 100120	M/s CETC INTERNATIONAL Co, LTD		<u>TECHNICAL SPECIFICATION - OEM M/S ZUDEN SECURITY TECH LTD SHENZHEN CHINA. LOCAL, ELECTROMECH Engineering Pakistan C/5, 201,10th Street, Khayabane-e- Shamsheer, Phase-V, DHA, Karachi MOBILE:0333-3887803. SPECS: VOLTAGE DC 10-18v Reaction Time: > 0.1 sec Temp: -30° C – +50° C No. of Beams: 04 Barrier Length: 70.8 cm Response Time: 10 ~ 500 ms</u> <u>GENERAL SPECIFICATION - OEM M/S ZUDEN SECURITY TECH LTD SHENZHEN CHINA. LOCAL, ELECTROMECH Engineering Pakistan C/5, 201,10th Street, Khayabane-e- Shamsheer, Phase-V, DHA, Karachi MOBILE: 0333-3887803. SPECS: VOLTAGE DC 10-18v Reaction Time: > 0.1 sec Temp: -30° C – +50° C No. of Beams: 04 Barrier Length: 70.8 cm Response Time: 10 ~ 500 ms</u>	
113	DNO62334	5226130/R 5226130	2910011956720 / INJECTOR ASSEMBLY FUEL	DETROIT SSDD MODEL: 16V149TI, 1000KW, 1605AMPS, 3PHASE	16 / ASSEMBLY			OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM	SUPERIOR DIESEL INC		<u>TECHNICAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM</u> <u>GENERAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
114	DNM63002	4893693	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/N UMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.COMDMARINE. COM)	CUMMIN S		<u>TECHNICAL SPECIFICATION -</u> BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTR Y: UK MANUFACTURE: CUMMINS MODEL: QSB6.7 <u>GENERAL</u> <u>SPECIFICATION - BEARING,</u> CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTR Y: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
115	DNM63132	4893693	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/N UMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.COMDMARINE. COM)	CUMMIN S		<u>TECHNICAL SPECIFICATION -</u> BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTR Y: UK MANUFACTURE: CUMMINS MODEL: QSB6.7 <u>GENERAL</u> <u>SPECIFICATION - BEARING,</u> CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTR Y: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
116	DGD61884	T52254 / E-6228	732099759431 1 / VEGETABLE PEELING MACHINE, ELECTRIC	GALLEY	1 / EACH/N UMBER	NO DATA AVAILAB LE		UK	HOBART MANUFA CTURING UK, STREET BRAUNT ON ROAD CITY BARNST APLE, STATE OR PROVINC E, DEVON, COUNTR Y UK POST-ZIP CODE. EX31 1GD,		<u>TECHNICAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT. 440V <u>GENERAL SPECIFICATION -</u> Motor Spec: 2HP Motor Capacity 150-300 kg weight 40 kg. Machine frame/ blade: L x B x H Body Stainless Steel 6x3' inch INPUT.440V	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									TELEPHONE, 01271347500, TELEFAX . 01271347502			
117	DNC63096	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	230 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK GENERAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK	
118	DNO62171	GREEN TRIDENT	6230015637756 / LIGHT, HEAD, GENERAL PURPOSE	DC & FF	6 / EACH/NUMBER			STREAMLIGHT INC 30 EAGLEVILLE UNITED STATES CAGE CODE 56654	STREAM LIGHT INC 30		TECHNICAL SPECIFICATION - DEPTH 2.53 IN; OVERALL 2.55 IN; POWERED BY 3 AAA BATTERIES GENERAL SPECIFICATION - DEPTH 2.53 IN; OVERALL 2.55 IN; POWERED BY 3 AAA BATTERIES	
119	DPK61855	ISO VG 80	4320735157688 / SYNTHETIC COMPRESSOR OIL (Brand = VOLVO) ISO VG 80 (250 ML = Packing)	MAIN ENGINE VOLVO PENTA	20 / EACH/NUMBER		2006032390	AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	VOLVO PANTA SWEDEN		TECHNICAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY: AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG GENERAL SPECIFICATION - OEM & SOURCE OF AVAILABILITY: AB VOLVO PENTA GROPEGARDSGATAN GOTEBOG SWEDEN SE-405 08 GOTEBOG	
120	DNF62504	71-S8-UQ	6060785232536 / FC-SC NICKEL PLATED BRASS CONNECTOR FOR OFC	PSS VIGIL	50 / EACH/NUMBER	AMPHENOL FIBER OPTIC PRODUCTS		AMPHENOL SOUTH CHINA BAO AN, SHENZHEN, CHINA PHONE: +86-755-719-9622 E-MAIL: +INFO@AMPHENOL	AMPHENOL CHINA		TECHNICAL SPECIFICATION - A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB) bRAND: AMPHENOL Fiber Optic Products GENERAL SPECIFICATION - A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB) bRAND: AMPHENOL Fiber Optic Products	
121	DNF63094	P-0155000	6130785166754 / UPS 10KVA 2H O/P 220 V 10000VA with batteries for back up.	PSS (CCTV SYS)	1 / EACH/NUMBER	ONL-10000/ST ABIMATIC		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		TECHNICAL SPECIFICATION - back up time: 45 Min with full load GENERAL SPECIFICATION - back up time: 45 Min with full load	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
122	DNS62511	20730038	299073518818 8 / CONNECTION G ROD	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	8 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u> <u>GENERAL SPECIFICATION -_MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	
123	DNZ48525	LC1D65AM7C	5935CH0011279 / CONTACTOR	SWITCHBOARD NO. 1	1 / EACH/NUMBER	JZB-600+400/12	218140-1; 218140-2	DINGMAO ECONOMIC DEVELOPMENT ZONE, ZHENJIANG CITY JIANGSU PROVINCE, CHINA	SAIERNICO		<u>TECHNICAL SPECIFICATION - OEM: SAIERNICODINGMAO LOCAL:NEW GLOBAL ELECTRIC CO JAMA MASJID ARAM BAGH SHAHRAH E LIAQUAT KARACHI. CONTACT 021-32627324</u> <u>GENERAL SPECIFICATION - OEM: SAIERNICODINGMAO LOCAL:NEW GLOBAL ELECTRIC CO JAMA MASJID ARAM BAGH SHAHRAH E LIAQUAT KARACHI. CONTACT 021-32627324</u>	
124	DNM44713	1000152	3439715231696 / SIPHONE PLUG AND NOZZLE RESEAL KIT	16E SPRAY GUN	5 / EACH/NUMBER	16E-H SPRAY GUN	NA	SULZER METCO (US)INC. 1101 PROSPECT AVENUE WESTBURY, NY 11590 USA TEL:+15163341300 FAX:+15163382414	SULZER METCO USA		<u>TECHNICAL SPECIFICATION - OEM: SULZER METCO US INC 1101 PROSPECT AVENUE WESTBURY NY 11590 USA MANUFACTURE SULZER METCO</u> <u>GENERAL SPECIFICATION -_OEM: SULZER METCO US INC 1101 PROSPECT AVENUE WESTBURY NY 11590 USA MANUFACTURE SULZER METCO</u>	
125	DNS62403	156 148	5330735185385 / O-RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	8 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
126	DNS62513	3161258	3020270357794 / GEAR	VOLVO PENTA SSDG D9A2A MG HE	1 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				SWEDEN				Tel: +46 31 23 54 60			1009161287(STBD) 1009161290 (PORT) <u>GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	
127	DNS62514	8131386	3020270357805 / GEAR	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u> <u>GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	
128	DNS62478	3837393-2	4270735159555 / HAND PUMP	FUEL CLEANER/WATER SEPARATOR, TWIN.	1 / EACH/NUMBER	D5-D16		WARTSIL FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 FINLAND	WARSILA FINLAND		<u>TECHNICAL SPECIFICATION -WARTSIL FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 FINLAND</u> <u>GENERAL SPECIFICATION - WARTSIL FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 FINLAND</u>	
129	DNS62512	8148111	3020270354450 / GEAR	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u> <u>GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	
130	DNM62471	5317052	2930715194444 / KIT, RAW WATER PUMP-MINO	CUMMINS MAIN ENGINE QSB7DM UK	1 / EACH/NUMBER	QSB7DM	22068610	NEWAGE ENG GMB.H ROTENBROCKENWEG 14-D-22113 HAMBURG U. K	CUMMINS		<u>TECHNICAL SPECIFICATION -SPARE FOR S/W PP OEM: USA Model: QAB7DM</u> <u>GENERAL SPECIFICATION - SPARE FOR S/W PP OEM: USA Model: QAB7DM</u>	
131	DNS62477	8148038	3120270354470 / BEARING SHELL	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	12 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		<u>TECHNICAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u> <u>GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
132	DNF63099	3BA00751AA	5998735182749 / IP MEDIA GATEWAYS WITH ACCESSORIES	ACTIVE	1 / EACH/NUMBER			M/s AL FUTTAIM TECHNOLOGIES LLC P.O. BOX UAE TEL+97147063111, 800238324 E MAIL aftech@alfuttaim.ae	ALCATEL LUCENT		<u>TECHNICAL SPECIFICATION</u> - The vendor must ensure 100% admin, operational and technical integration with existing Network comprising of Alcatel 4400 release 9.x.x. The proposed system must integrate with existing switches and transmission. The Gateways installed should be of hybrid type. <u>GENERAL SPECIFICATION</u> - The vendor must ensure 100% admin, operational and technical integration with existing Network comprising of Alcatel 4400 release 9.x.x. The proposed system must integrate with existing switches and transmission. The Gateways installed should be of hybrid type.	
133	DNQ62168	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	10 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND		<u>TECHNICAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
134	DNQ61992	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	4 / ROLL	NO DATA AVAILABLE		UK	UK ENGLAND		<u>TECHNICAL SPECIFICATION</u> - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION - NIMAGE:K4723</u> M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
135	SNJ3900 4	12892- 93J10- 235/12892- 93J00-235	536576522236 8 / SHIM, TAPPET (T: 2350)	SUZUKI DF300AP 300 HP OBM	12 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION -</u> MAKE: PAK SUZUKI CO LTD <u>GENERAL SPECIFICATION -</u> MAKE: PAK SUZUKI CO LTD	
136	DNH631 37	N/A	541070523258 3 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/N UMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABL E TOILET		<u>TECHNICAL SPECIFICATION -</u> Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension	
											Resistant Accessories for Iron Structure <u>GENERAL SPECIFICATION</u> - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsai or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure		
137	DNH63112	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122			ASKARI FIBER GLASS PORTABLE TOILET	TECHNICAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsai or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL SPECIFICATION - Item Specification</u></p> <p>:a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FALSAL or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure</p>	
138	DNZ56364	1205250013	4810785208925 / SPEED REGULATION VALVE	Synergy Propulsion Azimuth Thruster MRP60-FP China	1 / EACH/NUMBER	MRP90-FP / 2FRM6B36-L3X/16QM	HR-13001	Synergy propulsion Huanglong Industry Zone Wuyi Zhejiang China Tel: 86-579-8798 8916 Fax: 86-5798768 6777	Synergy propulsion Huanglong Industry Zone Wuyi Zhejiang China		<p><u>TECHNICAL SPECIFICATION - OEM/Make SHILIXIN/SYNERGY PROPULSION Shanghai Lixin Hydraulic Co Ltd Model 2FRM6B36-L3X/16QM AS PER CATALOGUE</u></p> <p><u>GENERAL SPECIFICATION - OEM/Make SHILIXIN/SYNERGY PROPULSION Shanghai Lixin Hydraulic Co Ltd Model 2FRM6B36-L3X/16QM AS PER CATALOGUE</u></p>	
139	DNJ62996	09482-00427	2920765222410 / SPARK	SUZUKI DF300AP 300	12 / EACH/N	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<p><u>TECHNICAL SPECIFICATION -</u></p> <p><u>NILGENERAL SPECIFICATION -</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PLUG (BKR6E)	HP OBM	UMBER						NIL	
140	DNJ52406	09202-06031	5315765222116 / PIN (6X12)	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
141	SNJ52847	55321-87J00	5340765221435 / ANODE, PROTECTION	SUZUKI DF300AP 300 HP OBM	114 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD	
142	DNM63002	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7 GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
143	DNM63132	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7 GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
144	DGE39893		0413599238762 / HOSE RUBBER WITH EXT ARMOURING OF STEEL STRIP		100 / METER						TECHNICAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750 INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES NOMINAL PROPRIETARY CHARACTERISTICS: GENERAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES NOMINAL PROPRIETARY CHARACTERISTICS: NPAC	
145	DGE34810	NO DATA AVAILABLE	055979001524 1 / TAPE-VARNISHED-WOVENGLASS S0.500IN THICKNESS 0.003 INCH		40 / ROLL						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
146	DGE44278	nil	035059571312 1 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM		520 / FATHOM						<u>TECHNICAL SPECIFICATION - 1. MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1. MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.</u></u>	
147	SGH48747	SPECS: DNC / S-29	021159923016 6 / SHEET STEEL CARBON COLD ROLLED (SIZE: L 2500 x 1250 x 02) MM		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
148	SGH487	SPEC:BS	021259571091		50 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	46	1449/3A/H S22/C	7 / CHANNEL STEEL CARBON 2-1/2X1-1/4 IN W/FT 2.95 LB		METER						BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED <u>GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED</u>	
149	DGB62851		028370571163 4 / BRAZING ALLOY, SILVER, STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1		5000 / GRAM						<u>TECHNICAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u> <u>GENERAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u>	
150	DGB48557	0246-4028 (BRAND-NICH) / c 21-1	024679463385 4 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	3 / EACH/NUMBER	HE-50A					<u>TECHNICAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed</u> <u>GENERAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed</u>	
151	DGH54064	0246-99-463-3880	0246UK511797 5 / BLOCK TRAVELER		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
152	DGB484	SKF RMS	026959950130		2 /						<u>TECHNICAL SPECIFICATION - NO</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	54	12 (31109995 01305)	5 / BEARING BALL DEEP GROVE SKF RMS 12 SZ 1-1/2X3-3/4X15/16"		EACH/N UMBER						DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
153	SGH487 45		056159521837 4 / Multicore (Dual) Core Limited Fire Hazard (LFH) Elastomeric insulated and Elastomeric Sheathed Cable /CABLE ELECT ELASTOMERIC,LFH,2CORE COND30/.250 440V 23AMP	DEFSTAN 02-526(NES 526) ISSUE 1 OF 2000	50 / METER						<u>TECHNICAL SPECIFICATION - DEFSTAN 02-526(NES 526) ISSUE 1 OF 2000 a. APPLICATION: GENERAL SERVICE CABLE FOR POWER AND LIGHTING CIRCUIT b. Voltage rating 440V c. Temperature ranges -30 to 105 °C</u> <u>GENERAL SPECIFICATION - DEFSTAN 02-526 (NES 526) ISSUE 1 OF 2000 a. APPLICATION: GENERAL SERVICE CABLE FOR POWER AND LIGHTING CIRCUIT b. Voltage rating 440V c. Temperature ranges -30 to 105 °C</u>	
154	DNF6299 7	N150/ N140,125, EXIDE	056279900465 3 / BATTERY 12V 115-125 AH SEC ACID TYPE	GENERAL USE	4 / EACH/N UMBER	N140, N125 EXIDE					<u>TECHNICAL SPECIFICATION - oem exide karachi pakistan</u> <u>GENERAL SPECIFICATION - oem exide karachi pakistan</u>	
155	SNM537 67	2645021	281579509073 4 / CAMRING	PERKINS D/G U-K	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
156	SNM515 95	3025451/3 090450	281571505403 0 / RING OIL PISTON		20 / EACH/N UMBER	K19-DM					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
157	DNQ610 16	SPECE: MIL-F- 24385F TYPE 6	421099224836 9 / FOAM COMPOUND FOR FIRE EXTINGUISHER (6%AFFF)IN 15-25 LTR CAN.(QPL PRODUCT ACCEPTABLE)	FOR FIRE FIGHTING EQUIPMENT	100 / CAN						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
158	DNM623 22	EBOH 48	414071509240 9 / COOLING UNIT (ATU)	A/C48000BTU OEM:M/S TAYLOR MADE USA	1 / EACH/N UMBER	EBDE48V / BM- EUBT-48					<u>TECHNICAL SPECIFICATION -</u> CRUISE AIR USA LOCAL ADDRESS MACHINERY CORP PKB PH 35678252 FAX 35683283 IMPORTED Make: USA (CRUISAIR)/ Local(BREEZETEC) Brand: DOMETIC/ BREEZETEC Capacity: 48,000 BTU Refrigerant: R-22 Parent equipment Condensing Unit 05 Tons (NSN 4120PK5073944) <u>GENERAL</u> <u>SPECIFICATION - CRUISE AIR USA</u> LOCAL ADDRESS MACHINERY CORP PKB PH 35678252 FAX 35683283 IMPORTED Make: USA (CRUISAIR)/ Local(BREEZETEC) Brand: DOMETIC/ BREEZETEC Capacity: 48,000 BTU Refrigerant: R- 22 Parent equipment Condensing Unit 05 Tons (NSN 4120PK5073944)	
159	DNQ581 40	54.107.00	421099541355 0 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7- 8 <u>GENERAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
160	DNH631 34		4110PK506114 1 / REFRIGERAT OR SINGLE DOOR NET CAPACITY 4.4 CU.FT 124 LTR	USER SIM DIVISION DOCKYARD	7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
161	DNH629	NO DATA	413070504652	SELF	2 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	95	AVAILABLE	9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY		EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					nullGENERAL SPECIFICATION - null	
162	SNF53943	ART, 170080 / 6025-0014-P1	3439013982750 / SOLDERING IRON ELECTRICAL 220VAC 60W 50HZ PS-90 KIT WITH TIP&TOOL STAND	SP-1/SP-2, SOLDERING IRON HANDPIECE	4 / EACH/NUMBER	KEMPER (GROUP)					TECHNICAL SPECIFICATION - TECH-SPECSS, IRON ELECTRICAL 220VAC 60W 50HZ oem , KEMPER EN VAN TWIST DIESEL B.V. netherlandGENERAL SPECIFICATION - TECH-SPECSS, IRON ELECTRICAL 220VAC 60W 50HZ oem , KEMPER EN VAN TWIST DIESEL B.V. netherland	
163	DNH61991	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		3 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DGP63246		3610705091304 / SHREDDING MACHINE COMET MODEL C-220 D/S-800/GBC DUO		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NEW SPECS UPDATED GENERAL SPECIFICATION - NEW SPECS UPDATED	
165	DNF62196	158-51010	5961995580307 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
166	DNF62197	158-51020	5961995580314 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAHI)	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
167	DNF61502	158-51020	5961995580314 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAHI)	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
168	DNF63097	NO.E91 IEC LR6	6135795058492 / BATTERY ALKALINE (ENERGIZER) (Non Rechargeable) 1.5V AA SIZE NO.E91 IEC LR6	GENERAL USE	78 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
169	DNM62238	CPMU-10	4130705126490 / CONDENSER COIL	MOBILE A/C PLANT	2 / EACH/NUMBER	CWM-2C70-PN					TECHNICAL SPECIFICATION - LENGTH: 65", HEIGHT: 76", WIDTH: 6", TUBE SIZE: 3/8", NO OF TUBES PER ROW: 65 IN NO, NO OF ROWS: 5 IN NO, FINS PER INCH: 12 IN NO, HEADER DIA: 1 3/4", INLET DISCHARGE CONNECTION: 7/8 GENERAL SPECIFICATION - LENGTH: 65", HEIGHT: 76", WIDTH: 6", TUBE SIZE: 3/8", NO OF TUBES PER ROW: 65 IN NO, NO OF ROWS: 5 IN NO, FINS PER INCH: 12 IN NO, HEADER DIA: 1 3/4", INLET DISCHARGE CONNECTION: 7/8	
170	DNM62286	CPMU-10	4130705126490 / CONDENSER COIL	MOBILE A/C PLANT	4 / EACH/NUMBER	CWM-2C70-PN					TECHNICAL SPECIFICATION - LENGTH: 65", HEIGHT: 76", WIDTH: 6", TUBE SIZE: 3/8", NO OF TUBES PER ROW: 65 IN NO, NO OF ROWS: 5 IN NO, FINS PER INCH: 12 IN NO, HEADER DIA: 1 3/4", INLET DISCHARGE CONNECTION: 7/8 GENERAL SPECIFICATION - LENGTH: 65", HEIGHT: 76", WIDTH: 6", TUBE SIZE: 3/8", NO OF TUBES PER ROW: 65 IN NO, NO OF ROWS: 5 IN NO, FINS PER INCH: 12 IN NO, HEADER DIA: 1 3/4", INLET DISCHARGE CONNECTION: 7/8	
171	DNG63003	8030-00-181-8372	8010010374771 / PRIMER,	C I W S	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SEALING COMPOUND		UMBER						SPECIFICATION - NO DATA AVAILABLE	
172	DNQ62658	005101010	8415991304874 / HOOD, ANTIFLASH..	DC LOCKER	150 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
173	DNF62170	913671EQ	6145795023724 / CABLE TIE P/N 913671EQ FOR TX/RX VRM	TX/RX VRM	200 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
174	DPC61971	CAT ELC TM (2056612 or 2056611)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	300 / LITER						TECHNICAL SPECIFICATION - TDS & IPC EnclosedGENERAL SPECIFICATION - TDS & IPC Enclosed	
175	DNH62999	NO DATA AVAILAB LE	1308500530126 / DEEP FREEZER 12 CUFT 220 V AC WAVES		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
176	DGP62713	NO DATA AVAILAB LE	005050000009 7 / PAPER DUPLICATING		380 / REAM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL</u> SPECIFICATION - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
177	DNF62282	TXFR-221	595070512426 5 / STEP DOWN TRANSFORME R 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH	MARINE VERSION SPLIT A/C	1 / EACH/N UMBER	DELTA TRFOR 400V/440 HZ 3P 5KVA 220V 50/60					TECHNICAL SPECIFICATION - 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI. <u>GENERAL</u> SPECIFICATION - 05 KVA I/P 440V, 60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI.	
178	DGE48654	2822-025- 00051	802017101264 4 / SOFT BRUSH		30 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB <u>LE</u> <u>GENERAL</u> SPECIFICATION - NO DATA AVAILABLE	
179	DNJ50294	814-2- 1014-001- 00	533076512445 0 / DIAPHRAGM (NDV .25MM- 8G)	DC CHILLER DIAPHRAGM VALVE	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILAB <u>LE</u> <u>GENERAL</u> SPECIFICATION - NO DATA AVAILABLE	
180	DNM62287	CMPU-09	442070512649 1 / EVAPORATOR COIL	COOLPOINT MOBILE A/C PLANT CWM- 2C70-PN PAKISTAN	1 / EACH/N UMBER	CWM- 2C70-PN					TECHNICAL SPECIFICATION - NO DATA AVAILAB <u>LE</u> <u>GENERAL</u> SPECIFICATION - NO DATA AVAILABLE	
181	SGB60215	NO DATA AVAILAB LE	028359579115 0 / ALUMINIUM PLATE (7ft 6inch X 3ft 9inch X 6mm)		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Item Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FIRM.GENERAL SPECIFICATION - Item Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING FIRM.	
182	DCC63016		840550010016 7 / Trouser Dress NO 8 Size 36"		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Trouser Dress NO 8 Size 36" GENERAL SPECIFICATION - Trouser Dress NO 8 Size 36"	
183	DCC63015		840550010009 3 / Trouser Dress NO 8 Size 34"		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Trouser Dress NO 8 Size 34" GENERAL SPECIFICATION - Trouser Dress NO 8 Size 34"	
184	DNO54194	415-2434	662077524993 7 / SENSOR GP-EXHAUST TEMPERATURE		1 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - SENSOR GP-EXHAUST TEMPERATURE GENERAL SPECIFICATION - SENSOR GP-EXHAUST TEMPERATURE	
185	DGP62749	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required GENERAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
186	DN063071	CLD-8-0107	4120FP106017 2 / ANTI CORROSION ZINC ROD		22 / EACH/NUMBER	Type CLD-4SCU Type CLD-6SCU Type CLD-8SCU Type CLD-12SCU Type CLD-17PSCU Type CLD-17PSCU Type CLD-22P					<u>TECHNICAL SPECIFICATION - ANTI CORROSION ZINC ROD</u> <u>GENERAL SPECIFICATION - ANTI CORROSION ZINC ROD</u>	
187	DCC63018		840550010016 9 / Trouser Dress NO 8 Size 40"		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Trouser Dress NO 8 Size 40"</u> <u>GENERAL SPECIFICATION - Trouser Dress NO 8 Size 40"</u>	
188	DCC63017		840550010016 8 / Trouser		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Trouser Dress NO 8 Size 38"</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Dress NO 8 Size 38"		UMBER						GENERAL SPECIFICATION - Trouser Dress NO 8 Size 38"	
189	DNO51681	511-7975	4310715701972 / PUMP GP-FUEL INJECTION		1 / EACH/NUMBER	C9.3					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
190	DN063092	01.14.21.105 / ACB-007-SEW	4420FP2050007 / ANTICORROSION BLOCK		4 / EACH/NUMBER	CLZM-5.5					TECHNICAL SPECIFICATION - ANTICORROSION BLOCK GENERAL SPECIFICATION - ANTICORROSION BLOCK	
191	DN063091	QB/CJ-013A-2-2002 / ZRFWC-SEW	2930FP1080023 / ZINC ANODE FW COOLER		64 / EACH/NUMBER	16PA6V-280STC					TECHNICAL SPECIFICATION - ZINC ANODE FW COOLER GENERAL SPECIFICATION - ZINC ANODE FW COOLER	
192	DN063072	G860022-02 / ZRACR-065-SEW	6115FP1050065 / ANTI-CORROSIVE ZINC ROD		2 / EACH/NUMBER	1FR6506-4SA42-2					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
193	DNO51883	398-5399	6685715248826 / SENSOR GP-PRESSURE		2 / EACH/NUMBER	398-5399					TECHNICAL SPECIFICATION - SENSOR GIVE ALArM AT MINIMUM 40 KPA AND MAXIMUM at 175 KP GENERAL SPECIFICATION - SENSOR GIVE ALArM AT MINIMUM 40 KPA AND MAXIMUM at 175 KPA	
194	DNF62321	aol pll-01	5850705293063 / led aviation mast light 110-240V AC 4WATT (RED COLOR)		30 / EACH/NUMBER	PLL-01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
195	DCC63014		8405500100092 / Trouser Dress NO 8 Size 32"		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - KNIFE CLASPS SEAMAN GENERAL SPECIFICATION - KNIFE CLASPS SEAMAN	
196	DN063051	01.14.21.104 / ACB-006-SEW	4420FP2050006 / ANTICORROSION BLOCK		9 / EACH/NUMBER	CLZM-5.5					TECHNICAL SPECIFICATION - ANTICORROSION BLOCK GENERAL SPECIFICATION - ANTICORROSION BLOCK	
197	DNF62911	NI 2020	6140705246001 / Lithium Lon Battery 10.8V OF 3D X-RAY SCANNER		5 / EACH/NUMBER	NI 2020					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
198	DCC63019		8405500100170 / Trouser Dress NO 8 Size 42"		100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Trouser Dress NO 8 Size 42"</u> <u>GENERAL SPECIFICATION - Trouser Dress NO 8 Size 42"</u>	
199	DNF63095	J9776A/r8n88a	7035715248832 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
200	DN063093	01.14.21.1.11 / ZACWP-014-SEW	4420FP2100014 / Zinc anode for condenser MODEL NO. 75*35*30		24 / EACH/NUMBER	75*55*30					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
201	DGD63212	B-505	4430705269616 / MOBILE TANDOOR (ROUND)		1 / EACH/NUMBER	B-505					<u>TECHNICAL SPECIFICATION - M/S INNER DRUM: 3M, S/S OUTER BODY: 1.2MM, 32 NOZZLE BURNER, HEAVY DUTY CASTER WHEEL, ITALIAN VALVE ASSY, M/S BURNER PLATE-4MM, GLASSWOOL INSULATION, 30INCH DIA</u> <u>GENERAL SPECIFICATION - M/S INNER DRUM: 3M, S/S OUTER BODY: 1.2 MM, 32 NOZZLE BURNER, HEAVY DUTY CASTER WHEEL, ITALIAN VALVE ASSY, M/S BURNER PLATE-4MM, GLASSWOOL INSULATION, 30INCH DIA</u>	