

TENDER BULLETIN

DATE & TIME 6/11/24 11:23 AM INVITATION TO TENDER TO BE OPENED ON 7/1/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGP60674	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
2	SNM62500	100-3880	2815015067155 / PUSHROD-VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	16 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
3	DNS56588	21707132/477556-5	4330331080376 / OIL FILTER	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	1 / EACH/NUMBER	NO DATA AVAILAB LE		FR	SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&LARGE B-72ESTATE AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
4	SNM56792	0103-100002	6685725156864 / PRESSURE GAUGE STAGE 2 (0-25 BAR)	ALPINE HP COMPRESSOR	1 / EACH/NUMBER	0103-100002		GERMANY ALPINE INDUSTRIAICON (PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN	GERMANY		<u>TECHNICAL SPECIFICATION - OEM / BRAND : MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								TEL:042-6852313,6862490 FAX:+92-42-6553674			PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674 <u>GENERAL SPECIFICATION - OEM / BRAND :</u> MS ALPPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAICON(PRIVATE) LIMITED 305/2 G. T ROAD BAGHBANPURA LAHORE PAKISTAN TEL:042-6852313,6862490 FAX:+92-42-6553674	
5	SNM57038	2495541	299071516842 1 / REGULATOR	D/G	2 / EACH/NUMBER	C 2.2	JAW00492	3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	USA		<u>TECHNICAL SPECIFICATION - REGULATOR CATTERPILLAR C2.2 DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905</u> <u>GENERAL SPECIFICATION - REGULATOR CATTERPILLAR C2.2 DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905</u>	
6	DNM59587	233-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
7	DNH64226	OWR-528 / NWD200/icon-2 (ORIENT)	731070517713 1 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENCER	2 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN	ORIENT		<u>TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER</u> <u>GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER</u>	
8	DPK56026	HA5430H	915073516428 4 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		<u>TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858</u> <u>GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
9	SNC52751	7009115	783070518104 1 / LIFTING BELT SLINGS	LIFTING BELT	7 / EACH/NUMBER			HEADOFFICE:VTTAG HARDSTRASSE CH-4132 MUTTENZ TEL +41(0) 617179898 FAX +41(0)617179890 info@vtt-group.com	VTT LTD SWISS COMPAN Y		<u>TECHNICAL SPECIFICATION</u> - colour yellow capacity(wll) 3 width 140 weigh per m 0.85 <u>GENERAL SPECIFICATION</u> - colour yellow capacity(wll) 3 width 140 weigh per m 0.85	
10	SNM57033	256-7704	533071521950 3 / SEAL- VALVE COVER	DG CAT 7.1 USA	4 / EACH/NUMBER	CAT7.1	Cat00C71 KGTY006 76	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR		<u>TECHNICAL SPECIFICATION</u> - ITEM IS USED IN CAT DG AIR SYSTEM <u>GENERAL SPECIFICATION</u> - ITEM IS USED IN CAT DG AIR SYSTEM	
11	DGP49001	60 NX 720/X9500 H 65	773070516072 2 / LED TV 60 /65 INCHES	TV 60"	1 / EACH/NUMBER	60 NX 720/ X9500H 65		M/S AB ELECTRONICS- SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI.	M/S AB ELECTR ONICS/S AMSUNG		<u>TECHNICAL SPECIFICATION</u> - M/S AB ELECTRONICS-SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI. <u>GENERAL SPECIFICATION</u> - M/S AB ELECTRONICS-SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI.	
12	SNM45562	1S6595	533000931804 8 / GASKET	3304PC CATTERPILLE R	15 / EACH/NUMBER		3512TA CATTERP ILLER	3512TA CATTERPILLER	USA		<u>TECHNICAL SPECIFICATION</u> - OEM: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM: CATERPILLAR	
13	DNM62711	3803851	431073517926 3 / COMPRESSO R, EXCH (COMPRESSO R)	VOLVO PENTA	1 / EACH/NUMBER	D6-370D-E		AB VOLVO PENTA SE405 08 GOTHENBURG SWEDEN	VOLVO PENTA		<u>TECHNICAL SPECIFICATION</u> - COMPRESSOR, EXCH (COMPRESSOR) <u>GENERAL SPECIFICATION</u> - COMPRESSOR, EXCH (COMPRESSOR)	
14	DNZ54615	D100573.10	293079513882 8 / DIAPHRAGM DRAIN VALVE FEED PIPE	MAIN AIR COMPRESSO R	1 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD ENGLAN D		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
15	DNZ56363	D100573.10	293079513882 8 / DIAPHRAGM DRAIN VALVE FEED PIPE	MAIN AIR COMPRESSO R	2 / EACH/NUMBER	NO DATA AVAILAB LE		UK	COMPAIR UK LTD ENGLAN D		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	
16	DNZ55897	95602.140	533101415911 8 / O RING	MAIN AIR COMPRESSO R	6 / EACH/NUMBER	NO DATA AVAILAB		UK	COMPAIR UK LTD		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				R	UMBER	LE						
17	SNM56735	214-7568	5331015135210 / SEAL O RING	MAIN ENGINE	64 / EACH/NUMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPILLAR		<u>TECHNICAL SPECIFICATION - MAKE:</u> CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189 <u>GENERAL SPECIFICATION - MAKE:</u> CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
18	SNM53856	7W-6249	2920013918347 / RELAY-SOLENOID, ENGINE STARTER, ELECTRICAL	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u> <u>GENERAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u>	
19	SNM53855	6V-9189	5310010536999 / LOCKNUT (M8X1.25-THD)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - THICKNESS (IN): 0.28 NUT TYPE: HEX NUT MATERIAL: STEEL MATERIAL DESCRIPTION: ISO 898-2 CLASS 10 COATING: ZINC PLATED HARDENED: YES THREAD: COARSE THREAD UNC HOLE THREAD PITCH: 1.25</u> <u>GENERAL SPECIFICATION - THICKNESS (IN): 0.28 NUT TYPE: HEX NUT MATERIAL: STEEL MATERIAL DESCRIPTION: ISO 898-2 CLASS 10 COATING: ZINC PLATED HARDENED: YES THREAD: COARSE THREAD UNC HOLE THREAD PITCH: 1.25</u>	
20	SNM53793	451-0548	5306715228521 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS	ALLIED CAT		<u>TECHNICAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
								61552-0610 COUNTRY USA			steelGENERAL SPECIFICATION - thread size: m14 material: steel zinc plated inner diameter: 9 mm (0.35 in) cross hole diameter: 5.5mm (0.21 in) screw type: banjo screw hex size (in): 0.75 material; description: steel	
21	SNM59318	6I-0593	5306715228548 / BOLT (M10X1.5X30-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.15 Thread: Coarse Thread Size (in - TPI) (in): M10-1.5 Hex Size (in): 0.51 Material Description: SteelGENERAL SPECIFICATION - Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.15 Thread: Coarse Thread Size (in - TPI) (in): M10-1.5 Hex Size (in): 0.51 Material Description: Steel	
22	DGE62503		0422705158411 / PVC MAT (SHEET LENGTH 18.5 M, WIDTH 1.5 M, THICKNESS 0.15 M.)	SELF	950 / SQ FEET			M/S ANWAR PLASTICS, SADDAR KARACHI &M/S BUKHARI PLASTICS MA JINNAH ROAD KARACHI, MOBILENO:021-2764323,0300-2456426.	M/S ANWAR PLASTICS, SADDAR KARACHI		TECHNICAL SPECIFICATION - SHEET LENGTH 18.5 M WIDTH 1.5 m THICKNESS 1.5 M GENERAL SPECIFICATION - SHEET LENGTH 18.5 M WIDTH 1.5 m THICKNESS 1.5 M	
23	SNM59313	7K-1181	2815010534712 / STRAP-CABLE	CATTER PILLER GENSET 3512B USA	1 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		TECHNICAL SPECIFICATION - STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): .19 - 4.00 GENERAL SPECIFICATION - STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): .19 - 4.00	
24	DGH41794	GDHBMK4092040	4010FT1007918 / STEEL WIRE ROPE (20MM/40M/NON-ROTATING/GA	9M COMBINED BOAT CRANE	2 / EACH/NUMBER	GD.HBM. K.S-40/6-PG&40/9	N/A	GURDESAN GEMI MAK. SAN.TIC.A.S, DILOVASI ORGANIZE SAN.BOL.4 NCU KISIM, KOCAELI, TURKEY TEL # 9.02627E+11	GURDESAN GEMI MAK. SAN.TIC. A.S		TECHNICAL SPECIFICATION - a. Length : 50 meter b. Dia : 20 mm c. brand/model/type: 20 mm, mbl>220 kn d. Ø20MM/40M/NON-ROTATING/GALVANIZED) GENERAL SPECIFICATION - a.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LVANIZED)					FAX # 9.02627E+11 INFO@GURDESAN.COM. TR			Length : 50 meter b. Dia : 20 mm c. brand/model/type: 20 mm, mbl>220 kn d. Ø20MM/40M/NON-ROTATING/GALVANIZED)	
25	DNF57848	CAT-6A U-FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE- 0.36MM 4/U- FTP PVC/LSZH-0.5 MM AQUA/BLEU/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	700 / FOOT	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-87688883	CHINA		<u>TECHNICAL SPECIFICATION</u> - oem, contech solution USA. www. CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U- FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION</u> - oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
26	SNM56548	067-6095	281579522955 6 / ROD	33KVA CATER PILLER DG DEO33EO UK	12 / EACH/N UMBER	DEO33E O	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millenuim Springvale Business Park Belfast BT	CATTERP ILLER U. K		<u>TECHNICAL SPECIFICATION</u> - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel <u>GENERAL SPECIFICATION</u> - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel	
27	DGP55855	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN	COMPUTER	5 / EACH/N UMBER	NO DATA AVAILAB LE		PK	PAKISTA N		<u>TECHNICAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION</u> - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
28	SNM57044	2451364	5330995516412 / SEAL	MAIN ENGINE CATTER PILLAR C-18	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM IS REQUIRED FOR TOH / MOH OF DGsGENERAL SPECIFICATION - ITEM IS REQUIRED FOR TOH / MOH OF DGs	
29	DNQ63339	SOLO A10-001	1290735226270 / SOLO A10 150ML (SMOKE DETECTOR TESTER)	SMOKE DETECTOR	2 / EACH/NUMBER	SOLO A10	NIL	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.		NO CLIMB PRODUCTS LTD	TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION GENERAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION	
30	SNM58658	3227488	4820715186720 / GASKET (1.1 MM THK)	DG CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH(IN): 10 OVERALL LENGTH(IN): 24GENERAL SPECIFICATION - OVERALL HEIGHT(IN): 0.1 OVERALL WIDTH (IN): 10 OVERALL LENGTH(IN): 24	
31	SNM57039	3227487	4820010141893 / GASKET (1.2 MM THK)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGsGENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
32	SNM52378	1004830/100-4830	5306014715165 / BOLT(M 10X1.5X2.0MM)	CATTER PILLAR DG C2.2 USA	10 / EACH/NUMBER	C2.2	JAW00493	LATIN AMERICA,MEXICO, CARRIBEAN CATERPILLAR AMERICAS CO.701 WATERFORD WAY,SUITE 200 MIAMI,FL 33126-4670 USA		CATTERPILLER (USA)	TECHNICAL SPECIFICATION - notes: thraed length (mm) 3.75 screw length (in): 0.79 screw type: hex flange head coating: zinc plated cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5 GENERAL SPECIFICATION - notes: thraed length (mm) 3.75 screw length (in): 0.79 screw type: hex flange head coating: zinc plated cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5	
33	SNM61058	2521466	2910015392763 / INJECTOR AS FUEL	D/G CATTER PILLAR C2.2	3 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGsGENERAL SPECIFICATION - ITEM REQUIRED FOR TOH / MOH OF DGs	
34	SNM59312	1540869	3120715186736 / BUSHING	DG CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATER PILLAR	TECHNICAL SPECIFICATION - Weight: 0.01 lbs (0.01 kg) Length: 4	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
					UMBER						in (10.16 cm) Height: 4 in (10.16 cm) Width: 1 in (2.54 cm) <u>GENERAL SPECIFICATION -</u> Weight: 0.01 lbs (0.01 kg) Length: 4 in (10.16 cm) Height: 4 in (10.16 cm) Width: 1 in (2.54 cm)	
35	SNM57046	2172752	5330015390573 / GASKET (VALVE BRACKET)	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW 00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs <u>GENERAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs	
36	SNM57284	1542427	5330998450295 / GASKET EXHAUST	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER		JAW 00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs <u>GENERAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs	
37	SNM57040	2305118	5330715186536 / GASKET	D/G CATTER PILLAR C2.2	1 / EACH/NUMBER	C2.2	JAW 00494	USA		CATER PILLAR	<u>TECHNICAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs <u>GENERAL SPECIFICATION -</u> ITEM REQUIRED FOR TOH / MOH OF DGs	
38	DNF58245		6070705229821 / 24 JOINT BOX	PSS SYSTEM	4 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN		LTE	<u>TECHNICAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type	
39	DNF57365		6070705229821 / 24 JOINT BOX	PSS SYSTEM	5 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN		LTE	<u>TECHNICAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type	
40	DNF58531		6070705229821 / 24 JOINT BOX	PSS SYSTEM	2 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN		LTE	<u>TECHNICAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION -</u> 1. Water proof 2. 24 core optical fiber splice box horizontal type	
41	SNF34362		6070705229831 / JOINT BOX 48 FIBER	PSS SYSTEM	8 / EACH/NUMBER	JOINT BOX 48 FIBER	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN		LTE	<u>TECHNICAL SPECIFICATION -</u> JOINT BOX 48 FIBER <u>GENERAL SPECIFICATION -</u> JOINT BOX 48 FIBER	
42	DNF63094	P-0155000	6130785166754 / UPS 10KVA	PSS (CCTV SYS)	1 / EACH/NUMBER	ONL-10000/ST		M/s CETC Mansion, No. 5 Wulutong North Street.		M/s CETC Internatio	<u>TECHNICAL SPECIFICATION -</u> back up time: 45 Min with full load	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			2H O/P 220 V 10000VA with batteries for back up.		UMBER	ABIMATIC		Xicheng Districe, Beijing, China	nal CO., LTD		<u>GENERAL SPECIFICATION</u> - back up time: 45 Min with full load	
43	DNF50804	SWTG DS-6.3	6350705220323 / SMART WALK THROUGH GATE	SWTG	2 / EACH/NUMBER	DS-6.3		DEFENCE SCIENCE AND TECHNOLOGY ORGANIZATION CHAKLALA CANTT RAWALPINDI	DESTO		<u>TECHNICAL SPECIFICATION - DIMENSIONS</u> HEIGHT 2210MM WIDTH 810MM DEPTH 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD RECHARGEABLE BATTERY 12 MONTHS LIFE <u>GENERAL SPECIFICATION - DIMENSIONS</u> HEIGHT 2210MM WIDTH 810MM DEPTH 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD RECHARGEABLE BATTERY 12 MONTHS LIFE	
44	DNS57959	200 011	5310735185436 / NUT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	221 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
45	DNS48161	131 019	5330735185407 / BEARING BUSH	WARTSILA MAIN ENGINE 9L20C3 FINLAND	4 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
46	DNF64225	EoD 5D/69141	676076518078 7 / CANON EOS 5D MARK III / iv FULL FRAM DSLR	It Self	1 / EACH/NUMBER	5d Mark III/iv		Canon Inc 30-2 Shimomaruko3- Chome, Ohla-Ku-Tokyo 146 - 8501 , Japan	Japan		<u>TECHNICAL SPECIFICATION -</u> Canon EOS PRO DSLR 5D Mark III/iv HD Full Frame -) Power Requiement Battery LP EF-E6 RECHARGEABALE 7.2 25600- Shutter Speed Mini 30 Sec Max 1/8000 - Video Resolution 1920 x 1080 Movie File format Mov (MPEG-4 AVC/H.264) All -1 IBP Modes - Image sensor CMOS - Image Resolution 22.3MP (5760X3840) <u>GENERAL SPECIFICATION -</u> Canon EOS PRO DSLR 5D Mark III/iv HD Full Frame -) Power Requiement Battery LP EF-E6 RECHARGEABALE 7.2 25600- Shutter Speed Mini 30 Sec Max 1/8000 - Video Resolution 1920 x 1080 Movie File format Mov (MPEG-4 AVC/H.264) All -1 IBP Modes - Image sensor CMOS - Image Resolution 22.3MP (5760X3840)	
47	SNM57036	7F7590	5330015954369 / GASKET	SSDG	4 / EACH/NUMBER	3304-B	2P6512	CATERPILLER INC.100 N. E ADAMS PEORIA, LLLINOIS 61629,USA	CATERPILLER		<u>TECHNICAL SPECIFICATION -</u> MAKE: CATERPILLAR <u>GENERAL SPECIFICATION -</u> MAKE: CATERPILLAR	
48	DNF64179	AT-FS980M/9 PS-30 + AT-FS980M/9 PS-NCA1	705073522686 4 / 8 PORT 10/100TX POE + SWITCH WITH 2 GIGABIT SFO MO	UFFAQ	6 / EACH/NUMBER	FS980M		Office No. 120 Building No. 12, First Floor Dubai Internet City United Arab Emirates Ph: +971 4 454 8740	Allied Telesis		<u>TECHNICAL SPECIFICATION -</u> 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks and one filxed AC power supply <u>GENERAL SPECIFICATION -</u> 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											and one fixed AC power supply	
49	SNM52356	N27838	433070521479 2 / FILTER ELEMENT	HPAC	2 / EACH/NUMBER	K28.0	0103-2016-02	BAUER COMPRESSORI SRL UNIPERSONALE VIA GALILEO GALILEI 9 ARCUGNANO (VI), ITALY PH: 00390444653653 FAX: 00390444653600	BAUER ITALY		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
50	DNS57956	201018	4310FT100714 1 / Air Filter Element	J.P Sauer & Sohn LPAC SC22-8-MA60 Germany	1 / EACH/NUMBER	SC22-8-MA60	N/A	BRAUNER BERG 15, KIEL, 24159, ALMANYA, TEL: +49 (0) 7562 975 540	SAUER, J.P. & SOHN MASCHINENBAU GMBH		<u>TECHNICAL SPECIFICATION - AS PER TPI</u> <u>GENERAL SPECIFICATION - AS PER TPI</u>	
51	DNJ62759	6Y2-24360-60	471076518966 0 / PRIMER PUMP ASSY	YAMAHA SMALL BOAT ENGINE F100B JAPAN	3 / EACH/NUMBER	F100B	60CL100410G	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@sea-quest.biz	YAMAHA LTD. 2500 SHINGAI WATA, SHIZUOK A, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@sea-quest.biz		<u>TECHNICAL SPECIFICATION - IPC</u> <u>GENERAL SPECIFICATION - IPC</u>	
52	DNQ63454	NITECH 800H/ NITECH 550/bmen-3-006	623099179696 7 / HAND LAMP PLASTIC RECHARGABLE NITECH 800/550H	FLOOD LIGHT LANTERNS	2 / EACH/NUMBER	NO DATA AVAILAB LE		UK	UK ENGLAN D		<u>TECHNICAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C.</u> <u>GENERAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C.	
53	DNQ62406	NITECH 800H/ NITECH 550/bmen-3-006	623099179696 7 / HAND LAMP PLASTIC RECHARGABLE NITECH 800/550H	FLOOD LIGHT LANTERNS	4 / EACH/NUMBER	NO DATA AVAILAB LE		UK		UK ENGLAN D	<p><u>TECHNICAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C.</u></p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:(A)part no:nitech 800h or equipment PRODUCT WITH LIGHT BULB: LED LIGHT CANDLE POWER: 50,000 CANDLE POWER ,MAX RE-CHARGE TIME: 14 HORS,CHARGING OPTION:DIRECT FROM MAINS 110V/220V., RECHARGEABLE BATTERY: 3000CYCLES;OPEARTING TEMPRATURE:-10°C TO +60°C.</u></p>	
54	DGE58504	096-0240-004C	402079515298 7 / ROPE NAVY FLEX 24 MM BROWN 3 STRAND POLYPROPYLENE (HAWSERLAID)	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS-ROPE@RANDERS-REB.DK.		UK	<p><u>TECHNICAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS;/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.</u></p> <p><u>GENERAL SPECIFICATION - ISO</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.	
55	DGE58503	096-0320-004C	4020795152989 / ROPE NAVY FLEX 32 MM BROWN 3 STRAND POLYPROPYLENE	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS-ROPE@RANDERS-REB.DK.	UK		<p><u>TECHNICAL SPECIFICATION - 1.</u> MANUFACTURED TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307:2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR</p> <p><u>GENERAL SPECIFICATION - 1.</u> MANUFACTURED TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307:2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR</p>	
56	DNF56424	84873025 / MWUA	4920785208811 / POWER PROTECTOR	Jiangsu Josun Main AC System China	1 / EACH/NUMBER	CJK-58, 31KW	JKY-50600	Jiangsu Josun Air Conditioner Co., Ltd 18-28, Tongjiang Rd, Taixing City, Jiangsu Tel:0523-7598753 Fax:0523-7599928 http: www.zhaoshenggroup.com Email: Josun@zhaoshenggroup.com	Jiangsu Josun Air Conditioner Co., Ltd, China		<p><u>TECHNICAL SPECIFICATION - AS PER CATALOGUE</u></p> <p><u>GENERAL SPECIFICATION - AS PER CATALOGUE</u></p>	
57	DNQ63353	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILABLE			UK	UK ENGLAND	<p><u>TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL</u> <u>SPECIFICATION - NIMAGE:K4723</u> M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
58	DNQ531 17	FP-30-008	492070516160 5 / CAST IRON BACK COVER	FF TRG PUMP	1 / EACH/N UMBER		006	MERAJ LIMITED HEAD OFFICE: PLOT NO 11 SECTOR 15 KORANGI INDUSTRIAL AREA KARACHI 74900 PAKISTAN TEL: 5050145-6 FAX: 92-21-5060663 E-MAIL:meraj@cyber.net. pk UAN: 111163725 URL: www.meraj.net.pk	MERAJ LIMITED		<u>TECHNICAL SPECIFICATION -</u> <u>CAST IRON BACK</u> <u>COVERGENERAL SPECIFICATION</u> <u>-CAST IRON BACK COVER</u>	
59	DNJ6239 9	17400- 98J01	518076522254 8 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION -</u> <u>NILGENERAL SPECIFICATION -</u> <u>NIL</u>	
60	DNQ626 29	08279009	621079517576 2 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	6 / EACH/N UMBER	UK (RFD BEAUFO RT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFO RT LTD (UK)		<u>TECHNICAL SPECIFICATION -</u> <u>LIFE RAFT INTERNAL LIGHT &</u> <u>BATTERY, RFD BEAUFORT LTD</u> <u>(UK)GENERAL SPECIFICATION -</u> <u>LIFE RAFT INTERNAL LIGHT &</u> <u>BATTERY, RFD BEAUFORT LTD</u> <u>(UK)</u>	
61	DNM605 91	435-6493	433071522467 7 / FUEL FILTER	Caterpillar DG DE200E0usa	12 / EACH/N UMBER	CAT C 7.1	CAT00C7 1LECW03 124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	Caterpillar USA		<u>TECHNICAL SPECIFICATION -</u> <u>OEM: CATERPILLAR DG GENERAL</u> <u>SPECIFICATION - OEM:</u> <u>CATERPILLAR DG</u>	
62	SNM516	FF9011	294001523005	CUMMINS 200	6 /	6CTA8.3	78515443	Cummins Americas Inc,	USA		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	77		0 / Fuel Filter	KVA DG	EACH/N UMBER			3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433- 5797			MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE: CUMMINS USA	
63	DPC579 29	TUFF- BOND HANGER ADHESIVE	804001009800 1 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	6 / GALLO N			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLO E E INC		TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPSGENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS	
64	SNS5506 2	288-0422	533001565461 2 / Seal-Oil (Front)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/N UMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. DBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUC TS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
65	SNM567 34	3J-1907	533101333644 4 / SEAL-O- RING	CATERPILLAR GENSET D3512B (YBB1) USA	2 / EACH/N UMBER	NA	CAT3512 BEYBB00 583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPI LLAR USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION - 0	
66	DNF6425 3	WKH-22G	731073522956 3 / HEATER (KERONA PORTABLE KEROSENE)	HEATER	8 / EACH/N UMBER	WKG-22G		PASECO CO LTD 724-1 WONSI DONG ANSAN- SI KYUNGKI-DO,KOREA 32-31-599-5650-4 82-31-495-1975	KOREA		TECHNICAL SPECIFICATION - HEATER (KERONA PORTABLE KEROSENE) make korea COUNTRY OF ORIGIN serbia brand faseco co ltdGENERAL SPECIFICATION - HEATER (KERONA PORTABLE KEROSENE) make korea COUNTRY OF ORIGIN serbia brand faseco co ltd	
67	DNM564 13	3067129	281579520786 0 / Assembly, fuel pump	320 KVA DG	1 / EACH/N UMBER	NT-855- G6	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMIN S		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
68	DNC56245	892524	2990MB0020688 / FITTING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
69	DNM59587	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
70	SNF57086	7429766	5930735218570 / PRESSURE SWITCH	Azimuth Thruster	1 / EACH/NUMBER	7429766	66925,669226	Rolls Royce OY Ab PO BOX 220, FIN-26101 Roma Finland Phone + 358283791. FAX NO + 358283794804 Azimuth Thruster/Propulsion Aftermarket Fax + 358283794804 Home Page: ww.rolls ? Royce. com	Rolls Royce OY Ab, Rauma, Finland		<u>TECHNICAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.</u> <u>GENERAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.</u>	
71	SNS55072	2257739 / 225-7739	5331015277570 / O-ring	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
72	SNS55080	232-1794	4720015239521 / Hose	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									GOVERNMENTAL AND DEFENSE PRODUCTS			
73	SNS55042	230-8998	472001523763 2 / Tube As (Cyl No.4)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
74	SNS55081	230-8997	472001523763 0 / Tube As (Cyl No.3)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
75	SNS55050	230-8995	472001523762 3 / Tube As (Cyl No.1)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
76	SNS55063	152-3968	533101505603 9 / O-ring	Caterpillar Emergency DG Marine Genset	1 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA		<u>TECHNICAL SPECIFICATION - CATERPILLAR GENERAL SPECIFICATION - CATERPILLAR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				C 4.4 USA					CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS			
77	DNM58114	imp/gp/stb/g01	2010715221031 / STUFFING BOX FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	3 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA		TECHNICAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED <u>GENERAL SPECIFICATION - LIP SEAL TYPE STUFFING BOX, TIDES MARINE SURE SEAL FOR 50MM SHAFT DIA, QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED</u>	
78	DNS64023	AGR 22BS-PR	0565765186392 / OVER CURRENT RELEASE	AIR CIRCUIT BREAKER	2 / ASSEMBLY	AGR 22B	NIL	TERASAKI JAPAN.	TERASAKI JAPAN		TECHNICAL SPECIFICATION - TERASAKI JAPAN AIR CIRCUIT BREAKER OVER CURRENT RELEASE WITH REVERSE POWER PROTECTION TRIP TYPE AGR 22BS-PR WITH 800 AMP CAPACITY <u>GENERAL SPECIFICATION - TERASAKI JAPAN AIR CIRCUIT BREAKER OVER CURRENT RELEASE WITH REVERSE POWER PROTECTION TRIP TYPE AGR 22BS-PR WITH 800 AMP CAPACITY</u>	
79	DGE64185		0461590004058 / HEAD SCREEN FOR ELECTRIC WELDING WITH GLASS BLACK.		31 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11), Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11), Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae	
80	DGE19296		0350595713130 / ROPE NYLON HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 28MM, (1-1/8"), TYPE-1,	TOWING & BERTHING ROPE	240 / METER						<p><u>TECHNICAL SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIREED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.<u>GENERAL SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIREED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
81	SPC54841		0442509434665 / PAINT FINISHING GENERAL SERVICE GLOSS HEAT RESISTANT METHOD OF APPLICATION BRUSHING FLASH POINT	HEAT RESISTANCE UPTO 204 C, PAINTING	120 / LITER						<p><u>TECHNICAL SPECIFICATION - 1.</u> DEFSTAN 80-32/2 OF 1990. 2. HEAT RESISTANCE 204 DEGREE 'C. 3. STAGE INSPECTION PRESCRIBED pACKING: 02 LTRS TIN GAUGE OF TIN 28 TO 30 SWG<u>GENERAL SPECIFICATION - 1.</u> DEFSTAN 80-32/2 OF 1990. 2. HEAT RESISTANCE 204 DEGREE 'C. 3. STAGE INSPECTION PRESCRIBED pACKING: 02 LTRS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			32 DEGREE C, (MIN) COLOUR BLACK (02 LTR TIN)								TIN GAUGE OF TIN 28 TO 30 SWG	
82	SPC54926	NO DATA AVAILABLE	0442509429125 / PAINT OIL FINISHING FOR MEASURERS (WHITE) FLASH POINT 32o C (MIN) PACKING: 04 LITER TIN GAUGE OF TIN 26 TO 28 SWG	FINISHING	140 / LITER						<u>TECHNICAL SPECIFICATION - DEFSTAN 80-54/4 OF 2005</u> <u>GENERAL SPECIFICATION - DEFSTAN 80-54/4 OF 2005</u>	
83	SGB56145		0267599235343 / Tee pipe equal galvanized (three sides equal) black		30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED</u> <u>GENERAL SPECIFICATION - INNER DIA: 45 MM, OUTSIDE DIA: 58 MM, THICKNESS: 6.5 MM, THREADS: 11, BS 1740/71 CORROSION RESISTING STEEL/FERROUS ALLOY, WITH LAYER OF MOLTEN ZINC MTC OF ITEM IS REQUIRED</u>	
84	DGE53679	NIL	0350599237118 / ROPE NYLON HAWSERLAID, Z-LAY, 3-STRNDS, NOM DIA: 05MM, CIRC: 5/8 INCH, TYPE:1		18590 / FATHOM						<u>TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.</u> <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
85	DGE56199	NIL	0350599237130 / ROPE NYLON, HAWSERLAID, 3-STRND, Z-LAY, NOM DIA: 28 MM, CIRC: 3.50 INCH, TYPE-1, MIN BRKG STRENGTH 15.500 TONS	MIN BRKG STRENGTH 15.500 TONS UNIT OF	920 / METER						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
86	DGB54016		0276799105870 / SCREW DRIVER RATCH, DOUBLE SPIRAL,AUTO RETURN, 250MM LG,3 BITS		57 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China <u>GENERAL SPECIFICATION -</u> Detail specification; Screw Driver Ratch, Double Spiral, Auto Return Technical data; Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China	
87	DGB50291		0272502720040 / DRILL-		30 / EACH/N						<u>TECHNICAL SPECIFICATION -</u> Material HSS, Hardness HRC65-66.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PARALELL-SHANK-3MM CARBON STEEL		UMBER						GENERAL SPECIFICATION - Material HSS, Hardness HRC65-66.	
88	SGH514 24		024679463386 0 / BLOCK-STEEL-DIA-ROPE.5"NO-OF-SHEAVES-2		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - BEARING TYPE: PLAIN. MAX LOAD RATING: 252.0 POUNDS. BLOCK TYPE: REGULAR. SHEAVE QTY: 02. TACKLE ACCOMODATED TYPE: FIBROUS ROPE. BECKET TYPE: ROUND EYE. SHELL LENGTH: 131.00 MM NOMINAL. SHEAVE OUTSIDE DIA: 76.00 MM NOMINAL. CENTER PIN DIA: 9.50 MM NOMINAL. GENERAL SPECIFICATION - BEARING TYPE: PLAIN. MAX LOAD RATING: 252.0 POUNDS. BLOCK TYPE: REGULAR. SHEAVE QTY: 02. TACKLE ACCOMODATED TYPE: FIBROUS ROPE. BECKET TYPE: ROUND EYE. SHELL LENGTH: 131.00 MM NOMINAL. SHEAVE OUTSIDE DIA: 76.00 MM NOMINAL. CENTER PIN DIA: 9.50 MM NOMINAL.	
89	SGH529 51		021259571079 6 / ANGLE STEEL CARBON BLACK SIZE 05" X 03" X 7/16"		57 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIREDGENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED	
90	SGH108 01	BS EN 10025-2/2004, MATERIAL GRADE S 275 JR	021259571071 8 / ANGLE STEEL CARBON E/S BLACK 1.25 X 1.25 X 0.25 INCH		125 / METER						TECHNICAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jrGENERAL SPECIFICATION - RUNNING LENGTH: 6.5 METER BS EN 10025-2/2004, mAterial grade s 275 jr	
91	SGH529 52		021259571079 8 / ANGLE STEEL		103 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CARBON BLACK SIZE 05" X 3-1/2" X 1/2"								MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR, Running Length: 6 METER MATERIAL TEST CERTIFICATE REQUIRED	
92	SGB449 21	NO DATA AVAILABL E	021459013040 8 / BOLT MACHINE STEEL BSF HEX HD SZ 2.0 X0.2500 INCH TPI 26		100 / TEN						TECHNICAL SPECIFICATION - MS AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) MATERIAL SPECIFICATIONS BS970 EN-4140 oem coc required GENERAL SPECIFICATION - MS AISI 4140 (PD 970: 2005 METRIAL GRADE 708M40 OR 42CRMO4) MATERIAL SPECIFICATIONS BS970 EN-4140 oem coc required	
93	DGB554 48		026759521327 8 / PIPING STEEL GALVANIZED (SEAMLESS), L :6 M, E/DIA 26.9MM, TH 2.6 MM, N/BORE:19.1 MM	UTS LENGTH. BULK SUPPLY	20 / METER						TECHNICAL SPECIFICATION - BSEN 10216-2 OF 2002, GRADE P265GH, BSEN ISO 1461:2022 FOR GALVANIZING GENERAL SPECIFICATION - BSEN 10216-2 OF 2002, GRADE P265GH, BSEN ISO 1461:2022 FOR GALVANIZING	
94	SGH515 27	SPECIFIC ATION: DNC/S23	021259571075 5 / ANGLE STEEL CARBON BLACK 04X04X5/8"		60 / METER						TECHNICAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED GENERAL SPECIFICATION - BSEN 10025 OF 2004 GRADE S275JR MATERIAL TEST CERTIFICATE REQUIRED	
95	DNF5601 4	BSEN 60317-8	056179519875 6 / WIRE WINDING ELECT COPPER POLYESTER ENAMEL cOND DIA 0.850 O/DIA 0.964MM	FOR WINDING.	30 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABE GENERAL SPECIFICATION - NO DATA AVAILABE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(GRADE-3 CLASS-180)									
96	DNH64217	MODEL NO SS-30P (STEEL)	1308500530129 / COOLER W/DRINKING20-25 LTR. 1/2TON AMPS 2.5 220V SING PHASE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DPC59036		0474504740012 / DEOXIDISING TUBE		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DNF50204	BSEN60317-8	0561795253560 / WIRE WINDING copper ELECT ENAMEL cond dia0.250 O/A DIA 0.301 MM	FOR WINDING	5 / KILOGRAMME	GHAZILE X					TECHNICAL SPECIFICATION - Purity: 99.95 % Copper Class: Class-180 BSEN60317-B grade-2(class 180 degree). GENERAL SPECIFICATION - Purity: 99.95 % Copper Class: Class-180 BSEN60317-B grade-2(class 180 degree).	
99	DNF64245	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	2 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
100	SNM57289	1353020/15080260M	2940745077280 / CARTRIDGE FILTERING 210MIC57 (MADE IN FRANCE)	BAUDOIN ENGINE (FRANCE)	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
101	DNJ60353	C261200100A	2990785027168 / SET BOLT OA/LG 70.5 NOM LG 60 DIA 16X13MM SET OF 20 PIECES	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / SET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	SNM52398	4L-9852	2940000743584 / AIR FILTER ELEMENT	CATERPILLER D/G (USA)	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											AVAILABLE	
103	SNM51612	A-055	3030999234867 / BELT VEE A-055 055X053X01/02IN		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - Type: A Size/ Model: A-55 MAKE OEM: Normally local/ Chinese Make: MITSUBISHI, SWR, RED POWER, SANYO, AUTO BELT, BOSH etc 055X053X01/02INGENERAL SPECIFICATION - Type: A Size/ Model: A-55 MAKE OEM: Normally local/ Chinese Make: MITSUBISHI, SWR, RED POWER, SANYO, AUTO BELT, BOSH etc 055X053X01/02IN	
104	SNM58032	7N5910	2930711003773 / IMPELLER P/N 7N5910 D/E CATERPELLE R USA	CATTER PILLER DIESEL ENGINE 50KW	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DNM51032	0142-22-19/02165054	2940725091331 / AIR FILTER ELEMENT (02165054)	DEUTZ D/G D/ENGINE (GERMANY)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
106	SNM56815	4L8473	2815715035128 / PLATE OD-90MM-ID-45MM-THK-3MM-BRASS		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4GENERAL SPECIFICATION - Inner Diameter (in): 1.77 Outer Diameter (in): 3.56 Weight (lb): 0.28 Length (in): 4.5 Height (in): 4	
107	DNM57000	7S3161	2815004509341 / TAPPET ENGINE POPPET VALVE		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
108	DGE63100	NO DATA AVAILABLE	4240PK5078177 / GUNNY BAGS		31870 / EACH/NUMBER						TECHNICAL SPECIFICATION - GUNNY BAGS 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF). <u>GENERAL SPECIFICATION - GUNNY BAGS</u> 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF).	
109	SNM56745	7E7997	312001297750 1 / BEARING HALH SET	3512TA, CATERPILLER USA	24 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
110	SNM56736	7N5246	312001322293 3 / BEARING WASHER THRUST	3516, CATERPILLAR D/G USA (JNB)	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
111	DNM63440	qxs-h80sn345 (t1)	413076509189 6 / COMPRESSOR 380-400V, 3PHASE,50HZ ,04TONS	DAIKIN AIR CONDITION 04TONS JAPAN	1 / EACH/NUMBER	QXS-H80SN345 (T1)					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
112	DNZ60340	1121237/12017	413078502675 4 / PACKING FOR SIDE COVER THICK 0.5MM ASBESTOS SHEET AA016	AIR CONDITIONER PLANT NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material: Asbestos Sheet</u> <u>GENERAL SPECIFICATION - Material: Asbestos Sheet</u>	
113	DNZ60341	112122	413078502675 3 / PACKING FOR BLIND COVER THICKNESS 0.5MM ASBESTOS SHEET AA015	AIR CONDITIONER PLANT NASR	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
114	DGP56697		361070500962 4 / LEDGER PAPER		100 / REAM						<u>TECHNICAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE GENERAL SPECIFICATION - WEIGHT OF LADGER PAPER: 55 ± 5% GSM SIZE: 43.18 X 68 .58 CM/(17 X 27 INCHES) PAPER COLOR: LIGHT GREEN (as per sample) EACH REAM CONTAINS : 500 SHEETS AS PER SAMPLE PAPER PROVIDED BY PNCPP PAPER WILL BE ACCEPTED AFTER END USER REMARKS /ACCEPTANCE	
115	DNM56473	E24FDZ/1	413071509189 1 / EVAPORATOR 24000BTU	AIR CONDITIONIN G UNIT OF MARINE AIR SYSTEM USA	4 / EACH/N UMBER	MARINE AIR/E24F DZ/1					TECHNICAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32 GENERAL SPECIFICATION - OEM: MARINE AIR SYSTEM (WWW.MARINEAIR.COM)/ OEM: GREE (2 Tons split) Dimensions of packing: Approx (45" x 20"x15") Lx B xH inches. IOC AVAILABILTY: ELAHI ELECTRONICS, HEAD OFFICE 7 & 8 PN FLEET CLUB IQBAL SHAHEED ROAD SADDAR KARACHI PHONE 021-7781627 FAX: 0217781631-32	
116	SNM56795	4W5738	312001202589 4 / BEARING HALF SLEEVE	CATTER PILLER D/G (BASIC ENGINE)	10 / EACH/N UMBER						TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
117	SGB570	A1226-1-9	311000227327		10 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
	63		6 / BEARING BALL ANNULAR SZ 40.00X90.00MMX1.4375 IN		EACH/NUMBER						OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required <u>GENERAL SPECIFICATION - OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required</u>	
118	DGP55694	G2102560EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u> <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u>	
119	SNM56748	8S4757	5306013234140 / BOLT	3512TA, CATERPILLER USA	12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate + Oil offers corrosion protection up to the point of assembly (recommend painting for external applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in):</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50GENERAL SPECIFICATION - Bolt Length (in): 8 Bolt Type: Hex Head Head Height (in): 0.71 Coating: Zinc Phosphate + Oil offers corrosion protection up to the point of assembly (recommend painting for external applications). Salt spray resistance of 72 hours to red rust. Coating color - dark grey to black. Grip Length (in): 5.5 Drive (in): 1 1/2 Material: Steel Thread: Standard Material Description: SAE J429 Grade 8. Head Marking - 6 radial lines (150 ksi Ultimate Tensile Strength) Thread Size (in - TPI) (in): 1-14 Grip Length - 2 (in): 5.50 Head Height 4(in): 0.71 Grade: 8 Total Bolt Length - 3 (in): 8 Hole Thread Pitch: 14 Finish: Phosphate and Oil Coated Head Width - 5 (in): 1.50	
120	DNZ60363	R27237	5330RC5072952 / O RING FOR HOUSING FUEL INJECTION VALVE M/ENG 8RLB66 NASR		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
121	SNM62490	4W8087	5330012110809 / SEAL WATER OLD PART NO. 7N8025	CATERPILLER DIESEL GENERATOR	16 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
122	SNM53820	5P-8245	5310010980624 / Washer-Hard (13.5X25.	3304PC, CATERPILLER D/GEN.USA	52 / EACH/NUMBER						TECHNICAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			5X3-mm thk)								COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER (IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12 HARDENED: YES FINISH: PHOSPHATE AND OIL COATED <u>GENERAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER (IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12 HARDENED: YES FINISH: PHOSPHATE AND OIL COATED</u>	
123	DNZ60301	306	530678503913 7 / COUPL BOLT WITH NUT&S. WASHER STEELU-352 SZ 53.00 .00X14.00MM	AIR CONDITION SEA WATER PUMP PNS NASR	18 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MATERIAL: SSGENERAL SPECIFICATION - MATERIAL: SS</u>	
124	DNJ45895	67751815B	5330765022870 / OIL SEAL FOR CRANK CASE NIIGATA MAINE ENGINE	CRANK SHAFT (NIIGATA D/E ITEM NO 1300-20)	6 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
125	SNM56796	6V9769	5331013529337 / SEAL O	3512TA, CATERPILLER	80 / EACH/NUMBER	3512TA					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			RING	D/ENGINE USA	UMBER						SPECIFICATION - NO DATA AVAILABLE	
126	DNM58841	3K0360	533100948648 2 / SEAL O RING	3512 TA CATERPILLAR USA	3 / EACH/NUMBER	3512 TA					TECHNICAL SPECIFICATION - Country Of Origin: USA Manufacturer: Caterpillar GENERAL SPECIFICATION - Country Of Origin: USA Manufacturer: Caterpillar	
127	DGE57003		533070500725 2 / RUBBER BLANKET 04 PLY		4 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine) GENERAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine)	
128	SNM62499	5P-0840	533101317950 2 / SEAL O RING	3512TA, CATERPILLER USA	51 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
129	DNF47379	TOA JAPAN	583070501751 2 / SRE SYSTEM COMPLETE SET (ACCESSORY AS PER NHQ APPROVAL)	SRE SYSTEM	2 / SET						TECHNICAL SPECIFICATION - CONSISTS UPON FOLLOWING MODULE: 1. TOA Mixer Power Amplifier 3 Mic Input, 2 Aux, Record Model A-2240 2. TOA Desktop Gooseneck Microphone Model EM-380 3. TOA UHF Dual wireless Microphone Hand type Model # WS-422 4. TOA Coaxial Array 2-way speaker, 15" LF speaker, 8ohm, Horizontal: 9, Vertical: 40, 98 dB (1 W, 1 m) Model# HS-150B 5. TOA Base Reflex speaker, 8ohm, 70, 100V Line Horizontal: 90, Vertical: 40, 98 dB (1 W, 1 m) Model# BS-1030 6. Speaker Stand 7. Supply of Imported 2Core 1.5mmsq Speaker Cable(ROLL) 8. Supply of Imported 2Core Shielded Microphone Cable GENERAL SPECIFICATION - CONSISTS UPON FOLLOWING MODULE: 1. TOA Mixer Power Amplifier 3 Mic Input, 2 Aux, Record Model A-2240 2. TOA Desktop	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Gooseneck Microphone Model EM-380 3. TOA UHF Dual wireless Microphone Hand type Model # WS-422 4. TOA Coaxial Array 2-way speaker, 15" LF speaker, 8ohm, Horizontal: 9, Vertical: 40, 98 dB (1 W, 1 m) Model# HS-150B 5. TOA Base Reflex speaker, 8ohm, 70, 100V Line Horizontal: 90, Vertical: 40, 98 dB (1 W, 1 m) Model# BS-1030 6. Speaker Stand 7. Supply of Imported 2Core 1.5mmsq Speaker Cable(ROLL) 8. Supply of Imported 2Core Shielded Microphone Cable	
130	DNZ5644 1	CZFF-#B	593578503312 1 / SOCKETS ROOM USE 250V 10AMPS CQ-0023	NASR	64 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
131	DNC582 57	ELEC- 2650 / IN 63047/ 2650	623079511027 2 / SEARCH LIGHT HAND HELD (24V DC&230 WATT)	GRIFFON HOVER CRAFT LTD UK	2 / EACH/N UMBER	GEEPAS ®					<u>TECHNICAL SPECIFICATION - 1. Make/ Brand: GEEPAS ® 2. Model: GSL5706 - 30Watt</u> <u>GENERAL SPECIFICATION - 1. Make/ Brand: GEEPAS ® 2. Model: GSL5706 - 30Watt</u>	
132	DGP505 49		753070500718 2 / WHITE OFFSET PAPER SIZE 50.8CMX76. 2CM GSM 62+5%,62-5%		212 / REAM						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
133	DGE642 21	NO DATA AVAILABL E	033050000013 8 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	464 / KILOGR AMME	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) </u> <u>GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
134	DGE62659	NO DATA AVAILABLE	033050000013 8 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	600 / KILOGRAMME	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - material:</u> Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) <u>GENERAL SPECIFICATION - material:</u> Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
135	SGE49363	NO DATA AVAILABLE	041350000013 2 / EAR DENFENDER-SMALL SIZE		1000 / PAIR	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
136	DGE57608		834070508791 4 / TENT SHELTER P.P 50 X 20 FT (ALONG WITH COMPLETE ACCESSORIES)	OLIVE GREEN WATERPROOF INNER LINNING OF,	9 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - PSG-600, SPECIFICATIONS:</u> • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO <u>SPECIFICATION OF CANVAS COTTON:</u> 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER PROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet</p> <p><u>GENERAL SPECIFICATION - PSG-600, SPECIFICATIONS:</u></p> <ul style="list-style-type: none"> • SIZE: 50 X 20 FT • COLOUR: JUNGLE GREEN/ OLIVE GREEN & CAMOUFLAGE. • NO OF FILES: SINGLE • NO OF FOLDS: TWO <p><u>SPECIFICATION OF CANVAS</u></p> <p>COTTON: 100% PURE CANVAS COTTON REQUIRED WHICH IS ROT PROOF, WATER PROOF & FIREPROOF. (OUTER FOLDS: COTTON CANVAS OR WATER pROOF). (INNER FOLDS: DOSUTI OR SHEETING CLOTH, DYED). • WALLS: 5'-8" (DETACHABLE) ALL ROUND WITH SUITABLE DOORS AND WINDOWS NO OF DOORS: 02X DOORS NO OF WINDOW: 04 X WINDOWS TAPE NEWAR : ANY SUITABLE • LIST OF ACCESSORIES • NO OF UPRIGHT POLES: 04 • NO OF RIDGE POLES: 03 • NO OF ROPES: 34 • NO OF PEGS: 34 Diameter of poles: 40 MM <p>Guage of poles: 16 Guage Length of pins: 12" Flapper for Ground sheet: Polyethylene Sheet is best for ground sheet</p> </p>	
137	SPK5834 1		915070505244 2 / TORQUE CONVERTOR OIL TYPE DEXTON II TADANO CRANE 40 TONS (01 ltr,04 ltrs,20 ltrs,208 ltr packing)		65 / LITER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
138	SNM179 56	CPMU-21 (24	414073512647 8 / CONDENSOR FAN BLADE	MOBILE A/C PLANT	15 / EACH/NUMBER	CWM-2C70-PN					<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
139	SPK58339	SPIRAX S2 ATF D2 (9150-17-107-6129)	9150705052100 / SHELL SPIRAX S2 ATF D2 (AUTOMATIC TRANSMISSION FLUID)UK STASCO SHELL (packing 209 ltrs drum)	FOR VBBS BOAT	209 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
140	DNQ62657	140501010	8415991304873 / GLOVES	FIRE FIGHTING	150 / PAIR						TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
141	DNF48082	525502	6650121579560 / BINOCULAR 7X50B/7X50c	BINOCULAR 7X50B OEM: ZEISS,CARL POB 1380	9 / EACH/NUMBER	7x50b/7X50c					TECHNICAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany GENERAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany	
142	DNF53774	ATLAS	6625715110586 / NETWORK ANALYSER MODEL ATLAS CABLE TESTER IT PEAK	CABLE TEST, M/S MAKKAYS 40T/3 BLK6 PECHS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
143	SNM565	CV20747	668599301365	SGA120283,	4 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	77		7 / THERMOSTAT E	PERKINS D/G 600 KVA UK	EACH/N UMBER						WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KGGENERAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG	
144	DGD193 41		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG		9 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
145	DGD326 43		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
146	DGD287 91		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25", THICKNESS 9 SWG		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD), ALUMINUM GRADE 3003. NO BREAKAGE/ BENT.	
147	DGD273 19	NO DATA AVAILAB LE	003550000045 6 / UTENSIL COOKING ALUMINUM WITH COVER O/D:18.5", H: 10",		2 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND CADMIUM (CD). Aluminum Grade: 3003GENERAL SPECIFICATION - ALUMINIUM ALLOY FOOD GRADE, 100% FREE FROM LEAD (PB) AND	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			THICKNESS 10 SWG, Cover Thickness: 10 SWG								CADMIUM (CD). Aluminum Grade: 3003	
148	DGD583 83	NO DATA AVAILABL E	003550000056 0 / COOKER PRESSURE-10 LITRES COMPLETE		3 / SET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free) <u>GENERAL SPECIFICATION -</u> Aluminum Food Grade (Lead Free)	
149	DGP601 19		005150000086 5 / F(SG) 24GUARDCOV ER C/BS&SPS L/NO/NS/STY/7 13 DT 260502		200 / CASE						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
150	DGP601 18		005150000086 6 / F(SG) 25FOR RECEIPTSUPP LYSHEET L/NO NS/STY/713 DT 260502		200 / CASE						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
151	DGP601 17		005150000086 7 / FORM F (SG)26 GUARD		300 / CASE						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
152	DGE504 51	NO DATA AVAILABL E	055979000198 5 / TAPE INSULATING BIAS WIDTH 0.500IN TH 0.01IN LENGTH 50.0 MTR	GENERAL ELECTRIC USE	134 / ROLL	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
153	SNM572 88	4P5975/5B 4855 & 7E9658	441072512783 8 / CONTACTOR GP WATER TEMP SHUTOFF 4P5975, 5B4855 Burning & 7E9658	HP COMPRESSO R	2 / EACH/N UMBER	KAP-23- 40E GERMAN Y					<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			Contractor A									
154	SNO58296	0657C1893S902A/0657C1893S901A	4320014307383 / IMPELLER, PUMP, CENTRifugal		2 / EACH/NUMBER	16V149t11000 kw1605 amps 3 ph (p/e)					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DNQ61651	GOMTEX Ø 30310003800	4730705269709 / hose assy rubber duraline/ gometex lg 100 ft id 1-1/2"		4 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETE X LG 100 FT ID 1-1/2"					TECHNICAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance. GENERAL SPECIFICATION - specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance.	
156	DGP61796	nil	7520705259580 / PERSONEL FOLDER FOR RECORD KEEPING OF of pn civilians		300 / EACH/NUMBER	nil					TECHNICAL SPECIFICATION - 1. SIZE OF FOLDER A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F. FILE FASTNER INNER LINING: CARD BOARD THICK 2.5 MM ± 0.1 MM G. EYELETS: BLACK ALUMINIUM H. TAG COTTON: LENGTH 260 MM ALONG WITH IRON TIP WITH BLACK ENAMEL 3. NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I. FOR NAME TALLEY: 40 MM 65 MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUE <u>GENERAL SPECIFICATION - 1. SIZE OF FOLDER</u> A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F. FILE FASTNER INNER LINING: CARD BOARD THICK 2.5 MM ± 0.1 MM G. EYELETS: BLACK ALUMINIUM H. TAG COTTON: LENGTH 260 MM ALONG WITH IRON TIP WITH BLACK ENAMEL 3. NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I. FOR NAME TALLEY: 40 MM 65 MM I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUE	
157	DNF49162	YYS-OP60N	6650785240913 / OPTICAL POWER METER WITH VFL		1 / EACH/NUMBER	YYS-OP60N					<p>TECHNICAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 μ+10dBm 60NC:--50 μ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 μ30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 μ 60C, 90%RH p. Operating TEMPERATURE : -10 μ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported</p> <p>GENERAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 μ+10dBm 60NC:--50 μ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Output power LIGHT SOURCE of red : 1 ĳ30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 ĳ 60C, 90%RH p. Operating TEMPERATURE : -10 ĳ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported	
158	DPK50340	flexiseal	8010705283910 / NIPPON PAINT FLEXISEAL ELASTOMERIC MEMBRANE (5 KG PACKING)		200 / KILOGRAMME	flexiseal membrane					<p><u>TECHNICAL SPECIFICATION</u> - flexiseal elastomeric membrane is a mastic positive water proofing which formulated ased on elastomeric styrene acylic polymer for exterior application. DFT = 60 - 100 micron Per Coat Drying Time = 2 Hours Hard Dry = 4 Hours Packing details If required: 5 KG container/ box. Date of manufacturing Should be mentioned on container/ Batch No. Minimum shelf life: Up to 36 month in tight sealed container.<u>GENERAL SPECIFICATION</u> - flexiseal elastomeric membrane is a mastic positive water proofing which formulated ased on elastomeric styrene acylic polymer for exterior application. DFT = 60 - 100 micron Per Coat Drying Time = 2 Hours Hard Dry = 4 Hours Packing details If required: 5 KG container/ box. Date of manufacturing Should be mentioned on container/ Batch No. Minimum shelf life: Up to 36 month in tight sealed container.</p>	
159	DNJ50934	853720A6	2910765236454 / CARBURETOR 1		3 / EACH/NUMBER	E40XMHL					<p><u>TECHNICAL SPECIFICATION</u> - null<u>GENERAL SPECIFICATION</u> - null</p>	
160	DNM58089	370-4617	6150016008656 / CABLE ASSEMBLY		1 / EACH/NUMBER	DE-660EO CATERPI					<p><u>TECHNICAL SPECIFICATION</u> - null<u>GENERAL SPECIFICATION</u> - null</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(USB)			LLAR GENERATOR C18 600 KVA /480KW						
161	DNF61367	AR2504E-H	599978523500 / AR2504E-H Huawei AR2500 Series IoT Gateway		1 / EACH/NUMBER	HUAWEI GATEWAY					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
162	DN048533	02.05.04.021	594578527698 2 / Thermal relay		2 / EACH/NUMBER	CLS-350					TECHNICAL SPECIFICATION - Thermal relay GENERAL SPECIFICATION - Thermal relay	
163	DNC59411	TM-C-S02	252073523768 2 / CARDAN SHAFT		2 / EACH/NUMBER	HJ322					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
164	SNM62497	228-7090	533101599302 3 / SEAL-O-RING		28 / EACH/NUMBER	cat c18					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
165	SNM56657	243-5220	3110015370690 / BEARING, BALL, ANNULAR		3 / EACH/NUMBER	C-18 DE605EO CATERPILLER					TECHNICAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8 GENERAL SPECIFICATION - Non drive end bearing kit Kit includes bearing, o-ring and preloading (wavy) washer Bearing diameter: 160 mm (6.3 in) Bearing length: 37 mm (1.46 in) VOLTAGE RANGE 400VOLT FREQUENCY 50HZ FREQUENCY DEVIATION AT STABLE STATE 0.5% VOLT RETURN TIME 2 SEC CONNECTIONS 3PH POWER FACTOR 0.8	
166	SNM55111	5P-6718	533101181495 1 / SEAL - O - RING		2 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - SEAL - O - RING GENERAL SPECIFICATION - SEAL - O - RING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
167	SNM55110	237-0284	291071526854 8 / LINE AS - FUEL (LOW PRESSURE RETURN)		1 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - LINE AS - FUEL (LOW PRESSURE RETURN)GENERAL SPECIFICATION - LINE AS - FUEL (LOW PRESSURE RETURN)	
168	SNF52816	HTS-RLY-24V8P / hhc70/2-1	594570524609 9 / 4x relays 24vDC		12 / EACH/NUMBER	RLY-24V8P /HHC70/2-1					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
169	DPC57841	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
170	DPC58189	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
171	DPC58264	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
172	DPC58349	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
173	DPC58406	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		25.5 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
174	DPC57992	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
175	DPC58141	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		20.4 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
176	DNQ61650	GOMTEX Ø 30310005000	4730705269708 / hose assy rubber duraline /gomtex lg 100 ft id 2"		4 / HUNDR ED FT	HOSE ASSY RUBBER DURALINE /GOMETE X LG 100 FT ID 2"					<u>TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.</u> oem/country of origin GOMTEX/ usa <u>GENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.</u> oem/country of origin GOMTEX/ usa	
177	DGP64558	CORE I5	7025705246091 / PERSONAL		4 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPUTER (CORE: I5)								<p>Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
178	DNM58179	317-7485	6130016005398 / COMMUNICAI		1 / EACH/NUMBER	DE-660EO CATERPILLAR					<p><u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TON ADAPTER (3)			GENERATOR C18 600 KVA /480KW						
179	DN054870	CSA-125-SEW/FFF3	5340785279633 / ISOMETRIC COMPOSITE SACRIFICIAL ANODE (125 OD = 164 Ømm, ID = 127 Ømm)		48 / EACH/NUMBER	CLS-350				NEWSPAPER	TECHNICAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN 125 OD = 164 (Ømm), ID = 127 (Ømm), Length of sleeve = 50 (mm) GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN 125 OD = 164 (Ømm), ID = 127 (Ømm), Length of sleeve = 50 (mm)	
180	SNF54666	VO0401H H-DC3000 (HDMI)	5963785268097 / video wall controller 04 channel output		1 / EACH/NUMBER	VI0801HH					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
181	DNF56230	CHDHX-801K3	7025785235460 / GOPRO HERO 8 WITH GOPRO KIT & 128 GB 4K CARD		1 / EACH/NUMBER	CHDHX-801K3					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
182	DSB57462	MAT166-0462	0870080254720 / SUCTION HOSE FLEXIBLE PIPE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Suction House Flexible Pipe Length=950mm Pay role outer fitting=27mm Flexible hose outer dia=36mm Brass nut inner dia=42.5mm Brass nut outer dia=53mm Pitch of Nut 2.0mm Inner dia of pay role=20mm A. In date shelf life of flexible hose B. Qualification of Pressure Test at 300 bar C. At 3F basis GENERAL SPECIFICATION - Suction House Flexible Pipe Length=950mm Pay role outer fitting=27mm Flexible hose outer dia=36mm Brass nut inner dia=42.5mm Brass nut outer dia=53mm Pitch of Nut 2.0mm Inner dia of pay role=20mm A. In date shelf life of flexible hose B. Qualification of Pressure Test at 300 bar C. At 3F basis	
183	DNZ6425	0660047-	669599279968		1 /	7160				NEWSPAP	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	8	20	6 / SWIFT SVP PROFILER		EACH/N UMBER					ER	SWIFT SVP PROFILER <u>GENERAL SPECIFICATION - SWIFT SVP PROFILER</u>	
184	SNM567 43	2W7585	312001212474 0 / THRUST WASHER		4 / EACH/N UMBER	3512 TA					<u>TECHNICAL SPECIFICATION - THRUST WASHER</u> <u>GENERAL SPECIFICATION - THRUST WASHER</u>	
185	SNM538 49	6I-0363	530514502765 4 / BOLT (M6X1X20-MM)		4 / EACH/N UMBER	DE110E2					<u>TECHNICAL SPECIFICATION - THREAD (MM): 1 LENGTH (MM): 20 DIAMETER Ø (MM): 6 MATERIAL: STEEL (ZINC PLATED)</u> <u>GENERAL SPECIFICATION - THREAD (MM): 1 LENGTH (MM): 20 DIAMETER Ø (MM): 6 MATERIAL: STEEL (ZINC PLATED)</u>	
186	DRP292 90	011- 110031- 000	8040ZO520308 9 / TAPE, FILM, KAPTON SILICONE, ADHESIVE		36 / EACH/N UMBER	SCANEA GLE					<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
187	SPK5833 6	m3277	915070524050 5 / engine oil fuchs titan cargo (15w40)		20 / LITER	m3277					<u>TECHNICAL SPECIFICATION -</u> <u>null</u> <u>GENERAL SPECIFICATION -</u> <u>null</u>	
188	DNM642 46	4309459	281501662927 9 / UPPER ENGINE GASKET		1 / EACH/N UMBER	QSB 6.7 300 HP CUMMIN S ENGINE					<u>TECHNICAL SPECIFICATION -</u> <u>COUNTRY: UK MANUFACTURE:</u> <u>CUMMINS MODEL: QSB 6.7</u> <u>GENERAL SPECIFICATION -</u> <u>COUNTRY: UK MANUFACTURE:</u> <u>CUMMINS MODEL: QSB 6.7</u>	
189	DNF6232 1	aol pll-01	585070529306 3 / led aviation mast light 110- 240V AC 4WATT (RED COLOR)		30 / EACH/N UMBER	PLL-01					<u>TECHNICAL SPECIFICATION -</u> <u>null</u> <u>GENERAL SPECIFICATION -</u> <u>null</u>	
190	DPK5958 0	STM7610A B10L	685014352474 2 / SAFETY DAGREASING SOLVENT		10 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO</u> <u>DATA AVAILABLE</u> <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> <u>AVAILABLE</u>	
191	DNF6309 5	J9776A/r8 n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/N UMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP</u> <u>ARUBA 24 PORT NETWORK</u> <u>SWITCH</u> <u>GENERAL</u> <u>SPECIFICATION - HP ARUBA 24</u> <u>PORT NETWORK SWITCH</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
192	SNM56659	317-5486	311071523984 7 / BEARING		4 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - INNER DIAMETER (IN): 1.77 OUTER DIAMETER (IN): 3.56 WEIGHT (IB): 0.28 LENGTH (IN): 4.5 HEIGHT (IN): 4 GENERAL SPECIFICATION - INNER DIAMETER (IN): 1.77 OUTER DIAMETER (IN): 3.56 WEIGHT (IB): 0.28 LENGTH (IN): 4.5 HEIGHT (IN): 4	
193	DGD55636	CGF-01	731070526966 2 / CHARCOAL GRILL 24"		1 / EACH/NUMBER	CGF-01					TECHNICAL SPECIFICATION - sSTAINLESS STEEL 304 TOP 1.5MM, CAST IRON GRILLS (HEAVY DUTY), CAST IRON FLAME BLOCKS (HEAVY DUTY), STAINLESS STEEL 304 LEGS 1 1/2" X 1 1/2" (ADJUSTABLE), ITALIAN VALVE DIRECT ASSEMBLY, HIGH EFFICIENT BURNERS (80,000 BTU), LPG/NUTURAL GAS SUPPORTED, STAINLESS STEEL DIP TRAY, DIMENSION: 35X35X34 (LXBXH) iN INCHES GENERAL SPECIFICATION - sSTAINLESS STEEL 304 TOP 1.5MM, CAST IRON GRILLS (HEAVY DUTY), CAST IRON FLAME BLOCKS (HEAVY DUTY), STAINLESS STEEL 304 LEGS 1 1/2" X 1 1/2" (ADJUSTABLE), ITALIAN VALVE DIRECT ASSEMBLY, HIGH EFFICIENT BURNERS (80,000 BTU), LPG/NUTURAL GAS SUPPORTED, STAINLESS STEEL DIP TRAY, DIMENSION: 35X35X34 (LXBXH) iN INCHES	
194	DNM64247	4309460	533001665761 1 / LOWER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE CM 2250					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
195	SNM47012	2656615	534070524601 9 / fuel filter head		2 / EACH/NUMBER	3-2500					TECHNICAL SPECIFICATION - OEM:MILLAT TRACTOR LTD, LHR GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM:MILLAT TRACTOR LTD, LHR	
196	DSB64475	23220CC/C3W33	311014506655 3 / BEARING, ROLLER, SELF-ALIGNING		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - • Make be indicated. • SKF FRANCE • Parent Equipment be indicated. Diesel Generator BD086 and BD063 GENERAL SPECIFICATION - • Make be indicated. • SKF FRANCE • Parent Equipment be indicated. Diesel Generator BD086 and BD063	
197	DNM64107	JL269	668570523837 9 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
198	DNM63956	JL269	668570523837 9 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
199	DNM63950	0140-4331	294078524088 4 / filter,air		2 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
200	DNM63954	0509-0514	533179523744 2 / SEAL OIL		2 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
201	DNF51788	2810019	616073524492 8 / battery 12v 170 ah		2 / EACH/NUMBER	CLASSIC V					TECHNICAL SPECIFICATION - DRY BATTERY Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KGGENERAL SPECIFICATION - DRY BATTERY Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KG	
202	DNM63953	0509-0507	533179523743 9 / SEAL OIL		2 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
203	DSB63627	9506720	137012386535 0 / Para Red FLARE MK8A		8 / EACH/NUMBER	PARA RED FLARE MK8A				MAMUN ALI BUMASUK PVT LTD SHOAIB UR REHMAN 2132201140 /	TECHNICAL SPECIFICATION - Para Red Rocket MK8A The Pains Wessex Para Red MK8A Rocket conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water, the pull wire ignitor and improved grip provides easy	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
										030092680 78 WWW. SHOAIB. REHMAN@ MABGRP. COM	handling. Ejecting a red flare on a parachute at 300m (1000ft), burning for 40 seconds at 30,000 candela. <u>GENERAL SPECIFICATION - Para Red Rocket MK8A The Pains Wessex Para Red MK8A Rocket conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water, the pull wire ignitor and improved grip provides easy handling. Ejecting a red flare on a parachute at 300m (1000ft), burning for 40 seconds at 30,000 candela.</u>	
204	DNF54578	dem-310gt	593070524633 3 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		2 / EACH/NUMBER	dgs-1510-28x					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
205	DNF63947	VE/S. Sockets/F P.1012	593050523486 3 / Switch Socket TWO PIN		77 / EACH/NUMBER	VE/S. Sockets/F P.1012					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
206	DN063355	G860022-02 / ZRACR-065-SEW	6115FP105006 5 / ANTI-CORROSIVE ZINC ROD		2 / EACH/NUMBER	1FR6 506-4SA42-2					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
207	DNQ63199	MM308R	422079530063 7 / TORCH BATTERY		15 / EACH/NUMBER	n/a					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
208	DNF48088	SUN-SC-10M-SC-SM SX-3P	704578524964 4 / Patch cords SC-SC (10 Meter)		8 / EACH/NUMBER	SUN-SC-10M-SC-SM SX-3P					<u>TECHNICAL SPECIFICATION - Complete Details regarding OFC Patchcord are available in the attached Brochure named "Fiber</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Simplex SC/UPC - simplex SC/UPC connector; Length: 10Meter (Tolerance:0~0.1M); SM, G652D; Simplex cable; 3.0mm PVC jacket								Optic Patchcord and pigtails" <u>GENERAL SPECIFICATION -</u> Complete Details regarding OFC Patchcord are available in the attached Brochure named "Fiber Optic Patchcord and pigtails"	
209	DSA61136	81504025	6350143569620 / CELLULE-PNEUMATIQU E 21504025		107 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
210	DNM64011	0102-1543	5330015734932 / joint-sump to cylinder block assembly (1 pair) / GASKET OIL BASE		2 / EACH/NUMBER	c22 d5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
211	DNF63937	YWF(K) 4E500-Z	4140785259575 / AXIAL FAN FOR CONDENSOR OF COLD ROOM PLANT		1 / EACH/NUMBER	YWF(K) 4E500-Z					<u>TECHNICAL SPECIFICATION -</u> Make: Wenling Sanmu Machine Electricity Co.Ltd OEM: USA Copeland The Central Industry Zone, Chengnan Town, Wenling city, Zhejiang Province China. Tele No: +86-576-86268888 86268019 Fax: +86-576-868020 Website: www.cnsanmu.com Email: info@cnsanmu.com BLACK FAN WITH MOTOR <u>GENERAL SPECIFICATION - Make:</u> Wenling Sanmu Machine Electricity Co.Ltd OEM: USA Copeland The Central Industry Zone, Chengnan Town, Wenling city, Zhejiang Province China. Tele No: +86-576-86268888 86268019 Fax: +86-576-868020 Website: www.cnsanmu.com Email: info@cnsanmu.com BLACK FAN WITH MOTOR	
212	DNF6181	d701-592	6350CA527106		1 /	na					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	7		4 / vapor swabs (pack of 12 swabs)		EACH/NUMBER						nullGENERAL SPECIFICATION - null	
213	DNM63952	0122-0935	533079526430 2 / GASKET OIL FILTER		2 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
214	DSA44850	ORB-TQT/70/V1/18ERPM MS	615070521687 1 / MAIN BOX		2 / EACH/NUMBER	m/s baig engineering					TECHNICAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY SYSTEM (BD) OEM: M/S BAIG ENGINEERINGGENERAL SPECIFICATION - MAKE/ MODEL: M/S BAIG ENGINEERING PARENT EQUIP: MAIN ENGINE SAFETY SYSTEM (BD) OEM: M/S BAIG ENGINEERING	
215	DNF62289	RSFD-II	613578528471 7 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		9 / EACH/NUMBER	RSFD-II					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
216	SNM45551	8159975-5	291033204861 1 / FUEL FILTER AND WATER SEPARATOR	DG VOLVO PENTA 210KVA	2 / EACH/NUMBER	NO DATA AVAILAB LE		FR	SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&LARGE B-72ESTATE AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19		TECHNICAL SPECIFICATION - OEM & MAKE: VOLVO PENTAGENERAL SPECIFICATION -OEM & MAKE: VOLVO PENTA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									KARACHI 75700			
217	DNM63942	256-7704	5330715219503 / SEAL-VALVE COVER	DG CAT 7.1 USA	6 / EACH/NUMBER	CAT7.1	Cat00C71 KGTY00676	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR		TECHNICAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM GENERAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM	
218	DNF62291	6-FMX-100B/cmbt-g-12-150	6140785221249 / MAINTENANCE FREE BATTERIES 12 VOLT 90-100 AH	Microwave	3 / EACH/NUMBER	Crown Micro		WAREHOUSE NO.CA02, Near R/A08, Jebel Ali Freezone, Dubai, UAE Phone(INTERNATIONAL) +971-4-883-9373 AX +971-4-883 9756	CROWN MICRO AGM CHINA		TECHNICAL SPECIFICATION - required for backup supply for microwave GENERAL SPECIFICATION - required for backup supply for microwave	
219	DNA48898	34235	5330705164334 / KIT VALVE	SEA WATER PUMP	2 / EACH/NUMBER	3535		DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMABAD		TECHNICAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104 GENERAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	
220	DNF54624	20077	5925144185090 / 2 POLE MULTI-9 BREAKER 25A 380 VOLT	MAIN SWITCH BOARD	5 / EACH/NUMBER	C-32H/MERLIN GERIN		SCHNEIDER ELECTRIC INDUSTRIES SAS (MERLIN GERIN) 35 RUE JOSEPH MONIER RUEIL MALMAISON FRANCE TEL:0141297000 FAX:0141297100 WWW.SCHNEIDER-ELECTRIC.FR	MERLIN GERIN		TECHNICAL SPECIFICATION - 2 POLE 380VOLT 50HZ 2PHASE 25A (multi 9) C60N GENERAL SPECIFICATION - 2 POLE 380VOLT 50HZ 2PHASE 25A (multi 9) C60N	
221	DNF58891	99-00182-00	5920735204999 / Power Surge Arrestor PoE RJ45 Outdoor Bottom 2xRJ45 Jacks	REDLINE	5 / EACH/NUMBER	LP-POE-ALPU-01	NIL	REDLINE COMMUNICATION, 302 Town Centre Blvd, Toronto, Ontario Canada, +19054798344, +186663366699, www.rdlcom.com, info@rdlcom.com	REDLINE COMMUNICATIONS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
222	DNM63831	3015067	5331013264774 / SEAL D RING	DIESEL GENERATOR	6 / EACH/NUMBER	KTAA 19-G6/G7	4061330-00	CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 TEL:8123775009 FAX:8123771715	CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES		TECHNICAL SPECIFICATION - LINER KIT REF NO 20 GENERAL SPECIFICATION - LINER KIT REF NO 20	
223	SNF44732	A9F44110	5925795144153 / IC60N 1P 10A C MINIATURE CIRCUIT BREAKER	KH RADAR SYSTEM (F-22P)	4 / EACH/NUMBER	IC60N		GR	NCAGE INFORMATION KELVIN HUGHES LIMITED NEW NORTH ROAD HAINAULT, ILFORD ESSEX UNITED KINGDOM IG6 2UR 0208 502 6887,020 8 559 8892 CLIVE. CORRIS @KELVIN HUGHES. CO.UK, WWW. KELVIN HUGHES. CO.UK		TECHNICAL SPECIFICATION - OEM: SCHNEIDER ELECTRIC MAKE: SCHNEIDER ELECTRIC BRAND FRANCE & MODEL: IC60N/A9F44110 TDS ARE ATTACHED RATED CURRENT: 10A ,RATED OPERATIONAL VOLTAGE: 240 V AC 50/60HZ GENERAL SPECIFICATION - OEM: SCHNEIDER ELECTRIC MAKE: SCHNEIDER ELECTRIC BRAND FRANCE & MODEL: IC60N/A9F44110 TDS ARE ATTACHED RATED CURRENT: 10A ,RATED OPERATIONAL VOLTAGE: 240 V AC 50/60HZ	
224	DNS47935	113 009	2815735185636 / SECURING RING	WARTSILA MAIN ENGINE	54 / EACH/NUMBER	9L20C3	MADPAAE084245, PAAE084242 RASDPAAE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								Fax (Spare parts) +358 10 709 1380				
225	DNS48054	125 002	5305735185468 / SEALING RING SELECTION	WARTSILA MAIN ENGINE 9L20C3 FINLAND	18 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
226	DNF64025	01-00-0587-00	6350715194477 / CONVEYOR BELT 100X LC	Luggage Scanning Machine size (40)	3 / EACH/NUMBER	XIS-100X	ASTVC18 0LL740	ASTROPHYSICS INC. UNITED STATES psc91789-5233 tel 9095985488 fax 9095985546 nai 334511+334517+334519+335999+488119	Astrophysics Manufacturing		<u>TECHNICAL SPECIFICATION - Security Equipment</u> <u>GENERAL SPECIFICATION - Security Equipment</u>	
227	DNS56368	ITL22L6B	4810775187938 / INTERNAL PARTS CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250-S/WO-K HOLLAND	1 / EACH/NUMBER	WART-LCT-CS250-S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion. service@wartsila.com http : //www.wartsila.com	Wartsila Propulsion Netherlands B.V.		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
228	DNF49043	05-00-0665-00	6350715194467 / POWER SUPPLY 5VDC, 15A	Luggage Scanning Machine size (40)	2 / EACH/NUMBER	XIS-100X	ASTVC18 0LL740	ASTROPHYSICS INC. UNITED STATES psc91789-5233 tel 9095985488 fax 9095985546 nai 334511+334517+334519+335999+488119	Astrophysics Manufacturing		<u>TECHNICAL SPECIFICATION - Security Equipment</u> <u>GENERAL SPECIFICATION - Security Equipment</u>	
229	DNF63861	AC4000 RF	5895705158501 / BIOMETRIC MACHINE (VIRDI)	BIOETRIC MACHINE (Viridi)VISITOR THUMB IMPRESSION.	3 / EACH/NUMBER	AC4000 RF		M/SJAFFER BROTHERS.	M/SJAFFER BROTHERS.		<u>TECHNICAL SPECIFICATION - M/SJAFFER BROTHERS. PRICE, 9,219.00/BIOETRIC MACHINE(Virdi) VISITOR THUMB IMPRESSION. AC4000RF.</u> <u>GENERAL SPECIFICATION - M/SJAFFER BROTHERS. PRICE,9,219.00 /BIOETRIC MACHINE(Virdi) VISITOR THUMB IMPRESSION. AC4000RF.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
230	DNS57649	471 598	4310735186120 / SUPPORT DISC	WARTSILA MAIN ENGINE 9L20C3 FINLAND	2 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - WARTSILA MAIN ENGINE 9L20C3</u> <u>GENERAL SPECIFICATION - WARTSILA MAIN ENGINE 9L20C3</u>	
231	DNS57629	471 193	5306735187069 / SCREW	WARTSILA MAIN ENGINE 9L20C3 FINLAND	3 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
232	DGP58350	12U	5995715206945 / RACK (12U)	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	1 / EACH/NUMBER	Aunet	AU12UB	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA		<u>TECHNICAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.</u> <u>GENERAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.</u>	
233	DNF52884	ALN-ENM	1005795204002 / SMOKE DETECTOR HOCHIKI WITH BASE YBN-R/3	FIRE ALARM SYSTEM ALN-ENM UK	4 / EACH/NUMBER	ALN-ENM	NLI	GROSVENER ROAD, GILLINGHAM BUSINESS PARK, GILLINGHAM, KENT ME80SA UNITED KINGDOM +44(0) 1634260133 info@hochikieurope.com	HOCHIKI EUROPE (UK) LTD		<u>TECHNICAL SPECIFICATION - OPERATING VOLTAGE : 17-41VDC ALARM CURRENT : 9.1 mA OPERATING TEMPERATURE : -10 C to 50 C OPERATING HUMIDITY : 95% RH-NON CONDENSING (AT 40 C) STORAGE TEMPRETURE : -30 C to +60 C STORAGE HUMIDITY : 80% RH AT 60 C TECHNICAL MANUAL ENCLOSED</u> <u>GENERAL SPECIFICATION - OPERATING VOLTAGE : 17-41VDC ALARM CURRENT : 9.1 mA OPERATING TEMPERATURE : -10 C to 50 C</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											OPERATING HUMIDITY : 95% RH-NON CONDENSING (AT 40 C) STORAGE TEMPRETURE : -30 C to +60 C STORAGE HUMIDITY : 80% RH AT 60 C TECHNICAL MANUAL ENCLOSED	
234	DNF64040	MIT 420-EN	6625994623063 / DIGITAL MEGGER MIT 420 EN INSULATION AND CONTINUITY TESTER INCLUDING (TEST WEE MEGGER)	TEST EQUIPMENT	1 / EACH/NUMBER	NO DATA AVAILAB LE			UK	M/S MEGGITT (UK) LTD TA MGGITT AVIONIC S 7 WHITTLE AVE HAMPSHIRE UK 9015 5SH TEL: 01489-483300 FAX: 01489-483340	TECHNICAL SPECIFICATION - PATTERN NO MENTIONED IN CONTRACT VIDE CONT NO. 852015//R-812/310497 DATED:05-06-2009 IS PATTERNIZED. GENERAL SPECIFICATION - PATTERN NO MENTIONED IN CONTRACT VIDE CONT NO. 852015//R-812/310497 DATED:05-06-2009 IS PATTERNIZED.	
235	DNM63811	3081489	5330014905726 / SEAL OIL	CUMMINS DG 750KVA	6 / EACH/NUMBER	PBD 825 (C)A	111142533	CHONGQING CUMMINS ENGINE COMPANY LTD	CUMMIN S CHINA		TECHNICAL SPECIFICATION - REQUIRED FOR MAINTENANCE OF DIESEL GENERATOR GENERAL SPECIFICATION - REQUIRED FOR MAINTENANCE OF DIESEL GENERATOR	
236	DNQ63318	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE			UK	UK ENGLAN D	TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
237	DNQ63147	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	5 / ROLL	NO DATA AVAILAB LE			UK	ENGLAN D	TECHNICAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john- holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL</u>	
238	SNJ45657	12892-93J00-240	5365765222370 / SHIM, TAPPET (T: 2400)	SUZUKI DF300AP 300 HP OBM	16 / EACH/N UMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
239	DNJ61834	25141-93L00-0EP / 25141-93L01-OEP / 25141-93L00-YAY	5340765221937 / HOUSING, SHIFT ROD GUIDE (BLACK)	SUZUKI DF300AP 300 HP OBM	1 / EACH/N UMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN		SUZUKI JAPAN	TECHNICAL SPECIFICATION - ENGINE MODEL: DF300AP <u>GENERAL SPECIFICATION - ENGINE MODEL: DF300AP</u>	
240	DNM640	FF9011	294001523005	CUMMINS 200	2 /	6CTA8.3	78515443	Cummins Americas Inc,		USA	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	93		0 / Fuel Filter	KVA DG	EACH/N UMBER			3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433- 5797			MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE: CUMMINS USA	
241	DNF6182 4	627-098	414072517236 4 / BLOWER	FLASH POINT TESTER	2 / EACH/N UMBER	HFP 339		WALTER HERZOG GmbH Test Equipment for Mineral Oil Products BadstraBe 3-5 D-97912 Lauda- Konigshofen,Postfach 1241 Germany	GERMAN Y		TECHNICAL SPECIFICATION - Operating Manual (Flash Point Tester)GENERAL SPECIFICATION - Operating Manual (Flash Point Tester)	
242	DNF6402 0	DH- PFM900-E/ IPC 9800ADH Plus/ IPC9300S ACT	582073523164 5 / ALMIGHTY IPC TESTER FOR CCTV CAMERA VIGIL SYSTEM	CCTV VIGIL SYSTEM	1 / EACH/N UMBER	IPC9300S ACT		M/S OPENPINOY PHILPINE TELL NO. (02) 8722-0909.FAX NO. (02) 8570-0909. CCTV@OPENPINOY.COM	M/S OPENPIN OY PHILPINE		TECHNICAL SPECIFICATION - BROUCHER ATTACHGENERAL SPECIFICATION - BROUCHER ATTACH	
243	DNM646 11	FTXN50JX V1	412076522267 6 / AIR CONDITIONAR 1.5 TON INVERTOR/RE VERSABLE	AC	1 / EACH/N UMBER	FTXN50J XV1		DIAKIN, JAPAN	JANPAN, MITSUBI SHI		TECHNICAL SPECIFICATION - NAGENERAL SPECIFICATION - NA	
244	DNM640 19	9Y3333	442001218434 8 / CORE ASSEMBLY FLUID	CATTER PILLAR D/G	1 / EACH/N UMBER			USA CATTER PILLAR	CATTER PILLAR		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
245	SGB561 61	DG SHIPS 6142	021859571176 2 / PIPING STEEL SEEMLESS DIA 1.0 INCH THICKNESS 0.270 INCH		20 / METER						TECHNICAL SPECIFICATION - Outer Diameter: 25.4 mm, Inner Diameter: 11.7 mm, Thickness: 6.85 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JRGENERAL SPECIFICATION - Outer Diameter: 25.4 mm, Inner Diameter: 11.7 mm, Thickness: 6.85 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
246	SNM496 84	7961447	130979499002 3 / FILTER- ELEMENT		10 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
247	DNF5789 6	BS EN 60317-8	056179525358 0 / WIRE,	WIRE FOR WINDING	5 / KILOGR						TECHNICAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			WINDING COPPER ELECT COND DIA 1.320 O/DIA 1.423 MM (CLASS-180) GRADE-2		AMME						(CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2GENERAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
248	DNF50512	BSEN60317-8	0561794393265 / WIRE, WINDING COPPER ELECT COND DIA: 0.560MM O/ DIA : 0.632 MM CLASS-180 GRADE-2	MOTOR WINDING	35 / KILOGRAMME	GHAZILE X					TECHNICAL SPECIFICATION - Copper purity 99.98% Class -180 GENERAL SPECIFICATION - Copper purity 99.98% Class -180	
249	DNA44334	0400-2998	2990725006910 / STOP RING DEUTZ BA12H716 0400-2998	DEUTZ DIESEL GENERATOR 350KW	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
250	DNG61292	SO-614PLF3	2910705060479 / SEPARATER ELEMENT	H S D O FILTERATION PLANT VELCON TL8400	20 / EACH/NUMBER	TL-8400					TECHNICAL SPECIFICATION - FILTER CHANGED AFTER 01 YEAR OR DIFFERENTIAL PRESSURE REACH 15 PSI AND WASHABLE (NOT RE-USED) VIDE MOAWIN LETTER 305/15/655 DATED 01 APR 13 AND 305/15/640 DATED 28 MAR 13. GENERAL SPECIFICATION - FILTER CHANGED AFTER 01 YEAR OR DIFFERENTIAL PRESSURE REACH 15 PSI AND WASHABLE (NOT RE-USED) VIDE MOAWIN LETTER 305/15/655 DATED 01 APR 13 AND 305/15/640 DATED 28 MAR 13.	
251	DNM64425	QP407PA A	4310765021898 / COMPRESSOR 2 TON BTU 24000 ROTARY 220V 50 HZT	A/C 02 TON WINDOW TYPE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
252	DNH61499	DV-200N	4310795113465 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
253	DNH64430		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
254	DNM41574	EBH16 / TV16/tve-24	4130US5065504 / COOLING UNIT	MAIN A/C CRISAIR USA TYP.F48E-P.	1 / EACH/NUMBER	921047473					TECHNICAL SPECIFICATION - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22 GENERAL SPECIFICATION - Brand: Breeze Tech Spec: 110 V 1Ph 60 Hz Refrigerant: R-22	
255	DNH64449	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	3 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
256	DNZ55501	NTN 7308B	3110785037049 / BEARING BALL ANGULAR NTN 7308B 040X090X23MM	CARGO F-W PUMP 2FDDV-65B NASR	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
257	DNH64424	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND		2 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DAWLANCE									
258	DNM644 26	8S1606	533000437875 2 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA- 9MM TH-03MM	3304PC, CATERPILLER D/GEN.USA	2 / EACH/N UMBER	3304 SSDG					<u>TECHNICAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
259	SNM455 73	1P1255	533001367572 4 / GASKET JOINT WD- 29MM LG- 70MM TH-1MM HOLE DIA- 11MM	FOR CATER PILLER DIESEL GENERATOR (USA)	4 / EACH/N UMBER	3304B					<u>TECHNICAL SPECIFICATION -</u> OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
260	DNF4870 4	J9627A	593073511469 1 / 48 Port 10/100 Layer 2 Managed Switch	AT-8300 SERIES	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network SwitchGENERAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch	
261	DNF6201 2	158-51010	596199558030 7 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
262	DNF5417 2	SERVO COTROL STAC JAPAN	611070504503 7 / STABLIZER 3KVA I/P50- 130V/160- 240VAC50/60H Z O/P110/220V STAC	ELECTRICAL GENERAL USE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
263	DSB6257 1	23TR4A	599000822545 1 / SYNCHRO RECEIVER ROTOR I/P- 115V 400HZ 7.8 WATT SIZE 23	MK73MOD1, INDICATOR, RECOMMEND ED COURSE	1 / EACH/N UMBER					OEM MS RADIO741 SALES@R ADIO741. COM +30231032 5605	<u>TECHNICAL SPECIFICATION - MIL-</u> S-20708-94GENERAL SPECIFICATION - MIL-S-20708-94	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										greece		
264	DNJ63862		5965765018642 / SPEAKER NVS 415A 2W P/A 1410L-83	PUBLIC ADDRESSERMODEL NVA-1410L-83	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
265	DNF47256	STABAC SB-500	6110705055051 / UPS 500VA I/P180-240VAC O/P220V 50/60HZ B.U. T1.5HR WITH BATT	TEST EQUIPMENT SATVRN-32	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
266	DNF61504	HDR-XR200/XR150	6710765119366 / DIGITAL VIDEO CAMERA SONY	DIGITAL VIDEO CAMERA	1 / EACH/NUMBER	HDR-XR200/XR150					TECHNICAL SPECIFICATION - DNSS LTR ST-S/3201/06229 DT 16JUN 06 GENERAL SPECIFICATION - DNSS LTR ST-S/3201/06229 DT 16JUN 06	
267	DGE64165	NO DATA AVAILABLE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	579 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
268	DGE64252	NO DATA AVAILABLE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	200 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											, WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
269	DGP62380		753070504576 7 / TRACING PAPER SIZE A-4 GSM 85+- 5% (250 SHEETS PER PACKET)		2 / PACKE T						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
270	DNQ64103	140501010	841599130487 3 / GLOVES	FIRE FIGHTING	6 / PAIR						<u>TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.</u>	
271	DGP58057		751059502542 3 / PAPER BUTTER WHITE		1000 / SHEET						<u>TECHNICAL SPECIFICATION - LENGTH 19.25" WIDTH 29" 30 GSM ± 5% White Color Transparent Sheet Sheet</u> <u>GENERAL SPECIFICATION - LENGTH 19.25" WIDTH 29" 30 GSM ± 5% White Color Transparent Sheet Sheet</u>	
272	SNJ13214	Y231004000	668576501026 6 / THERMOMET ER P/N Y2310 04000 FOR M/ENGINE	MAIN DIESEL GENERATOR ENGINE	30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
273	DGD64264	NO DATA AVAILABL	003550000038 5 / MINCING		1 / EACH/N	NO DATA AVAILAB					<u>TECHNICAL SPECIFICATION - MINCING MACHINE LARGE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		E	MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14		UMBER	LE					MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14" WD 17"HT 25" LOCAL MADE MILD STEEL B/ ATTCHED <u>GENERAL SPECIFICATION - MINCING MACHINE LARGE MOTOR 1 HP 220V MILD STEEL FULL COVER ACCIDENT PROOF SIZE LG14" WD 17"HT 25" LOCAL MADE MILD STEEL B/ ATTCHED</u>	
274	DGP62712	NO DATA AVAILAB LE	0050500000223 / PAPER DUPLICATING		300 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u> <u>GENERAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u>	
275	DNF62282	TXFR-221	5950705124265 / STEP DOWN TRANSFORMER 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH	MARINE VERSION SPLIT A/C	1 / EACH/NUMBER	DELTA TRFOR 400V/440 HZ 3P 5KVA 220V 50/60					<u>TECHNICAL SPECIFICATION - 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI.</u> <u>GENERAL SPECIFICATION - 05 KVA I/P 440V, 60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI.</u>	
276	DNF63935	YWF-4E-300-S 92/35-G	4140785238246 / AXIAL FAN		1 / EACH/NUMBER	YWF-4E-300 CHINA					<u>TECHNICAL SPECIFICATION - OEM, WEIGUANG CHINA WWW. WGMOTOR.COM</u> <u>GENERAL SPECIFICATION - OEM, WEIGUANG CHINA WWW. WGMOTOR.COM</u>	
277	DSB63628	9529000	1370992197117 / Hand flare RED (solas approved) mk-8		6 / EACH/NUMBER	mk-8				MAMUN ALI BUMASUK PVT LTD	<u>TECHNICAL SPECIFICATION - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										SHOAIB UR REHMAN 2132201140 / 03009268078 WWW. SHOAIB. REHMAN@MABGRP.COM	exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela. <u>GENERAL SPECIFICATION</u> - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela.	
278	DNF63853	51289	5999705284428 / VACUUM CLEANER WET AND DRY MOD 4200L		1 / EACH/NUMBER	42I					<u>TECHNICAL SPECIFICATION</u> - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8i/min at a pressure of 2 bar <u>GENERAL SPECIFICATION</u> - 2 stable castor wheels 2 rubber rear wheels built in detergent tank detergent socket tough, sturdy plastic tank two stage motor plastic body flow rate of 0.8i/min at a pressure of 2 bar	
279	DSB61221	GSM141-03F5DN16-1	5310142569009 / RONDELLE FREIN DN16 (MESMA)		3222 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
280	DNF64573	A074A900	5998795284988 / system control board scb1		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION</u> - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHAM,MK18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AREA MALIR CANTT KARACHI-75070.GENERAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070.	
281	DNF64572	134-88-01	5998795284989 / KEYPAD		1 / EACH/NUMBER	134-88-01					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
282	DNF64575	134-88-25	5998795284991 / LCD ASSEMBLY		1 / EACH/NUMBER	134-88-25					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
283	DNZ58916	E-02-14	4810785277589 / SECONDARY INTAKE VALVE		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
284	DNF63613	DJI RC	5998765280434 / dji rc smart controller occui sync 2.0		3 / EACH/NUMBER	CP.MA.00000080.01					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
285	DNF63715	DJI RC	5998765280434 / dji rc smart controller occui sync 2.0		5 / EACH/NUMBER	CP.MA.00000080.01					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
286	DNF64574	A074A915	5998795284987 / LCD CONTROL BOARD		1 / EACH/NUMBER	A074A905					TECHNICAL SPECIFICATION - Power Supply: 14 V 3.5 Amp ACGENERAL SPECIFICATION - Power Supply: 14 V 3.5 Amp AC	
287	DNM45004	276-5603	5331015842063 / SEAL-O-RING		2 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWNGENERAL SPECIFICATION - NOT KNOWN	