

TENDER BULLETIN

DATE & TIME 6/11/24 11:22 AM INVITATION TO TENDER TO BE OPENED ON 7/3/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	SNM61339	25593	4920795156036 / AIR FILTER	750KVA CUMMINS D/G	1 / EACH/NUMBER	QSK 23G CUMMINS UK		CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC. BOX 3005.COLUMBUS. INDIANA.U.S.A	QSK 23G CUMMINS UK		<u>TECHNICAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND.CUMMINS INC.BOX 3005.COLUMBUS. INDIANA.U.S.A</u> <u>GENERAL SPECIFICATION - OEM;CUMMINS LTD.49-51 GRESHAM ROAD MIDDLESEX TW18 2BD ENGLAND. CUMMINS INC.BOX 3005. COLUMBUS.INDIANA.U.S.A</u>	
2	DNM63001	4309460	5330016657611 / LOWER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE CM 2250					<u>TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u> <u>GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u>	
3	DNM63002	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.COMDMARINE.COM)	CUMMINS		<u>TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7</u> <u>GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7</u>	
4	DNM63132	4893693	3120015028264 / BEARING, CONNECTING	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE	CUMMINS		<u>TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ROD					(WWW.COMDMARINE.COM)			QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
5	DNM56996	4893693	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/N UMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.COMDMARINE.COM)	CUMMIN S		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
6	DNM59392	FF900300	291071517001 3 / FUEL FILTER	DIESEL ENGINE CUMMINS (GRP CREEK CRAFT)	6 / EACH/N UMBER	QSB.9- 305 MCD		OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201- 6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS. COM.	NIL		TECHNICAL SPECIFICATION - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM. GENERAL SPECIFICATION - OEM: M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377- 3920 FAX: 812-377-1715 EMA: STEVE.A.HEWITT@CUMMINS. COM.	
7	SNM62495	3408607/2 897691	281501569932 1 / SWITCH, PRESSURE	CUMMINS DG NT855-G6 USA	1 / EACH/N UMBER	NT-855- G6	2539008	CUMMINS USA CUMMINS ENGINE COMPANY INC BOX 3005 COLUMBUS INDIANA USA 17202	CUMMIN S USA		TECHNICAL SPECIFICATION - PRESSURE SWITCHGENERAL SPECIFICATION - PRESSURE SWITCH	
8	DNM48366	3538221/4 955657	299071519575 0 / KIT, TURBO CHARGER	CUMMINS DIESEL GENERATOR QSL9G3 UK	1 / EACH/N UMBER	QSL9G3	21957845	M/S CUMMINSUK	CUMMIN S UK		TECHNICAL SPECIFICATION - TURBO CHARGER CUMMINS DG QSL9G3GENERAL SPECIFICATION - TURBO CHARGER CUMMINS DG QSL9G3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
9	DNM56369	3048808/5473042	2815014903404 / KIT ENGINE PISTON	CUMMINS DG NT855-G6 UK	6 / EACH/NUMBER	NT855-G6	11518	CUMMINS ENGINE COMPANY LTD-46-50 COOMBE ROAD NEW MAIDEN, SURREY KT3, 4QL, ENGLAND	UK		<u>TECHNICAL SPECIFICATION - 256 KVA Diesel Generator</u> <u>GENERAL SPECIFICATION - 256 KVA Diesel Generator</u>	
10	DNM62471	5317052	2930715194444 / KIT, RAW WATER PUMP-MINO	CUMMINS MAIN ENGINE QSB7DM UK	1 / EACH/NUMBER	QSB7DM	22068610	NEWAGE ENG GMB.H ROTENBROCKENWEG 14-D-22113 HAMBURG U. K	CUMMINS		<u>TECHNICAL SPECIFICATION - SPARE FOR S/W PP OEM: USA Model: QAB7DM</u> <u>GENERAL SPECIFICATION - SPARE FOR S/W PP OEM: USA Model: QAB7DM</u>	
11	DNM56175	0327-1617-01	5998715224447 / CARD , CONTROL	50 KVA CUMMINS DG S3.8-G6	1 / EACH/NUMBER	78740893 /CONTROL PANEL (A040S953)PC1.1 ELECTRONIC GOVERNOR	HUY831347	CUMMINS POWER GENERATION LIMITED 1400 73RD AVE NE MINNEAPOLIS MN 55432 COUNTRY USA	CUMMINS		<u>TECHNICAL SPECIFICATION - PARENT EQUIPMENT: CUMMINS DG 220 KVA HIGHER ASSY: Engine Accessories</u> <u>GENERAL SPECIFICATION - PARENT EQUIPMENT: CUMMINS DG 220 KVA HIGHER ASSY: Engine Accessories</u>	
12	DNM60856	3918612	4720014108803 / HOSE PLAIN	CUMMINS STANDBY EMERGENCY GENERATOR 4BT3-9D UK	1 / EACH/NUMBER	4BT3-9D		CUMMINS CUSTOMER ASSISTANCE CENTER 1-800-DIESELS(1-800-343-7357)USA	CUMMINS		<u>TECHNICAL SPECIFICATION - ITEM REQUIRED FOR STOCK</u> <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR STOCK</u>	
13	DNZ46074	4956289	4710785217310 / INJECTOR FUEL SUPPLY TUBE	Cummins QSK38 DM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins		<u>TECHNICAL SPECIFICATION - N/A</u> <u>GENERAL SPECIFICATION - N/A</u>	
14	DNM45905	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	12 / EACH/NUMBER			CUMMINS USA	CUMMINS		<u>TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7</u> <u>GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7</u>	
15	DNM63002	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA	CUMMINS		<u>TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MODEL: QSB6.7GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
16	DNM63132	4893693	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA		CUMMINS	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
17	DNM56996	4893693	312001502826 4 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA		CUMMINS	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7GENERAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRTY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
18	DNM48705	3970911	6685015301220 / TRANSMITTER, TEMPERATURE /SENSOR WATER	MARINE ENGINE CUMMINS(UT BOAT)	5 / EACH/NUMBER	QSB5.9-225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND		M/S MECHANICAL & ELECTRICAL (UK) LTD	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
19	SNM51565	131026	1309790230683 / O.RING 131026		70 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
20	DNM55655	3069103/4026171	5330013384829 / GASKET FUEL PUMP	CUMMINS DIESEL ENGINE	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(3048341)								AVAILABLE	
21	DGP64653		7490705041308 / PLAIN PAPER COPIER STANDARIZED MEDIUM DUTY	OFFICE MACHINE	1 / EACH/NUMBER	CPM 25					TECHNICAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). COMPANY NAME: TOSHIBA e STUDIO GENERAL SPECIFICATION - TOSHIBA DIGITAL PHOTO-COPIER MODEL: e-Studio 2523A----- (25 Copies Per Minute, Built-in GDI Printer, Color Scanner, Electronic Sorting, 250 Sheets x1 Drawer, 100 Sheets Stack Feed By- Pass, 256 MB Memory, Copy Size A3, Multiple Copying 1-999 & Zoom 25%-400%). COMPANY NAME: TOSHIBA e STUDIO	
22	DNM60379	5562157/5562517	2930715235012 / after cooler		1 / EACH/NUMBER	qsb6.7					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
23	DNM62319	0402-0968-04	2895715267522 / ISOLATOR, VIBRATION		4 / EACH/NUMBER	C22 D5					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
24	DNM63000	4309459	2815016629279 / UPPER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
25	DNM56412	0300-6314-01	6110795248383 / Display, Control		1 / EACH/NUMBER	C330D5B					TECHNICAL SPECIFICATION - ELECTRICALGENERAL SPECIFICATION - ELECTRICAL	
26	DNM45905	4893693	3120015028264 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	12 / EACH/NUMBER		22066008	CUMMINS MER CRUISER DIESEL WEBSITE (WWW.COMDMARINE.COM)	CUMMINS		TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7GENERAL SPECIFICATION - BEARING,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CONNECTING ROD FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB6.7	
27	DGT62609	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	121 / CUBIC FOOT	NIL	NIL	LOCAL MARKET		LOCAL MARKET	<u>TECHNICAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18% <u>GENERAL SPECIFICATION</u> - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%	
28	DPC63537	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	25 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.		ORIGINAL COLOR CHIPS,A DIVISION	<u>TECHNICAL SPECIFICATION</u> - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS. <u>GENERAL SPECIFICATION</u> - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.	
29	DNF64296	NIKON 850 DSLR	635076522555 5 / NIKON 850 DSLR CAMERA ALONG WITH LENS 24-120 MM	STILL CAMERA	1 / EACH/NUMBER	NIKON 850 DSLR	NA	NIKON JAPAN		NIKON	<u>TECHNICAL SPECIFICATION</u> - HARD COPY IS ATTACHED <u>GENERAL SPECIFICATION</u> - HARD COPY IS ATTACHED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
30	DNF63592	AC-5000	7520735156923 / RFID MACHINE (OUTDOOR IP65 FINGERPRINT TERMINAL)	SECURITY EQUIPMENT	3 / EACH/NUMBER	AC-5000		Union Community Co.Ltd 3F, Hyundai Topic bldg., 44-3, Bangi-dong, Songpa-gu, Seoul, 138-050, Korea Tel) +82-2-6488-3000 Fax) +82-2-6488-3099 WEB:www.virditech.com	VIRDI KOREA		<u>TECHNICAL SPECIFICATION - IP-65 STANDARD, 2.8" TFT COLOR SCREEN, MEMORY CAPACITY FOR 20,000USERS / 61,000LOGS, 32MB FLASH RAM, 304X344 PIXEL (FINGER PRINT SENSOR)</u> <u>GENERAL SPECIFICATION - IP-65 STANDARD, 2.8" TFT COLOR SCREEN, MEMORY CAPACITY FOR 20,000USERS / 61,000LOGS, 32MB FLASH RAM, 304X344 PIXEL (FINGER PRINT SENSOR)</u>	
31	SNM43682	3588305/22171036	2920332067808 / BELT TENSIONER (COMPRESSOR)	COMPRESSOR	2 / EACH/NUMBER			AB VALVO PENTA DE 40508 GOTHENBURG SWEDEN	VALVO PENTA		<u>TECHNICAL SPECIFICATION - make & OEM: volvo penta</u> <u>GENERAL SPECIFICATION - make & OEM: volvo penta</u>	
32	SNM64033	6V1197	5331011802417 / SEAL O RING	MAIN ENGINE	2 / EACH/NUMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPILLAR		<u>TECHNICAL SPECIFICATION - CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189</u> <u>GENERAL SPECIFICATION - CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189</u>	
33	DNF64508	P-0143000-A /YT-100B	5660785172597 / COMPOSITE MATERIALS E-FENCE ROD S.S POLE SQUARE TUBE ANGLED TYPE , BLACK POWDER COATED & HOT DIP GALVANISED WITH ACCESSORIE	PSS	70 / EACH/NUMBER	YT-100B E-Fence Controller		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		<u>TECHNICAL SPECIFICATION - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S.								<p>LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICP/8885791 DT. 05-6-24 <u>GENERAL SPECIFICATION</u> - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICP/8885791 DT. 05-6-24</p>	
34	DNM58404	7C-9008	593014563534 1 / THERMOSTAT (JACKET WATER HEATER)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
35	SNM53854	243-4300	302071522864 6 / PULLEY-ALTERNATOR	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<p><u>TECHNICAL SPECIFICATION - OVERALL WIDTH (IN): 3.4 OVERALL HEIGHT (IN): 0.8 OVERALL LENGTH (IN): 3.4</u> <u>GENERAL SPECIFICATION - OVERALL WIDTH (IN): 3.4 OVERALL HEIGHT (IN): 0.8 OVERALL LENGTH (IN): 3.4</u></p>	
36	DNC63096	ELEC-0366	651079517445 9 / PLASTIC CABLE TIES	H/CRAFT	230 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		<u>TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK GENERAL SPECIFICATION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											-_LENGTH: 24 INCHES COLOUR: BLACK	
37	DNF64521	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-16P-4KS2	676078520784 6 / 16 CHANNEL PRO NETWORK VIDEO RECORDER	CCTV System NVR5216-4KS2 CHINA	1 / EACH/NUMBER	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-16P-4KS2	NA	NO.1199 bin'an road , binjiang district hangzhou , china, 310053 tel: +86-571-87688883		MS NETWORK	<u>TECHNICAL SPECIFICATION -</u> Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording <u>GENERAL SPECIFICATION -</u> Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
38	DGE44283	QA263527	402099083318 4 / ROPE FIBROUS 8 STRAND, DIA 48MM,	-	440 / METER	NO DATA AVAILABLE		UK		MARLOW ROPE LTD SOUTH ROAD HAILSHAM EAST SUSSEX UNITED KINGDOM	<u>TECHNICAL SPECIFICATION -</u> 1. BERTHING HAWSER BLK CONT FILAMENT POLYSTER & SS POLYPROPYLENE 2. MIN BREAKING LOAD:36.5 TONNES 3. SUPPLIED IN 220 MTR COIL 4. PART NO QA263527 <u>GENERAL SPECIFICATION -</u> 1. BERTHING HAWSER BLK CONT FILAMENT POLYSTER & SS POLYPROPYLENE 2. MIN BREAKING LOAD:36.5 TONNES 3. SUPPLIED IN 220 MTR COIL 4. PART NO QA263527	
39	DNF57274	121468/5P X300 01RTNG2/MLM-203/DH2024	613072517106 1 / UPS 3 KVA	N/A	3 / EACH/NUMBER	MLM-203/DH2024		GERMANY		GERMANY	<u>TECHNICAL SPECIFICATION -</u> MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT <u>GENERAL SPECIFICATION -</u> MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											220/230/240 VOLT PLUS MINUS 10 PERCENT	
40	DGT62831	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	4000 / FOOT	NO DATA AVAILAB LE		PK		TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI	TECHNICAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required GENERAL SPECIFICATION - A. DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
41	DNF64378	WPS5-12	6140785223035 / LONG BATTERY 12 VOLT 5AH	10 KVA UPS WPS5-12	14 / EACH/N UMBER	WB5-12	APC	kung long batteries industrial co, ltd tel no +886-49-2254-777 FAX +886-19-2255-139 EMAIL SALES@MAIL.KIB.COM.TW	CHINA		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
42	DNF64519	WPS5-12	6140785223035 / LONG BATTERY 12 VOLT 5AH	10 KVA UPS WPS5-12	128 / EACH/N UMBER	WB5-12	APC	kung long batteries industrial co, ltd tel no +886-49-2254-777 FAX +886-19-2255-139 EMAIL SALES@MAIL.KIB.COM.TW	CHINA		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
43	DGP64313	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/M404DN	COMPUTER	5 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port BothGENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
44	DGP64658	4003DN	7435705138632 / PRINTER HP LASER JET	COMPUTER	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN								Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
45	DGP587 31	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN	COMPUTER	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
46	SNF6385 1	HFV2421 R	671078521479 0 / NETWOR CAMERA 4MP, WDR IR BULLET WITH BASE	CCTV SYSTEM	2 / UNIT	HFV2421 R	NIL	NO 119 BIN'AN ROAD BINJIANG DISTRICT HANGZHOU CHINA 310053 TEL: +88-571- 87688883		M/S DAHUA	<u>TECHNICAL SPECIFICATION -</u> Image Sensor 1/3? 4Megapixel progressive CMOS Effective Pixels 2688(H) x1520(V) RAM/ROM 256M/16M Scanning System Progressive Minimum Illumination 0.1 Lux/F1.4(Color), 0Lux/F1.4(IR on) S/N Ratio More than 50dB IR Distance Distance up to 60m(197ft) IR On/Off Control Auto/ Manual IR LEDs 4 <u>GENERAL SPECIFICATION</u> -Image Sensor 1/3? 4Megapixel progressive CMOS Effective Pixels 2688(H) x1520(V) RAM/ROM 256M/16M Scanning System Progressive Minimum Illumination 0.1 Lux/F1.4(Color), 0Lux/F1.4(IR on) S/N Ratio More than 50dB IR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Distance Distance up to 60m(197ft) IR On/Off Control Auto/ Manual IR LEDs 4	
47	DNM563 57	456-4858	281579522954 8 / PUMP GP FUEL INJECTION	33KVA CATER PILLER DG DEO33EO UK	1 / EACH/N UMBER	DEO33E O	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millenuim Springvale Business Park Belfast BT	CATTERP ILLER U. K		<u>TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33E0 GENERATOT SET</u> <u>GENERAL SPECIFICATION - PART MANUAL C3.3 DE33E0 GENERATOT SET</u>	
48	DNF6437 6	SURT 6000 XLI/ELEN AS 6KVA	613070514291 8 / UPS 6KVA	OFFICE MACHINERY EQUIP	1 / EACH/N UMBER	EP-H 01		PK	M/S MANSOO R & SONS (PVT) LTD, MEZZANI NE FLOOR, PLOT NO. 11-C, STREET NO.28 , TAUHEE D COMMER CIAL AREA, PHASE V, DHA KARACHI 75500 TEL: 92- 21- 35862134 ,3583525 5 FAX:92- 21- 35861671 ,3583518 5 E.MAIL: SHANZ		<u>TECHNICAL SPECIFICATION - BAKcup TIME ONE AND HALF TO TWO HOURS. GENERAL SPECIFICATION - BAKcup TIME ONE AND HALF TO TWO HOURS.</u>	
49	SNM640 36	10000- 60390/709 2312c2	512079519309 8 / OIL FILTER	DG 300 KVA	4 / EACH/N UMBER	P330H-1	FGWNAV 04EJSW0 0202	FG WILSON U.K	FG WILSON		<u>TECHNICAL SPECIFICATION - oem : perkins</u> <u>GENERAL SPECIFICATION -_oem : perkins</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
50	DNJ63253	64D-11631-22-90	2815765212444 / PISTON (STD)	150 AET OBM ENGINE	1 / EACH/NUMBER	150AET 07 (6G 47) 1024899	1024899 6G47	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
51	DNF64271	MF60038 / 6-GFM-65	6130785173194 / 12V 100AH-65 A/H BATTERY	D/G DEUTZ 42KVA	4 / EACH/NUMBER	MF60038 HANKOOK KOREA		FENFANG BATTERIES CO LTD CHINA	M/S SAIL		<u>TECHNICAL SPECIFICATION - FENFANG BATTERIES CO LTD CHINA H=174 mm W=166 mm L=350 mm</u> <u>GENERAL SPECIFICATION - FENFANG BATTERIES CO LTD CHINA H=174 mm W=166 mm L=350 mm</u>	
52	DGP64314	HP4000/cl 11h	7025715133409 / BIO METRIC TIME AND ATTANDANCE MACHINE HP-4000	TIME AND ATTANDANCE MACHINE	1 / EACH/NUMBER	HP4000/CL11H		US		RSI(IR) USA	<u>TECHNICAL SPECIFICATION - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name & Time of Thumb impression</u> <u>GENERAL SPECIFICATION - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name & Time of Thumb impression</u>	
53	SNF63852	05-00-0096-00	6350715194459 / USB	Luggage Scanning	1 / EACH/NUMBER	XIS-100X	ASTVC18 0LL740	ASTROPHYSICS INC CTR UNITED STATES TEL	Astrophysics		<u>TECHNICAL SPECIFICATION - Security Equipment</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SECURITY KEY	Machine size (40)	UMBER			9095985488 FAX 9095985546	Manufactured		6350016155690GENERAL SPECIFICATION - Security Equipment 6350016155690	
54	DGP56889	50AU7000/46EH5000	7730705174391 / SAMSUNG LED TV 46/49 INCH	LED TV	2 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG	DELIVERY REQUIRED AT LAHOR	TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH GENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH	
55	DNM50875	467-1181	2940715223109 / FILTER ELEMENT-FUEL	ALLIED CAT50KVA ARGT-5011504 MODEL-16 DG USA	10 / EACH/NUMBER	ARGT-5011504 MODEL-16	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE GENERAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE	
56	DPC64188	HEN002004	8010795208200 / BOSTIK THINNERS / CLEANER M501	RHIB BOAT	30 / LITER	BOSTIK M501	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX, TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHAW INFLATABLES LTD		TECHNICAL SPECIFICATION - M501 IS USED TO CLEAN, DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA. GENERAL SPECIFICATION - M501 IS USED TO CLEAN,DEGREASE AND PREPARE SURFACES FOR ADHESION WITH BOSTIK 2402ADHESIVE.THINNING BOSTIK NE486,CLEANING GLUE BRUSHES.SUPPLIED IN 5 LTR SAELED CAN WITH A SCREW TOP.HIGHLY FLAMMABLE PRODUCT AND MUST BE STORED B/W 5 AND 25 DEG C IN DRY FLAMEPROOF AREA.	
57	DPC64189	HEN002002	6510795208197 / BOSTIK 2402 ADHESIVE + HARDENER	RHIB BOAT	20 / LITER	BOSTIK2402		HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX, TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.	HENSHAW INFLATABLES LTD		TECHNICAL SPECIFICATION - BOSTIK 2402 CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								uk, www.henshaw.co.uk			METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA. <u>GENERAL SPECIFICATION - BOSTIK 2402</u> CREATES A STRONG BOND WHICH IS RESISTANT TO HEAT -40 DEG C -90 DEG C,UV, SALTWATER AND HUMIDITY COVERAGE IS APPROX 4 SQUARE METER PER LITRE(VARIES WITH SURFACE).SUPPLIED AS 1 L TIN OF ADHESIVE AND A 40 ML BOTTLE OF BOSTIKURE D HARDENER.STORE B/W 5 DEG AND 25 DEG IN A DRY FLAMPROOF AREA.	
58	DNF64380	LQ-2190	7025735150505 / EPSON LQ-2190 DOT MATRIX PRINTER	EPSON	2 / EACH/NUMBER	EPSON		EPSON	EPSON		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
59	SNM64035	4587259	2950755207635 / FUEL FILTER	PERKIN Engine 1506A-E88TAG3 ITALY	10 / EACH/NUMBER	1506A-E88TAG3	LGDF1012	Elcos srl - S.S. 234 Km 58,25 Grumello Cremonese (CR) Italy tel. +39 0372 72330 fax. +39 0372 7233220 - info@elcos.net - www.elcos.net	ELCOS Generating Set ITALY		<u>TECHNICAL SPECIFICATION - Fuel Filter Perkins Engine Model No 1506A-E88TAG3</u> <u>GENERAL SPECIFICATION - Fuel Filter Perkins Engine Model No 1506A-E88TAG3</u>	
60	DNF63099	3BA00751AA	5998735182749 / IP MEDIA GATEWAYS WITH ACCESSORIES	ACTIVE	1 / EACH/NUMBER			M/s AL FUTTAIM TECHNOLOGIES LLC P.O. BOX UAE TEL+97147063111, 800238324 E MAIL aftech@alfuttaim.ae	ALCATEL LUCENT		<u>TECHNICAL SPECIFICATION - The vendor must ensure 100% admin, operational and technical integration with existing Network comprising of Alcatel 4400 release 9.x.x. The proposed system must integrate with existing switches and transmission. The Gateways installed should be of hybrid type. GENERAL SPECIFICATION - The vendor must ensure 100% admin, operational and technical integration with existing Network comprising of Alcatel 4400 release 9.x.x. The proposed system</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											must integrate with existing switches and transmission. The Gateways installed should be of hybrid type.	
61	DNM63149	104086A	6810715177915 / SILICON WHITE 315ML - 14412	DIESEL GENERATOR	1 / CARTON	NA	NA	PLOT NO 09 SECTOR 24 KORANGI INDUSTRIAL AREA KARACHI	ORIENT PRIVATE COMPANY LIMITED		<u>TECHNICAL SPECIFICATION - NK</u> <u>GENERAL SPECIFICATION - NK</u>	
62	DNJ64503	17400-98J01	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
63	DNH63112	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABLE TOILET		<u>TECHNICAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2'x2' False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FALSAL or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhaust Fan 8" (GFC or Royal) N. Electrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2'x2' False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FALSAL or	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure	
64	DNJ64576	09202-06031	5315765222116 / PIN (6X12)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
65	DNJ51928	09202-06031	5315765222116 / PIN (6X12)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
66	SNJ45678	09408-00105	4730765221654 / CLAMP	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
67	SNM56808	3583122	5315270363869 / LOCKING SPRING (FUEL SYSTEM)	(FUEL SYSTEM)	14 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 405 08 GOTHENBURG SWEDEN	VALVO PENTA SWEDEN		<u>TECHNICAL SPECIFICATION - oem & make: volvo penta</u> <u>GENERAL SPECIFICATION - oem & make: volvo penta</u>	
68	DNM56296	435-6493	4330715224677 / FUEL FILTER	Caterpillar DG DE200E0usa	20 / EACH/NUMBER	CAT C 7.1	CAT00C71LECW03124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	Caterpillar USA		<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR DG</u> <u>GENERAL SPECIFICATION - OEM: CATERPILLAR DG</u>	
69	DNF63590	ZKTECO SCR-100	7025735207035 / RFID Card Reader	UFFAQ	4 / EACH/NUMBER	SRC-100 / Pro ID 30		ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129 Tel: 86-755-8960 2345/46/47/48 E-mail: sales@zkteco.com	M/S: Zkteco		<u>TECHNICAL SPECIFICATION - As Attached</u> <u>GENERAL SPECIFICATION - As Attached</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								www.zkteco.com				
70	SNM64038	5F-9144	5331005913112 / O-RING	CATERPILLAR DG 275 KVA C-9	10 / EACH/NUMBER	C-9	CAT000C9LLX900927	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, UNITED STATES TELE NO 3095782353 FAX NO 3095783739 WWW.CAT.COM	ALLIED CAT		<u>TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9</u> <u>GENERAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9</u>	
71	DGP64315	NIL	7435705137719 / PRINTER COLOUR LASER JET 2605DN/ HP 3525.	COMPUTER	1 / EACH/NUMBER	JET2605DN/HP3525.		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
72	SNM51800	2339812KZ1001-43	2940121864488 / AIR FILTER	11.5 KW D/G PSU	5 / EACH/NUMBER		4081633	M/S POLY TECHNOLOGIES BEIGING CHINA	M/S POLY TECHNOLOGIES BEIGING CHINA	oem/authorized dealer coc required.	<u>TECHNICAL SPECIFICATION - M/S POLY TECHNOLOGIES BEIGING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI.</u> <u>GENERAL SPECIFICATION - M/S POLY TECHNOLOGIES BEIGING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI.</u>	
73	SNM64034	10000-79400	2815795208385 / Oil Pump	ENGINE	1 / EACH/NUMBER	N/A	1106A-70TA	F G WILSON ENGG LTD (UK)	F G WILSON ENGG LTD (UK)		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
74	DNC64291	8M6002465	2910MB0020427 / INJECTOR ASSEMBLY FUEL	PETROL MAIN ENGINE	6 / EACH/NUMBER	VERADO 350 HP	2B614987, 2B612137, 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u> null	
75	SNF63739	800 G3 TOWER PC	7020705215930 / HP ELITEDECK CORE I7	IT SELF	1 / EACH/NUMBER	800 G3 CORE i7	SGH717S BTV	HP HQ-TRE 71025 BOEBLINGEN GERMANY	HEWLETT PACKARD (HP)		<u>TECHNICAL SPECIFICATION - WINDOWS:10 PRO VERSION :</u> 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT <u>OPERATING SYSTEM</u> <u>GENERAL SPECIFICATION - WINDOWS:10</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PRO VERSION : 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM	
76	DNH644 29	NIL, LOCAL	732070516360 7 / ELECTRIC ROTI PLANT 1000 CHAPATI /HRS	ROTI PLANT	1 / EACH/N UMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA.		M/S SHARIF ENGINEE RING WORKS BAZAR KHARAD AN GUJRAN	<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
77	DGB626 53		028370000160 8 / INGOT- BRASS		1510 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg <u>GENERAL SPECIFICATION -</u> Specification: BSEN 1982 OF 1999, GRADE ENCC761S Compositional Designation: CuZn16Si4-C Weight of Ingot Range from Min 10 kg to Max 20 kg	
78	DGE641 50	319- SIVLER- DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		481 / EACH/N UMBER	319- SILVER- DE					<u>TECHNICAL SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN BO7RP9X98J 6. ITEM WEIGHT: Grams 7.PRODUCT DIMENSION: L- 200mm, W-25mm, T- 8mm, Brush Dimension: L- 78mm x W-22mm x 15mm 8. MODEL: Wooden handled Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement <u>GENERAL</u> <u>SPECIFICATION - 1.</u> ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BO7RP9X98J 6. ITEM WEIGHT: Grams 7.PRODUCT DIMENSION: L-200mm, W-25mm, T- 8mm, Brush Dimension: L- 78mm x W-22mm x 15mm 8. MODEL: Wooden handled Brass/ Steel Wire Brush- 6 Inches/ Can be customized as per user requirement	
79	DGE64305		0462502201803 / TUBING PLASTIC POLYETHLENE LAY FLAT WD.48	DC/FF	710 / KILOGRAMME						TECHNICAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317 GENERAL SPECIFICATION - 0.0002" for single ply. T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317	
80	SPC63741		0473504730040 / ZINC PHOSPHIDE (RAT POISON)		2 / KILOGRAMME						TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET) GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
81	DGE58480	NO DATA AVAILABE	0461590006480 / PAINT ROLLER 7 INCH,C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	300 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip GENERAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip	
82	SPC6374	WHO/SIF/	044250220120	KEROCANE	100 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	0	13.R5	1 / Lambda Cyhalothrin 2.5 or 25% EC. 01LTR PLASTIC PACKING WITH REGISTERED LABEL.	OIL.	LITER						Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label. <u>GENERAL SPECIFICATION -</u> Insecticide Lacquer Diazinon (Lambda Cyhalothrin 25 % EC) SPECIFICATION: Active Ingredients (A.I) (Lambda Cyhalothrin 25 % EC) WW: PACKING: - 01Ltr plastic packing with registered label.	
83	DPC641 90		044250442006 9 / RUST REMOVING OIL RUSTOLENE (PACKING 4 LTR TIN)		268 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
84	DGB124 52	ADSPEC-1076D	028359571121 4 / ROD ALUMINIUM BRONZE DIA 3.5" .WGT PER FT 31.980 LB , LENGTH:6 TO 10 FT.		0.6 / METER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
85	DPC574 61		044250001059 8 / PAINT FINISHING HEAT RESISTING, ALUMINIUM TEMP 535C/650C (04 LTR TIN) flash point 23C	TEMP 535-650 C	100 / LITER						<u>TECHNICAL SPECIFICATION - NS/P/001 OF 2013(REVISED EXCEPT FLASH POINT) Flash point 23C Type: silicon Resin Principal component: aluminum pigment/paste 50%(min) leafing,\thinner: xylene or petroleum naptha 1. ns/p/001 of 2013 (revised) except flash point 2. stage inspection prescribed PACKING: 04 LTRS TIN GAUGE OF TIN 26 TO 28 SWG</u> <u>GENERAL SPECIFICATION - NS/P/001 OF 2013(REVISED EXCEPT FLASH POINT) Flash point 23C Type: silicon Resin Principal component: aluminum pigment/paste 50%(min) leafing,\thinner: xylene or petroleum naptha 1. ns/p/001 of 2013</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(revised) except flash point 2. stage inspection prescribed PACKING: 04 LTRS TIN GAUGE OF TIN 26 TO 28 SWG	
86	DGB581 26		026659000039 0 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		57 / PAIR					sample required with quote	<u>TECHNICAL SPECIFICATION</u> - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg <u>GENERAL SPECIFICATION</u> - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	
87	DGB545 84		026759923533 5 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		152 / EACH/N UMBER					lab test required	<u>TECHNICAL SPECIFICATION</u> - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE ½ INCH, <u>GENERAL SPECIFICATION</u> - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE ½ INCH,	
88	DGP644 41		005150000136 8 / FORM APPLICATION CADET ENTRY F(RG)-4		16200 / SHEET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
89	DGB545 81	BS 1740, UI278&026 7-10666	026759923509 4 / ELBOW ROUND BLACK 0.75IN		92 / EACH/N UMBER					mention all tech specs	<u>TECHNICAL SPECIFICATION</u> - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel grade: astm-106 grade <u>GENERAL SPECIFICATION</u> - inner dia: 0.750 inch outer dia: 1.065 inch schedule. 40 material: mild steel	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											grade: astm-106 grade b	
90	DGB63233		0283705711634 / BRAZING ALLOY, SILVER, STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1		4965 / GRAM						<p><u>TECHNICAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</p> <p><u>GENERAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</p>	
91	DGB61079	BRAND (MADE IN WEST GERMANY)	0243702431004 / AGRICULTURAL SPRAYER MODEL GLORIA (172 RTG) CAPACITY 10 LITER		3 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
92	SNM64027	NIL	1325705027550 / RUBBER-CHARGING-LINE-FOR-GAUGE-MANIFOLD-LG-3-FT-B/P-2500-PSI		20 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - a. Maker ATLANTIS (Taiwan) b Parent equipment refrigeration/ air conditioning systems. c. Specifications are as under: General Specs: Charging line is made of flexible rubber pipes which used for gauge manifold, gas charging set to gas charging in refrigeration/ air conditioning systems in three colours. Yellow Red and Blue. Technical specs: (i) Internal dia 0.250" inch, length 36" inches both ends fitted with manually operate able flair nuts. (ii) Working pressure 600 PSI, bursting pressure 3000 PSI. (iii) Picture of the item is also enclosed for incorporation in RWIMS database.</p> <p><u>GENERAL SPECIFICATION</u> - a. Maker ATLANTIS (Taiwan) b Parent equipment refrigeration/ air conditioning systems. c.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Specifications are as under: General Specs: Charging line is made of flexible rubber pipes which used for gauge manifold, gas charging set to gas charging in refrigeration/ air conditioning systems in three colours. Yellow Red and Blue. Technical specs: (i) Internal dia 0.250" inch, length 36" inches both ends fitted with manually operate able flair nuts. (ii) Working pressure 600 PSI, bursting pressure 3000 PSI. (iii) Picture of the item is also enclosed for incorporation in RWIMS database.	
93	DPC64191		0474502242463 / SOAP SCRUBBING		1224 / KILOGRAMME						TECHNICAL SPECIFICATION - available in local market OF ANY BRAND UPDATED VIDE PNS AATISH LETTER 460/516 DATED 07 MAR 14 GENERAL SPECIFICATION - available in local market OF ANY BRAND UPDATED VIDE PNS AATISH LETTER 460/516 DATED 07 MAR 14	
94	DGE58386		0474504740127 / QANAT COMPLETE SiZe. 18.00X7.00 FT		14 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Size : Height 7' Length 18' b. Cloth/Material : Jersey two side heavy c. Front side : Golden with design d. Back side : Simple in different colours e. Also included : bamboo/sticks ropes ACCESSORIES f. Multicolor (i.e, Yellow, Red & Green) is hereby proposed for design of front and back side g. colour of design of front and back side of Qanat is Olive Green. GENERAL SPECIFICATION - a. Size : Height 7' Length 18' b. Cloth/Material : Jersey two side heavy c. Front side : Golden with design d. Back side : Simple in different colours e. Also included : bamboo/sticks ropes ACCESSORIES f. Multicolor (i.e, Yellow, Red & Green) is hereby proposed for design of front and back side g. colour of design of front and back side of	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Qanat is Olive Green.	
95	DNF64039	BS EN 60317-8	056179525358 0 / WIRE, WINDING COPPER ELECT COND DIA 1.320 O/DIA 1.423 MM (CLASS- 180) GRADE-2	WIRE FOR WINDING	40 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - DIA</u> : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS- 4665 PART-1 BSEN60317-8 <u>GRADE-2GENERAL</u> <u>SPECIFICATION - DIA : 1.320MM</u> O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
96	DNF64215	BS EN 60317-8	056179439325 2 / WIRE, WINDING COPPER ELECT COND DIA1.400MM O/A DIA 1.506 MM (CLASS- 180) GRADE 2	MOTOR WINDING	20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM <u>GENERAL SPECIFICATION -</u> purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM	
97	DNF62092	BS EN 60317-8	056179525360 9 / WIRE, WINDING COPPER ELECT COND DIA : 0.900MM O/ DIA : 1.017 MM (CLASS- 175 -180c) Grade-3	MOTOR WINDING	17.5 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-3 <u>GENERAL</u> <u>SPECIFICATION - DEFSTAN 61-12</u> ISSUE-2 OF 2008(PART-14) BS- 4665 PART-1 BSEN60317-8 GRADE-3	
98	SNM51589	A-051	303099923465 7 / BELT VEE A-051	GENERAL USE	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
99	DNM64496	5N9359 (3040-01- 203-0160)	304071503513 0 / SHAFT, SHOULDERED OA-LG168MM- COLLAR- DIA34.8MM SPLINED ENDED	INDUSTRIEL MARINE CATTER PILLER D/G	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Collar-Dia34.8mm Shaft 168 mm Spline Ended <u>GENERAL</u> <u>SPECIFICATION - Collar-Dia34.8mm</u> Shaft 168 mm Spline Ended	
100	DNA633	HMS 0-08	281573508919	MACHINERY	23 /						<u>TECHNICAL SPECIFICATION - NO</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	40		8 / FERRULE SIZE 1/2"	ON TYPE-21 & MCMVS	EACH/N UMBER						DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
101	DNJ45838	63313190C	281576502288 6 / MAIN METAL (ITEM NO 1300-5)		1 / SET					part no 6331390a required	TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
102	SNM64028	901-115	291079511305 7 / OIL FILTER	FG KEY DG PERKIN 1306-E87T 215	20 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DNF63442	MD231 (CROWN) /EH1504 /EH1418	444079510254 4 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIERS	3 / EACH/N UMBER	MD231 (CROWN) /EH1504/ EH1418					TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
104	SNM4138	OE52601	433099967830 4 / FUEL FILTER	SGA120283, PERKIN D/G 600KVA,UK	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	SNM17389	OE52601	433099967830 4 / FUEL FILTER	SGA120283, PERKIN D/G 600KVA,UK	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DNQ63436	ew6	451070508463 6 / ew6 EYE WASH bottle	FOR FIRE FIGHTING EQUIPMENT	4 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGE50755	NIL	402099923712 1 / ROPE NYLON, HAWSERLAID, 3-STRD, CIR	NGTH 1.330 TONS UNIT OF AVAILABILITY	780 / FATHOM						TECHNICAL SPECIFICATION - SPECS: BS: 4928/74 PART-2 TABLE1, BS: EN-696 ISO: 1140 OF 2004 120 FAHTAM PER COIL REQUIRED. GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			1.00", DIA 0.3125"								SPECIFICATION - SPECS: BS: 4928/74 PART-2 TABLE1, BS: EN-696 ISO: 1140 OF 2004 120 FAHTAM PER COIL REQUIRED.	
108	DGE527 95	NIL	402099923713 3 / ROPE NYLON, CIRCUMFERE NCE: 5 INCH, DIA: 40MM, Z-LAY, 3- STRAND,		460 / METER						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. 6. SPECS: BS4928 <u>GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. 6. SPECS: BS4928</u>	
109	SNM516 79	7N2048	312001297887 9 / BEARING SLEEVE CAMSHAFT	3516, CATERPILLAR D/G USA (JNB)	30 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
110	DNH644 99	NO DATA AVAILABL E	413070504652 9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	4 / EACH/N UMBER	GREE/PE L, MITSBUS HI/ DAKEN/ GENERA L, GENERA L, LG,					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
111	DGP643		361070500719		74 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	00		7 / POSITIVE PLATE SIZE 510 x 400 x 0.15 mm		EACH/N UMBER						Spec: Positive Plate(aluminium coated sheet) is pre- sentized plate that used in offset printing and it is pretreated with a light-sensitive coating. Required Size: 510 x 400 x 0.15 mm <u>GENERAL SPECIFICATION</u> - Spec: Positive Plate(aluminium coated sheet) is pre- sentized plate that used in offset printing and it is pretreated with a light-sensitive coating. Required Size: 510 x 400 x 0.15 mm	
112	DNH644 98		411073500724 0 / DEEP FREEZER 13CUFT 220AC 50/60HZ		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
113	DGP643 12	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION</u> - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											staples, paper clips, credit cards and CDs.	
114	DGP644 18	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
115	DGP642 57	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CDs. <u>GENERAL SPECIFICATION - TECHNICAL</u> SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
116	DGP644 72	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL</u> SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION - TECHNICAL</u> SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
117	DGP644	G2102560	361070509130		4 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	11	EU	4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		EACH/NUMBER						<p>TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p> <p><u>GENERAL SPECIFICATION - TECHNICAL</u> SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p>	
118	DNH64298		411070505150 4 / REFRIGERATOR 15-CUFT DOUBLE DOOR 220V AC 50 HZ	USER PNS M/PUR	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
119	DNM59694	214-925	494079506194 9 / SWIVEL STEEL LG-72MM O/D-26/20 T.P.I-18	AIR POWERED PORTABLE AIRLESS HYDRA SPRAY	3 / EACH/NUMBER	GRACO					<p><u>TECHNICAL SPECIFICATION - MAKE/MODEL: GRACO</u> <u>GENERAL SPECIFICATION - MAKE/MODEL: GRACO</u></p>	
120	DNA58120	R4SP-40	472073508916 0 / FLEXIBLE HOSE PIPE I/D 38.1 MM O/D	MACHINERY ON TYPE-21 & MCMVS	4.5 / FOOT						<p><u>TECHNICAL SPECIFICATION - DIAMETER INNER 40 MM DIAMETER OUTER 49 MM THICKNESS 01 MM RADIUS 34</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			57.1 MM 4500 PSI								ROLL LENGTH 30 MTR <u>GENERAL SPECIFICATION - DIAMETER</u> INNER 40 MM DIAMETER OUTER 49 MM THICKNESS 01 MM RADIUS 34 ROLL LENGTH 30 MTR	
121	DNG63601	NO DATA AVAILAB LE	473000189261 4 / UNION STEEL		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MATERIAL STEEL 250PSI WOG</u> NOM SIZE=6MM(1/4 INCHES) LENGTH MIN=39.37MM(1.555 INCHES) NPT=1/4-18 DASH NO: 22TA COUNTRY: USA <u>GENERAL SPECIFICATION - MATERIAL STEEL 250PSI WOG</u> NOM SIZE=6MM(1/4 INCHES) LENGTH MIN=39.37MM(1.555 INCHES) NPT=1/4-18 DASH NO:22TA COUNTRY: USA	
122	SGB56148	NO DATA AVAILAB LE	473070503853 3 / ELBOW BAND PIPE 90 DEGREE WITHOUT THREADS (WELDING PURPOSE) (IDxOD: 2X2.37 INCH)	FOR SHIP COUNSTRUCT ION PROJECTS	180 / EACH/N UMBER					lab test	<u>TECHNICAL SPECIFICATION - EN 10025-2-S275JR+AR(PIPE)*3,</u> MATERIAL GRADE: S-275JR SIZE: Inner Dia 2 INCH (50.8mm), Outer Dia 2.37 INCH (60.2mm) INTERNAL DIA: 2 INCH OUTER DIA: 2.370 INCH SCHEDULE 40 MATERIAL: MILD STEEL GRADE: ASTM-106 GRADE: B <u>GENERAL SPECIFICATION - EN 10025-2-S275JR+AR(PIPE)*3,</u> MATERIAL GRADE: S-275JR SIZE: Inner Dia 2 INCH (50.8mm), Outer Dia 2.37 INCH (60.2mm) INTERNAL DIA: 2 INCH OUTER DIA: 2.370 INCH SCHEDULE 40 MATERIAL: MILD STEEL GRADE: ASTM-106 GRADE: B	
123	SNM51579	2J0157	533000958822 4 / O RING (PAKING PREFORMED)	VALVE RED SPCL .25IPS 200PSI 5T 9	40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
124	DNZ62193	101CD-30	533078502988 9 / MECHANICAL SEAL SEA WATER PROVISION	S.W FOR PROVISION REFRIGERTIO N NASR	1 / SET						<u>TECHNICAL SPECIFICATION - Seal</u> Bore : 30mm Seal Dia : 52mm Stationary Dia with O Ring : 50 mm Stationary Dia without O Ring : 40 mm Total length : 65 mm Stock sample available at	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			REFRIGERTION AY-02								workshopGENERAL SPECIFICATION - Seal Bore : 30mm Seal Dia : 52mm Stationary Dia with O Ring : 50 mm Stationary Dia without O Ring : 40 mm Total length : 65 mm Stock sample available at workshop	
125	DNM63774	193736	5330795048904 / SEAL INJECTOR	MARINE DIESEL ENGINE	122 / EACH/NUMBER	MCM-160-HM					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
126	DNF61503	WP7-12 -LONG/LX7-12/ PR 12-70	6140CH5088427 / BATTERY 12VOLT 7AH LEAD ACID SEALED.	1 KVA UPS NS-1000	8 / EACH/NUMBER	WP7-12 -LONG				length 15cm height 9.5 cm width 6.5	TECHNICAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG. GENERAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG.	
127	DNF64377	PP3 , 6F22, (6135-00-900-2139)	6135701004118 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
128	DNF63217	RM12-7.2 /30882010 FE/LP12-5.0/WPS5-12	6140795089298 / BATTERY 12VDC 5AH LEAD ACID FOR UPS	SONAR TRAINERS UPS	64 / EACH/NUMBER	MLM-320C/GES203H					TECHNICAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE.10X9.8X10CM,MODEL.RM12-7.2, GENERAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE.10X9.8X10CM,MODEL.RM12-7.2,	
129	DNF64428	HI-PE MULTI-ZONE / PD6500	6350715095514 / WALKTHROUGH GATE METAL DETECTOR C/W ACCESOROES	SECURITY DETECTION (OEM CEIA ITALY)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
130	SNF58303	040349-00	6230999427885 / TORCH COMPLETE	FIRE & REPAIR PARTY	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WITH BULB	LOCKERS.							AVAILABLE	
131	DNF58599	SOGO / PHILIPS	6230765059400 / LIGHT EMERGENCY WITH TWO HEAD RECHARGEABLE I/P110/220V-O/P6V		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
132	DNZ59353	DH5-1	6220781004986 / MAST LIGHT FITTING RED GLASS DH5-1 105/M	LIGHTING SYSTEM TURKEY	29 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
133	DGP64442		7530705054601 / FORM F (CP)-37 ATTENDANCE CARD (NEW)	STATIONARY	70405 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - SIZE: LENGTH: 8.5 INCH WIDTH: 3.5 INCH WEIGHT: 240 GSM ± 5% CARD COLOUR: WHITE PRINTING INK: BLUE INK ON FRONT SIDE AND RED INK ON BACK SIDE PACKING: 1000 CARD IN EACH BOX</u> <u>GENERAL SPECIFICATION - SIZE: LENGTH: 8.5 INCH WIDTH: 3.5 INCH WEIGHT: 240 GSM ± 5% CARD COLOUR: WHITE PRINTING INK: BLUE INK ON FRONT SIDE AND RED INK ON BACK SIDE PACKING: 1000 CARD IN EACH BOX</u>	
134	DGE64147	NO DATA AVAILABLE	0340500000010 / CANVAS COVER WATER PROOF		5 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand)</u> <u>GENERAL SPECIFICATION - Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand)	
135	DNF64524	PHILIPS/CR/PERFECT/C	7910PK5085419 / ELECTRO SPRAY CONTRACT CLEANER (200ML)	PCB CLEAN MATERIAL	15 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGP61641		7540PK5070879 / IT48 I/TAX RETURN)9.5 X12"		5000 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
137	DGP64444		0051500000738 / FORM F (PA)1 CASH BOOK.		206 / BOOK					as per stock sample	TECHNICAL SPECIFICATION - SIZE: LENGTH: 16 INCH WIDTH: 11.75 INCH WEIGHT: 65 GSM ± 5% PAPER COLOUR: WHITE PRINTING INK: BLACK PAINTING: 100 PAGES OF BOOK, PRINTED ON BOTH SIDES. PACKING: 100 BOOKS PER COTTON GENERAL SPECIFICATION - SIZE: LENGTH: 16 INCH WIDTH: 11.75 INCH WEIGHT: 65 GSM ± 5% PAPER COLOUR: WHITE PRINTING INK: BLACK PAINTING: 100 PAGES OF BOOK, PRINTED ON BOTH SIDES. PACKING: 100 BOOKS PER COTTON	
138	DGE12235	NO DATA AVAILAB LE	0421500000008 / PERSONAL LOCKER CUM STEEL ALMIRAH		14 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type : handle lock APRENT EQUIPMENT: ACCOMODATION SPACEGENERAL SPECIFICATION -_SIZES: hieght: 6 FEET, 2 INCH width: 3 FEET ,11 INCH depth: 1 FEET, 8 INCH gauge of almira: 22 coating: silver colour lock type :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											handle lock APRENT EQUIPMENT: ACCOMODATION SPACE	
139	DGP644 35		00515000098 9 / FORM F (SV)29 GANGWAY CHECK REPORT BOOK		1626 / BOOK					as per stock sample	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
140	DGE626 52	NIL	834071510429 4 / INFRARED CAMOUFLAGE NET	CAMOUFLAGE THE VEHICAL INSTALLATION	6 / EACH/NUMBER	OPTICAL INFRARED CAMOUFLAGE NET, ANTI RADAR CAMOUFLAGE					<u>TECHNICAL SPECIFICATION - Type : Net Material: Plastic Waterproof : Yes Folded: Yes Colour: Woodland Size: Standardized size 6.8m x 6.8m and it can be tailored according to the requirement of enduser Transport Package: Inside PVC Bag or OPP Bag Outside Carton * fabric: 420D polyster plain weave weight: 200 grams/sqn color: printed wooden pattern: jungle camoplage with ir function ir value: 0.88,0.89,0.89 size: 6.8 x6.8 meters packing: packed in polythine/parachute bag and cotton bag</u> <u>GENERAL SPECIFICATION - Type : Net Material: Plastic Waterproof : Yes Folded: Yes Colour: Woodland Size: Standardized size 6.8m x 6.8m and it can be tailored according to the requirement of enduser Transport Package: Inside PVC Bag or OPP Bag Outside Carton * fabric: 420D polyster plain weave weight: 200 grams/sqn color: printed wooden pattern: jungle camoplage with ir function ir value: 0.88,0.89,0.89 size: 6.8 x6.8 meters packing: packed in polythine/parachute bag and cotton bag</u>	
141	DGP644 46		005150000107 0 / FORM F (NL)10 SHORT LEAVE BOOK		1320 / BOOK					as per stock sample	<u>TECHNICAL SPECIFICATION - Size: 8" cm x 11.5" cm Page Color: White GSM: 60+5% Ink: Black BOOK OF 100 PAGES</u> <u>GENERAL SPECIFICATION - Size: 8" cm x</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											11.5" cm Page Color: White GSM: 60+5% Ink: Black BOOK OF 100 PAGES	
142	DGT63256	NO DATA AVAILAB LE	010050000008 8 / Ply wood GD-I, 9 ply,	X 19.05 MM)	800 / SQ FEET	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM (±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993 BS 314-1: 2004 and BS EN 314-2: 1993 BS 1203: 1979 BS 4072: 1999 BS 6566-6: 1985 BS EN 323: 1993 moisture: 6-14% end user: PND 107 w/shop</p> <p><u>GENERAL SPECIFICATION - 1.</u> Both face and back veneers of Gurjan Wood. 2. Core, and inner plies of poplar 3. size: LengTh= 8', Width=4' & THickness= 19MM(±2MM) 4. ACCEPTANCE CRITERIA: Plywood, GD-I, 9-Ply, Both face and back veneers of Gurjan-wood, and core and inner plies of poplar. Thickness of Face, Back veneer 0.6mm. 5. TESTING CRITERIA: MOISTURE content Bonding Quality Glue Preservation Physical Evaluation Density. 6. SPECIFICATIONS/STANDARDS BS EN 322: 1993 BS 314-1: 2004 and BS EN 314-2: 1993 BS 1203: 1979 BS 4072: 1999 BS 6566-6: 1985 BS EN 323: 1993 moisture: 6-14% end user: PND 107 w/shop</p>	
143	DGP61253	TOSHIBA E-STUDIO	361070511825 6 / PLAIN		1 / EACH/N	"E- STUDIO-				Delivery required at	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		282	PAPER COPIER HEAVY DUTY (PHOTO STATE MACHINE) F-8		UMBER	2528A (25 CPM)"				islamabad	SPECIFICATION - NO DATA AVAILABLE	
144	DGE64184	NO DATA AVAILAB LE	047650000006 1 / GLOVES LEATHER FOR WELDING, treated with presservative, standard quality		204 / PAIR	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1.</u> DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL detials: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex <u>GENERAL SPECIFICATION - 1.</u> DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL detials: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex	
145	DGP644 47	NO DATA AVAILABL E	00515000062 6 / FORM F (NS)10 RECORD OF STOCK TAKING STOR		125 / EACH/N UMBER	NO DATA AVAILAB LE				as per stock sample	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
146	DGP644 36		005150000108 2 / FORM F (NL)22 LEAVE TICKET		1720 / BOOK					as per stock sample	<u>TECHNICAL SPECIFICATION - LENGTH 8" WIDTH 7" 60 GSM ± 5% White Color Paper printed With Black Ink 100 Pages (Book)</u> <u>GENERAL SPECIFICATION - LENGTH 8" WIDTH 7" 60 GSM ± 5% White Color Paper printed With Black Ink 100 Pages (Book)</u>	
147	DPC641 87	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	280 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	
148	DGD642 65	NO DATA AVAILABL E	732070501242 6 / MACHINE ATTA KNEADING100		1 / EACH/N UMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TO120KG CAPACITY 440V 50HZ 3PHS 5AMP								Grade) <u>GENERAL SPECIFICATION</u> - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)	
149	DGD64266	NO DATA AVAILAB LE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market <u>GENERAL SPECIFICATION</u> - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market	
150	DGE64181		0413546003650 / PVC PIPE DIA 1.50"		500 / METER						<u>TECHNICAL SPECIFICATION</u> - Size: DIA 1.50" <u>GENERAL SPECIFICATION</u> - Size: DIA 1.50"	
151	DGP64443	NO DATA AVAILAB LE	0050500000097 / PAPER DUPLICATING		425 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
152	DGP64445	NO DATA AVAILAB LE	0051500000521 / NAVALCENTR ALSURGERYT REATMENTCARD(MD)66		50000 / SHEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
153	DNM58900		4110765128322 / ENGEL REFRIGERAT OR FRONT DOOR (12V-24VDC) SEE COMD 8		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - capacity 25/35l 12v-24v dc <u>GENERAL SPECIFICATION</u> - capacity 25/35l 12v-24v dc	
154	DNM64211	0501207226	5930725128441 / PRESSURE SWITCH (24	MTU MAIN ENGINE	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			VDC) (F8)								AVAILABLE	
155	DGP644 13	MZ- 77Q8T0B/ AM	702573529300 9 / Samsung 870 QVO SATA III 2.5" SSD - 8TB hard drive		2 / EACH/ NUMBER	MZ- 77Q8T0B/ AM					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
156	DNQ586 15	GOMTEX Ø 303100038 00	473070526970 9 / hose assy rubber duraline/ gometex lg 100 ft id 1-1/2"		11 / EACH/ NUMBER	HOSE ASSY RUBBER DURALIN E/ GOMETE X LG 100 FT ID 1- 1/2"					<u>TECHNICAL SPECIFICATION -</u> specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance. <u>GENERAL</u> <u>SPECIFICATION -</u> specially formulated rubber, i extruded through a circular woven. low pressure drop thanks to its smooth inner wall, high thermal resistance.	
157	DNF6355 4	P33700	599879527962 8 / pcb- card/PCB-SCIP AND CAGE WEIGH		1 / EACH/ NUMBER	na					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
158	DNZ5890 7	E-03-05	281578527760 1 / THREE- STAGE LOWER LINER		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
159	DNF6438 4	5404220	599879528189 9 / panel control		1 / EACH/ NUMBER	cummins command control system					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
160	DNZ5890 9	E-03-10	281578527759 8 / THREE- STAGE PISTON SLEEVE		1 / EACH/ NUMBER	MCH18- Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
161	SNM538 47	390-7344	534071526913 7 / GAUGE - OIL		2 / EACH/ NUMBER	DE110E2					<u>TECHNICAL SPECIFICATION -</u> GAUGE - OIL <u>GENERAL</u> <u>SPECIFICATION -</u> GAUGE - OIL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
162	DNJ64292	15440-96J01	2940765265106 / FILTER FUEL PUMP		1 / EACH/NUMBER	F150FET X					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
163	DSM54062	SRMN 500 /AAGD 5M	9320705284422 / BUOYANCY TUBE POLYETHYLENE FOAM FILLED FOR 5 M ZODIAC		1 / EACH/NUMBER	R-12					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
164	DPC51762	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
165	DPC51956	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
166	DNF63005	410049	5905735268691 / SET OF NVD ADAPTER		1 / EACH/NUMBER	MS380PN2A					<u>TECHNICAL SPECIFICATION - SET OF NVD ADAPTER</u> <u>GENERAL SPECIFICATION - SET OF NVD ADAPTER</u>	
167	DSB50160	C93-435-3 /D8M125V4	5920142187078 / CART FUS RAPIDE4A HA22 (SUPERSCDED5929142187078RAZA-FSP (JNB)		408 / EACH/NUMBER	NO DATA AVAILAB LE				sample required	<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
168	DNF63007	410048	5905735268692 / SET OF NVD COLLIMATOR ADAPTERS		1 / EACH/NUMBER	MS380PN2A					<u>TECHNICAL SPECIFICATION - SET OF NVD COLLIMATOR ADAPTERS</u> <u>GENERAL SPECIFICATION - SET OF NVD COLLIMATOR ADAPTERS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			AND APPARTURE									
169	DNQ58617	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		3 / HUNDR ED FT	HOSE ASSY RUBBER DURALIN E /GOMETE X LG 100 FT ID 2"					<p><u>TECHNICAL SPECIFICATION -</u> SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa</p> <p><u>GENERAL SPECIFICATION -</u> SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa</p>	
170	DGP64308	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> _CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
171	DGP64381	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> _CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
172	DGP64260	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
											<u>GENERAL SPECIFICATION</u> -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p>	
173	DGP64331	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
174	DGP644 17	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<p><u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u> _CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
175	DNJ64293	17411-96J01	433076526511 1 / CASE WATER PUMP		1 / EACH/NUMBER	F150FET X					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
176	DNF64297	ub500	635078524635 9 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA model no: ub500		1 / EACH/NUMBER	ub500					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
177	DNH59051	vc 60 ms	733078527067 9 / vegetable cutting machine		2 / EACH/NUMBER	vc 60 ms					<u>TECHNICAL SPECIFICATION - a. Make/Brand : iMettos</u> <u>GENERAL SPECIFICATION - a. Make/Brand : iMettos</u>	
178	DNF63775	253-PVM	594599317822 2 / RELAY UNDER VOLTAGE 253-PVM		2 / EACH/NUMBER	253 PVM					<u>TECHNICAL SPECIFICATION - Used in ssdd 128 kw in control system for protection of under voltage</u> <u>SPECIFICATION OF UNDER VOLTAGE RELAY NORMAL VOLTAGE100V – 440V AC SYSTEM FREQUENCY 45/65HZ TRIP LEVEL ADJUSTMENT UNDER VOLTAGE 75 TO 100% OVER VOLTAGE 100 TO 125% OF NORMAL INPUT VOLTAGE TIME DELAY FACTORY PRE SET UP TO 30 SECONDS</u> <u>GENERAL SPECIFICATION - Used in ssdd 128 kw in control system for protection of under voltage</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION OF UNDER VOLTAGE RELAY NORMAL VOLTAGE100V – 440V AC SYSTEM FREQUENCY 45/65HZ TRIP LEVEL ADJUSTMENT UNDER VOLTAGE 75 TO 100% OVER VOLTAGE 100 TO 125% OF NORMAL INPUT VOLTAGE TIME DELAY FACTORY PRE SET UP TO 30 SECONDS	
179	DNZ63593	HUBA CONTROL type 520	6685775300693 / pressure transmitter		1 / EACH/NUMBER	huba					TECHNICAL SPECIFICATION - HP SAEFTY OF MAIN AC PLANT GENERAL SPECIFICATION - HP SAEFTY OF MAIN AC PLANT	
180	DNZ58908	E-03-07	2815785277597 / THREE-STAGE UPPER CYLINDER LINER		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compress or.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
181	DSB38413	local MAT166-0462	4730745246380 / SUCTION HOSE FLEXIBLE PIPE		2 / EACH/NUMBER	2020					TECHNICAL SPECIFICATION - origin: make pakistan m/s star engineering GENERAL SPECIFICATION - origin: make pakistan m/s star engineering	
182	DNJ64294	17400-96J021/17400-96J04	4330765265121 / WATER PUMP REPAIR KIT		1 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION COUNTRY OF ORIGIN : JAPAN	
183	DNZ58919	E-03-17	2990785277595 / THREE-STAGE EXHAUST VALVE(L-03-15D)		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compress or.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
184	DSB63517		6140TY6720800 / AUTO EMERGENCY LANTERN		59 / EACH/NUMBER	VR7FL NI-CD(1.2V-AH)					TECHNICAL SPECIFICATION - make: saft model: vr7fl ni-cd(1.2v-ah) brand: ref-no 790636 oem/coo: france GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CELL 1.2 V, 8 - 12 AMPS								make: saft model: vr7fl ni-cd(1.2v-ah) brand: ref-no 790636 oem/coo: france	
185	DNF63560	LD004	6230785289113 / CSM Life raft - Lithium cell & Canopy light		10 / NO	LD004					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
186	DNF64433	PE-LAP-SS (10 PAIRS)	5995705248823 / SELF SUPPORTING ARIEL TELEPHONE CABLE SIZE 10 PAIRS 0.5 MM		100 / METER	10/0.5 MM SSAU					<u>TECHNICAL SPECIFICATION - COMPANY NAME: PREMIER CABLES (PVT) LIMITED ADDRESS: 43-E, BLOCK-6, P.E.C.H.S, RAZI ROAD, SHAHRAH-E-FAISAL, KARACHI, PAKISTAN CONTACT NO: 02134397771</u> <u>GENERAL SPECIFICATION - COMPANY NAME: PREMIER CABLES (PVT) LIMITED ADDRESS: 43-E, BLOCK-6, P.E.C.H.S, RAZI ROAD, SHAHRAH-E-FAISAL, KARACHI, PAKISTAN CONTACT NO: 02134397771</u>	
187	DPK64152	Polysulphide GG	8030705287063 / SIKA Polysulphide GG sealant (2.5 LITERS COMP. A / 4.0 LITERS COMP.B)		100 / LITER	POLYSULPHIDE GG					<u>TECHNICAL SPECIFICATION - DENSITY -1.58 KG,/L SOLID CONTENT 100%</u> <u>GENERAL SPECIFICATION - DENSITY -1.58 KG,/L SOLID CONTENT 100%</u>	
188	DGP64414	MZ-77e4T0B/AM	7025735293010 / Samsung 870 eVO SATA III 2.5" SSD - 4TB hard drive		4 / EACH/NUMBER	MZ-77E4T0B/AM					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
189	DGB52491	8004	5340705246809 / perforated ss ladder steps fitted onboard f22ps 12-swg gR.304		75 / EACH/NUMBER	na					<u>TECHNICAL SPECIFICATION - S No Measurement Value Remarks a. Length: 600mm - b. Width : 180mm - c. Depth(lengthwise) 40mm With slight bend towards inner side d. Depth (Widthwise) 30mm With slight bend towards inner side e. Thickness 2mm - f. Distance between TWO HOLES FOR BOLTS: 120MM (AT WIDTH SIDE) size: Step with L= 180mm, W= 600mm Step with L=</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											180mm, W= 500mm <u>GENERAL SPECIFICATION - S No</u> Measurement Value Remarks a. Length: 600mm - b. Width : 180mm - c. Depth(lengthwise) 40mm With slight bend towards inner side d. Depth (Widthwise) 30mm With slight bend towards inner side e. Thickness 2mm - f. Distance between TWO HOLES FOR BOLTS: 120MM (AT WIDTH SIDE) size: Step with L= 180mm, W= 600mm Step with L= 180mm, W= 500mm	
190	SNF61521	HAKKO 937	3439TY672033 2 / SOLDERING STATION (HAKKO 937)		3 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - OEM, HAKKO CORPORATION JAPAN LOCAL BS ENTERPRISE R-28 MEZZANINE FLOOR KARACHIGENERAL SPECIFICATION - OEM, HAKKO CORPORATION JAPAN LOCAL BS ENTERPRISE R-28 MEZZANINE FLOOR KARACHI</u>	
191	DNM56260	5563450	289579527969 5 / control throttle		1 / EACH/NUMBER	cummins command control system					<u>TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null</u>	
192	DNF63004	410008	530573526869 6 / NVD MOUNTING PLATE WITH SCREWS		1 / EACH/NUMBER	MS380PN 2A					<u>TECHNICAL SPECIFICATION - NVD MOUNTING PLATE WITH SCREWSGENERAL SPECIFICATION - NVD MOUNTING PLATE WITH SCREWS</u>	
193	DNF63006	410005	599973526869 5 / NVD STAND		1 / EACH/NUMBER	MS380PN 2A					<u>TECHNICAL SPECIFICATION - NVD STANDGENERAL SPECIFICATION - NVD STAND</u>	
194	DNZ64318	bv650i-msx	6150ZO524879 3 / apc ups 650 va		13 / EACH/NUMBER	apc ups 650 va bv650i-msx					<u>TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null</u>	
195	DSB53861	VS9103G150	7021FT103050 9 / Client Boxed Computing Unit		4 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION - 0GENERAL SPECIFICATION - 0</u>	
196	SRP64310	FC-577 (SOFT 99)	6850ZO651119 9 / VINYL CLEANER FOAM SPRAY,		100 / BOTTLE	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY. VINYL.CARPETS PART NO FC-577</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			400ML								(WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT: 400ML/22 OZ/623 GMS <u>GENERAL SPECIFICATION - ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY.VINYL.CARPETS PART NO FC-577 (WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT:400ML/22 OZ/623 GMS</u>	
197	DNV57631	MBS3100-060G3917	6685725264180 / PRESSURE SENSOR		1 / EACH/NUMBER	0659.064.536				sample required	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
198	DNM63948	329-3796	2910016272835 / TUBE ASSEMBLY OIL JET		6 / EACH/NUMBER	C7-1502-117					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
199	SNM64037	10000-93306	5330715289161 / LOWER ENGINE GASKET		1 / EACH/NUMBER	P/E 1106A-70TAG					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	