

TENDER BULLETIN

DATE & TIME 6/25/24 10:19 AM INVITATION TO TENDER TO BE OPENED ON 7/10/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGT63254	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	6000 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
2	DGT63198	NIL	7230705132910 / BAMBOOS OF 35 to 45 FEETS, diameter: 4"-6"	-	10000 / FOOT	NO DATA AVAILAB LE		PK	TAWAKA L BANS STORE PLOT NO 26 TIMBER POND KEAMARI ROAD KARACHI		<u>TECHNICAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment : required <u>GENERAL SPECIFICATION - A.</u> DIAMETER AT TOP : 2 TO 3 INCHES B. DIAMETER AT BOTTOM : 4 TO 6 INCHES WALL THICKNESS: 10MM -12MM length: 35 to 45 feet termite treatment :required	
3	DNM43715	26560143/159-6102	2910014714630 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1	NA	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS 14009 OLD GALENA RD TC-A USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								TEL 3095782353			MAINTENANCE AND UPKEEP OF DG SYSTEM	
4	DNM39716	26560143/159-6102	2910014714630 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1	NA	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS 14009 OLD GALENA RD TC-A USA TEL 3095782353	CATERPILLAR USA		TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEMGENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
5	DNM58359	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		TECHNICAL SPECIFICATION - MAKE: CATERPILLARGENERAL SPECIFICATION - MAKE: CATERPILLAR	
6	SNM59319	462-1171	2940015633054 / FILTER, FLUID	DG CAT 7.1 USA	10 / EACH/NUMBER	CAT 7.1	CAT00C715GTY00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
7	SNM48989	123-2367	2910015894952 / FILTER ELEMENT -AIR (PRIMARY)	65 KVA DG DE65E3 UK	4 / EACH/NUMBER	DE65E3	E3G04139 (Eng)	CATERPILLAR SARL C/O EAME POWER SYSTEM BUILDING2 1MILLENNIUM SPRINGVALE BUSINESS PARK BELFAST BT-12 7AL, NORTHERN IRELAND UK.	CATERPILLAR SARL UK		TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR USAGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR USA	
8	DNA56628	31040	5330705164333 / KIT SEAL (INCLUDES 97,106,112,127,155,156,158,159)	SEA WATER PUMP	1 / EACH/NUMBER	CAT - 3531/3535		DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMABAD		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
9	SNM62498	380-1882	6625715228830 / SENSOR GP-PRESSURE (ENGINE OIL)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
10	DNM61637	380-1882	6625715228830 / SENSOR GP-PRESSURE (ENGINE OIL)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA				
11	DNM437 15	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION - ITEM IS</u> CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
12	DNM397 16	26560143/ 159-6102	291001471463 0 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR USA		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM <u>GENERAL</u> <u>SPECIFICATION - ITEM IS</u> CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM	
13	SNM473 17	423-8521	291071522305 9 / FILTER G P- WATER SEP AND FUEL	caterpillar C-13 USA	2 / EACH/N UMBER	NA	NA	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLlinois 61552	CATTER PILLER		<u>TECHNICAL SPECIFICATION -</u> OEM: CATERPILLAR <u>GENERAL</u> <u>SPECIFICATION - OEM:</u> CATERPILLAR	
14	SNM457 67	1R-1804	291099417715 7 / FILTER- ELEMENT- WTR SEP & FUEL	80 KVA DG CAT USA	12 / EACH/N UMBER	DE88EO	ZRE0132 3	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPI LAR USA		<u>TECHNICAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24 CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH <u>GENERAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH	
15	DNM63748	467-1181	2940715223109 / FILTER ELEMENT-FUEL	ALLIED CAT50KVA ARG T-5011504 MODEL-16 DG USA	1 / EACH/NUMBER	ARGT-5011504 MODEL-16	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR, 50 KVA ALLIED CAT DG 400 VOLT 50HZ 3PHASE</u>	
16	DNM43715	26560143/159-6102	2910014714630 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	1 / UNIT	CAT 7.1		ALLIED ENGINEERING AND SERVICES PVT LTD 21/3 SECTOR NO 22 KORANGI INDUSTRIAL AREA KARACHI	ALLIED ENGINEERING AND SERVICES PVT LTD		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u>	
17	DNM39716	26560143/159-6102	2910014714630 / FUEL ELEMENT FLUID	150 KVA DG CAT 7.1 USA	6 / UNIT	CAT 7.1		ALLIED ENGINEERING AND SERVICES PVT LTD 21/3 SECTOR NO 22 KORANGI INDUSTRIAL AREA KARACHI	ALLIED ENGINEERING AND SERVICES PVT LTD		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE AND UPKEEP OF DG SYSTEM</u>	
18	SNM56800	441-5111	4330715224679 / WATER SEPARATOR ELEMENT	CATERPILLAR GENSET DE200E0 USA	15 / EACH/NUMBER	CAT C7.1	CAT00C71LECW03124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728653	CATERPILLAR, USA		<u>TECHNICAL SPECIFICATION - Make: USA Model: CAT C7.1 Brand: CATERPILLAR Filtration Element</u> <u>GENERAL SPECIFICATION -_Make: USA Model: CAT C7.1 Brand: CATERPILLAR Filtration Element</u>	
19	DNM58080	4936969/5446701	2990715193442 / MANIFOLD, EXHAUST	UT BOAT ENGINE QSB5.9-225BHP	4 / EACH/NUMBER	QSB5.9-225 BHP		CUMMINS MER CRUISER DIESEL WEBSITE (www.cmdmarie.com)	CUMMINS	NEWSPAPER	<u>TECHNICAL SPECIFICATION - MANIFOLD, EXHAUST</u> <u>GENERAL SPECIFICATION - MANIFOLD, EXHAUST</u>	
20	DNF61145	DCC/HFBM/EL/007	5960705214363 / LOW NOISE AMPLIFIER (LNA)	SM RACK 100C2ZL PAK	7 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DCC	oem/coc certificate required	<u>TECHNICAL SPECIFICATION - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Q <u>GENERAL SPECIFICATION</u> - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Q	
21	DNM58359	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
22	DGE55542		0421599425637 / FILING CABINET SIZE, 4-DRAWERS W/LOCK combination AND COMPRESSOR PLATES GREY GUAGE SWG:22 SIZE; W18 INCH		4 / EACH/NUMBER					LAB TEST/MTC OF MATERIAL REQUIRED	<u>TECHNICAL SPECIFICATION - GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114</u> REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user <u>GENERAL SPECIFICATION - GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114</u> REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	
23	DGB54034		0276709105937 / SHOVEL HAND ROUND		10 / EACH/NUMBER					oem/coc authorized certificate	<u>TECHNICAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"							required	excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg. <u>GENERAL SPECIFICATION</u> - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg.	
24	DGB63342		0283705711634 / BRAZING ALLOY, SILVER, STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1		3900 / GRAM					NEWS PAPER	<u>TECHNICAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2% <u>GENERAL SPECIFICATION</u> - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%	
25	SNM45587	7W2327	2940795077526 / FILTER OIL	CATER PILLAR D/G ENGINE	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR	
26	DNM50877	7W2327	2940795077526 / FILTER OIL	CATER PILLAR D/G ENGINE	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR	
27	DNM27494	8S1606	5330004378752 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA-9MM TH-03MM	3304PC, CATERPILLAR D/GEN.USA	1 / EACH/NUMBER	3304 SSDG				LOCAL SOURCE: RK AUTOS TIBBET CENTER M. A JINNAH ROAD KARACHI	<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
28	DNM55656	7N8025/4N8087	5330012668826 / SEAL WATER NEW PART NO. 4N8087	CATER PILLAR D/G	36 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR	
29	DGB48678		0278546003470 /		1 / EACH/NUMBER	INCGO / TOTAL				MAKE / MODEL /	<u>TECHNICAL SPECIFICATION</u> - Forward / Reverse Drill Heavy duty	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PENUMATIC DRILL MACHINE S 1" R.P.M-530		UMBER					COUNTRY : UK/ GERMANY/ CHINA CONSIDER ONLY INCGO OR TOTAL & MANUFAC TURER	90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V <u>GENERAL SPECIFICATION - Forward / Reverse Drill Heavy duty</u> 90 PSI Max rotation speed: 500-700 RPM Ampere: 10-20 Amps Volts: 220V	
30	DNM61324	3801882	6620715271047 / SENSOR		1 / EACH/NUMBER	DE165E0					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
31	DNZ58912	E-02-02	2990785277636 / SECONDARY PISTON		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compress or.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
32	DCW63145		8430500100960 / BOOT ANTI SKID BLACK SIZE-13		75 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-13</u> <u>GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-13</u>	
33	DPC63424	POLP9460035MC2PK	6830705241433 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
34	DSB62151	CMY300705 / MAT-662-0076-C	6125TY6720781 / AEI AGOSTA VARIATOR-DT COMPLETE UNIT (HYDRAULIC PUMP)		2 / EACH/NUMBER	CMY300					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
35	SNM51820	c-7988	2940795245980 / sakura filter		4 / EACH/NUMBER	ft404					<u>TECHNICAL SPECIFICATION - STATUS :RELEASE PRODUCT MODEL :SPIN-ON FILTER TYPE :</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>OIL FILTER FILTER INFO :FULL FLOW H 1 (MM) :130 OD 1 (MM) :93 THREAD SIZE :M24X2-6H CONTAIN (PCS) :12 VOLUME (M) : 0.022 GASKET TYPE :SQUARE REMARK :FOTON FT404, FT504, TAISHAN TS554</p> <p><u>TRACTORS</u>GENERAL SPECIFICATION - STATUS : RELEASE PRODUCT MODEL : SPIN-ON FILTER TYPE :OIL FILTER FILTER INFO :FULL FLOW H 1 (MM) :130 OD 1 (MM) :93 THREAD SIZE :M24X2-6H CONTAIN (PCS) : 12 VOLUME (M) :0.022 GASKET TYPE :SQUARE REMARK :FOTON FT404, FT504, TAISHAN TS554 TRACTORS</p>	
36	DNZ58917	E-02-11	4810785277587 / SECONDARY EXHAUST VALVE		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<p><u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u></p>	
37	DCW63144		8430500100531 / BOOT ANTISKID BLACK SIZE 12		75 / PAIR						<p><u>TECHNICAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12</u> <u>GENERAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12</u></p>	
38	SNF51959	lx3v-0806mt-a1	5998705246116 / 1xplc		2 / EACH/NUMBER	LX3V-0806MT-A1					<p><u>TECHNICAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA</u> <u>GENERAL SPECIFICATION - WECON TECHNOLOGY CO LTD CHINA</u></p>	
39	DCW63141		8430500100699 / BOOT ANTI SKID BLACK SIZE 9		75 / PAIR						<p><u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9</u> <u>GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9</u></p>	
40	DCW63143		8430500100533 / BOOT ANTI SKID BLACK SIZE 11		75 / PAIR						<p><u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11</u> <u>GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11</u></p>	
41	DCW631		843050010070		75 /						<p><u>TECHNICAL SPECIFICATION -</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	42		0 / BOOT ANTI SKID BLACK SIZE 10		PAIR						BOOT ANTI SKID BLACK SIZE 10 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 10	
42	DGE61148	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
43	DGE60760	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
44	DGE60611	large 94.2 ltrs 300 plus	811570525959 7 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (leNGTH 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
45	DSB62152	CMY300900 / MAT-662-0076-C	6125TY672078 2 / AEI AGOSTA VARIATOR-DM COMPLETE UNIT (REGULATING PUMP)		2 / EACH/NUMBER	CMY300					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DSB61331	DSE 10.4 /6 PB 4, DSE 4.2/4 PB10	663572516965 5 / PROBE FOR ULTRASONIC		12 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			THICKNESS GUAGE								7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56 <u>GENERAL SPECIFICATION - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No. 7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56</u>	
47	DRG61935	4720ZO655500	4720ZO6555500 / PIPE HIGH PRESSURE		1 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM. GENERAL SPECIFICATION - EACH PIPE LENGTH 25 FEET WITH FEMALE FITTING ON BOTH END TESTED ON 5000PSI PIPE OF HIGH TENSION MATERIAL RUBBER, USED FOR CHARGING NITROGEN IN A/C TYRES.OD:15.6 MM.</u>	
48	DGD63212	B-505	4430705269616 / MOBILE TANDOOR (ROUND)		1 / EACH/NUMBER	B-505					<u>TECHNICAL SPECIFICATION - M/S INNER DRUM: 3M, S/S OUTER BODY: 1.2MM, 32 NOZZLE BURNER, HEAVY DUTY CASTER WHEEL, ITALIAN VALVE ASSY, M/S BURNER PLATE-4MM, GLASSWOOL INSULATION, 30INCH DIA GENERAL SPECIFICATION - M/S INNER DRUM: 3M, S/S OUTER BODY: 1.2 MM, 32 NOZZLE BURNER, HEAVY DUTY CASTER WHEEL, ITALIAN VALVE ASSY, M/S BURNER PLATE-4MM, GLASSWOOL INSULATION, 30INCH DIA</u>	
49	SNF47944	BSEN60317-8	0561795253560 / WIRE WINDING copper ELECT ENAMEL cond	FOR WINDING	40 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION - Purity: 99.95 % Copper Class: Class-180 BSEN60317-B grade-2(class 180 degree).GENERAL SPECIFICATION - Purity: 99.95 %</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			dia0.250 O/A DIA 0.301 MM								Copper Class: Class-180 BSEN60317-B grade-2(class 180 degree).	
50	DGH559 49		056159521837 8 / CABLE ELECTRIC ELASTOMERIC, LFH,3CORE COND 32/ 0.20 mm 440V 17AMP	DEFSTAN 02- 526 T-4	345 / METER						<u>TECHNICAL SPECIFICATION - DEFSTAN 02-526 Table-(b-4)</u> Standard Dia:32/0.200 Cable required in 100 mtrs roll for Spec See Attached document <u>GENERAL SPECIFICATION - DEFSTAN 02-526 Table-(b-4)</u> Standard Dia:32/0.200 Cable required in 100 mtrs roll for Spec See Attached document	
51	DGE486 75	530300/T 41114/RC5 56000	422050508458 9 / KNIFE DIVER,S (SEAHWK/ AQUAL UNG KNIFE) WITH LEG CLASP BLADE LENGTH APPROXI. 180MM/ SEAHWK/ AQUAL UNG KNIFE		17 / EACH/ NUMBER	/Cressi orca, black					<u>TECHNICAL SPECIFICATION - BRAND: AQUA LUNG 7 3/4"</u> POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE : BLACK CONTOURED RUBBER HANDLE. <u>GENERAL SPECIFICATION - BRAND: AQUA LUNG 7 3/4"</u> POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE : BLACK CONTOURED RUBBER HANDLE.	
52	DNM618 01	1.524- 975.0/1. 524.972.0	432072510761 2 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	2 / EACH/ NUMBER	HD 8/18- 4 M* KAR					<u>TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</u> <u>GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
53	DNM48385	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR					<p><u>TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</u></p> <p><u>GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</u></p>	
54	DNM52931	1.524-975.0/1.524.972.0	4320725107612 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	1 / EACH/NUMBER	HD 8/18-4 M* KAR					<p><u>TECHNICAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control</u></p> <p><u>GENERAL SPECIFICATION - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate :</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-off, Servo control	
55	DNQ58474	54.107.00	4210995413550 / INLINE INDUCTOR, 2.5" BSPF COUPLING, 445MM LG, 160.5 MM DIA	FIRE AND REPAIR PARTY POST UPPER DECK FO	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8 <u>GENERAL SPECIFICATION -</u> Water Requirement: 230l/min at 5.5 bar Operating Pressure Range: 3 to 10.5 bar Material: Light Alloy/ Aluminum alloy Jet Length: 24m (Max) Inline Inductor 2.5" BSPF Coupling 445MM LG,160.5 MM Dia SIZE 63 MM FLOW CAPACITY: 225 LPM EXPANSION RATIO : 7-8	
56	DNM55648	5P1260/3718124	4720011033697 / HOSE 7.62 CM(3") (HOSE NON MATELIC)	3304PC, CATERPILLER D/GEN.USA	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
57	DNH64632	NO DATA AVAILABLE	4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	2 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
58	SNM61069	1619279800	4310144361277 / AIR FILTER	OM366LA, ATLAS AIR	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELEMENT (FL980240001, 1619-279)	COMP.CO, FRANCE	UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
59	DGP578 55		3610705045303 / POSITIVE PLATE ROLAND OFFSET size: 925X740X0.3MM(BRND FUJI)		200 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - SIZE: 925X740X0.3MM(BRND FUJI)</u> <u>GENERAL SPECIFICATION - SIZE: 925X740X0.3MM(BRND FUJI)</u>	
60	DGP505 43		3610705005698 / IVORY CARD GSM 200 + 5% PACKET OF 100 SHEETS B-02 500X707MM		100 / PACKE T						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	DGP577 70		3610705007237 / PAGE CORD TWIN COMPOSING		20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection</u> <u>GENERAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection</u>	
62	DGB448 72		3950505035336 / CHAIN BLOCK 10 TONS CAPACITY WITH 45 FEET	FOR GENERAL USE	2 / EACH/N UMBER	ZL00340					<u>TECHNICAL SPECIFICATION - HEAVY DUTY HAND CHAIN HOIST CHAIN DIAMETER: 10 MM HEADROOM: 29.52 IN HOOK OPENING WIDTH: 2.51 INCH LIFT LOAD EFFORT: 85.98 LBS LOAD</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DRIFT MAKE JAPAN								CAPACITY: 10 TONS STANDARD LIFT: 20 FT WEIGHT: 260 LBS TESTING ACCEPTANCE: 150 % OF LOAD CAPACITY <u>GENERAL SPECIFICATION - HEAVY DUTY HAND CHAIN HOIST CHAIN DIAMETER: 10 MM HEADROOM: 29.52 IN HOOK OPENING WIDTH: 2.51 INCH LIFT LOAD EFFORT: 85.98 LBS LOAD CAPACITY: 10 TONS STANDARD LIFT: 20 FT WEIGHT: 260 LBS TESTING ACCEPTANCE: 150 % OF LOAD CAPACITY</u>	
63	DNM57331	N4067	4820725042380 / VALVE-INTAKE-24-R-STEEL-28X34MM	R C CHAMBER PNS IQBAL	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 24-R-STEEL-28X34MM</u> <u>GENERAL SPECIFICATION - 24-R-STEEL-28X34MM</u>	
64	SNM52380	33415118	5340992019646 / WASHER	P40,WATER PUMP THERMOSTAT E PERKINS DG UK	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - weight: 5g dimensions 4x4x1cm</u> <u>GENERAL SPECIFICATION - weight: 5g dimensions 4x4x1cm</u>	
65	DNZ60333	501	5330785027789 / GLAND PACKING CARBONIZED FIBER (NSD/CSG-II/2/132 DT30-04-2002	M/E PISTON COOLING PUMP TOMG-125 NASR	2 / METER						<u>TECHNICAL SPECIFICATION - Material: Carbonized fibre</u> <u>GENERAL SPECIFICATION - Material: Carbonized fibre</u>	
66	SNM26396	704035	5330735100033 / MECH. SHAFT SEAL, 025	S80-70-175, GENERAL SERVICE PUMP	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
67	SNM57035	576/179	5330795054710 / O RING RUBBER SIZE: 185X180X2.5MM	DORMAN DIESEL GENERATOR 500KVA 6SETCW/PE	40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
68	DNZ60298	501	5330785035601 / PACKING GLAND SET ID70MM	M/E SW COOL PUMP MODEL FEWV 300-2 NASR	4 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			OD100 (NSD/CSG-II/2/132 DT30-04-2002									
69	DNZ60334	264004 (132356)	5330785041797 / PACKING COMMANION FLANGE (JOINT-FABRIC) 71X0.8MM AA-125	A.C COMPRESSOR FOR PNS NASR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: Joint-Fabric GENERAL SPECIFICATION - Material: Joint-Fabric	
70	DNF64692	158-51020	5961995580314 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAHI)	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
71	DNM62762	32GB500182EE	5999745118298 / PRODIALOG 4 BASIC BOARD	80 TON CARRIER A/C PLANT OFFICERS WARD (FRANCE)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
72	DNF63583	NO.E91 IEC LR6	6135795058492 / BATTERY ALKALINE (ENERGIZER) (Non Rechargeable) 1.5V AA SIZE NO.E91 IEC LR6	GENERAL USE	305 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
73	DGE58491	NO DATA AVAILAB LE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	774 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
74	DGD64530	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - capacity: 36 LITTERs GENERAL SPECIFICATION - capacity: 36 LITTERs	
75	DGE62606	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIES 3 IN NO		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos	
76	DGE62733		834070501671 7 / COVER CANVAS WATER PROOF TARPAULIN SZ. 20.00X20. 00 FT		6 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - size: 20 x 20 FEET Color: Olive Green / Green / Dark Brown / Desert. Material: a. 100% ± 10% Canvas Cotton Cloth b. Water Proof c. Border Stitched & buckle affixed at border on equal interval <u>GENERAL SPECIFICATION</u> - size: 20 x 20 FEET Color: Olive Green / Green / Dark Brown / Desert. Material: a. 100% ± 10% Canvas Cotton Cloth b. Water Proof c. Border Stitched & buckle affixed at border on equal interval	
77	SGE47952	4800	831099139716 0 / GLASS SEWING THREAD 03 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)	E&H VOL BELLOWS	6 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
78	DGE35482	NO DATA AVAILABLE	047650000006 1 / GLOVES LEATHER FOR WELDING, treated with preservative, standard quality		56 / PAIR	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - 1. DESCRIPTION GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL</p> <p>detials: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex <u>GENERAL SPECIFICATION - 1. DESCRIPTION</u> GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 2. MATERIAL GOAT SKIN LEATHER LINED WITH KEVLAR AND GLASS FILAMENT 3. MODEL XPRO GOAT SKIN CUT AND HEAT RESISTANT WELDING GLOVES 4. SPECIFICATION PREMIUM GOAT GRAIN LEATHER WELDING GLOVE WITH BLACK COW SPLIT LEATHER GAUNTLET AND INSIDE LINED WITH 100% KEVLAR/ GLASS FILAMENT (ANSI CUT LEVEL A5) AND SET-IN KEYSTONE THUMB FOR GREATER COMFORT. ELASTICIZED BACKS FOR A SNUG FIT. 5. APPLICATION METAL, CONSTRUCTION ETC 6. AVAILABLE SIZES XS TO 3 XL</p> <p>detials: 1. PRODUCT CLASSIFICATION: Welding gloves 2. COMPOSITION: COW LEATHER, FLEECE LINING 3. COLOUR: Yellow 4. SIZE : 16 " 5. PACKAGING ; 1 dozen pair per polybag broucher uploaded as annex</p> <p><u>TECHNICAL SPECIFICATION -</u> Capacity :Maximum Usage/ Application : To hang load Material :</p>	
79	DGB57696	NO DATA AVAILAB LE	02685000006 1 / SCALE- SPRING-		6 / EACH/N UMBER	NO DATA AVAILAB LE						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			BALANCE-20-STONE-280-LBS								Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow <u>GENERAL SPECIFICATION - Capacity :Maximum Usage/ Application : To hang load Material : Steel Brand :Miyakawa Beam Width: ½ mm Finishing :Golden Yellow</u>	
80	DPK61621	ISO VG 460	915070100332 1 / OIL-SHELL OMALA S2 G 460 (PACKING 209 LTR DRUM)	BHER-E-PAIMA	60 / LITER						<u>TECHNICAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSD</u> <u>GENERAL SPECIFICATION - TECHNICAL DATA SHEET ENCLOSD</u>	
81	SGB52128		027550000002 6 / MEASURING TAPE STEEL ½" x 300'		3 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition</u> <u>GENERAL SPECIFICATION - Crescent Lufkin ½" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure – Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition</u>	
82	DNQ61132	140501010	841599130487 3 / GLOVES	FIRE FIGHTING	60 / PAIR						<u>TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
83	DNQ61171	140501010	8415991304873 / GLOVES	FIRE FIGHTING	61 / PAIR						<p><u>TECHNICAL SPECIFICATION -</u> OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL</u> <u>SPECIFICATION - OEM M/S</u> COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.</p>	
84	DGP62159		7510701005039 / UV Flexo Ink (Black Colour)		300 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION -</u> MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4.silian brand ink PROPERTIES/CHARACTERISTICS: 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR. DENOMINATION : PACKING TO BE PROVIDED IN LOWEST DENOMINATION OF KGS AS INK GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP. <u>GENERAL SPECIFICATION -</u> MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4. silian brand ink</p> <p>PROPERTIES/CHARACTERISTICS: 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR. DENOMINATION : PACKING TO BE PROVIDED IN LOWEST</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											DENOMINATION OF KGS AS INK GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP.	
85	DGB54802	XK-1000/Exec el-40C	667078511607 2 / DIGITAL WEIGHING SCALE FOR RATIONS WEIGHING		2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration</p> <p><u>GENERAL SPECIFICATION -</u> model: Any Model oem: As per procured model end user: VSD useage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx.: 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter. ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration</p>	
86	DGB54531	NO DATA AVAILAB LE	711070503606 7 / SAFE STEEL WITH KEYS AND COMB LOCK	FOR GENERAL PERPOSE	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			OF C/B 18" X18"X17"TH 1/8"								than 3/8" d. No of levers: Minimum 02 <u>GENERAL SPECIFICATION</u> - Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02	
87	DGB64167	NO DATA AVAILAB L E	711070503606 7 / SAFE STEEL WITH KEYS AND COMB LOCK OF C/B 18" X18"X17"TH 1/8"	FOR GENERAL PERPOSE	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02 <u>GENERAL SPECIFICATION</u> - Description: Safe Steel with Combination Lock for CBs b. Size: 18' x 18' x 17' c. Thickness: Not less than 1/8" d. Door thickness: Not less than 3/8" d. No of levers: Minimum 02	
88	DGE62619		045154600446 4 / TAPE, COTTON WIDTH 3/4 INCH 50 MTR ROLL QUALITY HEAVY.		110 / ROLL						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB L E <u>GENERAL SPECIFICATION</u> - NO DATA AVAILAB L E	
89	DGP61391	NO DATA AVAILAB L E	005050000011 4 / PAPER, TYPING, LARGE, GSM40±5%, WHITE, REAMOF500S HEET, SIZEA-04 210X297MM.		62 / REAM	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB L E <u>GENERAL SPECIFICATION</u> - NO DATA AVAILAB L E	
90	DGD48753	NO DATA AVAILAB L E	003550000056 0 / COOKER PRESSURE-10 LITRES COMPLETE		7 / SET	NO DATA AVAILAB L E					<u>TECHNICAL SPECIFICATION</u> - Aluminum Food Grade (Lead Free) <u>GENERAL SPECIFICATION</u> - Aluminum Food Grade (Lead Free)	
91	SNM47233	7E9658	471071512827 8 / CONTACTOR (WATER	D/G	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - oem: catterpillar <u>GENERAL SPECIFICATION</u> - oem: catterpillar	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			TEMPERATUR E)									
92	DGB62931	WORKING 100PSIG MAX FLANGE CONN-	024154600193 4 / GATE VALVE 1.5" PRESSURE 100PSI		8 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - Specifications: Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves Make : Kurtek Vana Sanayi VE Ticaret Ltd. STI. connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb</u></p> <p><u>GENERAL SPECIFICATION - Specifications: Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves Make : Kurtek Vana Sanayi VE Ticaret Ltd. STI. connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb</u></p>	
93	SNF52839	MCTX-4PRT-SWTCH	593070524871 2 / 4 PORT SWITCH		10 / EACH/NUMBER	MCTX-4PRT-SWTCH					<p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>	
94	DRG49403		1730ZO654972 2 / TRESTLE FORWARD		5 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - 1. HEIGHT: 4 FT 2. WIDTH: 5 FT 3. LENGTH: 7.5 FT 4. MATERIAL : ALUMINIUM 'L' SECTION: 40X40 5. STEPS & TOP PLATFORM : 4MM THICK ALUMINUM 6. CHECKER PLATE (5 X 5 FT) 7. STAIRS STEP 5 FT 1 FT 8. 4 X SIDE RIGGER SCREW JACKS 9. 2 X WHEELS 8 INCH (FRONT END ONLY)</u></p> <p><u>GENERAL SPECIFICATION - 1. HEIGHT: 4 FT 2. WIDTH: 5 FT 3. LENGTH: 7.5 FT 4. MATERIAL : ALUMINIUM 'L' SECTION: 40X40 5. STEPS & TOP PLATFORM : 4MM THICK ALUMINUM 6. CHECKER PLATE (5 X 5 FT) 7. STAIRS STEP 5 FT 1 FT 8. 4 X SIDE RIGGER SCREW JACKS 9. 2 X WHEELS 8</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCH (FRONT END ONLY)	
95	DCW63138		8430500100532 / BOOT ANTI SKID BLACK SIZE 06		75 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 06 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 06	
96	DRG49398	rl-w501	3431ZO6567519 / TORCH LARGE SHOCK PROOF.		9 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Battery powered (alkaline) LED shockproof black color torch of aluminum material (11.8 x2.9x2 cm size). Recommended Black Eye Mini company or equivalent. GENERAL SPECIFICATION - Battery powered (alkaline) LED shockproof black color torch of aluminum material (11.8 x2.9x2 cm size). Recommended Black Eye Mini company or equivalent.	
97	DCW63140		8430500100698 / BOOT ANTI SKID BLACK SIZE 8		75 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8	
98	DNF56999	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		26 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
99	DGP54893	B12B808411	7025145835182 / SCANNER EPSON DS-6000		1 / SET	DS-6000					TECHNICAL SPECIFICATION - SCANNER EPSON DS-60000 FLAT BED COLOR IMAGE SCANNER 600DPI COLOR CCD 4 LINE SENCER (RGB & BLACK FLAT BED 11.7" X 17" GENERAL SPECIFICATION - SCANNER EPSON DS-60000 FLAT BED COLOR IMAGE SCANNER 600DPI COLOR CCD 4 LINE SENCER (RGB & BLACK FLAT BED 11.7" X 17"	
100	DGE58293	MEDIUM 66.2 LTRS 2000 PLUS	8115705259598 / COLEMAN or EQUIVALENT ICE BOXES		9 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(MEDIUM) 66.2 LTRS 2000 (PLUS)								(plus) approx. <u>GENERAL SPECIFICATION - BOTH SIDE HANDLES CAPACITY 66.2 LTRS SIZE (LENGTH 32" WIDTH 16" HEIGHT 18" WALL THICKNESS 3 CM) capacity 200 (plus) approx.</u>	
101	DN061062	7620.464.004.4	2815FP3030383 / Hole-type nozzle		6 / EACH/NUMBER	tbd620v12					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
102	DNF58178	HST-cjx2-1810/HEP-600C-12	5935705246117 / magnetic connector		3 / EACH/NUMBER	CJX2-1810 C-LIN					<u>TECHNICAL SPECIFICATION - as per enclosed</u> <u>GENERAL SPECIFICATION - as per enclosed</u>	
103	DNZ58913	E-03-12	2815785277599 / THREE-STAGE PISTON		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
104	DNO61837	447-8230	2930715234012 / Seawaterpump Gp Aux		2 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION - Seawaterpump Gp Aux</u> <u>GENERAL SPECIFICATION - Seawaterpump Gp Aux</u>	
105	DSB63553		0011041950216 / THERMOSTAT E T021 16(2)A-250/380V~50T O300C		2 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - Part no: Not Available Make/ Model/ Brand/ Equivalent : DEST 0-300 °C KOREA Further information may be obtained from under mentioned supplier: HUMAYUN ELECTRIC HEATER Shop#, Aram Bagh Electric Market, Shahrah-e-Liaqat, Karachi. 0300-9200510,0324-3234032</u> <u>GENERAL SPECIFICATION - Part no: Not Available Make/ Model/ Brand/ Equivalent : DEST 0-300 °C KOREA Further information may be obtained from under mentioned supplier: HUMAYUN ELECTRIC HEATER Shop#, Aram Bagh Electric Market, Shahrah-e-Liaqat, Karachi. 0300-9200510,0324-3234032</u>	
106	DCW63146		8430500100961 / BOOT ANTI SKID BLACK		75 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-14</u> <u>GENERAL SPECIFICATION - BOOT</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SIZE-14								ANTI SKID BLACK SIZE-14	
107	DCW63139		8430500100697 / BOOT ANTI SKID BLACK SIZE 7		75 / PAIR						<u>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 7</u> <u>GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 7</u>	
108	DNZ58918	E-03-16	2940785277648 / THREE-STAGE INTAKE VALVE (L-03-15B)		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
109	DNM61143	332-7865	5975715238805 / TIE-CABLE		600 / EACH/NUMBER	C7.1					<u>TECHNICAL SPECIFICATION - NOT KNOWN</u> <u>GENERAL SPECIFICATION - NOT KNOWN</u>	
110	DGD55555	cfmv-01	7320705269665 / COFFEE VENDING MACHINE		2 / EACH/NUMBER	CFMV-01					<u>TECHNICAL SPECIFICATION - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l</u> <u>GENERAL SPECIFICATION - heating fast: 5min, great water qty flow: max. 400ml/cup, dispense great powder qty: max. 100g/cup, continuously dispense cups: above 100cups. power/output:ac 220v/50hz: 1600w, water and capacity: 3canisters, 1600g, boiler capacity: 4.3l</u>	
111	DN053977	CSA-80-SEW/FFF7	5340785279635 / ISOMETRIC COMPOSITE SACRI FICIAL ANODE (80 OD = 118 Ømm, ID = 84 Ømm)		60 / EACH/NUMBER	215ZF907-12-0					<u>TECHNICAL SPECIFICATION - NSX-FHJYJ-HZ3 1.0 MPa DN80 OD = 118 (Ømm), ID = 84 (Ømm), Length of sleeve = 40 (mm)</u> <u>GENERAL SPECIFICATION - NSX-FHJYJ-HZ3 1.0 MPa DN80 OD = 118 (Ømm), ID = 84 (Ømm), Length of sleeve = 40 (mm)</u>	
112	DSB62174	YED0526/01 - A4E02596	6110FT1028668 / Power Bridge		3 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION - N/A</u> <u>GENERAL SPECIFICATION - N/A</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
113	SNF57089	0103-034021-250	668578515449 6 / THERMOCOUPLE 5M	H/PAC	5 / EACH/NUMBER			ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY</u> ;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY</u> ;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.	
114	DGT62010	NIL	551070519913 4 / KAIL WOOD SLEEPER GRADE-A (LOCAL)	KAIL WOOD (TIMBER)	100 / CUBIC FOOT	NIL	NIL	LOCAL MARKET	LOCAL MARKET		<u>TECHNICAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%</u> <u>GENERAL SPECIFICATION - size: LENGTH: 8 TO 16 FEET WIDTH: 8 to 14 INCH THICKNESS: 6 to 8 INCHES SPECIFICATIONS: psg: 69 (FOR VISUAL INSPECTION ONLY) moisture contents: 06% to 18%</u>	
115	DNM64302	3077198	533000491594 1 / GASKET, RKR LEVER HOUSING	CUMMINS DG VTA28-G5 USA	4 / EACH/NUMBER	VTA28-G5	25354882	CUMMINS ENGINE COMPANY, INC. BOX 3005 COLUMBUS, INDIANA, USA 47202	CUMMINS ENGINE COMPANY, INC. USA		<u>TECHNICAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA TAPET COVER GASKET</u> <u>GENERAL SPECIFICATION - 650 KVA CUMMINS DG VTA28-G5 USA TAPET COVER GASKET</u>	
116	SNM59314	233-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	CAT00C715GT00677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
117	SNM62688	DG4V-5-2A	594573521849 5 / SOLENOID VALVE	WINDLASS	1 / EACH/NUMBER	DG4V-5-2A	13053	MAIN FACTORY. #1509-5 DADAE SAHA-KU BUSAN KOREA TEL:82-51-265-1746/82-51-265-1747 FAX:82-51-265-1748 E-MAIL: YOOWONMTECH@HANM	YOO WON M - TECH CO LTD		<u>TECHNICAL SPECIFICATION - CRITICALLY REQUIREMENT OF WINCH OPERATION</u> <u>GENERAL SPECIFICATION - CRITICALLY REQUIREMENT OF WINCH OPERATION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								AIL. NET/UDOHAN@HANMAIL. NET WEB:WWW. YOOWONMTECH.COM				
118	DGP636 26	CS- WDC09- 655- BAA/CMW 9U	712570514141 8 / 9U WALL MOUNT 19" CABINET	NET WORKING	1 / EACH/N UMBER	NO DATA AVAILAB LE		CH	M/S RAISECO M SUITE NO.401A PANURA MA CENTRE 2 RAJA GHAZAN FAR ALI ROAD SADDAR KARACHI PHON NO. 021- 35661550 -1		<u>TECHNICAL SPECIFICATION - CONTECH BRAND</u> <u>GENERAL SPECIFICATION - CONTECH BRAND</u>	
119	DGP566 20	CS- WDC09- 655- BAA/CMW 9U	712570514141 8 / 9U WALL MOUNT 19" CABINET	NET WORKING	1 / EACH/N UMBER	NO DATA AVAILAB LE		CH	M/S RAISECO M SUITE NO.401A PANURA MA CENTRE 2 RAJA GHAZAN FAR ALI ROAD SADDAR KARACHI PHON NO. 021- 35661550 -1		<u>TECHNICAL SPECIFICATION - CONTECH BRAND</u> <u>GENERAL SPECIFICATION - CONTECH BRAND</u>	
120	SNM619 48	85484	433070517262 9/ SEPARATOR CARTRIDGE LPAC ALPINE	LPAC	2 / EACH/N UMBER	NK200	L2010/4	ALPINE INDUSTRIAL PVT LTD 305/2 GT ROAD BAGH PURA LAHORE PAKISTAN	ALPINE PAKISTA N (LAHORE)		<u>TECHNICAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102</u> <u>GENERAL SPECIFICATION - OPERATION AND MAINTENANCE MANNUAL 0102</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
121	DNC57381	(DOS3), N1115.	635022616408 4 / OPTICAL SMOKE DETECTOR HEAD	SALWICO CS4000 FIRE ALARM	1 / EACH/NUMBER	SALWICO DOS3	SG-1360	73	CONSILIU M MARINE ABSALS MASTAR EGATAN 21GOTEB ORGSWE DENSE- 40276876 3HISINGS BACKAS E-402 76+46 31 710 77 00+46 31 710 78 00556070 - 9353CON SILIUM@ CONSILI UM. SEHTTPS ://WWW. CONSILI UM. SE4669		<u>TECHNICAL SPECIFICATION -</u> NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILIU M MARINE AB SALSMASTAREGATAN 21 GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILIU M@CONSILIU M.SE HTTPS://WWW.CONSILIU M.SE 4669 <u>GENERAL SPECIFICATION -</u> NCAGE: SK264 NCAGESD: A Type Code: E NCAGE Information: CONSILIU M MARINE AB SALSMASTAREGATAN 21 GOTEBORG SWEDEN SE-40276 8763 HISINGS BACKA SE-402 76 +46 31 710 77 00 +46 31 710 78 00 556070-9353 CONSILIU M@CONSILIU M.SE HTTPS://WWW.CONSILIU M.SE 4669	
122	SNM61053	MSM GRFY 035F20D43	482072517712 6 / MEGNIT SOLENOID	AGG HYDRO PP	1 / EACH/NUMBER	SRP-1010FP	NA	SCHOTTEL GmbH & Co KG D.56322 SPAY/RHEIN GERMANY	SCHOTTEL		<u>TECHNICAL SPECIFICATION -</u> oem: volvo penta schottel gmbh germany AMGNIT SOLENOID OPERATING VELVE 24VDC SUPPLY <u>GENERAL</u> SPECIFICATION - oem: volvo penta schottel gmbh germany AMGNIT SOLENOID OPERATING VELVE 24VDC SUPPLY	
123	SNM60094	08414	473071517302 6 / CQP NYLON QUICK COUPLING	ABRASIVE BLAST CLEANING MACHINE	10 / EACH/NUMBER			CLEMCO INDUSTRIES CORP. USA WWW. CLEMCOINDUSTRIES. COM	CLEMCO		<u>TECHNICAL SPECIFICATION -</u> JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING <u>GENERAL</u> SPECIFICATION - JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING	
124	SNM51686	2652C112	413079517190 1 / AIR FILTER	60 KVA PERKINS	3 / EACH/NUMBER	DK 51280	4ZK05396	PERKINS UK	PERKIN UK		TECHNICAL SPECIFICATION - AIR FILTER GENERAL SPECIFICATION - AIR FILTER	
125	DNM40037	3863223	472014565506 2 / HYDRAULIC HOSE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	1 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6899 oem: Volvo Penta (Sweden) GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6899 oem: Volvo Penta (Sweden)	
126	DGB60075	NO DATA AVAILABLE	413070516016 9 / SPLIT A/C BRASS VALVE SIZE 3/8	SPLIT AIR CONDITION,, LS-W246 SERIES.	21 / EACH/NUMBER	LSW246		LOCAL SOURCE:HASHOO CENTRE ABDULLAH HAROON ROAD KARACHI.	LG ELECTRONICS, INC PAKISTAN		TECHNICAL SPECIFICATION - MAKE:GREE & ACSON CAPACITY: 1.5 TON & 2 TON GENERAL SPECIFICATION - MAKE:GREE & ACSON CAPACITY: 1.5 TON & 2 TON	
127	DNS46873	196-013	482073517061 1 / THERMOSTATIC VALVE FOR HT WATER	MAIN ENGINE	2 / EACH/NUMBER			WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	WARTSILA PAKISTAN		TECHNICAL SPECIFICATION - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821 GENERAL SPECIFICATION - OEM : WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	
128	DNQ59378	SOLO A10-001	129073522627 0 / SOLO A10 150ML (SMOKE DETECTOR TESTER)	SMOKE DETECTOR	2 / EACH/NUMBER	SOLO A10	NIL	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	NO CLIMB PRODUCTS LTD		TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION GENERAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION	
129	DNQ58644	SOLO A10-001	129073522627 0 / SOLO A10 150ML	SMOKE DETECTOR	4 / EACH/NUMBER	SOLO A10	NIL	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN	NO CLIMB PRODUCTS		TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(SMOKE DETECTOR TESTER)					HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	TS LTD		FREE SOLUTION <u>GENERAL SPECIFICATION</u> - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION	
130	DNM47835	2366057	4330715186669 / FILTER ELEMENT FUEL	D/G CATTER PILLAR C2.2	10 / EACH/NUMBER		JAW00494	USA	CATER PILLAR		<u>TECHNICAL SPECIFICATION</u> - oem : caterpillar <u>GENERAL SPECIFICATION</u> - oem : caterpillar	
131	DGB59987	VE-SWR-7x7-3mm	5325785196464 / STAINLESS STEEL WIRE rope 3mm/2MM (7x7) 304I/316	PHYSICAL FENCE VIGIL II VCPMIEC	20600 / METER	ss316 (WIRE GRADE 316 STAINLE SS STEL) EQUIVALENT: SS316L		CHINA NATIONAL PRECISION MACHINERY i&e CORPORATION (CPMIEC)	CHINA		<u>TECHNICAL SPECIFICATION</u> - (1)-description=steel wire rope 3mm (7x7) 304I, (2) -nominal diameter= 3mm,/2MM (3) - material= stainless steel 304I/316, (4) -approximate mass= 0.034kg/m, (5)- minimum breaking loads 1570mpa=5.32kn-544kg, (6) -stand information 7x7, (7) -available roll size=(500m,1000m, 1500m,2000m,3000m), (8) Code: EW- SS20/316) <u>GENERAL SPECIFICATION</u> - (1)-description=steel wire rope 3mm (7x7) 304I, (2) -nominal diameter= 3mm,/2MM (3) - material= stainless steel 304I/316, (4) -approximate mass= 0.034kg/m, (5)- minimum breaking loads 1570mpa=5.32kn-544kg, (6) -stand information 7x7, (7) -available roll size=(500m,1000m, 1500m,2000m,3000m), (8) Code: EW- SS20/316)	
132	DNM59975	KRP1699	6620998568640 / TRANSMITTER, PRESSURE	PERKIN DG 250 KVA 1506A-E88TAG3 ITALY	2 / EACH/NUMBER	1506A-E88TAG3	LGDF1012	Elcos srl - S.S. 234 Km 58,25 Grumello Cremonese (CR) Italy tel. +39 0372 72330 fax. +39 0372 7233220 - info@elcos.net - www.elcos.net	ELCOS Generating Sets		<u>TECHNICAL SPECIFICATION</u> - PERKINS ENGINE MODEL 1506A-E88TAG3 <u>GENERAL SPECIFICATION</u> - PERKINS ENGINE MODEL 1506A-E88TAG3	
133	DNQ58905	NIL	8415998696940 / SURCOAT WHITE WITH RED CROSS (COTTON/NO MAX MATERIAL)	STOCKING SHIPS FF	4 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK		<u>TECHNICAL SPECIFICATION</u> - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP</u> (N) LETTER 340731/P-34 DATED 28 FEB 12.	
134	DNS57953	200 006	3120735185414 / BELLOWS	WARTSILA MAIN ENGINE 9L20C3 FINLAND	6 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
135	DNS57634	471 066	5340580007124 / PLATE	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
136	DNS57633	471 584	2010735185533 / FLUSHING CANAL SHAFT	WARTSILA MAIN ENGINE 9L20C3 FINLAND	2 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
137	DNS57635	471 062	5340580007126 / PLATE	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
138	DNS47936	165 015	2815735185687 / RETAINER RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	36 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
139	SNM59316	06NA660016S	5915151799286 / OIL FILTER	CARRIER AIR CONDITION	1 / EACH/NUMBER	30GX-092-A-901-EE		CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388	CARRIER FRANCE		<u>TECHNICAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388</u> <u>GENERAL SPECIFICATION - CARRIER SA BP 49 ROUTE DETHIL 01120 MONTIVEL FRANCE. TEL: 33(0)472252108 FAX: 33(0)472252388</u>	
140	DNF57675	P-0113000	7050785166789 / IPSAN HARDDISK_W D 2T	PSS	39 / EACH/NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION - Harddisk_WD 2T</u> <u>GENERAL SPECIFICATION - Harddisk_WD 2T</u>	
141	SNF52110	DH-IPC-HD2231T-ZS-S2/ DH-IPC-HDBW2231RP-ZS-S2/VFS / P-0123000	5820785166799 / 2 MP WDR IR DOME NETWORK CAMERA	PSS VIGIL	8 / EACH/NUMBER			M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
142	DPC48826	387 008	4940735186272 / GLUE	WARTSILA MAIN ENGINE 9L20C3	4 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPOUND- LOCTITE 5399	FINLAND			242 RASDPA AE084243 , PAAE084 244	Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380			TPI	
143	DNQ580 81	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	53 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		<u>TECHNICAL SPECIFICATION -</u> NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL <u>GENERAL</u> <u>SPECIFICATION -</u> NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
144	DNJ6110 9	09944- 09820	512070523099 0 / TILT CYLINDER CAP TOOL	300HP OBM	2 / EACH/N UMBER	DF300AP	30002P- 712896	M/S PAK SUZUKI MOTORS CO LTD, KARACHI TELEPHONE NO: 021- 34723511	M/S PAK SUZUKI MOTORS		<u>TECHNICAL SPECIFICATION -</u> Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5 Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition <u>GENERAL SPECIFICATION -</u> Engine type- 4-stroke DOHC Number of cylinders -V-6 Bore mm (in)- 98 (3.86) Stroke mm (in)- 89 (3.50) Total displacement cm3 (cu. in)- 4 028 (245.6) Compression ratio : 1 9.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Spark plug - NGK BKR6E Ignition system - Full-transistorized ignition	
145	SNM51655	KP-1	4820705211776 / LOW AMBIENT CONTROL	MOBILE AC PLANT	10 / EACH/NUMBER	KP-1	CWM-2C70-PN 0410	COOL POINT	COOL POINT		<u>TECHNICAL SPECIFICATION - METALIC</u> <u>GENERAL SPECIFICATION - METALIC</u>	
146	SNF51862	0702-004-00	5999795133797 / AUTO AND MANUAL START CONTROL MODULE (DSE 702)	SSDG CATTERPILLAR	5 / EACH/NUMBER	NO DATA AVAILAB LE		UK	DEEP SEA ELECTRONICS PLC HIGH FIELD HOUSE HUNMAN BY INDUSTRIAL ESTATE NORTH YORKSHIRE YO114PH UK		<u>TECHNICAL SPECIFICATION - oem, deep sea electronics ()dse uk. local source. m/s pyramid automation 8-a/2 gulberg iii near hussain chowk lahore. tel: 92 42 35760910-2 fax 92 42 35754944 e-mail: sales@PYRAMID AUTOMATION. com</u> <u>GENERAL SPECIFICATION - oem, deep sea electronics ()dse uk. local source. m/s pyramid automation 8-a/2 gulberg iii near hussain chowk lahore. tel: 92 42 35760910-2 fax 92 42 35754944 e-mail: sales@PYRAMID AUTOMATION. com</u>	
147	DNM57290	2010TM-OR	2910013538540 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	3 / EACH/NUMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFIN		<u>TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u> <u>GENERAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL.</u>	
148	DNF57683	VCNP-21OH-IR	5820705156826 / LONG RANGE IR CAMERA	CCTV CAMERA SYSTEM	1 / EACH/NUMBER			V SECURE VISION FIRE&SECURITY,OFFICE NO.16,CROWN CENTRE SB-1,BLOCK13-C, GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-34830466,34830392, FAX:+92-91-36832287.	V SECURE VISION FIRE&SECURITY		<u>TECHNICAL SPECIFICATION - V SECURE VISION FIRE&SECURITY, OFFICE NO.16,CROWN CENTRE SB-1,BLOCK13-C,GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-34830466,34830392,FAX:+92-91-36832287. OEM:VISION INC KOREA</u> <u>GENERAL SPECIFICATION -V SECURE VISION FIRE&SECURITY,OFFICE NO.16, CROWN CENTRE SB-1,BLOCK13-C,GULSHEN-E-IQBAL KARACHI-7500.TEL:+92-21-</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											34830466,34830392,FAX:+92-91-36832287. OEM:VISION INC KOREA	
149	DNM64301	450-9606/5034411	2520150035112 / EMCP 4.2 (Enigne Control Panel)	CATERPILLAR GENSET D3512B (YBB1) USA	2 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
150	DNC64671	8M6002465	2910MB0020427 / INJECTOR ASSEMBLY FUEL	PETROL MAIN ENGINE	6 / EACH/NUMBER	VERADO 350 HP	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
151	DNC56246	8806621	3410MB0020689 / BEARING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION - BEARING</u> <u>GENERAL SPECIFICATION - BEARING</u>	
152	SNM59314	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
153	DNF64303	800 G3 TOWER PC	7020705215930 / HP ELITEDECK CORE I7	IT SELF	1 / EACH/NUMBER	800 G3 CORE i7	SGH717S BTV	HP HQ-TRE 71025 BOEBLINGEN GERMANY	HEWLETT PACKARD (HP)		<u>TECHNICAL SPECIFICATION - WINDOWS:10 PRO VERSION :</u> 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM <u>GENERAL SPECIFICATION - WINDOWS:10 PRO VERSION :</u> 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM	
154	DNM618	PROPELL	201071522034	MARINE GEAR	1 /	NA		CUMMINS ENGINE CO	CUMMIN		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	22	ER MICHIGAN GOLDLINE	9 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	BOX	EACH/NUMBER			4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	S USA		PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED <u>GENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u>	
155	DNM58113	PROPELLER MICHIGAN GOLDLINE	201071522034 9 / PROPELLER MICHIGAN GOLDLINE CLOCKWISE ROTATION FOR 60 MM SHAFT DIA	MARINE GEAR BOX	3 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA		<u>TECHNICAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u> <u>GENERAL SPECIFICATION - PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, BLADE AREA 85 %, BORE 50 X 38 X L120 (1:10) KEYWAY 14 MM. DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED</u>	
156	SNS52811	25167	473017619899 6 / HOLLOW SCREW	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	10 / EACH/NUMBER	D9A2A		VOLVO AB GOETEBORG SWEDEN	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
157	DPC61632		047450474007 9 / POWDER P.B.N		100 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SPECIFICATION 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG <u>GENERAL SPECIFICATION - SPECIFICATION</u> 1. CHEMICAL NAME N-PHENYL-2-NAPHTHYLAMINE 2. MOLECULAR FORMULA C16H13N 3. CAS NO. 135-88-6 4. APPEARANCE PALE OR BROWN POWDER 5. MELTING POINT 105.0 OC MIN REDUCTION IN WEIGHT AFTER 6. 0.20% MAX HEATING 7. ASH 0.20% MAX 8. PHENYLAMINE CONTENT NO BLUE AND PURPLE REACTION BY TESTING 9. SCREEN RESIDUE (100 MESHES) 0.2% MAX BOILING POINT 365.5 OC. SOLUBLE IN ACETONE, 10. PROPERTY CHLOROFORM, ALCOHOL AND TETRACOL. INSOLUBLE IN GASOLINE AND WATER 11. PACKAGE 25 KGS BAG</p>	
158	DGE31488	202-GNFG	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER I.R. SIZE 9		150 / PAIR	202-GNFG					<p><u>TECHNICAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity <u>GENERAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity	
159	DPK64099	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		50 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
160	DGE58499	NO DATA AVAILABLE	0350595713118 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875") (5MM)		840 / FATHOM	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. <u>GENERAL SPECIFICATION - 1.</u> TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
161	DGE584 31		042159942563 7 / FILING CABINET SIZE, 4- DRAWERS W/LOCK combination AND COMPRESSO R PLATES GREY GUAGE SWG:22 SIZE; W18 INCH		12 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user <u>GENERAL SPECIFICATION -</u> GUAGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT.52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	
162	DGE601 15		045159451009 4 / MATTRESS FOAM RUBBER WITH COVER 82" X36"X4" (WARRANTY 10 YEARS		57 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - 1.</u> ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM. <u>GENERAL</u> <u>SPECIFICATION - 1. ACCEPTABLE</u> BRAND OF; a.DIAMOND SUPREME A-1 b.MASTER MOLTY FOAM.	
163	DPC634 66	NO DATA AVAILABL E	044450001055 1 / SOLUTION FOR SCALE REMOVING packing 20 or 25 ltr		50 / LITER						<u>TECHNICAL SPECIFICATION - NO</u> DATA AVAILABLE <u>GENERAL</u> <u>SPECIFICATION - NO DATA</u> AVAILABLE	
164	DGB573 12		026659000039 0 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		64 / PAIR						<u>TECHNICAL SPECIFICATION -</u> made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg <u>GENERAL</u> <u>SPECIFICATION - made of iron steel</u> coated total length approx: 5 1/2 feet	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	
165	DGB61831	HA-680	0268590012396 / Weighing Machine B/Roo		2 / EACH/NUMBER	HA-680/HA-622					<p><u>TECHNICAL SPECIFICATION - 1.</u> body weighing: 120 kg maximum weight ; 160 kg (sub- divisions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO</p> <p><u>JAPANGENERAL SPECIFICATION -1.</u> body weighing: 120 kg maximum weight ; 160 kg (sub- divisions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN</p>	
166	DGT47852	NO DATA AVAILABLE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		672 / SQ FEET						<p><u>TECHNICAL SPECIFICATION - SPECIFICATION:</u> BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											subject item is 12mm to 13mm	
167	DGT52172	NO DATA AVAILAB LE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLIES OF SHESHAM WOOD) 7 PLY TYPE OF BOND WBP TREATED WITH PRESERVATIVE		896 / SQ FEET						<p><u>TECHNICAL SPECIFICATION - SPECIFICATION:</u> BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm</p>	
168	DGP64515	NO DATA AVAILAB LE	0051500001403 / Binder Medium F(NS) -101 SIZE 9X12 INCH, Board Texture, Hard & Plyable Thickness 03 mm		112 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - Size:</u> 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press</p> <p><u>GENERAL SPECIFICATION - Size:</u> 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
169	SGB56146		0267599235349 / TEE PIPE EQUAL (GALVANISED) 03.00IN		50 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm <u>GENERAL SPECIFICATION</u> - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm	
170	DGE57595	NO DATA AVAILABLE	0320599232703 / Coir Yarn Type Good Quality 112 LBS		140 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg <u>GENERAL SPECIFICATION</u> - Dimension/Size = 4mm Material = Coconut Husk Color = Brown Strand = 02 Ply Rope Type = Twisted Pair Packing Type= Coil/Roll Breaking Load = 50 Kg	
171	DGB37525		0272502720040 / DRILL-PARALELL-SHANK-3MM CARBON STEEL		58 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material HSS, Hardness HRC65-66. <u>GENERAL SPECIFICATION</u> - Material HSS, Hardness HRC65-66.	
172	DGB64419	1473	0248791296148 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56 1/2"X31 1/4 X 26"	BODY 16 GAUGE, DOOR NOT LESS THAN 3/8" THK-	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03 <u>GENERAL SPECIFICATION</u> - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
173	DGD28330	NO DATA AVAILABLE	0032500032013 / SPOON TEA FOR CNS		162 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) <u>GENERAL SPECIFICATION</u> - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL)	
174	DGB30145		0263594149649 / SHACKLE BOW TO SCREW FOR RIGGING SIZE 0.625"-1.25"-0.750"	LG 2.5" SPEC=5031, 003503588	200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material of item: Forged Steel b. Drawing of item: Enclosed <u>GENERAL SPECIFICATION</u> - Material of item: Forged Steel b. Drawing of item: Enclosed	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
175	DGB54026	0251-14505	025170411973 7 / FERRULE- WIRE-ROPE 1.5 INCH (12mm)		500 / EACH/N UMBER						TECHNICAL SPECIFICATION - ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA:27.2 MM ferrule length: 45 mm GENERAL SPECIFICATION - ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA: 27.2 MM ferrule length: 45 mm	
176	DGH53981		056159521853 7 / CABLE ELECT WELDING FLEX 1 CORE COND 1107/0. 20 DIA 14.5MM		500 / METER						TECHNICAL SPECIFICATION - DEF STAN 61-12/1 PART 19 & BS 638 PART 4 OF 1996 GENERAL SPECIFICATION - DEF STAN 61- 12/1 PART 19 & BS 638 PART 4 OF 1996	