

TENDER BULLETIN

DATE & TIME 6/25/24 10:19 AM INVITATION TO TENDER TO BE OPENED ON 7/11/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF58405	CAT-6A U-FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE- 0.36MM 4/U- FTP PVC/LSZH-0.5 MM AQUA/BLUE/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	449 / FOOT	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-87688883	CHINA		<u>TECHNICAL SPECIFICATION -</u> oem, contech solution USA. www. CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U- FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL</u> <u>SPECIFICATION -</u> oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
2	DGE50471	ASTM D 6413	721050515517 1 / FIRE RETARDANT SPRING MATRESS (L6. 5"XW2'XH6)	MATRESSES FOR BED	42 / EACH/N UMBER			LOCAL ADDRESS:AL- KHAIR HOUSE-43-T,AL- KHAIR CHOWK,AL-KHAIR ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	AL- KHAIR HOUSE- 43-T		<u>TECHNICAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500- 1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PROVIDED FOR APPROVAL) GENERAL SPECIFICATION - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500- 1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
3	DNF64635	ABX-104 / P-0186000	635078516763 2 / ALARM SYSTEM/INFR ARED INTRUSION DETECTORS	PSS	10 / EACH/N UMBER	ZUDSEC -ABX SERIESE / BOSCH 4281		CETC mansion no 5 Wulutong North Street Xicheng District Beijing China 100120		M/s CETC INTERNA TIONAL Co, LTD	TECHNICAL SPECIFICATION - OEM M/S ZUDEN SECURITY TECH LTD SHENZHEN CHINA. LOCAL, ELECTROMECH Engineering Pakistan C/5, 201,10th Street, Khayabane-e- Shamsheer, Phase-V, DHA, Karachi MOBILE:0333- 3887803. SPECS: VOLTAGE DC 10- 18v Reaction Time: > 0.1 sec Temp: -30° C – +50° C No. of Beams: 04 Barrier Length: 70.8 cm Response Time: 10 ~ 500 msGENERAL SPECIFICATION - OEM M/S ZUDEN SECURITY TECH LTD SHENZHEN CHINA. LOCAL, ELECTROMECH Engineering Pakistan C/5, 201,10th Street, Khayabane-e- Shamsheer, Phase-V, DHA, Karachi MOBILE: 0333-3887803. SPECS: VOLTAGE DC 10-18v Reaction Time: > 0.1 sec Temp: -30° C – +50° C No. of Beams: 04 Barrier Length: 70.8 cm Response Time: 10 ~ 500 ms	
4	DNF64724	NIKON D-3500/NIKON D-200/NIKON D-7000	672025152214 0 / STILL DIGITAL CAMERA	STILL DIGITAL CAMERA	1 / EACH/N UMBER	NIKON D- 3500/NIK ON D- 7000		OC		INTERFO TO A/S,O H BANGSV 51,	TECHNICAL SPECIFICATION - OEM ADD:INTERFOTO A/S,O H BANGSV 51,HOEVIK CITY, NORWAY.PSC:1322, TEL#67534990,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									HOEVIK CITY, NORWAY .PSC: 1322, TEL#6753 499, FAX#675 39794		FAX#67539794GENERAL SPECIFICATION - OEM ADD: INTERFOTO A/S,O H BANGSV 51, HOEVIK CITY,NORWAY.PSC:1322, TEL#67534990,FAX#67539794	
5	DGE647 48	N/A	933070518127 9 / PLASTIC SHEET	GENERAL ITEM	36 / ROLL			LOCAL MARKET	GENERAL ITEM		TECHNICAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm GENERAL SPECIFICATION - PLASTIC SHEET TRANSPARENT Size: 1.8 Meter wide, 20 Meter Roll thickness: 01 mm	
6	SNF5185 9	LC1D80A 110VAC	441073517777 6 / CONTACTOR	PORTAL CRANE	4 / EACH/NUMBER	LC1D80A		ISTANBUL AVRUPA VINC GEMI EKIMANLARI SAN. VETIC.LTD.STI. Guzelyali Mah. Manolya Sok. No:15/2 Pendik/Istanbul/TURKIYE. Tel: +90(216) 392 25 51, +90(216)392 29 83	SCHNEIDER		TECHNICAL SPECIFICATION - INPUT:110VAC 50Hz 80A GENERAL SPECIFICATION - INPUT:110VAC 50Hz 80A	
7	DNO647 54	5226130/R 5226130	291001195672 0 / INJECTOR ASSEMBLY FUEL	DETROIT SSDD MODEL: 16V149TI, 1000KW, 1605AMPS, 3PHASE	6 / ASSEMBLY			OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM GENERAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM	SUPERIOR DIESEL INC		TECHNICAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM GENERAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM	
8	DNM642 18	5284228	281571519313 3 / NOZZLE	CUMMINS MAIN ENGINE	6 / EACH/N	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street	M/s IMPEX		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PISTON COOLING	CUMMINS MODEL QSB6.7?305MD USA	UMBER			Columbus IN, USA	NINE INC		Columbus IN, USA <u>GENERAL SPECIFICATION - M/s Cummins Inc</u> 500 Jackson Street Columbus IN, USA	
9	DPK64516	ZIC ATF 3	9150735221369 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID	TILT & TRIM ASSEMBLY	30 / LITER	ZIC ATF 3	NIL	SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea	SK LUBRICANTS		<u>TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)</u> <u>GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs & Rhibs (Tilt & trim assembly)</u>	
10	DGP64844	NHQ APPROVED MODEL	7535705133021 / LAPTOP COMPUTER AS PER NHQ APPROVED MODEL (HP/DELL/LENOVO)	COMPUTER	1 / EACH/NUMBER	NO DATA AVAILABLE		PK	VIDE NHQ LETTER ST-S/3200/8198 DT 23/07/08		<u>TECHNICAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ)). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION).</u> <u>GENERAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ)). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION).</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
11	DNF64317	srt5kxli	6130785141278 / APC SMART UPS 5KVA	ILS SYSTEM	1 / EACH/NUMBER	NO DATA AVAILAB LE		US		APC CO. LTD.USA.	TECHNICAL SPECIFICATION - OEM ADD:APC CO.LTD,USA. backup 20-30Min with Full Load GENERAL SPECIFICATION - OEM ADD:APC CO.LTD,USA. backup 20-30Min with Full Load	
12	DNM64219	5289420	3030715193145 / BELT V RIBBED	CUMMINS MAIN ENGINE QSB6.7? 305MD USA	1 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA		M/s Cummins Inc	TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
13	DGE64255	Art 38600	8430725198427 / SHOES ARROW CLOG WHITE ESD	All ESD GERMANY	15 / PAIR	NIL	NIL	Abeba SPEzial schuhausstatar GmbH Schlackenbergstrasse 5 6638 St. Ingbert +49 06894-3103-100		M/s Abeba	TECHNICAL SPECIFICATION - Size 35-47 CE, EN ISO 20347:2012, OB, A,FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable Instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining GENERAL SPECIFICATION - Size 35-47 CE, EN ISO 20347:2012, OB, A,FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable Instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining	
14	DGE64555	Art 38600	8430725198427 / SHOES ARROW CLOG WHITE ESD	All ESD GERMANY	15 / PAIR	NIL	NIL	Abeba SPEzial schuhausstatar GmbH Schlackenbergstrasse 5 6638 St. Ingbert +49 06894-3103-100		M/s Abeba	TECHNICAL SPECIFICATION - Size 35-47 CE, EN ISO 20347:2012, OB, A,FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable Instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining GENERAL SPECIFICATION - Size 35-47 CE, EN ISO 20347:2012, OB, A,FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable Instep area	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining</p>	
15	DGE64852	L-4" Dia 1"	046170514204 1 / REFILE PAINT ROLLER WITH HANDLE LENGTH 4 INCH DIA 1 INCH	HULL PAINT SCHEME	1582 / EACH/NUMBER	NO DATA AVAILAB LE		PK		M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531	<p><u>TECHNICAL SPECIFICATION -</u> Refile Paint Roller With Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan description: complete paint roller with handle SOURCE OF AVAILABILTY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work</p> <p><u>GENERAL SPECIFICATION -</u> Refile Paint Roller With Handle Length 4 Inch Dia 1 Inch Make: local OEM: pakistan description: complete paint roller with handle SOURCE OF AVAILABILTY: M/S AJAZ PAINT HOUSE MARRIOT ROAD KARACHI PHON NO.021 32412531 Parent equipment be indicated : Hypox Work</p>	
16	DGE64855	NIL	423070518126 8 / BAG PAPER FOR CONTAMINATED CLOTHING	NIL	310 / EACH/NUMBER		NIL	PLASTIC MARKET			<p><u>TECHNICAL SPECIFICATION -</u> REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) Dimensions: Height: = 40 cm Width: = 32 cm Depth: = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have double padding at its bottom.</p> <p><u>PACKING: STANDARD</u></p> <p><u>GENERAL SPECIFICATION -</u> REQ NEW PATT AUTHORITY LETTER (CICP letter no. CICP/PATT/1057/3490 dated 30 March 2015) Dimensions: Height: = 40 cm Width: = 32 cm Depth: = 11 cm Paper specifications: (1) Paper sack: Multi-layered, 3-ply (2) GSM: 100 – 150 (3) Paper bag should be printed with phrase "Contaminated Material". (4) Each bag should have</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											double padding at its bottom. PACKING: STANDARD	
17	DGP64831	60 NX 720/X9500H 65	773070516072 2 / LED TV 60 /65 INCHES	TV 60"	1 / EACH/NUMBER	60 NX 720/X9500H 65		M/S AB ELECTRONICS-SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI.	M/S AB ELECTRONICS/SAMSUNG		TECHNICAL SPECIFICATION - M/S AB ELECTRONICS-SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI. GENERAL SPECIFICATION - M/S AB ELECTRONICS-SHOP NO 1 CLIFTON VIEW APARTMENT NEAR III TALWAR KARACHI.	
18	DNQ63346	429083	421070515009 1 / VALVE ASSEMBLY 7KG CO2 FIRE EXTINGUISHER.	07 KG CO2 FIRE EXTINGUISHER	40 / EACH/NUMBER	PBS-5		M/S:AZAM ENTERPRISES KARACHI PHONE: 2624690.	AZAM ENTERPRISES KARACHI PHONE: 2624690		TECHNICAL SPECIFICATION - COUNTRY : PAKISTAN MAKE : Local/ Pakistan GENERAL SPECIFICATION - COUNTRY : PAKISTAN MAKE : Local/ Pakistan	
19	DNM64254	4115P025	431079517188 3 / PISTON & RING KIT	60 KVA PERKINS	3 / SET	DK 51280	4ZK05396	PERKINS UK	PERKINS UK		TECHNICAL SPECIFICATION - PISTON RINGS SET COMPRISING 01 COMPRESSION RING 01 SCRAPER RING AND 01OIL RING AND PISTON STD GENERAL SPECIFICATION - PISTON RINGS SET COMPRISING 01 COMPRESSION RING 01 SCRAPER RING AND 01OIL RING AND PISTON STD	
20	DNM64375	4093730/FS1280	433079519320 1 / SEPARATOR FUEL WATER	CUMMINS D/G 6BTAA5.9-G5	5 / EACH/NUMBER	6BTAA5.9-G5	84093540	CUMMINS UK	CUMMINS UK		TECHNICAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTAN GENERAL SPECIFICATION - ITEM AVILIBLE IN CUMMINS PAKISTAN	
21	SNM61944	H43850	472071517921 6 / XTREME DUTY AIR LESS HOSE	AIR LESS	2 / EACH/NUMBER			GRACO FLUID EQUIPMENT (SHANGHAI) CO. LTD. ROOM 118 1ST FLOOR NO2 XIN YUAN BUILDING NO 509, CAO BAO ROAD, SHANGHAI, P.R CHINA 200233	GRACO		TECHNICAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M) GENERAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M)	
22	DNS64819	4993120	599801630699 6 / electronic components assy/Electronic Control Module	Electronic Control Module	2 / EACH/NUMBER	28410537001	0	500 JACKSON ST COLUMBUS	CUMMINS INC.		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
23	DNM64792	4970909/FS19841	291071517541 6 / FUEL	DIESEL GENERATOR	3 / EACH/NUMBER	FS 19841		STX Engine Co, Kr. 80, Seongsan-dong,	Cummins Filtration		TECHNICAL SPECIFICATION - FUEL FILTER DUPLEX TYPE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FILTER DUPLEX TYPE	QSB7DM	UMBER			Seongsan-gu. Changwon, Korea			(FS19841) OF 7 MICRON MADE OF FLEET GUARD FOR DIESEL GENERATOR CUMMINS QSB7DM. GENERAL SPECIFICATION - FUEL FILTER DUPLEX TYPE (FS19841) OF 7 MICRON MADE OF FLEET GUARD FOR DIESEL GENERATOR CUMMINS QSB7DM.	
24	DNC64660	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	5 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK	GRIFFON HOVER WORK		TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK GENERAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK	
25	DGP64736	260 GSM-+5% 22X28	5895715202228 / MULTI COLOUR CARD SHEET SEPARATERS 260GSM 22X28	FOR PRINTING STY ITEM	7 / PACKE T			M/S STACKO COMPANY. KARACHI	LOCAL		TECHNICAL SPECIFICATION - b. Multi colour card sheets (separators) i.e. white, yellow, blue and pink colour card sheets c. Weight of single sheet 260 ± 5 d. Size 22 x 28 inches e. 100 sheets per packet SEPARATERS 260 GSM-+5% 22X28" GENERAL SPECIFICATION -_b. Multi colour card sheets (separators) i.e. white, yellow, blue and pink colour card sheets c. Weight of single sheet 260 ± 5 d. Size 22 x 28 inches e. 100 sheets per packet SEPARATERS 260 GSM-+5% 22X28"	
26	DGP64735	M855DN/M750DN (D3L09A)	5895715202229 / DYE CUTTING FOR COLOUR SEPARATER	FOR PRINTING	10 / EACH/NUMBER			LOCAL SUPPLIER	IMPORTE D BEST QUIALITY		TECHNICAL SPECIFICATION - Make: Wooden mounted board for fixing of sharp blades for cutting of multi colour card sheets (seperators) „h Size of wooden mounted board 5 x 8 inches „h Different sizes best quality sharp iron blades as per quantity demanded Manufacturing item Wooden mounted board for fixing of sharp blades for cutting of multicolor card sheets (separators) alongwith Lamination of 2500 multicolor separators and stars size (10.5 x 8 inch) Size of wooden mounted board 5 x 8 inches Size of blades: 8 x 1 inch Size of blades: 7.5 x 1 inch Size of blades: 7 x 1 inch	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Size of blades: 6.5 x 1 inch Size of blades: 6 x 1 inch Size of blades: 5.5 x 1 inch Size of blades: 5 x 1 inch Size of blades: 4.5 x 1 inch Size of blades: 4 x 1 inch Size of blades: 3.5 x 1 inch Size of blades: 3 x 1 inch Size of blades: 2.5 x 1 inch Size of blades: 2 x 1 inch Size of blades: 1.5 x 1 inch Size of blades: 1 x 1 inch Size of blades: 0.5 x 1 inch Parent equipment be indicated: Heidelberg Letter Press Printing Machine</p> <p><u>GENERAL SPECIFICATION</u> Make: Wooden mounted board for fixing of sharp blades for cutting of multi colour card sheets (seperators) „h Size of wooden mounted board 5 x 8 inches „h Different sizes best quality sharp iron blades as per quantity demanded Manufacturing item Wooden mounted board for fixing of sharp blades for cutting of multicolor card sheets (separators) alongwith Lamination of 2500 multicolor separators and stars size (10.5 x 8 inch) Size of wooden mounted board 5 x 8 inches Size of blades: 8 x 1 inch Size of blades: 7.5 x 1 inch Size of blades: 7 x 1 inch Size of blades: 6.5 x 1 inch Size of blades: 6 x 1 inch Size of blades: 5.5 x 1 inch Size of blades: 5 x 1 inch Size of blades: 4.5 x 1 inch Size of blades: 4 x 1 inch Size of blades: 3.5 x 1 inch Size of blades: 3 x 1 inch Size of blades: 2.5 x 1 inch Size of blades: 2 x 1 inch Size of blades: 1.5 x 1 inch Size of blades: 1 x 1 inch Size of blades: 0.5 x 1 inch Parent equipment be indicated: Heidelberg Letter Press Printing Machine</p>	
27	DNF64224	121468/5P X300 01RTNG2/MLM-203	613072517106 1 / UPS 3 KVA	N/A	1 / EACH/NUMBER	MLM-203 /DH2024		GERMANY	GERMANY		<p><u>TECHNICAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		/DH2024									VOLT PLUS MINUS 10 PERCENT <u>GENERAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT</u>	
28	SNM51604	CH10929	2940795160207 / LUB OIL FILTER	DIESEL GENERATOR	10 / EACH/NUMBER	2806-E14TAG3	TGDF2038U14293T	PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND	PERKINS ENGINE COMPANY LTD		<u>TECHNICAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND</u> <u>GENERAL SPECIFICATION - PERKINS ENGINE COMPANY LTD PETERBOROUGH PE 15NA ENGLAND</u>	
29	DGP64708	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/M404DN	COMPUTER	6 / EACH/NUMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</u> <u>GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</u>	
30	DGP64725	4003DN	7435705138632 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/M404DN	COMPUTER	4 / EACH/NUMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</u> <u>GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
31	DNH64712	LHM 230 / Y592	392078516738 7 / HAND PALLET TROLLEY (HYDRAULIC) 2.5 TON	ICE SHOP	2 / EACH/NUMBER			CHINA MADE OKATSU	CHINA		<u>TECHNICAL SPECIFICATION -</u> Load Capacity: 2500 KgS MIN FORK HEIGHT: 85 MM Fork Width WXL: 540 x 1150 mm WHEEL TYPE: PU Weight: 70 kgS Platform Ground CLEARANCE: Min 3 cm Max 15 cm <u>GENERAL SPECIFICATION -</u> Load Capacity: 2500 KgS MIN FORK HEIGHT: 85 MM Fork Width WXL: 540 x 1150 mm WHEEL TYPE: PU Weight: 70 kgS Platform Ground CLEARANCE: Min 3 cm Max 15 cm	
32	DNQ63438	PHY32.C	463070521240 8 / RUBBER DIAPHRAGM FOR FIXED 700 L BOTTLE	AFFF FOAM BOTTLE	2 / EACH/NUMBER	RUBBER DIAPHRAGM FOR PHY32.C	J20552/B7482	ZHENDAN FIRE EQUIPMENT WORKS CHINA. POC IS M/S CSTC CHINA. ITEM IS LOCALLY AVAILABLE AT M/S LONGMAN MILLS LAHORE.	ZHENDAN FIRE EQUIPMENT WORKS		<u>TECHNICAL SPECIFICATION -</u> SIZE 1080X1125X2150 MM <u>GENERAL SPECIFICATION -</u> SIZE 1080X1125X2150 MM	
33	DNF64439	SURT 6000 XLI/ELENAS 6KVA	613070514291 8 / UPS 6KVA	OFFICE MACHINERY EQUIP	1 / EACH/NUMBER	EP-H 01		PK	M/S MANSOOR & SONS (PVT) LTD, MEZZANINE FLOOR, PLOT NO. 11-C, STREET NO.28 , TAUHEED COMMERCIAL AREA, PHASE V, DHA KARACHI 75500 TEL: 92-21-35862134 ,35835255		<u>TECHNICAL SPECIFICATION -</u> BAKCUP TIME ONE AND HALF TO TWO HOURS. <u>GENERAL SPECIFICATION -</u> BAKCUP TIME ONE AND HALF TO TWO HOURS.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									FAX:92-21-35861671,35835185 E.MAIL:SHANZ			
34	DNJ64423	93310-836U0	3110765212481 / BEARING	YAMAHA 150 AET,07 (6G47) JAPAN	6 / EACH/NUMBER	150 AET,07 (6G47)	6G4L1024900	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	JAPAN		TECHNICAL SPECIFICATION - SPARE REQUIRED FOR OPS REQUIRMENTGENERAL SPECIFICATION - SPARE REQUIRED FOR OPS REQUIRMENT	
35	DNJ64420	6R5-11633-10	2805765212485 / PIN PISTON	YAMAHA 150AET 07 (6G47) JAPAN	6 / EACH/NUMBER	150AET 07(6G47)	6G4L1024900	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	JAPAN		TECHNICAL SPECIFICATION - SPARE REQUIRED FOR OPS REQUIRMENTGENERAL SPECIFICATION - SPARE REQUIRED FOR OPS REQUIRMENT	
36	DNJ64421	64D-11631-22-90	2815765212444 / PISTON (STD)	150 AET OBM ENGINE	1 / EACH/NUMBER	150AET 07 (6G 47) 1024899	10248996G47	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
37	DNJ64422	64D-11642-22-90	2815765212451 / PISTON 2 (STD)	150 AET OBM ENGINE	1 / EACH/NUMBER	150AET 07 (6G 47) 1024899	10248996G47	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954	YAMAHA MOTOR CO LTD		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
38	DGP64691	50AU7000/46EH5000	7730705174391 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG		TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCHGENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH	
39	DGP64830	50AU7000/46EH5000	7730705174391 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG		TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCHGENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH	
40	DNS64814	8148038	3120270354470 / BEARING SHELL	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	12 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60	AB Volvo Penta Sweden		TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)GENERAL SPECIFICATION -MADADGAR 1009155503(STBD)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
41	DNM64750	3583729/21405494	2815145458943 / DRIVE BELT	PROPULSION AND STEERING SYSTEM /MAIN ENGINE VOLVO D6 370	2 / EACH/NUMBER	NO DATA AVAILAB LE			OC	VOLVO PENTA GOTEBURG SWEDEN	<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
42	DNJ64813	57130-87D10	3110765221607 / BUSH, DRIVE SHAFT	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION -</u> <u>NILGENERAL SPECIFICATION -</u> <u>NIL</u>	
43	DNQ63411	AH0014	4940755204939 / FLAME DECTECTOR	FIRE ALARM AH0014 ITALY	3 / EACH/NUMBER	AH0014	NA	INZM ELECTRONICS 9001:2008 REGD. COMPANY VIA FOSSO ANTICO LOC. CENTOBULCHI 63076 MONTEPRANDONE(AP) ITALY TEL:+39 0735 705007 FAX:+39 0735 704912	INIM ELECTRONICS		<u>TECHNICAL SPECIFICATION -</u> <u>HORING LIH/DRAGER/SENCE-</u> <u>WARE INPUT220V/ 110VAC &</u> <u>24VDC GENERAL SPECIFICATION</u> <u>-_HORING LIH/DRAGER/SENCE-</u> <u>WARE INPUT220V/ 110VAC &</u> <u>24VDC</u>	
44	DNC64812	8M6002465	2910MB0020427 / INJECTOR ASSEMBLY FUEL	PETROL MAIN ENGINE	12 / EACH/NUMBER	VERADO 350 HP	2B614987 2B612137 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		<u>TECHNICAL SPECIFICATION -</u> <u>nullGENERAL SPECIFICATION -</u> <u>null</u>	
45	DPK64112	N28355-1	9150123772290 / OIL SYNTHETIC/L UBRICATING OIL HYDRAULIC (VDL100) OEM = BAUER	HPAC	45 / LITER	NO DATA AVAILAB LE			GR	SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORDHERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDYNAMICS.COM WWW. SMITHSDETECTION. COMGENERAL SPECIFICATION - SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORDHERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDYNAMICS.COM WWW.		

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									221361C COMMENT S@GRAS EBYDYN AMICS. COM WWW. SMITHSD ETECTIO N.COM		SMITHSDETECTION.COM	
46	DPK63858	SAPHIRE LO TEMP 2	9150223091607 / LUBRICANT GREASE (ROCOL SAPHIRE LO TEMP 2) (18KG packing)	LLADR ANTENA	20 / KILOGRAMME			ITW CHEMICAL PRODUCTS SCANDINAVIA APS FORMELY: KEMA A/S ST1: PRIORSVEJ 36 CIT: SILKEBORG CTR: DENMARK PSC: 8600 TEL: 86826444 FAX: 86826464	WUHAN BIN HU ELECTONICS CO. CHINA		<u>TECHNICAL SPECIFICATION - LUBRICATING GREASE</u> <u>GENERAL SPECIFICATION - LUBRICATING GREASE</u>	
47	DGE64848	04769430557, BS2992TABLE8ITEM 8/5	0476599430557 / BRUSH VARNISH TYNEX FIBER FLAT SQUARE EDGE LENGTH 2.5 INCH, THICK 0.750 INCH	DR CL PS. HIN. SE	330 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable <u>GENERAL SPECIFICATION - 2.</u> Dimensions LENGTH 2.5 INCH, THICK 0.750 INCH 3. Shape SQUARE EDGE 4. Packaging Separately packed/ wrapped/ any suitable	
48	DGE64477	0415-9061	0415599231419 / SAFETY WALK THREAD NONMETALIC, NON-SKID, LENGTH= 2- FEET, WIDTH= 6-INCH,		1050 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-feet, Width 6-INCH <u>GENERAL SPECIFICATION - 1.</u> Make / Model / Brand / Equivalent be endorsed: Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-feET, Width 6-INCH	
49	DGP64734	NO DATA AVAILABL E	0051500001403 / Binder Medium F(NS) -101 SIZE 9X12 INCH, Board Texture, Hard & Plyable Thickness 03 mm		154 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION -</u> Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press</p> <p><u>GENERAL SPECIFICATION -</u> Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press</p>	
50	DGB61334	73801/ at-46012/73801	0274502740008 / GUN GREASE	OEM INSIZE GERMANY	5 / EACH/N UMBER	AT-46012					<p><u>TECHNICAL SPECIFICATION -</u> CAPACITY BULK 400 CUBIC CM, STANDARD SIZE 140Z CARTRDGE, METALIC BEND SPOUT 160 MM, HIGH PRESSURE NYLONE HOSE 305 MM VIDE PNS JAUHAR LETTER PN/PNS JAUHAR/03/1323932 DT 05 OCT 18.</p> <p><u>GENERAL SPECIFICATION -</u> CAPACITY BULK 400 CUBIC CM, STANDARD SIZE 140Z CARTRDGE, METALIC BEND SPOUT 160 MM, HIGH PRESSURE NYLONE HOSE 305 MM VIDE PNS JAUHAR LETTER PN/PNS</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											JAUHAR/03/1323932 DT 05 OCT 18.	
51	DNQ63433		024359129583 4 / FIRE EXTINGUISHER CO2 (CARBON DIOXIDE) 2 1/2LB C /W DISCHARGE HORN ASSM	FOR FIRE FIGHTING	79 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS EN -3 GENERAL SPECIFICATION - BS EN -3	
52	DGE64922	bp310	209070050000 1 / CHAIR TUBULAR WHITE PLASTIC SEAT		150 / EACH/NUMBER	bp310					TECHNICAL SPECIFICATION - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand" GENERAL SPECIFICATION - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"	
53	DNH64746	NIL	130876053011 9 / 2 TONS WINDOW A/C -220V (GENERAL USA)	NIL	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA) GENERAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA)	
54	DNH64791	NIL	130876053011 9 / 2 TONS WINDOW A/C -220V (GENERAL USA)	NIL	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA) GENERAL SPECIFICATION - 2 TON A/C -220V (MAKE GENERAL USA)	
55	DGE64577	NO DATA AVAILABLE	047259523774 4 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30* Diameter External dia 74.5 CM – Internal dia 44.5 CM – Thickness 11.5CM Buoyancy Rating:181N. OEM UK/ France likely supplier INDUS SCUBA Clifton at Karachi Contact 0301-2779709 EMAIL: indusscuba.pk@gmail.com GENERAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30*	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Diameter External dia 74.5 CM – Internal dia 44.5 CM – Thickness 11.5CM Buoyancy Rating:181N. OEM UK/ France likely supplier INDUS SCUBA Clifton at Karachi Contact 0301-2779709 EMAIL: indusscuba.pk@gmail.com	
56	DNF64591	BS EN 60317-8	056179439325 2 / WIRE, WINDING COPPER ELECT COND DIA1.400MM O/A DIA 1.506 MM (CLASS- 180) GRADE 2	MOTOR WINDING	200 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM <u>GENERAL SPECIFICATION</u> - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM	
57	DGB51177	NO DATA AVAILABL E	311071505860 3 / ROLLER BEARING NU 232 M/C3 SIZE 160X290X48 MM	D/G SET 800K/W 450V 60HZ	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
58	DNM64702	1.524- 975.0/1. 524.972.0	432072510761 2 / KARCHER MACHINE	KARCHER MACHINE, ALFRED KARCHER CO. GER	2 / EACH/N UMBER	HD 8/18- 4 M* KAR					<u>TECHNICAL SPECIFICATION</u> - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30-180 / 3-18 bar / Mpa Max Pressure :270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch- off, Servo control <u>GENERAL SPECIFICATION</u> - Technical Specifications: Make : Karcher Model: HD 8/18-4 M Current Type: 3 / 400 / 50 Ph / V / Hz Flow Rate : 380-760 l/h Working Pressure: 30- 180 / 3-18 bar / Mpa Max Pressure : 270 / 27 bar / Mpa Max Inlet Temperature: 60 ° C Connected Load: 4.6 kW General Specifications: Equipment: Spray gun, High pressure hose, power nozzle, Pressure switch-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											off, Servo control	
59	DNF64820	MD231 (CROWN) /EH1504 /EH1418	4440795102544 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM	DEHUMIDIFIERS	7 / EACH/NUMBER	MD231 (CROWN) /EH1504/ EH1418					<u>TECHNICAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG <u>GENERAL SPECIFICATION -</u> Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 l/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG	
60	DNH64818		4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	20 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	DNM64811		3230731001865 / BLADE POWER HACKSAW HSS 18X1-1/4X1/16INX6TPI		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE <u>GENERAL SPECIFICATION -</u> Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE	
62	DGP64715	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHRED MASTER)		14 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> <u>TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.<u>GENERAL SPECIFICATION - TECHNICAL</u></p> <p>SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p>	
63	DGP648 26	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - TECHNICAL</u></p> <p>SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.<u>GENERAL SPECIFICATION - TECHNICAL</u></p> <p>SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
64	DGE64571		533070500725 2 / RUBBER BLANKET 04 PLY		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 1.</u> Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine) <u>GENERAL SPECIFICATION - 1.</u> Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine)	
65	SNM47236	1345958, OLD PN 4W1596	533101208757 9 / SEAL O RING (4W 1596)	3512 M/ENGINE, VALVE MECH. COVER GP-12	28 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - oem:</u> caterpillar <u>GENERAL SPECIFICATION - oem:</u> caterpillar	
66	DNF64699	158-51010	596199558030 7 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
67	DNF64722	PP3 , 6F22, (6135-00-900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.</u> <u>GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.</u>	
68	DPK64739	Mobilux EP2	961179017039 6 / Mobilux Grease EP2 (16 OR 18 Kg Packing)		32 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
69	DNF64661	390DCS/2	803077501631 0 / DEGREASER CLEANER, SOLVENT NON OILY (200ML)	PCB CLEAN MATERIAL (M/S PERFECT BELGIUM)	2 / EACH/NUMBER		390DCS/00				<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
70	DGE64511	NO DATA AVAILABL	041350000019 0 / TUBING		1120 / METER		NO DATA AVAILAB				<u>TECHNICAL SPECIFICATION - Size: Wall Thick: 2.5mm. Length of</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		E	PLASTIC TRANSPARENT(G/USE) O/D 32MM I/D 27MM TH.2.5 MM, LENGTH (MIN) 50 METER, MATERIAL: PLASTIC GRADE-1			LE					Tube: 50ft Spec: 5039 pg 99 s: P.P. INV 1991 <u>GENERAL SPECIFICATION</u> - Size: Wall Thick: 2.5mm. Length of Tube: 50ft Spec: 5039 pg 99 s: P.P. INV 1991	
71	DPK64527	H 572	9150992203468 / OIL OM 65 (Packing = 05 liters)	30MM GUN	330 / LITER						<u>TECHNICAL SPECIFICATION</u> - bs-4475 of 2000 grade cs 68 defstan 01-5/issue 17 mar 11 200 Ltr drum <u>GENERAL SPECIFICATION</u> - bs-4475 of 2000 grade cs 68 defstan 01-5/issue 17 mar 11 200 Ltr drum	
72	DPK63594	J2360/MOBIL 85W/140	9150010355392 / MOBIL HD OIL SAE (85W-140) GL-5 (Packing 04 Liter)	USE FOR DIESEL ENGINE	112 / LITER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
73	DGE64432	NO DATA AVAILABLE	7330701002289 / WATER COOLER PLASTIC 20 LTR(BRAND RAHBAR/INDUS/JOY0).		98 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - WITH FULLCOVER <u>GENERAL SPECIFICATION</u> - WITH FULLCOVER	
74	DPK64232	XG-279, G-403 (DEFSTAN 91-27 ISSUE 2 OF 2011	9150992202418 / GREASE AUTOMOTIVE & ARTILLERY XG-279 (G-403) (Packing 3KG TIN)		21 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - Composition: low viscosity mineral OI8L and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TIN <u>GENERAL SPECIFICATION</u> - Composition: low viscosity mineral OI8L and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TIN	
75	DPK64222	G-32	9150795024119 / SHELL HIGH QUALITY REFRIGRATOR OIL S2FR-A46	REFRIGERANT COMPRESSOR OIL	209 / LITER						<u>TECHNICAL SPECIFICATION</u> - REFRIGERATOR OIL GROUP: DIN 51503, KAA, KCG <u>GENERAL SPECIFICATION</u> - REFRIGERATOR OIL GROUP: DIN 51503, KAA, KC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
76	DNQ64106	005101010	841599130487 4 / HOOD, ANTIFLASH..	DC LOCKER	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. <u>GENERAL</u> <u>SPECIFICATION -</u> OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T:+44(0) 2889521401 F:+44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
77	DNF64721	ep- 1000t/blaz er vista 1000	703570505992 7 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	5 / EACH/N UMBER	BLAZER VISTA 1000/Auro ra					<u>TECHNICAL SPECIFICATION -</u> backup time: 10 minutes Product Name: AURORA Input: 220V <u>ACGENERAL SPECIFICATION -</u> backup time: 10 minutes Product Name: AURORA Input: 220V AC	
78	DNJ62760		234071512794 7 / WATER SCOOTER WITH STOWAGE TROLLEY AND RAIN PROTECTING COVER	WATER SCOOTER VX- 1100 SPORTS	1 / EACH/N UMBER	VX1050E- A /VX- 1100 SPORTS					<u>TECHNICAL SPECIFICATION -</u> COLOR: CYAN WITH BLACK LENGTH: 3.37 M WIDTH: 1.24 M HEIGHT:1.20 DRY WEIGHT: 310 ENGINE TYPE: 3-CYLINDER,4 STROKE TR-1 HIGH OUTPUT YAMAHA MARINE ENGINE DISPLACMENT: 1049 CC BORE x STROKE(mm): 82 x 66.2 COMPRESSION RATIO:11.0 :1 COOLING SYSTEM : WATER COOLED PUMP TYPE : 155MM AXIAL FLOW FUEL TYPE RECOMMENDED : REGULAR UNLEADED FUEL SUPPLY SYSTEM: ELECTRONIC FUEL INJECTION FUEL CAPACITY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(LITER): 70 LUBRICATION SYSTEM: DRY SUMP TOTAL OIL CAPACITY (LITER) : 3.5 STORAGE CAPACITY (LITER): 113.9 RIDER CAPACITY:1-3 PERSONS MODEL YEAR :2024 DISPLACMENT:1049 CC,4 STROKE <u>GENERAL SPECIFICATION - COLOR: CYAN WITH BLACK LENGTH: 3.37 M WIDTH: 1.24 M HEIGHT:1.20 DRY WEIGHT: 310 ENGINE TYPE: 3-CYLINDER,4 STROKE TR-1 HIGH OUTPUT YAMAHA MARINE ENGINE DISPLACMENT: 1049 CC BORE x STROKE(mm): 82 x 66.2 COMPRESSION RATIO:11.0 :1 COOLING SYSTEM : WATER COOLED PUMP TYPE : 155MM AXIAL FLOW FUEL TYPE RECOMMENDED : REGULAR UNLEADED FUEL SUPPLY SYSTEM: ELECTRONIC FUEL INJECTION FUEL CAPACITY (LITER): 70 LUBRICATION SYSTEM: DRY SUMP TOTAL OIL CAPACITY (LITER) : 3.5 STORAGE CAPACITY (LITER): 113.9 RIDER CAPACITY:1-3 PERSONS MODEL YEAR :2024 DISPLACMENT:1049 CC,4 STROKE</u>	
79	DNH64745	NO DATA AVAILAB LE	1308500530126 / DEEP FREEZER 12 CUFT 220 V AC WAVES		1 / EACH/ NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILAB LE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILAB LE</u>	
80	DGP62311	NO DATA AVAILAB LE	0050500000214 / Paper Printing Computer NCR Paper 2 PLY		85000 / SHEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE: LENGTH: 12 INCH WIDTH: 9 INCH WEIGHT: 50 GSM + 5% PACKING: 1000 SHEETS IN EACH CARTON</u> <u>GENERAL SPECIFICATION - SIZE: LENGTH: 12 INCH WIDTH: 9 INCH WEIGHT: 50 GSM + 5% PACKING: 1000 SHEETS IN EACH CARTON</u>	
81	DGP623	NO DATA	005050000021	FAN FOLDED	85000 /	NO DATA					<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	13	AVAILABLE	5 / PAPER PRINTING COMPUTER WHITE NCR PAPER 3PLY FAN FOLDED SPOCKE	SPOCKET ON BOTH SIDES	SHEET	AVAILABLE					SIZE: LENGTH: 241 MM WIDTH: 305 MM WEIGHT: GSM 50 + 5% FAN FOLDED SPOCKET ON BOTH SIDES PACKING: 1000 SHEETS IN EACH BOX <u>GENERAL SPECIFICATION</u> - SIZE: LENGTH: 241 MM WIDTH: 305 MM WEIGHT: GSM 50 + 5% FAN FOLDED SPOCKET ON BOTH SIDES PACKING: 1000 SHEETS IN EACH BOX	
82	DGP62315	NO DATA AVAILABLE	0050500000218 / PAPER PRINTING COMPUTER WHITE SIZE381X280MMNCRPAPER2PLY(F8)		165000 / SHEET	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - SIZE: LENGTH: 381 MM WIDTH: 280 MM WEIGHT: 52 GSM + 5% PACKING: 1000 SHEETS IN EACH BOX <u>GENERAL SPECIFICATION</u> - SIZE: LENGTH: 381 MM WIDTH: 280 MM WEIGHT: 52 GSM + 5% PACKING: 1000 SHEETS IN EACH BOX	
83	SNM62489	EOCR	5999765126454 / ELECTRONIC OVER LOAD I/P 220V 6A (GREEN POWER)	AIR COND SYS CWM-2C70-PN JAPAN	30 / EACH/NUMBER	CWM-2C70-PN FUJI JAPAN					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
84	DNM57197	HD 6/15 m	7910725118904 / KARCHER COLD WATER HIGH PRESSURE CLEANER WITH		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - 220-440V/ 60Hz <u>GENERAL SPECIFICATION</u> - 220-440V/ 60Hz	
85	DGE64709	IACD42106 or CITEXH-1140	4240995275985 / SAFETY HARNESS (100% POLYESTER WITH BUCKLES & D-RING	PPE	72 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - MATERIAL: 100% POLYESTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH: >=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Specification may be endorsed to avoid complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN. <u>GENERAL SPECIFICATION - MATERIAL:</u> 100% POLYSTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH: >=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Specification may be endorsed to avoid</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN.	
86	DGE649 51	CTLBS122 02003	534073526740 9 / BASE 4' (1220 X 200 X 3MM)		96 / FOOT RUN	BASE 4' CTLBS12 202003					<u>TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS</u> <u>GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS</u>	
87	DGE649 31	CTLCB100 08025	534073526741 0 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		72 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10 008025					<u>TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS</u> <u>GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS</u>	
88	DSB6360 3	201395	623014481901 2 / FPN TYPE PORTABLE LIGHT CELLS		22 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
89	DNM645 81	JL269	668570523837 9 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
90	DNM642 34	JL269	668570523837 9 / PORTABLE GAS DETECTOR		3 / EACH/NUMBER	JL269					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
91	DNM64262	JL269	6685705238379 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
92	DNM64382	JL269	6685705238379 / PORTABLE GAS DETECTOR		1 / EACH/NUMBER	JL269					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
93	DNF64833	EL-ETHS-200	2990715277944 / ANTI CONDENSATION HEATER FOR DG PERKIN		3 / EACH/NUMBER	EL-220					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
94	DNC64749	TM-C-S02	2520735237682 / CARDAN SHAFT		4 / EACH/NUMBER	HJ322					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
95	DNF64261	03-00-0623-00	6350715300703 / DAS BOARD 3.2		1 / EACH/NUMBER	1.2 XIS-6545					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
96	DNJ64383	6D8-43880-01	6105765265003 / MOTOR ASSY		1 / EACH/NUMBER	F90BETL					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
97	DGP64828	CORE I5	7025705246091 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5					<u>TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											requiredGENERAL SPECIFICATION _CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
98	DGP64351	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					TECHNICAL SPECIFICATION - CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window requiredGENERAL SPECIFICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											_CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
99	SNM62492	2654408	2940705246596 / lubricating oil filter		10 / EACH/NUMBER	3-2500					<u>TECHNICAL SPECIFICATION - MAKE: PERKINS</u> <u>GENERAL SPECIFICATION - MAKE: PERKINS</u>	
100	DSA62276	FC039	5950TY6720062 / CAISSON DETRAITEMENT D AIR ECHANGEUR		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - type: 1000 h refrigerating power b/w-10 Cet + 25 c: 25000 Kcel/h gas orifice diameter: 2-1/8" odf overall length: 432 mm theoretical dia: 66 mm liquid orifice dia: 7/8" odf</u> <u>GENERAL SPECIFICATION - type: 1000 h refrigerating power b/w-10 Cet + 25 c: 25000 Kcel/h gas orifice diameter: 2-1/8" odf overall length: 432 mm theoretical dia: 66 mm liquid orifice dia: 7/8" odf</u>	
101	DNF64849	RSFD-II	6135785284717 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		5 / EACH/NUMBER	RSFD-II					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
102	DNF64392	877621-031	5998735292303 / HPE ProLiant ML350		1 / EACH/NUMBER	ML350 Gen10					<u>TECHNICAL SPECIFICATION - Processor type: Intel® Xeon® Scalable processors, 1st and 2nd</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Gen10 XEON SILVER 4110 - 2.1GHZ 16GB NO HDD HOT-SWAP 2.5 - TOWER server								generations Processor name: Intel® Xeon® Scalable processors, 1st or 2nd generation Processor family 1st generation: Intel® Xeon® Scalable 8100 series, Intel® Xeon® Scalable 6100 series, Intel® Xeon® Scalable 5100 series, Intel® Xeon® Scalable 4100 series, Intel® Xeon® Scalable 3100 series 2nd generation: Intel® Xeon® Scalable 8200 series, Intel® Xeon® Scalable 6200 series, Intel® Xeon® Scalable 5200 series, Intel® Xeon® Scalable 4200 series, Intel® Xeon® Scalable 3200 series <u>GENERAL SPECIFICATION -</u> Processor type: Intel® Xeon® Scalable processors, 1st and 2nd generations Processor name: Intel® Xeon® Scalable processors, 1st or 2nd generation Processor family 1st generation: Intel® Xeon® Scalable 8100 series, Intel® Xeon® Scalable 6100 series, Intel® Xeon® Scalable 5100 series, Intel® Xeon® Scalable 4100 series, Intel® Xeon® Scalable 3100 series 2nd generation: Intel® Xeon® Scalable 8200 series, Intel® Xeon® Scalable 6200 series, Intel® Xeon® Scalable 5200 series, Intel® Xeon® Scalable 4200 series, Intel® Xeon® Scalable 3200 series	
103	DNF64824	J9776A/r8n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
104	DNO64850	hr1234wf2/ WP 1236W-LONG	614001618242 1 / BATTERY, RECHARGABLE (12V, 34W)		5 / EACH/NUMBER	8GSYBTU					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
105	DNF64391	06jgt5	705072527928 6 / intel ssd 480gb sata 2.5" dell emc (6 Gbps)		3 / EACH/NUMBER	ssdsc2kg480g8r					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
106	DNF64720	AA2500mah	6140715281910 / battery pack rechargeable NIMH (pack of 4) DURACELL AA 2500MAH		100 / PACKAGE	AA2500MAH					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
107	DGE64921	CTLCS15011016	5340735267412 / CROSS (1500 X 1100 X 1.6MM)		40 / EACH/NUMBER	CROSS CTLCS15011016					TECHNICAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
108	DGE64693	large 94.2 ltrs 300 plus	8115705259597 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
109	DGE64656	large 94.2 ltrs 300 plus	8115705259597 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM)	
110	DGE64452	large 94.2 ltrs 300 plus	8115705259597 / coleman ice boxes or EQUIVALENT (LARGE) 94.2 LTRS 300 (PLUS)		6 / EACH/NUMBER						TECHNICAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3 CM) GENERAL SPECIFICATION - large handle with wheels, both sides handles 94.6 ltrs size (length 35" WIDTH 17" HEIGHT 17" WALL THICKNESS 3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CM)	
111	DNF62283	NCB-FS09D-LCSC-5	5995705246355 / D-LINK SC-LC SINGLEMODE Os2 DUPLEX PATCH CORD 5M		5 / EACH/NUMBER	NCB-FS09D-LCSC-5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
112	DNF57823	Winner pro 2K	6150TA5249657 / UPS 2KVA (10 minuts backup time)		2 / EACH/NUMBER	Winner pro 2K					<u>TECHNICAL SPECIFICATION - UPS APC 2 KVA with access 2 KVA AT LEAST 10 MINUTE BACKUP TIME WITH full load (2 KVA) Complete Details regarding 2KVA & 1KVA UPS are avialable in the attached Brochure named "WinnerPro"</u> <u>GENERAL SPECIFICATION - UPS APC 2 KVA with access 2 KVA AT LEAST 10 MINUTE BACKUP TIME WITH full load (2 KVA) Complete Details regarding 2KVA & 1KVA UPS are avialable in the attached Brochure named "WinnerPro"</u>	