

## TENDER BULLETIN

DATE & TIME 6/5/24 1:58 PM

INVITATION TO TENDER TO BE OPENED ON 6/24/2 10:00 AM

AND ITEM REQ BY

**CONDITIONS**

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNM54876	5N9359 (3040-01-203-0160)	3040715035130 / SHAFT, SHOULDERED OA-LG168MM-COLLAR-DIA34.8MM SPLINED ENDED	INDUSTRIEL MARINE CATTER PILLER D/G	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended</u> <u>GENERAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spline Ended</u>	
2	DGP64092	50AU7000/46EH5000	7730705174391 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG		<u>TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u> <u>GENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u>	
3	DGP64161	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		10 / EACH/NUMBER						<u>TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u> <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											security, 4. DIMENSIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
4	DGP64154	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		3 / SET	CORE I5				Delivery required at islamabad	<p><u>TECHNICAL SPECIFICATION -</u>  CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required</p> <p><u>GENERAL SPECIFICATION</u>  -CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED /</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
5	DGP64095	CORE I5	702570524609 1 / PERSONAL COMPUTER (CORE: I5)		2 / SET	CORE I5					<u>TECHNICAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i. Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required <u>GENERAL SPECIFICATION -</u> CPU Technology: Intel Core i5 (12th Gen or above) (Minimum 3 ghz, 6MB, 4 Core) System Memory: MINIMUM 8 GB DDR4 SDRAM Hard Disk 1 TB SATA/ SSD Optical Disk Drive: DVD RW Keyboard: USB 3d Optical Mouse: USB Optical LED: Minimum 18.5" HDMI DISPLAY LAN: Built In 10/100/1000 Warranty: MINIMUM 01 Year (OEM) Operating System: Windows 10 or above (LICENSED) GRAPHICS: INTEL r HD GRAPHICS ,(MINIMUM 2 GB SHARED / DEDICATED GRAPHIC CARD i.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Authorized Dealer COC required ii. OEM sealed packed PCs iii. Certificate of Genuineness required iv. Online Warranty required v. Online verification required vi. PCs Without any modification/ up-gradation vii. Genuine licensed window required	
6	DGP64098	G2102560EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		12 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - TECHNICAL</u>  SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p> <p><u>GENERAL SPECIFICATION - TECHNICAL</u>  SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p>	
7	DGP64156	NHQ APPROVED MODEL	7535705133021 / LAPTOP COMPUTER AS PER NHQ APPROVED MODEL (HP/DELL/LENOVO)	COMPUTER	1 / EACH/NUMBER	NO DATA AVAILAB LE		PK	VIDE NHQ LETTER ST-S/3200/8198 DT 23/07/08		<p><u>TECHNICAL SPECIFICATION - HP/DELL/LENOVO LAPTOP. S NO</u>  COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ)). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5. OPTICAL DISK</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION). <u>GENERAL SPECIFICATION -</u> HP/DELL/LENOVO LAPTOP. S NO COMPONENTS SPECIFICATION 1. CPU TECHNOLOGY: INTEL® CORE I5 (10TH GENERATION OR ABOVE (MINIMUM 2.3 GHZ). 2. SYSTEM MEMORY: 8 GB DDR3/DDR4. 3. DISPLAY: 15.6" LED. 4. HARD DISK: 500 gb ssd. 5 OPTICAL DISK DRIVE: DVD-RW 6. WEBCAM: YES 7. GRAPHICS: INTEL ® HD/HD GRAPHICS. 8. WIRELESS CONNECTIVITY: YES 9. BLUETOOTH: YES 10. WARRANTY: 01 YEAR 11. OPERATING SYSTEM: WINDOWS (LICENSED VERSION).	
8	DGP64166	4003DN	743570513863 2 / PRINTER HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN	COMPUTER	2 / EACH/ NUMBER	NO DATA AVAILAB LE		PK		PAKISTA N	<u>TECHNICAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both <u>GENERAL SPECIFICATION -</u> Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both	
9	DNM59011	54043-2 (S.NO 45225188)	293070513302 0 / RADIATOR ASSEMBLY	MOBILE DG 250KW	2 / EACH/ NUMBER	6CT8.3	23224/8	PK	PAK MEHRAN RADIATO R HOUSE SHAHAD AT CENTER	Local Source of Availability: M/s Agrico Internationa l 6 Saghir	<u>TECHNICAL SPECIFICATION - a.</u> Make. Millat Tractor Lahore b. Model. 32500 c. Brand. Millat Tractor Radiator Lahore <u>GENERAL SPECIFICATION - a.</u> Make. Millat Tractor Lahore b. Model. 32500 c. Brand. Millat Tractor Radiator Lahore	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
										Hussain Shaheed Road, Saddar Karachi Tel 92-21-32226337 & 32224987 Mobile: 0334-4504000 Email agrico786@gmail.com & agrico785@yahoo.com Web: www.agrico.com.pk		
10	DNF50499	J9776A/r8n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
11	DNH64133		411070511157 1 / WATER DISPENSER	WATER COOLER (SUNNY/MECO)	10 / EACH/NUMBER	WA60000514					<u>TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W</u> <u>GENERAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420 W Cooling Power 100 W</u>	
12	DGP53434	G2102560EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATIONS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.<u>GENERAL SPECIFICATION - TECHNICAL</u></p> <p>SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p>	
13	DNM47272	ST43729	5306795102511 / BOLT	3012/CV12, CYLINDE BLOCK, PERKIN,UK	12 / EACH/NUMBER	3012 TAG1A					<p><u>TECHNICAL SPECIFICATION -</u> Brand/ Rating: 600 KVA Perkins DG MAKE: PERKINS UK local supplier: sm jaffer &amp; co keamari karachi<u>GENERAL SPECIFICATION -</u> _Brand/ Rating: 600 KVA Perkins DG MAKE: PERKINS UK local supplier: sm jaffer &amp; co keamari karachi</p>	
14	DNF64105	VM-1120A TOA	5835765013358 / AMPLIFIER 100/120W,TOA JAPAN	PA SYSTEM	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	
15	DGH54491	NO DATA AVAILAB LE	5610705061098 / PORTA CABIN 20X8FT SEA CONTAINER FULLREFUR BISHED TO SUIT		1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - a.</u> Dimension: 20 x 08 feet Sea Container b. Material: Thermopole or any heat/ electric insulating material c. Fixtures: Cabinets Racks Working desks Office Furniture 01 x Fan in each partition Lighting Facility d. Separation / Partition: Yes e. Windows: 01 x in each partition f. Doors: 01 x in each partition (with lock and and keys) g. Flooring: Wooden or any insulator h. Power</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Supply Sockets for office machinery and Air Conditioner supported j. Pictures Enclosed <u>GENERAL SPECIFICATION</u> - a. Dimension: 20 x 08 feet Sea Container b. Material: Thermopole or any heat/ electric insulating material c. Fixtures: Cabinets Racks Working desks Office Furniture 01 x Fan in each partition Lighting Facility d. Separation / Partition: Yes e. Windows: 01 x in each partition f. Doors: 01 x in each partition (with lock and and keys) g. Flooring: Wooden or any insulator h. Power Supply Sockets for office machinery and Air Conditioner supported j. Pictures Enclosed	
16	DNF62165	158-51010	5961995580307 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
17	DNF62013	158-51020	5961995580314 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAHI)	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
18	DNF62166	158-51020	5961995580314 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAHI)	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
19	DNF46775	SAIGA 5C-2V	5995785110611 / COAXIAL CABLE 75 OHM	V/UHF AMPLIFIER (WINNER SAT WA680)	200 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
20	DNF58665	NO DATA AVAILABLE	6130705064740 / UPS 1.5 KVA		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - BACKUP TIME 50 MINUTES FOR 1X PC Make: APC Model: 1500VA Specs: APC Smart UPS, Line interactive, 1500 VA, Tower, 230V, 8x IEC C13 outlets, Smart connect, Port+smart slot, AVR, LCD <u>GENERAL SPECIFICATION</u> - BACKUP TIME 50 MINUTES FOR 1X PC Make: APC Model: 1500VA Specs: APC Smart UPS, Line	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											interactive, 1500 VA, Tower, 230V, 8x IEC C13 outlets, Smart connect, Port+smart slot, AVR, LCD	
21	DNF58402	2000VA STABIMATIC/APC	6130715117506 / UPS 2KVA	SELF END USE	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - "back up time of subject UPS" is required for 15 TO 20 minuit back up time</p> <p><u>GENERAL SPECIFICATION</u> - "back up time of subject UPS" is required for 15 TO 20 minuit back up time</p>	
22	DNF62097	040020500	6130775095617 / AUTOMATIC BATTERY CHARGER.I/P 220/240V,8.5A, O/P28.5VDC, 50AMP	TYPE MASS24/50, WHEEL HOUSE DESK, JOSHILA	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
23	SNF12605	PM100 (5965-98-204-2848)	5965705054986 / PUSH TO TALKMICROPHONEIMPEDANCE150 OHM (PM-100) TOA JAPAN	INSTALLATION OF TWO WAY COMMUNICATION SY	4 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
24	DGP57856		7530705007179 / PAPER COVER YELLOW GSM 125+5% REAM OF 500SHEETB-02 500X707MM		50 / REAM						<p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE</p> <p><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>	
25	DGE62738	NO DATA AVAILABLE	0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	507 / KILOGRAMME	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION</u> - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) <u>GENERAL SPECIFICATION</u> - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											, WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
26	DGD24752		773070504803 8 / DISH FLAT RICE 12 INCH BLUE CRESTED		30 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - DISH FLAT RICE 12 INCH (BLUE CRESTEDS) MATERIAL PORCELAIN FOOD GRADE REGAL CHINA)</u> <u>GENERAL SPECIFICATION - DISH FLAT RICE 12 INCH (BLUE CRESTEDS) MATERIAL PORCELAIN FOOD GRADE REGAL CHINA)</u>	
27	DGD49040		773070504807 8 / CUP TEA BLUE CRESTED		55 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM</u> <u>GENERAL SPECIFICATION - Cup Tea Blue PN Crest and shell on edge of cup. Material porcelain, Size: Dia 9CM, depth 6CM, Height 7 CM</u>	
28	DNF61471	PANASONIC VACUUM CLEANER / 7540	791073100184 5 / VACCUM CLEANER HEAVY DUTY 220V 1300W 50HZ MODEL MC-CL443	IT SELF	1 / EACH/NUMBER	7540 JAPAN					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
29	DNF61699	390DCS/2	8030775016310 / DEGREASER CLEANER, SOLVENT NON OILY (200ML)	PCB CLEAN MATERIAL (M/S PERFECT BELGIUM)	2 / EACH/NUMBER	390DCS/00					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
30	SGT52773	NO DATA AVAILAB LE	010050000008 6 / PLY WOOD GD-I, 9PLY (CORE AND INNER PLIES OF POPLAR AND BOTH FACE & BACK VENEER OF GURJAN 0.6 MM) TYPE OF		550 / SQ FEET	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE LENGTH 8FEET WIDTH 4FEET THICKNESS 19MM</u> Specification 1. Moisture tent BS EN 322 : 1993 2. Bonding quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993 <u>GENERAL SPECIFICATION - SIZE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BOND INT								LENGTH 8FEET WIDTH 4FEET THICKNESS 19MM Specification 1. Moisture tent BS EN 322 : 1993 2. Bonding quality BS 314-1 : 2004 and BS EN 314-2: 1993 3. Glue BS 1203 : 1979 4. Preservation BS 4072 : 1999 5. Physical evaluation BS 6566-6 : 1985 6. Density BS EN 323 : 1993	
31	DNH64096	NO DATA AVAILABLE	4110500530125 / REFRIGE 12CU/FT DOUBLE DOOR 220V 50 HZ PHILCO/DAWLANCE/WAVES/ PEL	DAWLANCE, WAVES, PHILICO (PAKISTAN), PEL (PAK)	1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
32	DGP57845		7510701005039 / UV Flexo Ink (Black Colour)		100 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4. silian brand ink</u> <u>PROPERTIES/CHARACTERISTICS:</u> 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR. DENOMINATION : PACKING TO BE PROVIDED IN LOWEST DENOMINATION OF KGS AS INK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP. <u>GENERAL SPECIFICATION -</u> MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4. silian brand ink</p> <p>PROPERTIES/CHARACTERISTICS: 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR.</p> <p>DENOMINATION : PACKING TO BE PROVIDED IN LOWEST DENOMINATION OF KGS AS INK GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP.	
33	DNF53398	9155/9355 UPS 8-15KVA	7025795057057 / UPS 15KVA (CPS15-A31) 0.8 POWER FACTOR I/P380-415V O/P220-240V	15KVA POWERWARE UPS	1 / EACH/NUMBER					newspaper	TECHNICAL SPECIFICATION - OVERLOAD ON INVERTER: 10 min 100-110%; 1min 110-125%; 5 sec 125-150%; 300 ms>150% BACKUP TIME 02 HOURS.GENERAL SPECIFICATION - OVERLOAD ON INVERTER: 10 min 100-110%; 1min 110-125%; 5 sec 125-150%; 300 ms>150% BACKUP TIME 02 HOURS.	
34	DNF54938	1500VA APC	7035PK5071980 / UPS 1.5 KVA WITH ACCESSORIES	USE END SELF	1 / EACH/NUMBER	APC					TECHNICAL SPECIFICATION - BACKUP OF UPS TIME IS MINIMUM 25-30 MINUTES. GENERAL SPECIFICATION - BACKUP OF UPS TIME IS MINIMUM 25-30 MINUTES.	
35	DNF57273	SMT3000I C/SURTD3000XLI/3000VA APC	6130715063823 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
36	DNF57962	SMT3000I C/SURTD3000XLI/3000VA APC	6130715063823 / UPS 3KVA APCI/P220V	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E)					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		00VA APC	O/P220V W/BATTERY BACKUP 25 MINUTES.			/SYSTEK PVT.					OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
37	DNF58184	SMT3000I C/SURTD3 000XLI/30 00VA APC	613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
38	DNF58974	SMT3000I C/SURTD3	613071506382 3 / UPS 3KVA	SELF	1 / EACH/N	MODEL ESP-808					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		000XLI/3000VA APC	APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.		UMBER	(E) /SYSTEK PVT.					WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
39	DNF59081	SMT3000I C/SURTD3 000XLI/3000VA APC	613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/NUMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
40	DNF4355	SUA1000I/	613070509030	UPS	5 /	APC					TECHNICAL SPECIFICATION - NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	3	APC BRAND	1 / UPS OF APC BRAND 240V 1000VA BBACKUP TIME 1-1.30 HOURS		EACH/N UMBER	BRAND					DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
41	DGP43668	NO DATA AVAILAB LE	0050500000114 / PAPER, TYPING, LARGE, GSM40±5%, WHITE, REAMOF500S HEET, SIZEA-04 210X297MM.		408 / REAM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
42	DNF61696	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	10 / EACH/N UMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	
43	DNF57280	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	17 / EACH/N UMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES.	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	
44	SNF56575	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	3 / EACH/NUMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
45	DNF61316	NO DATA AVAILABL E	0565780000059 / FAN TABLE FB300 24Z 18T		8 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
46	DGD48749	NO DATA AVAILABL E	0031500000039 / CUP TEA BREAK FAST 7 OZS GOLDEN CREST( AS PER STOCK SAMBLE)		201 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MATERIAL: PORCELIN GENERAL SPECIFICATION - MATERIAL: PORCELIN	
47	SGB60215	NO DATA AVAILABL E	0283595791150 / ALUMINIUM PLATE (7ft 6inch X 3ft 9inch X 6mm)		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Item Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING FIRM. GENERAL SPECIFICATION - Item Specification: BS:EN 573-3/1995 GRADE EN.AW.5083 MAY PLEASE BE ENDORSED BS:EN 485-2 ALSO. LAB TESTING CHARGES RS:5200/- WILL BE BORNE BY SUPPLYING FIRM.	
48	DNF58403	GPMS-10 KVA (CHINA)	5975785274915 / AUTOMATIC VOLTAGE STABLIZER 10 KVA		1 / EACH/N UMBER	N/A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
49	DRG49179	GP-123	2810ZO5238491 / GP-123 Complete with Accessories		10 / EACH/N UMBER	GP-123 Engine				newspaper	TECHNICAL SPECIFICATION - GP-123 Twin Cylinder 123cc Engine gen specs: Package Include: • GP-123 Engine • Hub Set (Hub + Hub Screw) • Propeller Plate • Carburetor Set (WJ71S Carburetor Throttle Arm (2Peices)) • Reed Valve Set Combo • Muffler Kit (2xMuffler with Gasket) • Twin Ignition • Hall Sensor • 2xNGK CM6 Spark Plugs • Magnet GENERAL SPECIFICATION - GP-123 Twin Cylinder 123cc Engine gen specs: Package Include: • GP-123 Engine • Hub Set (Hub + Hub Screw) • Propeller Plate • Carburetor Set	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(WJ71S Carburetor Throttle Arm (2Peices)) • Reed Valve Set Combo • Muffler Kit (2xMuffler with Gasket) • Twin Ignition • Hall Sensor • 2xNGK CM6 Spark Plugs • Magnet	
50	DNF58584	GXT4-10KRT230E	5975715267407 / EMERSON LIBERT GXT 10KVA UPS WITH BATTERIES (STANDARD BACKUP)		1 / EACH/NUMBER	EMERSON LIEBERT GXT4 10KVA UPS					<p><u>TECHNICAL SPECIFICATION - A.</u>  MAKE / MODEL: EMERSON LIEBERT GXT4 10 KVA UPS B. UPS PART NUMBER / MODEL: GXT4-10KRT230E C. POWER RATINGS (VA/W):10000 VA / 9000 W INPUT AC PARAMETERS D. VOLTAGE RANGE (VAC): 176 - 280 E. FREQUENCY RANGE (HZ): 40~70; AUTO SENSING F. INPUT SOCKET: HARDWIRED INPUT ON PD2-CE10HWRMBS STANDARD POWER DISTRIBUTIONS BOX G. OUTPUT SOCKETS: 4 X IEC320-C13 + 4 X IEC320-C19 +HARDWIRED ON PD2-CE10HWRDMBS STANDARD POWER DISTRIBUTION H. VOLTAGE (V): 230 FACTORY DEFAULT J. WAVEFORM: PURE SINEWAVE BATTERY PARAMETERS K. TYPE: VALVE-REGULATED, NON-SPILLABLE, LEADACID L. QUANTITY X VOLTAGE X RATING: 20 X 12 V X 5 AHR 20 X 12 V X 9 AHR M. RECHARGE TIME: 5 HOURS TO 90% CAPACITY AFTER FULL DISCHARGE WITH 100% LOAD ENVIRONMENTAL N. OPERATING: 0° C - TO +40°C (+32°F TO +104°F) (NO DERATING) P. RELATIVE HUMIDITY: 0% RH TO 95% RH, NON-CONDENSING Q. OPERATING ALTITUDE: UP TO 1000M (3281FT) AT 25°C (77°F) WITHOUT <u>GENERAL SPECIFICATION - A.</u> MAKE / MODEL: EMERSON LIEBERT GXT4 10 KVA UPS B. UPS PART</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NUMBER / MODEL: GXT4-10KRT230E C. POWER RATINGS (VA/W):10000 VA / 9000 W INPUT AC PARAMETERS D. VOLTAGE RANGE (VAC): 176 - 280 E. FREQUENCY RANGE (HZ): 40~70; AUTO SENSING F. INPUT SOCKET: HARDWIRED INPUT ON PD2-CE10HDWRMBS STANDARD POWER DISTRIBUTIONS BOX G. OUTPUT SOCKETS: 4 X IEC320-C13 + 4 X IEC320-C19 +HARDWIRED ON PD2-CE10HWRDMBS STANDARD POWER DISTRIBUTION H. VOLTAGE (V): 230 FACTORY DEFAULT J. WAVEFORM: PURE SINEWAVE BATTERY PARAMETERS K. TYPE: VALVE-REGULATED, NON-SPILLABLE, LEADACID L. QUANTITY X VOLTAGE X RATING: 20 X 12 V X 5 AHR 20 X 12 V X 9 AHR M. RECHARGE TIME: 5 HOURS TO 90% CAPACITY AFTER FULL DISCHARGE WITH 100% LOAD ENVIRONMENTAL N. OPERATING: 0° C - TO +40°C (+32°F TO +104°F) (NO DERATING) P. RELATIVE HUMIDITY: 0% RH TO 95% RH, NON-CONDENSING Q. OPERATING ALTITUDE: UP TO 1000M (3281FT) AT 25°C (77°F) WITHOUT</p>	
51	DSB57613	GSM 1487 DET-7 (39679)	473014305908 1 / PLANE FLANGE		70 / EACH/NUMBER	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION</u> - a. Material - Mild Steel b. Dia - DE 76.1 mm c. Testing Pressure - less and equal to 70 bars d. OEM - DCN Naval Group France</p> <p><u>GENERAL SPECIFICATION</u> - a. Material - Mild Steel b. Dia - DE 76.1mm c. Testing Pressure - less and equal to 70 bars d. OEM - DCN Naval Group France</p>	
52	DPK57618	shell corena s3	915070528921 1 / SHELL		10 / LITER	SHELL CORENA					<p><u>TECHNICAL SPECIFICATION</u> - as per oem technical data sheet</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		r46	CORENA S3 R46			S3 R46					GENERAL SPECIFICATION - as per oem technical data sheet	
53	DNF57619	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
54	DSB64242	4702B	5331142939676 / O RING 4.3-1.3 QUALITY B		8 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - OEM France (KT Flow Regulator) GENERAL SPECIFICATION - OEM France (KT Flow Regulator)	
55	DN057311	ly54171026	5331795280448 / OIL seal - hpac fw pump		8 / EACH/NUMBER	LY54171026					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
56	DNF61608	RSFD-II	6135785284717 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		5 / EACH/NUMBER	RSFD-II					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
57	DNF57499	rm 10-hf	5810735248460 / modem-1/ RM10 Wideband SDM - WBHF Modem (MS-188-110C)		1 / EACH/NUMBER	RM 10-HF					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
58	SNF57087	Drop Wire 1.00mm	7045705249626 / Drop Copper Cable Drop Wire 1mm		500 / METER	Drop Wire 1.00mm					TECHNICAL SPECIFICATION - COMPLETE DETAILS REGARDING ALL TYPE OF COPPER CABLES ARE AVIALABLE ON THE PAGE NO 16 &17 IN THE PROVIDED BROCHURE NAMED PTCL PRODUCT CATALOGUE -COPPER TELECOM CABLES" NOTE: 1MM IS THE OUTER DIAMETER SIZE FOR FURTHER DETAILS KINDLY CONCERN ABOVE MENTIONED BROCUHERGENERAL SPECIFICATION - COMPLETE DETAILS REGARDING ALL TYPE OF COPPER CABLES ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AVIALABLE ON THE PAGE NO 16 &17 IN THE PROVIDED BROCHURE NAMED PTCL PRODUCT CATALOGUE -COPPER TELECOM CABLES" NOTE: 1MM IS THE OUTER DIAMETER SIZE FOR FURTHER DETAILS KINDLY CONCERN ABOVE MENTIONED BROCUHER	
59	DPC58483	15447	8030007535006 / Sealing compound		13 / CAN	-			MILITARY SPECIFICATIONS PROMULGATED BY MILITARY DE	MILITARY SPECIFICATIONS PROMULGATED BY MILITARY DE	TECHNICAL SPECIFICATION - AS PER TPGENERAL SPECIFICATION -_AS PER TP	
60	DNF53457	DSLR A47 III / ILCE-7CLB/ ILCE-7C	5836200045912 / SONY Dslr CAMERA A7C alongwith lens	SONY DIGITAL VIDEO CAMERA	3 / EACH/NUMBER	NO DATA AVAILAB LE		JP		SONY CORPORATION, TOKYO, JAPAN	TECHNICAL SPECIFICATION - OEM ADD: SONY CORPORATION, TOKYO, JAPAN.GENERAL SPECIFICATION - OEM ADD: SONY CORPORATION, TOKYO, JAPAN.	
61	DNF50633	K0-399 /0102-034022-226	6626785154466 / AIR TEMPERATUR E CONTROLLER RANGE O-300 C volt100-240V AC	MOBILE LPAC /AC UNIT ALPINE	14 / EACH/NUMBER	OMRON E5C4-R	100-125 PSI		ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674.	CHINA	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	
62	DNF40813	JISC8201 / 3RV1011-0KA10	7830785180094 / CONTACTOR 3 POLE (PUMP+FAN)	7.5 TON ACUS	1 / EACH/NUMBER	CWC.110. A.SPN / Siemens germany	--	FUJI ELECTRIC JAPAN		FUJI ELECTRIC JAPAN	TECHNICAL SPECIFICATION - power rating: 35 Amp (110 VAC 3pole) 7.5 TON ACU(GLYCOL CHILLER) COOLING CAPACITIES 7.5 TON+7.5 TON I/P 2 LINE 380V-50Hz 3 SYSTEM REFREGERANT NO CFC ACU MAX INPUT 41A+41A HYDRALIC CIRCUIT MISTURE ALENIA SPECIFICATION 13A- 198-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											PM 40% PURE ETHYLENE GLYCOL +60% DISTILLED WATER INHIBITOR <u>GENERAL SPECIFICATION</u> - power rating: 35 Amp (110 VAC 3pole) 7.5 TON ACU (GLYCOL CHILLER) COOLING CAPACITIES 7.5 TON+7.5 TON I/P 2 LINE 380V-50Hz 3 SYSTEM REFREGERANT NO CFC ACU MAX INPUT 41A+41A HYDRALIC CIRCUIT MISTURE ALENIA SPECIFICATION 13A- 198-PM 40% PURE ETHYLENE GLYCOL +60% DISTILLED WATER INHIBITOR	
63	DNF61800	PAM-195-P	5945735173093 / SOLINOIDS SUPPLY MODULE AZMIUTH THRUSTER	TUC AZMIUTH THRUSTER	1 / EACH/NUMBER	WARTSILA 9L20		WARTSILA FINLAND		WARTSILA FINLAND	<u>TECHNICAL SPECIFICATION</u> - WARTSILA FINLAND MAKE/BRAND: W-E-ST ELECTRONICS GMBH GERMANY. <u>GENERAL SPECIFICATION</u> - WARTSILA FINLAND MAKE/BRAND: W-E-ST ELECTRONICS GMBH GERMANY.	
64	DPK64094	SAE 75W-90	9150013631192 / LUBRICANT OIL MOBIL 1 SHC (TRANSMISSION OIL) (Packing 20 Liters Drum)	ENGINE	140 / LITER	NO DATA AVAILABLE		US		M/S MOBILE OIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 22037-4090 TEL: 703-846-4090 IDNS: 001294834	<u>TECHNICAL SPECIFICATION</u> - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090 <u>GENERAL SPECIFICATION</u> - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090	
65	SNM57291	197-6995	2815016245772 / GUIDE	CATERPILLAR 3516 DIESEL	26 / EACH/NUMBER	CATERPILLAR	CATERPILLAR	CATERPILLAR USA		CATERPILLAR	<u>TECHNICAL SPECIFICATION</u> - Length/Height (in): 8 Width (in): 0.7	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			VALVE (STANDARD) EXHAUST	ENGINE	UMBER	3516	3516		USA		GENERAL SPECIFICATION - Length/Height (in): 8 Width (in): 0.7	
66	DNA11845	31040	5330705164333 / KIT SEAL (INCLUDES 97,106,112,127,155,156,158,159)	SEA WATER PUMP	1 / EACH/NUMBER	CAT - 3531/3535		DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMABAD		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
67	DPK62236	SW 220	9150993496946 / Compressor Oil	0	10 / LITER	0	0	BUILDING D , CHERTSEY ROAD, SUNBURY ON THAMES	CASTRO L MARINE UK		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
68	SNM40196	3584168	4720171237895 / EXHAUST HOSE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	3 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEBORG, SWEDEN	AB VOLVO PENTA		TECHNICAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6901 GENERAL SPECIFICATION - REQUIRED FOR VOLVO MAIN ENGINE D-6901	
69	DNF56447	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-16P-4KS2	6760785207846 / 16 CHANNEL PRO NETWORK VIDEO RECORDER	CCTV System NVR5216-4KS2 CHINA	1 / EACH/NUMBER	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-16P-4KS2	NA	NO.1199 bin'an road , binjiang district hangzhou , china, 310053 tel: +86-571-87688883	MS NETWORK		TECHNICAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording GENERAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
70	DNF60620	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-	6760785207846 / 16 CHANNEL PRO NETWORK VIDEO	CCTV System NVR5216-4KS2 CHINA	1 / EACH/NUMBER	DHI-NVR4216-16P-4KS2/L/DHI-NVR4216-	NA	NO.1199 bin'an road , binjiang district hangzhou , china, 310053 tel: +86-571-87688883	MS NETWORK		TECHNICAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024,	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		16P-4KS2	RECORDER			16P-4KS2					1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording <u>GENERAL SPECIFICATION - Main Processor Quad-core embedded processor Operating System Embedded LINUX Display Interface 1 HDMI, 1 VGA Resolution 3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768 Multi-screen Display 1/4/8/9/16 OSD Camera title, Time, Video loss, Camera lock, Motion detection, Recording</u>	
71	DNF43192	ASM-150	1420705131936 / AUTOMATIC ENGINE CONTROLLER	D/G	1 / EACH/NUMBER	Frank W Murphy				SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&LARGE B-72ESTATE AVNEUE SITE PO BOX 7158PH# 92(021) 2574910-19 KARACHI 75700	<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
72	DNF54859	121468/5PX300 OIRTNG2/MLM-203/DH2024	6130725171061 / UPS 3 KVA	N/A	1 / EACH/NUMBER	MLM-203/DH2024		GERMANY		GERMANY	<u>TECHNICAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT</u> <u>GENERAL SPECIFICATION - MODEL MLM-203</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											/DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT	
73	DNF57281	WT-5810 TOA	583072520733 1 / SOUND AND PA SYSTEM WIRELESS TUNER WT-5810 TOA	UFFAQ Wt/5810c076R TOA, Germany	1 / EACH/NUMBER	Wt/5810c076R		"TOA Electronic Europe Gmbti, Suderstrabe 282, 20537 Hamburg, Germany Tel: +49 / (0) 40 / 25 17 19-0 Fax: +49 / (0) 40 / 25 17 19-98 Web: www.toa.com"	TOA Electronic sCoporation		<u>TECHNICAL SPECIFICATION - OEM MS TOA CORPORATION.</u> Video Wall Matrix controller <u>GENERAL SPECIFICATION - OEM MS TOA CORPORATION.</u> Video Wall Matrix controller	
74	SNM61337	124-3815	530679522957 5 / BOLT (M8X1.25X16-MM)	33KVA CATERPILLER DG DEO33EO UK	24 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G04238/E3G04237/E3G04236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millenuim Springvale Business Park Belfast BT	CATTERPILLER U. K		<u>TECHNICAL SPECIFICATION - Bolt</u> Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.12 Thread: Coarse Thread Size (in - TPI) (in): MS-1.25 Material Description: Dimensions, tolerances, material, and quality requirements for hexagon flange head bolts. Metric-ISO 4162 Hexagon Bolts with Flange. Inch- ASME B 1S.2.1 Hex Flange Head Screws Notes: Thread Length (mm)3.125 Hole Thread Pitch: 1.25 <u>GENERAL SPECIFICATION - Bolt</u> Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.12 Thread: Coarse Thread Size (in - TPI) (in): MS-1.25 Material Description: Dimensions, tolerances, material, and quality requirements for hexagon flange head bolts. Metric-ISO 4162 Hexagon Bolts with Flange. Inch- ASME B 1S.2.1 Hex Flange Head Screws Notes: Thread Length (mm)3.125 Hole Thread Pitch: 1.25	
75	DNS57901	FCCH0520	4330FT101647 3 / CARTRIDGE FILTER 5 MICRON	CARTRIDGE FILTER ASSEMBLY	20 / EACH/NUMBER	CWS Cartridge Filter Assy		15542 MOSHER AVE TUSTIN CA A.B.D., TRIEU@COMPASSWATER.COM	COMPASS WATER SOLUTIONS, INC.		<u>TECHNICAL SPECIFICATION - OEM: Compass Water Solutions</u> Address: INC. 15542 Mosher Ave p/E : Aqua-Sep RO Plant 3025230-J633 Tustin CA U.S.A. AS PER OEM PUBLICATION COUNTRY OF ORIGIN CANADAGENERAL <u>SPECIFICATION - OEM: Compass</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Water Solutions Address: INC. 15542 Mosher Ave p/E : Aqua-Sep RO Plant 3025230-J633 Tustin CA U.S. A. AS PER OEM PUBLICATION COUNTRY OF ORIGIN CANADA	
76	DNF61657	SCFC09S YE3	606078523253 8 / SM-SIMPLEX-SC/APC-FC/APC 3.0 M OFC PATCH CORD	PSS VIGIL	100 / EACH/NUMBER	SCFC09S YE3		FIBREFAB ASIA & PACIFIC NO.2708, HANGGANG FUCHUN BUILDING. 6031 SHENNAN ROAD. FUTIAN DISTRICT. SHENZHEN, CHINA. TEL: 86-755-2561-3694 FAX: 86-755-2561-3697 E-MAIL: SALES@FIBREFAB.COM	FIBER FAB CHINA		<u>TECHNICAL SPECIFICATION - A1</u> 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB) <u>GENERAL SPECIFICATION - A1</u> 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB)	
77	DNF45993	P-0155000	613078516675 4 / UPS 10KVA 2H O/P 220 V 10000VA with batteries for back up.	PSS (CCTV SYS)	1 / EACH/NUMBER	ONL-10000/ST ABIMATIC		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION -</u> back up time: 45 Min with full load <u>GENERAL SPECIFICATION -</u> back up time: 45 Min with full load	
78	DNF64113	P-0155000	613078516675 4 / UPS 10KVA 2H O/P 220 V 10000VA with batteries for back up.	PSS (CCTV SYS)	1 / EACH/NUMBER	ONL-10000/ST ABIMATIC		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC International CO., LTD		<u>TECHNICAL SPECIFICATION -</u> back up time: 45 Min with full load <u>GENERAL SPECIFICATION -</u> back up time: 45 Min with full load	
79	DNH64306	HPU-48CH03	413078515703 4 / A/C 4 TON FLOOR STANDING	4 TON A/C HPU-48CH03	1 / EACH/NUMBER	GF-48TF		HAIER CHINA LOCAL MARKET (TUBA INTER FIRM)	HAIER CHINA		<u>TECHNICAL SPECIFICATION -</u> BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HR SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPRESSOR), LG, GREE GENERAL SPECIFICATION - BRABDI GREE SOURCE OF AVAILABILITY:LOCEL MARKET (TUBA INTER FIRM) COOLING CAPACITY 48000 BTU/HR SUPPLY 300-450AC 3Ø 50Hz NET DIMENSION 1820 x 530 x 310 MM (IN DOOR) 1008 x 480 x 830 MM (OUT DOOR) Window A/cs: General, LG, PEL, gree split a/cs: general, lg, mitsubishi, daikin, gree, package: GENERAL, LG, MITSUBISHI, DAIKIN, carrier A/C PLANTS: MCQUAY (WITH COPELAND COMPRESSORS), DAIKIN, CARRIER, M/S COOLPOINT (WITH COPELAND, CARRIER, OR DAIKIN COMPRESSOR), LG, GREE	
80	DNV188 96	2080/G- 1/2080/g	599875523182 9 / MOTHER BOARD PCB SMART LOOP 2L	FIRE ALARM 2080/G-1 ITALY	1 / EACH/N UMBER	2080/G-1	NA	INZM ELECTRONICS 9001:2008 REGD. COMPANY VIA FOSSO ANTICO LOC. CENTOBULCHI 63076 MONTEPRANDONE(AP) ITALY TEL:+39 0735 705007 FAX:+39 0735 704912	INIM ELECTR ONICS		TECHNICAL SPECIFICATION - INPUT;220V/ 110VAC & 24VDC GENERAL SPECIFICATION -INPUT;220V/ 110VAC & 24VDC	
81	DNF5987 7	MF60038 / 6-GFM-65	613078517319 4 / 12V 100AH- 65 A/H BATTERY	D/G DEUTZ 42KVA	8 / EACH/N UMBER	MF60038 HANKOO K KOREA		FENFANG BATTERIES CO LTD CHINA	M/S SAIL		TECHNICAL SPECIFICATION - FENFANG BATTERIES CO LTD CHINA H=174 mm W=166 mm L=350 mm GENERAL SPECIFICATION - FENFANG BATTERIES CO LTD CHINA H=174 mm W=166 mm L=350 mm	
82	DPK6385 9	SAE 90 (80W90)	915025114513 5 / ENGINE GEAR OIL SAE 90 (80W90) (03 Ltr to 18 Ltr PACKING)	YAMAHA OUTBOARD ENGINE	35 / LITER	NO DATA AVAILAB LE		US	SOCIETY OF AUTOMO TIVE ENGINEE RS INC, COMMAN WEALTH DRIVE, WARREN		TECHNICAL SPECIFICATION - SAE 90 (80W90) GENERAL SPECIFICATION - SAE 90 (80W90)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									DALE, USA., PSC: 15096, TEL#724-776-4841			
83	DNF64100	LQ-2190	7025735150505 / EPSON LQ-2190 DOT MATRIX PRINTER	EPSON	1 / EACH/NUMBER	EPSON		EPSON	EPSON		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
84	SNJ39004	12892-93J10-235/12892-93J00-235	5365765222368 / SHIM, TAPPET (T: 2350)	SUZUKI DF300AP 300 HP OBM	12 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD GENERAL SPECIFICATION - MAKE: PAK SUZUKI CO LTD	
85	DNH59941	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	4 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122	ASKARI FIBER GLASS PORTABLE TOILET		TECHNICAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure GENERAL SPECIFICATION - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure	
86	DNH63137	N/A	5410705232583 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	10 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122		ASKARI FIBER GLASS PORTABLE TOILET	<p><u>TECHNICAL SPECIFICATION</u> - Item Specification :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof &amp; wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>SPECIFICATION - Item Specification</u>  :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof &amp; wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsai or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system I. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure</p>	
87	DPK64012	ARCTIC 32/146264	9150795170256 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)	COMPRESSOR	10 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Ermyn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000	Mobil Oil Company Limited		<p><u>TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32</u>  <u>GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32</u></p>	
88	SNM57042	6V-0128	5330015369801 / GASKET (SEAL CONNECTOR)	DG 550 KVA	4 / EACH/NUMBER	C-18ACERT	CAT00C18LNB01738	CATTERPILLERSARL SSS/O EAMI POWER SYSTEMBUILDING 21 MILLENIUM SPRINGVALE BUISNESSPARK BELFAST BT 12 AL NORTHREN IRLAND UK	Catterpillar		<p><u>TECHNICAL SPECIFICATION - VOLTAGE RANGE 400VOLTS FREQUENCY 50 HZ VOLTAGE RETURN TIME 2 SEC CONNECTION 3 PHASE POWER FACTOR 0.8</u>  <u>GENERAL SPECIFICATION - VOLTAGE RANGE 400VOLTS FREQUENCY 50 HZ VOLTAGE RETURN TIME 2 SEC CONNECTION 3 PHASE POWER FACTOR 0.8</u></p>	
89	DNF4777	SUVTP20	613071517252	UPS	1 /	Smart-		APC USA	APC		<p><u>TECHNICAL SPECIFICATION -</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	9	KH3B4S/1 200782	7 / APC SMART-UPS VT 20KVA 400V W/3 BATT MOD EXP TO 4		EACH/N UMBER	UPS VT					APC Smart-UPS VT 20kVA 400V w/3 Batt Mod Exp to 4, Start-Up 5X8, Int Maint Bypass, Parallel Capable. Output Power Capacity 16 kW / 20 kVA Max Configurable Power 16 kW / 20 kVA Nominal Output Voltage 400V 3PH Output Voltage Note Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage POWER BACKUP TIME: 15-20 minutes <u>GENERAL SPECIFICATION</u> -APC Smart-UPS VT 20kVA 400V w/3 Batt Mod Exp to 4, Start-Up 5X8, Int Maint Bypass, Parallel Capable. Output Power Capacity 16 kW / 20 kVA Max Configurable Power 16 kW / 20 kVA Nominal Output Voltage 400V 3PH Output Voltage Note Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage POWER BACKUP TIME: 15-20 minutes	
90	DNF4411 5	01230840/ RES81042 BFSCR	743570521666 6 / SERVER RACK F SERIES II RACK 42U 800X 1090 C/W	HP SERVER DL 380	4 / EACH/N UMBER	DL380	SGH830X X1T	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	EMERSO N		<u>TECHNICAL SPECIFICATION - F</u> Series II Rack 42U 800X 1090 C/W: 1. Perforated doors with lock and key. 2. Split side panels .3. EIA mounting rails. 4. levelling feet .5. color black 6. Curved front door A complete Rack includes all of the followings: <u>GENERAL SPECIFICATION - F</u> Series II Rack 42U 800X 1090 C/W: 1. Perforated doors with lock and key. 2. Split side panels .3. EIA mounting rails. 4. levelling feet .5. color black 6. Curved front door A complete Rack includes all of the followings:	
91	DNF5998 4	CAT-6	783070519365 0 / d link 24 AWG 4 pair CAT-6 s/ftp CABLE ROLL (305M / 1000ft)	DAWN NETWORK	1 / ROLL	D-LINK		M/S MICROTECH INC 184, CO-OPERATIVE MARKET SADDAR KARACHI	M/S MICROTE CH INC		<u>TECHNICAL SPECIFICATION -</u> Cable Name: D-Link 24 AWG Cat 6 s/FTP Cable Roll (pic enclosed) Brand: D-Link (4 pair Foilded Twisted Pair (s/FTP) Cable) material: solid bare copper with 24 awg brand: d link (4 pair folded twisted pair (s/ftp) cable. shield: aluminum polyester foil	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											jacket material: pvc ul 94v-0 GENERAL SPECIFICATION - Cable Name: D-Link 24 AWG Cat 6 s/FTP Cable Roll (pic enclosed) Brand: D-Link (4 pair Foilded Twisted Pair (s/FTP) Cable) material: solid bare copper with 24 awg brand: d link (4 pair folded twisted pair (s/ftp) cable. shield: aluminum polyester foil jacket material: pvc ul 94v-0	
92	DNH64104	NIL	4120735139117 / AIR CONDITIONER SPLIT 1.5 TONS	AIR CONDITIONING	2 / EACH/NUMBER	NO DATA AVAILABLE		OC		THILAND	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
93	SNM57041	272-0390	5330015880805 / SEAL PLAIN ENCASED	DG 550 KVA	2 / EACH/NUMBER	C-18ACERT	CAT00C18LNB01738	CATTERPILLER SARL S/O EAME POWER SYSTEMBUILDING21 MILLENIUM SPRINGVALE BUISNESS PARK BELFAST BT 127 ALNORTHREN IRLAND UK		Catterpillar	TECHNICAL SPECIFICATION - CROSS SECTION HEIGHT (IN): 0.29 CROSS SECTION WIDTH (IN): 0.16 INSIDE DIAMETER (IN): 34.6 MATERIAL: FKM MATERIAL DESCRIPTION: FKM RUBBER IS CAPABLE OF SERVICE TEMPERATURES OF -40 TO 150C AND IS RESISTANT TO AIR, FUEL (INCLUDING BIO-DIESEL), LUBRICANTS AND OILS. FKM RUBBER SHOULD NOT BE USED IN APPLICATIONS THAT REQUIRE RESISTANCE TO WATER OR COOLANT. SEAL/O-RING TYPE: PIP VOLTAGE RANGE: 400 VOLTS FREQUENCY: 50 HZ VOLTAGE RETURN TIME: 2 SEC CONNECTIONS: 3 PHASE POWER FACTOR: 0.8 GENERAL SPECIFICATION - CROSS SECTION HEIGHT (IN): 0.29 CROSS SECTION WIDTH (IN): 0.16 INSIDE DIAMETER (IN): 34.6 MATERIAL: FKM MATERIAL DESCRIPTION: FKM RUBBER IS CAPABLE OF SERVICE TEMPERATURES OF -40 TO 150C AND IS RESISTANT TO AIR, FUEL (INCLUDING BIO-DIESEL),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LUBRICANTS AND OILS. FKM RUBBER SHOULD NOT BE USED IN APPLICATIONS THAT REQUIRE RESISTANCE TO WATER OR COOLANT. SEAL/O-RING TYPE: PIP VOLTAGE RANGE: 400 VOLTS FREQUENCY: 50 HZ VOLTAGE RETURN TIME: 2 SEC CONNECTIONS: 3 PHASE POWER FACTOR: 0.8	
94	DNF61636	800 G3 TOWER PC	7020705215930 / HP ELITEDECK CORE I7	IT SELF	1 / EACH/NUMBER	800 G3 CORE i7	SGH717S BTV	HP HQ-TRE 71025 BOEBLINGEN GERMANY		HEWLETT PACKARD (HP)	<u>TECHNICAL SPECIFICATION - WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393</u> PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM <u>GENERAL SPECIFICATION - WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393</u> PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM	
95	SNM57292	8H9520	5330010675652 / SEAL	3304PC, CATTERPILLAR D/G	20 / EACH/NUMBER			CATTERPILLAR US		CATTERPILLAR	<u>TECHNICAL SPECIFICATION - Shaft Diameter (mm): 22 Bore Diameter (mm): 35 Primary Sealing Material: Rubber</u> <u>GENERAL SPECIFICATION - Shaft Diameter (mm): 22 Bore Diameter (mm): 35 Primary Sealing Material: Rubber</u>	
96	DPK57309		0475509429213 / LINSEED OIL BOILED ACID NO8 SP GR 0.935-0.955 AT 15.5 DEG C.		160 / LITER						<u>TECHNICAL SPECIFICATION - BS6900</u> <u>GENERAL SPECIFICATION - BS6900</u>	
97	DGE39893		0413599238762 / HOSE RUBBER WITH EXT ARMOURING OF STEEL		100 / METER						<u>TECHNICAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750 INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			STRIP								NOMINAL PROPRIETARY CHARACTERISTICS: NPACGENERAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750 INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES NOMINAL PROPRIETARY CHARACTERISTICS: NPAC	
98	DPK57306	ZX13-500 GRAMME	0474509100528 / ANTISEIZE COMPOUND ZX13-500 GRAMME (NSN8030999100528)		60 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DGE57600	NO DATA AVAILAB LE	0350595713118 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875")		600 / FATHOM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
100	DPC57968	DGS 5961	0442504420152 / PAINT COALTAR EPOXY COMPENENT-A (BLACK) (20	SHIP BOTTOM ANTI CORROSIVE.	260 / LITER						TECHNICAL SPECIFICATION - DGS 5961 GENERAL SPECIFICATION - DGS 5961	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LTR DRUM)									
101	SGB44961		026659441344 1 / SCREW MACHINE BRASS BSW ROUND HD SZ 1.500X0.312 IN		50 / TEN						<u>TECHNICAL SPECIFICATION -</u> Length=38mm, Dia= 8mm, Material grade of Brass: Grade 4.8 (OR) Aluminum copper content 61% <u>GENERAL SPECIFICATION -</u> Length=38mm, Dia= 8mm, Material grade of Brass: Grade 4.8 (OR) Aluminum copper content 61%	
102	SNF51976	4972	058479995921 5 / LAMP FILAMENT SIDE CLIPS AND YELLOW24V 2.4W 6.5X44. 5MM T SHP		20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
103	DNF57277	DEF107A , B22996 , 62-2PT2	058379910503 3 / TORCH HAND ELECT WATERPROO F R/A HEAD SPARE LAMP SZ 187X43MM		7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
104	SNF51807	MC- YL620+ Panasonic	056579415077 9 / VACUUM CLEANER 220/230V 1500W 10L W/ACCESSOR IES SPARES&STO WAGE BOX		5 / EACH/N UMBER	MC- YL620+ Panasonic					<u>TECHNICAL SPECIFICATION -</u> VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620 <u>GENERAL SPECIFICATION - VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620</u>	
105	DNF61781	MC- YL620+ Panasonic	056579415077 9 / VACUUM CLEANER 220/230V 1500W 10L W/ACCESSOR IES SPARES&STO WAGE BOX		1 / EACH/N UMBER	MC- YL620+ Panasonic					<u>TECHNICAL SPECIFICATION -</u> VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620 <u>GENERAL SPECIFICATION - VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620</u>	
106	DNF62396	4371187	056579437118 7 / DRILL		1 / EACH/N	4371187					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MACHINE ELECT 220V 5A 50HZ SIZE 23MM 530RPM		UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
107	DGH59697		0561595218537 / CABLE ELECT WELDING FLEX 1 CORE COND 1107/0.20 DIA 14.5MM		200 / METER						<u>TECHNICAL SPECIFICATION - DEF STAN 61-12/1 PART 19 &amp; BS 638 PART 4 OF 1996</u> <u>GENERAL SPECIFICATION - DEF STAN 61-12/1 PART 19 &amp; BS 638 PART 4 OF 1996</u>	
108	DNF64091	N250 PLUS EXIDE / OSAKA OR EQUALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	5 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u> <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u>	
109	DNF51071	BLACK&DECKER / BPHR223K/BLAR-56	0565792085982 / DRILLING MACHINE PORTABLE 115-220V 3/8 IN (BLACK&DECKER)	IT SELF	2 / EACH/NUMBER	BLAR-56					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
110	SNM57137	2P1785	2815010112686 / PUM GROUP		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - WEIGHT: 21.8 LBS (9.89 KG) LENGTH: 13.78 IN (35 CM) HEIGHT: 9.84 IN (24.99 CM) WIDTH: 7.87 IN (19.99 CM)</u> <u>GENERAL SPECIFICATION - WEIGHT: 21.8 LBS (9.89 KG) LENGTH: 13.78 IN (35 CM) HEIGHT: 9.84 IN (24.99 CM) WIDTH: 7.87 IN (19.99 CM)</u>	
111	SNM57295	6N9915	2815011434335 / VALVE INLET	CATTER PILLER D/G (OIL PAN)	8 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Weight: 0.4 lbs (0.19 kg) Length: 6.1 in (15.49 cm) Height: 2.6 in (6.6 cm) Width: 2.6 in (6.6 cm) Material: chrome, nickel, or tungsten steel or Austenitic stainless steel alloys such as 21-2N and 21-4N</u> <u>GENERAL SPECIFICATION - Weight: 0.4 lbs (0.19 kg) Length: 6.1 in (15.49 cm) Height: 2.6 in (6.6 cm) Width: 2.6 in</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(6.6 cm) Material: chrome, nickel, or tungsten steel or Austenitic stainless steel alloys such as 21-2N and 21-4N	
112	SGB54832		4710995711796 / PIPING STEEL SEAMLESS DIAMETER 1.250 INCH, THICKNESS 0.125 INCH		4 / METER						<u>TECHNICAL SPECIFICATION</u> - Outer Diameter: 31.75 mm, Inner Diameter: 25.41mm, Thickness: 3.17 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel <u>S275JRG</u> <u>GENERAL SPECIFICATION</u> - Outer Diameter: 31.75 mm, Inner Diameter: 25.41mm, Thickness: 3.17 mm, Length: 6.096 Mtr, Material With Grade: MILD/ Carbon Steel S275JR	
113	DNF59575	LL-01A10-230C	4240705114965 / EMERGENCY LAMP WITH 10 METER CABLE TYPE 60W EX GLS LEAD LAMP	SAFETY RELATED EQUIPMENT	12 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
114	DNF55837	LL-01A10-230C	4240705114965 / EMERGENCY LAMP WITH 10 METER CABLE TYPE 60W EX GLS LEAD LAMP	SAFETY RELATED EQUIPMENT	2 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
115	DGH54077	MUREX SAFFIRE 36EC	3439795095020 / MUREX SAFFIRE 36EC FLASH BACK ARRESTOR CYLINDER REGULATOR (ACETYLENE)	WELD/CUTT MUREX SAFEFIRE 36EC	1 / EACH/NUMBER	MUREX SAFFIRE 36EC (FUEL GAS)					<u>TECHNICAL SPECIFICATION</u> - STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED) <u>GENERAL SPECIFICATION</u> - STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED)	
116	DGP61998		3610705045303 / POSITIVE PLATE ROLAND OFFSET size: 925X740X0.3MM(BRND FUJI)		200 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - SIZE: 925X740X0.3MM(BRND FUJI) <u>GENERAL SPECIFICATION</u> - SIZE: 925X740X0.3MM(BRND FUJI)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
117	DNH64097	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
118	DNM32296	141-7143	4730015071292 / HOSE - ELBOW	CATTER PILLER GENSET 3512B USA	2 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
119	DNM32295	217-6692	4730015071291 / HOSE - TEE	CATTER PILLER GENSET 3512B USA	2 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N . E ADAMS, STREET, PEORIA, IL 61629 USA	CATTER PILLER USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
120	DNF58090	457-6114	6625715195285 / CA3/DATA LINK CABLE ASSEMBLY	CATERPILLAR 466-6258 USA	1 / EACH/NUMBER	466-6258	1955E180 ED	M/S CATERPILLAR	M/S CATERPILLAR		<u>TECHNICAL SPECIFICATION -</u> <u>NILGENERAL SPECIFICATION -</u> <u>NIL</u>	
121	SNM6215	210-2542/4688824	2815015431126 / VALVE INLET	CATERPILLAR 3516 DIESEL ENGINE	24 / EACH/NUMBER	CATERPILLAR 3516	CATERPILLAR 3516	CATERPILLAR USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - IPC ATTACHED</u> <u>GENERAL SPECIFICATION - IPC ATTACHED</u>	
122	SNM52357	A034P660	2940795213417 / ELEMENT AIR FILTER-PRIMARY	40 KVA DG C44D5	4 / EACH/NUMBER	C44D5		CUMMINS POWER GENERATION LIMITED COLUMBUS AVENUE MANSTON PARKMANSTON RAMSGATE KENT CT125BF UNITED KINGDOM PH NO +441843255000 FAX +4H1843255902	CUMMINS POWER GENERATION LIMITED		<u>TECHNICAL SPECIFICATION -</u> <u>ELEMENT AIR FILTER-</u> <u>PRIMARYGENERAL</u> <u>SPECIFICATION - ELEMENT AIR</u> <u>FILTER-PRIMARY</u>	
123	SNM43456	6L1650	5331008696574 / SEAL 'O' RING	CATERPILLAR MAIN ENGINE C-18?	10 / EACH/NUMBER		T2P01496	USA	CATERPILLAR		<u>TECHNICAL SPECIFICATION -</u> <u>MAKE: CATERPILLAR GENERAL</u> <u>SPECIFICATION - MAKE:</u> <u>CATERPILLAR</u>	
124	SNF54646	BSB-1104 TIM DIN	5925765160798 / MCB 2 POLE 220 V 30AMPS	CONVERSION OF BOATSWAIN INTO MRO/BEHR KUSHA	10 / EACH/NUMBER	BSB-1104 TIM DIN		M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTAH HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL: 2639514&2638482	M/S DIGI TECH SHOP NO2 NEW MEMON		<u>TECHNICAL SPECIFICATION -</u> <u>nullGENERAL SPECIFICATION -</u> <u>null</u>	
125	DNF60912	P-0190000	5140785167178 / EQUIPMENT	PSS	10 / EACH/NUMBER			M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District,	M/s CETC International Co., Ltd.		<u>TECHNICAL SPECIFICATION -</u> <u>EQUIPMENT BOX METAL</u> <u>(650x750x250) MM PORTABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			BOX (650x750x250) MM PORTABLE MATERIAL, Stainless Steel, grade 316L					Beijing, China 100120.			material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer <u>GENERAL</u> <u>SPECIFICATION - EQUIPMENT</u> BOX METAL (650x750x250) MM PORTABLE material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer	
126	SNC218 47	51203	533072513222 8 / BONDED SEAL 1/2	WATER JET SYSTEM	100 / EACH/ NUMBER	NO DATA AVAILAB LE		GR	GERMAN Y		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
127	DNM480 30	423-8521	291071522305 9 / FILTER G P- WATER SEP AND FUEL	caterpillar C-13 USA	3 / EACH/ NUMBER	NA	NA	CATER PILLAR DIESEL GENERATOR SET Electric power North America Attn: Product support Manager AC 6109 Mossville, LLlinois 61552	CATTER PILLER		<u>TECHNICAL SPECIFICATION -</u> <u>OEM: CATERPILLAR</u> <u>GENERAL</u> <u>SPECIFICATION - OEM:</u> CATERPILLAR	
128	DNF5935 7	P-0155000	613078516675 4 / UPS 10KVA 2H O/P 220 V 10000VA with batteries for back up.	PSS (CCTV SYS)	2 / EACH/ NUMBER	ONL- 10000/ST ABIMATI C		M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China	M/s CETC Internatio nal CO., LTD		<u>TECHNICAL SPECIFICATION -</u> <u>back up time: 45 Min with full load</u> <u>GENERAL SPECIFICATION - back</u> <u>up time: 45 Min with full load</u>	
129	SNM177 41	MK 9053N	494572521141 1 / BRAKE CONTROLLER CURRENT RELAY (500MA)	DOCK LIFT SYSTEM MK 9053-50- 500mA GERMANY	2 / EACH/ NUMBER	MK 9053N	NA	E.DOLD U.SOHNE KG D- 78120 FURTWANGEN	GERMAN Y		<u>TECHNICAL SPECIFICATION -</u> <u>CURRENT RELAY GIVE</u> <u>INFORMATION TO SERVO</u> <u>COTROLLER FOR BRAKE</u> <u>RELEASING.</u> <u>GENERAL</u> <u>SPECIFICATION - CURRENT</u> <u>RELAY GIVE INFORMATION TO</u> <u>SERVO COTROLLER FOR BRAKE</u> <u>RELEASING.</u>	
130	DNS481 64	165 052	533173518547 1 / SEALING SET FOR INJECTION PUMP	WARTSILA MAIN ENGINE 9L20C3 FINLAND	18 / EACH/ NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel.	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION -</u> <u>DOCUMENT NUMBER 54292</u> <u>SPECIFICATIONS 231205, 231206</u> <u>OEM: WARTSILA MAKE: FINLAND</u> <u>MODEL: 9L20</u> <u>GENERAL</u>	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
							AE084243 PAAE084 244	+358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380			SPECIFICATION - DOCUMENT NUMBER 54292 SPECIFICATIONS 231205, 231206 OEM: WARTSILA MAKE: FINLAND MODEL: 9L20	
131	DNM543 16	998-695	534079518280 9 / SLEEVE	PERKIN DG P- 275H-2 UK	6 / EACH/N UMBER	P-275H-2	WS5545N 1614661	PERKIN UK	PERKIN UK		TECHNICAL SPECIFICATION - PERKIN 250 KVAGENERAL SPECIFICATION - PERKIN 250 KVA	
132	DNQ602 31	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
133	SNJ4894 1	15642- 90J00	294076522180 3 / FILTER, FUEL PUMP	SUZUKI DF300AP 300 HP OBM	23 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
134	DNM480 80	US PAT 4,202,309	291078516368 9 / FUEL FILTER	03 KW DIESEL GENERATOR	20 / EACH/N UMBER		5841019	M/S POLY TECHNOLOGIES BEIGING CHINA	M/S POLY TECHNO LOGIES BEIGING CHINA		TECHNICAL SPECIFICATION - Make: Lombardini Model: 15LD350 Type: i type Output: 3 kw Description: Decoy DG M/S POLY TECHNOLOGIES BEIGING CHINA LOCAL SOURCE:GOOD LUCK AUTOS TIBET CENTRE KARACHI. GENERAL SPECIFICATION - Make: Lombardini Model: 15LD350 Type: i type Output: 3 kw Description: Decoy	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											DG M/S POLY TECHNOLOGIES BEIJING CHINA LOCAL SOURCE: GOOD LUCK AUTOS TIBET CENTRE KARACHI.	
135	DNM51533	9L-4896	3030015827906 / BELT,V	CATERPILLAR DG 275 KVA C-9	6 / EACH/NUMBER	C-9	CAT000C9LLX900927	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, UNITED STATES TELE NO 3095782353 FAX NO 3095783739 WWW.CAT.COM	ALLIED CAT		<u>TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9</u> <u>GENERAL SPECIFICATION -CATERPILLAR DG 275 KVA MODEL NO. C-9</u>	
136	DGE60223	GMS-388A-07	4910725136314 / ESD SHOES COVER WITH CONDUCTIVE STRAP	ESD LABORATORY EQUIPMENT	6 / EACH/NUMBER	NO DATA AVAILAB LE		GR	ROHDE & SCHWARZ INTL GMBH MUHLDO RFATRBE 15-81671 MUNICH GERMANY		<u>TECHNICAL SPECIFICATION - A.</u> Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c. ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5 <sub>2</sub> / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL <u>GENERAL SPECIFICATION - A.</u> Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c. ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5 <sub>2</sub> / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL	
137	DNF60521	DCC/HFBM/EL/009	5995705214365 / 10 MHZ SYNCHRONIZATION CLOCK	SM RACK 100C2ZL PAKISTAN	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212	DCC		<u>TECHNICAL SPECIFICATION - It is used to synchronize the receivers</u> Frequency: 10 MHz Supply Voltage: 5V Clock Output Connector: SMA-Female PPS Output Connector: SMA-Female <u>GENERAL SPECIFICATION - It is used to synchronize the receivers</u> Frequency: 10 MHz Supply Voltage: 5V Clock Output Connector: SMA-Female PPS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Output Connector: SMA-Female	
138	SNF29864	LS14250C li-soci2	613501525994 3 / SAFT LITHIUM BATTERY 3.6 V Is14250 li-soci2	ALTIMETER	100 / EACH/NUMBER	LS14250 C LI-SOCI2	NK	LARSON & BRUSGAARD MOSEVEJ 3 4070 KIRKE HYLLINGE DENMARK TEL: 45 46 48 24 80 FAX: 45 46 48 24 90 WWW.L-AND-B.DK EMAIL: L-AND-B@L-AND-B.DK		LARSON & BRUSGAARD	TECHNICAL SPECIFICATION - oem, saft batteries td. france / usa. local source, SCENARIO INTERNATIONAL M ASGHAR BOOTA PH: 0300-2210392 E-76A, BLOCK-E GULSHAN-E-JAMAL KARACHI FAX: 92 (21) 4680814 EMAIL: scenario1310@gmail.com GENERAL SPECIFICATION - oem, saft batteries td. france / usa. local source, SCENARIO INTERNATIONAL M ASGHAR BOOTA PH: 0300-2210392 E-76A, BLOCK-E GULSHAN-E-JAMAL KARACHI FAX: 92 (21) 4680814 EMAIL: scenario1310@gmail.com	
139	DNF60628	DCC/HFB M/EL/018	584070521435 2 / VGA GAIN CONTROLLER	DF RACK/ SM RACK 100C2LZ PAKISTAN	1 / EACH/NUMBER	100C2LZ	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212		DCC	TECHNICAL SPECIFICATION - Microcontroller with LAN connectivityGENERAL SPECIFICATION - Microcontroller with LAN connectivity	
140	DNF60520	DCC/HFB M/EL/018	584070521435 2 / VGA GAIN CONTROLLER	DF RACK/ SM RACK 100C2LZ PAKISTAN	1 / EACH/NUMBER	100C2LZ	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, Khi 021-35363212		DCC	TECHNICAL SPECIFICATION - Microcontroller with LAN connectivityGENERAL SPECIFICATION - Microcontroller with LAN connectivity	
141	DNF59258	ED-786D/d787	666570522104 0 / HAND HELD EXPLOSIVE DETECTOR	DESTO EXPLOSIVE DETECTOR PAKISTAN	1 / EACH/NUMBER	ED-786D/d787		DESTO (HQ) CHAKLALA CANTT, RAWALPINDI-46200, PAKISTAN PHONE NO +92-51-9280507, FAX +92-51-92-9280502 EMAIL desto@isbpaknet.com.pk		DESTO (DEFENCE & SCIENCE TECHNOLOGY ORGANIZATION)	TECHNICAL SPECIFICATION - 1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>NG (Nitro Glyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C <u>GENERAL SPECIFICATION</u> -</p> <p>1. Principle: Ions concentration 2. Respective Time: Immediate 3. Operating Voltage: 14.5VDC + Volts 4. Battery Type: Li-ion recharged 5. Battery life: 04 Hours 6. Max Charging Time: 02 hrs 30 minutes 7. Low Voltage Alarms: 09 Volts + 1 Volt 8. Audio Indicators: Beep 9. Visual Indicators: LED 10. Operating Temp Range: +5 C to +55 C 11. Storage Temp Range: +5 C to 80 C Range of ED-D787 has been designed to detect the presence Explosives of various from the following explosive substances: Detector 1. TNT (Tri Nitro Toluene) 2. NG (Nitro Glyceone) 3. Dynamite 4. ANFO (Ammonium Nitrate Fuel Oil) 5. Tetryl MANUAL ZERO 10 SEC FROM SWITCH ON RESPONSE TIME IMMEDIATE BATTERY VOLTAGE TYPE +-12V, AA SIZE CELL INDICATOR PEIZO BUZZER VISUAL INDICATOR LED TEMP 0-60C</p>	
142	DNM53314	3970911	6685015301220 / TRANSMITTER, TEMPERATURE /SENSOR WATER	MARINE ENGINE CUMMINS(UT BOAT)	4 / EACH/NUMBER	QSB5.9-225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND	M/S MECHANICAL & ELECTRICAL (UK) LTD		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
143	DPK46845	CASTROL TRANSMAX ATF DEX-	9150705197314 / CASTROL transmax atf dex-	RHIB BOAT INBOARD DIESEL ENGINE	80 / LITER	-	-	CASTROL	CASTROL		<u>TECHNICAL SPECIFICATION</u> - CASTROL ATF <u>GENERAL SPECIFICATION</u> - CASTROL ATF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		MERCMULTIVEHICLE	mercmultivehicle								MULTIVEHICLE	
144	DGE39252		0350595713032 / ROPE COIR HAWSERLAID CIR 2"		460 / FATHOM						TECHNICAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut)GENERAL SPECIFICATION - 3 STRD CIR 2" DIA 0.625 MATERIAL COIR (Husk of CoConut)	
145	DGE44279	NO DATA AVAILAB LE	0350595713118 / ROPE NYLON, HAWSERLAID, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875")		601 / FATHOM	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
146	SGB23340		0214580001164 / BOLT STEEL		700 / EACH/NUMBER						TECHNICAL SPECIFICATION - 216/B TPI 20 FULL THREAD SIZE 8.00 X 1.25 X 46.00MM DIAMETER: 8 MM PITCH: 1.25 MM LENGTH: (THREADED AREA ONLY EXCLUDING HEAD) 40 MM LENGTH: (THREADED AREA + HEAD) 46 MM HEAD DIAMETER: 13 MM METRIAL GRADE EN 4140GENERAL SPECIFICATION - 216/B TPI 20 FULL THREAD SIZE 8.00 X 1.25 X 46.00MM DIAMETER: 8 MM PITCH: 1.25 MM LENGTH: (THREADED AREA ONLY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											EXCLUDING HEAD) 40 MM LENGTH: (THREADED AREA + HEAD) 46 MM HEAD DIAMETER: 13 MM METRIAL GRADE EN 4140	
147	SGB130 94		021459013122 4 / BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6. 000X1.500 IN		400 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - size: BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6.000X1.500 IN STEELL GRADE AISI 4140 (PD 970:2005 GRADE 708M40/42CRM40 Material Grade EN 4140 (OEM CoC Required). <u>GENERAL SPECIFICATION</u> - size: BOLT MACHINE STEEL BSF HEX HD SZ 0.750X6.000X1.500 IN STEELL GRADE AISI 4140 (PD 970:2005 GRADE 708M40/42CRM40 Material Grade EN 4140 (OEM CoC Required).	
148	DNJ6075 3	AE011020 10B	293076507594 1 / MECHANICAL SEAL 0305 FOR COOLING WATER PUMP	COOLING WATER PUMP (6DSM 22)	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
149	SNM489 85	1445694X, OLD P/N 8N1233/22 9-1631	281501207367 6 / RING PISTON TOP (8N1233)	3512 M/ENGINE, ROD & PISTON GP-12	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR US <u>GENERAL SPECIFICATION</u> - OEM & MAKE: CATERPILLAR USA	
150	SNF5929 1		343979502053 7 / SOLDERING GUN 20 TO 200 W SIZE- STANDARD 220V/50 CYCLE	FOR ASTT	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
151	DNZ4819 2	112401	413078502676 7 / SEAL SHAFT LENGTH 82 MM DIA 70 MM AA005	AIR CONDITIONER PLANT 6C75 (2)EB NASR	7 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
152	DNZ6033 9	112604	413078502676 9 / SPRING DISCHARG	AIR CONDITIONER PLANT	6 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			VAVE C/HC 752 AA010	NASR							AVAILABLE	
153	SNM164 29	51-01111- 6413/51- 011146016	312070505186 1 / THRUST BEARING (FOR JOURNAL DIA METER)	M A N DIESEL ENGINE	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
154	SNM401 55	K-60	530571505404 2 / ALLEN SCREW	PIPING & EXTERNAL GEARBOX PARTS WAF 560	4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
155	SNM516 56	0337-3568	5305RC507089 7 / ADJUSTING SCREW TIMER GEAR DEUTZ MWM BA-8M-816 PNS KALMAT	DEUTZ M/ENGINE FOR PNS KALMAT	20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
156	SNM473 26	3P0649	533000367565 2 / SEAL O RING	3516, CATERPILLAR D/G USA (JNB)	10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR DGG</u> <u>GENERAL SPECIFICATION - OEM: CATERPILLAR DG</u>	
157	SNM455 82	9M4849	533000847435 1 / SEAL	3304PC, CATERPILLER D/GEN.USA	22 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM &amp; MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM &amp; MAKE: CATERPILLAR</u>	
158	DNM333 54	8S1606	533000437875 2 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA- 9MM TH-03MM	3304PC, CATERPILLER D/GEN.USA	1 / EACH/N UMBER	3304 SSDG					<u>TECHNICAL SPECIFICATION - OEM &amp; MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGG</u> <u>GENERAL SPECIFICATION - OEM &amp; MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG</u>	
159	SNM457 59	2H3934 (5331-00- 291-7192)	533000291719 2 / SEAL (PACKING PREFORMED)	3306,PILLER DIESEL GENERATOR (USA)	20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - OEM: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM: CATERPILLAR</u>	
160	DNZ6036 0	R27429	533078503432 3 / O,RING FOR STARTING AIR	MAIN ENGINE 8RLB-66 NASR	8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			VALVE HOUSING ID135.87X7MM CF-122									
161	DNZ60361	R27231	5330785034337 / O RING RUBBER 29X3.50MM CF-121	MAIN ENGINE 8RLB 66 NASR	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
162	DNJ60350	C262300360	5330785027271 / GASKET EXH GAS O/LET L-415 B-190 TH-3 HOLE 14 DIA11. 4MML0053	DAIHASTU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR OEM DAIHATSU Supplier M/S CHINA SHIPBULIDING TRADING CHINA GENERAL SPECIFICATION - DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR OEM DAIHATSU Supplier M/S CHINA SHIPBULIDING TRADING CHINA	
163	DNF30413	1679-0011-01	6145RC5084592 / RADIATOR WIRE FOR RX-EK-895	SPIRACONE ANTENA MODEL 3002A 36S	600 / METER						TECHNICAL SPECIFICATION - a. Make: British Aero Space Australia Limited. b. Parent Equipment: Spiracon Antenna (HF DF System). GENERAL SPECIFICATION - a. Make: British Aero Space Australia Limited. b. Parent Equipment: Spiracon Antenna (HF DF System).	
164	DNG31061	275447-1	5970004327371 / TAPE INSULATIONN ELECTRICAL	CIWS	5 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
165	DNF54244	525502	6650121579560 / BINOCULAR 7X50B/7X50c	BINOCULAR 7X50B OEM: ZEISS,CARL POB 1380	9 / EACH/NUMBER	7x50b/7X50c					TECHNICAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany GENERAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany	
166	SNM52370	7139-540	2910998294339 / LINER, TRANSFER PUMP	FUEL INJECTION PUMP	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DNM31176	319-5889	5331705240185 / SEAL		2 / EACH/NUMBER	3512B					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
168	DNJ47674	17400-94412	534076526562 1 / KIT WATER PUMP REPAIR		1 / EACH/NUMBER	DT-40WL/E40XMHL					<u>TECHNICAL SPECIFICATION - OEM: PAK SUZUKI MOTORS KIT INLCUDE 1 pc x Water Pump Impeller 1 pc x Water Pump Plate 1 pc x Water Pump Key 1 pc x Water Pump Plate Gasket 1 pc x Cover 1 pc x Notched Loop</u> <u>GENERAL SPECIFICATION - OEM: PAK SUZUKI MOTORS KIT INLCUDE 1 pc x Water Pump Impeller 1 pc x Water Pump Plate 1 pc x Water Pump Key 1 pc x Water Pump Plate Gasket 1 pc x Cover 1 pc x Notched Loop</u>	
169	DNF60630	EL-ETHS-200	299071527794 4 / ANTI CONDENSATION HEATER FOR DG PERKIN		1 / EACH/NUMBER	EL-220					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
170	DNJ60855	DF300A-E03-014-028	280576529236 5 / TRIM CYLINDER		4 / EACH/NUMBER	DF300A					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
171	DPC57425	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
172	DPC57339	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)		10.2 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u> <u>GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)</u>	
173	DPC57064	POLP9460035MC2PK	683070524143 3 / hELIUM OXYGEN (HELIOX)		15.3 / CUBIC METER	not known					<u>TECHNICAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)								M)GENERAL SPECIFICATION - HELIUM OXYGEN (HELIOX) MIXTURE OF 71% HELIUM 29% OXYGEN (CYLINDER 5.10 CUBIC M)	
174	DSB44189	FLX-7233010-VTX /A0291-001F14	4720143363010 / FLEXIBLE DE36 LONG 500		3 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - satisfactory pressure testing upto 10 bar physical verification as per sampleGENERAL SPECIFICATION - satisfactory pressure testing upto 10 bar physical verification as per sample	
175	SSM28228	4271470071	5925745178318 / MAIN AC CIRCUIT BREAKER 120/160 AMPERE		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
176	DNJ54445	17411-96J01	4330765265111 / CASE WATER PUMP		1 / EACH/NUMBER	F150FET X					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
177	DNF59086	8237-1177	2815735289116 / TURNER PCB CONTROL UNIT (733 CONTROL)		1 / EACH/NUMBER	733-CONTROL					TECHNICAL SPECIFICATION - 733 control containing TECS software reference as 733-LS) i. Temperature range -40°C to 100°C ii. Voltage input 18 V to 32 V DC, Nominal) iii. Input power 20 watt maximum continuous Main function: i. Speed synchronization ii. Load sharingGENERAL SPECIFICATION -_733 control containing TECS software reference as 733-LS) i. Temperature range -40°C to 100°C ii. Voltage input 18 V to 32 V DC, Nominal) iii. Input power 20 watt maximum continuous Main function: i. Speed synchronization ii. Load sharing	
178	DNF18761	H3CR-F8	6645785237275 / SOLID STATE TIMER (AC 100-240/DC 100-125 0		1 / EACH/NUMBER	H3CR-F8					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
179	DNF58018	CAT6	5995505238643 / Cat6 Cable		1 / EACH/NUMBER	ML-ES-PC01M					TECHNICAL SPECIFICATION - Cat6 Cable GENERAL SPECIFICATION - Cat6 Cable	
180	DNM54590	A044S583	5330715267629 / SEAL-TIMING CASE FRONT COVER OIL SEAL		1 / EACH/NUMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
181	DSA38858		5340TY6720913 / CURTAIN RAILING		44 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum GENERAL SPECIFICATION - Length: 1.75 Meter Width: 16mm Height: 8mm Material grad: Aluminum	
182	SNF52819	mcx-elec-pnl	5975705246327 / electrical panel		6 / EACH/NUMBER	MCX-ELEC-PNL					TECHNICAL SPECIFICATION - BROUCHER ATTACHED GENERAL SPECIFICATION - BROUCHER ATTACHED	
183	DSB27350	lw-7239014-vtx/GSM141003G	5310142569014 / LOCK WASHER DN27 GALVANSED STEEL		26 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - L 58 mm X W 42 mm X H 64 mm with rectangular shape hole of size 16 X 10 mm ; INNER: 20MM ; OUTER: 36MM ; THICKNESS: 01MM GENERAL SPECIFICATION - L 58 mm X W 42 mm X H 64 mm with rectangular shape hole of size 16 X 10 mm ; INNER: 20MM ; OUTER: 36MM ; THICKNESS: 01MM	
184	DNM57769	A054G720	2815795247877 / Kit,Radiator		1 / EACH/NUMBER	C275D5B/C330D5B					TECHNICAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins GENERAL SPECIFICATION - a. Radiator MODEL: WUHAN-334422-00 b. Radiator S.No: 22021806008000585 c. Radiator Ref no: A054G720 d. DG 250 KVA Cummins	
185	DNO60376	GSP5563	6810735233794 / Antiscaling 5 Ltr		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Antiscaling 5 Ltr GENERAL SPECIFICATION - Antiscaling 5 Ltr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
186	DSA15977		5999TY6715012 / MALE&FEMALE 2PIN (COMPLETE)		60 / EACH/NUMBER	not held					TECHNICAL SPECIFICATION - PART NO: USED FOR AC 220V SUPPLY MALE/FEMALE SOCKET SUPPLIER: AMIR ENTERPRISES GENERAL SPECIFICATION - PART NO: USED FOR AC 220V SUPPLY MALE/FEMALE SOCKET SUPPLIER: AMIR ENTERPRISES	
187	DSB36779	SAFDRY ND80-RAQ2-4X450MM	3439145151083 / ELECTRODE E69 DIA 4MM E11018G		2000 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
188	SNM47244	393-4006	5330715239974 / GASKET		2 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR	
189	DPC58711	SIKAFLEX -290	8030795167621 / SIKA-FLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER-290DC	12 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		TECHNICAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129 GENERAL SPECIFICATION - ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather-resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
190	SPK58338	OMALA 68	9150270001857 / SHELL OMALA OIL 68 (PACKING 209 LTR DRUM)	MTP 750DD HUB OIL	209 / LITER	NO DATA AVAILAB LE		OC		TURKEY	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
191	SNS55065	238-8289	4720FT1018944 / Pipe As	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A		CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									AND DEFENSE PRODUCTS			
192	SNF54682	LOCAL	055279541783 1 / CLOCK-ELECTRONIC-9IN-DIAL	SELF	15 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
193	DPC60336	DEFSTAN 80-50/3 Shade no 106 BS 381-C OF 1996	044250910672 4 / PAINT FINISHING, ALKYD (ROYAL BLUE) FLASH POINT 32C (04 LTR Packing)	VEHICLES + COMPAK BARGE	500 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TINGENERAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN	
194	DNM60113	323-9312	530601622659 6 / BOLT (M10X1X50-MM)		2 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL GENERAL SPECIFICATION - LENGTH: 50MM, COATING: PHOSPHATE & OIL	
195	SNM45578	7N8018	533001128413 0 / SEAL WATER	CATER PILLER DIESEL GENERATOR	38 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
196	DNF52401	6 242 01	613099742767 0 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk GENERAL SPECIFICATION - country of origin uk	
197	DNC55174		792099122782 5 / CLOTH CLEANING	30MM GUN	900 / EACH/NUMBER						TECHNICAL SPECIFICATION - size 1x1 feet GENERAL SPECIFICATION - size 1x1 feet	
198	DNZ58920	E-01-01	299078527767 6 / FIRST LEVEL CONNECTING ROD		1 / EACH/NUMBER	MCH18-Standard Super silent breathing					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
						air compress or.						
199	DNZ58914	E-03-13	2815785277655 / THREE-STAGE PISTON RING		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compress or.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
200	DNJ60352	Z665024000B	2990785027164 / GASKET ALLUMINUM I/D 24MM O/D 32MM THICKNESS 2MM L0069	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	