

TENDER BULLETIN

DATE & TIME 6/5/24 1:46 PM

INVITATION TO TENDER TO BE OPENED ON 6/27/2 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPK63620	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	100 / LITER	JAPAN		JAPAN	SHELL		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
2	DNF48901	0102-034002-226	6110785154471 / MAIN CONTACTOR 95 AMP COIL VOLTAGE 220V AC	L/PAC	1 / EACH/NUMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABIY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABIY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.</u>	
3	DNF53459	0102-034006-226	5999785154475 / OVER IOAD SS3-120 (0-120 AMP) Range 01 – 120 Amp (Adjustable)	L/PAC	4 / EACH/NUMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABIY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR (MAC</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR (MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.<u>GENERAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR (MAC ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR (MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.</u></p>	
4	DNF52399	0102-034006-226	599978515447 5 / OVER IOAD SS3-120 (0-120 AMP) Range 01 – 120 Amp (Adjustable)	L/PAC	3 / EACH/NUMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		<p><u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR (MAC ELECTRIC) OF CHINA ORIGIN</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR (MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.<u>GENERAL SPECIFICATION - SOURCE OF AVAILABILY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC. MAKE: MAC OPR (MAC ELECTRIC) OF CHINA ORIGIN</u></p> <p>RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR (MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.</p>	
5	DNS54091	21707132/477556-5	4330331080376 / OIL FILTER	VOLVO PENTASSDG D9A2AMG HE SWEDEN	9 / EACH/NUMBER	NO DATA AVAILAB LE		FR	SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									BU SMALL&L ARGE B- 72ESTAT E AVNEUE SITE PO BOX 7158PH# 92(021) 2574910- 19 KARACHI 75700			
6	DNF53775	ST895	662578520489 6 / LCD CCTV CAMERA VIDEO TESTER	ST895 Camera Video Tester Set	1 / SET	ST895	-	Wanglu Tech Co.Ltd 5/F,No.3building,He GuangWu Heng Road, Shangshe,TianHe district, Guang Zhou,China Overseas Market Tel:+86-(0)20-87566118 Fax: +86-(0)20-38075108 E-mail: cctvtester@wanglu. com.cn	Wanglu Technolog y Co. Ltd		<u>TECHNICAL SPECIFICATION - This</u> Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables <u>GENERAL SPECIFICATION -</u> This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables	
7	DNF62509	6 FMX- 150B/wp1 50/TPK 12150/12N DT150S	614070522258 4 / BATTERY 12 VOLT 150 AH VOLTA	MT VEHICEL WB-300	2 / EACH/N UMBER	6 FMX- 150B	NIL	NRTC HARIPUR PAKISTAN	NRTC PAKISTA N		<u>TECHNICAL SPECIFICATION -</u> ITEM IS PART OF JAMMER WB-300 12 volt 150 ah volta tower shape <u>GENERAL SPECIFICATION -</u> ITEM IS PART OF JAMMER WB-300 12 volt 150 ah volta tower shape	
8	DNF57765	AS082122 1081/APC- 1500 VA SMT	613071516845 0 / APC SMART-UPS 1500 VA WITH BATTERIES	UPS APC- 1500VA	1 / EACH/N UMBER	APC-1500 VA SMT		CORPORATE HEADQUARTERS, 132 FAIRGROUNDS,WEST KINGSTON, RI 02892 USA	USA		<u>TECHNICAL SPECIFICATION - a.</u> Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES" <u>GENERAL</u> <u>SPECIFICATION - a.</u> Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES"	
9	DNF5897	AS082122	613071516845	UPS APC-	1 /	APC-1500		CORPORATE	USA		<u>TECHNICAL SPECIFICATION - a.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	5	1081/APC-1500 VA SMT	0 / APC SMART-UPS 1500 VA WITH BATTERIES	1500VA	EACH/NUMBER	VA SMT		HEADQUARTERS, 132 FAIRGROUNDS, WEST KINGSTON, RI 02892 USA			Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES" <u>GENERAL SPECIFICATION</u> - a. Input/ Output voltage: 220V AC b. Input/ Output voltage: 110V AC c. Frequency: 50/ 60 Hz D. backup time : 15-30 MINUTES"	
10	DNM61393	060759	433071518528 0 / FLANGED TYPE OIL-REFRIGERANT SEPARATOR	MAIN AC PLANT(STUS)	1 / EACH/NUMBER	A F 58889		ALCO CONTROLS P O BOX 1270011911 ADIE ROAD St LOUIS USA Ph(314)569-4500 FAX (314)569-4593	ALCO CONTROLS		<u>TECHNICAL SPECIFICATION</u> - DOUBLE CONECTION WITH SOLID COPPER <u>GENERAL SPECIFICATION</u> - DOUBLE CONECTION WITH SOLID COPPER	
11	SNM52365	0023331	311072513010 6 / ANTI-FRICTION BEARING NU 212E	CLUTCH	1 / EACH/NUMBER			GR	M/S SCHOTT EL GERMAN Y HEAD QUARTER SCHOTT EL GMBH & CO KG D-56523 SPAY (RHEIN)		<u>TECHNICAL SPECIFICATION</u> - Inside diameter: 60 mm Outside diameter: 110 mm Width: 22 mm Weight: 0.825 kg <u>GENERAL SPECIFICATION</u> - Inside diameter: 60 mm Outside diameter: 110 mm Width: 22 mm Weight: 0.825 kg	
12	DNM59980	5110	596371521968 7 / AUTOMATIC ENGINE CONTROL MODULE	DG 750 KVA DETROIT 92 SERIES 8163-7406 USA	1 / EACH/NUMBER	5110	16VF-14959	DEEP SEA ELECTRONICS INC. 3230 WILLIAMS AVENUE ROCKFORD, ILLINOIS 61101-2668, U.S.A PHONE:+1(815)316-8706. FAX: +(815)316-8708. EMAIL: dsesales@deepseausa.com web: www.laibapower@yahoo.com	DEEP SEA ELECTRONICS INC.		<u>TECHNICAL SPECIFICATION</u> - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 16 Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60Hz <u>GENERAL SPECIFICATION</u> - DC SUPPLY 8V TO 35V. CRANKING DROPOUTS 0V FO 50MS. FUEL RELAY OUTPUT: 16 Amp DC AUXILIARY RELAY OUTPUTS 5 Amp DC. EXCITATION RANGE: 0V TO 35V. OPERATING CURRENT: 320mA-215mA FREQUENCT: 50Hz-60Hz	
13	DPC618	100	534071516068	DECK	20 /			OEM:ORIGNAL COLOR	ORIGNAL		<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	85		8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	COVERING FOR CONCRETE SURFACE	BAG			CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	COLOR CHIPS,A DIVISION		OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX: 586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS. <u>GENERAL SPECIFICATION - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE: 586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.</u>	
14	DNF60135	RP200-12/93290064C	9999735179016 / BATTERY 12V 200A/H H (MAINTENCE FREE)	Diesel Generator cummince	2 / EACH/NUMBER	RP200-12		ROCKT PREMIUM BATTERY.KOREA.WWW.gbattery.com	ROCKT PREMIUM BATTERY .KOREA		<u>TECHNICAL SPECIFICATION - ROCKT PREMIUM BATTERY. KOREA.WWW.gbattery.com</u> <u>GENERAL SPECIFICATION - ROCKT PREMIUM BATTERY. KOREA.WWW.gbattery.com</u>	
15	DNF62212	BP 5-12	6140735131011 / BATTERY 12V /5AH(DRY LED ACID)	UPS 5KVA	16 / EACH/NUMBER	NO DATA AVAILAB LE		KO	M/S VISION KORIAN		<u>TECHNICAL SPECIFICATION - 12V 5AH 4"X3.5"X2.7"</u> <u>GENERAL SPECIFICATION - 12V 5AH 4"X3.5" X2.7"</u>	
16	DPC59983	1141674/22567233	6150735141424 / COOLANT READY MIX (5 LTR) (volvopenta)	VOLVOPANTA ENGINE	80 / LITER	NO DATA AVAILAB LE		00	M/S AB VOLVOP ANTA 405 08 GOTEBO RG SWEEDN		<u>TECHNICAL SPECIFICATION - PACKING: 05 Liter can</u> <u>GENERAL SPECIFICATION - PACKING: 05 Liter can</u>	
17	DNF61486	NS4P1G	5915705215938 / GIGABYTE TRANSMISSIO N NETWORK SWITCH- 4PORT POE-HD	CCTV SYSTEM NS4P1G PAKISTAN	12 / EACH/NUMBER	NS4P1G		AL-Sa'ee Business Solutions, Suit 30, 3rd Floor, Crown Centre. Plot SB-1 Opp Bait-ul-Mukarram Masjid, Gulshan-d-Iqbal Karachi	Al-Sa'ee/Pro Secure		<u>TECHNICAL SPECIFICATION - Gigabyte transmission network switch- 4 port POE-HD resolution transmission (compatible) Make China branded</u> <u>GENERAL SPECIFICATION - Gigabyte transmission network switch- 4 port POE-HD resolution transmission (compatible) Make China branded</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
18	DPC62753	H-300 HUX	8040735140710 / HARDNER (SET OF 2X1KG BOTTLE)	AC COMPRESSOR KALMAT GWADER	25 / SET	NO DATA AVAILABLE			00		TECHNICAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>GENERAL SPECIFICATION - A.V 330-360, Viscosity, cps @ 40 c., Color, Gardner.6, Appearance, Brown , Flash point, 200f>	
19	DNZ57955	D100802.50	4310014166854 / CYLINDER LINER ASSEMBLY	MAIN CIRCUIT BRACKER	1 / EACH/NUMBER	NO DATA AVAILABLE			UK	COMPAIR UK LTD. REAVELL 53-56 WHITE HOUSE ROAD IPSWICH ENGLAND IPI 5PB	TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .	
20	DGT40793	USA001	5306705180067 / FIR DOUGLAS SHORE SIZE 26'X6-1/2	NIL	66 / CUBIC FOOT				NOT KNOWN		TECHNICAL SPECIFICATION - SHORES ARE REQUIRED FOR DOCKING OF SUBMARINES AND SHIP IN FLOATING DOCK-I & IV. GENERAL SPECIFICATION - SHORES ARE REQUIRED FOR DOCKING OF SUBMARINES AND SHIP IN FLOATING DOCK-I & IV.	
21	DNZ56362	D100573.13	2930795138829 / DIAPHRAGM DRAIN VALVE SIGNAL PIPE	MAIN AIR COMPRESSOR	2 / EACH/NUMBER	NO DATA AVAILABLE			UK	COMPAIR UK LTD ENGLAND	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
22	SNM51678	FF9003000	2910715170013 / FUEL FILTER	DIESEL ENGINE CUMMINS (GRP CREEK CRAFT)	40 / EACH/NUMBER	QSB.9-305 MCD		OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM.	NIL		TECHNICAL SPECIFICATION - OEM:M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A. HEWITT@CUMMINS.COM. GENERAL SPECIFICATION - OEM: M/S CUMMINS INC. 500 JACKSON ST COLUMBUS STE: IN UNITED STATES 47201-6258 TEL: 812-377-3920 FAX: 812-377-1715 EMA: STEVE.A.HEWITT@CUMMINS.COM.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
23	DNV58398	H76228-8	5330795229234 / SERVICE KIT C	PROPULSION SHAFT SEAL	1 / KIT	200 PSE	NIL	WARTSILA UK LTD MARPLES WAY, HAVANT HAMPSHIRE, PO9 INX,UK	WARTSILA UK		<u>TECHNICAL SPECIFICATION - SEE ATTACHED DOCUMENT</u> <u>GENERAL SPECIFICATION - SEE ATTACHED DOCUMENT</u>	
24	DNM57632	3581894	2815270382280 / ROCKER ARM (CYLINDER HEAD, EXCHANGE)	PLUG (CYLINDER HEAD, EXCHANGE)	24 / EACH/NUMBER	D6-370D-E		AB VALVO PENTA SE 40508 GOTHENBURG SWEDEN	VALVO PENTA SWEDEN		<u>TECHNICAL SPECIFICATION - ROCKER ARM (CYLINDER HEAD, EXCHANGE)</u> <u>GENERAL SPECIFICATION - ROCKER ARM (CYLINDER HEAD, EXCHANGE)</u>	
25	DNM61317	BRA10312H	2530715140377 / AIR COMPRESSOR 10HP 380V, 3PHASE, MAX. 175PSI	AIR COMPRESSOR	1 / EACH/NUMBER	FTK100300		US	SNAP ON LOGISTICS COMPANY CUSTOMER WARRANTY INFORMATION CENTER KENOSH A WISCONSIN 53141-1410.262-656-5200		<u>TECHNICAL SPECIFICATION - a. OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175</u> <u>GENERAL SPECIFICATION - a. OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175</u>	
26	SPK59384	841GB	9150795160135 / DEKS OLJE D.2 FLEXIBLE HIGH GLOSS FINISH (01 LITER Pack) OEM = OWATROL	SHIP WOODEN STRUCTURE, HULL	22 / LITER			MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL: +33(0) 160 86 48 70, FAX: +38 (0) 160 88 84 84-LEQUAL	OWATROL-DURIEU GROUP-BP75-		<u>TECHNICAL SPECIFICATION - MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL: +33(0) 160 86 48 70, FAX: +38 (0) 160 88 84 84-LEQUAL</u> <u>GENERAL SPECIFICATION - MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL: +33(0) 160 86 48 70, FAX: +38 (0) 160 88 84 84-LEQUAL</u>	
27	DNZ55896	D102008.50 / D66376.50	4310014164572 / PISTON ASSEMBLY	MAIN AIR COMPRESSOR	1 / EACH/NUMBER	NO DATA AVAILABLE		UK	COMPAIR UK LTD		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
28	DNM423	11998/119	533017112794	D/G 150KVA	4 /			GR	M/S		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	57	98-2	8 / GASKET (F8)		EACH/NUMBER				VOLVO PENTA GERMAN Y		nullGENERAL SPECIFICATION - null	
29	SNM61060	6V4365	5331014381780 / SEAL O RING	MAIN ENGINE	10 / EACH/NUMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPILLAR		TECHNICAL SPECIFICATION - CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189GENERAL SPECIFICATION -CATTER PILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P.O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
30	DNF63352	P-0143000-A/YT-100B	5660785172597 / COMPOSITE MATERIALS E-FENCE ROD S.S POLE SQUARE TUBE ANGLED TYPE , BLACK PODER COATED & HOT DIP GALVANISED WITH ACCESSORIES.	PSS	30 / EACH/NUMBER	YT-100B E-Fence Controller		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		TECHNICAL SPECIFICATION - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC 15W P/NO.(ES-626) 13) E-FENCE LIGHT P/NO. (SR-FL/TL/G) NOTE: ITEM S.NO.12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK GENERAL SPECIFICATION - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											(9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC 15W P/NO.(ES-626) 13) E-FENCE LIGHT P/NO. (SR-FL/TL/G) NOTE: ITEM S.NO.12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK	
31	SNM538 43	174-9638	530601507158 2 / BOLT	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	32 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION</u> - total length (in): 1.6 total width (in): 0.8 total height (in): 0.8 screw length (in): 1.18 screw type: hex flange head coating: oil with corrosion inhibitor cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5 <u>GENERAL SPECIFICATION</u> - total length (in): 1.6 total width (in): 0.8 total height (in): 0.8 screw length (in): 1.18 screw type: hex flange head coating: oil with corrosion inhibitor cable length (in): 0.15 thread: coarse thread size (in-tpi) (in): m10-1.5	
32	SNM537 94	241-3359	531001543595 8 / WASHER-SEALING (13.25X18.45X1.6-MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	12 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION</u> - Inside Diameter (in): 0.522 Material: Aluminum/Rubber Coating: None Outside Diameter (in): 0.726 Thickness (in): 0.063 Washer Type: Sealing Washer <u>GENERAL SPECIFICATION</u> - Inside Diameter (in): 0.522 Material: Aluminum/Rubber Coating: None Outside Diameter (in): 0.726 Thickness (in): 0.063 Washer Type: Sealing Washer	
33	SNM538 48	335-7585	533101627283 9 / O RING	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> -	
34	SNM538 21	198-9169	472071522837 0 / HOSE	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	4 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610	ALLIED CAT		<u>TECHNICAL SPECIFICATION</u> - width(IN): 0.9, LENGTH(in): 49.5, HEIGHT(in): 0.9 <u>GENERAL SPECIFICATION</u> - width(IN): 0.9, LENGTH(in): 49.5, HEIGHT(in): 0.9	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA				
35	DNJ58839	32700	432076516874 3 / WASH DOWN PUMP	SFB (ENGINE)	1 / EACH/ NUMBER	F350A	102563X35	JABSCO USA PH: 1 978 281 0440//YAMAHA CORPORATION USA/JAPAN	YAMAHA		<u>TECHNICAL SPECIFICATION -</u> YAMAHA CORPORATION USA/JAPAN a. Equipment pressure Shut off valve pressure 3.5 Bar b. Electrical Supply 24V DC c. Inlet Outlet ports piping dimensions for 13mm (1/2") bore hose 250mm long, 2500mm, 105mm wide, 100mm height <u>GENERAL SPECIFICATION -</u> YAMAHA CORPORATION USA/JAPAN a. Equipment pressure Shut off valve pressure 3.5 Bar b. Electrical Supply 24V DC c. Inlet Outlet ports piping dimensions for 13mm (1/2") bore hose 250mm long, 2500mm, 105mm wide, 100mm height	
36	DGP57236	10SDR 9S7- 16W112- 864 / WS- 66 / MSGL638 SE209	702573523241 7 / LAPTOP MSI 15.6 GL63- 8SE	UFFFAQ	1 / UNIT	MSI 15.6 GL63-8SE		OFFICE 3037, 3RD FLOOR, 46-66/B LAJOS STREET, 1036 BUDAPEST, HUNGARY	MSI HUNGARY		<u>TECHNICAL SPECIFICATION - MSI</u> LAPTOP MSI 15.6 DISPLAY GL63- 8SE-8SE INTEL 8 GEN CORE I7 PROCESSOR OS WINDOWS 10 PRO GRAPHICS NVIDIA GEFORCE RTX 2060 6 GB DDR6 RAM 32 GB SSD 1TB WITH M2 128 GB <u>GENERAL SPECIFICATION - MSI</u> LAPTOP MSI 15.6 DISPLAY GL63- 8SE-8SE INTEL 8 GEN CORE I7 PROCESSOR OS WINDOWS 10 PRO GRAPHICS NVIDIA GEFORCE RTX 2060 6 GB DDR6 RAM 32 GB SSD 1TB WITH M2 128 GB	
37	DNM58859	184850	311073517561 2 / NEEDLE BEARING	IPS 500	1 / EACH/ NUMBER	IPS 500	IPS- F3940012 979	VOLVO PENTA	VPL SWEDEN VOLVO PENTA		<u>TECHNICAL SPECIFICATION -</u> VOLVO PENTAGENERAL <u>SPECIFICATION - VOLVO PENTA</u>	
38	DNF61135	CAT-6A U- FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE- 0.36MM 4/U- FTP	CCTV System CAT-6A U-FTP CHINA	230 / FOOT	CAT-6A U-FTP	NA	No. 1199 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-87688883	CHINA		<u>TECHNICAL SPECIFICATION -</u> oem, contech solution USA. www. CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U- FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			PVC/LSZH-0.5 MM AQUA/BUE/G RAY7.47MM								capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION</u> - oem, contech solution USA. www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
39	DNO60230	GCP-677PC16	432001045264 2 / SEAL ASSEMBLY, SHAFT, SPRING LOAD	SEA WATER CIRCULATING PUMP	1 / EACH/NUMBER			M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199	M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR		<u>TECHNICAL SPECIFICATION</u> - 1.250 INCH DIA SHAFT Part no GCP-689-16, john crane mechanical seal type 21 for 1-1/4shaft dia M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199 <u>GENERAL SPECIFICATION</u> - 1.250 INCH DIA SHAFT Part no GCP-689-16, john crane mechanical seal type 21 for 1-1/4shaft dia M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199	
40	DNO63211	GCP-677PC16	432001045264 2 / SEAL ASSEMBLY, SHAFT, SPRING LOAD	SEA WATER CIRCULATING PUMP	1 / EACH/NUMBER			M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199	M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR		<u>TECHNICAL SPECIFICATION</u> - 1.250 INCH DIA SHAFT Part no GCP-689-16, john crane mechanical seal type 21 for 1-1/4shaft dia M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199 <u>GENERAL SPECIFICATION</u> - 1.250 INCH DIA SHAFT Part no GCP-689-16, john crane mechanical seal type 21 for 1-1/4shaft dia M.T. DAVIDSON COMPANY 302 GRAND AVE SUPERIOR UNITED STATES CAGE CODE 16062 PHONE NO 715-394-4444 FAX NO 715-394-6199	
41	SNM610	0619455	533101469760	MAIN ENGINE	7 /		NA	USA	CATER		<u>TECHNICAL SPECIFICATION</u> -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	59		7 / SEAL 'O' RING	CATTER PILLAR C-18	EACH/NUMBER				PILLAR		ITEM REQUIRED FOR TOH/MOH OF MAIN ENGINES <u>GENERAL SPECIFICATION - ITEM REQUIRED FOR TOH/MOH OF MAIN ENGINES</u>	
42	DPC62751	DERAKAN E 8084	803073514178 9 / EPOXY VINYL ESTER RESIN	MRTP33&VBS S BOATS	50 / KILOGRAMME	NO DATA AVAILABLE		OC	1. ASHLAND CHEMICAL HISPANIA ,S.L. PARTIDA POVET 37 APDO CORREOS 26, BENICARLO, CASTELLON 12580, SPAIN. TEL#+34964467393 , FAX#+3496447411 7. 2. M/S YONCA-ONUK JV, TERSANELER CADDESI 50/3 34.940 TUZLA ISTAN		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY-2: ASHLAND CHEMICAL HISPANIA,S.L.PARTIDA POVET 37,APDO CORREOS 26 BENICARLO, CASTELLON 12580,SPAIN.TEL#+34964 46 7393,FAX#+34 964 47 4117</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY-2: ASHLAND CHEMICAL HISPANIA,S.L.PARTIDA POVET 37,APDO CORREOS 26 BENICARLO, CASTELLON 12580,SPAIN.TEL#+34964 46 7393,FAX#+34 964 47 4117</u>	
43	SNC61516	BE01	6140MB300007 5 / dual agm Battery	EXIDE SERVICE Battery	1 / EACH/NUMBER	EP 1200	PL-TME98-001-L818	BUILDING 200 13000 DEERFIELD PARKWAY MILTON, GEORGIA, 30004 UNITED STATES	EXIDE		<u>TECHNICAL SPECIFICATION - a. Complete description of the Battery: Dual AGM Battery b. Specification : 1200Wh c. Model : EP 1200 d. Voltage : 12V e. Rating (AH) of the Battery : 140 Ah f. Parent Equipment Batteries and service facilities g. Population in Parent Equipment 01 h.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Source of availability : Building 200 13000 DEERFIELD PARKWAY MILTON, GEORGIA, 30004 UNITED STATES <u>GENERAL SPECIFICATION</u> - a. Complete description of the Battery: Dual AGM Battery b. Specification : 1200Wh c. Model : EP 1200 d. Voltage : 12V e. Rating (AH) of the Battery : 140 Ah f. Parent Equipment Batteries and service facilities g. Population in Parent Equipment 01 h. Source of availability : Building 200 13000 DEERFIELD PARKWAY MILTON, GEORGIA, 30004 UNITED STATES	
44	SNM538 17	0676135 / 067-6135	531501650330 2 / KEY-WOODRUFF	DG CAT 7.1 USA	8 / EACH/NUMBER	CAT 7.1	NIL	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION</u> - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs <u>GENERAL SPECIFICATION</u> - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
45	DPC592 88	MS-941/CO2 or MS941	685001383671 9 / Cleaning compound solvent	NIL	40 / CAN	NA	NA	MILLER-STEPHENSON CHEMICAL COMPANY, INC, 55 BACKUS AVE, DANBURY, USA	MILLER-STEPHENSON CHEMICAL COMPANY, INC, DANBURY, USA		<u>TECHNICAL SPECIFICATION</u> - PMS Item <u>GENERAL SPECIFICATION</u> - PMS Item	
46	DPC601 51	RIVOLTA SLX-500	6850FT100406 9 / Cleaner for Electrical	NIL	2 / EACH/NUMBER	NA	NA	BREMER & LEGUIL GMBH, AM BURGACKER 30-42, DUISBURG, GERMANY Postal Code: 47051	BREMER & LEGUIL GMBH, GERMANY		<u>TECHNICAL SPECIFICATION</u> - PMS Item <u>GENERAL SPECIFICATION</u> - PMS Item	
47	DNF5065 6	BLR-MC 12	594572523135 5 / POWER FACTOR CONTROLLER RELAY	PFIPs 504 KVAR	3 / EACH/NUMBER	MLR-MC-12	321134	BELUK INTERNATIONAL INGOLSTADTER STRASSE 62. TELE: 089-3169330 TELE FAX: 089-3110046	MERLIN GERIN		<u>TECHNICAL SPECIFICATION</u> - 450V 60Hz 9VA HEM MODEL BLR-MC-12 MAKE MERLIN GERIN MADE IN GERMANY <u>GENERAL SPECIFICATION</u> - 450V 60Hz 9VA HEM MODEL BLR-MC-12 MAKE MERLIN GERIN MADE IN GERMANY	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
48	DNF56443	SCST09S YE3	601078523256 6 / SM-SIMPLEX-SC/APC-ST/APC 3.0 M OFC PATCH CORD	PSS VIGIL	11 / EACH/NUMBER	SCST09S YE3		FIBREFAB ASIA & PACIFIC NO.2708, HANGGANG FUCHUN BUILDING. 6031 SHENNAN ROAD. FUTIAN DISTRICT. SHENZHEN, CHINA. TEL: 86-755-2561-3694 FAX: 86-755-2561-3697 E-MAIL: SALES@FIBREFAB.COM	FIBERFAB CHINA		<u>TECHNICAL SPECIFICATION</u> - Connector: SC/APC Length: 03 Meters Core: Single mode fiber Density: Simplex Vibration (dB): 0.1 (5 to 50Hz)(1.5mm) Tensil Strength: 0.1 (0 to 15 Kg pull) A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB) <u>GENERAL SPECIFICATION</u> - Connector: SC/APC Length: 03 Meters Core: Single mode fiber Density: Simplex Vibration (dB): 0.1 (5 to 50Hz)(1.5 mm) Tensil Strength: 0.1 (0 to 15 Kg pull) A1 0.16 dB 32 dB Ins. Loss (dB) B1 0.02 dB 22 dB Ret. Loss (dB)	
49	DNF63354		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	1 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		<u>TECHNICAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
50	DNS55322	145 002	281573518556 4 / PROTECTING PIPE	WARTSILA MAIN ENGINE 9L20C3 FINLAND	1 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
51	DNS61054	200 006	312073518541 4 / BELLOWS	WARTSILA MAIN ENGINE 9L20C3 FINLAND	3 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION</u> - TPI <u>GENERAL SPECIFICATION</u> - TPI	
52	DNS60519	1161277	803014547069 4 / SEALANT	VOLVO PENTA SSDG D9A2A	5 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg,	AB Volvo Penta		<u>TECHNICAL SPECIFICATION</u> - MADADGAR 1009155503(STBD)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				MG HE SWEDEN	UMBER			Sweden Tel: +46 31 23 54 60	Sweden		1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
53	DNS49336	165 042	2815735185700 / TWO WAY PRESSURE VALVE, COMPL.	WARTSILA MAIN ENGINE 9L20C3 FINLAND	16 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243 , PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	
54	SNM53817	0676135 / 067-6135	5315016503302 / KEY-WOODRUFF	DG CAT 7.1 USA	8 / EACH/NUMBER	CAT 7.1	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs</u> <u>GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs</u>	
55	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08</u> <u>GENERAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08</u>	
56	DNN50952	YBH-20	4320FP3000007 / YBH-20 Portable submersible electric pump	YBH-20 PORTABLE SUBMERSIBLE ELECTRIC PUMP (F-22P SHIPS)	1 / SET	YBH-20	N/A		JIANGSU ZHENHUA PUMP MANUFACTURE CO.,LTD		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
57	DNN55087	YBH-20	4320FP3000007 / YBH-20 Portable	YBH-20 PORTABLE SUBMERSIBLE	3 / SET	YBH-20	N/A		JIANGSU ZHENHUA PUMP		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			submersible electric pump	E ELECTRIC PUMP (F-22P SHIPS)					MANUFACTURE CO.,LTD			
58	DGT34983	NO DATA AVAILABLE	9340705149923 / MEDIUM DENSITY FIBER BOARD (LASANI) TEAK COLOUR. LAMINATION ONE SIDE, DENSITY 750 KG/CUB to 850 KG/CUB . METER SIZE L:8' W: 4' TH: 6MM, MOISTURE RESISTANT	WOOD WORKS SHIPS&ESTABLISHMENT	9 / SHEET	NO DATA AVAILABLE		PK	SOURCE: M/S MEHRAN ART WOOD SHOP NO 9, PANJETA NI HOUSE, SIDDIQ WAHAB ROAD, TIMBER MARKET KARACHI . TEL/ FAX: +92-21-32776064 .MOBILE 0322-2578654.		<u>TECHNICAL SPECIFICATION - SIZE</u> Length: 8 feet Width: 4 feet Thickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB <u>GENERAL SPECIFICATION - SIZE</u> Length: 8 feet Width: 4 feet THickness : 6 MM colour : teak DENSITY 750 KG/CUB TO 850 KG/CUB	
59	DNQ62162	22/90142	4210997817034 / SYPHON TUBE ASSY (AFFF)	FIRE EXTINGUISHER	6 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK ENGLAND		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
60	SNJ51741	9900B-45292 /31135-94900	5360765222416 / SPRING	SUZUKI DF300AP 300 HP OBM	40 / EACH/NUMBER	SUZUKI DF300AP 300 HP OBM	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
61	DNQ53119	FP-30-001	4920705161599 / CAST IRON FRONT COVER	FF TRG PUMP	1 / EACH/NUMBER		006	MERAJ LIMITED HEAD OFFICE: PLOT NO 11 SECTOR 15 KORANGI INDUSTRIAL AREA KARACHI 74900 PAKISTAN TEL: 5050145-6 FAX: 92-21-5060663 E-MAIL:meraj@cyber.net.pk UAN: 111163725 URL: www.meraj.net.pk	MERAJ LIMITED		<u>TECHNICAL SPECIFICATION - cast iron front cover</u> <u>GENERAL SPECIFICATION - cast iron front cover</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
62	DNQ53118	FP-30-010	4920705161607 / CAST IRON SEAL COVER	FF TRG PUMP	1 / EACH/NUMBER		006	MERAJ LIMITED HEAD OFFICE: PLOT NO 11 SECTOR 15 KORANGI INDUSTRIAL AREA KARACHI 74900 PAKISTAN TEL: 5050145-6 FAX: 92-21-5060663 E-MAIL:meraj@cyber.net.pk UAN: 111163725 URL: www.meraj.net.pk	MERAJ LIMITED		<u>TECHNICAL SPECIFICATION - CAST IRON SEAL COVER</u> <u>GENERAL SPECIFICATION - CAST IRON SEAL COVER</u>	
63	DNJ63315	17400-98J01	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	4 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
64	DNJ58834	15413-93J10	2895765221634 / CASE ASSY, FUEL FILTER	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
65	DNJ47612	65770-93J02 / 65770-93J04 / 65770-93J13	2940765222205 / PUMP, SQUEEZE	SUZUKI DF300AP 300 HP OBM	8 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - Manufacture: Suzuki Motor Corporation Japan OEM: SUZUKI country of origin: JAPAN</u> <u>GENERAL SPECIFICATION - Manufacture: Suzuki Motor Corporation Japan OEM: SUZUKI country of origin: JAPAN</u>	
66	DNJ63255	09482-00427	2920765222410 / SPARK PLUG (BKR6E)	SUZUKI DF300AP 300 HP OBM	12 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
67	DNJ63270	57130-87D10	3110765221607 / BUSH, DRIVE SHAFT	SUZUKI DF300AP 300 HP OBM	4 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
68	DNJ58836	17471-98J01	2920765222099 / PANEL, PUMP CASE UNDER	SUZUKI DF300AP 300 HP OBM	3 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
69	DNJ58842	15411-93J10	5340765221628 / CAP, FUEL FILTER	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
70	SNJ54843	09383-07003	5331765221793 / E RING	SUZUKI DF300AP 300 HP OBM	20 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
71	SNJ56872	09320-08062	9320765221766 / CUSHION	SUZUKI DF300AP 300 HP OBM	16 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
72	DNF63356	S-100-12/YH-100-12 / P-0145000-A	6130785167249 / POWER SUPPLY 12V6A 119-239V	FIXED PTZ IP CAMERA	1 / EACH/NUMBER	YH-100-12		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120	M/S CETC INTERNATIONAL CO CETC CHINA		<u>TECHNICAL SPECIFICATION - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664</u> <u>GENERAL SPECIFICATION - M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120 oem hi- tech security products nargis block ilama iqbal town lahore 03081517664</u>	
73	SNJ54844	25141-93L00-Y5S	5340765221943 / HOUSING, SHIFT ROD GUIDE (WHITE)	SUZUKI DF300AP 300 HP OBM	15 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NIL</u> <u>GENERAL SPECIFICATION - NIL</u>	
74	DPC62993	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	6 / GALLON			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLOE E INC		<u>TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u> <u>GENERAL SPECIFICATION - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS</u>	
75	DNF57656	2290247	4470785225283 / UPS, UPS2000G, 6KVA, SINGLE PHASE	Power Equipment	1 / EACH/NUMBER	UPS2000-UPS2000-G-6KRTL	2102290247BTK60000852102290247BTK6000108	9th Floor, Tower 6, The Gateway, No. 9 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong	HUAWEI		<u>TECHNICAL SPECIFICATION - BACKUP TIME: 15 MINS</u> <u>GENERAL SPECIFICATION - BACKUP TIME: 15 MINS</u>	
76	SNM57032	943478	4720995332967 / HOSE CLAMP (CHARGE AIR COOLER)	AIR COOLER	50 / UNIT	D6-370D-E	NA	AB VOLVO PENTA SE 405 08 GOTHENBURG SWEDEN	SWEDEN		<u>TECHNICAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u> <u>GENERAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u>	
77	SNM61052	2M-9780	5331009390687 / SEAL-O-RING	CATERPILLAR GENSET D3512B	20 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
				(YBB1) USA								
78	SNM61051	4J-5477	5331008558059 / SEAL-O-RING	CATERPILLAR GENSET D3512B (YBB1) USA	12 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
79	DGP57826	12U PDU	5995705177966 / 19 INCH WALL MOUNT RACK 12U	CNA LAN NETWORK	1 / EACH/NUMBER			TOTEN	TOTEN		<u>TECHNICAL SPECIFICATION - 19</u> INCH WALL MOUNT RACK 12U WIDTH 600 MM, DEPTH 600MM, DOUBLE SECTION, GREY, GLAZED (FRONT GLASS DOOR , BACK WALL FITTED SWG16, SWG 18 OF 4 WAY BRITISH FLAT PIN SOCKET M/S INBOX TECHNOLOGIES PVT LTD KARACHIGENERAL <u>SPECIFICATION - 19 INCH WALL</u> MOUNT RACK 12U WIDTH 600 MM, DEPTH 600MM, DOUBLE SECTION, GREY, GLAZED (FRONT GLASS DOOR , BACK WALL FITTED SWG16, SWG 18 OF 4 WAY BRITISH FLAT PIN SOCKET M/S INBOX TECHNOLOGIES PVT LTD KARACHI	
80	SNS55051	198-8645	4720015235169 / Hose (Crankcase Breather)	Caterpillar Emergency DG Marine Genset C 4.4 USA	2 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
81	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENS		<u>TECHNICAL SPECIFICATION -</u> BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08 <u>GENERAL SPECIFICATION -</u> BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									E PRODUCTS		(IN): 4 THICKNESS (IN): 0.08	
82	DNF56170	KR40KVA / NST-5400040	613070523223 / 8 / 40 KVA UPS WITH 60 MINUTES BACKUP TIME	40 KVA UPS WITH 60 MINUTES	1 / EACH/NUMBER	KR40KVA / NST-5400040	NIL	ADVANCE ENGINEERING GROUP 72H BLOCK2, P.E.C.H.S NEAR NOOR MASJID KASHMIR KARACHI PAKISTAN	ADVANCE ENGINEERING GROUP		TECHNICAL SPECIFICATION - SPECIFICATION: UPS ONLINE DOUBLE CONVERSION SINE WAVE. BRAND: ABLEREX MODEL: KR40KVA ORIGIN: ITALY 3 PHASE IN/OUT 50HZ BACKUP TIME: 60 MINUTES ON 100-120 COMPUTER SYSTEM WITH EXTERNAL BATTERIES BATTER BRAND: SPRINTER EXIDE BATTERY RATING: 12V 41AH X 40 PSC BATTERY ORIGIN: PORTUGAL WARRANTY: 02 YEARS COMPREHENSIVE REPLACEMENT WARRANTY WILL BE OFFERED INCLUDING BATTERIES GENERAL SPECIFICATION - SPECIFICATION: UPS ONLINE DOUBLE CONVERSION SINE WAVE. BRAND: ABLEREX MODEL: KR40KVA ORIGIN: ITALY 3 PHASE IN/OUT 50HZ BACKUP TIME: 60 MINUTES ON 100-120 COMPUTER SYSTEM WITH EXTERNAL BATTERIES BATTER BRAND: SPRINTER EXIDE BATTERY RATING: 12V 41AH X 40 PSC BATTERY ORIGIN: PORTUGAL WARRANTY: 02 YEARS COMPREHENSIVE REPLACEMENT WARRANTY WILL BE OFFERED INCLUDING BATTERIES	
83	DNM59982	CPMU-32	599970521945 / 5 / THERMOSTAT CONTROL (FOR MANUAL MODE)	MOBILE AC CWM-2C70-PN	1 / EACH/NUMBER	ETC-3000	12	ADDA PLOT, SHARAIZ AVENUE, JATTI UMRA ROAD, RAIWIND ROAD, LAHORE	M/S COOL POINT PVT LTD LAHORE		TECHNICAL SPECIFICATION - RANGE -50 TO + 50 WIDE RANGE THERMOSTAT UT 72 GENERAL SPECIFICATION - RANGE -50 TO + 50 WIDE RANGE THERMOSTAT UT 72	
84	DGE21192		0414599231710 / LINING MATERIAL FOR USE IN		100 / SQ FEET						TECHNICAL SPECIFICATION - ITEM SPECIFICATION: DESCRIPTION=LINING MATERIAL FOR USE IN CRANE,WIDTH=12",	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CRANES LG.4. WD.12" THICKNESS 1/4". DENOMINATION SQ FT								THICKNESS=1/4", DENOMINATION SQ FT MATERIAL= DENSELY WOVEN, SEMI-FLEXIBLE FRICTION MATERIAL (YARN SPUN FROM MIXTURE OF GLASS &SYNTHETIC FIBERS REINFORCED WITH FINE COPPER WIRE TO IMPROVE STRENGTH AND HEAT DISSIPATION CHARACTERISTICS) <u>GENERAL SPECIFICATION - ITEM SPECIFICATION:</u> DESCRIPTION=LINING MATERIAL FOR USE IN CRANE,WIDTH=12", THICKNESS=1/4", DENOMINATION SQ FT MATERIAL= DENSELY WOVEN, SEMI-FLEXIBLE FRICTION MATERIAL (YARN SPUN FROM MIXTURE OF GLASS &SYNTHETIC FIBERS REINFORCED WITH FINE COPPER WIRE TO IMPROVE STRENGTH AND HEAT DISSIPATION CHARACTERISTICS)	
85	DPC604 16	BS1913/66	047450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE JELLY 18KG DRUM	SKF COUPLING	700 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE</u> <u>GENERAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE</u>	
86	DPK6352 9		047550942921 3 / LINSEED OIL BOILED ACID NO8 SP GR 0.935- 0.955 AT 15.5 DEG C.		60 / LITER						<u>TECHNICAL SPECIFICATION - BS6900</u> <u>GENERAL SPECIFICATION - BS6900</u>	
87	DGE270 98	nil	035059571312 1 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM		120 / FATHO M						<u>TECHNICAL SPECIFICATION - 1. MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1. MIN</u> BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.</p>	
88	DGE17199	nil	035059571312 1 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM		1660 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1.</u> MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1. MIN</u> BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
89	DGE58500	nil	035059571312 1 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM		240 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1.</u> MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1.</u> MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.</p>	
90	DGE20639	nil	035059571312 1 / Rope Nylon Hawser laid White 3 Strand Circular 1 Inch Diameter 8MM		360 / FATHO M						<p><u>TECHNICAL SPECIFICATION - 1.</u> MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NLYON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES. <u>GENERAL SPECIFICATION - 1.</u> MIN BREAKING LOAD: 13.2 KN, 2. 120 FATHOM PER COIL, 3. WEIGHT: 04KG/100M, 4. DENSITY: RELATIVE DENSITY 1.14, 5. CHEMICAL RESISTANCE: LIMITED</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RESISTANCE TO ACIDS 6. MANUFACTURED TO STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 9554 OF 2005 & ISO 2307 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATES.	
91	SGE16759	NIL	035059571312 6 / ROPE NYLON, HAWSERLAID WHITE, 3- STRAND, CIRC: 02- INCH, DIA: 16MM,		200 / FATHO M	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK GENERAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK	
92	DGE20641	NIL	035059571312 6 / ROPE NYLON, HAWSERLAID WHITE, 3- STRAND, CIRC: 02- INCH, DIA: 16MM,		60 / FATHO M	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK GENERAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM per COIL. 3. OEM: COTESI UK	
93	DPC60346		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
94	DPC593 21		044250000587 2 / INSECTICIDE BENZINE HEXACHLORI DE		10 / LITER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
95	SGH514 25		028359571116 7 / SHEET ALUMINIUM ALLOY SIZE: L X W X TH, 144 INCH X 48 INCH X 0.128 INCH. WT. PER SQ FOOT: 1.764 (LB). QUATER HARD AUTHORITY: BR-3200		2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION</u> - 1. mechanical properties: bs en 485-2 of 2016 2. chemical composition: bsen 573-3 of 2007 3. trmp condition: h12 4. grade: en aw 5251 5. quater hard authority br-3200 <u>GENERAL SPECIFICATION</u> - 1. mechanical properties: bs en 485-2 of 2016 2. chemical composition: bsen 573-3 of 2007 3. trmp condition: h12 4. grade: en aw 5251 5. quater hard authority br-3200	
96	SGE493 57	NIL	041359923892 3 / RUBBER SHEET SOLID NATURAL (CLOTH INSERT)		50 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL. <u>GENERAL SPECIFICATION - SPECIFICATION OF ITEM AS PER NMCRL: 1. STRENGTHENING FEATURE= INSERT, 2. STRENGTHENING FEATURE MATERIAL= FABRIC OR FLAX, 3. NONMETALLIC HARDNESS RATING= 42.0 MINIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, 4. MINIMUM TENSILE STRENGTH= 2500 POUNDS PER SQUARE INCH, 5. WIDTH= 43-INCHES NOMINAL, 6. THICKNESS= 0.031-INCHES NOMINAL, 7. LENGTH= 72-INCHES 8. MATERIAL= RUBBER NATURAL.</u>	
97	DGE704 2	0414-2846	041459923097 5 / GASKET COPPER & ASBESTOS I. DIA 33/64" E. DIA 7/8"THICK 3/32".		72 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
98	DPC632 13	DEFSTAN 80-50/3 Shade no 106 BS 381-C OF 1996	044250910672 4 / PAINT FINISHING, ALKYD (ROYAL BLUE) FLASH POINT 32C (04 LTR Packing)	VEHICLES + COMPAK BARGE	500 / LITER						<u>TECHNICAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN</u> <u>GENERAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN</u>	
99	SPC5938 2	Defstan 80-78 OF 1995	044250942119 3 / PAINT FINISHING	BILGES, CABINS	180 / LITER						<u>TECHNICAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)								prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) <u>GENERAL SPECIFICATION - FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection</u> prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
100	SGB49055		0212595710705 / BAR STEEL CORROSION RESISTING H/R RD 03" WT PER FT24. 030LBS	MAT IDEN SYMBLO. L42H35 18% CHROM	2 / METER						<u>TECHNICAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter</u> <u>GENERAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter</u>	
101	SGB31181	DIA 3/16 LG3/4TO 2	0266590013907 / FIXED PUSH ON POLYTHENE STUD FOR SECURING INSULATION	DIA 3/16 LG 3/4 TO 2	130 / HUNDR ED						<u>TECHNICAL SPECIFICATION - DIA 3/16 LG3/4TO 2</u> <u>GENERAL SPECIFICATION - DIA 3/16 LG3/4TO 2</u>	
102	DGH32341		0211599230139 / PLATE STEEL CARBON SIZE 2500X1250X03 MM	HOUSE SIDE FTG	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects.</u> <u>GENERAL SPECIFICATION - BSEN:10025/2 OF 2019, STEEL GRADE: S275 JR. special instructions: a. MILL TEST certificate (MTC) required alongwith supply. the certificate should have information on mechanical & chemical properties, steel grade, batch & heat number</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											alongwith date. b. each plate shall have a suitable stamp at a corner indicating batch number, grade and manufacturer for case identification. c. material should be freshly rolled & free steel all defects.	
103	SGE202 72417	DEFSTAN 40-3	033059571325 3 / TWINE HEMP 3- STRAND, MIN BKG STRENGTH 810 LBS, DIA: 7mm		47 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM</u> Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS <u>GENERAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM</u> Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS	
104	DGB632 52		028370571163 4 / BRAZING ALLOY, SILVER,STRIP WIDTH 0.1875 TH 0.048IN LG22-24inch MATERILA AG 1		4510 / GRAM						<u>TECHNICAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u> <u>GENERAL SPECIFICATION - size: length: 600 mm width: 05 mm thickness: 01 mm spec: BS-EN 1044/1999 GRADE AG-103 composition: a. silver (ag) 55% b. Copper (cu) 21% c. zinc (zn) 22% d. tin (sn) 2%</u>	
105	SGB202 73929	NO DATA AVAILABL E	026559944020 1 / PIN COTTER DIA 0.224" - 0.249" (UNDERLOOP		2000 / DOZEN						<u>TECHNICAL SPECIFICATION - DIA 0.224" MIN & 0.249" MAX.</u> UNDERLOOP LG 1.5" NOMINAL. MATERIAL STEEL, LOW CARBON. POINT TYPE: EXTENDED PRONG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LG 1.5") MATERIAL STEEL, LOW CARBON								CHISEL. STYLE DESIGNATOR: STANDARD. SURFACE TREATMENT: PHOSPHATE COATED DEF STAN 03-11. GENERAL SPECIFICATION - DIA 0.224" MIN & 0.249" MAX. UNDERLOOP LG 1.5" NOMINAL. MATERIAL STEEL, LOW CARBON. POINT TYPE: EXTENDED PRONG CHISEL. STYLE DESIGNATOR: STANDARD. SURFACE TREATMENT: PHOSPHATE COATED DEF STAN 03-11.	
106	SGB194 11		026659001603 0 / WASHER FLAT ROUND MILD STEEL 0.625X0. 687X1.375X0. 128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	300 / KILOGR AMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIREDGENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED	
107	SGB615 74		026659001603 0 / WASHER FLAT ROUND MILD STEEL 0.625X0. 687X1.375X0. 128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS 1769	190 / KILOGR AMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIREDGENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED	
108	SGE493 56		033059571326 8 / TWINE		100 / KILOGR						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			LINEN ROPING 3 STRD NATURAL MIN BKG STRENGTH 50 LBS		AMME						SPECIFICATION - NO DATA AVAILABLE	
109	DGD31682		003250003201 1 / Knives Table Small		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) PN Crest engraved on knife Stainless Steel M/Grade SS 316 (Food Grade) GENERAL SPECIFICATION - Material S/S 304 FOOD GRADE NON Magnetic (LOCAL) PN Crest engraved on knife Stainless Steel M/Grade SS 316 (Food Grade)	
110	DGB54583	NO EACH PKT)	0251704119610 / CLIP-FLAG-FIXED-EYE W/O SWIVEL DGS 002503348/01-OF 01 (10 IN	FOR FLAG FITTING	1620 / EACH/NUMBER						TECHNICAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material GENERAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material	
111	SGB49412		021450214065 1 / BOLT AND NUT M S HEX HEAD SZ 2.000X0.187 IN		400 / EACH/NUMBER						TECHNICAL SPECIFICATION - SiZe: 2.000 X 0.187 Inches BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT GRADE: M 12 NUT THICKNESS: 12-14 MM GENERAL SPECIFICATION - SiZe: 2.000 X 0.187 Inches BOLT GRADE: M 12 HEAD DIA: 18-19 MM HEAD THICKNESS: 08-10 MM NUT GRADE: M 12 NUT THICKNESS: 12-14 MM	
112	DGE24426	805-1340571-16X36	204000821080 8 / Small Standard Duty (SSD) Foam Filled Marine Fender		3 / EACH/NUMBER						TECHNICAL SPECIFICATION - Size of fender: 16x36 inches (400x900mm) Safe Working Load: 02 tons Type/ class: 1 Energy absorption at 60% compression: 2000 ft lbs (0.28 ton-m) Reaction force at 60% compression: 10500 lbs (4.76 tons) Other characteristics :	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Thick nylon filament reinforced polyurethane skin. ζ Heat laminated 100% closed cell foam core. ζ Integral end fittings are of stainless steel. <u>GENERAL SPECIFICATION -</u> Size of fender: 16x36 inches (400x900mm) Safe Working Load: 02 tons Type/ class: 1 Energy absorption at 60% compression: 2000 ft lbs (0.28 ton-m) Reaction force at 60% compression: 10500 lbs (4.76 tons) Other characteristics : Thick nylon filament reinforced polyurethane skin. ζ Heat laminated 100% closed cell foam core. ζ Integral end fittings are of stainless steel.	
113	DGE100 25	805- 1340571- 16X36	204000821080 8 / Small Standard Duty (SSD) Foam Filled Marine Fender		4 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Size of fender: 16x36 inches (400x900mm) Safe Working Load: 02 tons Type/ class: 1 Energy absorption at 60% compression: 2000 ft lbs (0.28 ton-m) Reaction force at 60% compression: 10500 lbs (4.76 tons) Other characteristics : Thick nylon filament reinforced polyurethane skin. ζ Heat laminated 100% closed cell foam core. ζ Integral end fittings are of stainless steel. <u>GENERAL SPECIFICATION -</u> Size of fender: 16x36 inches (400x900mm) Safe Working Load: 02 tons Type/ class: 1 Energy absorption at 60% compression: 2000 ft lbs (0.28 ton-m) Reaction force at 60% compression: 10500 lbs (4.76 tons) Other characteristics : Thick nylon filament reinforced polyurethane skin. ζ Heat laminated 100% closed cell foam core. ζ Integral end fittings are of stainless steel.	
114	DGH506 77		056159521849 1 / CABLE ELECT	DEFSTAN 02- 526	100 / METER						<u>TECHNICAL SPECIFICATION -</u> DEF-STAN 02-526 ISSU-2/2008. <u>GENERAL SPECIFICATION -</u> DEF-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELASTOMERI C,LFH,3CORE COND126/.40 440V 100AMP100LG								STAN 02-526 ISSU-2/2008.	
115	DGE135 48		047659943040 1 / BRUSH WHITE WASH 2KNOT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Size : 8" b, Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market GENERAL SPECIFICATION - a. Size : 8" b, Brand: China c. Material: Handle Grip Wood, Color Brown/ White d. Commercial item available in local market	
116	DPK5602 2	XG-264	047450910051 6 / GREASE XG-264 (as per table 5A of Defstan 01-5/17)		97 / KILOGRAMME						TECHNICAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17 GENERAL SPECIFICATION - AS PER TABLE 5A OF DEFSTAN 01-5/17	
117	DPK6352 6	DEFSTAN 1-5 (XG-460)	047450910052 4 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	111 / KILOGRAMME						TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C GENERAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C	
118	DNF64244	BS EN 60317-8	0561795253580 / WIRE, WINDING COPPER ELECT COND DIA 1.320 O/DIA 1.423 MM (CLASS-180) GRADE-2	WIRE FOR WINDING	40 / KILOGRAMME						TECHNICAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2GENERAL SPECIFICATION - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
119	DGH20350		0561595218352 / CABLE ELECT BUTYL CSP SH 4 CORE COND16/.200 440V 12AMP		35 / METER						TECHNICAL SPECIFICATION - DEFSTAN-02-526 (TABLE-B10) GENERAL SPECIFICATION - DEFSTAN-02-526 (TABLE-B10)	
120	DNF63334	BS EN 60317-8 Grade 2	0561794393252 / WIRE, WINDING ELECT COPPER COND	MOTOR WINDING	20 / KILOGRAMME						TECHNICAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MMGENERAL SPECIFICATION - purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA : 1.506 MM	
121	DNJ60347	Z565003700	2990785027157 / GASKET COPPER I/D 27MM O/D 35MM THICKNESS 1MM L0063	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNM28876	4W0788/105-2508	2915012025893 / PUMP (PRIMERY FUEL PUMP/HAND PUMP)	3306,FUEL SYS, CATERPILLAR D/G USA	1 / EACH/NUMBER	3306 & 3304B					TECHNICAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PCGENERAL SPECIFICATION - (a)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NSN NO : 2915-01-202-5893 (b) SHIP : AUX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA)/ 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC	
123	SNO602 19	BCA304	311000554539 6 / BEARING BALL ANNULAR SZ 20.00X52. 00X15.00MM		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
124	SNM515 78	2654407	294001080386 1 / OIL FILTER	PERKIN D/E 606/Y6-102 OEM: ADAMJEE D/ENGG	30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
125	DNZ6036 9	R21410	281578503839 4 / JOINT RING STEEL ON CYLINDER LINER 810MMO/D758 MM ID26M=CF005	MAIN ENGINE 8RLB 66 NASR	8 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
126	DGB566 16	810- 1385705 NON MAGNETI C / 1385705	451000540171 1 / BOWL WATER CLOSET INLET SPUD 1.5 INCH	SHOWER BATH FIXTURE . 500IN	3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
127	DGB539 97	CATLOG- NO.(USA) 42-059- 008WHITE	343971506689 2 / ELECTRODE (WHITE)TUFF COTE CUTTING U/WATER DIA 5/16X18	FOR GENERAL USE	300 / PACKE T						<u>TECHNICAL SPECIFICATION - UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING. GENERAL SPECIFICATION - UTILIZED DURING UNDERWATER WELDING OPERATION. MUST BE AS PER ISO 9000 STANDARD. MUST HAVE WATER PROOF COATING.</u>	
128	SNM613 38	8N8225	312001151837 1 / BEARING SLEEVE	CATTERPILLA R D/G	5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - oem: CATTERPILLAR D/GGENERAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											oem: CATTERPILLAR D/G	
129	DNZ63518	112401	413078502676 7 / SEAL SHAFT LENGTH 82 MM DIA 70 MM AA005	AIR CONDITIONER PLANT 6C75 (2)EB NASR	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
130	DNZ60227	112401	413078502676 7 / SEAL SHAFT LENGTH 82 MM DIA 70 MM AA005	AIR CONDITIONER PLANT 6C75 (2)EB NASR	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
131	DNZ50882	112601	413078502677 4 / PLATE SUCTION VALVE 1/D 76 MM O/D 99 MM SWEDISH STEEL AA001	AIR CONDITIONER PLANT 6C75- EB NASR	28 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
132	DGP59111		361070504934 2 / DUPLICATOR ELECTRICAL GESTETNER HEAVY DUTY		1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
133	DGP62161		361070500723 7 / PAGE CORD TWIN COMPOSING		20 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - 1.</u> Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection <u>GENERAL SPECIFICATION - 1.</u> Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											PNCPP 3. Mode of inspection Joint inspection	
134	DGP49831	NO DATA AVAILAB LE	3610705088454 / PLAIN PAPER COPIER STANDARD1Z ED(PHOTO STATE MACHINE)		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
135	DNZ51758	109220A	4130785052058 / CONNECTING ROD 70X18X124.5MM	CARGO REFRIGERATI ON COMPRESSO R 4C552A-F.	12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
136	DGB40048	GAte valve dn 350	4820705051152 / GATE VALVE 14 inch (DN 350)	GENERAL USE	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES: 22MM Inner dia: 14 inch (DN 350)</u> <u>GENERAL SPECIFICATION - INNER DIA:350MM OUTER DIA: 572 MM FL: 381 MM HEIGHT: 1539MM NO OF HOLES: 12 SIZE OF HOLES: 22MM Inner dia: 14 inch (DN 350)</u>	
137	DNZ53313	AD371X10	4820785034741 / BUTTER FLY VALVEDN200P N10DIA200MM REMOTE OPERATEDWI THOUT-BF09	PIPING PART NASR	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MATERIAL OF ITEM (CAST IRON)</u> <u>GENERAL SPECIFICATION - MATERIAL OF ITEM (CAST IRON)</u>	
138	DNM55662	30HW.TRE	4820715103304 / EXPANSION VALVE	ASC-800-S, MOBILE A/C PLANT,SABRO 4380843	1 / EACH/NUMBER	30HW. TRE					<u>TECHNICAL SPECIFICATION - Maker: ALCO Brand: USA Equipment: Mobile AC Plants OEM: ALCO</u> <u>GENERAL SPECIFICATION - Maker: ALCO Brand: USA Equipment: Mobile AC Plants OEM: ALCO</u>	
139	SNM61017	8S-1965	5330715086030 / GASKET OIL PAN	CATTER PILLER DIESEL EXCHANGER	2 / EACH/NUMBER	3306b					<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR USA ENGINE S.NO 85Z13936</u> <u>GENERAL SPECIFICATION - MAKE:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				(USA)							CATERPILLAR USA ENGINE S.NO 85Z13936	
140	SNM57294	5S6735	5330007607367 / GASKET	3304PC, CATERPILLER D/GEN.USA	12 / EACH/NUMBER	3304PC, 3304					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
141	SNM61335	7M7273	5330002463312 / GASKETSTYLE O/D136X92MM WD14X21MM TH2.5MM H/D10MM I/D65X95MM	FOR CATERPILLER DIESEL GENERATOR (USA)	18 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
142	SNM45590	5P-8245	5310010980624 / Washer-Hard (13.5X25.5X3-mm thk)	3304PC, CATERPILLER D/GEN.USA	32 / EACH/NUMBER						TECHNICAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER (IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12 HARDENED: YES FINISH: PHOSPHATE AND OIL COATED GENERAL SPECIFICATION - WASHER TYPE: FLAT WASHER MATERIAL: HARDENED STEEL COATING: ZINC PHOSPHATE AND OIL MATERIAL DESCRIPTION: HARDENED STEEL FITS BOLT SIZES (IN): 1/2 INNER DIAMETER (IN): 0.531 INSIDE DIAMETER (IN): 0.53 OUTSIDE DIAMETER (IN): 1.00 OUTER DIAMETER (IN): 1.004 THICKNESS (IN): 0.12 INSIDE DIAMETER (ID) - 1 (IN): 0.53 OUTSIDE DIAMETER (OD) - 2 (IN): 1.00 THICKNESS - 3 (IN): 0.12	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HARDENED: YES FINISH: PHOSPHATE AND OIL COATED	
143	DNM43892	7S7144	5360005196605 / SPRING	3304PC, CATERPILLER D/GEN.USA	24 / EACH/NUMBER						TECHNICAL SPECIFICATION -, make: CATERPILLER D/G. USAGENERAL SPECIFICATION -, make: CATERPILLER D/G.USA	
144	DNG54784	20648	5340011673961 / ZINC ANODE	HD-1079/SLQ-32(V), HEAT EXCHANGER, LIQUID	50 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
145	DNJ60349	Z501328000	5330785027276 / JIS GASKET (3) 280 FOR TURBO CHARGER DIA 385 MM L0054	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
146	DNJ60357	Z461355511TC	5330785032646 / SEAL OIL TC 355511 RUBBER SYTH SPRINGY OD 55 1D 34MM WD 11MM	6SDB-18A DAIHATSU DIESEL GENERATOR	24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
147	DNZ60362	R27230	5330785034336 / O RING RUBBER 14.5X2.50MM	MAIN ENGINE 8RLB-66 NASR	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
148	SNM56807	0215-6432	5330725069607 / GASKET OF AIR INTEK SYSTEM M/E DUETZ	DEUTZ M/E MWM (GERMANY)	6 / EACH/NUMBER	BA-8M-816 DEUTZ MWM					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
149	DNZ60366	R21411/R27127	5330785034506 / O RING FOR CYLINDER LINER AND COVER 850X9MM RUBBER CF-113	DALIAN SULZER DIESEL ENGINE -8 RLB66	16 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
150	DNJ60356	Z461406008S	5330765012100 / SEAL OIL LO PP P/N Z461406008S I/D40 O/D60 ND8MM (A2375E 2.4"	FOR MAIN DIESEL ENGINE 6DSM-22	24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DNZ60306	501	5330785039072 / GLAND PACKING LG 240MM SQUARE	M/E F.W.COOL PUMP	2 / SET						TECHNICAL SPECIFICATION - 240 MM SQUARE GENERAL SPECIFICATION - 240 MM SQUARE	
152	DNZ60368	R23126	5360785046663 / SPRING (STEEL). 2X8X980MM-COIL-OF-NO-203	MAIN ENGINE 8RLB66DALIAN SULZER NASR	8 / EACH/NUMBER	8RLB66					TECHNICAL SPECIFICATION - SWEADEN GENERAL SPECIFICATION - SWEADEN	
153	DGE60116		5330705007252 / RUBBER BLANKET 04 PLY		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine) GENERAL SPECIFICATION - 1. Thickness of rubber blanket 1mm 2. Not flexible rubber 3. Required Size 25 x 36 inches (for Roland Offset Printing Machine)	
154	DNC57961		5940UK5069942 / TERMINAL LUG RING MOUNTING 10MM2 CSA CBL M6 FIXING	E-O-DIRECTOR EARTHING EQUIPMENT	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - Copper GENERAL SPECIFICATION - Copper	
155	DNF59082	STABAC SB-500	6110705055051 / UPS 500VA I/P180-240VAC O/P220V 50/60HZ B.U. T1.5HR WITH BATT	TEST EQUIPMENT SATVRN-32	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DNF60911	CW-770	5995715118130 / POWER CABLE 3		810 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			CORE FOR CCTV SYSTEM								AVAILABLE	
157	SNF18596	PHILLIPS	6240701003270 / LAMP FILAMENT 24V 40W SCREW TYPE SIZE 64X40 MM PHILLIPS	ELECTRICAL USE	94 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	DNG60616	275447-1	5970004327371 / TAPE INSULATIONN ELECTRICAL	CIWS	4 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DNF61332	AGFA-G335	6750PK5069051 / AGFA FIXER G335-FOR RADIO FILM	X-RAY MACHINE SMART 225	40 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DPC58482		8030000650957 / CORROSION RESISTANT		30 / QUART						TECHNICAL SPECIFICATION - MIL-DTL-81706 GENERAL SPECIFICATION - MIL-DTL-81706	
161	DGE50491		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	224 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
162	SGE49530		8135705064882 / TAPE TRANSPARENT ADHESIVE WATER PROOFED WD.12 MM LG. 66 MTR.	GENERAL USE.	180 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
163	DGE59872	NO DATA AVAILAB LE	8340505039261 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S 3 IN NO								<p>Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p>	
164	DGE530 12	NO DATA AVAILABL E	834050503926 1 / SHAMIANA SIZE 18.X 36.		23 / EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - 1.</u> Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPLETE WITH ALL ACCESSORIE S 3 IN NO								<p>Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos <u>GENERAL SPECIFICATION - 1.</u>Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 ¼ inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
165	DNG62172	8112 or A-A-1665	8415002688330 / GLOVES, MEN'S		56 / PAIR						<u>TECHNICAL SPECIFICATION</u> - cotton gloves w.r.t eligibility criteria: a. Anti-slip and breathable - Better grip comprising of dotted or plain cotton at palm side. b. Heat resistance - Quality of material should withstand temperature around 100-150 degree without any affect on texture quality. c. Excellent dexterity. d. Wear resistant. <u>GENERAL SPECIFICATION</u> - cotton gloves w.r.t eligibility criteria: a. Anti-slip and breathable - Better grip comprising of dotted or plain cotton at palm side. b. Heat resistance - Quality of material should withstand temperature around 100-150 degree without any affect on texture quality. c. Excellent dexterity. d. Wear resistant.	
166	DGE57002		7490705043905 / UNDERLAY BLANKET SIZE LG.36"WD.26" THICKNESS 1MM .ONE PLY.	ROLAND PARVA OFFSET MECHINE	1 / METER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
167	DGP56693		7510705049232 / PAPER OFFSET SIZE 36 1/2 X 33 1/2 INCHS GSM 80 ± 5%,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE		1 / REAM						<u>TECHNICAL SPECIFICATION</u> - PAPER OFFSET SIZE 36 1/2 X 33 1/2 INCHS GSM 80 ± 5%,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE <u>GENERAL SPECIFICATION</u> - PAPER OFFSET SIZE 36 1/2 X 33 1/2 INCHS GSM 80 ± 5%,VRG, COLOR WHITE (PRODUCTS PULP AND PAPER) WOOD FREE	
168	SNM51585	26581	6685715051263 / GAUGE PRESS 4-1/2 O-400 PSI-DIAL DIA 136.5 MM-0T02800 KPA	CLAYTON STEAM GENERATOR USA (6900LBS/HR)	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
169	DNF56012	MODEL NO MPK TRV1	6780765085706 / MARINE PACK FOR HANDY CAM (VIDEO CAMERA RECORDER) TRVI SONY	VIDEO CAMERA RECORDER	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
170	DPC63465	CAT ELC TM (2056612 or 2056611)	6810705084532 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
171	DNM55660	CPMU-25	4330705126468 / OIL SEPARATOR	AIR COND SYS CWM-2C70-PN	2 / EACH/NUMBER	CWM-2C70-PN					TECHNICAL SPECIFICATION - Model No: CPMU-25 Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point GENERAL SPECIFICATION - Model No: CPMU-25 Maker: M/s Cool Point Brand: Local Equipment: Mobile AC Plants OEM: M/s Cool Point	
172	DNJ59254	RV-23H-CH	6105765120929 / HOISTING MOTOR	DERVICE CRANE TYPE SHCD-0708 JAPAN	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
173	DNF47195	AS PER SPECIFICATION	6145755120718 / pro shielded 2 core micwire electro-voice	PA SYSTEM	300 / METER	3935X50					TECHNICAL SPECIFICATION - 1 Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll) GENERAL SPECIFICATION - 1 Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll)	
174	DGT58049	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		100 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u> <u>GENERAL SPECIFICATION - SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)</u>	
175	DNS47934	100003	281573515160 3 / Anti polishing ring	WARTSILA MAIN ENGINE 9L20C3 FINLAND	13 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
176	DNF54939	TS50P SAMSON	772073512071 4 / speaker stand samson (for ELX115 speakers)	PA SYSTEM	4 / EACH/N UMBER	TS50P SAMSON					<u>TECHNICAL SPECIFICATION - Professional Speaker stand, SAMSON TS50P for microphone, Ultra light weight collapsible tripod. Weight metal base for stability. Non reflecting black finish.</u> <u>GENERAL SPECIFICATION - Professional Speaker stand, SAMSON TS50P for microphone, Ultra light weight collapsible tripod. Weight metal base for stability. Non reflecting black finish.</u>	
177	DNF55955	YYS- OP60N	665078524091 3 / OPTICAL POWER METER WITH VFL		1 / EACH/N UMBER	YYS- OP60N					<u>TECHNICAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 ζ+10dBm 60NC:--50 ζ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 ζ30mW j. Flashlight Torch: YES k.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 ĳ 60C, 90%RH p. Operating TEMPERATURE : -10 ĳ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported</p> <p><u>GENERAL SPECIFICATION</u> - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 ĳ+10dBm 60NC:--50 ĳ+26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 ĳ30mW j. Flashlight Torch: YES k.</p> <p>Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 ĳ 60C, 90%RH p. Operating TEMPERATURE : -10 ĳ50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fc/sc/st interface supported</p>	
178	DNM57480	65605007	5365735281914 / series n7 segments 4th stage piston rings		1 / EACH/NUMBER	NA					<p><u>TECHNICAL SPECIFICATION</u> - PARENT EQUIPMENT SERIAL NO. 0216836 PARENT EQUIPMENT MODEL HL500-600 OEM COUNTRY NETHERLAND,HOLLAND</p> <p><u>GENERAL SPECIFICATION</u> - PARENT EQUIPMENT SERIAL NO.0216836 PARENT EQUIPMENT MODEL HL500-600 OEM COUNTRY NETHERLAND,HOLLAND</p>	
179	SRP52808	S737 (PACKING)	6810992245628 / ALCOHOL		100 / LITER	NO DATA AVAILAB					<p><u>TECHNICAL SPECIFICATION</u> - BRITISH APPROVED BS.1595, US</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		2.5 LI)	ISOPROPYLE (ISOPROPANO L) AR GRADE			LE					EQUIVALENT TT-I-735A GRADE B, FRENCH EQUIVALENT TI AIR3660/A, JOINNT SERVICE DESIGNATION AL-11 NATO CODE S-737 <u>GENERAL SPECIFICATION - BRITISH APPROVED BS.1595, US EQUIVALENT TT-I-735A GRADE B, FRENCH EQUIVALENT TI AIR3660/A, JOINNT SERVICE DESIGNATION AL-11 NATO CODE S-737</u>	
180	DNM62710	8631533	299079529319 1 / Camshaft position se		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
181	SNM61946	3801882	662071527104 7 / SENSOR		1 / EACH/NUMBER	DE165E0					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
182	DNF61656	mctx-elct-pnl	597570524610 5 / electrical panel		3 / EACH/NUMBER	MCTX-ELCT-PNL					<u>TECHNICAL SPECIFICATION - BROUCHER ATTACHED</u> <u>GENERAL SPECIFICATION - BROUCHER ATTACHED</u>	
183	DSB50673	4NMA4015B	533014434684 8 / JOINT QUAD RING 4NMA4015B		72 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
184	DNF61606	dem-310gt	593070524633 3 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		2 / EACH/NUMBER	dgs-1510-28x					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
185	SNM55153	359-0724	289571526907 9 / ROD AS CONNECTING (LENGTH B) (LENGTH B)		4 / EACH/NUMBER	DE110E2					<u>TECHNICAL SPECIFICATION - ROD AS CONNECTING (LENGTH B) (LENGTH B)</u> <u>GENERAL SPECIFICATION - ROD AS CONNECTING (LENGTH B) (LENGTH B)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
186	DGD55626	B-501	732078527065 9 / CHINESE WOK BURNER SINGLE		2 / EACH/NUMBER	B-501					TECHNICAL SPECIFICATION - DIMENSION 1200 X 1250 X 810+440 MM, VOLTAGE 220V/50 HZ, POWER 42 KW, LPG PRESSURE 2800 PA, LPG CONSUMPTION 4 KG PER HOUR, METERIAL S/S 304, AIR INTAKE DN 20, WATER INLET DN15, DRAINAGE DN40 GENERAL SPECIFICATION - DIMENSION 1200 X 1250 X 810+440 MM, VOLTAGE 220V/50 HZ, POWER 42 KW, LPG PRESSURE 2800 PA, LPG CONSUMPTION 4 KG PER HOUR, METERIAL S/S 304, AIR INTAKE DN 20, WATER INLET DN15, DRAINAGE DN40	
187	SNM58031	1918303	291001556946 9 / PRIMARY SPEED SENSOR		1 / EACH/NUMBER	DE-660EO CATERPILLAR GENERATOR C18 600 KVA /480KW					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
188	DCC51235		844070329138 5 / GLOVES FIRE RETARDANT SIZE MEDIUM		100 / PAIR						TECHNICAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE MEDIUM GENERAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE MEDIUM	the item is procured against stock sample.
189	DNF62516	JZ2-H72-4/8/16	610578528921 7 / electric motor 380v 50hz 3phase		1 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
190	DSB44192	TNM-7233607-VTX /10XCE1LE14FF1LE14FF800	472014329360 7 / HOSE ASSEMBLY NONMETALIC /TUYAUTERIE NON META		4 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - 1. Length : 32 inch 2. Dia: 10mm 3. Pressure: 10 bar Satisfactory pressure testing up to 10 bar physically varification as per sample GENERAL SPECIFICATION - 1. Length : 32 inch 2. Dia: 10mm 3. Pressure: 10 bar Satisfactory pressure testing up to 10 bar physically varification as per sample	
191	DGP578	WDBWZE	702571524884		1 /	WDBWZE					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	17	0000NBK-00 (MY CLOUD EX4100)	1 / NETWORK ATTACHED STORAGE (NAS), MY CLOUD EX4100, 04 BAY ENCLOSURE (40tb or above).		EACH/NUMBER	0000NBK-EESN					nullGENERAL SPECIFICATION - null	
192	SNM53953	346-0220	294071524013 8 / FILTER GP-ENGINE OIL		12 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - Make: USA Model: C7.1 Brand: CATERPILLARGENERAL SPECIFICATION - Make: USA Model: C7.1 Brand: CATERPILLAR	
193	DNF61879	toten 6u	593070524631 1 / networking switch rack toten 6u 600 x 600 single section 1 fixed tray, 2 fan.		1 / UNIT	TOTEN 6U					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
194	DNF59950	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
195	DRP53514	HB 50	8010ZO522548 5 / NIPPON EPOXY FINISH PAINT (packing 5 liters (04 liters base and 1 liter hardener)		100 / LITER	0					TECHNICAL SPECIFICATION - COLOUR:AS PER CARD, TEXTURE:GLOSSY, SPECIFIC GRAVITY:1.4 1.5 DEPENDING ON COLOUR, SOLID CONTENT: APPROX 100% BY VOLUME, ABRASION:EXCELLENT RESISTANCE TO ABRASION, ADHESION:EXCELLENT ON CONCRETE SURFACEGENERAL SPECIFICATION - COLOUR:AS PER CARD, TEXTURE:GLOSSY, SPECIFIC GRAVITY:1.4 1.5 DEPENDING ON COLOUR, SOLID CONTENT:APPROX 100% BY VOLUME, ABRASION:EXCELLENT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											RESISTANCE TO ABRASION, ADHESION:EXCELLENT ON CONCRETE SURFACE	
196	DNZ58921	E-02-01	2990785277677 / TWO AND THREE-STAGE CONNECTING ROD (WITH OIL THROWING NEEDLE)		2 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
197	SNM56661	7E7933	2930715270128 / REGULATOR WATER		8 / EACH/NUMBER	3512 TA					TECHNICAL SPECIFICATION - REGULATOR WATER GENERAL SPECIFICATION - REGULATOR WATER	
198	DNH57481	65605003	4220735280848 / 4TH STAGE CYLINDER		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosed GENERAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosed	
199	DCC51236		8440703291384 / GLOVES FIRE RETARDANT SIZE LARGE		200 / PAIR						TECHNICAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE LARGE GENERAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE LARGE	the item is procured against stock sample.
200	DN053266	HF150NB-PP0300-09UEC/A20112020406008 / 201-FIL 5M-ATE	4620FP1050047 / SECURITY FILTER		7 / EACH/NUMBER	A20112020406008 / 201-FIL 5M-ATE					TECHNICAL SPECIFICATION - 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO) GENERAL SPECIFICATION - 5 MICRON FILTER FOOD GRADE MESH MAKE/BRAND: MS CSTC CHINA, MS COBETTER USA, MS ASSISTECH ENTERPRISES	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											PAKISTAN OEM: MS COBETTER USA OEM: ZHEJIANG CHIMEY ENVIRONMENT SCIENCE & TECHNOLOGY CO LTD CHINA OEM: (COBETTER USA PART NO)	
201	DGD55638	COP-01	7330705270669/ CONVEYOR OVEN (HATIMI-IMPORTED)		1 / EACH/NUMBER	HEP-12					<u>TECHNICAL SPECIFICATION - VOLTS: 220-240V, DIMENSION (MM): 1100X570X360, VOLTAGE AND POWER: 220V/100W, NET WEIGHT: 65KG, POWER SOURCE (OPERATIONAL): GAS/LPG, TEMPERATURE RANGE: 0 TO 400 CELSIUS</u> <u>GENERAL SPECIFICATION - VOLTS: 220-240V, DIMENSION(MM): 1100X570X360, VOLTAGE AND POWER: 220V/100W, NET WEIGHT: 65KG, POWER SOURCE (OPERATIONAL): GAS/LPG, TEMPERATURE RANGE: 0 TO 400 CELSIUS</u>	
202	DN055833	7620.740.013.5 / FIL230912	2815FP3030393 / FUEL DUPLEX FILTER		4 / EACH/NUMBER	TBD620V12					<u>TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps</u> <u>GENERAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps</u>	
203	DN053255	7620.740.013.5 / FIL230912	2815FP3030393 / FUEL DUPLEX FILTER		12 / EACH/NUMBER	TBD620V12					<u>TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps</u> <u>GENERAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps</u>	
204	DN058541	7620.740.013.5 /	2815FP3030393 / FUEL		22 / EACH/NUMBER	TBD620V12					<u>TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		FIL230912	DUPLEX FILTER		UMBER						Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps <u>GENERAL SPECIFICATION - FUEL DUPLEX FILTER</u> Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG – 12V 22 B Technical Detail: 12V, 22Amps	
205	DNF62871	r40	594070524610 5 / access control terminal		2 / EACH/NUMBER	R40/U90					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
206	SRQ43396	CLOTH NYLON	8405ZO653003 0 / CLOTH FIRE & WATER PROOF NYLON DRY CLAD		100 / METER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - W=56"OR 60",TH=0.21MM COLOUR;BLACKISH NYLON DRY CLAD</u> <u>GENERAL SPECIFICATION - W=56"OR 60",TH=0.21MM COLOUR;BLACKISH NYLON DRY CLAD</u>	
207	SPK58342	50053 0658 kz	915070524050 6 / avia syntofluid pe-b10 (hydraulic fluid) 1 LTR PACKING		5 / LITER	HYDRAU LIC FLUID FOR THE RESCUE CAGE LEVELLIN G SYSTEM					<u>TECHNICAL SPECIFICATION - OEM FUCHS</u> <u>GENERAL SPECIFICATION - OEM FUCHS</u>	
208	DNF62754	J9776A/r8 n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
209	DNF60440	J9776A/r8 n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
210	DNF59591	a3-06-2449-1	614071528485 7 / BATTERY PACK 9 v lithium		6 / EACH/NUMBER	LIMNO2					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	