

TENDER BULLETIN

DATE & TIME 7/23/24 12:16 PM INVITATION TO TENDER TO BE OPENED ON 8/5/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DGB53948		473000257216 3 / TEE EQUAL Dia 1/4 inch		10 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62 <u>GENERAL SPECIFICATION -</u> Outer Diameter: 16 mm, Inner Diameter: 10 mm, Thickness: 3 mm, Fitting Type: Non threaded Socket type, Material With Grade: Brass /UNS C36000 / ASTM B62	
2	DRQ46932	2018AP3184	155078522031 7 / MAVIC 2 ENTERPRISE	QUAD COPTER	2 / EACH/N UMBER	L 1P	NA	DJI CHINA (AS PER DICP DIRECTIONS)	DJI		<u>TECHNICAL SPECIFICATION -</u> MAX FLIGHT TIME - 31 MINT MAX SPEED - 72 KM/HR 8 KM 1080P VIDEO 907 GRM WEIGHT SERVICE CEILLING 6000 MTR <u>GENERAL SPECIFICATION -</u> MAX FLIGHT TIME - 31 MINT MAX SPEED - 72 KM/HR 8 KM 1080P VIDEO 907 GRM WEIGHT SERVICE CEILLING 6000 MTR	
3	DNF65901	LP12-200/ 6FM-200 A/H	613078515655 2 / 12V 200AH VALVE REGULATED SEALED LEAD ACID BATTERY	DOMESTIC 6FM-200A/H (NAVY BARGE 001)	4 / EACH/N UMBER	6FM- 200A/H , SN 12200, RP 200- 12		CHANGHAISTAR CHANGHAI CHINA	CHINA		<u>TECHNICAL SPECIFICATION -</u> CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											make: homage/VISION model: 6fm200 voITAGE 12v AMP: 200ah <u>GENERAL SPECIFICATION - CHANGHA</u> STAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voITAGE 12v AMP: 200ah	
4	DNF66012	J9776A/r8n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					<u>TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u> <u>GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH</u>	
5	DNH63251	SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE	596273514247 4 / SPLIT TYPE A/C 01 TON MITSUBISHI / LG/GREE 12000 BTU (INVERTIBLE/ REVERSIBLE)	SPLIT TYPE A/C 01 TON	2 / EACH/NUMBER	12PITH		00		none inverter types required	<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
6	DNF65898	r40	594070524610 5 / access control terminal		8 / EACH/NUMBER	R40/U90					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
7	DNC65628	ELEC-0366	651079517445 9 / PLASTIC CABLE TIES	H/CRAFT	225 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK		GRIFFON HOVER WORK	<u>TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK</u> <u>GENERAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK</u>	
8	DGP65796	KD55X7000F/UHD 4K Smart TV AU7000	773070521489 2 / SMART LED TV 55"	F-22P SIMULATOR	1 / EACH/NUMBER	LE55K6600UG/KD55X7000F/UHD 4K Smart TV AU7000	NOT KNOWN	PLOT NO.C-4/A, S.I.T.E., Karachi, Pakistan. Tel: +92921)32571111-2 Fax: +92(21)32553111		SONY	<u>TECHNICAL SPECIFICATION - a. Item : Smart LED b. Company Name: Haier/SONY c. Model No : LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e. Resolution: 3840 x 2160 f. Digital TV system: DVB S2 + T2 g. Aspect Ratio : 16:9</u> <u>GENERAL SPECIFICATION - a. Item : Smart</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											LED b. Company Name: Haier/SONY c. Model No : LE55K6600UG/KD55X70000F/UHD 4K Smart TV AU7000 d. Size : 55 x inches e. Resolution: 3840 x 2160 f. Digital TV system: DVB S2 + T2 g. Aspect Ratio : 16:9	
9	SNM63013	6J-2245	5331011946105 / SEAL-O-RING	CATERPILLAR GENSET D3512B (YBB1) USA	34 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - MAKE: CATERPILLAR</u>	
10	SNM64505	067-6987	2910016114223 / KIT-ELEMENT (FUEL FILLTER)	DG CATERPELLER	10 / EACH/NUMBER	C2-2 DE18E3/DE22E2		CATTERPELLER USA CO 701 WATERFOLD WAY SIUT 200 MIANI USA CONTACT NO 305-476-6800 FAX NO 305-476-6801	CATTERPELLER USA		<u>TECHNICAL SPECIFICATION - FUEL FILLTER USE FOR PROVISION OF CLEAN FUEL TO DG FOR SMOOTH RUNNING OF ENGINE</u> <u>GENERAL SPECIFICATION - FUEL FILLTER USE FOR PROVISION OF CLEAN FUEL TO DG FOR SMOOTH RUNNING OF ENGINE</u>	
11	DNO62334	5226130/R 5226130	2910011956720 / INJECTOR ASSEMBLY FUEL	DETROIT SSDD MODEL: 16V149TI, 1000KW, 1605AMPS, 3PHASE	16 / ASSEMBLY			OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM	SUPERIOR DIESEL INC		<u>TECHNICAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM</u> <u>GENERAL SPECIFICATION - OEM: SUPERIOR DIESEL INC. 6881 BULLDOG DR NORTH CHARLESTON SC UNITED STATES 29406-4717 843-553-8331 843-553-7536 DUNS 042630020 ARTHUR@SUPERIORDIESELENGINES.COM HTTP://WWW.SUPERIORDIESELENGINES.COM</u>	
12	DNQ64385	HN-1	6230177069984 / HAND EMERGENCY LIGHT	EMERGENCY LIGHTING SYS/PORTABLE	3 / EACH/NUMBER	GSL5706 - 30Watt		MANUFACTURE NAME & ADDRESS:N-V-NEATHERLAND HAARLEM DONKERE SPAARNE-22 POST BOX 665-HAARLEM.	N-V, NEATHERLAND		<u>TECHNICAL SPECIFICATION - MAKE/BRAND: GEEPAS (R)</u> <u>GENERAL SPECIFICATION - MAKE/BRAND: GEEPAS (R)</u>	
13	DNA498	34235	533070516433	SEA WATER	2 /	3535		DEFENCE SCIENCE AND	DESTO		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	90		4 / KIT VALVE	PUMP	EACH/NUMBER			TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	ISLAMABAD		make: Rochem (Germany) DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104 <u>GENERAL SPECIFICATION</u> - make: Rochem (Germany) DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	
14	DNM64816	10021024/MCH-6 ET /HL 110 E-5 VERSION: 65220026	4310014664730 / PORTABLE ELECTRIC DRIVEN AIR CHARGING COMPRESSOR (BASCA HOLUGT SAUER)	AIR CHARGING COMPRESSOR (HOLUGT)	1 / EACH/NUMBER	mch-6		NL	M/S HOLUGT SAUER P.O BOX 6129 4000 HC TIEL NETHERLAND TEL: +31(0) 344 577 511 WWW.HOLUGT-SAUER.NL		<u>TECHNICAL SPECIFICATION</u> - OEM: M/S HOLUGT SAUER P.O BOX 6129 4000 HC TIEL NETHERLAND TEL: +31(0) 344 577 511 WWW.holugt-sauer.nl <u>GENERAL SPECIFICATION</u> - OEM: M/S HOLUGT SAUER P.O BOX 6129 4000 HC TIEL NETHERLAND TEL: +31(0) 344 577 511 WWW.holugt-sauer.nl	
15	DPK62236	SW 220	9150993496946 / Compressor Oil	0	10 / LITER	0	0	BUILDING D , CHERTSEY ROAD, SUNBURY ON THAMES	CASTROL MARINE UK		<u>TECHNICAL SPECIFICATION</u> - <u>GENERAL SPECIFICATION</u> -	
16	DNF64508	P-0143000-A /YT-100B	5660785172597 / COMPOSITE MATERIALS E-FENCE ROD S.S POLE SQUARE TUBE ANGLED TYPE , BLACK PODER COATED & HOT DIP GALVANISED WITH	PSS	70 / EACH/NUMBER	YT-100B E-Fence Controller		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		<u>TECHNICAL SPECIFICATION</u> - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ACCESSORIES.								6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICIP/8885791 DT. 05-6-24 <u>GENERAL SPECIFICATION</u> - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICIP/8885791 DT. 05-6-24	
17	SNM64531	98650.1164-97	4820995913685 / 3RD STAGE SAFETY VALVE	HPAC	1 / EACH/NUMBER	HAB25	H22867001	GARDNER DENVER LTD CLAYBROOK DRIVE REDDITCH WORCESTERSHIRE B98 DS UK TELEPHONE # 0044 (0) 1527838200 FAX # 0044 (0) 1527838438 E MAIL: highpressure@gardnerdenver.com		GARDNER DENVER LTD UK	<u>TECHNICAL SPECIFICATION - 3RD STAGE SAFETY VALVE OF HPAC</u> <u>GENERAL SPECIFICATION - 3RD STAGE SAFETY VALVE OF HPAC</u>	
18	DNF64213	P-0189000/C P4050D	5140785167177 / EQUIPMENT BOX METAL (400x500x250) MM	PSS	18 / EACH/NUMBER			M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District, Beijing, China 100120.		M/s CETC International Co., Ltd.	<u>TECHNICAL SPECIFICATION - a.</u> Portable equipment box of size (400x500x250mm) is used for housing of 12V DC Power Supply, POE switch, circuit breaker, extension board, spare cables etc b.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PORTABLE								The box may be of rust free material (Aluminum/ SS) to sustain harsh environmental conditions. c. The box must be weather proof. d. The box is to be equipped with temperature sensor (Thermistor) and aluminum foiling side box with inlet/ outlet exhaust fans along with dust filter to maintain optimum temperature. e. Equipment box should be adequately water resistant to protect electronics housed inside the box. <u>GENERAL SPECIFICATION</u> - a. Portable equipment box of size (400x500x250mm) is used for housing of 12V DC Power Supply, POE switch, circuit breaker, extension board, spare cables etc b. The box may be of rust free material (Aluminum/ SS) to sustain harsh environmental conditions. c. The box must be weather proof. d. The box is to be equipped with temperature sensor (Thermistor) and aluminum foiling side box with inlet/ outlet exhaust fans along with dust filter to maintain optimum temperature. e. Equipment box should be adequately water resistant to protect electronics housed inside the box.	
19	DNF64700	5842NL-PE6PT	660578516838 1 / 6 POWER POINTS EXTENSION BOARD	6 POWER POINTS EXTENSION BOARD	1 / EACH/NUMBER			PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76	PAK MAC		<u>TECHNICAL SPECIFICATION</u> - PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76 <u>GENERAL SPECIFICATION</u> - PAK MAC 55A ST £ 48 F-B/4 ISLAMABAD PH 2850772-76	
20	DNF63577		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	4 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		<u>TECHNICAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type <u>GENERAL SPECIFICATION</u> - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
21	SNF63852	05-00-0096-00	635071519445 9 / USB SECURITY	Luggage Scanning Machine size	1 / EACH/NUMBER	XIS-100X	ASTVC180LL740	ASTROPHYSICS INC CTR UNITED STATES TEL 9095985488 FAX	Astrophysics Manufactu		<u>TECHNICAL SPECIFICATION</u> - Security Equipment 6350016155690 <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			KEY	(40				9095985546	red		SPECIFICATION - Security Equipment 6350016155690	
22	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	ZRE01323	CATERPILLAR INC! CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-349-8400	CATERPI LAR USA		TECHNICAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08 GENERAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08	
23	DNQ65131	B1 PRENEC	5970995224526 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NIMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john- holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
24	SNJ51741	9900B-45292 /31135-94900	5360765222416 / SPRING	SUZUKI DF300AP 300 HP OBM	40 / EACH/NUMBER	SUZUKI DF300AP 300 HP OBM	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
25	DNJ65019	09482-00427	2920765222410 / SPARK PLUG (BKR6E)	SUZUKI DF300AP 300 HP OBM	6 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
26	DPK64012	ARCTIC 32/146264	9150795170256 / MOBIL EAL ARCTIC 32 (1	COMPRESSO R	10 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited	Mobil Oil Company Limited		TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32 GENERAL SPECIFICATION - MOBIL EAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LITRE PACKING)					ExxonMobil House, Ermyn Way Leatherhead, Surrey, KT22 8UX Telephone: 01372 22 2000			ARCTIC 32	
27	DNJ65268	48144-93J00	6250765221907 / HOLDER, TILT LIMIT SWITCH	SUZUKI DF300AP 300 HP OBM	4 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CO LTD JAPAN MAKE: JAPANGENERAL SPECIFICATION - OEM: SUZUKI MOTOR CO LTD JAPAN MAKE: JAPAN	
28	DNJ65269	48140-93J01	2895765221622 / CAM, TILT LIMIT SWITCH	SUZUKI DF300AP 300 HP OBM	4 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: JAPAN OEM: SUZUKI MOTOR CO LTD JAPANGENERAL SPECIFICATION - MAKE: JAPAN OEM: SUZUKI MOTOR CO LTD JAPAN	
29	DNJ65018	37100-98J21	2920765222090 / PANEL ASSY, DUAL	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - MAKE: PAK SUZUKI GENERAL SPECIFICATION - MAKE: PAK SUZUKI	
30	SNM64038	5F-9144	5331005913112 / O-RING	CATERPILLAR DG 275 KVA C-9	10 / EACH/NUMBER	C-9	CAT000C9LLX900927	CATERPILLAR INC.!DBA CATERPILLAR!DIV GOVERNMENTAL AND DEFENSE!PRODUCTS, 14009 OLD GALENA RD TC-A, UNITED STATES TELE NO 3095782353 FAX NO 3095783739 WWW.CAT.COM	ALLIED CAT		TECHNICAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9GENERAL SPECIFICATION - CATERPILLAR DG 275 KVA MODEL NO. C-9	
31	DGE60223	GMS-388A-07	4910725136314 / ESD SHOES COVER WITH CONDUCTIVE STRAP	ESD LABORATORY EQUIPMENT	6 / EACH/NUMBER	NO DATA AVAILAB LE		GR	ROHDE & SCHWARZ INTL GMBH MUHLDO RFATRBE 15-81671 MUNICH GERMANY		TECHNICAL SPECIFICATION - A. Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c. ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5j / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL GENERAL SPECIFICATION - A. Basic weight (gsm): 40 b. ESD Strip Thickness (mm): -0.08+ / -0.01 c.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											ESD Strip Width (mm): 200 + / -1 d. Surface Resistance: 10 5 ₂ / CM2 e. Shore Hardness: 70D f. Bending Strength: 40MPa POLYPROPYLENE 40GR SHOE COVER COMPLETE OF CONDUCTIVE GROUNDING STRIP ONE SIZE TO FIT ALL	
32	SNF64307	R 250	6110745169020 / VOLTAGE REGULATOR	ALTERNATOR (PNT PURJOSH)	3 / EACH/NUMBER	LSA 42.2	RLT 045 TN 030	MOTEURN LEROY - SOMER BOVLEVARD MARCELLIN LORY 16015 ANGOULEME FRANCE	FRANCE		TECHNICAL SPECIFICATION - VOLTAGE REGULATOR MOTEURN LEROY - SOMER BOVLEVARD MARCELLIN LORY 16015 ANGOULEME FRANCE GENERAL SPECIFICATION - VOLTAGE REGULATOR MOTEURN LEROY - SOMER BOVLEVARD MARCELLIN LORY 16015 ANGOULEME FRANCE	
33	SNM53851	0329091/5185891	3120014715440 / Washer-Thrust (Standard-Lower)	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		TECHNICAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08 GENERAL SPECIFICATION - BRAND: CATERPILLAR WASHER TYPE: THRUST MATERIAL: STEEL (ZINC PLATED) INSIDE DIAMETER (IN): 4 THICKNESS (IN): 0.08	
34	SNF63739	800 G3 TOWER PC	7020705215930 / HP ELITEDECK CORE I7	IT SELF	1 / EACH/NUMBER	800 G3 CORE i7	SGH717S BTV	HP HQ-TRE 71025 BOEBLINGEN GERMANY	HEWLETT PACKARD (HP)		TECHNICAL SPECIFICATION - WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM GENERAL SPECIFICATION - WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM	
35	DNF6163	800 G3	702070521593	IT SELF	1 /	800 G3	SGH717S	HP HQ-TRE 71025	HEWLETT		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
6		TOWER PC	0 / HP ELITEDECK CORE I7		EACH/NUMBER	CORE i7	BTV	BOEBLINGEN GERMANY	T PACKARD (HP)		WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM GENERAL SPECIFICATION - WINDOWS:10 PRO VERSION : 1607 OS BUILD : 14393 PROCESSOR : INTEL(R) CORE (TM)i7-7700 CPU : 3.60Ghz INSTALLED RAM : 4.00 GB SYSTEM TYPE : 64-BIT OPERATING SYSTEM	
36	DNM56754	PROPELLER MICHIGAN GOLDLINE DOR CCW	2010715220347 / PROPELLER MICHIGAN GOLDLINE DOR CCW FOR 60 MM SHAFT DIA	MARINE GEAR BOX	1 / EACH/NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMINS USA		TECHNICAL SPECIFICATION - Material: Brass/ Manganese Bronze / Nibral (alloy of nickel, bronze, and aluminum(NiBrAl)) Dia: 26 Inch Number of blades: 04 Blade Type: Left Hand (LH) DOR: Counter Clockwise Keyway: 14 MM Bore: 50mm x 38 mm x L120 (1:10) BLADE AREA: 85 % PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED GENERAL SPECIFICATION - Material: Brass/ Manganese Bronze / Nibral (alloy of nickel, bronze, and aluminum (NiBrAl)) Dia: 26 Inch Number of blades: 04 Blade Type: Left Hand (LH) DOR: Counter Clockwise Keyway: 14 MM Bore: 50mm x 38 mm x L120 (1:10) BLADE AREA: 85 % PROPELLER MICHIGAN GOLDLINE GL485 26" X 20" IN MnBr, DOR= COUNTER CLOCKWISE ROTATION. QUOTATION ALONWITH TECH SPECS ATTACHED	
37	DNH64854	NIL, LOCAL	7320705163607 / ELECTRIC ROTI PLANT	ROTI PLANT	1 / EACH/NUMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN	M/S SHARIF ENGINEER		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1000 CHAPATI /HRS					GUJRANWALA.	RING WORKS BAZAR KHARADAN GUJRAN			
38	DNF63525	6500K (E27)	6110785141900 / ENERGY SAVER DAY LIGHT 220V/20W	LIGHTING	19 / EACH/NUMBER	6500K (E27)		CH	OEM ADDRESS: GE HUNGARY ZRT, H-1340 BUDAPEST, E-MAIL : VACI UT 77.WWW.GELIGHTING.COM, COUNTRY CHINA.		<u>TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -</u>	
39	DGE39893		0413599238762 / HOSE RUBBER WITH EXT ARMOURING OF STEEL STRIP		100 / METER						<u>TECHNICAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750 INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES NOMINAL PROPRIETARY CHARACTERISTICS: NPAC</u> <u>GENERAL SPECIFICATION - DGS6971 TABLE-1 MATERIAL: RUBBER SPECIAL FEATURES: 60 FT LG INSIDE DIAMETER: 0.750 INCHES NOMINAL OUTSIDE DIAMETER: 1.125 INCHES NOMINAL PROPRIETARY CHARACTERISTICS: NPAC</u>	
40	DGB62651		0283595711465 / ROD NAVAL BRASS ROUND (DIA 4.125", WT/MTR49.90 lb/ft		2 / METER						<u>TECHNICAL SPECIFICATION - BSEN 12163/2011, GRADE: CW712R (CZ112) RUNNING LENGTH: 1.5 METER authority: as per br 320d</u> <u>GENERAL SPECIFICATION - BSEN 12163/2011, GRADE: CW712R (CZ112) RUNNING LENGTH: 1.5</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											METER authority: as per br 320d	
41	SGB58592		0214590131015 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3. 750X1.250 INCH		40 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable. <u>GENERAL SPECIFICATION</u> - Material: MS, Grade AISI 4140, BS 708M40. DIN 42CrM04 is also acceptable.	
42	DGE61230	DEFSTAN 40-3	0330595713253 / TWINE HEMP 3-STRAND, MIN BKG STRENGTH 810 LBS, DIA: 7mm		17 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - APPROX CIRC 7/8" DIA 7MM Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS <u>GENERAL SPECIFICATION</u> - APPROX CIRC 7/8" DIA 7MM Materiel: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS	
43	DGB48557	0246-4028 (BRAND-NICH) / c 21-1	0246794633854 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS, CAPACITY 01 TON	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	3 / EACH/NUMBER	HE-50A					<u>TECHNICAL SPECIFICATION</u> - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed <u>GENERAL SPECIFICATION</u> - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHI HH5010A (OR) Equivalent mtc required, table 40 a is enclosed	
44	DNQ61421	BS - EN - 3	024359129583 3 / FIRE EXTINGUISHER CO2 5.5 KGS RED	FIRE FIGHTING EQUIPMENT	141 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - SPECS: BS - EN - 3 NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150~160mm CYLINDER HIGH (mm): 800~840mm CYLINDER WEIGHT (Kg) 6~8KG EXTINGUISHER WEIGHT(kg) 11~13kg</u></p> <p><u>GENERAL SPECIFICATION - SPECS: BS - EN - 3 NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150~160mm CYLINDER HIGH (mm): 800~840mm CYLINDER WEIGHT (Kg) 6~8KG EXTINGUISHER WEIGHT(kg) 11~13kg</u></p>	
45	DGE27988		2040PK5101052 / RUBBER SHEET SIZE WEIGHT: 10-KG, LENGTH: 7-ft, WIDTH: 1-FT,	FENDER	284 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK:</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			THICKNESS: 3/8-INCH								500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321- 2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552GENERAL SPECIFICATION - MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50°±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@ LIVE.COM (2) LONGMAN QAISER BAHTTI 0321- 2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
46	SNF5180 7	MC- YL620+ Panasonic	056579415077 9 / VACUUM CLEANER 220/230V 1500W 10L W/ACCESSOR IES SPARES&STO WAGE BOX		5 / EACH/N UMBER	MC- YL620+ Panasonic					TECHNICAL SPECIFICATION - VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620GENERAL SPECIFICATION - VACUM CLEANER 220/230V 1500W 10L MODEL-PANASONIC TOUGH STYLE+ PLUS MC-Y4620	
47	DPC650 49	0474-7041	047450224264 2 / CEMENT		350 / KILOGR						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			PORTLAND (50 KG BAG)		AMME						SPECIFICATION - NO DATA AVAILABLE	
48	DNF63871	PAK / GFC/MILL AT/EQUIVALE N	056570000004 8 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)	END USE SELF	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
49	SGH37397	16-2-2B, DEFSTAN 61-12PT5	056159111671 6 / CABLE ELECT SMALL MULTICORE PVC INSULATED&S HEATED 02 CORE COND 16/0.2	16-2-2B, DEFSTAN 61-12PT5	200 / METER						TECHNICAL SPECIFICATION - DEF,STAN 61-12. PART-5/2008 CABLE IDENTIFICATION CODE:16-2-2 B. DESCRIPTION AMENDED &SPECS ADDED VIDE LETTER GSSD/GEN/309 DT 22 JULY 2016. GENERAL SPECIFICATION - DEF, STAN 61-12. PART-5/2008 CABLE IDENTIFICATION CODE:16-2-2 B. DESCRIPTION AMENDED &SPECS ADDED VIDE LETTER GSSD/GEN/309 DT 22 JULY 2016.	
50	DNA63340	HMS 0-08	281573508919 8 / FERRULE SIZE 1/2"	MACHINERY ON TYPE-21 & MCMVS	23 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
51	SNM64559	1351021	281574507729 2 / IMPELLER (WHEEL) NO: MSG/4927/689 DT 25-05-2002		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DNH61499	DV-200N	431079511346 5 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
53	DGH62638	MUREX SAFFIRE 36EC	343979509502 0 / MUREX SAFFIRE 36EC FLASH BACK ARRESTOR CYLINDER REGULATOR (ACETYLENE)	WELD/CUTT MUREX SAFEFIRE 36EC	30 / EACH/NUMBER	MUREX SAFFIRE 36EC (FUEL GAS)					TECHNICAL SPECIFICATION - STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED) GENERAL SPECIFICATION - STANDARD EN730, MAX WORKING PRESSURE 1.5 BAR (TDS ENCLOSED)	
54	DGP59111		361070504934 2 /		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DUPLICATOR ELECTRICAL GESTETNER HEAVY DUTY		UMBER						<u>SPECIFICATION - NO DATA AVAILABLE</u>	
55	DNH63750	wdf-318	4110731001200 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
56	DGP64920	G2102560 EU	3610705091304 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u> <u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</u>	
57	DGB63197	CH50-10	4030705039310 / CHAIN BLOCK 5TON CAPACITY WITH 45 FEET	FOR GENERAL PURPOSE-	2 / EACH/NUMBER	CH50-10					<u>TECHNICAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			DRIFT LINE DIA 9MM-								Acceptance CRITERIA : lifting OF 5 Tons Load1 <u>GENERAL SPECIFICATION - Make:</u> ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load1	
58	DNG63193		5120000172844 / POP RIVETING MACHINE		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
59	SGB51521	FLG02-SEW/gd1152 / 1001357	4730995253347 / FLANGE PIPE ROUND	FOR GENRAL USE	10 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Inner dia 1 ¼ inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness ½ inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn8%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches</u> <u>GENERAL SPECIFICATION - Inner dia 1 ¼ inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness ½ inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn8%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches</u>	
60	SNM64560		5330US5079674 / SEAL (STEERING RECEIVER)	ELECTRO HYDRAULIC STEERING SYSTEM (USA)	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
61	SNM61947	7L2130	5330003018371 / SEAL ASSEMBLY, SHAFT.	CATTER PILLAR D/G (USA)	21 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - LENGTH: 7.11CM HEIGHT: 9.65 CM WIDTH: 3.05 CM BRAND: CATERPILLAR</u> <u>GENERAL SPECIFICATION - LENGTH: 7.11 CM HEIGHT: 9.65 CM WIDTH: 3.05 CM BRAND: CATERPILLAR</u>	
62	DNZ60367	R27110	5330785034244 / O-RING FOR LINER OF	MAIN ENGINE 8RLB-66 DALIAN	8 / EACH/NUMBER	8RLB66					<u>TECHNICAL SPECIFICATION - SWEADEN</u> <u>GENERAL SPECIFICATION - SWEADEN</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CYLINDER COVER SIZE 114X7MM CF-117	SULZER NASR								
63	DNM63774	193736	533079504890 4 / SEAL INJECTOR	MARINE DIESEL ENGINE	122 / EACH/NUMBER	MCM-160-HM					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
64	DNM65023	050307	536512191242 7 / SPACER RING 3RD STAGE	HP AIR COMPRESSOR R-150-BAR (GERMANY)	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
65	DNF62165	158-51010	596199558030 7 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DNF65025	158-51010	596199558030 7 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
67	DNF63452	6 242 01	613099742767 0 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk GENERAL SPECIFICATION - country of origin uk	
68	DNZ63605	DH5-1	622078100498 6 / MAST LIGHT FITTING RED GLASS DH5-1 105/M	LIGHTING SYSTEM TURKEY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
69	DGB48558	CH50-10	024650000106 5 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		4 / EACH/NUMBER	CH50-10					TECHNICAL SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40' GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10. 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn). Maximum working load is 05 Ton. Height of lift is 40'</p>	
70	DGE40879	O/FLY 23X19FT, I/FLY 20X19FT	8340PK509764 1 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANZOOR SONS KARACHI PAKISTAN	2 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage GENERAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p>	
71	DPC64187	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	280 / LITER						<p><u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u></p>	
72	DNF64847	KFAE-55C	610570504423 6 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ	EXHAUST BLOWER STEERING COMPART	1 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE</u> <u>GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			3PHASE									
73	SNM56577	CV20747	6685993013657 / THERMOSTATE	SGA120283, PERKINS D/G 600 KVA UK	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KGGENERAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG	
74	DGD64265	NO DATA AVAILABLE	7320705012426 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/NUMBER	GSA/23/A KM					TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)	
75	DNF63426	DPSI 8-16X40	0552780000245 / BINOCULAR WITH CASE	SELF & USE	6 / EACH/NUMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	
76	SNF54647	DPSI 8-16X40	0552780000245 / BINOCULAR	SELF & USE	2 / EACH/NUMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			WITH CASE								KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)GENERAL SPECIFICATION - PART NO.8-16X40 MAKE-OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES. R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9fHYUNDAI MARINE BLDG,646 YEOKSAM. DONG KANGNAMGU SEOUL 135-080.TEL:080-777-3200 OR 3201 (TOLL FREE)	
77	DNF6228 2	TXFR-221	595070512426 5 / STEP DOWN TRANSFORMER R 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH	MARINE VERSION SPLIT A/C	1 / EACH/ NUMBER	DELTA TRFOR 400V/440 HZ 3P 5KVA 220V 50/60					TECHNICAL SPECIFICATION - 05 KVA I/P 440V,60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI.GENERAL SPECIFICATION - 05 KVA I/P 440V, 60HZ 3PH O/P 220 1PH LOCAL SOURCE. MAZHAR TRANSFORMER WINDER SHOP 165 CO OPRATIVE MAKET SADAR KARACHI.	
78	DGE443 40	NO DATA AVAILABL E	834570511936 2 / VELVET GREEN W=54" L=25 Yard Min	PRESENTATIO N VIP ITEM	60 / METER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
79	DPK5958 1	ARDROX6 345-5L	685014445180 4 / GAS TURBINE CLEANING SOLVENT PACKING 25 LITERS		20 / LITER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
80	DPK64151	ARDROX6345-5L	6850144451804 / GAS TURBINE CLEANING SOLVENT PACKING 25 LITERS		20 / LITER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
81	DNH51240	UNE-36011	9530705283936 / HIGH CARBON STEEL ROD (C35K) DIA -80 MM		15 / METER	NA					<u>TECHNICAL SPECIFICATION - Dimension Dia: 80mm Length: 2750mm Composition C=0.3200-0.3900 Cr=0.2000-0.4000 Mn=0.5000-0.8000 Ni=0.3900 P=0.025 (Max) S=0.025(Max)</u> <u>GENERAL SPECIFICATION - Dimension Dia: 80mm Length: 2750mm Composition C=0.3200-0.3900 Cr=0.2000-0.4000 Mn=0.5000-0.8000 Ni=0.3900 P=0.025 (Max) S=0.025(Max)</u>	
82	DRG58232	WHEEL CHASSIS DIA 6 INCH	2540ZO6539418 / CHASIS WHEEL MOVEABLE (DIA 6"WITH CTR BOLT)		4 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - WHEEL WITH CHASIS(HOLDING STRIPS ON BOTH SIDES) + CENTRALLY BOLTED AT BOTTOM (DIA OF BOLT .85"),WHEELOD=6", MAKE:LOCAL/IMPORTED</u> <u>GENERAL SPECIFICATION - WHEEL WITH CHASIS(HOLDING STRIPS ON BOTH SIDES) + CENTRALLY BOLTED AT BOTTOM (DIA OF BOLT .85"),WHEELOD=6", MAKE:LOCAL/IMPORTED</u>	
83	DNF63332	LD004	6230785289113 / CSM Life raft - Lithium cell & Canopy light		6 / NO	LD004					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
84	DNF63568	ds-1ln6-uu	5995131182007 / hikvision utp cable		50 / METER	ds-1ln6-uu					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
85	DPK64152	Polysulphide GG	8030705287063 / SIKA Polysulphide GG sealant (2.5 LITERS COMP. A / 4.0 LITERS COMP.B)		100 / LITER	POLYSULPHIDE GG					<u>TECHNICAL SPECIFICATION - DENSITY -1.58 KG,/L SOLID CONTENT 100%</u> <u>GENERAL SPECIFICATION - DENSITY -1.58 KG,/L SOLID CONTENT 100%</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
86	DNF63610	ha-10si	599970524608 8 / ir beam		4 / EACH/NUMBER	HA-10SI					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
87	SNM53838	367-5799	471071526910 1 / TUBE		4 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - TUBE GENERAL SPECIFICATION - TUBE	
88	SNM61946	3801882	662071527104 7 / SENSOR		1 / EACH/NUMBER	DE165E0					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
89	DSB62174	YED0526/01 - A4E02596	6110FT102866 8 / Power Bridge		3 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - N/A GENERAL SPECIFICATION - N/A	
90	DNM65232	A057P715/AG059F437	599871526781 0 / REGULATOR, VOLTAGE		1 / EACH/NUMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
91	DNO64817	69577	431077523458 3 / Maintenance Set Kit M (After 3000 Running Hours) Consist Of:		1 / EACH/NUMBER	SC 22					TECHNICAL SPECIFICATION - Maintenance kit include: O-ring for oil plug, Drive belt, Safety valve, oil thermovalve insert (70 oC), Minimum pressure valve ,Solenoid vv, Pressure senso GENERAL SPECIFICATION - Maintenance kit include: O-ring for oil plug, Drive belt, Safety valve, oil thermovalve insert (70 oC), Minimum pressure valve , Solenoid vv, Pressure senso	
92	DGB66150	SH1IN-SEW	472070529233 0 / flexible/Spring hose 1" dia		14 / METER	PVCSRH019					TECHNICAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT SYNTHETIC RUBBER COMPOUND. B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 36 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL PILES OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS. GENERAL SPECIFICATION - A. MATERIAL: FLEXIBLE HOSE PIPE (SEA100 R12-16) INNER TUBE IS MADE OF OIL RESISTANT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SYNTHETIC RUBBER COMPOUND. B. INNER DIAMETER: 25 MM (1 INCH) OR SAE SIZE -16 C. OUTER DIAMETER: 36 MM (1.4 INCH) D. TEMPERATURE RATING: 40 TO 120°C E. PRESSURE RATING: 3500 PSI F. WEIGHT: 2 KG/M G. REINFORCEMENT: SPIRAL PILES OF STEEL WIRE WRAPPED IN ALTERNATING DIRECTIONS.	
93	DNQ63358	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		3 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMETEX LG 100 FT ID 2"					TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa GENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
94	DGB66149	SH2IN-SEW	472070529232 8 / spring hose 2" dia		33 / METER	PVCSRH-0050					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
95	DSB63519	182659/mcb 3.5	203014363577 0 / SERVOVALVE MCB3-5		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Electro-Hydraulic valve block along with servo motor synchronized with steering station. GENERAL SPECIFICATION - Electro-Hydraulic valve block along with servo motor synchronized with steering station.	
96	DPK63551	TELLUS S2 MX 46	259071514851 3 / HYDRAULIC OIL (SHELL TELLUS S2 MX 46)		200 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - SHELL TELLUS S2 MX 46 ISO FLUID TYPE = HM GENERAL SPECIFICATION - SHELL TELLUS S2 MX 46 ISO FLUID TYPE = HM	
97	DNO64853	GSP5563	681073523379 4 / Antiscaling 5 Ltr		5 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - Antiscaling 5 Ltr GENERAL SPECIFICATION - Antiscaling 5 Ltr	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
98	DNF64297	ub500 / SA300	6350785246359 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA model no: ub500		1 / EACH/NUMBER	ub500					TECHNICAL SPECIFICATION - ITEM PROCURE P/NO. SA300 VIDE CONT.2220159/R-2301/310590 DT22-6-24 OEM, SECURINA DETECTION SYSTEM CO LTD. SHENZHEN CHINA.GENERAL SPECIFICATION - ITEM PROCURE P/NO. SA300 VIDE CONT. 2220159/R-2301/310590 DT22-6-24 OEM, SECURINA DETECTION SYSTEM CO LTD. SHENZHEN CHINA.	
99	DNF64109	3654718	5963715300692 / MODULE ELECTRONIC CONTROL		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - OEM, M/S CUMMINS USA. LOCAL SOURCE, M/S ORIENT ENERGY SYSTEMS (PRIVATE) LTD. PLOT # 16SECTOR 24,KORANGI INDUSTRIAL AREAD KARACHI. (021) 33507209GENERAL SPECIFICATION - OEM, M/S CUMMINS USA. LOCAL SOURCE, M/S ORIENT ENERGY SYSTEMS (PRIVATE) LTD. PLOT # 16SECTOR 24,KORANGI INDUSTRIAL AREAD KARACHI. (021) 33507209	
100	DNF64720	AA2500mah	6140715281910 / battery pack rechargeable NIMH (pack of 4) DURACELL AA 2500MAH		100 / PACKET	AA2500MAH					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
101	DNF63333	LD015	6160785289107 / CSM Life raft - Lithium cell & Canopy light		6 / NO	LD015					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
102	SNM64037	10000-93306	5330715289161 / LOWER ENGINE GASKET		1 / EACH/NUMBER	P/E 1106A-70TAG					TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	