

TENDER BULLETIN

DATE & TIME 7/23/24 12:15 PM INVITATION TO TENDER TO BE OPENED ON 8/6/24 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPK61264	FCW NMMA CERTIFIED	9150765179546 / YAMALUBE/A DDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing)	350HP YAMAHA	350 / LITER	JAPAN		JAPAN	SHELL		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
2	DNM64218	5284228	2815715193133 / NOZZLE PISTON COOLING	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	6 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		<u>TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u> <u>GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA</u>	
3	DNM63811	3081489	5330014905726 / SEAL OIL	CUMMINS DG 750KVA	6 / EACH/NUMBER	PBD 825 (C)A	111142533	CHONGQING CUMMINS ENGINE COMPANY LTD	CUMMINS CHINA		<u>TECHNICAL SPECIFICATION - REQUIRED FOR MAINTENANCE OF DIESEL GENERATOR</u> <u>GENERAL SPECIFICATION - REQUIRED FOR MAINTENANCE OF DIESEL GENERATOR</u>	
4	DSB61331	DSE 10.4 /6 PB 4, DSE 4.2/4 PB10	6635725169655 / PROBE FOR ULTRASONIC THICKNESS GUAGE		12 / EACH/NUMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No. 7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56</u> <u>GENERAL SPECIFICATION - German/ KARL DEUTSCH/ Wall Thickness Gauge ECHOMETER 1076 TC Basic Data TC. Doc No.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											7413.076. Part Code Cable Plug Order No. Housing No. DSE 4.2/4 PB10 1 m Lemo 00 1465.671 56	
5	DNF65977	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	1 / EACH/NUMBER	BLAZER VISTA 1000/Auro ra					<u>TECHNICAL SPECIFICATION</u> - backup time: 10 minutes Product Name: AURORA Input: 220V <u>ACGENERAL SPECIFICATION</u> - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
6	DNS65322	544060 01	3040171027102 / FRICTION ELEMENT	ALPHA LEVEL	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
7	DGP65772	NO DATA AVAILAB LE	0050500000097 / PAPER DUPLICATING		360 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
8	DGP65776	NO DATA AVAILAB LE	0050500000097 / PAPER DUPLICATING		400 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
9	DGP65900	NO DATA AVAILAB LE	0050500000117 / PAPER PRINTING WHITE		200 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - SPECIFICATION: 500 SHEETS IN EACH REAM. SPECS ADDED VIDE LETTER GSD/STY/GEN/1/122 DT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			56GSM +5% SIZEA2 420MMX594MM.								05 OCT 10. <u>GENERAL SPECIFICATION - SPECIFICATION:</u> 500 SHEETS IN EACH REAM. SPECS ADDED VIDE LETTER GSD/STY/GEN/1/122 DT 05 OCT 10.	
10	DGP65777	NO DATA AVAILAB LE	0050500000223 / PAPER DUPLICATING		400 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u> <u>GENERAL SPECIFICATION - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u>	
11	DNS65326	73632	5331171027165 / O RING (SEE COMD F8)	ALPHA LEVEL	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
12	DPC65931	BS 627 (F-8) (R 5123)	8010705128764 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOU	25 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
13	DNF65474	T27018050	7920998348397 / SPONGE (SPARE FLAT SPONGE SET) PACK OF 3		1 / PACKE T	T27018050					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
14	DSB62635	RL830-C602/604	5998735281963 / motherboard bcu		1 / EACH/N UMBER	rl830-c602/c604					<u>TECHNICAL SPECIFICATION - processor: 2 lga 2011 sockets chipset: intel C602/C6024 express chipset memory:16 ddr3 dimm upto 512gb expansion: 4pcie x 16/2 pcie x8 display outputs: 1 vga lan: 4 lan com: 2com usb: 8usb 2.0</u> <u>GENERAL SPECIFICATION - processor: 2 lga 2011 sockets chipset: intel C602/C6024 express chipset memory:16 ddr3 dimm upto 512gb expansion: 4pcie x 16/2 pcie x8 display outputs: 1 vga lan: 4 lan com: 2com usb: 8usb 2.0</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
15	DRG61932	CHOCKS	1730ZO653251 1 / CHOCKS AND LASHING		10 / SET	DRALLIM MC1 WEBBIN G TIE DOWN					TECHNICAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED GENERAL SPECIFICATION - DESIGN LOAD: 3000LB, ULTIMATE LOAD: 4000LB, WEIGHT WITH 6 MTR WEBBING: 3LB, DETAIL SPECIFICATION ENCLOSED	
16	DGE47871	k817-r / MADE BY LOCAL	534070527873 4 / rubber wheel (under carriage)		20 / EACH/NUMBER						TECHNICAL SPECIFICATION - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL) GENERAL SPECIFICATION - A) 6" RED PP WHEEL NYLON MATERIAL WITH REUOLING BRACKET COMPLETE (MADE BY LOCAL) B) 6" RED PP WHEEL NYLON MATERIAL WHEEL ONLY (MADE BY LOCAL)	
17	DNF66014	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		6 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
18	DNF60951	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		5 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
19	DNF65914	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8	599870527756 7 / SVAS SECURE 4G DATA WINGLES/jazz		3 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		WIN10/MAC/LINUX	(DEVICE)									
20	DNF65952	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
21	DNF61083	WINXP (SP3 ONWARD S) /VIST/WIN7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		8 / EACH/NUMBER	NA					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
22	DNF66143	gxt mt + cx 3 kva	5999705246330 / vertiv ups 3kva/2400w		1 / EACH/NUMBER	GXT MT + CX 3 KVA					<u>TECHNICAL SPECIFICATION - i.</u> Input voltage : 220V ii. Frequency : 50Hz iii. Phase : Single Phase iv. Rating: 3000VA (2700V) v. Output Voltage : 230 Volt vi. Frequency: 50Hz vii. Phase : Single Phase. viii. Operating temp: 0-40°C ix. Battery (external battery bank): 6x 12v 200ah maintenance free BACKUP TIME 30-45 MINUTES <u>GENERAL SPECIFICATION - i.</u> Input voltage : 220V ii. Frequency : 50Hz iii. Phase : Single Phase iv. Rating: 3000VA (2700V) v. Output Voltage : 230 Volt vi. Frequency: 50Hz vii. Phase : Single Phase. viii. Operating temp: 0-40°C ix. Battery (external battery bank): 6x 12v 200ah maintenance free BACKUP TIME 30-45 MINUTES	
23	DNO66006	447-8230	2930715234012 / Seawaterpump Gp Aux		1 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION - Seawaterpump Gp Aux</u> <u>GENERAL SPECIFICATION - Seawaterpump Gp Aux</u>	
24	DCF66054		8345595714624 / FLAG NATIONAL CHINA 4 BD		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - FLAG NATIONAL CHINA 4 BD</u> <u>FITTED SZ 4.50X3.00FT</u> <u>GENERAL SPECIFICATION - FLAG NATIONAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FITTED SZ 4.50X3.00FT								CHINA 4 BD FITTED SZ 4.50X3.00FT	
25	DCF66022		8345595714559 / FLAG NATIONAL AUSTRALIA 4 BD FITTED SZ 6.00X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL AUSTRALIA 4 BD FITTED SZ 6.00X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL AUSTRALIA 4 BD FITTED SZ 6.00X3.00FT	
26	DNF65970	HID RP40	5810715279711 / HID ICLASS R40 SE reader		6 / EACH/NUMBER	hid					TECHNICAL SPECIFICATION - RFID card reader ; HID iClass SE reader ; R40/ U90 GENERAL SPECIFICATION - RFID card reader ; HID iClass SE reader ; R40/ U90	
27	DCF66055		8345500000786 / FLAG NATIONAL DJIBUTI 4BD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL DJIBUTI 4BD GENERAL SPECIFICATION - FLAG NATIONAL DJIBUTI 4BD	
28	DCF66052		8345505000071 / FLAG NATIONAL BRUNEI 04 BD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL BRUNEI 04 BD GENERAL SPECIFICATION - FLAG NATIONAL BRUNEI 04 BD	
29	DCF66051		8345595714569 / FLAG NATIONAL BAHRAIN 4 BD FITTED SZ 5.00X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL BAHRAIN 4 BD FITTED SZ 5.00X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL BAHRAIN 4 BD FITTED SZ 5.00X3.00FT	
30	DCD65899		8440503900856 / CAP ROUND WHITE SIZE 7"		450 / EACH/NUMBER						TECHNICAL SPECIFICATION - CAP ROUND WHITE SIZE 7" GENERAL SPECIFICATION - CAP ROUND WHITE SIZE 7"	
31	SNM47246	8T-4132	5310014138764 / NUT plain hexagon (M16X2-THD)		16 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
32	SPK58342	500530658 kz	9150705240506 / avia syntofluid pe-b10 (hydraulic fluid) 1 LTR PACKING		5 / LITER	HYDRAULIC FLUID FOR THE RESCUE CAGE LEVELLING SYSTEM					TECHNICAL SPECIFICATION - OEM FUCHS GENERAL SPECIFICATION - OEM FUCHS	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
33	DSX64237	2AF048	530575506266 2 / H H SCREW 8X40MM STEEL		352 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
34	DNO65622	Part No. 230.01 (Art. No. 424883)	534072525869 3 / Impeller		1 / EACH/N UMBER	NI 25- 200/22/20 5 U3.1D- S-W133- 24/200					<u>TECHNICAL SPECIFICATION - 25-200/02 NT</u> <u>GENERAL SPECIFICATION - 25-200/02 NT</u>	
35	DCF66053		834559571460 4 / FLAG NATIONAL CANADA 4 BD FITTED SZ 6.00X3.00FT		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - FLAG NATIONAL CANADA 4 BD FITTED SZ 6.00X3.00FT</u> <u>GENERAL SPECIFICATION - FLAG NATIONAL CANADA 4 BD FITTED SZ 6.00X3.00FT</u>	
36	DCF66023		834550000078 1 / FLAG NATIONAL AZERBIJAN 4BD		5 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - FLAG NATIONAL AZERBIJAN 4BD</u> <u>GENERAL SPECIFICATION - FLAG NATIONAL AZERBIJAN 4BD</u>	
37	DRG61633	I-6000T CC-6000 OR I- 633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		3 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
38	DNJ65320	63P- 13761-01	291576520065 6 / INJECTOR	YAMAHA OUTBOARD ENGINE 150HP	4 / EACH/N UMBER	F150BET	NIL	YAMAHA MOTOR COMPANY LIMITED, JAPAN	YAMAHA MOTOR COMPAN Y		<u>TECHNICAL SPECIFICATION - YAMAHA MOTOR COMPANY LIMITED, JAPAN</u> <u>GENERAL SPECIFICATION - YAMAHA MOTOR COMPANY LIMITED, JAPAN</u>	
39	DNJ65332	35029	531071519893 5 / O-RING (78.97X3. 53MM)	MERCURY OBM ENGINE 1150F23HD USA	1 / ASSEM BLY	150HP 4 STROKE	IB983809	MERCURY MARINE USA	MARCUR Y MARINE USA		<u>TECHNICAL SPECIFICATION - LIFE EXTENDED</u> <u>GENERAL SPECIFICATION - LIFE EXTENDED</u>	
40	DPK65773	PP 47-32 / P- 903SW220 -5TTL	4310FM045000 1 / POLYESTER OIL CARRIER COMPRESSO R (5 LTRS PACKING)	CHILL WATER UNIT	30 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA, UNITED SATE	CARRIER CORP 1419 N MARKEE T ST, SACRAM ENTO, CA,UNIT		<u>TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE</u> <u>GENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
41	DNF65975	CR-123A/123	6135765231675 / DRY LITHIUM BATTERY CELL 3 VOLT	NIGHT VISION GOGGLES	100 / EACH/NUMBER	CR-123A		MATSUSHITA ELECTRONIC INDUSTRIAL CO LTD OSAKA 5708511 JAPAN.	PANASONIC		<u>TECHNICAL SPECIFICATION - IDEAL FOR NVG ,D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin japan</u> <u>GENERAL SPECIFICATION - IDEAL FOR NVG ,D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin japan</u>	
42	DNJ65318	8M6000652	2815715193193 / FUEL INJECTOR	MERCURY OBM ENGINE 1150F23HD USA	4 / EACH/NUMBER	150 HP 4 STROKE	IB983809	MERCURY MARINE USA	MERCURY MARINE USA		<u>TECHNICAL SPECIFICATION - A</u> <u>GENERAL SPECIFICATION - A</u>	
43	DNF65969	050523500058	6625785149879 / 12 V 150 AH BATTERY	ENGINEERING MATERIAL	2 / EACH/NUMBER	NO DATA AVAILAB LE		CH	M/S ZTE PAKISTAN (PVT) LTD PLOT NO. 36 ST. NO5 SECTOR NO. I-9/3 ISLAMAB AD.		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
44	DNM65454	949841-VOLVO	5330270363930 / O-RING	VOLVO PENTA ENGINE	6 / EACH/NUMBER	NO DATA AVAILAB LE		27	M/S AB VOLVO PENTA. CITY: GOTEBO RG SWEDEN GOTEBO RG		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
45	DNS66025	MRN-102-051/ CODE257, CODE 269	4510FT1008599 / Muslim Shower	MRN Shower Wet Unit (with Wall Model Vacuum Toilet)	12 / EACH/NUMBER	MERCAN, MRN Shower Wet Unit	0	DERI ORGANIZE SANAYI BOLGESI 7. YOL F 7 PARSEL TUZLA	MERCAN GEMICILIK SAN. VE TIC. A.S.		<u>TECHNICAL SPECIFICATION - likely supplier: SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											3240447.GENERAL SPECIFICATION - likely supplier: SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-3240447.	
46	DNF57360	S.NO 58071	6625795136599 / AMPERE METER RANGE 0-500AMPS (DC) SHUNT RATIO: 45MV SIZE 96MM2 X96MM2	110VDC RECTIFIER	5 / EACH/NUMBER	44C4			GR	SIEMENS GERMAN Y	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
47	DNF66013	A046K182	6130715232093 / Battery (12V, 75 A/H)	138 KVA DG C150D5B	2 / EACH/NUMBER	C150D5B	78630284	M/S ORIENT ENERGY SYSTEM (PVT) LTD 52 WEST FIRST FLOOR WAHEED PLAZA BLUE AREA ISLAMABAD		CUMMIN S/ORIENT ENERGY SYSTEM	TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
48	DNC66144	ELEC-0366	6510795174459 / PLASTIC CABLE TIES	H/CRAFT	200 / EACH/NUMBER	H/CRAFT 8100TD		GRIFFON HOVER WORK UK		GRIFFON HOVER WORK	TECHNICAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK GENERAL SPECIFICATION - LENGTH: 24 INCHES COLOUR: BLACK	
49	DPK65912	2901 170100	9150171130055 / LUBRICATING OIL, AIR COMPRESSOR/ ROTOXTEND DUTY FLUID (PACKING 20 LTR CAN)	MEDICAL OXYGEN GENERATOR O-500 ECO	40 / LITER	GA 45+	API 526878	ATLAS COPCO AIR POWER N.V, B-2610 WILRIJK ? BELGIUM. TEL: +32-3-87021 11 FAX: +32-3-8702730 WWW.atlascopco.be		ATLAS COPCO	TECHNICAL SPECIFICATION - 1. LUB OIL FOR RATARY AIR COMPRESSOR 2. CHARACTERISTICS OF SHELL CORENA S4 R (46,68) AND SHELL CORENA S3 R (46, 68) ALSO SAME AS ABOVE MENTION OIL. GENERAL SPECIFICATION - 1. LUB OIL FOR RATARY AIR COMPRESSOR 2. CHARACTERISTICS OF SHELL CORENA S4 R (46,68) AND SHELL CORENA S3 R (46, 68) ALSO SAME AS ABOVE MENTION OIL.	
50	DNJ65329	8M0035337	5330715218851 / SEAL, PORT	OBM ENGINE 150 XL 4S USA	4 / EACH/NUMBER	150 XL 4S	1B983809	MURCERY MARINE W6250 PIONEER ROAD FOND DU LAC WISCONSIN USA		MERCURY USA	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
51	DNJ6533	8M003842	533071521885	OBM ENGINE	1 /	150 XL 4S	1B983809	MURCERY MARINE		MERCURY	TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	1	9	2 / SEAL, THROTTLE BODY	150 XL 4S USA	EACH/NUMBER			W6250 PIONEER ROAD FOND DU LAC WISCONSIN USA	Y USA		<u>GENERAL SPECIFICATION -</u>	
52	DNJ65263	8M0046588	533071521889 1 / GASKET COOLER TO SUMP	OBM ENGINE 150 XL 4S USA	1 / EACH/NUMBER	150 XL 4S	1B983809	MURCERY MARINE W6250 PIONEER ROAD FOND DU LAC WISCONSIN USA	MERCURY USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
53	DGE58384	MIL-F-44422	402001338330 9 / FAST ROPE ASSEMBLY, INSERTION AND EXTRACTION (LENGTH: 120 FT)	-	7 / ROLL	NO DATA AVAILABLE		US	ELITE TACTICAL SOURCE INC-106 ANGEL LINE DRIVE, NC 2873, SERVICE @ ELITETACTICAL SOURCE.COM		<u>TECHNICAL SPECIFICATION - 1.</u> LENGTH: 120 FT, WHITE EXTRACTION LOOPS ROPE, 2. MATERIAL: NYLON, 3. DIA: 0.562 INCH, 4. BREAKING STRENGTH: 35,000 LBS, 5. SHELF LIFE: 10 YRS, 6. COUNTRY OF ORIGIN: USA 7. OEM/COC: REQUIRED. <u>GENERAL SPECIFICATION - 1.</u> LENGTH: 120 FT, WHITE EXTRACTION LOOPS ROPE, 2. MATERIAL: NYLON, 3. DIA: 0.562 INCH, 4. BREAKING STRENGTH: 35,000 LBS, 5. SHELF LIFE: 10 YRS, 6. COUNTRY OF ORIGIN: USA 7. OEM/COC: REQUIRED.	
54	DNS65451	3838406	533173515946 8 / O-RING	VOLVO PENTA SSDG (STUS)	3 / EACH/NUMBER	D9A2A-MG		WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND	WARSILA FINLAND		<u>TECHNICAL SPECIFICATION -</u> WARSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 VAASA FINLAND <u>GENERAL SPECIFICATION -</u> WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND	
55	DNJ65258	8M0005958	533101604577 2 / O-RING	OBM ENGINE 150 XL 4S USA	1 / EACH/NUMBER	150 XL 4S	1B983809	MURCERY MARINE W6250 PIONEER ROAD FOND DU LAC WISCONSIN USA	MERCURY USA		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
56	DNJ65266	8M6000366	533071519444 8 / HEAD GASKET	MERCURY OBM ENGINE 1150F23HD USA	1 / EACH/NUMBER	1150F23HD	1B983809	W6250 POINEER ROAD PO BOX 1939 TOWN FOND DULAC POST CODE 54936-1939 USA	MURCURY		<u>TECHNICAL SPECIFICATION -</u> Head Gasket <u>GENERAL SPECIFICATION -</u> Head Gasket	
57	DNM65373	925096	533025146213 8 / O.RING	IPS 600 D-6435 D-A	4 / EACH/NUMBER			M/S VOL VOPENTA AB GOTHENBURG SWEDEN.	SWEDEN		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILITY;VPL PLOT# 6 SECTOR 24 KORANGI INDUSTRIAL AREA KARACHIGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SOURCE OF AVAILABILITY;VPL PLOT# 6 SECTOR 24 KORANGI INDUSTRIAL AREA KARACHI	
58	DNM65374	3586568	5330735156706 / SEALING	IPS 600 D-6435 D-A	4 / EACH/NUMBER	IPS 600 D-6435 D-A		M/S VOLVO PENTA AB GOTHENBURG SWEDEN.		SWEDEN	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;VPL PLOT# 6 SECTOR 24 KORANGI INDUSTRIAL AREA KARACHI. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;VPL PLOT# 6 SECTOR 24 KORANGI INDUSTRIAL AREA KARACHI.	
59	DNS65453	976039	5330145477435 / O-RING	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	10 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60		AB Volvo Penta Sweden	TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)GENERAL SPECIFICATION -MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
60	DNS66021	200 008	5305735185465 / SEALING RING	WARTSILA MAIN ENGINE 9L20C3 FINLAND	30 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 , PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
61	DGE57192	HEN003007	8010795208198 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	35 / METER	HENSHAW UK	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX,TEL"01963 33237, FAX 01963 34578, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk		HENSHAW INFLATABLES LTD	TECHNICAL SPECIFICATION - 1. FOR HIGH END PRODUCTS IN MARINE INDUSTRY OUTER LAYER: CSM HYPALONEIS EASY TO BOND. EXTERNAL COATING: CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE) INTERNAL COATING: CR (NEOPRENE) TENSILE STRENGTH: >=350 DAN/GCM TEAR RESISTANCE: >=16 DAN WEIGHT: 1300 (+/- 100G) G/M2 2. Complete item/store	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>description: Fabric 1300 GSM Military Grey Hypalon Packing Detail: Roll 3. Detailed Specification / Technical data / Testing / Acceptance Criteria: Base Fabric: Polyester (high tenacity 1100 dtex-990 deniers) External coating: CSM (Chlorosulfonated Polyethylene) over layer of CR (Neoprene) Internal Coating: CR (Neoprene) Tensile Strength: >=350 daN/gcm Tear Resistance: >=16 daN Weight: 1300 (+/- 100g) g/m2 Marine Standard, resistant to UV rays, abrasion, hydrocarbons and extreme temperatures, fire and heat resistant, air tight, flexible and easy to bond to many materials 4. MAKE: HENSHAW UK OEM Country of Origin/ Manufacture: HENSHAW Company, United Kingdom <u>GENERAL SPECIFICATION - 1. FOR HIGH END PRODUCTS IN MARINE INDUSTRY OUTER LAYER: CSM HYPALONEIS EASY TO BOND. EXTERNAL COATING: CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE) INTERNAL COATING: CR (NEOPRENE) TENSILE STRENGTH: >=350 DAN/GCM TEAR RESISTANCE: >=16 DAN WEIGHT: 1300 (+/- 100G) G/M2</u> 2. Complete item/store description: Fabric 1300 GSM Military Grey Hypalon Packing Detail: Roll 3. Detailed Specification / Technical data / Testing / Acceptance Criteria: Base Fabric: Polyester (high tenacity 1100 dtex-990 deniers) External coating: CSM (Chlorosulfonated Polyethylene) over layer of CR (Neoprene) Internal Coating: CR (Neoprene) Tensile Strength: >=350 daN/gcm Tear Resistance: >=16 daN Weight: 1300 (+/- 100g) g/m2 Marine</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Standard, resistant to UV rays, abrasion, hydrocarbons and extreme temperatures, fire and heat resistant, air tight, flexible and easy to bond to many materials 4. MAKE: HENSHAW UK OEM Country of Origin/ Manufacture: HENSHAW Company, United Kingdom	
62	DNH65893		168071520694 6 / AIR CONDITIONER (FLOOR STANDING) 2 TONS	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	2 / EACH/N UMBER	GF-24TF	AE0091M 0100MAG 961772	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA		<u>TECHNICAL SPECIFICATION -</u> Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix. <u>GENERAL SPECIFICATION -</u> Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.	
63	DNF52884	ALN-ENM	100579520400 2 / SMOKE DETECTOR HOCHIKI WITH BASE YBN-R/3	FIRE ALARM SYSTEM ALN- ENM UK	4 / EACH/N UMBER	ALN-ENM	NLI	GROSVENER ROAD, GILLINGHAM BUSINESS PARK,GILLINGHAM,KENT ME80SA UNITED KINGDOM +44(0) 1634260133 info@hochikieurope.com	HOCHIKI EUROPE (UK) LTD		<u>TECHNICAL SPECIFICATION -</u> OPERATING VOLTAGE : 17-41VDC ALARM CURRENT : 9.1 mA OPERATING TEMPERATURE : -10 C to 50 C OPERATING HUMIDITY : 95% RH-NON CONDENSING (AT 40 C) STORAGE TEMPRETURE : -30 C to +60 C STORAGE HUMIDITY : 80% RH AT 60 C <u>TECHNICAL MANUAL ENCLOSED</u> <u>GENERAL SPECIFICATION - OPERATING VOLTAGE : 17-41VDC ALARM CURRENT : 9.1 mA OPERATING TEMPERATURE : -10 C to 50 C OPERATING HUMIDITY : 95% RH- NON CONDENSING (AT 40 C) STORAGE TEMPRETURE : -30 C to +60 C STORAGE HUMIDITY : 80% RH AT 60 C TECHNICAL MANUAL ENCLOSED</u>	
64	DNF65631	P-0018	614578516497 6 / BVR1*6MM (YELLOW&GR EEN)/POWER CABLE	PSS	200 / METER	BVR1*6m m (Yellow& Green)		CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA. 100120	M/S CETC INTERNA TIONAL CO LTD		<u>TECHNICAL SPECIFICATION -</u> OEM M/S CETC INTERNATIONAL CO. LTD DIAMETER 6mm Yellow&Green 1-Core <u>GENERAL SPECIFICATION - OEM M/S CETC INTERNATIONAL CO. LTD DIAMETER 6mm Yellow&Green 1- Core</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
65	DNH65838	N/A	541070523258 3 / PORTABLE TOILET GRP 5'X5'X7'	PORTABLE TOILET	1 / EACH/NUMBER	LOCAL		ASKARI FIBER GLASS PORTABLE TOILET NAJAM 03332236122		ASKARI FIBER GLASS PORTABLE TOILET	<p><u>TECHNICAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29 Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure <u>GENERAL SPECIFICATION - Item Specification</u> :a. Roof, walls and floor structure of iron pipe (16 Gauge), b. Roof & wall insulated with thermopole 25mm, c. Outer wall of fiber sheet/GRP, gi colour coated sheet. d. 2?x2? False (Gypsum) ceiling at roof, e. 01 x Eastern commode with FAlsal or Master brand sanitary, F. 01 X MUSLIM SHOWER (Plastic Material) G. 01 X Durr Wash Basin (18" x 22") H. 01 X Mirror (1.5' X 2') I. 01 x SS Towel rod (1.5') J. PPR fitting for Water Supply K. Complete Commissioning of water inlet and drain system l. 02 x LED 14 Watt lightsinside 01 x capsule light philips saver outside of door m. 01 x Exhuast Fan 8" (GFC or Royal) N. Elelctrical Work (Pakistan Cable 3/29</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Cable for lighting and Exhaust Fan, Industrial Sockets outer side for supply line) O. Paint and Corrosion Resistant Accessories for Iron Structure	
66	DNJ65264	8M0097226	6680715195209 / TACHOMETER KIT HELM MOUNT	MERCURY OBM 1150F23HD	1 / EACH/NUMBER	150 HP FOUR STROKE	1B983809	MERCURY MARINE USA	MERCURY MARINE USA		<u>TECHNICAL SPECIFICATION - TACHOMETER KIT HELM MOUNT</u> <u>GENERAL SPECIFICATION - TACHOMETER KIT HELM MOUNT</u>	
67	DNJ65265	8M0104733	6680715195208 / TACHOMETER KIT, TRANSOM MOUNT	MERCURY OBM 1150F23HD	1 / EACH/NUMBER	150 HP FOUR STROKE	1B983809	MERCURY MARINE USA	MERCURY MARINE USA		<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
68	DPC65836	2992504	8040152010978 / ADHESIVE/STICKER LOCTITE	IVECO MAIN ENGINE FVAE2884A*B 201 HC 8100TD	8 / EACH/NUMBER		001859,001861,001923 & 001924	IVECO MOTORS IVECO SPA POWER TRAIN MKT. ADVERTISING&PROMOTION VIALE DELL" INDUSTRIA 15/17 20010 PREGNANA MILANESE MILANO(ITALY)	IVECO MOTORS MILANO (ITALY)		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
69	DNM65149	943478	4720995332967 / HOSE CLAMP (CHARGE AIR COOLER)	AIR COOLER	4 / UNIT	D6-370D-E	NA	AB VOLVO PENTA SE 405 08 GOTHENBURG SWEDEN	SWEDEN		<u>TECHNICAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u> <u>GENERAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER</u>	
70	DNF65118	NR-AL 01070759	5925755141899 / CIRCUIT BREAKER 250 AMPS 3PHASE 50-60HZ	160 KVA PERKIN DG	1 / EACH/NUMBER	nfc250-smx/smx mitsubishi electric		IT	OEM ADDRESS: PERKINS ENGINES CO LTD EASTFIELD, PETERBOROUGH PE 15NA, ENGLAND TEL: 0044(0) 1733 58 3000 FAX:		<u>TECHNICAL SPECIFICATION - Voltage: 450 AC Ampere : 250 Frequency: 50-60 HZ Height 27.8 cm (270 mm) Length: 22.8 cm (228 mm) Depth: 11.2 cm (112 mm)</u> <u>GENERAL SPECIFICATION - Voltage: 450 AC Ampere : 250 Frequency: 50-60 HZ Height 27.8 cm (270 mm) Length: 22.8 cm (228 mm) Depth: 11.2 cm (112 mm)</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									#0044 (0) 1733 582240 UK.			
71	DNF6601 1	LP12-200/ 6FM-200 A/H	613078515655 2 / 12V 200AH VALVE REGULATED SEALED LEAD ACID BATTERY	DOMESTIC 6FM-200A/H (NAVY BARGE 001)	6 / EACH/N UMBER	6FM- 200A/H , SN 12200, RP 200- 12		CHANGHAISTAR CHANGHAI CHINA	CHINA		<u>TECHNICAL SPECIFICATION -</u> CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voLTAGE 12v AMP: 200ah <u>GENERAL SPECIFICATION -</u> CHANGHAISTAR CHANGHAI CHINA a. Priority 1 Make: XINNENG () QUANXHOU Singlang electric technology Co Ltd (China) Model: SN 12200 Brand/ Equivalent: 12V 200AH Maintenance free sealed lead acid b. Priority 2 Make: Rocket (China) Model: RP 200-12 Brand/ Equivalent: 12V 200AH c. priority 3 make: homage/VISION model: 6fm200 voLTAGE 12v AMP: 200ah	
72	DNF6551 2	15 opzv 1500 (GFMJ. 1500 AH)	611750514525 5 / 2V 1500AH gfmj BATTERIES	SOLAR PANEL SYSTEM 10KVA	12 / EACH/N UMBER	15 opzv 1500 gfmj		GR	M/S CHENGY ANG ROAD QUFU 273100 PR CHINA TEL:+86 537- 4438666 , 4411936 FAX: +86 537 4411936		<u>TECHNICAL SPECIFICATION -</u> SOURCE OF AVAILABILTY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858 <u>GENERAL</u> <u>SPECIFICATION - SOURCE OF</u> AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858	
73	DNF6442 7	190- 01165-00 /GARMIN	580501500608 2 / HAND	GPS	2 / EACH/N UMBER	GARMIN 78		OEM:5TH FLOOR HARBOUR PLACE 103 SOUTH CHURCH STREET	4030 NELSON AVENU		<u>TECHNICAL SPECIFICATION -</u> Physical Size : 2.6x6.0x1.2 In	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		ETREX 30 32x	HELD GPS 1.2 X1.2X4.4 INCHES ELECTRONIC					GEORGE TOWN GRAND CAYMAN ISLAND. STMEA SAIF ZONE UAE SHARJAH DUBAI.	SEATEL INC CONORD CA USA.		Display: 2.6 In, 160x240 Pixel compass accuracy: +- 2 Degree, +- 5 Degree In Extreme Northern & Southern Latitudes Altimeter Accuracy : +- 10 Ft, Range from -2000 Ft to 30,000 Ft Operating Temp: -15 to 70 C Radio Frequency: 2.4 GHZ/ ANT+ Wireless Communication Protocol GPS Accuracy: 33 Ft 95% DGPS Accuracy: From 10 to 16 Ft 95% <u>GENERAL SPECIFICATION -</u> Physical Size : 2.6x6.0x1.2 In Display: 2.6 In, 160x240 Pixel compass accuracy: +- 2 Degree, +- 5 Degree In Extreme Northern & Southern Latitudes Altimeter Accuracy : +- 10 Ft, Range from -2000 Ft to 30,000 Ft Operating Temp: -15 to 70 C Radio Frequency: 2.4 GHZ/ ANT+ Wireless Communication Protocol GPS Accuracy: 33 Ft 95% DGPS Accuracy: From 10 to 16 Ft 95%	
74	DNH661 41	-	494073513213 3 / WASHING MACHINE WITH AUTOMATIC CAPACITY DRY WEIGHT UPTO 21/25 KG	WASHING MACHINE	1 / EACH/N UMBER	th2721ds2 b1		OC	M/S ELECTR OLUX WASCAT OR SWEDEN		<u>TECHNICAL SPECIFICATION -</u> make : lg thailand <u>GENERAL SPECIFICATION -</u> make : lg thailand	
75	DGE540 18		035059571313 0 / ROPE NYLON HAWSERLAID, 3-STRAND, CIRC: 3-1/2 INCH, NOM DIA: 28MM, (1- 1/8"), TYPE-1,	TOWING & BERTHING ROPE	620 / METER						<u>TECHNICAL SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES. <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p><u>SPECIFICATION - 1.</u> type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIREED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.</p>	
76	DGB61831	HA-680	026859001239 6 / Weighing Machine B/Roo		2 / EACH/NUMBER	HA-680/HA-622					<p><u>TECHNICAL SPECIFICATION - 1.</u> body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN</p> <p><u>GENERAL SPECIFICATION - 1.</u> body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN</p>	
77	DNQ65552	G4A1H0121CMOD	024399531692 7 / FIRE HOSE DURALINE/GO MTEX I/D2 LENGTH: 40 FEET (1+1M) /FEMALE COUPLING	FOR FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION -</u> length: 40 feet (1+1m)/female coupling</p> <p><u>GENERAL SPECIFICATION -</u> length: 40 feet (1+1m)/female coupling</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
78	DNQ63431		0245590013711 / FIRE HOSE CANVAS WITH BOYONET TYPE JOINT COUPLING 1" X20 FT		4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
79	DNF65999	BS EN 60317-8	0561705253569 / WIRE, WINDING COPPER ELECT COND DIA: 0.710MM O/ DIA : 0.790 MM (CLASS 180)		18.5 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION - DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2</u> <u>GENERAL SPECIFICATION - DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2</u>	
80	DNF65891	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	8 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u> <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u>	
81	DNF65954	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	9 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u> <u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u>	
82	DNF65315	BS EN 60317-8	0561795253609 / WIRE, WINDING COPPER ELECT COND DIA : 0.900MM O/ DIA : 1.017 MM (CLASS-175 -180c) Grade-3	MOTOR WINDING	20 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - COPPER PURITY %: 99% ACCEPTABLE TOLERANCE LIMITS: 0.05 MM LOCAL SOURCE, NASIR & HAMZA ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI] DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-3</u> <u>GENERAL SPECIFICATION - COPPER PURITY %: 99% ACCEPTABLE TOLERANCE LIMITS: 0.05 MM LOCAL SOURCE, NASIR & HAMZA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI] DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-3	
83	SNM66027	2654407	294001080386 1 / OIL FILTER	PERKIN D/E 606/Y6-102 OEM: ADAMJEE D/ENGG	2 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DNM65951	QP407PA A	431076502189 8 / COMPRESSOR 2 TON BTU 24000 ROTARY 220V 50 HZT	A/C 02 TON WINDOW TYPE	1 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
85	DNM65897	QP407PA A	431076502189 8 / COMPRESSOR 2 TON BTU 24000 ROTARY 220V 50 HZT	A/C 02 TON WINDOW TYPE	2 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
86	DNQ58138	ACG- 72019	421078508891 0 / SPRING HOLDER FOR FIRE EXTINGUISHER	FOR FIRE EXTINGUISHER ALL TYPES	265 / EACH/ NUMBER						TECHNICAL SPECIFICATION - HOLD the syphon tube of fire extinguisher GENERAL SPECIFICATION - HOLD the syphon tube of fire extinguisher	
87	DNH65979	9178 chrome	4110PK506736 6 / REFRIGERATOR OR 14CUFT	REFRIGERATOR 14CUFT (PAKISTAN)	1 / EACH/ NUMBER	9178 CHROME					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
88	DNH66111	NO DATA AVAILABLE	4110PK507382 0 / WATER COOLER STORAGE TYPE CAPACITY 30 LITERS 220V .33HP	WATER COOLER STORAGE TYPE	2 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
89	DGP66002		361070500723 7 / PAGE		20 / KILOGRAM						TECHNICAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CORD TWIN COMPOSING		AMME						(approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection <u>GENERAL SPECIFICATION</u> - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection	
90	DNH65895	NO DATA AVAILABLE	4110731001910 / WATER COOLER 40/45 LITER ELECT220 AKS 40PW/Front STEELBODY	WATER COOLER	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
91	DNM66079		3230731001865 / BLADE POWER HACKSAW HSS 18X1-1/4X1/16INX6TPI		5 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE <u>GENERAL SPECIFICATION</u> - Dimensions (LXWXT): 18 X 1-1/4 X 1/16 X 6TPI (6 Teeth per inch) MATERIAL: HSS (HIGH SPEED STEEL) USE FOR CUTTING ON HACKSAW MACHINE	
92	DNG65963		5120002933208 / DISPENSER, SEALANT		2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
93	DNF66082	158-51010	5961995580307 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
94	DNF65902	PP3 , 6F22, (6135-00-900-2139)	6135701004118 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25.75X017MM	AVO METER	29 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
95	DNF65976	NO.E91 IEC LR6	6135795058492 / BATTERY ALKALINE (ENERGIZER) (Non Rechargeable) 1.5V AA SIZE NO.E91 IEC LR6	GENERAL USE	850 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DNF65903	RM12-7.2 /30882010 FE/LP12-5.0/WPS5-12	6140795089298 / BATTERY 12VDC 5AH LEAD ACID FOR UPS	SONAR TRAINERS UPS	128 / EACH/NUMBER	MLM-320C/GES203H					TECHNICAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE.10X9.8X10CM,MODEL.RM12-7.2, GENERAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE.10X9.8X10CM,MODEL.RM12-7.2,	
97	DNF66085	HI-PE MULTI-ZONE / PD6500	6350715095514 / WALKTHROUGH GATE METAL DETECTOR C/W ACCESORIOS	SECURITY DETECTION (OEM CEIA ITALY)	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DGP65843		7530705046800 / PINK PRINTING PAPER A2-420X594 MM 60 ± 5 GSM		250 / REAM						TECHNICAL SPECIFICATION - PINK PRINTING PAPER Weight 60 ± 5 gsm Size A2-420X594 MM EACH REAM CONTAINS 500 SHEETS GENERAL SPECIFICATION - PINK PRINTING PAPER Weight 60 ± 5 gsm Size A2-420X594 MM EACH REAM CONTAINS 500 SHEETS	
99	DGE62505	NO DATA AVAILABLE	0413500000190 / TUBING PLASTIC TRANSPARENT		1610 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Size: Wall Thick: 2.5mm. Length of Tube: 50ft Spec: 5039 pg 99 s: P.P. INV 1991 GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			T(G/USE) O/D 32MM I/D 27MM TH.2.5 MM, LENGTH (MIN) 50 METER, MATERIAL: PLASTIC GRADE-1								SPECIFICATION - Size: Wall Thick: 2.5mm. Length of Tube: 50ft Spec: 5039 pg 99 s: P.P. INV 1991	
100	DNQ634 27	A-A-50063	843000262825 4 / SAFETY SHOES (BOOTS KNEE),SIZE 7 WITH HARD TOE,HEAT RESIST	FOR FIRE FIGHTING EQUIPMENT	20 / PAIR						TECHNICAL SPECIFICATION - HEIGHT: 15 INCHES MATERIAL OVERALL: RUBBER COLOUR OVERALL: BLACK Easy to pull on and off Light weight Simple long-term care GENERAL SPECIFICATION - HEIGHT: 15 INCHES MATERIAL OVERALL: RUBBER COLOUR OVERALL: BLACK Easy to pull on and off Light weight Simple long-term care	
101	DGP659 04		753070500717 1 / WHITE OFFSET PAPER SIZE 58.42CMX91.44CM		25 / REAM						TECHNICAL SPECIFICATION - GM 80 (+-) 10 gm GENERAL SPECIFICATION - GM 80 (+-) 10 gm	