

TENDER BULLETIN

DATE & TIME 7/8/24 12:23 PM INVITATION TO TENDER TO BE OPENED ON 7/22/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DPC614 31	Defstan 80-78 OF 1995	044250942119 3 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	500 / LITER						<u>TECHNICAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) <u>GENERAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
2	SPC5858 7	DGS 5961	044250442016 4 / PAINT COALTAR EPOXY COMPONENT -A (BROWN) (20 LTR DRUM)	BUXLY/BERGE R/ICI/KOSAR GRP-A VIDE NHQ LT	100 / LITER						<u>TECHNICAL SPECIFICATION -</u> dgs 5961 <u>GENERAL SPECIFICATION -</u> dgs 5961	
3	SGE565 29	NO DATA AVAILABL E	043250000000 6 / DUST RESPIRATOR		2000 / EACH/N UMBER	M 511- N95					<u>TECHNICAL SPECIFICATION -</u> packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size: Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95% <u>GENERAL SPECIFICATION -</u> packing: standard Product Name: KN95 Respirator Face Mask Aerosol Type: Non Oil Color: White Size:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Universal Exhalation valve: No Strap Attachment: Stapled Adjustable Noise: clip Yes Standard: KN95 China (GB 2626-2006) Filtering Rate: = 95%	
4	DPC57968	DGS 5961	044250442015 2 / PAINT COALTAR EPOXY COMPENENT- A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	260 / LITER						<u>TECHNICAL SPECIFICATION - DGS 5961</u> <u>GENERAL SPECIFICATION - DGS 5961</u>	
5	DPC57895	DEFSTAN 80-50/3 Shade no 106 BS 381-C OF 1996	044250910672 4 / PAINT FINISHING, ALKYD (ROYAL BLUE) FLASH POINT 32C (04 LTR Packing)	VEHICLES + COMPAK BARGE	500 / LITER						<u>TECHNICAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TINGENERAL SPECIFICATION - DEFSTAN 80- 50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN</u>	
6	SPC54850	NO DATA AVAILABL E	044250442015 1 / PAINT ZINC RICH EPOXY HARDENER (Component B)	BUXLY/BERGE R/ICI/KOSAR GRP-A VIDE NHQ LT	100 / LITER						<u>TECHNICAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WHITH IN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY:WITHIN 1 HRS (B) TACK FREE:WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ, METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXLY THINNER EP-TH- 10 (xi) % OF ZINC IN AGENT 70% <u>MINGENERAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH</u></u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY: WITHIN 1 HRS (B) TACK FREE: WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ, METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUXTLY THINNER EP-TH-10 (xi) % OF ZINC IN AGENT 70% MIN	
7	DPC61200		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						TECHNICAL SPECIFICATION - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
8	DPC59892	NO DATA AVAILABLE	044250442003 9 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	500 / LITER						TECHNICAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN <u>GENERAL SPECIFICATION</u> - Flash point 32C(Min) DEFSTAN 80-59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
9	DPK63779	FCW NMMA	915076522310 7 /	ENGINE OIL SUZUKI	310 / LITER	NA		SUZUKI THAILAND	OBM SUZUKI		TECHNICAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SUZUKI/ADDINOL MARINE 4 STROKE ENGINE OIL 10W-40						THAILAND		STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 <u>GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5</u>	
10	DGE21530	O/FLY 23X19FT, I/FLY 20X19FT	8340PK509764 1 / 400 LBS TENT/IP DOUBLE FLY MILITARY PATTERN, WITH GALVANIZED STEEL FRAME AND COMPLETE ACCESSORIES	MANZOOR SONS KARACHI PAKISTAN	2 / EACH/ NUMBER						<p><u>TECHNICAL SPECIFICATION - SPECIFICATION: OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</u></p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>avoid complicationS at later stage</p> <p><u>GENERAL SPECIFICATION - SPECIFICATION:</u> OUTER FLY : 23 X 19 FT INNER FLY : 20 X 19 FT LIST OF ACCESSORIES: 1. ROPE WITH TOGGLES : 01 IN NO 2. SCREEN WEATHER : 01 IN NO 3. TENT POLE STANDING FOR TENT : 400 LBS 4. TENT POLE RIDGE FOR TENT : 400 LBS 5. TENT SALITAH : 01 IN NO 6. BAGS MADE OF CANVAS FOR TENT BAG FOR POLES/RIDGES & PINS : 03 IN NO 7. HAMMER IRON 02 KG WITH HANDLE WOOD KAHOU/SISSO OR TEAK : 02 IN NO 8. TENT PIN IRON LG 24 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 9. TENT PIN IRON MEDIUM LG 18 INCH FOR TENT 400 LBS ALONGWITH : 06 SPARES 10. ROPE, CORD & LINE MADE OF COTTON FOR TENT : 400 LBS</p> <p>manufacturer/LIKELY SUPPLIERS : m/s M BILAL textiles M/s Paramount Tarpaulin Industries Pvt Karachi M/s H Nizam Uddin & Sons or any other firm with export permit provide at time of inspection. inspection criteria : joint inspection by cins/user. complete accessories to be incorporated to avoid complicationS at later stage</p>	
11	DPC574 60		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	600 / LITER						<p><u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION -1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
12	DPC612 84	Defstan 80-78 OF 1995	044250942119 3 / PAINT FINISHING INTERIOR WHITE FIRE RETARDANT flash point 32C (20 LTR drum)	BILGES, CABINS	500 / LITER						<u>TECHNICAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG) <u>GENERAL SPECIFICATION -</u> FLASH POINT 32 C (Min) DEFSTAN 80-78/2 OF 1995 Stage inspection prescribed NS/P/002 OF 1976 PACKING: 20 LTRS DRUM (GAUGE OF DRUM 24 TO 26 SWG)	
13	DPC603 46		044250442005 1 / PAINT FINISHING (SKY BLUE)	FINISHING INTERIOR	500 / LITER						<u>TECHNICAL SPECIFICATION - 1.</u> NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg <u>GENERAL SPECIFICATION</u> - 1. NS/P/002 OF 2013(REVISED). EXCEPT FOR PACKING 2. STAGE INSPECTIONPRESCRIBED. 3. TO BE TESTED AGAINST DEFSTAN 80-78/2 OF 1995. 4. COLOUR SHADE NO 101OF BS-381 OF 1996. packing: 04 ltr tin gauge of tin 26 to 28 swg	
14	SPC5240 3	NO DATA AVAILABL E	044250442003 9 / PAINT ENAMEL (SIGNAL RED), Flash Point 32C (04 LTR Packing)	GENERAL SERVICES USE EXTERIOR, INTERIOR	80 / LITER						<u>TECHNICAL SPECIFICATION -</u> Flash point 32C(Min) DEFSTAN 80- 59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TINGENERAL SPECIFICATION - Flash point 32C(Min) DEFSTAN 80- 59/1 OF 1976 Colour shade no 537 OF BS: 381-C OF 1996 stage inspection prescribed 04 LTR TIN	
15	DPC632 13	DEFSTAN 80-50/3	044250910672 4 / PAINT	VEHICLES + COMPAK	500 / LITER						<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 80-50/3 OF 1991 Colour	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		Shade no 106 BS 381-C OF 1996	FINISHING, ALKYD (ROYAL BLUE) FLASH POINT 32C (04 LTR Packing)	BARGE							shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TINGENERAL SPECIFICATION - DEFSTAN 80-50/3 OF 1991 Colour shade no 106 of BS 381-C OF 1996 Stage Inspection Prescribed Flash point 32C 04 LTR TIN	
16	DPC52573		0442500010598 / PAINT FINISHING HEAT RESISTING, ALUMINIUM TEMP 535C/650C (04 LTR TIN) flash point 23C	TEMP 535-650C	100 / LITER						TECHNICAL SPECIFICATION - NS/P/001 OF 2013(REVISED EXCEPT FLASH POINT) Flash point 23C Type: silicon Resin Principal component: aluminum pigment/paste 50%(min) leafing,\thinner: xylene or petroleum naphtha 1. ns/p/001 of 2013 (revised) except flash point 2. stage inspection prescribed PACKING: 04 LTRS TIN GAUGE OF TIN 26 TO 28 SWG GENERAL SPECIFICATION - NS/P/001 OF 2013(REVISED EXCEPT FLASH POINT) Flash point 23C Type: silicon Resin Principal component: aluminum pigment/paste 50%(min) leafing,\thinner: xylene or petroleum naphtha 1. ns/p/001 of 2013 (revised) except flash point 2. stage inspection prescribed PACKING: 04 LTRS TIN GAUGE OF TIN 26 TO 28 SWG	
17	DPC59376	106 OF BS381-C OF 1996	0442504420061 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	460 / LITER						TECHNICAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996. GENERAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.	
18	DPC54116	537 OF BS381-C OF 1996	0442509434483 / PAINT FINISHING ACID AND ALKALI RESISTING (SIGNAL RED 537) Flash Point: 32 degree c (min)	FINISHING	440 / LITER						TECHNICAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO 537 TO BS: 381-C Of 1996GENERAL SPECIFICATION - DEFSTAN 80-72/3 OF 2005 NS/P/010 OF 2013 (REVISED) STAGE INSPECTION PRESCRIBED COLOUR SHADE NO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Packing: Standard OEM 04 ltr tin non corrosive gauge of tin 26 to 28 swg								537 TO BS: 381-C Of 1996	
19	DNZ5649 1	3408563	668578521723 4 / PRESSURE SENSOR	Cummins QSK 38 DM Main Engine	1 / EACH/N UMBER	QSK38- DM	33170174	Cummins, Engine Co. Ltd	Cummins		<u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A</u>	
20	DNJ6327 0	57130- 87D10	311076522160 7 / BUSH, DRIVE SHAFT	SUZUKI DF300AP 300 HP OBM	4 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL</u>	
21	DNJ6299 6	09482- 00427	292076522241 0 / SPARK PLUG (BKR6E)	SUZUKI DF300AP 300 HP OBM	12 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL</u>	
22	DNJ6331 5	17400- 98J01	518076522254 8 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	4 / EACH/N UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416- 93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471- 98J01 PANEL, PUMP CASE UNDERGENERAL SPECIFICATION _WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416- 93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471- 98J01 PANEL, PUMP CASE UNDER</u>	
23	DPK6126 1	FCW NMMA	915076522310 7 / SUZUKI/ADDIN OL MARINE 4 STROKE ENGINE OIL 10W-40	ENGINE OIL SUZUKI	240 / LITER	NA		SUZUKI THAILAND	OBM SUZUKI THAILAN D		<u>TECHNICAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5	
24	DPK61853	HA5430H	915073516428 4 / SEA STAR HYDRAULIC FLUID	HYDRAULIC	100 / QUART	F350A	6AW-1004474	TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	TELEFLEX MARINE CANADA		TECHNICAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858 GENERAL SPECIFICATION - MIL SPEC H-5606 G COUNTRY: USA/ CANADA TELEFLEX MARINE CANADA 3831 NO. 6 ROAD RICHMOND, B.C CANADA V6V 1P6 FAX: 604-270-7172 WWW. seastarsteering.COM, EMAIL: info@teleflex.bc.ca ph: 604-248-3858	
25	DNZ63244	3050944	533001496433 8 / FLANGE GASKET	Cummins QSK38 DM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
26	SPC58588	DGS 5961	044250442015 2 / PAINT COALTAR EPOXY COMPENENT-A (BLACK) (20 LTR DRUM)	SHIP BOTTOM ANTI CORROSIVE.	100 / LITER						TECHNICAL SPECIFICATION - DGS 5961 GENERAL SPECIFICATION - DGS 5961	
27	DNF64574	A074A915	599879528498 7 / LCD CONTROL BOARD		1 / EACH/NUMBER	A074A905					TECHNICAL SPECIFICATION - Power Supply: 14 V 3.5 Amp AC GENERAL SPECIFICATION - Power Supply: 14 V 3.5 Amp AC	
28	DNF64575	134-88-25	599879528499 1 / LCD ASSEMBLY		1 / EACH/NUMBER	134-88-25					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
29	DNF64572	134-88-01	599879528498 9 / KEYPAD		1 / EACH/NUMBER	134-88-01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
30	DNF64573	A074A900	599879528498 8 / system control board scb1		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHM,MK 18,4FD,UK LOCAL SOURCE:M/S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070.GENERAL SPECIFICATION - OEM:M/S HARTRIDGE NETWORK RADCLIVE ROAD ,BUCKINGHAM,MK 18,4FD,UK LOCAL SOURCE:M/S COUNTRY WIDE TRADE LINKERS 9-D,1ST FLOOR,CANTT BAZAR AREA MALIR CANTT KARACHI-75070.	
31	DNF58186	K138Y/ K-133	6230JP508744 9 / TORCH WATER PROOF (FOR UNDER WATER DIVING) TOSHIBA	FOR DIVING	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DNF59577	SERVO COTROL STAC JAPAN	611070504503 7 / STABLIZER 3KVA I/P50-130V/160-240VAC50/60HZ O/P110/220V STAC	ELECTRICAL GENERAL USE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
33	DNM53314	3970911	6685015301220 / TRANSMITTER, TEMPERATURE /SENSOR WATER	MARINE ENGINE CUMMINS(UT BOAT)	4 / EACH/NUMBER	QSB5.9-225BHP		23, BRENTFORD ROAD, KINGSHEATH, BIRMINGHAM B14 4DQ, ENGLAND	M/S MECHANICAL & ELECTRICAL (UK) LTD		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
34	DNM63515	5284228	2815715193133 / NOZZLE PISTON COOLING	CUMMINS MAIN ENGINE CUMMINS MODEL QSB6.7?305MD USA	6 / EACH/NUMBER	QSB6.7-305MD		M/s Cummins Inc 500 Jackson Street Columbus IN, USA	M/s IMPEX NINE INC		TECHNICAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA GENERAL SPECIFICATION - M/s Cummins Inc 500 Jackson Street Columbus IN, USA	
35	DNM63131	4309459	2815016629279 / UPPER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
36	DNM63933	0122-0922/LF16087	2940715267678 / ELEMENT LUBE OIL FILTER (FFL PART No. LF16087)		2 / EACH/NUMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
37	DNM63135	4309460	5330016657611 / LOWER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE CM 2250					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	
38	SNM51595	3025451/3090450	2815715054030 / RING OIL PISTON		20 / EACH/NUMBER	K19-DM					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
39	DNM63133	3969562	3120015815885 / BEARING, CONNECTING ROD	DIESEL GENERATOR QSB7DM	6 / EACH/NUMBER			CUMMINS USA		CUMMINS	TECHNICAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD GENERAL SPECIFICATION - BEARING, CONNECTING ROD IS A PART OF CONNECTIONG ROD OF DIESEL GENERATOR CUMMINS QSB7DM 6 CYL. STANDARD	
40	DNM63778	168306	5305190044577 / SLOTTED SET SCREW	Cummins QSK 38 DM Main Engine	18 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd		Cummins	TECHNICAL SPECIFICATION - Dimension: Length 51mm Dia 12.5 mm GENERAL SPECIFICATION - Dimension: Length 51mm Dia 12.5 mm	
41	SNM52382	3915506	4820715098277 / VALVE INTAKE	6CT,6CTA8.9, CUMMINS D/G USA	6 / EACH/NUMBER	6CT, 6CTA8.9					TECHNICAL SPECIFICATION - BRAND: CUMMINS WEIGHT: 0.036 KG SIZE: 18X19X4 CM GENERAL SPECIFICATION - BRAND: CUMMINS WEIGHT: 0.036 KG SIZE: 18X19X4 CM	
42	DNH65551	OWR-528 / NWD200/icon-2 (ORIENT)	7310705177131 / HOT AND COLD WATER DISPENSER white colour only	WATER DISPENCER	1 / EACH/NUMBER	OWR-528/icon-2 (orient)	OWR-528	ORIENT WATER DISPENCER PAKISTAN		ORIENT	TECHNICAL SPECIFICATION - white colour only NASGAS WATER DISPENCER GENERAL SPECIFICATION - white colour only NASGAS WATER DISPENCER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
43	DGP65275	-	7025705131682 / SONY BRAVIA/TCL/ SAMSUNG/ LG (43") LED TV OR EQUIVALENT	LED TV 36	1 / EACH/NUMBER	SONY BRAVIA/TCL/ SAMSUNG/ LG		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
44	DNF65519	CR-123A/123	6135765231675 / DRY LITHIUM BATTERY CELL 3 VOLT	NIGHT VISION GOGGLES	200 / EACH/NUMBER	CR-123A		MATSUSHITA ELECTRONIC INDUSTRIAL CO LTD OSAKA 5708511 JAPAN.	PANASONIC		<u>TECHNICAL SPECIFICATION - IDEAL FOR NVG ,D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin japan</u> <u>GENERAL SPECIFICATION - IDEAL FOR NVG ,D BALL, AND TACTICAL FLASH LIHTS ITS A LIGHT WEIGHT AND DURABLE POWER SOURCE. IT POSSESE GREAT PEFOMANCE IN EXTREME TEMPERATURES. country of origin japan</u>	
45	DNM63942	256-7704	5330715219503 / SEAL- VALVE COVER	DG CAT 7.1 USA	6 / EACH/NUMBER	CAT7.1	Cat00C71 KGTY00676	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPILLAR		<u>TECHNICAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM</u> <u>GENERAL SPECIFICATION - ITEM IS USED IN CAT DG AIR SYSTEM</u>	
46	DPK61844	ATF DEXRON II,III	9150218708820 / HYDRAULIC FLUID AUTO TRANSMISSION (ATF DEXRON II,III)		175 / LITER	NO DATA AVAILAB LE			IT		<u>TECHNICAL SPECIFICATION - Name Method ATF Dexron III Density @15C, Relative ASTM D4052 0.861 Colour ASTM D1500 Red Appearance visual Clear and Bright Viscosity,Kinematic 100c ASTM D445 7.9 Pour point ASTM D97 -42.5 Viscosity, Brookfield @-40c ASTM D445 32</u> <u>GENERAL SPECIFICATION - Name Method ATF Dexron III Density @15C, Relative ASTM D4052 0.861 Colour ASTM D1500 Red Appearance visual Clear and Bright Viscosity,Kinematic 100c ASTM D445 7.9 Pour point ASTM D97 -42.5 Viscosity, Brookfield @-40c ASTM D445 32</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
47	DGP64173	HP Scanner 20G05A/L2 747A	749070521848 3 / HP SCANNER PRO 2500 F1 FLATBED	HP SERVER Pro 2500 F1	1 / EACH/NUMBER	HP Scanner 20G05A/P ro 2500 F1	NIL	MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441	HP		TECHNICAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297 GENERAL SPECIFICATION - SCANNER TYPE FLATBED, ADF SCAN RESOLUTION UP TO 600DPI COLOR ADN MONOCHROME,ADF, UPTO 1200DPI, DUTY CYCLE UP TO 1500 PAGES BIT DEPTH 24 BITS EXTERNAL 48 BIT INTERNAL LEVEL OF GRAY SCALE 256 SCAN SIZE 216 X 297	
48	DNA48897	31040	533070516433 3 / KIT SEAL (INCLUDES 97,106,112,127 ,155,156,158,159)	SEA WATER PUMP	1 / EACH/NUMBER	CAT - 3531/3535		DEFENCE SCIENCE AND TECHONOLGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMAB AD		TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
49	DNO55281	3808616-VOLVO	299027044164 6 / SENSOR	VOLVO PENTA ENGINE	1 / EACH/NUMBER	NO DATA AVAILAB LE		27	M/S AB VOLVO PENTA. CITY: GOTEBO RG SWEDEN GOTEBO RG		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
50	DGP65274	16919193710 (EXPRESS SERVICE CODE)	743578520521 9 / SVAS WEB TERMINAL (LAPTOP DELL/HP CI3)	SVAS SYSTEM NY-SVAS-08 CHINA	1 / SET	NY-SVAS-08	NA	DELL INC 1 DELL WAY. ROUND ROCK, TEXAS CHINA 78682. TEL 1-866-931-3355	CHINA		TECHNICAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15GENERAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15	
51	DNF65363	P-0143000-A /YT-100B	566078517259 7 / COMPOSITE MATERIALS E-	PSS	40 / EACH/NUMBER	YT-100B E-Fence Controller		M/s CETC International Co., Ltd. CETC Mansion, No.5 Wulutong North Street, Xicheng District,	M/s CETC Internatio nal Co., Ltd.		TECHNICAL SPECIFICATION - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FENCE ROD S.S POLE SQUARE TUBE ANGLED TYPE , BLACK PODER COATED & HOT DIP GALVANISED WITH ACCESSORIE S.					Beijing, China 100120.			Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICIP/8885791 DT. 05-6-24 <u>GENERAL SPECIFICATION</u> -_Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICIP/8885791 DT. 05-6-24	
52	SNM645 20	95001.255	530579522575 2 / SET SCREW - M8 X 20	HPAC HAB25 UK	1 / EACH/N UMBER	HAB25	H2286700 1	GARDNER DENVER LTD CLAYBROOK DRIVE REDDITCH WORCESTERSHIRE B98 DS UK TELEPHONE # 0044 (0) 1527838200 FAX # 0044 (0)	GARDNER DENVER LTD		<u>TECHNICAL SPECIFICATION</u> - SET SCREW - M8 X 20 OF <u>HPACGENERAL SPECIFICATION</u> - SET SCREW - M8 X 20 OF HPAC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
								1527838438 E MAIL: highpressure@gardnerdenv er.com				
53	SGP647 71	LQ 350 / 310	702576520513 1 / EPSON PRINTER	NS-2021 ENCRYPTER	1 / EACH/N UMBER	LQ 310	N/A	3.5 OWA 3-CHOME SUWA-SHI NAGANO - KEN 392-8502 JAPAN	SEIKO EPSON CORPOR ATION		TECHNICAL SPECIFICATION - LQ 310 ENCRYPTOR PRINTER GENERAL SPECIFICATION - LQ 310 ENCRYPTOR PRINTER	
54	DNJ5789 7	881180A0 2	280501605032 3 / RING SET, PISTON	Mercury OBM Engine	3 / EACH/N UMBER	300 HP Mercury	2B469929	Murcery Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	Murcery Marine USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
55	DGP613 71	F(MT)-14	005170515294 4 / F(MT)-14 MT DRIVERS GUIDANCE HAND BOOK	-	6333 / EACH/N UMBER	-		PNCPP	PNCPP		TECHNICAL SPECIFICATION - LENGTH: 5.5 INCH WIDTH: 4.5 INCH GSM OF PAPER: 25 ± GSM GSM OF BOOK COVER: 150 GSM COLOUR OF COVER: BLUE (As per sample) COLOUR OF PAPER: WIHTE PRINTING: BOTH SIDE PRINTING WITH BLACK INK PAGES IN BOOK: BOOK OF 128 PAGES PACKING: 500 BOOKS IN ONE BOXGENERAL SPECIFICATION - LENGTH: 5.5 INCH WIDTH: 4.5 INCH GSM OF PAPER: 25 ± GSM GSM OF BOOK COVER: 150 GSM COLOUR OF COVER: BLUE (As per sample) COLOUR OF PAPER: WIHTE PRINTING: BOTH SIDE PRINTING WITH BLACK INK PAGES IN BOOK: BOOK OF 128 PAGES PACKING: 500 BOOKS IN ONE BOX	
56	DNF6536 8	N-120 / 6- QA-120, N- 150 / n-150 12v 120 ah	613078517319 6 / 12V 120 A/H BATTERY EXIDE	D/G KABOTA 20KVA	1 / EACH/N UMBER	N-120 VOLTA		SAIL FENGFAN BATTERY CO LTD CHINA	M/S SAIL		TECHNICAL SPECIFICATION - SAIL FENGFAN BATTERY CO LTD CHINA H=200 mm W=180 mm L=490 mmGENERAL SPECIFICATION - SAIL FENGFAN BATTERY CO LTD CHINA H=200 mm W=180 mm L=490 mm	
57	DNQ626 60	IITEM INDINEGO US DEVELOP	841559516024 6 / SURCOAT BLUE	FIRE FIGHTING EQUIPMENT	6 / EACH/N UMBER			LOCALLY AVAIL ABLE/IND DEVELOP.	LOCALLY AVAIL ABLE/IND DEVELO P.		TECHNICAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP.GENERAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
58	DGP65316	50AU7000/46EH5000	773070517439 1 / SAMSUNG LED TV 46/49 INCH	LED TV	1 / EACH/NUMBER	46EH5000		SAMSUNG	SAMSUNG		<u>TECHNICAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u> <u>GENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH</u>	
59	DNF65370	AT-FS980M/9 PS-30 + AT-FS980M/9 PS-NCA1	705073522686 4 / 8 PORT 10/100TX POE + SWITCH WITH 2 GIGABIT SFO MO	UFFAQ	1 / EACH/NUMBER	FS980M		Office No. 120 Building No. 12, First Floor Dubai Internet City United Arab Emirates Ph: +971 4 454 8740	Allied Telesis		<u>TECHNICAL SPECIFICATION - 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks and one fixed AC power supply</u> <u>GENERAL SPECIFICATION - 08 X Port (08 10/100/1000 Mbps) RJ45+2x 1000 Mbps SFP Ports slots. Support IEEE 802 1P Port security & storm control Web based GUI & command line interface Power supply 100-240 VAC 50/60 Hz 8 port 10/100TX POE + switch with 2 Gigabit Sfo module combo uplinks and one fixed AC power supply</u>	
60	DNJ62759	6Y2-24360-60	471076518966 0 / PRIMER PUMP ASSY	YAMAHA SMALL BOAT ENGINE F100B JAPAN	3 / EACH/NUMBER	F100B	60CL100410G	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@seaquest.biz	YAMAHA LTD. 2500 SHINGAIWATA, SHIZUOKA, JAPAN Tel : +81 538 32 1115 Fax : +81 538 32 1634 Email/URL : info@seaquest.biz		<u>TECHNICAL SPECIFICATION - IPC</u> <u>GENERAL SPECIFICATION - IPC</u>	
61	DPC55160	387 008	494073518627 2 / GLUE COMPOUND-LOCTITE 5399	WARTSILA MAIN ENGINE 9L20C3 FINLAND	6 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION - TPI</u> <u>GENERAL SPECIFICATION - TPI</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
							RASDPA AE084243 PAAE084 244	Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380				
62	DGE585 04	096-0240- 004C	402079515298 7 / ROPE NAVY FLEX 24 MM BROWN 3 STRAND POLYPROPYL ENE (HAWSERLAID)	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS- ROPE@RANDERS-REB.DK. PARENT/SYS;/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE. GENERAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL;+4589111213 FAX; +4589111212 E-MAIL;RANDERS- ROPE@RANDERS-REB.DK. PARENT/SYS;/TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.	
63	DGE585 03	096-0320- 004C	402079515298 9 / ROPE NAVY FLEX 32 MM BROWN 3 STRAND POLYPROPYL ENE	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL; +4589111213 FAX; +4589111212 E-MAIL; RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - 1. MANUFACTURD TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR GENERAL SPECIFICATION - 1. MANUFACTURD TO STANDARD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9554:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR	
64	DGP583 50	12U	599571520694 5 / RACK (12U)	UPGRADING OF MARITIME SAFETY INFORMATION MANAGMENT	1 / EACH/NUMBER	Aunet	AU12UB	M/S Skill Orbit using ESIR GIS software orig USA	M/S Skill Orbit using ESIR GIS software orig USA		TECHNICAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix. GENERAL SPECIFICATION - Upgrading of Existing Maritime Safety Information Management System (MSI) is required for Navarea ix.	
65	DGE571 89	EP020107 4	662573517996 8 / ESD AUDIT KIT	ETR	1 / EACH/NUMBER			GLOBAL MAINT SERVICE, OFFICE 6, PAR VIEW APPT BLOCK 13A, GULSHAN-E-IQBA, KARACHI	GMS		TECHNICAL SPECIFICATION - tERA-OHM METER TERARESIST 8000 ME SURFACE RESISTANT TEST KIT OEM-ESD PROTECT GERMANY ORIGIN: GERMANY TDS ATTACHEDGENERAL SPECIFICATION - tERA-OHM METER TERARESIST 8000 ME SURFACE RESISTANT TEST KIT OEM-ESD PROTECT GERMANY ORIGIN: GERMANY TDS ATTACHED	
66	DNQ633 53	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
67	DNQ63147	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	5 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
68	DNQ63318	B1 PRENEC	597099522452 6 / TAPE INSULATING 38MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMAGE:K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley. minton@john-holden.com www www. JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
69	SNJ45658	12892-93J00-243	536576522237 1 / SHIM, TAPPET (T: 2425)	SUZUKI DF300AP 300 HP OBM	16 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
70	SNJ45659	12892-93J00-245	536576522237 2 / SHIM, TAPPET (T: 2450)	SUZUKI DF300AP 300 HP OBM	16 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
71	SNJ45660	12892-93J00-250	536576522237 4 / SHIM, TAPPET (T: 2500)	SUZUKI DF300AP 300 HP OBM	16 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u> <u>GENERAL SPECIFICATION - OEM: SUZUKI MOTOR JAPAN</u>	
72	DNJ65095	17400-98J01	518076522254 8 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u> <u>GENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u>	
73	DNJ65254	17400-98J01	518076522254 8 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u> <u>GENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											UNDERGENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER	
74	SNJ45663	12891-93J00	2895765222456 / TAPPET	SUZUKI DF300AP 300 HP OBM	12 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)GENERAL SPECIFICATION - OEM: SUZUKI MOTOR CORPORATION (JAPAN)	
75	DNJ65321	6AW-13784-00	2915765203878 / COVER, PUMP	YAMAHA OBM	4 / EACH/NUMBER	NO DATA AVAILAB LE	6CE-1029885, 6CF-1009814	YAMAHA MOTOR CO. LTD JAPAN	JAPAN		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
76	DNJ65091	15440-93J00	2940765221800 / FILTER, FUEL (EPI)	SUZUKI DF300AP 300 HP OBM	2 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
77	SNJ51739	09367-10001 / 08367-10001	4730765221951 / JOINT	SUZUKI DF300AP 300 HP OBM	20 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL	
78	DNM64093	FF9011	2940015230050 / Fuel Filter	CUMMINS 200 KVA DG	2 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797	USA		TECHNICAL SPECIFICATION - MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE: CUMMINS USA	
79	SNM51677	FF9011	2940015230050 / Fuel Filter	CUMMINS 200 KVA DG	6 / EACH/NUMBER	6CTA8.3	78515443	Cummins Americas Inc, 3350 SW 148 AVENUE, SUITE 205 Miramar, FL, 33027 USA Tell (1-954) 431-5511 Fax (1-954)433-5797	USA		TECHNICAL SPECIFICATION - MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE: CUMMINS USA	
80	DPK59328	MIL-PRF-17331	9150013687075 / LUBRICATING OIL, STEAM TURBINE OIL, RADCOLUBE 17331 (2190 TEP) (Packing	MAIN GEARBOX, CPP SYSTEM, HPACs AND LPACs	8 / DRUM	MILITARY SPECIFIC ATIONS		CARLETON LIFE SUPPORT SYSTEMS INC. 2734 HICKORY GROVE RD DAVENPORT IA USA 52804-1203 TEL: 563-383-6467 FAX: 563-383-6430 EMA: LPETERS@CARLETONLS.COM /WWW.	MILITARY SPECIFIC ATIONS		TECHNICAL SPECIFICATION - VISCOSITY 8.2cSt MIN AT 210 DEG F AND 82.0cSt MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEITGENERAL SPECIFICATION - VISCOSITY 8.2 cSt MIN AT 210 DEG F AND 82.0cSt	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			= 205 LTRS)					CARLETONLS.COM			MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEIT	
81	DPK57136	MIL-PRF-17331	9150013687075 / LUBRICATING OIL, STEAM TURBINE OIL, RADCOLUBE 17331 (2190 TEP) (Packing = 205 LTRS)	MAIN GEARBOX, CPP SYSTEM, HPACs AND LPACs	7 / DRUM	MILITARY SPECIFICATIONS		CARLETON LIFE SUPPORT SYSTEMS INC. 2734 HICKORY GROVE RD DAVENPORT IA USA 52804-1203 TEL: 563-383-6467 FAX: 563-383-6430 EMA: LPETERS@CARLETONLS.COM /WWW.CARLETONLS.COM		MILITARY SPECIFICATIONS	TECHNICAL SPECIFICATION - VISCOSITY 8.2cSt MIN AT 210 DEG F AND 82.0cSt MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEIT GENERAL SPECIFICATION - VISCOSITY 8.2 cSt MIN AT 210 DEG F AND 82.0cSt MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEIT	
82	DNF65365	APC Smart-UPS VT 40KVA	6130715207037 / APC Smart-UPS VT 40KVA	UFFFAQ	1 / EACH/NUMBER	APC Smart-UPS VT 40KVA		132 fairgrounds round west kingston, R1 02892, United States: call 401-789-5735 Web: www.apc.com		APC, UK	TECHNICAL SPECIFICATION - As Attached OEM: China/Saima Trade Tower, A910, II Chundrigar Road Saddar Karachi (021) 32213399 GENERAL SPECIFICATION - As Attached OEM: China/Saima Trade Tower, A910, II Chundrigar Road Saddar Karachi (021)32213399	
83	DNF65367	Symmetra LX-16KVA-UPS	6130715207038 / APC UPS Symmetra LX 16 KVA	UFFFAQ	1 / EACH/NUMBER	Symmetra Lx		132 fairgrounds round west kingston, R1 02892, United States: call 401-789-5735 Web: www.apc.com		APC, UK	TECHNICAL SPECIFICATION - As Attached LOCAL SOURCE, M/S DELTA TRADERS KARACHI TEL: 0307-3925152 E-MAIL deltatraders2001@gmail.com Standard Backup Time GENERAL SPECIFICATION - As Attached LOCAL SOURCE, M/S DELTA TRADERS KARACHI TEL:0307-3925152 E-MAIL deltatraders2001@gmail.com Standard Backup Time	
84	DNZ63781	205128	5310785217166 / PLAIN WASHER	Cummins QSK38 DM Main Engine	36 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd		Cummins	TECHNICAL SPECIFICATION - 1/2 in GENERAL SPECIFICATION - 1/2 in	
85	DNO55281	3808616-VOLVO	2990270441646 / SENSOR	VOLVO PENTA ENGINE	1 / EACH/NUMBER	NO DATA AVAILABLE		AB VALVO PENTA SE 40508 GOTHENBURG SWEDEN		VALVO PENTA	TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
86	DNF65356	15 opzv 1500	6117505145255 / 2V 1500AH	SOLAR PANEL SYSTEM	12 / EACH/NUMBER	15 opzv 1500 gfmj		GR		M/S CHENGY	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILTY : M/S	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		(GFMJ. 1500 AH)	gfmj BATTERIES	10KVA	UMBER				ANG ROAD QUFU 273100 PR CHINA TEL:+86 537-4438666 , 4411936 FAX: +86 537 4411936		AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858 <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858</u>	
87	DNF65311	15 opzv 1500 (GFMJ. 1500 AH)	611750514525 5 / 2V 1500AH gfmj BATTERIES	SOLAR PANEL SYSTEM 10KVA	6 / EACH/NUMBER	15 opzv 1500 gfmj		GR	M/S CHENGY ANG ROAD QUFU 273100 PR CHINA TEL:+86 537-4438666 , 4411936 FAX: +86 537 4411936		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858</u> <u>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858</u>	
88	DNF64020	DH-PFM900-E/IPC 9800ADH Plus/IPC9300S ACT	582073523164 5 / ALMIGHTY IPC TESTER FOR CCTV CAMERA VIGIL SYSTEM	CCTV VIGIL SYSTEM	1 / EACH/NUMBER	IPC9300S ACT		M/S OPENPINOY PHILPINE TELL NO. (02) 8722-0909.FAX NO. (02) 8570-0909. CCTV@OPENPINOY.COM	M/S OPENPINOY PHILPINE		<u>TECHNICAL SPECIFICATION - BROUCHER ATTACH</u> <u>GENERAL SPECIFICATION - BROUCHER ATTACH</u>	
89	DNH64912	HRE-ARP-1217-1	732070521036 7 / FULL AUTOMATED ROTI PLANT COMPLETE BODY	COMPLETE HRE-APR-1217 PAKISTAN	1 / EACH/NUMBER	HRE-APR-1217/A1500/A3000	NA	SMALL INDUSTRIAL ESTATE 3, GUJRANWALA MIR MUZAFFAR ROAD GUJRANWALA	HR ENTERPRISES		<u>TECHNICAL SPECIFICATION - model no a1500 & a3000 mechanical data a. electrical heater b. work space required 40" x 13" room with well ventilation c. length 12 feet width 3.5 to 4.5 feet height 4.5 feet (app) d. ALL MATERIAL STRUCTURE IN MS PIPE. E. OUTER CASSING 22 SWG G I SHEET F. REVOLVING WHEELS. ELECTRICAL DATA A. GEAR MOTOR 1.5 KW B.</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CONTROL PANNEL C. AUTO VARIABLE PANEL D. 06 NOS OF CONTRACTORS E. 02 NOS OF HEAT CONTROLLER F. HEATER AS PER EXISTING G. 02 NOS THERMOC COUPLES H. MAIN POWER CABLE 05 FEET J. ALL HEATER PROTECTIVE TO ANY HAZARDS. MATERIAL grade: SS 304 TYPE CAPICITY: 3000 CHAPATI PER HOURGENERAL SPECIFICATION - model no a1500 & a3000 mechanical data a. electrical heater b. work space required 40" x 13" room with well ventilation c. length 12 feet width 3.5 to 4.5 feet height 4.5 feet (app) d. ALL MATERIAL STRUCTURE IN MS PIPE. E. OUTER CASSING 22 SWG G I SHEET F. REVOLVING WHEELS. ELECTRICAL DATA A. GEAR MOTOR 1.5 KW B. CONTROL PANNEL C. AUTO VARIABLE PANEL D. 06 NOS OF CONTRACTORS E. 02 NOS OF HEAT CONTROLLER F. HEATER AS PER EXISTING G. 02 NOS THERMOC COUPLES H. MAIN POWER CABLE 05 FEET J. ALL HEATER PROTECTIVE TO ANY HAZARDS. MATERIAL grade: SS 304 TYPE CAPICITY: 3000 CHAPATI PER HOUR	
90	DNM64019	9Y3333	4420012184348 / CORE ASSEMBLY FLUID	CATTER PILLAR D/G	1 / EACH/NUMBER			USA CATTER PILLAR	CATTER PILLAR		<u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A</u>	
91	DPC56057	X00069385	6810725232428 / COOLANT CS 10/90 CORROSION INHIBITOR PREMIX (PACKING 200 OR 20 LITER)	All MTU Engines	160 / LITER	CS 10/90	Various	MTU Friedrichshafen GmbH, Friedrichshafen Germany Website: www.mtu-online.com	MTU Friedrichshafen GmbH		<u>TECHNICAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added quality water 10% Coolant and 90% Water Manufactured by MTU</u> <u>GENERAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
92	DGE366 35	BS 5120 (1975)	041359923877 4 / HOSE RUBBER COLOUR BLACK INT DIA 0.375" LG 60FT NO OF PLIES3		125 / METER						quality water 10% Coolant and 90% Water Manufactured by MTU <u>TECHNICAL SPECIFICATION -</u> SIZE: DIA:3.2MM LENGTH PER UNIT/ELECTROD E:350 MM TECHNICAL SPECIFICATION: Ø: 3.2 MM SPEC: AWS A5.1 OF 2004 E TH-907A CHEMICAL COMPOSITION: C = 0.04 NI 1.70- 1.90 SI = 0.10 TI 0.10-0.22 MN 1.20- 1.40 MO = 0.05 S = 0.015 CR = 0.05 P = 0.015 NB = 0.02 V = 0.02 N = 80PMM MECHANICAL SPECIFICATION AND ACCEPTANCE CRITERIA: DESCRIPTION MECHANICAL SPECIFICATION TENSILE STRENGTH 390 (MPA) YIELD POWER (470-650) ELONGATION 20.0% PACKAGING 05 KG PER BAG. FINAL DELIVERY WITH ONE BATCH/LOT CLASSIFICATION SOCIETY APPROVAL OF ANY INTERNATIONAL CLASSIFICATION I.E. LR,BV,ABS,DNV.GL, C€,JIS, ISO-9001- 2015 SEE ATTACHED DOCUMENTS FOR DETAILS NOTE: SURFACE QUALITY OF WELDING ELECTRODE SHOULD CONFORM TO THE CONDITION OF GB/T 14957. AT THE FRONT OF WELDING ELECTRODE PACK, ANTI-RUST OIL SHOULD BE APPLIED TO PROTECT IT FROM RUST. <u>GENERAL SPECIFICATION -</u> SIZE: DIA:3.2MM LENGTH PER UNIT/ELECTROD E:350 MM TECHNICAL SPECIFICATION: Ø: 3.2 MM SPEC: AWS A5.1 OF 2004 E TH-907A CHEMICAL COMPOSITION: C = 0.04 NI 1.70- 1.90 SI = 0.10 TI 0.10-0.22 MN 1.20- 1.40 MO = 0.05 S = 0.015 CR = 0.05 P = 0.015 NB = 0.02 V = 0.02 N = 80PMM MECHANICAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>SPECIFICATION AND ACCEPTANCE CRITERIA: DESCRIPTION MECHANICAL SPECIFICATION TENSILE STRENGTH 390 (MPA) YIELD POWER (470-650) ELONGATION 20.0% PACKAGING 05 KG PER BAG. FINAL DELIVERY WITH ONE BATCH/LOT CLASSIFICATION SOCIETY APPROVAL OF ANY INTERNATIONAL CLASSIFICATION I.E. LR,BV,ABS,DNV.GL, C€,JIS, ISO-9001- 2015 SEE ATTACHED DOCUMENTS FOR DETAILS NOTE: SURFACE QUALITY OF WELDING ELECTRODE SHOULD CONFORM TO THE CONDITION OF GB/T 14957. AT THE FRONT OF WELDING ELECTRODE PACK, ANTI-RUST OIL SHOULD BE APPLIED TO PROTECT IT FROM RUST.</p>	
93	DGE32157	202-GNFG	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER I.R. SIZE 9		30 / PAIR	202-GNFG					<p><u>TECHNICAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity</p> <p><u>GENERAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity	
94	SPC5140 1	BS 3981	047350942925 0 / PIGMENT POWDER BURNT SIENA (Packing 56 LB or 400 Gram) TIGER BRAND	USE DRY INGREDIENTS FOR PAINTS	40 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - BS 3981 BRAND= TIGER</u> <u>GENERAL SPECIFICATION - BS 3981 BRAND= TIGER</u>	
95	DPC585 54		047350473004 0 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGR AMME						<u>TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)</u> <u>GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)</u>	
96	DPK6130 2	DEFSTAN 01-5	047550220234 8 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		400 / LITER						<u>TECHNICAL SPECIFICATION - sSPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u> <u>GENERAL SPECIFICATION - sSPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u>	
97	DGE641 85		046159000405 8 / HEAD SCREEN FOR		31 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11),</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECTRIC WELDING WITH GLASS BLACK.								Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae <u>GENERAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11),</u> Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dinii protection. standards: en166, en169, en175, & ce make : delta plus, france / uae	
98	DPC56708	732RTV	042599225196 2 / SILICON RUBBER SILASTIC 732RTV (SEALING COMPOUND) WHITE 90ML TUBE (OEM DOW CORNING)	PROPELLER SEALING	100 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
99	DPC59472	732RTV	042599225196 2 / SILICON RUBBER SILASTIC 732RTV (SEALING COMPOUND) WHITE 90ML TUBE (OEM DOW CORNING)	PROPELLER SEALING	142 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
100	SGB49415		021459003565 3 / BOLT MACHINE STEEL BSW	P/N BS 916	200 / TEN						<u>TECHNICAL SPECIFICATION - MATERIAL GRADE: AISI 4140 / ANY RELEVANT GRADE e.g. BS 708M40 NOMINAL LENGTH: 1 ½ Inch</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			HEX HD SZ 1.5 X0.375"THD LG 3/4"TPI 16								<p>OUTER DIA: 3/8 Inch THREAD LENGTH: 3/4 Inch TPI: 16 HEAT TREATMENT CONDITION: R</p> <p><u>GENERAL SPECIFICATION -</u> MATERIAL GRADE: AISI 4140 / ANY RELEVANT GRADE e.g. BS 708M40 NOMINAL LENGTH: 1 1/2 Inch OUTER DIA: 3/8 Inch THREAD LENGTH: 3/4 Inch TPI: 16 HEAT TREATMENT CONDITION: R</p>	
101	SGB561 63	BS2451 (5350-99-923-3461)	028370923346 1 / CHILLED-IRON-GRIT-TYPE-FINE-GD-24		1000 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION -</u> STANDARD PARTIDE SIZE: G-24=0.6 TO 1.0 MM STANDARD: ISO 11124-2, METALLIC BLAST-CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 %</p> <p><u>GENERAL SPECIFICATION -</u> STANDARD PARTIDE SIZE: G-24=0.6 TO 1.0 MM STANDARD: ISO 11124-2, METALLIC BLAST-CLEANING ABRASIVE. GRIT PARTICLE SHAPE. HARDNESS: ROCKWELL 61 TO 64 HRC, ± 3 HRC SHAPE: ANGULAR AND IRREGULAR. DENSITIES: 7g/ cm3 (APPARENT DENSITY) 3.8 g/ m3 (BULK DENSITY) CHEMICAL COMPOSITION (APPROXIMATE VALUES) CARBON C: 3.00 % to 3.20 % MANGANESE Mn: 0.30 % to 1.00 % SILICON SI: 1.00 % to 1.50 % PHOSPHOROUS P: 0.10 % to 0.60 % SULFUR S: 0.07 % to 0.17 %</p>	
102	DGD651		024770511752	STOVE	6 /						<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	45		1 / STOVE/BURNER GAS OPERATED (I/D 18" VALVE DIA 2")SEE COM F8	BURNER (EGLE STAR)	EACH/NUMBER						STOVE/BURNER GAS OPERATED (I/D 18" VALVE DIA 2")SEE COM F8 EGGLE STARGENERAL SPECIFICATION - STOVE/BURNER GAS OPERATED(I/D 18" VALVE DIA 2")SEE COM F8 EGGLE STAR	
103	DGE37219	0043A00	0245999233890 / Bowl Water Closet Colour White Single Piece	WC FITTED IN SAILOR,S BATH ROOM	4 / EACH/NUMBER	Annex/Master/Durr					TECHNICAL SPECIFICATION - 1* MAIN BODY : IN PORCELAIN MATERIAL &GENERAL SPECIFICATION - 1* MAIN BODY : IN PORCELAIN MATERIAL &	
104	SGB56868	0251-14505	0251704119737 / FERRULE-WIRE-ROPE 1.5 INCH (12mm)		275 / EACH/NUMBER						TECHNICAL SPECIFICATION - ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA:27.2 MM ferrule length: 45 mm GENERAL SPECIFICATION - ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA: 27.2 MM ferrule length: 45 mm	
105	DGH63372	SAFFIRE MODEL NM250, PART NO. 116324	0281502811666 / NOZZLE INNER GAS CUTTING TORCH SIZE 1/16 INCH	REF NO 529-4 SHEET U	20 / EACH/NUMBER						TECHNICAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.GENERAL SPECIFICATION - saffire a-nme, SIZE 1/16", MODEL NM250, PART NO. 116324, TDS enclosed.	
106	DGE58385		0474504740019 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAN,INNER PLY 5 OZ+9 OZ,UPPER	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03 <u>GENERAL SPECIFICATION -</u> Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03	
107	DNF65314	BS EN 60317-8	0561795253580 / WIRE, WINDING COPPER ELECT COND DIA 1.320 O/DIA 1.423 MM (CLASS-180) GRADE-2	WIRE FOR WINDING	70 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION -</u> DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 PURITY 99.95 % Copper <u>GENERAL SPECIFICATION -</u> DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 PURITY 99.95 % Copper	
108	DNF65476	N250 PLUS EXIDE / OSAKA	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	2 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					<u>TECHNICAL SPECIFICATION -</u> BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA <u>GENERAL SPECIFICATION -</u> BATTERY LEAD	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		OR EQUALEN T									ACID 12V 200AH EXIDE / OSAKA	
109	SNF64309	R20SG	056279910110 1 / BATTERY DRY N/RECHARGE ABLE 1.5V LG 61 MM DIA 32.5MM R20SG	TORCH LIGHT	1500 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
110	DNM65358	NR-20550/96	292072508958 7 / FOG GENERATOR TF-35 FOR CONTROL OF MOSQUITOES	FOR GENERATOR TF35FOR CONTROL (GERMANY)	1 / EACH/N UMBER	TF-35					<u>TECHNICAL SPECIFICATION - IGEBAGENERAL SPECIFICATION - IGEBAGENERAL</u>	
111	DNM64495	7L7504	2930US508082 3 / BODY SEA WATER PUMP	CATTER PILLER D/G (U S A)	1 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
112	DNA63341	SN 02-06	281573508919 9 / FERRULE SIZE 3/8"	MACHINERY ON TYPE-21 & MCMVS	40 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
113	DNM65144	901-115	291079511305 7 / OIL FILTER	FG KEY DG PERKIN 1306- E87T 215	2 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
114	DNA63338	SN 02-04	281573508919 7 / FERRULE SIZE 1/4"	MACHINERY ON TYPE-21 & MCMVS	20 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
115	DGE44122		422050510192 9 / LIFE JACKET	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	30 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003</u> <u>GENERAL SPECIFICATION - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33"</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003	
116	DNM64501	5N9360 (4320-01-201-2865)	4320715035131 / IMPELLER ASSY (D18M07Y13P472) I/D25 O/D60MM 12FINS RUBBER INNER SLEEVE BRASS	INDUSTRIEL MARINE CATTER PILLER ENGINE	1 / EACH/NUMBER	5n-9360					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DNH65516		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE COMPLETE	SELF	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY) GENERAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
118	DNH65323	NO DATA AVAILABLE	4110PK5073820 / WATER COOLER STORAGE TYPE CAPACITY 30 LITERS 220V .33HP	WATER COOLER STORAGE TYPE	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	DNH64631		4140705041640 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
120	DNZ48192	112401	4130785026767 / SEAL SHAFT LENGTH 82	AIR CONDITIONER PLANT 6C75 (2)EB NASR	7 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MM DIA 70 MM AA005									
121	DGP619 98		361070504530 3 / POSITIVE PLATE ROLAND OFFSET size: 925X740X0.3MM(BRND FUJI)		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - SIZE: 925X740X0.3MM(BRND FUJI) GENERAL SPECIFICATION - SIZE: 925X740X0.3MM(BRND FUJI)	
122	DNH653 59	wdf-318	411073100120 0 / DEEP FREEZER 18 CU FT-220 V AC 50 HZ PEL, WAVES AND DAWLANCE		1 / EACH/NUMBER	WDF-318					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DGP652 73	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CDs.	
124	DGB49077	CH50-10	4030705039310 / CHAIN BLOCK 5TON CAPACITY WITH 45 FEET DRIFT LINE DIA 9MM-	FOR GENERAL PURPOSE-	1 / EACH/NUMBER	CH50-10					TECHNICAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load1 GENERAL SPECIFICATION - Make: ELEPHANT JAPAN Shipping Weight: 84.0 Lbs. Test Load: 7.5 Tons Load Chain size: 3.54 Inch Weight: 84 LBS Type: Manual Acceptance CRITERIA : lifting OF 5 Tons Load1	
125	SGB62684		5306PK5065902 / BOLT 14X58MM<STEEL>DIA 15/32" NOM LG 1-15/16" TPI 15		80 / EACH/NUMBER						TECHNICAL SPECIFICATION - material: stainless steel (MEDIUM CLASS STEEL)GENERAL SPECIFICATION - material: stainless steel (MEDIUM CLASS STEEL)	
126	SNZ64311		5307PK5065918 / STUD 12X65MM<STEEL>DIA1/2" O/ALG 2-5/8" TH LG1-3/16" X5/8"TPI15		200 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL: SS DIA: 12MM X 2.00 PITCH LENGTH: 65MM GENERAL SPECIFICATION - MATERIAL: SS DIA: 12MM X 2.00 PITCH LENGTH: 65MM	
127	DGB39396	MODEL P-40	5130765016394 / ELECTRIC PORTABLE PLANNER AND GROOVERS (C/WD 136 MAX-C/D 3MM)	GENERAL USE	5 / EACH/NUMBER						TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null	
128	DNM65213	3081012	4720715097533 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	1 / EACH/NUMBER	3081012					TECHNICAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR GENERAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR	
129	DGB53400	NO DATA AVAILABE	4730705038535 / band pipe m/s 2.5 inch	DUMP BARGE COUNSTRUCTION	22 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload) <u>GENERAL SPECIFICATION - Material: Mild Steel Grade JR275 Size: 2.5 inch x 4.775 mm thick Schedule: 40 OEM: Pakistan/China Usage: Fuel and sea water system specification: en 10025-2-s275jr+ar (pipe) *3 material: s275jr (detail specification upload)</u>	
130	DNG64694	5149571	5330218931577 / GASKIT MAJOR OVERHAUL	GM DETROIT ENGINE 149 SERIES	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
131	DNM64426	8S1606	5330004378752 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA-9MM TH-03MM	3304PC, CATERPILLER D/GEN.USA	2 / EACH/NUMBER	3304 SSDG					<u>TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG</u> <u>GENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG</u>	
132	SNM62490	4W8087	5330012110809 / SEAL WATER OLD PART NO. 7N8025	CATER PILLER DIESEL GENERATOR	16 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
133	DNG64695	5148334	5365715110332 / RING FIRE	GM DETROIT M/ENGINE USA	12 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
134	DNG64698	5199131	5365715110335 / RING SET	GM DETROIT M/ENGINE USA	12 / SET						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
135	DNF64509	MOD 265 TOA JAPAN	5830JP5078165 / TOA SOLID STATE PA AMPLIFIER 100VAC 50/60HZ25WO/ P MOD 265	PA SYSTEM	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
136	DNF62012	158-51010	5961995580307 / DIODE 25AMPS	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			600VOLT.								AVAILABLE	
137	DSB62571	23TR4A	5990008225451 / SYNCHRO RECEIVER ROTOR I/P-115V 400HZ 7.8 WATT SIZE 23	MK73MOD1, INDICATOR, RECOMMENDED COURSE	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MIL-S-20708-94</u> <u>GENERAL SPECIFICATION - MIL-S-20708-94</u>	
138	DNF65478	WP7-12 -L O NG/LX7-12/ PR 12-70	6140CH5088427 / BATTERY 12VOLT 7AH LEAD ACID SEALED.	1 KVA UPS NS-1000	8 / EACH/NUMBER	WP7-12 -L O NG					<u>TECHNICAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG.</u> <u>GENERAL SPECIFICATION - SPECIFICATION:BATTERY 12V 7AH SEALED M/FREE.MODEL NO. PR12-7, ,WEIGHT 2.15KG.</u>	
139	DNF64513	GLD-3000C (STABIMATIC) /PANDA/S TAC	6110705060205 / STABILIZER 3KVA I/P50-130/160-240VAC 50/60HZ O/P110/220V LOCAL	ELECTRICAL GENERAL USE	1 / EACH/NUMBER	GLD-3000C (STABIMATIC)					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
140	DNF65391	1165190/1165180/1165170 / AD10-2HHMD	6350715088918 / TR HAND HELD METAL DETECTOR SUPPER SCAN	SELF (SECURITY EQUIP) OEM GARRETT USA	2 / EACH/NUMBER	1165180/1165170 / AD10-2HHMD					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
141	DGE34854		6530505024908 / OVER BED TABLE ADJUSTABLE 805X405MM STAND 4 WHEEL S/S ROUND		7 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Item Specification: Height-30 Cm,Length-28 Cm, Width-15 Cm, Steel brand Standard 16" Gauge, Adjustable Stand Handle, 04 Wheel plastic</u> <u>GENERAL SPECIFICATION - Item Specification: Height-30 Cm,Length-28 Cm, Width-15 Cm, Steel brand Standard 16" Gauge, Adjustable Stand Handle, 04 Wheel plastic</u>	
142	SNC52813	ELEC-2650 / IN 63047/2650	6230795110272 / SEARCH LIGHT HAND HELD (24V	GRIFFON HOVER CRAFT LTD UK	50 / EACH/NUMBER	GEEPAS®					<u>TECHNICAL SPECIFICATION - 1. Make/ Brand: GEEPAS® 2. Model: GSL5706 - 30Watt</u> <u>GENERAL SPECIFICATION - 1. Make/ Brand:</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DC&230 WATT)								GEEPAS ® 2. Model: GSL5706 - 30Watt	
143	DGP57856		7530705007179 / PAPER COVER YELLOW GSM 125+5% REAM OF 500SHEETB-02 500X707MM		50 / REAM						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
144	DGD63563	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - capacity: 36 LITTERs</u> <u>GENERAL SPECIFICATION - capacity: 36 LITTERs</u>	
145	DPC49694	NO DATA AVAILABLE	6840705057111 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	10 / LITER						<u>TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u> <u>GENERAL SPECIFICATION - Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.</u>	
146	DPC57391	R-5021	8010705111038 / PIGMENT (PANTHER BLACK)	GRP WORK, M/S ZAIN SONS KARCHI, PH7731541	50 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 05 Kg packing</u> <u>GENERAL SPECIFICATION - 05 Kg packing</u>	
147	DGE58502		8340705087913 / TENT 40 POUND ARMY PATT = FLY & FOLD DOUBLE = L7W 6FT (JUNGLE GREEN)	GENERAL PERPOSE	15 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - a. Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER <u>GENERAL SPECIFICATION</u> - a. Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER</p> <p><u>TECHNICAL SPECIFICATION</u> - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus</p>	
148	DGE58501		8340705087915 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	2 / EACH/NUMBER							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent ; Iron Poles (Centre & Ride) ; Iron Hammer ; Iron Stick for walls ; Iron pins ; Iron pegs ; Repair Kit ; P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN <u>GENERAL SPECIFICATION</u> - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent ; Iron Poles (Centre & Ride) ; Iron Hammer ; Iron Stick for walls ; Iron pins ; Iron pegs ; Repair Kit ; P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OF ORIGIN: PAKISTAN	
149	DGE53951		0310500000004 / CANVAS COTTON GREY (WD: 24")		1179 / METER	NO DATA AVAILABLE					<p><u>TECHNICAL SPECIFICATION - SIZE: WIDTH 24" WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</u><u>GENERAL SPECIFICATION - SIZE: WIDTH 24" WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance</u></p>	
150	DNQ62662	NIL	8415705102555 / SURCOAT WHITE WITH RED CROSS	FIRE FIGHTING, BSO TAILORS, PN DOCKYARD	10 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - UK/SC/4765 ISSUE 09 OEM: COONEEN GROUP UK</u><u>GENERAL SPECIFICATION - UK/SC/4765 ISSUE 09 OEM: COONEEN GROUP UK</u></p>	
151	DNQ62661	NIL	8415705102560 / SURCOAT RED WITH WHITE STRAP	FIRE FIGHTING, BSO TAILORS, PN DOCKYARD	2 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - DC/MS/5603-2 ISSUE 04</u><u>GENERAL SPECIFICATION - DC/MS/5603-2 ISSUE 04</u></p>	
152	DGP63615	NO DATA AVAILABLE	7435705114870 / PERSONAL COMPUTER CORE i7 (AS PER NHQ APPROVED SPEC)	SELF	1 / SET						<p><u>TECHNICAL SPECIFICATION - specification of pc: HP/DELL CORE i7 SYSTEM OR HIGHER EQUIVALENT. 1. CPU Technology: Intel ® Core i7 (8th/9th/10th/11th/12th Generation or above) (Minimum 2.4 & 4.7 GHz or above), 2. System Memory: 8/16 GB RAM DDR3/DDR4 or (02 x 4GB OR 02X08 gm RAM ddr3/ddr4). 3. Hard Disk: 1 TB SATA 4. Optical Disk Drive: DVD RW 5. Keyboard: wired/usb 6. Mouse: wired/usb 7. LED: 18.5" HDMI Display 8. LAN: Ethernet Card: 10/100/1000 Mbps 9. Warranty: 3 Years 10. Operating System: Windows (Licensed Version</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>window-10 or above). 11. Graphics: Intel ® HD Graphics 750, (Minimum 2 GB shared/ dedicated GraphIC CARD)<u>GENERAL SPECIFICATION - specification of pc: HP/DELL CORE i7 SYSTEM OR HIGHER EQUIVALENT. 1. CPU Technology: Intel ® Core i7 (8th/9th/10th/11th/12th Generation or above) (Minimum 2.4 & 4.7 GHz or above), 2. System Memory: 8/16 GB RAM DDR3/DDR4 or (02 x 4GB OR 02X08 gm RAM ddr3/ddr4). 3. Hard Disk: 1 TB SATA 4. Optical Disk Drive: DVD RW 5. Keyboard: wired/usb 6. Mouse: wired/usb 7. LED: 18.5" HDMI Display 8. LAN: Ethernet Card: 10/100/1000 Mbps 9. Warranty: 3 Years 10. Operating System: Windows (Licensed Version window-10 or above). 11. Graphics: Intel ® HD Graphics 750, (Minimum 2 GB shared/ dedicated GraphIC CARD)</u></p>	
153	DPC573 94	BUTANOX M-60	681073100099 4 / METHAIL ETHYLE KETONE PER OXIDE		160 / KILOGR AMME						<p><u>TECHNICAL SPECIFICATION - SPECIFICATION: APPERANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4</u> <u>GENERAL SPECIFICATION - SPECIFICATION: APPERANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4</u></p>	
154	DPC569 50	TS10268/ ZOK 27	685099225402 0 / COMPRESSO R CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSO R G.T.E.TYPE 21	150 / LITER						<p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
155	DNF65369	ep-1000t/blazer vista 1000	7035705059927 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BVBS-2	1 / EACH/NUMBER	BLAZER VISTA 1000/Auro ra					<u>TECHNICAL SPECIFICATION</u> - backup time: 10 minutes Product Name: AURORA Input: 220V <u>ACGENERAL SPECIFICATION</u> - backup time: 10 minutes Product Name: AURORA Input: 220V AC	
156	DGD65151	NO DATA AVAILAB LE	7320705012426 / MACHINE ATTA KNEADING100 TO120KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/NUMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION</u> - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade) <u>GENERAL SPECIFICATION</u> -_Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)	
157	DGD65150	NO DATA AVAILAB LE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY s/steel		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market <u>GENERAL SPECIFICATION</u> - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market	
158	DGD65152	T52254 / E-6228	7320705045236 / MINCING MACHINE NO 22 WITH 2HP MOTOR BASE FRAME RPM 1420		1 / EACH/NUMBER	pakistan					<u>TECHNICAL SPECIFICATION</u> - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN <u>TECHNICALY ACCPEPTENCE BY END USER</u> <u>GENERAL SPECIFICATION</u> - Frame of Machine Material: Mild Steel, MATERIAL OF Motor body and Mincing Machine: Cast Iron NOTE: ITEMS MADE IN PAKISTAN <u>TECHNICALY ACCPEPTENCE BY END USER</u>	
159	DNF63931	D7	0553790000045 / INDUSTRIAL X-RAY FILM PB D7 SIZE 10x40cm (VACUPACK)	PHOTOGRAP HOC	2 / PACKE T	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILAB LE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILAB LE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
160	SPC58340	BS 627 (F-8) (R 5123)	8010705128764 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOU	50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
161	DSB63628	9529000	1370992197117 / Hand flare RED (solas approved) mk-8		6 / EACH/NUMBER	mk-8					TECHNICAL SPECIFICATION - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela. GENERAL SPECIFICATION - The Handflare MK8 conforms to SOLAS 74 as amended. Designed to withstand exceptional environmental exposure and to perform reliably even after immersion in water. Featuring a telescopic handle with improved grip, making it very compact for stowage. Easily extended for safe handling and operation by pull wire ignitor. Produces hot red flame for 60 seconds at 15000 candela.	
162	DNQ64390	GOMTEX Ø 30310003800	4730705269709 / hose assy rubber duraline/ gometex lg 100 ft id 1-1/2"		13 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETEX LG 100 FT ID 1-1/2"					TECHNICAL SPECIFICATION - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3 specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.<u>GENERAL SPECIFICATION</u> - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3 specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.</p>	
163	DNQ61651	GOMTEX Ø 30310003800	473070526970 9 / hose assy rubber duraline/ gometex lg 100 ft id 1-1/2"		4 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETEX LG 100 FT ID 1-1/2"					<p><u>TECHNICAL SPECIFICATION</u> - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3 specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.<u>GENERAL SPECIFICATION</u> - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3 specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.	
164	DCD65473		845550080115 2 / BADGE CAP CPO GOLD		1600 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - BADGE CAP CPO GOLD</u> <u>GENERAL SPECIFICATION - BADGE CAP CPO GOLD</u>	
165	DCD63946		845570390176 0 / BADGE ARM MEDICAL (LAB) ARTIFICER RED EMBROIDRY		300 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
166	DNJ65523	50020-96869-YAY	285076530170 0 / LOWER UNIT		1 / EACH/ NUMBER	Z2H5KAL #E01					<u>TECHNICAL SPECIFICATION - LOWER UNIT</u> <u>GENERAL SPECIFICATION - LOWER UNIT</u>	
167	DCD65351		845550518005 0 / CAP PEAK FOR FEMALE MEDICAL ASSISTANT		300 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION - CAP PEAK FOR FEMALE MEDICAL ASSISTANT MEHR BAND BLACK RED BADGE PEAK REXENE Inside Peak leather board Upper cap jersey cloth black White jersey ribbed around the cap Button Chain strip Inside Rexene patti Chain strip buckle plastic</u> <u>GENERAL SPECIFICATION - CAP PEAK FOR FEMALE MEDICAL ASSISTANT MEHR BAND BLACK RED BADGE PEAK REXENE Inside Peak leather board Upper cap jersey cloth black White jersey ribbed around the cap Button Chain strip Inside Rexene patti Chain strip buckle plastic</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
168	DNQ61650	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		4 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMETEX LG 100 FT ID 2"					<u>TECHNICAL SPECIFICATION -</u> SPECIALY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa <u>GENERAL SPECIFICATION -</u> SPECIALY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
169	DN065362	ZH1-30-1 / MLXCW30-SEW	534078526987 4 / SEA WATER PUMP MECHANICAL SEAL		1 / EACH/NUMBER	CLS-350					<u>TECHNICAL SPECIFICATION -</u> BORE: 30 MM DIA: 55 MM LENGTH: 68 MM COVER DIA: 90 MM <u>GENERAL SPECIFICATION -</u> BORE: 30 MM DIA: 55 MM LENGTH: 68 MM COVER DIA: 90 MM	
170	DNF65364	og-svtpm40kh-p	596378523835 5 / power module apc smart ups vt-40 kva		1 / EACH/NUMBER	og-svtpm40kh-p					<u>TECHNICAL SPECIFICATION -</u> maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load. <u>GENERAL SPECIFICATION -</u> maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load.	
171	DNF65495	og-svtpm40kh-p	596378523835 5 / power module apc smart ups vt-40 kva		1 / EACH/NUMBER	og-svtpm40kh-p					<u>TECHNICAL SPECIFICATION -</u> maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load. <u>GENERAL SPECIFICATION -</u> maximum back up time of 40 KVA UPS installed at SEC FCOC is 02 hour when running on maximum load.	
172	DNF64917	ub500	635078524635 9 / WALK THROUGH GATE WITH MONITOR &		2 / EACH/NUMBER	ub500					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			FACE CAPTURE CAMERA model no: ub500									
173	DNF63947	VE/S. Sockets/F P.1012	5930505234863 / Switch Socket TWO PIN		77 / EACH/NUMBER	VE/S. Sockets/F P.1012					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
174	DCD65155		8455504801609 / soft badge shoulder crescent and star mcpo pak marine		1000 / PAIR						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
175	DCD63944		8455703901758 / BADGE ARM MEDICAL (LAB) MT-I RED EMBROIDRY		300 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
176	DCD63943		8455703901757 / BADGE ARM MEDICAL (LAB) MT-II RED EMBROIDRY		300 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
177	DNF62320	s115 sport camera backpack	6760715235453 / bag with trolley large pelican s115 sport camera backpack		1 / EACH/NUMBER	S115 SPORT CAMERA BACKPACK					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
178	DN063355	G860022-02 / ZRACR-065-SEW	6115FP1050065 / ANTI-CORROSIVE ZINC ROD		2 / EACH/NUMBER	1FR6 506-4SA42-2					TECHNICAL SPECIFICATION - MATERIAL: ZINC 99.9 ±2% GENERAL SPECIFICATION - MATERIAL: ZINC 99.9 ±2%	
179	DPK57358	s4 p 100	9150705270734 / compressor oil shell corena s4 p 100		10 / LITER	s4 p 100					TECHNICAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											= METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES <u>GENERAL SPECIFICATION - SPECIFICATION, APPROVALS & RECOMMENDATIONS SHELL REFRIGERATION OIL S4 FR-F MEETS THE REQUIREMENTS OF DIN 51503 KD. TYPICAL PHYSICAL CHARACTERISTICS PROPERTIES</u> = METHOD = REFRIGERATION OIL S4 FR-F 68 ISO VISCOSITY GRADE = ISO 3448 = 68 REFRIGERATOR OIL GROUP = DIN 51503 = KD KINEMATIC VISCOSITY @ 40 C (MM2/S) = ISO 3104 = 66 KINEMATIC VISCOSITY @ 100 C (MM2/S) = ISO 3104 = 8.8 DENSITY @ 15 C (KG/M3) = ISO 12185 = 991 FLASH POINT (COC) (DEGREE CELSIUS) = ISO 2592 >230 POUR POINT (DEGREE CELSIUS) = ISO 3016 = -42 NEUTRALIZATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NUMBER (MG KOH/G) = ASTM D664(TAN) 0.06 CHARACTERISTICS WHEN USED WITH R134A – FLOC-POINT (DEGREE CELSIUS) = DIN 51351 -30 CHARACTERISTICS WHEN USED WITH R134A – REFRIGERANT (@250 C) = DIN 51393 >96 MISCIBILITY = MISCIBLE OVER THE WHOLE RANGE OF TYPICAL REFRIGERATION TEMPERATURES	
180	DPC49051	BLK01	6810705279759 / ADVANCE COAT Polyethylene COATING POWDER BLACK SHADE		40 / KILOGRAMME	POLYETHYLENE					<u>TECHNICAL SPECIFICATION - Polyethylene Coating Powder)</u> <u>GENERAL SPECIFICATION - Polyethylene Coating Powder)</u>	
181	DCD65352		8455703901761 / BADGE ARM MEDICAL (MW) MT-II RED EMBROIDRY		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
182	DNF62321	aol pll-01	5850705293063 / led aviation mast light 110-240V AC 4WATT (RED COLOR)		30 / EACH/NUMBER	PLL-01					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
183	DCD65361		8455703138362 / ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE		1500 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE</u> <u>GENERAL SPECIFICATION - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE</u>	
184	DNM64011	0102-1543	5330015734932 / joint-sump to cylinder block assembly (1 pair) / GASKET OIL BASE		2 / EACH/NUMBER	c22 d5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
185	DCD65355		845570390176 4 / badge arm medical (mw) artificer red embroidery		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
186	DCD65353		845570390176 2 / BADGE ARM MEDICAL (MW) MT-I RED EMBROIDRY		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
187	DCD65354		845570390176 3 / badge arm medical (mw) lmt red embroidery		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
188	DCD63945		845570390175 9 / BADGE ARM MEDICAL (LAB) LMT RED EMBROIDRY		300 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
189	DNF65520	RSFD-II	613578528471 7 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		13 / EACH/NUMBER	RSFD-II					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
190	DGB65291	XT10/209822	345572528080 6 / CUTTING DISC RHODIUS XT10 SIZE 105x1x16		85 / EACH/NUMBER	RHODIUS TOPLINE					<u>TECHNICAL SPECIFICATION - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS</u> <u>GENERAL SPECIFICATION - MATERIAL SPECIFICATIONS: STAINLESS STEEL, RUST AND ACID PROOFED STEELS, HIGH TENSILE, HIGH ALLOYED STEELS, TOOL STEELS, HARDENED STEELS, HARDOX, HIGH TENSILE METAL SHEETS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
191	SNM62500	100-3880	2815015067155 / PUSHROD-VALVE	CATERPILLAR GENSET D3512B (YBB1) USA	16 / EACH/NUMBER	NA	CAT3512 BEYBB00583	CATERPILLAR, INC . 100 N.E. ADAMS STREET, PEORIA, IL 61629 USA	CATERPILLAR USA		<u>TECHNICAL SPECIFICATION - 0</u> <u>GENERAL SPECIFICATION - 0</u>	
192	DNM64247	4309460	5330016657611 / LOWER ENGINE GASKET		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u> <u>GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7</u>	
193	SNM61057	TGEL46	4120785208552 / THERMOSTATIC EXPENSION VALVE (TXV) DANFOSS	AIR COOL CHILLER85 TON TGEL46 CHINA	1 / EACH/NUMBER	TGEL46	SNWM789230	DANFOSS COMATROL 201206 SHANGHAI BUILDING#22, NO.1000 JIN HAI ROAD JIN QIAO, PUDONG CHINA	DENFOS S CHINA		<u>TECHNICAL SPECIFICATION - TGEL 35TR, 125KW R410A PS 46 BAR/MWP 667 PSIG</u> <u>GENERAL SPECIFICATION - TGEL 35TR, 125KW R410A PS 46 BAR/MWP 667 PSIG</u>	
194	DNM63831	3015067	5331013264774 / SEAL D RING	DIESEL GENERATOR	6 / EACH/NUMBER	KTAA 19-G6/G7	4061330-00	CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES 47201-6258 TEL:8123775009 FAX:8123771715	CUMMINS INC.500 JACKSON ST COLUMBUS IN UNITED STATES		<u>TECHNICAL SPECIFICATION - LINER KIT REF NO 20</u> <u>GENERAL SPECIFICATION - LINER KIT REF NO 20</u>	
195	DNM58028	CMPU-08	5930785211577 / LOW PRESSURE SWITCH	6 TON AC CWFSC-8+CWCU-108 CHINA	8 / EACH/NUMBER	LPL-2545	NA	XIAN CHAUNG CHINA TSUEN WAN OFFICE YUEN SANG WATCH INDUSTRIES LIMITED 1ST FLOOR 100 TEXACO RAOD TSUEN WAN	XIAN HCUANG CHINA		<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
196	DNJ62399	17400-98J01	5180765222548 / WATER PUMP REPAIR KIT	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00 GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER</u> <u>GENERAL SPECIFICATION - WATER PUMP REPAIR KIT ACCESSORIES 17461-93J00 IMPELLER, WATER PUMP 17416-93J01 SEALING CASE 17472-98J00</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GASKET, PUMP CASE PANEL 17473-98J00 PANEL, WATER PUMP 09420-05009 KEY 17471-98J01 PANEL, PUMP CASE UNDER	
197	DGE32561	VE-ST-ALB-3613	156070520874 9 / ANTI SKID STAIR STEP (36IN X 13 IN)	STAIR CASES	60 / EACH/NUMBER	NIL	N/A	259, A-4, Akhtar Colony, Karachi 021-35385382	M/S VISION ENGINEERING		<u>TECHNICAL SPECIFICATION - ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 36 IN X 13 IN. Material Grade: Aluminum alloy 600 series</u> <u>GENERAL SPECIFICATION - ALUMINIUM ANTI-SKID STAIR TREAD COVERS TO PROVIDE SLIP RESISTANCE. MATERIAL ALUMINIUM WITH RUBBER STRIPS. SIZE 36 IN X 13 IN. Material Grade: Aluminum alloy 600 series</u>	
198	DPK59299	DEFSTAN 01-5	047550220234 8 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		220 / LITER						<u>TECHNICAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u> <u>GENERAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u>	
199	DPC56914	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	500 / LITER						<u>TECHNICAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u> <u>GENERAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u>	
200	DPC49897	106 OF BS381-C OF 1996	044250442006 1 / PAINT VEHICLE CELLULOSE (ROYAL NAVY BLUE)	VEHICLES, DECORATIVE FINISHING	400 / LITER						<u>TECHNICAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u> <u>GENERAL SPECIFICATION - DEF STAN 80-37/2 COLOR SHADE NO, 106 OF BS 381 C OF 1996.</u>	
201	DPC57918	BS 245 OF 1976	044250442007 0 / THINNER FOR PAINT		600 / LITER						<u>TECHNICAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg</u> <u>GENERAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
202	DPC56913	BS 245 OF 1976	0442504420070 / THINNER FOR PAINT		600 / LITER						TECHNICAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg GENERAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg	
203	DPC56129	BS 245 OF 1976	0442504420070 / THINNER FOR PAINT		600 / LITER						TECHNICAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg GENERAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg	
204	DPC61452	BS 245 OF 1976	0442504420070 / THINNER FOR PAINT		500 / LITER						TECHNICAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg GENERAL SPECIFICATION - BS 245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg	
205	DNM50678	7-50-16	1325794600403 / TYRE-750X16-WITH-TUBE	HOLMAN A/COMP DRIVEN BY ROLLS ROYCE D/G	16 / EACH/NUMBER	C-6-NFL-602014					TECHNICAL SPECIFICATION - a. Tyre 7-50-16 with Tube Tread 6 Ply Nylon, Wall 4 Ply Nylon Max load single 3195 at 94 PSI Max load duel 3085 at 94 PSI b. MAKE/ MODEL/ BRAND EQUIVALENT: HIWAY MASTER, CONSTANT AND NONKAND TIWAN ETC. GENERAL SPECIFICATION - a. Tyre 7-50-16 with Tube Tread 6 Ply Nylon, Wall 4 Ply Nylon Max load single 3195 at 94 PSI Max load duel 3085 at 94 PSI b. MAKE/ MODEL/ BRAND EQUIVALENT: HIWAY MASTER, CONSTANT AND NONKAND TIWAN ETC.	
206	DNH65740	NO DATA AVAILABLE	1308500530116 / AIR CONDITIONER 1.5 TON WINDOW TYPE		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
207	DNH65739		4120705051919 / AIR CONDITIONER 1.5 TON SPLIT TYPE	SELF	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - GREE, GENERAL, LG, MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			COMPLETE								GENERAL SPECIFICATION - GREE,GENERAL,LG,MITSUBISHI, DAIKIN (INVERTER BASED SPLIT TYPE ACs MAY BE PREFERRED FOR NORTH REGION ONLY)	
208	DNM52877	3081012	472071509753 3 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	1 / EACH/NUMBER	3081012					TECHNICAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR GENERAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR	
209	DNM57496	3081012	472071509753 3 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	2 / EACH/NUMBER	3081012					TECHNICAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR GENERAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR	
210	DNM54092	3081012	472071509753 3 / SUCTION (BASE) VALVE	AC COND UNIT CRUISAIR WFAH48E OEM:TAYLER	1 / EACH/NUMBER	3081012					TECHNICAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR GENERAL SPECIFICATION - Make/ OEM: U.S.A, CRUISAIR	
211	DGB22252	FLG02-SEW/gd1152 / 1001357	473099525334 7 / FLANGE PIPE ROUND	FOR GENRAL USE	40 / EACH/NUMBER						TECHNICAL SPECIFICATION - Inner dia 1 ¼ inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness ½ inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn8%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches GENERAL SPECIFICATION - Inner dia 1 ¼ inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness ½ inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn8%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches	
212	SNM62499	5P-0840	533101317950 2 / SEAL O RING	3512TA, CATERPILLER USA	51 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
213	DPC62991	IN70052	804079510343 4 / LOCTITE 638 50ML	GRIFFON 2000TD(M), HOVERCRAFT	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
				,UK							AVAILABLE	
214	DNM61859	3805782	6620735126507 / VALVE PLATE ASSY	COMPRESSOR D6SHI-350X AWM/D	2 / EACH/NUMBER	D6SHI-350X AWM/D BELGIUM					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
215	DPK56035		9150FP0020002 / GREASE SHELL GADUS S2 V 100 2 (18 KG Packing)		108 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
216	SNM62497	228-7090	5331015993023 / SEAL-O-RING		28 / EACH/NUMBER	cat c18					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
217	DNM63950	0140-4331	2940785240884 / filter,air		2 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
218	DNM63954	0509-0514	5331795237442 / SEAL OIL		2 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
219	DNM63953	0509-0507	5331795237439 / SEAL OIL		2 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
220	DPC56917	CODE S 136	6850725279746 / solution w (LUB OIL TEST KIT AGENT)		4 / BOTTLE	CODE S 136					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
221	DPK59578		0930930237881 / ABCITE X1060 Thermoplastic Powder coating (RAL 9005-2 BLACK)		4 / CAN	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
222	DPK57623	Castrol Redicool NF premix	2930705288787 / Engine Coolant		450 / LITER	redicool NF					TECHNICAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT GENERAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT	
223	DNM64246	4309459	2815016629279 / UPPER ENGINE GASKET		1 / EACH/NUMBER	QSB 6.7 300 HP CUMMINS ENGINE					TECHNICAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7 GENERAL SPECIFICATION - COUNTRY: UK MANUFACTURE: CUMMINS MODEL: QSB 6.7	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
224	DNM63952	0122-0935	533079526430 2 / GASKET OIL FILTER		2 / EACH/N UMBER	C110D5					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
225	DPK62173	PP 47-32 / P-903SW220-5TTL	4310FM045000 1 / POLYESTER OIL CARRIER COMPRESSO R (5 LTRS PACKING)	CHILL WATER UNIT	45 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA, UNITED SATE	CARRIER CORP 1419 N MARKEE T ST, SACRAM ENTO, CA,UNIT		<u>TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE</u> <u>GENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST, SACRAMENTO,CA,UNITED SATE</u>	