

TENDER BULLETIN

DATE & TIME 7/10/24 12:57 PM INVITATION TO TENDER TO BE OPENED ON 7/24/2 10:00 AM AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	SNM54823	464-6253	481071522303 1 / LIFTER VALVE	DG CAT 7.1 USA	24 / EACH/N UMBER	CAT 7.1	CAT00C7 15GTY00 677	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR		<u>TECHNICAL SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs <u>GENERAL</u> <u>SPECIFICATION -</u> ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DGs	
2	DGE55540		422050510192 9 / LIFE JACKET	FOR PERSONNAL SAFETY,PNS QASIM,PRIZE ENT	110 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - (1)</u> Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33“ bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD- 1688/2003 <u>GENERAL</u> <u>SPECIFICATION - (1)</u> Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33“ bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003	
3	DNC64837	884408A08	4810MB002038 5 / VALVE KIT CONTROL - ELECTRIC BOOST	PETROL MAIN ENGINE	4 / EACH/N UMBER	350	2B614987 , 2B612137 , 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCUR Y MARINE		<u>TECHNICAL SPECIFICATION -</u> VALVE KIT CONTROL - ELECTRIC BOOST <u>GENERAL SPECIFICATION</u> <u>-</u> VALVE KIT CONTROL - ELECTRIC BOOST	
4	SNM57038	2495541	299071516842 1 /	D/G	2 / EACH/N	C 2.2	JAW0049 2	3701 STATE ROAD 26 EAST TOWN LAFA VETTE	USA		<u>TECHNICAL SPECIFICATION -</u> REGULATOR CATERPILLAR C2.2	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			REGULATOR		UMBER			IN POST CODE 47905			DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905 <u>GENERAL SPECIFICATION - REGULATOR CATERPILLAR C2.2 DIESEL GENERATOR 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905</u>	
5	DPK58530	SAE 75W-90	915001363119 2 / LUBRICANT OIL MOBIL 1 SHC (TRANSMISSION OIL) (Packing 20 Liters Drum)	ENGINE	190 / LITER	NO DATA AVAILAB LE		US	M/S MOBILE OIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 22037-4090 TEL: 703-846-4090 IDNS: 001294834		<u>TECHNICAL SPECIFICATION - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090</u> <u>GENERAL SPECIFICATION - OEM: M/S MOBILE OPIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOW S RD FAIR FAX VA USA 32037-4090 TEL 703-846-4090</u>	
6	SNM53856	7W-6249	292001391834 7 / RELAY-SOLENOID, ENGINE STARTER, ELECTRICAL	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/NUMBER	N/A	E3S01292	CATERPILLAR INC MANAGER ,CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 610 MOSSVILLE,LLLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u> <u>GENERAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6</u>	
7	DPC55639	CRESTOMER 1196PA	803079514178 8 / BOUNDING MATERIAL (25 KG PACKING)	MRTP33&VBS S BOATS	30 / KILOGRAMME	NO DATA AVAILAB LE		UK	1. SCOTT BADER CO.LTD. (UK) WOLLASTON, WELLINGBOROUGH,		<u>TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY-1:M/S YONCA-ONUJ JV, TERSANELER CADDESI 50/3 34.940, TUNZLA, ISTANBUL.TEL#+90(216)3929970-72, FAX#+90(216)3929969, E-MAIL: info@yonca-onuk.com</u> <u>GENERAL SPECIFICATION - SOURCE OF</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									NORTHA MPTONS HIRE NN29 7RL. TEL#+44 (0)1933 663100, FAX#+(0) 1933 665650&+ 44 1933 666 007. 2. M/S YONCA- ONUJ JV, TERSAN ELER CADDESI 50/3 34.940 TUZLA ISTAN		AVAILABILITY-1:M/S YONCA-ONUJ JV,TERSANELER CADDESI 50/3 34.940,TUNZLA,ISTANBUL. TEL#+90(216)3929970-72,FAX#+90 (216)3929969,E-MAIL:info@yonca-onuk.com	
8	SNM619 45	CPMU-05	413078521161 5 / CONDENSER AXIAL FAN MOTOR	6 TON AC AIR COOLED CWFSC- 8+CWCU-108 CHINA	3 / EACH/N UMBER	YWF6D- 600-S- 137/70-G- 1.47A 920	NA	PACIFIC FANS INDUSTRY CHINA CHAOYANG DISTRIC BEIJING	PACIFIC FANS INDUSTRY CHINA		<u>TECHNICAL SPECIFICATION - 6 TON AC OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: PACIFIC FANS INDUSTRY CHINA CHAO YANG DISTRICT BEIJING CHINAGENERAL SPECIFICATION - 6 TON AC OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: PACIFIC FANS INDUSTRY CHINA CHAO YANG DISTRICT BEIJING CHINA</u>	
9	DNJ6475 1	64D- 11631-22- 90	281576521244 4 / PISTON (STD)	150 AET OBM ENGINE	1 / EACH/N UMBER	150AET 07 (6G 47) 1024899	1024899 6G47	YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538- 37-1668 FAX 0081-538-37- 1954	YAMAHA MOTOR CO LTD		<u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>	
10	DPC566 54	PHL 765 / PHA 046	801079514041 5 / INTERTHANE 990 RAL 7000	MRTP 33 &MABS	20 / LITER	NO DATA AVAILAB LE		UK	INTERNA TIONAL PAINT LTD PO BOX 20980 ORIAL		<u>TECHNICAL SPECIFICATION - . GENERAL SPECIFICATION - .</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									HOUSE 16 CONNAUGHT PLACE LONDON W2 2ZB UK			
11	DPK56311	F ECO-DT 5W30	915079517186 2 / TITAN Supersyn F ECO-DT SAE 5W-30 packed in (1 Litre CAN)	LAND ROVER JEEP	500 / LITER			NAM: MINISTRY OF DEFENCE, DIRECTORATE OF STANDARDIZATION, STAN 1, ST1: ROOM 1138, KENTIGERN HOUSE, 65 BROWN S CTR: UNITED KINGDOM TEL: 0141 224 2531 FAX: 0141 224 2503	UK		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
12	DPC57949	QGU60W + QGA046	801079522265 3 / INTERTHANE 870 ACRYLIC POLYURETHANE FINISH DK GREY (Packing Comp A= 17.50 , Comp B= 2.50 Ltr)	EXTERNAL DECKS, DECK MOORINGS AND INTERNAL DECKS	100 / LITER	INTERNATIONAL PAINTS	NIL	International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, UK		<u>TECHNICAL SPECIFICATION</u> - Color : Wide range via the Chroma scan® system Gloss Level : Semi-Gloss Volume Solids: 56% ± 3% (depends on color) Typical Thickness: 3-5 mils (75-125 microns) dry equivalent to 5.4-8.9 mils (134-223 microns) wet Theoretical Coverage: 180 sq.ft/US gallon at 5 mils d.f.t and stated volume solids 4.50 m²/liter at 125 microns d.f.t and stated volume solids Practical Coverage: Allow appropriate loss factors Method of Application : Airless Spray, Air Spray, Brush, Roller (Technical Details included in Data Sheet and Picture) <u>GENERAL SPECIFICATION</u> - Color : Wide range via the Chroma scan® system Gloss Level : Semi-Gloss Volume Solids: 56% ± 3% (depends on color) Typical Thickness: 3-5 mils (75-125 microns) dry equivalent to 5.4-8.9 mils (134-223 microns) wet Theoretical Coverage: 180 sq.ft/US	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											gallon at 5 mils d.f.t and stated volume solids 4.50 m ² /liter at 125 microns d.f.t and stated volume solids Practical Coverage: Allow appropriate loss factors Method of Application : Airless Spray, Air Spray, Brush, Roller (Technical Details included in Data Sheet and Picture)	
13	SNM51624	2WB250-25	481078519585 1 / SOLENOID VALVE	FIRE MAIN SYSTEM	1 / EACH/NUMBER	2WB250-25	NIL	YUEQING RIGHTEIGHT PNEAMATIC CO LTD CHINA	CHINA		<p><u>TECHNICAL SPECIFICATION -</u> Valve Body Material: Brass Function: 2/2 Way Normally Closed Port Size: 1", DN25 Voltage: AC110V, AC220V, DC24V, DC12V Action Type: Semi Direct Operated Orifice Size: 25mm Fluid Temperature: -5°C - +80°C Diaphragm Material: NBR, Viton, EPDM Working Pressure: 0-7 Bar Medium: Water, Oil, Gas, Air SOLENOIED VALVE DIA 1 INCH , OPERATED BY 220 V AC SUPPLY INSTALLED IN FIREMAIN MAGAZINE SPRINKLING SYSTEM</p> <p><u>GENERAL SPECIFICATION -</u> Valve Body Material: Brass Function: 2/2 Way Normally Closed Port Size: 1", DN25 Voltage: AC110V, AC220V, DC24V, DC12V Action Type: Semi Direct Operated Orifice Size: 25mm Fluid Temperature: -5°C - +80°C Diaphragm Material: NBR, Viton, EPDM Working Pressure: 0-7 Bar Medium: Water, Oil, Gas, Air SOLENOIED VALVE DIA 1 INCH , OPERATED BY 220 V AC SUPPLY INSTALLED IN FIREMAIN MAGAZINE SPRINKLING SYSTEM</p>	
14	DNF45814	US/CHINA BRAND/ P-0003	603078516496 3 / PREMIERE / PTCL OPTICAL FIBRE 6-CORE CABLE	PSS (CCTV SYS)	1700 / METER			CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA. 100120	M/S CETC INTERNATIONAL CO LTD		<p><u>TECHNICAL SPECIFICATION -</u> DIAMETER 7.5MM Make: PREMIERE/PTCL cables</p> <p><u>GENERAL SPECIFICATION -</u> DIAMETER 7.5 MM Make: PREMIERE/PTCL cables</p>	
15	DNM64727	385720510	590599871629 1 / WATER	COOLING SYSTEM	1 / UNIT	SDG15PS	00151403045	S. M. JAFFER & CO. JAFFER HOUSE 17,	PERKINS		<p><u>TECHNICAL SPECIFICATION -</u> PART NO: 385720510 WATER</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TEMPERATURE SENSOR					TIMBER POND, KEAMARI (P. O. BOX No. 4488), KARACHI UAN: 0092-21-111-765-765 FAX: 0092-21-32851162 & 32850080 E-Mail: info@smjaffer.com			TEMPERATURE SENSOR <u>GENERAL SPECIFICATION</u> - PART NO: 385720510 WATER TEMPERATURE SENSOR	
16	DNJ65035	36622-98J00	1440765221885 / HARNESS ASSY, DUAL STATION MAIN	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		<u>TECHNICAL SPECIFICATION</u> - NIL <u>GENERAL SPECIFICATION</u> - NIL	
17	DPC57474	TUFF-BOND HANGER ADHESIVE	8040010098001 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLON			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 IDN: DUNS 001744697	MOORE GOODLOE E INC		<u>TECHNICAL SPECIFICATION</u> - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS <u>GENERAL SPECIFICATION</u> - Material RUBBER SYNTHETIC, FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS	
18	DPK59328	MIL-PRF-17331	9150013687075 / LUBRICATING OIL, STEAM TURBINE OIL, RADCOLUBE 17331 (2190 TEP) (Packing = 205 LTRS)	MAIN GEARBOX, CPP SYSTEM, HPACs AND LPACs	8 / DRUM	MILITARY SPECIFICATIONS		CARLETON LIFE SUPPORT SYSTEMS INC. 2734 HICKORY GROVE RD DAVENPORT IA USA 52804-1203 TEL: 563-383-6467 FAX: 563-383-6430 EMA: LPETERS@CARLETONLS.COM /WWW.CARLETONLS.COM	MILITARY SPECIFICATIONS		<u>TECHNICAL SPECIFICATION</u> - VISCOSITY 8.2cSt MIN AT 210 DEG F AND 82.0cSt MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEIT <u>GENERAL SPECIFICATION</u> - VISCOSITY 8.2 cSt MIN AT 210 DEG F AND 82.0cSt MINIMUM AT 100 DEG FAHRENHEIT AND 110.00cSt MAXIMUM AT 100 DEG FAHRENHEIT	
19	DNF64728	000-133-495	5920785209729 / FUSE LITHIUM BATTERY CR2450-F2 ST2	Furuno Echo Sounder FE-700 Japan	50 / EACH/NUMBER	N/A	2260-7923	FURUNO ELECTRIC CO. LTD 9-52 ASHIHARA-CHO, NISHINOMIYA, 662-8580, JAPAN Tele No. +81 798 65-2111 Fax: +81 798 65-4200	FURUNO ELECTRIC CO. LTD		<u>TECHNICAL SPECIFICATION</u> - AS PER CATALOGUE <u>GENERAL SPECIFICATION</u> - AS PER CATALOGUE	
20	DNF65039	DCC/HFBM/HW/114	7050705215673 / TOUCH INPUT DISPLAY (TID)	OPERATOR CONTROL DCC-2016 PAKISTAN	3 / EACH/NUMBER	NA	NA	Commercially Of The Shelf (COTS)/Local Market	COTS		<u>TECHNICAL SPECIFICATION</u> - INPUT DEVICE 10" installed in HF DF System <u>GENERAL SPECIFICATION</u> - INPUT DEVICE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											10" installed in HF DF System	
21	DPC56057	X00069385	6810725232428 / COOLANT CS 10/90 CORROSION INHIBITOR PREMIX (PACKING 200 OR 20 LITER)	All MTU Engines	160 / LITER	CS 10/90	Various	MTU Friedrichshafen GmbH, Friedrichshafen Germany Website: www.mtu-online.com	MTU Friedrichshafen GmbH		<p><u>TECHNICAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added quality water 10% Coolant and 90% Water Manufactured by MTU</u></p> <p><u>GENERAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added quality water 10% Coolant and 90% Water Manufactured by MTU</u></p>	
22	DPC47977		0473509423131 / PIGMENT AND OIL PASTE WHITE LEAD / KOLOR KUT WATER FINDING PASTE FOR PETROLEUM AND CHEMICAL		160 / EACH/NUMBER						<p><u>TECHNICAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm</u></p> <p><u>GENERAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm</u></p>	
23	DGE36635	BS 5120 (1975)	0413599238774 / HOSE RUBBER COLOUR BLACK INT DIA 0.375" LG 60FT NO OF PLIES3		125 / METER						<p><u>TECHNICAL SPECIFICATION - SIZE: DIA:3.2MM LENGTH PER UNIT/ELECTROD E:350 MM</u></p> <p><u>TECHNICAL SPECIFICATION: Ø: 3.2 MM SPEC: AWS A5.1 OF 2004 E TH-907A CHEMICAL</u></p> <p><u>COMPOSITION: C = 0.04 NI 1.70-1.90 SI = 0.10 TI 0.10-0.22 MN 1.20-1.40 MO = 0.05 S = 0.015 CR = 0.05 P = 0.015 NB = 0.02 V = 0.02 N = 80PMM MECHANICAL</u></p> <p><u>SPECIFICATION AND ACCEPTANCE CRITERIA: DESCRIPTION MECHANICAL SPECIFICATION TENSILE STRENGTH 390 (MPA) YIELD POWER (470-650) ELONGATION 20.0% PACKAGING 05 KG PER BAG. FINAL DELIVERY WITH ONE BATCH/LOT CLASSIFICATION SOCIETY APPROVAL OF ANY INTERNATIONAL CLASSIFICATION I.E. LR,BV,ABS,DNV.GL, C€,JIS,</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ISO-9001- 2015 SEE ATTACHED DOCUMENTS FOR DETAILS NOTE: SURFACE QUALITY OF WELDING ELECTRODE SHOULD CONFORM TO THE CONDITION OF GB/T 14957. AT THE FRONT OF WELDING ELECTRODE PACK, ANTI-RUST OIL SHOULD BE APPLIED TO PROTECT IT FROM RUST. GENERAL SPECIFICATION - SIZE: DIA:3.2MM LENGTH PER UNIT/ELECTRODE:350 MM TECHNICAL SPECIFICATION: Ø: 3.2 MM SPEC: AWS A5.1 OF 2004 E TH-907A CHEMICAL COMPOSITION: C = 0.04 NI 1.70-1.90 SI = 0.10 TI 0.10-0.22 MN 1.20-1.40 MO = 0.05 S = 0.015 CR = 0.05 P = 0.015 NB = 0.02 V = 0.02 N = 80PMM MECHANICAL SPECIFICATION AND ACCEPTANCE CRITERIA: DESCRIPTION MECHANICAL SPECIFICATION TENSILE STRENGTH 390 (MPA) YIELD POWER (470-650) ELONGATION 20.0% PACKAGING 05 KG PER BAG. FINAL DELIVERY WITH ONE BATCH/LOT CLASSIFICATION SOCIETY APPROVAL OF ANY INTERNATIONAL CLASSIFICATION I.E. LR,BV,ABS,DNV.GL, C€,JIS, ISO-9001- 2015 SEE ATTACHED DOCUMENTS FOR DETAILS NOTE: SURFACE QUALITY OF WELDING ELECTRODE SHOULD CONFORM TO THE CONDITION OF GB/T 14957. AT THE FRONT OF WELDING ELECTRODE PACK, ANTI-RUST OIL SHOULD BE APPLIED TO PROTECT IT FROM RUST.</p>	
24	DGE32157	202-GNFG	047659000775 8 / GLOVES SEAMLESS		30 / PAIR	202-GNFG					<p>TECHNICAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size:</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			DIPPED RUBBER I.R. SIZE 9								<p>AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity</p> <p><u>GENERAL SPECIFICATION - a.</u> Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who Involve / Deal with high voltage electricity</p>	
25	DPC58554		0473504730040 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)</u><u>GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											POINT: 788F (PACKING: 01 KG PACKET)	
26	DPK61302	DEFSTAN 01-5	0475502202348 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		400 / LITER						<u>TECHNICAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u> <u>GENERAL SPECIFICATION - sPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)</u>	
27	DGE65491	NO DATA AVAILAB L E	0461590006480 / PAINT ROLLER 7 INCH,C/W SHEEP SKIN COVER AND HANDLE STEEL FRAME, WOODEN HANDLE	BLST PAINT UNDER WATER HULL	215 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</u> <u>GENERAL SPECIFICATION - a. Item Name : Paint Roller 7" b. Roller Size : 7 inches c. Roller Cover : Cover with Polyamide d. Frame : Chrome Steel e. Handle : PVC/ Wooden Handle for maximum grip</u>	
28	DGE44803		0421599244635 / CHAIR- PEDESTAR		25 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
29	SPC58589	NO DATA AVAILAB L E	0442500010644 / THINNER FOR VARNISH (Packing 04 liter)		260 / LITER						<u>TECHNICAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY</u> <u>GENERAL SPECIFICATION - DEF STAN 80-38/2 195 1. FLASH POINT: 16°C 2. INGREDIENTS PROPERTIES BY VOLUME: - METHY ISO BUTYL KETONE: 32 ± 3% - ETHYLENE GLYCOL ACETATE: 7 ± 3% - ISO BUYYLE ALCOHAOL : 25 ± 3% OEM M/S FALAH TRADING AGENCY</u>	
30	SPC5858	BS 245 OF	044250442007		220 /						<u>TECHNICAL SPECIFICATION - BS</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	5	1976	0 / THINNER FOR PAINT		LITER						245 OF 1976 20 ltr packing gauge of drum 24 to 26 swg <u>GENERAL SPECIFICATION - BS 245 OF 1976</u> 20 ltr packing gauge of drum 24 to 26 swg	
31	SPC47958	NO DATA AVAILAB LE	044250442003 0 / DULAC HI-BUILD (Packing = 0.91 Liter)		91 / LITER	ICI					<u>TECHNICAL SPECIFICATION - LACQURE MAKE: ICI OEM</u> <u>GENERAL SPECIFICATION - LACQURE MAKE: ICI OEM ICI</u>	
32	DPC57644	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1200 / BOTTLE						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
33	DPC60364	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1146 / BOTTLE						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
34	DPC61495	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1600 / BOTTLE						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
35	DPC57930	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1300 / BOTTLE						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u> <u>GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL</u>	
36	DPC58897	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT		1274 / BOTTLE						<u>TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(Mospel/Tyfon OR EQUIVALENT)								REGISTERED LABELGENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
37	DPC59472	732RTV	042599225196 2 / SILICON RUBBER SILASTIC 732RTV (SEALING COMPOUND) WHITE 90ML TUBE (OEM DOW CORNING)	PROPELLER SEALING	142 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
38	DGB54058	HA-680	026859001239 6 / Weighing Machine B/Roo		2 / EACH/NUMBER	HA-680/HA-622					TECHNICAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPANGENERAL SPECIFICATION - 1. body weighing: 120 kg maximum weight ; 160 kg (sub- diviions of the weighing dial) 2. height measuring: 10-100 cm/27-74 inch height measuring range sub- division of graduation 3. size of platform (l x w); 370x270 mm 4. overall dimensions (l x w x h) ;910x340x290 mm 5 weight ; 10 kg MODEL NO HA622 WEIGHING MACHINE TANITA CORPORATION TOKYO JAPAN	
39	DGB65571	1473	024879129614 8 / SAFE-STL FIRE PROOF WITH COMB LOCK SZ.56	BODY 16 GAUGE,DOOR NOT LESS THAN3/8"THK-	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - A. BODY: 16 GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03GENERAL SPECIFICATION - A. BODY: 16	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1/2"X31 1/4 X 26"								GAUGE B. DOOR: NOT LESS THAN 3/8" THICK C. NO OF LEVERS: MINIMUM. 03	
40	DGE37219	0043A00	0245999233890 / Bowl Water Closet Colour White Single Piece	WC FITTED IN SAILOR,S BATH ROOM	4 / EACH/NUMBER	Annex/Master/Durr					<u>TECHNICAL SPECIFICATION - 1*</u> MAIN BODY : IN PORCELAIN MATERIAL & <u>GENERAL SPECIFICATION - 1*</u> MAIN BODY : IN PORCELAIN MATERIAL &	
41	DNF64744	CW1-18	0561795198751 / WIRE, WINDING COPPER ELECT COND DIA : 1.180MM O/ DIA : 1.308 MM	FOR WINDING.	66.14 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2 <u>GENERAL SPECIFICATION -</u> Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2	
42	DNF64243	CW1-18	0561795198751 / WIRE, WINDING COPPER ELECT COND DIA : 1.180MM O/ DIA : 1.308 MM	FOR WINDING.	60 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2 <u>GENERAL SPECIFICATION -</u> Standard Specs: BS 4665 Part 1 of 1971; DEFSTAN 61-12 of 2008 Issue 2	
43	DNF64479	BS EN 60317-8	0561795198769 / WIRE, WINDING COPPER ELECT COND DIA 1.320MM O/ADIA : 1.423 MM (CLASS-180)	WIRE WINDING,	152 / KILOGRAMME						<u>TECHNICAL SPECIFICATION -</u> Copper Purity %: 99% Acceptable tolerance limits: 0.05 mm Conductor Dia: 1.320 mm Overall Dia: 1.423 mm LOCAL SOURCE, NASIR & HAMZA ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI] <u>GENERAL SPECIFICATION -</u> Copper Purity %: 99% Acceptable tolerance limits: 0.05 mm Conductor Dia: 1.320 mm Overall Dia: 1.423 mm LOCAL SOURCE, NASIR & HAMZA ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI]	
44	DNF64141	BS EN 60317-8	0561705253569 / WIRE, WINDING COPPER		20 / KILOGRAMME	GHAZILE X					<u>TECHNICAL SPECIFICATION -</u> DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECT COND DIA: 0.710MM O/ DIA : 0.790 MM (CLASS 180)								SPECIFICATION - DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2	
45	DNF65014	PHILIPS / 0583-17069	058379412845 2 / FLOOD LED LIGHT 220V 50W SWB G3 COMPLETE ASSY DIA-12"		6 / EACH/NUMBER	PHILIPS BVPI50					TECHNICAL SPECIFICATION - FLOOD LED LIGHT 220V 50W SWB G3 BVPI50 COMPLETE ASSY DIA-12" OEM, PHILIPS PAKISTANGENERAL SPECIFICATION - FLOOD LED LIGHT 220V 50W SWB G3 BVPI50 COMPLETE ASSY DIA-12" OEM, PHILIPS PAKISTAN	
46	DNF65013	BS EN 60317-8	056179525360 9 / WIRE, WINDING COPPER ELECT COND DIA : 0.900MM O/ DIA : 1.017 MM (CLASS-175 -180c) Grade-3	MOTOR WINDING	30 / KILOGRAMME						TECHNICAL SPECIFICATION - COPPER PURITY %: 99% ACCEPTABLE TOLERANCE LIMITS: 0.05 MM LOCAL SOURCE, NASIR & HAMZA ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI] DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-3GENERAL SPECIFICATION - COPPER PURITY %: 99% ACCEPTABLE TOLERANCE LIMITS: 0.05 MM LOCAL SOURCE, NASIR & HAMZA ENTERPRISES ADDRESS: [OFFICE # D/273 NAVY HOUSING SCHEME ZAMZAMA CLIFTON 9 KARACHI] DEFSTAN 61-12 ISSUE-2 OF 2008 (PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-3	
47	DNH65020	NO DATA AVAILABLE	343170504874 8 / WELDING RECTIFIER, W/CART, WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK	USER WELDING SHOP DOCKYARD	1 / SET						TECHNICAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KITGENERAL SPECIFICATION - WELDING RECTIFIER W/CART I/P 380/440V 3P 50/60HZ O/P600A WITH500A30/50M STICK WELDING ACESSARIES KIT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			WELDING KIT									
48	DGP619 98		361070504530 3 / POSITIVE PLATE ROLAND OFFSET size: 925X740X0. 3MM(BRND FUJI)		200 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> SIZE: 925X740X0.3MM(BRND FUJI) <u>GENERAL SPECIFICATION - SIZE:</u> 925X740X0.3MM(BRND FUJI)	
49	DGP652 76	CP1515N/ HP COLOR LASER 150A PRINTER 4ZB94A	361070506112 0 / HP COLOR LASER JET CP1515N PRINTER	SELF/ANY COMPUTER OR LAPTOP	2 / EACH/N UMBER	CP1515N/ HP COLOR LASER 150A PRINTER 4ZB94A					<u>TECHNICAL SPECIFICATION -</u> SPECIFICATION: (A)TYPE:COLOR. (B)PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-. <u>GENERAL SPECIFICATION -</u> SPECIFICATION: (A)TYPE:COLOR. (B)PRINT TECHNOLOGY:COLOR LASER. (C)PROCESSOR SPEED: 450 MHZ. (D)STANDARD RAM:96 MB. (E)MAX RAM:352 MB. (F) RESOLUTION:600X600 dpi. (G) PRINT SPEED COLOR:8ppm. (H) PRINT SPEED B/W:12 PPM. PRICE OFLASER JET CP1515 RS:46,490/-.	
50	DGP651 92	G2102560 EU	361070509130 4 / SHREDDING MACHINE, GBC DUO (SHERED MASTER)		3 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION -</u> TECHNICAL SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIIIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs. <u>GENERAL SPECIFICATION -</u> TECHNICAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECS/FEATURES/BENEFITS: 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M.MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.	
51	DGE65494	ASTIM D374	5970705047303 / nomex paper-12		42 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
52	DGD65536	MS-3443-A/DW-136G	7310705121904 / MICROWAVE OVEN 34/36 LTR 220/110VAC 50/60HZ 1PHASE	MICROWAVE OVEN 34LTR	1 / EACH/NUMBER	DW-136G					<u>TECHNICAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE)</u> <u>GENERAL SPECIFICATION - brand name: (i.e.WESTPOINT/ LG /SHARP / TOSHIBA / DAWLANCE)</u>	
53	DGD65535	LG-MP-9482 SR	7310735118939 / MICROWAVE OVEN-LG SHARP WAVES/DAWLANCE & TOSHIBA	MICROWAVE OVEN LG	1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - capacity: 36 LITTERs</u> <u>GENERAL SPECIFICATION - capacity: 36 LITTERs</u>	
54	DNQ62663	NIL	8415705102557 / SURCOAT YELLOW WITH WHITE STRAP (COTTON/NO MAX MATERIAL)	FIRE FIGHTING, BSO TAILORS, PN DOCKYARD	7 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - UK/SC/4765 ISSUE 09</u> <u>GENERAL SPECIFICATION - UK/SC/4765 ISSUE 09</u>	
55	SPC56286	BUTANOX M-60	6810731000994 / METHYLENE KETONE PER OXIDE		50 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SPECIFICATION: APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4 <u>GENERAL SPECIFICATION - SPECIFICATION:</u> APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4	
56	DPC57394	BUTANOX M-60	6810731000994 / METHAILETHYLE KETONE PEROXIDE		160 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - SPECIFICATION:</u> APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4 <u>GENERAL SPECIFICATION - SPECIFICATION:</u> APPEARANCE: CLEAR AND COLOURLESS LIQUID TOTAL ACTIVE OXYGEN: 9.8-10% DENSITY: 20C 1.170g/cm3 VISCOSITY 20 C: 25 mPa.S CAS NO 1338-23-4	
57	DPC56950	TS10268/ZOK 27	6850992254020 / COMPRESSOR CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSOR G.T.E. TYPE 21	150 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
58	DGD65538	NO DATA AVAILABLE	7320705012426 / MACHINE ATTA KNEADING 100 TO 120KG CAPACITY 440V 50HZ 3PHS 5AMP		1 / EACH/NUMBER	GSA/23/A KM					<u>TECHNICAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)</u> <u>GENERAL SPECIFICATION - Make/Model/Brand/GSA/23/AKM 100-120 kg Capacity, 440 Volts Material of Tub Stainless Steel (Food Grade)</u>	
59	DGD65537	NO DATA AVAILABLE	7320705013216 / POTATOES PEELER MACHINE 15 to 20 kg CAPACITY		1 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item commercially available in local Market</u> <u>GENERAL SPECIFICATION - specs: 15 to 20 kg Capacity s/steel 2 HP Motor Item</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			s/steel								commercially available in local Market	
60	DGP65591	NO DATA AVAILAB LE	005050000009 7 / PAPER DUPLICATING		400 / REAM	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL</u> <u>SPECIFICATION -</u> Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON	
61	DGD48778	NO DATA AVAILAB LE	003454600044 0 / JUGS MILK CHINA 1 PINT		19 / EACH/N UMBER	CERA-E- NOOR					<u>TECHNICAL SPECIFICATION -</u> material ; porcelain capacity ; 1 pint golden crested with pn logo <u>GENERAL SPECIFICATION -</u> material ; porcelain capacity ; 1 pint golden crested with pn logo	
62	DNF61994	MD6. 200.100.B (12 D3-M)	613577511875 4 / MARINE BATTERIES 12 V 200AH	MARINE STARTER	12 / EACH/N UMBER	MUTLU MD6. 200.100.B					<u>TECHNICAL SPECIFICATION -</u> S&A, DEFENCE TRADERS TOOBA APARTMENT ,KARACHI CEL.:0300- 2811770 OEM,MUTLU TURKEY, <u>GENERAL SPECIFICATION -</u> S&A, DEFENCE TRADERS TOOBA APARTMENT ,KARACHI CEL.:0300- 2811770 OEM,MUTLU TURKEY,	
63	DGT58049	NO DATA AVAILAB LE	010050000004 3 / Timber Gurjan Grade-I (Red pine) SLEEPER seasoned (swan)		100 / CUBIC FOOT	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION -</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%) <u>GENERAL SPECIFICATION</u> <u>-</u> SIZE: LENGTH= 12 FEET TO 23 FEET, WIDTH= 08 INCH TO 12 INCH, THICKNESS= 05 INCH TO 10 INCH MOISTURE CONTENT: 30% (±10%)	
64	SPC58340	BS 627 (F- 8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOU	50 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> NO DATA AVAILAB <u>GENERAL</u> <u>SPECIFICATION -</u> NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
65	DGD55629	B-650	7330705269675 / VEGETABLE CUTTER		2 / EACH/NUMBER	b-650					<u>TECHNICAL SPECIFICATION</u> - stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade <u>GENERAL SPECIFICATION</u> - stainless steel body, motor: 1 h/p, bottom frame: 1/1 angle 3mm thickness, high efficient blade	
66	DNF64730	AALR6	6135735281524 / AA2 ENERGIZER LITHIUM BATTERY 1.5V RECHARGEABLE SIZE H: 145mm		250 / PAIR	ENERGIZER LITHIUM					<u>TECHNICAL SPECIFICATION</u> - (2 PACK) <u>GENERAL SPECIFICATION</u> - (2 PACK)	
67	DSM58069	056169A1	6105TY6715342 / NEW MOTOR PROTECTOR 2ACE-POWER SUPPLY		1 / EACH/NUMBER	NO DATA AVAILABLE					<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE	
68	DNF64991	tm2a r18lt	5963745268094 / analog input module modicon plc 100 ton ac plant		2 / EACH/NUMBER	TM2A R18LT					<u>TECHNICAL SPECIFICATION</u> - 12 bits 8 channel temperature probe <u>GENERAL SPECIFICATION</u> - 12 bits 8 channel temperature probe	
69	DSB50369	CUB5VB00	6625016039841 / Voltmeter		2 / EACH/NUMBER	N/A					<u>TECHNICAL SPECIFICATION</u> - N/A <u>GENERAL SPECIFICATION</u> - N/A	
70	DNM64834	4573219	5905785291615 / MAGNETIC CONTACTOR 32A		1 / EACH/NUMBER	NXC-32					<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
71	DCD60066		8455703138362 / ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE		1500 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE <u>GENERAL SPECIFICATION</u> - ANCHOR BRASS FOR CAP BARRET FOR PAK MARINE	
72	DCD60412		8455703901745 / BADGE ARM MEDICAL		500 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			(CHEM) RED EMBROIDERY									
73	DCD45173		8455703901853 / BADGE ARM YARD ab- I MECHANICAL (M) VELCRO BASE WITH PLAIN GREY BASE CLOTH AND BLACK EMBROIDERY		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
74	DPC56915	QGZ684/QGA046	8010171296548 / INTERTHANE 870 LIGHT GREY		200 / LITER	INTERTHANE870 LIGHT GRAY					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
75	DCD49592		8455703901845 / BADGE ARM BLUE AB- I YARD ELECTRONIC (E)		500 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
76	DGD55633	JE-01	7320705269664 / STAINLESS STEEL JUICE EXTRACTOR		2 / EACH/NUMBER	UDZZ-A2000					TECHNICAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201 GENERAL SPECIFICATION - MOTOR: 550W, WEIGHT:14KG, CAPACITY: 600ML/TIMES, ROTATING SPEED 2800RPM, DIMENSION: 430X350X450MM Steel Grade-201	
77	DCC19618		8440501890013 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40"		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40" GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 40"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
78	DNF56911	CPU RT-700	5998755270937 / cpu RT-700 for suface grinding machine		1 / EACH/NUMBER	rt-700					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
79	SNM61055	1004075	3110725264612 / Rolling Bearing		2 / EACH/NUMBER	SRP 210 FP					<u>TECHNICAL SPECIFICATION - Vessel: Classification society : BV Code word:DAMEN 512410 Vessel type: Azimuth Stern Driven Tug (ASD) Propulsion unit: Input power: 600 kW Input speed: 1800 rpm Gear ratio: i = 3.967:1 Propeller arm length (PAL): 2000 mm Weight (per propulsion unit): approx. 4,809 t Oil quantity: approx. 432 l Housing material: cast iron</u> <u>GENERAL SPECIFICATION - Vessel: Classification society : BV Code word:DAMEN 512410 Vessel type: Azimuth Stern Driven Tug (ASD) Propulsion unit: Input power: 600 kW Input speed: 1800 rpm Gear ratio: i = 3.967:1 Propeller arm length (PAL): 2000 mm Weight (per propulsion unit): approx. 4,809 t Oil quantity: approx. 432 l Housing material: cast iron</u>	
80	DN050092	A20112010322006	4620FP1050051 / Reverse osmosis membrane		14 / EACH/NUMBER	SW30HRE-4040					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
81	SPC58308	11528	7930222582489 / DRY SAND 2 MM TO 2.6 MM	RO PLANT F-22P SHIP SWRO-1020PT3	1500 / KILOGRAMME	LOCAL		KNICKBERG 1G, D-21077 HAMBURGCONTACT NO 040/7038577-0FAX NO 040/7038577-155INFO@ROCHEM. DEFAX NO 040/7038577-155INFO@ROCHEM.DE3	ROCHEM RO-WASSER BEHANDLUNG GMBH, GERMANY		<u>TECHNICAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUST</u> <u>GENERAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUST</u>	
82	DNM61393	060759	4330715185280 / FLANGED TYPE OIL-REFRIGERANT SEPARATOR	MAIN AC PLANT(STUS)	1 / EACH/NUMBER	A F 58889		ALCO CONTROLS P O BOX 1270011911 ADIE ROAD St LOUIS USA Ph(314)569-4500 FAX (314)569-4593	ALCO CONTROLS		<u>TECHNICAL SPECIFICATION - DOUBLE CONECTION WITH SOLID COPPER</u> <u>GENERAL SPECIFICATION - DOUBLE CONECTION WITH SOLID COPPER</u>	
83	SNM515	0005109	512072513008	CLUTCH	10 /			GR	M/S		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	76		6 / SOCKET HEAD SCREW DIN 912 M12X40-8.8		EACH/NUMBER				SCHOTT EL GERMANY HEAD QUARTER SCHOTT EL GMBH & CO KG D-56523 SPAY (RHEIN)		ZINC PLATED • DIN 912/ ISO 4762 • Fully Threaded • Class 8.8 • Thread (d) M12 x 1.75 • Length (L) 40 mm • Wrench Size (s) 10 mm • Head Diameter (dk) max. 18 mm • Head Height (m) max. 12 mm • Class 8.8 • Material Steel • Wrench size H 1 0 (Hex) <u>GENERAL SPECIFICATION -</u> • ZINC PLATED • DIN 912/ ISO 4762 • Fully Threaded • Class 8.8 • Thread (d) M12 x 1.75 • Length (L) 40 mm • Wrench Size (s) 10 mm • Head Diameter (dk) max. 18 mm • Head Height (m) max. 12 mm • Class 8.8 • Material Steel • Wrench size H 1 0 (Hex)	
84	DPC650 45	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 ft2/lb)	DECK COVERING FOR CONCRETE SURFACE	20 / BAG			OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501.	ORIGINAL COLOR CHIPS,A DIVISION		<u>TECHNICAL SPECIFICATION -</u> OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS. <u>GENERAL SPECIFICATION -</u> OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS;RESINOUS FLOORING SYS.	
85	DPC488 96	SIKAFLEX -290	803079516762 1 / SIKA-FLEX 290 DC WOODEN DECK CAULKING 300ML OR 600ML CARTDG	PRIMER-290DC	24 / EACH/NUMBER			SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	SIKA LIMITED		<u>TECHNICAL SPECIFICATION -</u> ? 1-component formulation ? Non-corrosive ? Sandable ? UV- and weather- resistant ? Water (sea & fresh) resistant SIKA LIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129 <u>GENERAL SPECIFICATION -</u> ? 1-component	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											formulation ? Non-corrosive ? Sandable ? UV- and weather-resistant ? Water (sea & fresh) resistant SIKALIMITED WELWYN GARDEN CITY, HERTS AL 7 IBQ UK TELL:01707 394444, FAX: 01707 329129	
86	DNM61799	3393042/4334440	2930715177064 / IMPELLER	MAIN ENGINE CUMMINS KTA50M2	2 / EACH/NUMBER			CUMMINS Ins SOUTH CAROLINA USA.	CUMMINS USA		<u>TECHNICAL SPECIFICATION</u> - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL. <u>GENERAL SPECIFICATION</u> - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL.	
87	DNM61317	BRA10312H	2530715140377 / AIR COMPRESSOR 10HP 380V, 3PHASE,MAX. 175PSI	AIR COMPRESSOR	1 / EACH/NUMBER	FTK100300		US	SNAP ON LOGISTICS COMPANY CUSTOMER WARRANTY INFORMATION CENTER KENOSHA WISCONSIN 53141-1410.262-656-5200		<u>TECHNICAL SPECIFICATION</u> - a. OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175 <u>GENERAL SPECIFICATION</u> - a. OEM & Make: Fountain b. Model: FTK100300 b. Origin: Taiwan 30AMP,460V,MAG STARTER,HOUR METER AUTO DRAIN,AIR DELIVERY SCFM@PS 36.00175	
88	SNM40196	3584168	4720171237895 / EXHAUST HOSE	Volvo Penta Main Engine D6-370 AB (CNS BARGE)	3 / EACH/NUMBER	D-6835	2006032441, 2006032411	AB VOLVO PENTA, GOTEORG, SWEDEN	AB VOLVO PENTA		<u>TECHNICAL SPECIFICATION</u> - REQUIRED FOR VOLVO MAIN ENGINE D-6901 <u>GENERAL SPECIFICATION</u> - REQUIRED FOR VOLVO MAIN ENGINE D-6901	
89	DGE50471	ASTM D 6413	7210505155171 / FIRE RETARDANT	MATRESSES FOR BED	42 / EACH/NUMBER			LOCAL ADDRESS:AL-KHAIR HOUSE-43-T,AL-KHAIR CHOWK,AL-KHAIR	AL-KHAIR HOUSE-		<u>TECHNICAL SPECIFICATION</u> - MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SPRING MATRESS (L6.5"XW2'XH6)					ROAD GULBERG II, LAHORE-54660 PAKISTAN TEL: 042-5716580-86 FAX: 042-5716588,5753719.	43-T		SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL) <u>GENERAL SPECIFICATION -</u> MATERIAL SPRING: IMPORTED STEEL WIRE(BONNEL/HELICAL) SPRING STRENGTH: 1500-1800N/MM2 COVERING FABRIC: FIRE RETARDANT FOAM: GOOD QUALITY FOAM FELT SHEET (NAMDA): GOOD QUALITY FELT STEEL INTERNAL FABRIC: IMPORTED NON WOVEN FABRIC JOINTING CLIP & BRING: IMPORTED GOOD QUALITY COLOR; AS PER APPROVED BY PAKISTAN NAVY (SAMPLE COLOUR & SHADES TO BE PROVIDED FOR APPROVAL)	
90	SNM62485	048500	2930715150440 / IMPELLER KIT	WESTERBEKE GENERATOR 5.7 EDT 50HZ	4 / EACH/NUMBER			OEM: WESTERBEKE CORP 150 JOHN HANCOCK RD TAUNTON MA UNITED STATES 02780 508-823-7677 508-884-9688 DUNS 001767706 SALES@WESTERBEKE.COM HTTP://WWW.WESTERBEKE	WESTERBEKE CORP.		<u>TECHNICAL SPECIFICATION -</u> WESTERBEKE 048500 IMPELLER KIT WITH A COVER O-RING, IMPELLER DRIVE SCREW AND A COUPLE OF SPARE COVER SCREWS, 50.8MM, DIAMETER AND 22MM WIDE. FITS A 12MM SLOTTED SHAFT. <u>GENERAL SPECIFICATION - WESTERBEKE</u> 048500 IMPELLER KIT WITH A COVER O-RING, IMPELLER DRIVE SCREW AND A COUPLE OF SPARE COVER SCREWS, 50.8MM, DIAMETER AND 22MM WIDE. FITS A 12MM SLOTTED SHAFT.	
91	DPC592	FG-K2-	663079513257	LUB OIL	6 /	NO DATA		UK	UK		<u>TECHNICAL SPECIFICATION - -</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
	87	404-KW	6 / WATER / INSOLUBLES / TBN NSN 6630-14-5300825	TESTING KIT KITTIWAKE	EACH/N UMBER	AVAILAB LE					<u>GENERAL SPECIFICATION - -</u>	
92	DPK60079	R 141b	6810715225084 / OIL FLUSHING AGENT R 141B	MAIN AC	28 / KILOGR AMME	R 141b	NA	COMSTAR INTERNATIONAL INC 20-45 128TH STREET COLLEGE POINT, NY 11356 +1 (800) 328-0142 USA www.comstarproducts.com	COMSTAR INTERNATIONAL INC		<u>TECHNICAL SPECIFICATION -</u> Transport package: Disposable cylinder RS-141b oil flushing agent <u>GENERAL SPECIFICATION -</u> Transport package: Disposable cylinder RS-141b oil flushing agent	
93	SNM17741	MK 9053N	4945725211411 / BRAKE CONTROLLER CURRENT RELAY (500MA)	DOCK LIFT SYSTEM MK 9053-50-500mA GERMANY	2 / EACH/N UMBER	MK 9053N	NA	E.DOLD U.SOHNE KG D-78120 FURTWANGEN	GERMANY		<u>TECHNICAL SPECIFICATION -</u> CURRENT RELAY GIVE INFORMATION TO SERVO COTROLLER FOR BRAKE RELEASING. <u>GENERAL SPECIFICATION -</u> CURRENT RELAY GIVE INFORMATION TO SERVO COTROLLER FOR BRAKE RELEASING.	
94	DNS47937	167 013	2815735185885 / PUSH ROD	WARTSILA MAIN ENGINE 9L20C3 FINLAND	18 / EACH/N UMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243, PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantia 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tix 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		<u>TECHNICAL SPECIFICATION -</u> TPI <u>GENERAL SPECIFICATION -</u> TPI	
95	DPC58345	QGU60W + QGA046	8010795222653 / INTERTHANE 870 ACRYLIC POLYURETHANE FINISH DK GREY (Packing Comp A= 17.50 , Comp B= 2.50 Ltr)	EXTERNAL DECKS, DECK MOORINGS AND INTERNAL DECKS	100 / LITER	INTERNATIONAL PAINTS	NIL	International Paint Pvt Ltd, STONEYGATE LANE, FELLING, GATESHEAD, UK. Ph:0191 4696111	International Paint Pvt Ltd, UK		<u>TECHNICAL SPECIFICATION -</u> Color : Wide range via the Chroma scan® system Gloss Level : Semi-Gloss Volume Solids: 56% ± 3% (depends on color) Typical Thickness: 3-5 mils (75-125 microns) dry equivalent to 5.4-8.9 mils (134-223 microns) wet Theoretical Coverage: 180 sq.ft/US gallon at 5 mils d.f.t and stated volume solids	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											4.50 m ² /liter at 125 microns d.f.t and stated volume solids Practical Coverage: Allow appropriate loss factors Method of Application : Airless Spray, Air Spray, Brush, Roller (Technical Details included in Data Sheet and Picture) <u>GENERAL SPECIFICATION</u> - Color : Wide range via the Chroma scan® system Gloss Level : Semi-Gloss Volume Solids: 56% ± 3% (depends on color) Typical Thickness: 3-5 mils (75-125 microns) dry equivalent to 5.4-8.9 mils (134-223 microns) wet Theoretical Coverage: 180 sq.ft/US gallon at 5 mils d.f.t and stated volume solids 4.50 m ² /liter at 125 microns d.f.t and stated volume solids Practical Coverage: Allow appropriate loss factors Method of Application : Airless Spray, Air Spray, Brush, Roller (Technical Details included in Data Sheet and Picture)	
96	DNS56418	3CA80-5.0-S	4820775188083 / CHECK VALUE	WARTSILA STERN THRUSTER PROP CS250-S/WO-K HOLLAND	1 / EACH/NUMBER	WART-LCT-CS250-S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion.service@wartsila.com http : //www.wartsila.com	Wartsila Propulsion Netherlands B.V.		<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
97	DPC57226	PILOT-II	8010795171839 / MAMMUT PRIMER WHITE	Tall ship	40 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flixborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN		<u>TECHNICAL SPECIFICATION</u> - undercoat primer white <u>GENERAL SPECIFICATION</u> - undercoat primer white	
98	DGP54120	HP A3 LaserJet CP5225dn	7435705137718 / PRINTER COLOUR HP LASER JET CP-1215 /HP	COMPUTER	1 / EACH/NUMBER	HP A3 LaserJet CP5225dn		PK	PAKISTAN		<u>TECHNICAL SPECIFICATION</u> - - <u>GENERAL SPECIFICATION</u> - -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CP 1518 AS PER APPROVED SPECIFICATION									
99	DGP57826	12U PDU	599570517796 6 / 19 INCH WALL MOUNT RACK 12U	CNA LAN NETWORK	1 / EACH/NUMBER				TOTEN	TOTEN	<p><u>TECHNICAL SPECIFICATION - 19 INCH WALL MOUNT RACK 12U WIDTH 600 MM, DEPTH 600MM, DOUBLE SECTION, GREY, GLAZED (FRONT GLASS DOOR , BACK WALL FITTED SWG16, SWG 18 OF 4 WAY BRITISH FLAT PIN SOCKET M/S INBOX TECHNOLOGIES PVT LTD KARACHIGENERAL</u></p> <p><u>SPECIFICATION - 19 INCH WALL MOUNT RACK 12U WIDTH 600 MM, DEPTH 600MM, DOUBLE SECTION, GREY, GLAZED (FRONT GLASS DOOR , BACK WALL FITTED SWG16, SWG 18 OF 4 WAY BRITISH FLAT PIN SOCKET M/S INBOX TECHNOLOGIES PVT LTD KARACHI</u></p>	
100	DPC63604	LAZ684-Light Grey	801079514525 9 / PAINT INTERSHEEN 579 LIGHT GREY (Packing = 20Ltrs)	HULL PRESERVATION OF F-22P FRIGATES	40 / LITER	NO DATA AVAILABLE			UK	M/S INTERNATIONAL PAINT LTD P O BOX 20980 ORIAL HOUSE 16 CONNAUGHT PLACE LONDON W2 2ZB UK	<p><u>TECHNICAL SPECIFICATION - WAR PAINT ISSUE 37</u></p> <p><u>GENERAL SPECIFICATION - WAR PAINT ISSUE 37</u></p>	
101	SNM56578	10000-46312	291579517530 9 / LIFT PUMP KIT	45KVA PERKIN	1 / EACH/NUMBER		45KVA PERKIN	CATTER PILLER UK	UK		<p><u>TECHNICAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX. RX1 GUARANTEED 144-148 MHZ</u></p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 Ω) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLE ICOM'S BATTERY PACK ONLY CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK) GENERAL SPECIFICATION - FREQUENCY RANGE USA: 144-148 MHZ (TX). 136.174 HHZ (RX) GENERAL (LM): 136-174 MHZ. TX. RX1 GUARANTEED 144-148 MHZ RANGE ONLY OPERATING TEMP RANGE: -10 C +60 C +14F TO -140F FREQUENCY STABILITY: ±10 PPM (-10 C TO +60 C) ANTENNA CONNECTOR: BNC (50 Ω) POWER SUPPLY REQUIREMENT: 72 V DC (6 10 3 V DC ACCEPTABLE ICOM'S BATTERY PACK ONLY CURRENT DRAIN (AT 7.2 V DC) TRANSMIT AT 5.5W LESS THAN 2.0 A AT 0.5W LESS THAN 0.8 A RECEIVE AT MAX AF LESS THAN 250MA STAND BY LESS THAN 70MA POWER SAVE LESS THAN 20MA NO OF MEMORY CHANNELS: 107:INC 1 CALL AND 6 PROGRAMMED SCAN EDGES</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TUNING STEPS: 5. 10. 12.5. 15. 20. 25. 30 AND 50 KHZ DIMENSIONS: 54(W). 132(H).35(D) MM (PROJECTION NOT INCLUDED): 350G:12.3OZ(WITH BP 222) 190G: 6.7 OZ(WITHOUT BATTERY PACK)	
102	DPC60832		047350942313 1 / PIGMENT AND OIL PASTE WHITE LEAD / KOLOR KUT WATER FINDING PASTE FOR PETROLEUM AND CHEMICAL		150 / EACH/NUMBER						TECHNICAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm GENERAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm	
103	SPC51403		047350473014 6 / ZINC OXIDE WHITE	FWT TAKE OFF DR	100 / KILOGRAMME						TECHNICAL SPECIFICATION - DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX503R GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES : THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1%	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) IGNITED BASIS 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D407S CADMIUM (CD)* 0.002MAX 0.0003 ASTM 0407S IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER(CU) 0.001MAX 0.0001 ASTMND4075O LOSS AT 110°C (MOISTURE) 0.25 MAX 0.1S ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2,500 LB NET WT PALLET, OR 2.000 LB FIBC. (PACKING 25 KG BAG)GENERAL SPECIFICATION - DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLEIN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX503R GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES : THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETTED FORM (GRADE 103P),</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D407S CADMIUM (CD)* 0.002MAX 0.0003 ASTM 0407S IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER(CU) 0.001MAX 0.0001 ASTMND4075O LOSS AT 110°C (MOISTURE) 0.25 MAX 0.1S ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2,500 LB NET WT PALLET, OR 2.000 LB FIBC. (PACKING 25 KG BAG)	
104	DPC618 26		047350473004 0 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
105	DPK5852 8	DEFSTAN 01-5	047550220234 8 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		320 / LITER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17) <u>GENERAL SPECIFICATION -</u> SPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)	
106	DPK6151 9	DEFSTAN 01-5	047550220234 8 / BRAKE FLUID DOT-4		380 / LITER						<u>TECHNICAL SPECIFICATION -</u> SPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)								GENERAL SPECIFICATION - SPECIFICATIONS: SAE J1704 Rev Sep 2008 (DEFSTAN 01-5/17)	
107	DPC623 75		044370505489 6 / GAS HELIUM 99.995% PURE (CYLINDER 9.40 CUBIC M)		37.6 / CUBIC METER						TECHNICAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM GENERAL SPECIFICATION - HE 405 4.5 99.995 % 02 5 PPM H20 5PPM	
108	DPC576 27	king MOSPEL	044250442011 9 / MOSQUITO REPELLANT (Mospel/Tyfon OR EQUIVALENT)		1500 / BOTTLE						TECHNICAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL GENERAL SPECIFICATION - DEET (DIETHYL TOLUAMIDE) 20%. 45 MI PLASTIC PACKING WITH REGISTERED LABEL	
109	DGB625 19		027670910593 7 / SHOVEL HAND ROUND MOUTH DIMENSIONS 10-1/2X12-1/2" LG OF H28"		61 / EACH/N UMBER						TECHNICAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg. GENERAL SPECIFICATION - a. Shovel round point with Y handle. b. Total Length: Approx 01 x Mtr. c. No excess of metal, no dents, no cracks d. Blade weight approx. 2.5 Kg.	
110	DGB344 10	SKF N 312	026979950209 1 / BEARING PARALLEL ROLLER SKF N 312 060X130X31M M		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DGE650 37	bp310	209070050000 1 / CHAIR TUBULAR WHITE PLASTIC SEAT		125 / EACH/N UMBER	bp310					TECHNICAL SPECIFICATION - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand" GENERAL SPECIFICATION - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
112	DGE63460	bp310	209070050000 1 / CHAIR TUBULAR WHITE PLASTIC SEAT		200 / EACH/ NUMBER	bp310					<u>TECHNICAL SPECIFICATION</u> - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand" <u>GENERAL SPECIFICATION</u> - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"	
113	DPK50937	DEFSTAN 1-5 (XG-460)	047450910052 4 / GREASE NAVAL GRAPHITE XG-460 3 KG PACK	XG-460	270 / KILOGR AMME						<u>TECHNICAL SPECIFICATION</u> - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C <u>GENERAL SPECIFICATION</u> - <u>TECHNICAL DATA</u> (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C	
114	DNQ47867	692170650	304072509152 4 / TOP HEAD DRIVE SHAFT	DOCK BILGE PUMP GERMANY	4 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 2680 mm <u>GENERAL SPECIFICATION</u> - Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 2680 mm	
115	DNQ47866	ITSHF405 6-SEW / 647100209	304072509405 6 / INTERMEDIAT E DRIVE	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	4 / EACH/ NUMBER						<u>TECHNICAL SPECIFICATION</u> - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 3100 mm <u>TECHNICAL DATA</u> , Drawing	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			SHAFT								No. D003 MARTHETIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar <u>GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 3100 mm\ TECHNICAL DATA , Drawing No. D003 MARTHETIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar</u>	
116	DNQ46495	ITSHFD4-SEW / 692170658	3040725094058 / INTERMEDIATE DRIVE SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MARTHETIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar</u> <u>GENERAL SPECIFICATION - Material: High Carbon Steel C35K Outer Dia: 100 mm Length: 2987 mm Material = C35K (High Carbon Steel) Shaft size = 2987 mm Outer Dia = 100 mm Model: ZVZ 400/300 TECHNICAL DATA , Drawing No. D004 MARTHETIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar</u>	
117	DNM58737	1R0750	2910014449487 / FILTER AS FLUID	CATERPILLER D/ENGINE USA	3 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - OEM&MAKE: CATERPILLAR</u> <u>GENERAL SPECIFICATION - OEM&MAKE: CATERPILLAR</u>	
118	DNQ46494	PSDF4-SEW / 647100205	4320725094081 / PUMP SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	2 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - TECHNICAL DATA , Drawing No. D008 MARTHETIAL/ GRADE, Stainless Steel 304 PRODUCTION METHOD, Drawn from solid bar</u> <u>GENERAL SPECIFICATION - TECHNICAL DATA , Drawing No. D008 MARTHETIAL/ GRADE, Stainless Steel 304 PRODUCTION METHOD, Drawn from solid bar</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
119	DNQ46496	1907-ISFT-FD4- SEW / 647100208	432072509406 2 / INTERMEDIATE DRIVE SHAFT	DOCK BILGE PP.ZVZ 400/300 FD-IV OEM:	4 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 1907 mm <u>TECHNICAL DATA , Drawing No. D005</u> MATERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar <u>GENERAL SPECIFICATION -</u> Material: High Carbon Steel C35K Outer Dia: 80 mm Length: 1907 mm <u>TECHNICAL DATA , Drawing No. D005</u> MATERIAL/ GRADE, 4140 or equivalent PRODUCTION METHOD, Drawn from solid bar	
120	DNH65778	NO DATA AVAILABLE	413070504652 9 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSUBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY	SELF	1 / EACH/NUMBER	GREE/PEL, MITSUBUSHI/ DAKEN/ GENERAL, LG,					<u>TECHNICAL SPECIFICATION -</u> null <u>GENERAL SPECIFICATION -</u> null	
121	SNM63012	8N 8221	311001184802 9 / BEARING CONNECTING ROD O.25	CATERPILLER (USA)	8 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR	
122	SNM45582	9M4849	533000847435 1 / SEAL	3304PC, CATERPILLER D/GEN.USA	22 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR <u>GENERAL SPECIFICATION -</u> OEM & MAKE: CATERPILLAR	
123	DPC58552	NO DATA AVAILABLE	684070505711 1 / INSECTICIDE K-OTHRINE ec 15 (01 LITER PACKING) (OEM M/S Bayer Environmental	TO CONTROL INSECT PASTS COCKROACHES BUGS	10 / LITER						<u>TECHNICAL SPECIFICATION -</u> Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. <u>GENERAL SPECIFICATION -</u> Specification: Active Ingredient (A.I) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			Sciences)								packing with registered label.	
124	DPC61774	EPIGRIPL524	8010998400988 / EPIGRIP L524-HIGH BUILD 2-PACK MODIFIED EPOXY COATING IN WHITE COLOR	BILGES PAINTING FRIGATES TYPE 24	100 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
125	DGP39672		7435705127034 / MEDIA CONVERTER (FIBER TO ETHERNET) ALONGWITH ACCESS- SEE F8	STANDALONG COMPONENT ROUTER CISCO 3825	6 / EACH/NUMBER	UN-1000-SS-A 2RJ45					<u>TECHNICAL SPECIFICATION - Brand: ULTRA NET</u> <u>GENERAL SPECIFICATION - Brand: ULTRA NET</u>	
126	SPC54158	R-5002	8010705111037 / PIGMENT (BRILIANT WHITE)	GRP WORK, M/S ZAIN SONS. KARCHI.PH; 7731541	80 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
127	DPC42660	R-5021	8010705111038 / PIGMENT (PANTHER BLACK)	GRP WORK, M/S ZAIN SONS KARCHI, PH7731541	120 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 05 Kg packing</u> <u>GENERAL SPECIFICATION - 05 Kg packing</u>	
128	DPC61631	NO DATA AVAILABE	6850785031104 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200MLCLEANER (UNIVERSAL DEGREASER) (OEM = PERFECTS	REQUIREMENT FOR PNS NASR	230 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.</u> <u>GENERAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM : PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13.	
129	DPK5771 1	ROCOL AEROSPE C 300 (XG291)	915099838180 8 / GREASE MULTIPURPOSE:HEAVY DUTY XG-291 (G-421) 3 KG PACK	GENERAL GREASE	57 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry <u>GENERAL SPECIFICATION - 1.</u> Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry	
130	DPK6013 8	ROCOL AEROSPE C 300 (XG291)	915099838180 8 / GREASE MULTIPURPOSE:HEAVY DUTY XG-291 (G-421) 3 KG PACK	GENERAL GREASE	69 / KILOGRAMME						<u>TECHNICAL SPECIFICATION - 1.</u> Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry <u>GENERAL SPECIFICATION - 1.</u> Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of, Manufacturing & Expiry	
131	DPC574 79	TS10268/ ZOK 27	685099225402 0 / COMPRESSOR CLEANING INHABITING	CLEANING FLUID COMPRESSOR G.T.E.TYPE 21	60 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			FLUID (CCIF) P/NO ZOK 27									
132	DPC627 52	TS10268/ ZOK 27	685099225402 0 / COMPRESSO R CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSO R G.T.E.TYPE 21	150 / LITER						<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
133	SPC5212 4	P-21	681070508042 0 / DE- SCALLING COMPOUND ARCOBURAG (OEM ARCO, PACKING 20 TO 25 KG)	A/C PLANT CHILLER WATER CONDENSER SHEEL	150 / KILOGR AMME						<u>TECHNICAL SPECIFICATION -</u> >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning. <u>GENERAL SPECIFICATION -</u> >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning.	
134	DGD466 06	NO DATA AVAILABL E	003450000026 3 / Saucer Tea Blue Crested and Blue Shell On Edge of saucer Size width 5.5" Depth 1cm.		45 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - MATERIAL: PORCELIN</u> <u>GENERAL SPECIFICATION - MATERIAL: PORCELIN</u>	
135	DGD487 73	NO DATA AVAILABL E	003450000026 3 / Saucer Tea Blue Crested and Blue Shell On Edge of		25 / EACH/N UMBER	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - MATERIAL: PORCELIN</u> <u>GENERAL SPECIFICATION - MATERIAL: PORCELIN</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			saucer Size width 5.5" Depth 1cm.									
136	DGD487 79		003154600024 1 / CUPS EGG GOLDEN CRESTED		25 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u> <u>GENERAL SPECIFICATION - MATERIAL PORCELAIN FOOD GRADE CERA-E-NOOR (LOCAL)</u>	
137	DPK5738 5	OENOPER L	801074517562 7 / FOOD GRADE RESIN (OENOPERL 'cold applied' solventfree epoxy) (204KG packing) BRAND= MAXPERLES	COLD/COOL ROOM	90 / KILOGR AMME	NO DATA AVAILAB LE					<u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>	
138	SNM570 34	26561118	294099126340 8 / seFUEL FILTER OF PERKIN DIEI generator 153.5 kva		10 / EACH/N UMBER	26561118					<u>TECHNICAL SPECIFICATION - null</u> <u>GENERAL SPECIFICATION - null</u>	
139	DCC196 17		844050189001 2 / WEBBING BLACK PANTONE COLOUR SHADE 19- 4005/6/7 TCX WIDTH 3CM LENGTH 36"		150 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"</u> <u>GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 36"</u>	
140	DCC196 20		844050189001 5 / WEBBING BLACK PANTONE COLOUR SHADE 19- 4005/6/7 TCX		150 / EACH/N UMBER						<u>TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 48"</u> <u>GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			WIDTH 3CM LENGTH 48"								WIDTH 3CM LENGTH 48"	
141	DRQ64474	POLYTHE NENATUR AL	9330ZO6529824 / POLYTHENE NATURAL (WIDTH 1.5 MR)		500 / KILOGR AMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - a.</u> Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components</p> <p><u>GENERAL SPECIFICATION - a.</u> Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components</p>	
142	DRQ64507	POLYTHE NENATUR AL	9330ZO6529824 / POLYTHENE NATURAL (WIDTH 1.5 MR)		370 / KILOGR AMME	NO DATA AVAILAB LE					<p><u>TECHNICAL SPECIFICATION - a.</u> Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components <u>GENERAL SPECIFICATION - a. Make/ Model/ Brand/ :Local Equivalent be endorsed b. OEM/ Country of Origin: Pakistan/ China Manufacture c. End user to be indicated: 29 F/L d. Parent equipment be INDICATED : Self e. Detailed Specifications: (1) 150-200 micro thickness Technical data/ Testing/ : (2) 500-1000 gauge Acceptance Criteria be : (3) Less Opaque mentioned : (4) water proof f. Requirement of F3 CERTIFICATE : N/A g. Requirement of minimum SHELF LIFE : No shelf life h. Application : Wrapping/ preservation of A/C components</u>	
143	DGD55552	b-596	7320705270640 / CHICKEN ROASTER 4 ROD VERTICAL		2 / EACH/NUMBER	b-596					<u>TECHNICAL SPECIFICATION - Capacity: 16birds, double jacket s/s: body insulated, inner s/s 1.2, outer s/s, ss" rod 1/2 thickness, sliding door tempreed glass 5mm, motor 1/2 hp. imported, dimension: 1066x685x1524mm</u> <u>GENERAL SPECIFICATION - Capacity: 16birds, double jacket s/s: body insulated, inner s/s 1.2, outer s/s, ss" rod 1/2 thickness, sliding door tempreed glass 5mm, motor 1/2 hp. imported, dimension: 1066x685x1524mm</u>	
144	DCC19619		8440501890014 / WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"		150 / EACH/NUMBER						<u>TECHNICAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"</u> <u>GENERAL SPECIFICATION - WEBBING BLACK PANTONE COLOUR SHADE 19-4005/6/7 TCX WIDTH 3CM LENGTH 44"</u>	