

## TENDER BULLETIN

DATE & TIME 7/15/24 10:22 AM INVITATION TO TENDER TO BE OPENED ON 7/29/24 10:00 AM AND ITEM REQ BY

### CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

| S. No | LPR No   | PART NO            | NSN / Description  | P/Equipment             | QTY / DENO       | Model                       | SR NO OF PR | MANUF ADO               | Availabili ty        | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|--|-------------------------|------------------|-----------------------------|-------------|-------------------------|----------------------|----------------|---|-----------|
| 1     | DPK63620 | FCW NMMA CERTIFIED | 9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing) | 350HP YAMAHA            | 100 / LITER      | JAPAN                       |             | JAPAN                   | SHELL                |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |           |
| 2     | DPK58815 | FCW NMMA CERTIFIED | 9150765179546 / YAMALUBE/ADDINOL API SJ SAE 10W-30 (4 Stroke Marnie Oil)(01 Liter Packing) | 350HP YAMAHA            | 120 / LITER      | JAPAN                       |             | JAPAN                   | SHELL                |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |           |
| 3     | SNZ61231 | 123                | 4730705227977 / COPPER ELBOW DIA 1 3/4"  | AC REFRIGERANT GAS LINE | 80 / EACH/NUMBER | ELBOW (Cu/Ni) &#8709; 1 3/4 | NA          | M/S Fast Engineering    | M/S Fast Engineering |                | <u>TECHNICAL SPECIFICATION - Copper Grade: C12200/ Type L Union and elbows have no come in standard sizes with no bifurcation of external &amp; internal diameter. ELBOW Ø1 -3/4" BOTH SIDE FEMALE THREADED MATERIAL: SSGENERAL SPECIFICATION - Copper Grade: C12200/ Type L Union and elbows have no come in standard sizes with no bifurcation of external &amp; internal diameter. ELBOW Ø1 -3/4" BOTH SIDE FEMALE THREADED MATERIAL: SS</u> |           |
| 4     | DNZ46492 | 3029820            | 5331013264775 / O-RING   | MAIN DG                 | 12 / EACH/NUMBER | 6LTA                        | NIL         | Cummins, Engine Co. Ltd | Cummins              |                | <u>TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION -</u>   |           |

| S. No | LPR No   | PART NO                                  | NSN / Description   | P/Equipment                   | QTY / DENO       | Model            | SR NO OF PR                                | MANUF ADO  | Availability              | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--|---|-------------------------------|------------------|------------------|--|--|---------------------------|----------------|--|-----------|
|       |          |  | SEAL  |                               | UMBER            |                  |  |  |                           |                | N/A  |           |
| 5     | DNC57928 | 8M0022158                                | 5307MB0020444 / STUD (M10 X 205)                                      | PETROL MAIN ENGINE            | 10 / EACH/NUMBER | 350              | 2B614987<br>,<br>2B612137<br>,<br>2B619494 | MERCURY MARINE SINGAPORE PTE LTD<br>11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122  | MERCURY MARINE            |                | <u>TECHNICAL SPECIFICATION - STUD (M10 X 205)</u><br><u>GENERAL SPECIFICATION - STUD (M10 X 205)</u>   |           |
| 6     | DNZ63214 | 4101150                                  | 5330016480731 / CONNECTION GASKET                                     | Cummins QSK38 DM Main Engine  | 2 / EACH/NUMBER  | QSK38-DM         | 33170174                                   | Cummins, Engine Co. Ltd  | Cummins                   |                | <u>TECHNICAL SPECIFICATION - N/A</u><br><u>GENERAL SPECIFICATION - N/A</u>   |           |
| 7     | DNF58400 | ST895                                    | 6625785204896 / LCD CCTV CAMERA VIDEO TESTER                          | ST895 Camera Video Tester Set | 2 / SET          | ST895            | -  | Wanglu Tech Co.Ltd<br>5/F,No.3building,He GuangWu Heng Road, Shangshe,TianHe district, Guang Zhou,China Overseas Market<br>Tel:+86-(0)20-87566118<br>Fax: +86-(0)20-38075108<br>E-mail: cctvtester@wanglu.com.cn | Wanglu Technology Co. Ltd |                | <u>TECHNICAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables</u><br><u>GENERAL SPECIFICATION - This Product is designed for On-site installation and maintenance of video monitoring system. Optical Power Meter, used for Optic fiber CCTV monitor System, Cable testing, it is powerful in testing LAN cables</u> |           |
| 8     | DNF65357 | DH-SD6AL245 XA-HNR/<br>DH-SD6AL245 U-HNI | 6710785219481 / HD CAMERA DHAUA 2MP 45X STAR LIGHT LASER PTZ NET WORK | PSS                           | 2 / EACH/NUMBER  | DH-SD6AL245U-HNI | -  | DAHUA TECHNOLOGY CO LTD<br>NO 1199 BIN'AN ROAD, BINJIAND DISTT HANGZHOU,CHINA P.C. 310053<br>TEL. +86 571 8768 8883<br>FAX. +86 571 8768 8815<br>E MAIL overseas@dahuatech.com                                   | DAHUA CHINA               |                | <u>TECHNICAL SPECIFICATION - 1/2.8" MEGAPIXEL STARVIS CMOS POWERFUL 45 X OPTICAL ZOOM MAX 50/60 FPS@ 1080P AUTO TRACKING AND IVS SUPPORT HI-POE IR DISTANCE UPTO 550M IP67</u><br><u>GENERAL SPECIFICATION - 1/2.8" MEGAPIXEL STARVIS CMOS POWERFUL 45 X OPTICAL ZOOM MAX 50/60 FPS@ 1080P AUTO TRACKING AND IVS SUPPORT HI-POE IR DISTANCE UPTO 550M IP67</u>   |           |
| 9     | DNF65327 | DH-SD6AL245 XA-HNR/<br>DH-SD6AL245 U-HNI | 6710785219481 / HD CAMERA DHAUA 2MP 45X STAR LIGHT LASER PTZ NET WORK | PSS                           | 2 / EACH/NUMBER  | DH-SD6AL245U-HNI | -  | DAHUA TECHNOLOGY CO LTD<br>NO 1199 BIN'AN ROAD, BINJIAND DISTT HANGZHOU,CHINA P.C. 310053<br>TEL. +86 571 8768 8883<br>FAX. +86 571 8768 8815  | DAHUA CHINA               |                | <u>TECHNICAL SPECIFICATION - 1/2.8" MEGAPIXEL STARVIS CMOS POWERFUL 45 X OPTICAL ZOOM MAX 50/60 FPS@ 1080P AUTO TRACKING AND IVS SUPPORT HI-POE IR DISTANCE UPTO 550M IP67</u><br><u>GENERAL SPECIFICATION - 1/2.8" MEGAPIXEL STARVIS CMOS</u>   |           |

| S. No | LPR No   | PART NO      | NSN / Description   | P/Equipment          | QTY / DENO       | Model                                    | SR NO OF PR   | MANUF ADO   | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------|---|----------------------|------------------|--|---------------|---|--------------|----------------|---|-----------|
|       |          |              |   |                      |                  |  |               |   |              |                | POWERFUL 45 X OPTICAL ZOOM<br>MAX 50/60 FPS@ 1080P AUTO<br>TRACKING AND IVS SUPPORT HI-<br>POE IR DISTANCE UPTO 550M<br>IP67  |           |
|       |          |              |   |                      |                  |  |               | E MAIL<br>overseas@dahuatech.com  |              |                |   |           |
| 10    | DNF65029 | ATV31HU75N4A | 662573522921<br>5 / VFD<br>(VARIABLE FREQUENCY DRIVE)             | CONTROL SYSTEM       | 1 / UNIT         | SVO55FP5-4                               | 1261600029/30 | Wilder RoadWali Hing Building, Huaide Nanzing, Fuyong, Baon District Shenzhen, Guangdong, China 518100 Tel: (86755) 29608571 Ext: 612 Fax: (86755) 29608109 |              | CARRIER        | <u>TECHNICAL SPECIFICATION - Model: SV055FP5-4 INPUT: 380-480V 3 Phase 17.5A 50/60 Hz OUTPUT: 0-Input V 3 Phase 12.0A 0.1-400 Hz 9.1 KVA/7.5 KW Ser No 55034160366</u><br><u>GENERAL SPECIFICATION - Model: SV055FP5-4 INPUT: 380-480V 3 Phase 17.5A 50/60 Hz OUTPUT: 0-Input V 3 Phase 12.0A 0.1-400 Hz 9.1 KVA/7.5 KW Ser No 55034160366</u>  |           |
| 11    | SPK58310 | ZIC ATF 3    | 915073522136<br>9 / ZIC ATF 3 DEXRON SYNTHETIC TRANSMISSION FLUID | TILT & TRIM ASSEMBLY | 60 / LITER       | ZIC ATF 3                                | NIL           | SK LUBRICANTS 26, JONG-RO-JONGNO-GU, SEOUL,KOREA www.skzic.com Made in Korea  |              | SK LUBRICANTS  | <u>TECHNICAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs &amp; Rhibs (Tilt &amp; trim assembly)</u> <u>GENERAL SPECIFICATION - ZIC ATF3 GM DEXRON-III H Ford Mercon Alliason C-4 Fully Synthetic Used in MFBs &amp; Rhibs (Tilt &amp; trim assembly)</u>   |           |
| 12    | DNQ58130 | RHZK 6/30-2  | 473078516508<br>8 / PRESSURE REDUCER                              | EDBA                 | 12 / EACH/NUMBER | RHZK6.8/30, TYPE: CRPIII-145-6.8-30-T II |               | M/S NANTONG HAIZHOU MARINE EQUIP CO LTD INDUSTRY AREA TIANBU TOWN NAIMEN JANSU CHINA  |              | CHINA          | <u>TECHNICAL SPECIFICATION - a. Make/ Model: RHZK6.8/30 b. OEM/ Country of Origin: Nantong Haizhou Marine Equipment Co Ltd./ China c. Parent Equipment: EDBA (Extended Duration Breathing Apparatus) SOA: M/S BHATTI ENTERPRISES STOCKIEST MILL STORE STEAM JOINING SHEETS BOILER PACKING, ALL KIND OF VALVE &amp; SAFETY EQUIPMENT OFFICE NO 5455, 1st FLOOR ADNAN CENTER NICOL ROAD KARACHI</u> <u>GENERAL SPECIFICATION - a. Make/ Model: RHZK6.8/30 b. OEM/ Country of Origin: Nantong Haizhou Marine Equipment Co Ltd./ China c. Parent Equipment: EDBA (Extended Duration Breathing Apparatus) SOA:</u> |           |

| S. No | LPR No   | PART NO                            | NSN / Description                                      | P/Equipment                                 | QTY / DENO       | Model      | SR NO OF PR | MANUF ADO   | Availability                    | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------------------------|--|---|------------------|------------|-------------|---|---------------------------------|----------------|--|-----------|
|       |          |                                    |  |   |                  |            |             |   |                                 |                | M/S BHATTI ENTERPRISES STOCKIEST MILL STORE STEAM JOINING SHEETS BOILER PACKING, ALL KIND OF VALVE & SAFETY EQUIPMENT OFFICE NO 5455, 1st FLOOR ADNAN CENTER NICOL ROAD KARACHI .  |           |
| 13    | DNF58090 | 457-6114                           | 6625715195285 / CA3/DATA LINK CABLE ASSEMBLY           | CATERPILLAR 466-6258 USA                    | 1 / EACH/NUMBER  | 466-6258   | 1955E180ED  | M/S CATERPILLAR   | M/S CATERPILLAR                 |                | <u>TECHNICAL SPECIFICATION - NIL</u><br><u>GENERAL SPECIFICATION - NIL</u>   |           |
| 14    | DGP65532 | 16919193710 (EXPRESS SERVICE CODE) | 7435785205219 / SVAS WEB TERMINAL (LAPTOP DELL/HP CI3) | SVAS SYSTEM NY-SVAS-08 CHINA                | 1 / SET          | NY-SVAS-08 | NA          | DELL INC 1 DELL WAY. ROUND ROCK, TEXAS CHINA 78682. TEL 1-866-931-3355  | CHINA                           |                | <u>TECHNICAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15</u><br><u>GENERAL SPECIFICATION - SVAS WEB Terminal (SVAS configured laptop) 3000 SERIES INSPIRON 15</u>   |           |
| 15    | DNM54459 | H43850                             | 4720715179216 / XTREME DUTY AIR LESS HOSE              | AIR LESS                                    | 1 / EACH/NUMBER  |            |             | GRACO FLUID EQUIPMENT (SHANGHAI) CO. LTD. ROOM 118 1ST FLOOR NO2 XIN YUAN BUILDING NO 509, CAO BAO ROAD, SHANGHAI, P.R CHINA 200233 | GRACO                           |                | <u>TECHNICAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M)</u><br><u>GENERAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M)</u>   |           |
| 16    | DNM59874 | 08414                              | 4730715173026 / CQP NYLON QUICK COUPLING               | ABRASIVE BLAST CLEANING MACHINE             | 10 / EACH/NUMBER |            |             | CLEMCO INDUSTRIES CORP. USA WWW.CLEMCOINDUSTRIES.COM  | CLEMCO                          |                | <u>TECHNICAL SPECIFICATION - JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING)</u><br><u>GENERAL SPECIFICATION - JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING)</u> |           |
| 17    | DNF65718 | MP12V150F                          | 6150785202832 / BATTERY 12VDC 150AH                    | 1500 lines Navcomm Switches MP12V150F CHINA | 2 / EACH/NUMBER  | MP12V150F  | Nil.        | 9F, Building-A, No.50 Zijinghua Road, Hangzhou, China Tel# +86-571-28827013 Fax# +86-571-28828290                                   | M/s NARADA POWER SOURCE CO. LTD |                | <u>TECHNICAL SPECIFICATION - IT IS USED TO PROVIDE THE BACKUP POWER SUPPLY TO RECTIFIER</u><br><u>GENERAL SPECIFICATION - IT IS USED TO PROVIDE THE BACKUP POWER SUPPLY TO RECTIFIER</u>   |           |

| S. No | LPR No   | PART NO   | NSN / Description  | P/Equipment             | QTY / DENO               | Model                | SR NO OF PR | MANUF ADO  | Availability             | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---|--|-------------------------|--------------------------|----------------------|-------------|--|--------------------------|----------------|--|-----------|
| 18    | DGP57236 | 10SDR<br>9S7-<br>16W112-<br>864 / WS-<br>66 /<br>MSGL638<br>SE209 | 702573523241<br>7 / LAPTOP<br>MSI 15.6 GL63-<br>8SE                      | UFFAQ                   | 1 / UNIT                 | MSI 15.6<br>GL63-8SE |             | OFFICE 3037, 3RD<br>FLOOR, 46-66/B LAJOS<br>STREET, 1036<br>BUDAPEST, HUNGARY  | MSI<br>HUNGAR<br>Y       |                | <u>TECHNICAL SPECIFICATION - MSI<br/>LAPTOP MSI 15.6 DISPLAY GL63-<br/>8SE-8SE INTEL 8 GEN CORE I7<br/>PROCESSOR OS WINDOWS 10<br/>PRO GRAPHICS NVIDIA GEFORCE<br/>RTX 2060 6 GB DDR6 RAM 32 GB<br/>SSD 1TB WITH M2 128 GB</u><br><u>GENERAL SPECIFICATION - MSI<br/>LAPTOP MSI 15.6 DISPLAY GL63-<br/>8SE-8SE INTEL 8 GEN CORE I7<br/>PROCESSOR OS WINDOWS 10<br/>PRO GRAPHICS NVIDIA GEFORCE<br/>RTX 2060 6 GB DDR6 RAM 32 GB<br/>SSD 1TB WITH M2 128 GB</u> |           |
| 19    | DGP63221 | P J560D   | 743570515171<br>3 /<br>MULTIMEDIA<br>PROJECTORS<br>VIEW SONIC P<br>J560D | MULTIMEDIA<br>PROJECTOR | 1 /<br>EACH/N<br>UMBER   | P J560D              |             | SOURCE OF<br>AVAILABILITY: M/S<br>MUSHKO ELECTRONICS<br>(PVT) LTD SAFA HOUSE<br>ABDULLAH HAROON<br>ROAD KARACHI. TEL:<br>021-35660770-3 FAX: 92<br>21 35660801 |                          |                | <u>TECHNICAL SPECIFICATION -<br/>SOURCE OF AVAILABILITY: M/S<br/>MUSHKO ELECTRONICS (PVT)<br/>LTD SAFA HOUSE ABDULLAH<br/>HAROON ROAD KARACHI. TEL:<br/>021-35660770-3 FAX: 92 21<br/>35660801 .</u><br><u>GENERAL<br/>SPECIFICATION - SOURCE OF<br/>AVAILABILITY: M/S MUSHKO<br/>ELECTRONICS (PVT) LTD SAFA<br/>HOUSE ABDULLAH HAROON<br/>ROAD KARACHI. TEL: 021-<br/>35660770-3 FAX: 92 21 35660801 .</u>  |           |
| 20    | DNC65783 | ELEC-<br>0366   | 651079517445<br>9 / PLASTIC<br>CABLE TIES                                | H/CRAFT                 | 200 /<br>EACH/N<br>UMBER | H/CRAFT<br>8100TD    |             | GRIFFON HOVER WORK<br>UK   | GRIFFON<br>HOVER<br>WORK |                | <u>TECHNICAL SPECIFICATION -<br/>LENGTH: 24 INCHES COLOUR:<br/>BLACK</u><br><u>GENERAL SPECIFICATION<br/>-LENGTH: 24 INCHES COLOUR:<br/>BLACK</u>  |           |
| 21    | DNF65695 | 121468/5P<br>X300<br>01RTNG2/<br>MLM-203<br>/DH2024               | 613072517106<br>1 / UPS 3 KVA  | N/A                     | 2 /<br>EACH/N<br>UMBER   | MLM-203<br>/DH2024   |             | GERMANY  | GERMAN<br>Y              |                | <u>TECHNICAL SPECIFICATION -<br/>MODEL MLM-203 /DH2024 BACK<br/>UP REQUIREMENT 4-8 HOURS<br/>POWER SUPPLY 220/230/240<br/>VOLT PLUS MINUS 10<br/>PERCENT</u><br><u>GENERAL<br/>SPECIFICATION - MODEL MLM-203<br/>/DH2024 BACK UP REQUIREMENT<br/>4-8 HOURS POWER SUPPLY<br/>220/230/240 VOLT PLUS MINUS 10<br/>PERCENT</u>   |           |
| 22    | DGP65483 | 4003DN  | 743570513863<br>2 / PRINTER  | COMPUTER                | 5 /<br>EACH/N            | NO DATA<br>AVAILAB   |             | PK   | PAKISTA<br>N             |                | <u>TECHNICAL SPECIFICATION -<br/>Laser, 266 MHz, RAM 16 MB , 1200</u>  |           |

| S. No | LPR No   | PART NO         | NSN / Description   | P/Equipment                                | QTY / DENO      | Model                     | SR NO OF PR  | MANUF ADO  | Availabili ty | Tender Remarks      | TECH / GEN SPECS   | Dimension |
|-------|----------|-----------------|---|--|-----------------|---------------------------|--------------|--|---------------|---------------------|--|-----------|
|       |          |                 | HP LASER JET 2035/HP LASER JET 2055/HP LASER JET Pro 400/M401D/HP 402D/M402DN/ M404DN |  | UMBER           | LE                        |              |  |               |                     | x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both<br><u>GENERAL SPECIFICATION - Laser, 266 MHz, RAM 16 MB , 1200 x 12 dpi, 12 ppm(print speed b/w), Pages per month 25000 pages, Paper Type A4/A5/B5/Legal/Envelope, Connectivity Paraller and USB Port Both</u>   |           |
| 23    | DNM56675 | 23108           | 294071517241 1 / HIGH VOLUME COALESCENT FILTER  | Abrasive Blasting Machine (7910US50716 23) | 2 / UNIT        | CLEMCO 23108              |              | CLEMCO INDUSTRIES COOPERATION, USA www.clemcoindustries.com  |               | CLEMCO              | <u>TECHNICAL SPECIFICATION - PORTABLE, MAX CAPACITY 8000 CFM AT 150 PSI, REMOVE PARTICLES UPTO 10 MICRON, SINGLE OUTLET, 02 X 6 INCH WHEELS</u><br><u>GENERAL SPECIFICATION - PORTABLE, MAX CAPACITY 8000 CFM AT 150 PSI, REMOVE PARTICLES UPTO 10 MICRON, SINGLE OUTLET, 02 X 6 INCH WHEELS</u>   |           |
| 24    | DNJ64752 | 64D-11642-22-90 | 281576521245 1 / PISTON 2 (STD)   | 150 AET OBM ENGINE                         | 1 / EACH/NUMBER | 150AET 07 (6G 47) 1024899 | 1024899 6G47 | YAMAHA MOTOR CO LTD 2500 SHINGAI LWATA SHIZUOKA 438-8501 JAPAN PHONE 0081-538-37-1668 FAX 0081-538-37-1954 |               | YAMAHA MOTOR CO LTD | <u>TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -</u>   |           |
| 25    | DGP64041 | HP4000/cl 11h   | 702571513340 9 / BIO METRIC TIME AND ATTANDANCE MACHINE HP-4000                       | TIME AND ATTANDANCE MACHINE                | 2 / EACH/NUMBER | HP4000/C L11H             |              |  | US            | RSI(IR) USA         | <u>TECHNICAL SPECIFICATION - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name &amp; Time of Thumb impression</u><br><u>GENERAL</u> |           |

| S. No | LPR No   | PART NO                           | NSN / Description  | P/Equipment | QTY / DENO      | Model     | SR NO OF PR | MANUF ADO   | Availabilty                     | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------------------------|--|-------------|-----------------|-----------|-------------|---|---------------------------------|----------------|---|-----------|
|       |          |                                   |  |             |                 |           |             |   |                                 |                | <p><u>SPECIFICATION</u> - Technical Spec: i. User capacity 2000 ii. Fingerprint Capacity 2000 iii. ID card capacity (optional) iv. Record capacity Minimum 150,000 v. Display Minimum 2" color screen vi. Standerd Functions: Fingerprint, Pin Code, TCP/IP, USB connectivity vii. Operating Temp 0 C-45C viii. Operating Humidity 90% RH ix. Language English x. Communication: TCP/IP, USB-host Data should be able to be transferred on MS Excel sheet with data fields: Name &amp; Time of Thumb impression</p> |           |
| 26    | DPK55980 | 92-8m013395<br>1/92-8M013394<br>9 | 915071522921<br>1 / POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC | 300 HP OBM  | 50 / QUART      | 1300V24LD | 2B550466    | MERCURY MARINE<br>W6250 PIONEER ROAD<br>FOND DU LAC, WI 54936-1939<br>TEL NO 920-929-5000 | USA                             |                | <p><u>TECHNICAL SPECIFICATION</u> - POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCURY OBMs 300,. IPC OF THE SAME AND SPECIFICATION ENCLSOED.<br/><u>GENERAL SPECIFICATION</u> - POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCURY OBMs 300,. IPC OF THE SAME AND SPECIFICATION ENCLSOED.</p>  |           |
| 27    | DNF65845 | WPL65-12AN or P-0159000           | 614078516675<br>5 / UPS BATTERY_12V 65AH                         | PSS         | 9 / EACH/NUMBER |           |             | M/s CETC Mansion, No. 5 Wulutong North Street. Xicheng Districe, Beijing, China           | M/s CETC International CO., LTD |                | <p><u>TECHNICAL SPECIFICATION</u> - OEM KUNG LONG BATTERIES INDUS.LTD. SOA: AIR PORT BATTERY SHOP G35 FALAK NAZ TOWER SHAHR E FAISAL KARACHI M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China . <u>GENERAL SPECIFICATION</u> - OEM KUNG LONG BATTERIES INDUS.LTD. SOA: AIR PORT BATTERY SHOP G35 FALAK NAZ TOWER SHAHR E FAISAL KARACHI M/S CETC Mansion, NO.5 Wulutong North Street. Xicheng Districe, Beijing, China .</p>  |           |
| 28    | DGP56889 | 50AU7000/46EH5000                 | 773070517439<br>1 / SAMSUNG                                      | LED TV      | 2 / EACH/N      | 46EH5000  |             | SAMSUNG   | SAMSUNG                         |                | <p><u>TECHNICAL SPECIFICATION</u> - SAMSUNG LED TV 46/49</p>  |           |

| S. No | LPR No   | PART NO         | NSN / Description   | P/Equipment   | QTY / DENO       | Model             | SR NO OF PR   | MANUF ADO  | Availability                             | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------|---|---|------------------|-------------------|---------------|--|--|----------------|---|-----------|
|       |          |                 | LED TV 46/49 INCH   |   | UMBER            |                   |               |  |  |                | INCHGENERAL SPECIFICATION - SAMSUNG LED TV 46/49 INCH   |           |
| 29    | DNN55087 | YBH-20          | 4320FP3000007 / YBH-20 Portable submersible electric pump           | YBH-20 PORTABLE SUBMERSIBLE ELECTRIC PUMP (F-22P SHIPS) | 3 / SET          | YBH-20            | N/A           |  | JIANGSU ZHENHUA PUMP MANUFACTURE CO.,LTD |                | TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -   |           |
| 30    | DNJ64753 | 09387-39002     | 2815765222216 / RING  | SUZUKI DF300AP 300 HP OBM                               | 9 / EACH/NUMBER  | DF300AP           | 30002P-712896 | SUZUKI MOTOR CO LTD JAPAN  | SUZUKI JAPAN                             |                | TECHNICAL SPECIFICATION - NILGENERAL SPECIFICATION - NIL  |           |
| 31    | DNQ65724 | 08279009        | 6210795175762 / LIFE RAFT INTERNAL LIGHT & BATTERY                  | UK RFD  | 16 / EACH/NUMBER | UK (RFD BEAUFORT) | 08279009      | RFD BEAUFORT LTD (UK)  | RFD BEAUFORT LTD (UK)                    |                | TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)  |           |
| 32    | DNM65614 | 4936969/5446701 | 2990715193442 / MANIFOLD, EXHAUST                                   | UT BOAT ENGINEQSB5.9-225BHP                             | 1 / EACH/NUMBER  | QSB5.9-225 BHP    |               | CUMMINS MER CRUISER DIESEL WEBSITE (www.cmdmarie.com)  | CUMMINS                                  |                | TECHNICAL SPECIFICATION - MANIFOLD, EXHAUSTGENERAL SPECIFICATION - MANIFOLD, EXHAUST  |           |
| 33    | DGP65533 | 719064-B21      | 7035015656707 / SERVER HP PROLIANT (HPE DL380 GEN9 8SFF CTO SERVER) | HP SERVER DL 380  | 1 / EACH/NUMBER  | DL380             | SGH830X1T     | MS ORA-TECH SYSTEM, FOUR SQUARE PLAZA 4TH FLOOR,BUILDING NO 21-A, H.H FAROOQI ROAD OFF TARIQ ROAD, PECHS, BLOCK-II, KARACHI. TELEPHONE NO 021-34535933 FAX NO : 021-34536441 | HP                                       |                | TECHNICAL SPECIFICATION - PROCESSOR: 2 x HPE-03 DL380 Gen9 Intel Xeon E5-2609v4 (1.7 GHz/8-Core/20mb/85W) Processor Kit RAM: HPE 256GB (8x32GB) Dual Rank x 4 DDR4-2400 CAS-17-17-17 Load Reduce Memory Kit HARD DISK: 03X HPE 1.8TB SAS 12G Enterprises 10K SFF WITH 256 GB SSD (2.5inch) SC 3Yrs Wty 512e Digitally Signed Firmware HDD GENERAL SPECIFICATION - PROCESSOR: 2 x HPE-03 DL380 Gen9 Intel Xeon E5-2609v4 (1.7 GHz/8-Core/20mb/85W) Processor Kit RAM: HPE 256GB (8x32GB) Dual Rank x 4 DDR4-2400 CAS-17-17-17 Load Reduce Memory Kit HARD DISK: 03X HPE 1.8TB SAS 12G Enterprises 10K SFF WITH 256 GB SSD (2.5inch) SC 3Yrs Wty 512e Digitally Signed Firmware HDD |           |
| 34    | DNM648   | 943478          | 472099533296  | AIR COOLER  | 8 / UNIT         | D6-370D-          | NA            | AB VOLVO PENTA SE 405  | SWEDEN                                   |                | TECHNICAL SPECIFICATION -   |           |



| S. No | LPR No   | PART NO                      | NSN / Description   | P/Equipment                  | QTY / DENO       | Model             | SR NO OF PR | MANUF ADO               | Availability   | Tender Remarks          | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------------------|---|------------------------------|------------------|-------------------|-------------|-------------------------|--|-------------------------|--|-----------|
|       | 21       |                              | 7 / HOSE CLAMP (CHARGE AIR COOLER)                                |                              |                  | E                 |             | 08 GOTHENBURG SWEDEN    |  |                         | MAKE: VOLVO PENTA , CHARGE AIR COOLER<br>GENERAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER   |           |
| 35    | DNH65720 | NIL                          | 412073513911<br>8 / AIR CONDITIONER 02 TONS SPLIT TYPE            | AIR CONDITIONING             | 2 / EACH/NUMBER  | NO DATA AVAILABLE |             | OC                      |  | THILAND                 | TECHNICAL SPECIFICATION - as per standardization policy nme dte ammendment letter 1653648 dt 25 april 2019 following split ac make are to be procured: gree, daikin, mitsubishi, lg, general<br>GENERAL SPECIFICATION - as per standardization policy nme dte ammendment letter 1653648 dt 25 april 2019 following split ac make are to be procured: gree, daikin, mitsubishi, lg, general |           |
| 36    | DNF65612 | 15 opzv 1500 (GFMJ. 1500 AH) | 611750514525<br>5 / 2V 1500AH gfmj BATTERIES                      | SOLAR PANEL SYSTEM 10KVA     | 12 / EACH/NUMBER | 15 opzv 1500 gfmj |             | GR                      | M/S CHENGYANG ROAD QUFU 273100 PR CHINA TEL:+86 537-4438666 , 4411936 FAX: +86 537 4411936 |                         | TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858<br>GENERAL SPECIFICATION - SOURCE OF AVAILABILITY : M/S AKHTAR COMPUTERS PAKISTAN BULAND MARKAZ 23 BLUE AREA ISLAMABAD. TEL: 051-2829803-6 FAX: 051-2276858   |           |
| 37    | DNZ63245 | 3635158                      | 533001618471<br>0 / THERMOSTAT HOUSING COVER GASKET               | Cummins QSK38 DM Main Engine | 1 / EACH/NUMBER  | QSK38-DM          | 33170174    | Cummins, Engine Co. Ltd | Cummins  |                         | TECHNICAL SPECIFICATION - N/A<br>GENERAL SPECIFICATION - N/A   |           |
| 38    | DNF64952 | 5601.3800.03                 | 662572513376<br>4 / TRIPLE POWER SUPPLY HM7042-5 WITH ACCESSORIES | POWER SUPPLY                 | 1 / EACH/NUMBER  | NGE 103B          |             | GR                      |  | ROHDE & SCHWARZ GERMANY | TECHNICAL SPECIFICATION - R&S NGE 103B POWER SUPPLY AS REPLACEMENT OF OBSOLETE ITEM 2X0-32V 1X0-5.5V Company: Rohde & Schwarz Pakistan (Pvt.) Ltd. Point of Contact: Mr Adil Butt Address: C-101 KDA Scheme 01 opposite Pakistan Maritime Museum   |           |

| S. No | LPR No   | PART NO | NSN / Description   | P/Equipment       | QTY / DENO       | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------|---|-------------------|------------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |         |   |                   |                  |       |             |           |              |                | <p>Karsaz road KARACHI-75350. Tel: 0345-2010347, +92 21111050050-203 Email: adil.butt@rohde-schwarz.com obsolete items: R&amp;S NGE 103B power supply <u>GENERAL SPECIFICATION - R&amp;S NGE 103B POWER SUPPLY AS REPLACEMENT OF OBSOLETE ITEM 2X0-32V 1X0-5.5V Company: Rohde &amp; Schwarz Pakistan (Pvt.) Ltd. Point of Contact: Mr Adil Butt Address: C-101 KDA Scheme 01 opposite Pakistan Maritime Museum Karsaz road KARACHI-75350. Tel: 0345-2010347, +92 21111050050-203 Email: adil.butt@rohde-schwarz.com obsolete items: R&amp;S NGE 103B power supply</u></p> |           |
| 39    | DPC57475 |         | 047350942313<br>1 / PIGMENT AND OIL PASTE WHITE LEAD / KOLOR KUT WATER FINDING PASTE FOR PETROLEUM AND CHEMICAL |                   | 65 / EACH/NUMBER |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm</u> <u>GENERAL SPECIFICATION - Net Weight: (Per Piece) 3 OZ. (85 Grams) Packing Dimensions: 14.5 X 3.2 X 2.8 cm</u></p>   |           |
| 40    | DGE62618 |         | 035059571303<br>4 / ROPE COIR, HAWSERLAID, 3-STRAND, CIRC: 3-INCH, DIA: 1-INCH (24MM)                           |                   | 400 / FATHOM     |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION - LENGTH PER COIL: 120 FATHOM, OEM COC REQUIRED.</u><u>GENERAL SPECIFICATION - LENGTH PER COIL: 120 FATHOM, OEM COC REQUIRED.</u></p>  |           |
| 41    | SPC58311 | 732RTV  | 042599225196<br>2 / SILICON RUBBER SILASTIC 732RTV (SEALING COMPOUND) WHITE 90ML                                | PROPELLER SEALING | 50 / EACH/NUMBER |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>  |           |

| S. No | LPR No   | PART NO          | NSN / Description  | P/Equipment                       | QTY / DENO       | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|------------------|--|-----------------------------------|------------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                  | TUBE (OEM DOW CORNING)   |                                   |                  |       |             |           |              |                |  |           |
| 42    | SGH51425 |                  | 0283595711167 / SHEET ALUMINIUM ALLOY SIZE: L X W X TH, 144 INCH X 48 INCH X 0.128 INCH. WT. PER SQ FOOT: 1.764 (LB). QUATER HARD AUTHORITY: BR-3200 |                                   | 2 / EACH/NUMBER  |       |             |           |              |                | TECHNICAL SPECIFICATION - 1. mechanical properties: bs en 485-2 of 2016 2. chemical composition: bsen 573-3 of 2007 3. trmp condition: h12 4. grade: en aw 5251 5. quater hard authority br-3200<br>GENERAL SPECIFICATION - 1. mechanical properties: bs en 485-2 of 2016 2. chemical composition: bsen 573-3 of 2007 3. trmp condition: h12 4. grade: en aw 5251 5. quater hard authority br-3200   |           |
| 43    | DGB52212 |                  | 0212595710705 / BAR STEEL CORROSION RESISTING H/R RD 03" WT PER FT24. 030LBS   | MAT IDEN SYMBLO. L42H35 18% CHROM | 6 / METER        |       |             |           |              |                | TECHNICAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter<br>GENERAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter   |           |
| 44    | SGB56164 |                  | 0212595710681 / BAR-STEEL-HOT-ROLLED-RD-0.31 INCH  |                                   | 3 / METER        |       |             |           |              |                | TECHNICAL SPECIFICATION - Specification PD- 970 Material grade 605 M(36) running length ; 10 ft<br>GENERAL SPECIFICATION - Specification PD- 970 Material grade 605 M(36) running length ; 10 ft   |           |
| 45    | DGP62383 | NO DATA AVAILABE | 0051500001403 / Binder Medium F(NS) -101 SIZE 9X12 INCH, Board Texture, Hard & Plyable Thickness 03 mm   |                                   | 60 / EACH/NUMBER |       |             |           |              |                | TECHNICAL SPECIFICATION - Size: 9 x 12 inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press<br>GENERAL SPECIFICATION - Size: 9 x 12 |           |

| S. No | LPR No   | PART NO      | NSN / Description   | P/Equipment  | QTY / DENO        | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------|---|--------------|-------------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |              |   |              |                   |       |             |           |              |                | <p>inches Hard cover binder with steel clip Quality / Thickness of straw board with rexine: 03mm Golden steel corners at the edges of the cover binders Color of rexine: Navy blue dark Best quality imported rexine with golden foil printing (Data for printing of title will be provided by PN Central Printing Press. NAVCOM: 56050 / 021-48506050) Acceptance Criteria: As per sample provided by PN Central Printing Press</p> |           |
| 46    | DGE65530 | bp310        | 209070050000<br>1 / CHAIR TUBULAR WHITE PLASTIC SEAT  |              | 125 / EACH/NUMBER | bp310 |             |           |              |                | <p><u>TECHNICAL SPECIFICATION</u> - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"<br/><u>GENERAL SPECIFICATION</u> - height 34.5 inches width 20 inches diameter 19 inches (approx) Brand: "Master Brand"</p>   |           |
| 47    | DNF65613 | BSEN 60317-8 | 056179519875<br>6 / WIRE WINDING ELECT COPPER POLYESTER ENAMEL cOND DIA 0.850 O/DIA 0.964MM (GRADE-3 CLASS-180) | FOR WINDING. | 30 / KILOGRAMME   |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br/><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>   |           |
| 48    | SPC61234 |              | 047450474001<br>2 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)   |              | 70 / EACH/NUMBER  |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br/><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>   |           |
| 49    | DGE62632 |              | 047450474012<br>7 / QANAT COMPLETE SiZe. 18.00X7.00 FT  |              | 30 / EACH/NUMBER  |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side:.Simple / different color. d. Cloth Material:. Jersey two side heavy. e. Accessories:.Bamboos, sticks and ropes. f. Bamboos: Quantity , 120, Length 10 ft each</p>   |           |

| S. No | LPR No   | PART NO                               | NSN / Description  | P/Equipment      | QTY / DENO       | Model                   | SR NO OF PR | MANUF ADO | Availabilty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------------------------------------|--|------------------|------------------|-------------------------|-------------|-----------|-------------|----------------|--|-----------|
|       |          |                                       |  |                  |                  |                         |             |           |             |                | <p>bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, I. Multi-color (Yellow, Red and Green) are proposed for front/ back side design. <u>GENERAL SPECIFICATION</u> - a. Size: Height 7 Feet, Length 18 Feet. b. Front Side: Golden/ Design. c. Back Side:.Simple / different color. d. Cloth Material:. Jersey two side heavy. e. Accessories:.Bamboos, sticks and ropes. f. Bamboos: Quantity , 120, Length 10 ft each bamboo g. Rope: QUANTITY, 120, Length 12 ft each Rope h. Color of Design for Front/ Back. Olive Green, I. Multi-color (Yellow, Red and Green) are proposed for front/ back side design.</p> |           |
| 50    | DNF63743 | PAK / GFC/MILL AT/ EQUIVALENT         | 0565700000048 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)                                | END USE SELF     | 2 / EACH/NUMBER  |                         |             |           |             |                | <p><u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br/><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE</p>   |           |
| 51    | DNF65012 | BS EN 60317-8                         | 0561795253580 / WIRE, WINDING COPPER ELECT COND DIA 1.320 O/DIA 1.423 MM (CLASS-180) GRADE-2 | WIRE FOR WINDING | 100 / KILOGRAMME | GHAZILE X               |             |           |             |                | <p><u>TECHNICAL SPECIFICATION</u> - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 PURITY 99.95 % Copper<br/><u>GENERAL SPECIFICATION</u> - DIA : 1.320MM O/DIA : 1.423MM (CLASS-180) DEFSTAN 61-12 ISSUE-2 OF 2008(PART-14) BS-4665 PART-1 BSEN60317-8 GRADE-2 PURITY 99.95 % Copper</p>   |           |
| 52    | DNF65312 | N250 PLUS EXIDE / OSAKA OR EQUIVALENT | 0562795620006 / BATTERY LEAD ACID 12V 200AH  | DG USED          | 3 / EACH/NUMBER  | N250 PLUS EXIDE / OSAKA |             |           |             |                | <p><u>TECHNICAL SPECIFICATION</u> - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA<br/><u>GENERAL SPECIFICATION</u> - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</p>   |           |

| S. No | LPR No   | PART NO                             | NSN / Description   | P/Equipment                     | QTY / DENO       | Model                         | SR NO OF PR | MANUF ADO | Availabilty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|-------------------------------------|---|---------------------------------|------------------|-------------------------------|-------------|-----------|-------------|----------------|--|-----------|
| 53    | DNF65795 | N250 PLUS EXIDE / OSAKA OR EQUALENT | 056279562000<br>6 / BATTERY LEAD ACID 12V 200AH                                 | DG USED                         | 4 / EACH/NUMBER  | N250 PLUS EXIDE / OSAKA       |             |           |             |                | <u>TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u><br><u>GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA</u>   |           |
| 54    | DNF65779 | MD231 (CROWN) /EH1504 /EH1418       | 444079510254<br>4 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM | DEHUMIDIFIERS                   | 60 / EACH/NUMBER | MD231 (CROWN) /EH1504/ EH1418 |             |           |             |                | <u>TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 I/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</u><br><u>GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 I/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</u> |           |
| 55    | DNF65721 | MD231 (CROWN) /EH1504 /EH1418       | 444079510254<br>4 / PREMI-AIR DEHUMIDIFIERS,300W, 220/240V SIZE: 350X452X275 MM | DEHUMIDIFIERS                   | 1 / EACH/NUMBER  | MD231 (CROWN) /EH1504/ EH1418 |             |           |             |                | <u>TECHNICAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 I/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</u><br><u>GENERAL SPECIFICATION - Rated Voltage: 220-240 V- Rated Frequency: 50Hz Power: 240W Working Temperature: 5 oC-35 oC Dehumidifying Capacity: 10 I/Day Hi Side Pressure: 1.7MPa Low Side Pressure: 0.7MPa Refrigerant Charge: R134A/0.09 KG Weight: 10.5 KG</u> |           |
| 56    | DNM59732 | 92002                               | 4730US507162<br>8 / NOZZLE SILICON CARBIDE                                      | ABRASIVE BLAST CLEANING MACHINE | 2 / EACH/NUMBER  | CTSD-X-6/50                   |             |           |             |                | <u>TECHNICAL SPECIFICATION - MAKE: CLEMCO USA</u><br><u>GENERAL SPECIFICATION - MAKE: CLEMCO USA</u>   |           |

| S. No | LPR No   | PART NO            | NSN / Description                                  | P/Equipment                     | QTY / DENO         | Model              | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|--|---------------------------------|--------------------|--------------------|-------------|-----------|---------------|----------------|---|-----------|
|       |          |                    | ALLOY I/D7/16" LG8"FOR ABRASIVE BLAST              |                                 |                    |                    |             |           |               |                |   |           |
| 57    | DGE62971 | NO DATA AVAILAB LE | 4240PK5078177 / GUNNY BAGS                         |                                 | 3000 / EACH/NUMBER |                    |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - GUNNY BAGS</u> 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF).</p> <p><u>GENERAL SPECIFICATION - GUNNY BAGS</u> 1- material = jute 2- type of bags = hessian bag (1/1 plain) 3- dimension (inches/cm) = 40x20/101x51 4- proter x shots/ends x picks per dm = 11x12/47X47 5- weight of fabric (gsm) = (305gsm) 6- weight of bag = 350 gm 7- tensile strength wp x wft (kgf)112 x 120 (KGF) 8- seam strength wft x wp (kgf) 34 x 36 (KGF).</p> |           |
| 58    | DNQ63203 | ACG-72019          | 4210785088910 / SPRING HOLDER FOR FIRE EXTINGUSHER | FOR FIRE EXTINGUISHER ALL TYPES | 722 / EACH/NUMBER  |                    |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - HOld the syphon tube of fire extinguisher</u><u>GENERAL SPECIFICATION - HOld the syphon tube of fire extinguisher</u></p>   |           |
| 59    | DNQ63429 | LOCAL              | 4210705007917 / NOZZLE FOR HOSE CANVAS             |                                 | 16 / EACH/NUMBER   | SL-13BP SHILA FIRE |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - Series: W2500 Model: Pwr 1 &amp; 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide &amp; light aluminium alloy</u><u>GENERAL SPECIFICATION - Series: W2500 Model: Pwr 1 &amp; 1p OEM/Brand: pwr control: manual output: 130-23- liter per minute at 6 bar pressure material: polyamide &amp; light aluminium alloy</u></p>   |           |
| 60    | DGP65527 |                    | 3610705117912 / SHREDDING                          | SHREDDER MACHINE                | 2 / EACH/NUMBER    | ST-12C/ST-12CD     |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - ST-12C/ST-12CD</u><u>GENERAL SPECIFICATION - ST-12C/ST-12CD</u></p>   |           |

| S. No | LPR No   | PART NO            | NSN / Description  | P/Equipment               | QTY / DENO      | Model   | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------|--|---------------------------|-----------------|---|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                    | MACHINE (HEAVY DUTY)   |                           |                 |   |             |           |               |                |  |           |
| 61    | DNH65813 | NO DATA AVAILAB LE | 4130705046529 / A/C 2 TON SPLIT TYPE 2 TON, GREE/ MITSBUSHI/ DAKEN/ GENERAL, 24000 BTU 220 V 50 HZ ANY BRAND AS PER NHQ POLICY | SELF                      | 1 / EACH/NUMBER | GREE/PE L, MITSBUS HI/ DAKEN/ GENERA L, GENERA L, LG, |             |           |               |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |
| 62    | DGP59111 |                    | 3610705049342 / DUPLICATOR ELECTRICAL GESTETNER HEAVY DUTY   |                           | 1 / EACH/NUMBER |   |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 63    | DGP62161 |                    | 3610705007237 / PAGE CORD TWIN COMPOSING   |                           | 20 / KILOGRAMME |   |             |           |               |                | TECHNICAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection<br>GENERAL SPECIFICATION - 1. Dimension/ Size etc: 100 meter (approximately) long roll of flexible plastic cord which is used to tie the bundle of papers, set of forms, books and miscellaneous stationery items. 2. Acceptance Criteria Acceptable as sample of Page Cord provided by PNCPP 3. Mode of inspection Joint inspection |           |
| 64    | DNH65615 |                    | 4110705111571 / WATER DISPENSER  | WATER COOLER (SUNNY/MECO) | 1 / EACH/NUMBER | WA60000514  |             |           |               |                | TECHNICAL SPECIFICATION - Make: Orient Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey) Voltage 220-240 V Frequency 50 Hz Heating Power 420   |           |



| S. No | LPR No   | PART NO              | NSN / Description   | P/Equipment   | QTY / DENO              | Model          | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------|---|---|-------------------------|----------------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |                      |   |   |                         |                |             |           |              |                | W Cooling Power 100 W<br><u>GENERAL SPECIFICATION</u> - Make: Orient<br>Technical specification: 3 Tab Water Dispenser ICON 3 (Mesh grey)<br>Voltage 220-240 V Frequency 50 Hz<br>Heating Power 420 W Cooling Power 100 W  |           |
| 65    | DNM59696 | 6712-666             | 494079506195<br>7 / HOSE<br>W/ADAPTOR<br>15M LG10MM<br>I/D 17.50MM<br>O/D<br>W/PRESSURE<br>=400 BAR | AIR<br>POWERED<br>PORTABLE<br>AIRLESS<br>HYDRA<br>SPRAY | 3 /<br>EACH/<br>NUMBER  |                |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> -<br>LENGTH : 15METER ID: 10MM OD:<br>17.50MM PRESSURE:400BAR<br>LOCAL ADD:ASHI ENTERPRISES<br>ROOM NO:48 3RD FLOOR MOOSA<br>MARKET OPP SINDH MADERSA<br>SHAHRAH-E-LIAQAT KARACHI<br>74000 CELL: 0334-3500149 VIDE<br>GM(SR&C)LETTER<br>SRC/HE/131/349 DT 24 JAN 13.<br><u>GENERAL SPECIFICATION</u> -<br>LENGTH : 15METER ID: 10MM OD:<br>17.50MM PRESSURE:400BAR<br>LOCAL ADD:ASHI ENTERPRISES<br>ROOM NO:48 3RD FLOOR MOOSA<br>MARKET OPP SINDH MADERSA<br>SHAHRAH-E-LIAQAT KARACHI<br>74000 CELL: 0334-3500149 VIDE<br>GM(SR&C)LETTER<br>SRC/HE/131/349 DT 24 JAN 13. |           |
| 66    | DNM65780 | 193736               | 533079504890<br>4 / SEAL<br>INJECTOR  | MARINE<br>DIESEL<br>ENGINE                              | 66 /<br>EACH/<br>NUMBER | MCM-<br>160-HM |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - NO<br>DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA<br>AVAILABLE   |           |
| 67    | DNM60038 | 050307               | 536512191242<br>7 / SPACER<br>RING 3RD<br>STAGE   | HP AIR<br>COMPRESSO<br>R-150-BAR<br>(GERMANY)           | 8 /<br>EACH/<br>NUMBER  |                |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - NO<br>DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA<br>AVAILABLE   |           |
| 68    | DGH54491 | NO DATA<br>AVAILABLE | 561070506109<br>8 / PORTA<br>CABIN 20X8FT<br>SEA<br>CONTAINER<br>FULLREFUR<br>BISHED TO<br>SUIT     |   | 1 /<br>EACH/<br>NUMBER  |                |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - a.<br>Dimension: 20 x 08 feet Sea<br>Container b. Material: Thermopole or<br>any heat/ electric insulating material<br>c. Fixtures: Cabinets Racks Working<br>desks Office Furniture 01 x Fan in<br>each partition Lighting Facility d.<br>Separation / Partition: Yes e.<br>Windows: 01 x in each partition f.<br>Doors: 01 x in each partition (with  |           |

| S. No | LPR No       | PART NO           | NSN / Description  | P/Equipment                                   | QTY / DENO               | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|--------------|-------------------|--|---|--------------------------|-------|-------------|-----------|---------------|----------------|---|-----------|
|       |              |                   |  |   |                          |       |             |           |               |                | lock and and keys) g. Flooring: Wooden or any insulator h. Power Supply Sockets for office machinery and Air Conditioner supported j. Pictures Enclosed<br><u>GENERAL SPECIFICATION</u> - a. Dimension: 20 x 08 feet Sea Container b. Material: Thermopole or any heat/ electric insulating material c. Fixtures: Cabinets Racks Working desks Office Furniture 01 x Fan in each partition Lighting Facility d. Separation / Partition: Yes e. Windows: 01 x in each partition f. Doors: 01 x in each partition (with lock and and keys) g. Flooring: Wooden or any insulator h. Power Supply Sockets for office machinery and Air Conditioner supported j. Pictures Enclosed |           |
| 69    | DNJ6386<br>2 |                   | 596576501864<br>2 / SPEAKER<br>NVS 415A 2W<br>P/A 1410L-83   | PUBLIC<br>ADDRESSERM<br>ODEL NVA-<br>1410L-83 | 1 /<br>EACH/N<br>UMBER   |       |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE  |           |
| 70    | DNF5240<br>1 | 6 242 01          | 613099742767<br>0 / CHARGER<br>PANEL LIGHT,<br>TYPE 10-<br>MODIFIED<br>110/130V AND<br>200/250V<br>50/60HZ           | PANNEL<br>LIGHT                               | 2 /<br>EACH/N<br>UMBER   |       |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - country of origin uk<br><u>GENERAL SPECIFICATION</u> - country of origin uk  |           |
| 71    | DNF6584<br>4 | NO.E91<br>IEC LR6 | 613579505849<br>2 / BATTERY<br>ALKALINE<br>(ENERGIZER)<br>(Non<br>Rechargeable)<br>1.5V AA SIZE<br>NO.E91 IEC<br>LR6 | GENERAL<br>USE                                | 50 /<br>EACH/N<br>UMBER  |       |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE  |           |
| 72    | DNF6552<br>1 | NO.E91<br>IEC LR6 | 613579505849<br>2 / BATTERY<br>ALKALINE<br>(ENERGIZER)   | GENERAL<br>USE                                | 200 /<br>EACH/N<br>UMBER |       |             |           |               |                | <u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE<br><u>GENERAL SPECIFICATION</u> - NO DATA AVAILABLE  |           |

| S. No | LPR No   | PART NO                   | NSN / Description  | P/Equipment                         | QTY / DENO       | Model              | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|---------------------------|--|-------------------------------------|------------------|--------------------|-------------|-----------|---------------|----------------|---|-----------|
|       |          |                           | (Non Rechargeable)<br>1.5V AA SIZE<br>NO.E91 IEC<br>LR6        |                                     |                  |                    |             |           |               |                |   |           |
| 73    | DNF60296 | HI-PE MULTI-ZONE / PD6500 | 6350715095514 / WALKTHROUGH GATE METAL DETECTOR C/W ACCESOROES | SECURITY DETECTION (OEM CEIA ITALY) | 2 / EACH/NUMBER  |                    |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 74    | DNG65625 | 275447-1                  | 5970004327371 / TAPE INSULATIONN ELECTRICAL                    | CIWS                                | 10 / ROLL        |                    |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 75    | DNH65719 | NO DATA AVAILAB LE        | 4110750530105 / REFRIGERAT OR 6CUFT 220V 50HZ                  |                                     | 1 / EACH/NUMBER  | NO DATA AVAILAB LE |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 76    | DGP65775 |                           | 7530705016199 / WHITE OFFSET PAPER 20" X30" VRG 84 GSM +/-5%   |                                     | 47 / REAM        |                    |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 77    | DGE63731 | NO DATA AVAILAB LE        | 0330500000138 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT    | GENERAL USE                         | 685 / KILOGRAMME | NO DATA AVAILAB LE |             |           |               |                | TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) |           |
| 78    | DGE62616 | NO DATA AVAILAB LE        | 0340500000010 / CANVAS   |                                     | 2 / EACH/NUMBER  | NO DATA AVAILAB LE |             |           |               |                | TECHNICAL SPECIFICATION - Water Proof, In single sheet Size: 30   |           |

| S. No | LPR No   | PART NO            | NSN / Description   | P/Equipment | QTY / DENO      | Model              | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|---|-------------|-----------------|--------------------|-------------|-----------|---------------|----------------|---|-----------|
|       |          | E                  | COVER WATER PROOF   |             | UMBER           | LE                 |             |           |               |                | x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand)GENERAL SPECIFICATION - Water Proof, In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand)  |           |
| 79    | DGP61641 |                    | 7540PK5070879 / IT48 I/TAX RETURN)9.5 X12"                                |             | 5000 / SHEET    |                    |             |           |               |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 80    | DGE65431 | NO DATA AVAILAB LE | 0423500000002 / HOSPITAL STANDARD WARD BED LG.210CM,WD. 91 CM,HIGHT 57CM. |             | 5 / EACH/NUMBER | NO DATA AVAILAB LE |             |           |               |                | TECHNICAL SPECIFICATION - a. Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 21/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 61/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handles. j. two screw clanks one for head side aand other for foot side. k. Maturine bag hooks with smooth clips- 02 in Nos. l. wite powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crc 1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever |           |

| S. No | LPR No   | PART NO | NSN / Description   | P/Equipment        | QTY / DENO              | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|---------|---|--------------------|-------------------------|-------|-------------|-----------|--------------|----------------|---|-----------|
|       |          |         |   |                    |                         |       |             |           |              |                | <p>for up and down of patient head &amp; feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head end should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)</p> <p><u>GENERAL SPECIFICATION - a.</u></p> <p>Three crane adjustable b. main frame 18 g pipesub frame and foot side and head side bow swg pipe c. height adjustable pipe use 21/2 x 1 20" gauge d. crane pipe 18 gauge e. top size 3 x 61/4 include drip rod stand. f. both sides fiber side (made in china). g. wheel 5" (made in china). h. side railing set (made in china). i. tilting system (head/foot/knee) is required alongwith adjustable handles. j. two screw clanks one for head side aand other for foot side. k. Maturine bag hooks with smooth clips- 02 in Nos. l. wite powder paint color as per international standard 1. lg 210 cm 2. wd 91 cm 3. height 57 cm. Grade: crc 1. Drip Point/IV STAND: To be included on both sides of the bed. 2. Dimension: Length of patient bed: 7 ft Width of patient bed: 3 ft 3. Paint/ Coating: Half White 4. Lever: Lever for up and down of patient head &amp; feet 5. Wheels: The bed should have 4 x wheels with three stopper / breaks. 6. Head End: Head end should be removable 7. Material: CRC 8. Urine bag point: To be included on both sides of the bed. 9. Weight capacity: 230kg (approx)</p> |           |
| 81    | DGE62631 |         | 834070508791<br>3 / TENT 40<br>POUND ARMY<br>PATT = FLY &<br>FOLD DOUBLE<br>= L7W 6FT | GENERAL<br>PERPOSE | 10 /<br>EACH/N<br>UMBER |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION - a.</u></p> <p>Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on</p>  |           |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|--------|---------|-------------------|-------------|------------|-------|-------------|-----------|--------------|----------------|---|-----------|
|       |        |         | (JUNGLE GREEN)    |             |            |       |             |           |              |                | <p>sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER <u>GENERAL SPECIFICATION</u> - a. Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER</p> |           |

| S. No | LPR No   | PART NO | NSN / Description  | P/Equipment     | QTY / DENO      | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------|--|-----------------|-----------------|-------|-------------|-----------|--------------|----------------|--|-----------|
| 82    | DGE61552 |         | 834070508791<br>3 / TENT 40 POUND ARMY PATT = FLY & FOLD DOUBLE = L7W 6FT (JUNGLE GREEN) | GENERAL PERPOSE | 2 / EACH/NUMBER |       |             |           |              |                | <p><u>TECHNICAL SPECIFICATION - a.</u><br/>Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER <u>GENERAL SPECIFICATION - a.</u> Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs., QUANTITY</p> |           |

| S. No | LPR No   | PART NO | NSN / Description   | P/Equipment     | QTY / DENO      | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------|---|-----------------|-----------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |         |   |                 |                 |       |             |           |              |                | 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria: CINS/END USER  |           |
| 83    | DGE61553 |         | 834070508791<br>5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT | GENERAL PURPOSE | 2 / EACH/NUMBER |       |             |           |              |                | <u>TECHNICAL SPECIFICATION -</u><br>Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent ; Iron Poles ( Centre & Ride) ; Iron Hammer ; Iron Stick for walls ; Iron pins ; Iron pegs ; Repair Kit ; P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN <u>GENERAL SPECIFICATION -</u> Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent ; |           |



| S. No | LPR No   | PART NO                          | NSN / Description   | P/Equipment     | QTY / DENO      | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|----------------------------------|---|-----------------|-----------------|-------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                                  |   |                 |                 |       |             |           |               |                | Iron Poles ( Centre & Ride) ; Iron Hammer ; Iron Stick for walls ; Iron pins ; Iron pegs ; Repair Kit ; P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN  |           |
| 84    | DGE61555 | OUTER FLY&FOLD MADE OF COTT/CONV | 834070508791<br>6 / TENT MARQUEE UNIVERSAL G.S(SZ27X19.6FT)<br>FOLD&FLY TWO (J/GREEN) | GENERAL PURPOSE | 2 / EACH/NUMBER |       |             |           |               |                | <p>TECHNICAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % cOTTON cANVAS II. WATER AND ROT RESISTANT FABRICIN LIVE GREEN.III.GROUND SHEET AND MUD FLAP:180 GSM(+/- 5%. IV. ACCESSARIES COMPLEATE WITH METAL PLATES OFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES. *.DIMENTION LENGTH X WIDTH OUTER TENT 1.USABLE AREA 5.5 X6 MTRS CENTER HIEGHT 3.65 M WALL HIEGHT 1.63 (OPTION 1) II. USABLE AREA 6.8X8.2 MTRS CENTER HIEGHT 3.65 M WALL HIEGHT 1.63 (OPTION 2)GENERAL SPECIFICATION - 1. 600 gsm (+/- 5%) 100 % cOTTON cANVAS II. WATER AND ROT RESISTANT FABRICIN LIVE GREEN.III. GROUND SHEET AND MUD FLAP: 180 GSM(+/- 5%. IV. ACCESSARIES COMPLEATE WITH METAL PLATES OFPOWDER COATED STEEL PIPES IRON PES GROUNDS PINS AND GUY ROPES. *.DIMENTION LENGTH X WIDTH OUTER TENT 1.USABLE AREA 5.5 X6 MTRS CENTER HIEGHT 3.65 M WALL HIEGHT 1.63 (OPTION 1) II. USABLE AREA 6.8X8.2 MTRS</p> |           |

| S. No | LPR No   | PART NO            | NSN / Description   | P/Equipment                              | QTY / DENO       | Model     | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|---|--|------------------|-----------|-------------|-----------|---------------|----------------|---|-----------|
|       |          |                    |   |  |                  |           |             |           |               |                | CENTER HIEGHT 3.65 M WALL HIEGHT 1.63 (OPTION 2)  |           |
| 85    | DNF61843 | 390DCS/2           | 8030775016310 / DEGREASER CLEANER, SOLVENT NON OILY (200ML) | PCB CLEAN MATERIAL (M/S PERFECT BELGIUM) | 46 / EACH/NUMBER | 390DCS/00 |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u></p> <p><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u></p>   |           |
| 86    | DGE61557 | NO DATA AVAILAB LE | 8340705014084 / TENT FOR CPOS AND SAILORS WT. 120 LBS       |  | 4 / EACH/NUMBER  |           |             |           |               |                | <p><u>TECHNICAL SPECIFICATION - cins observation and annex b is enclosed as document a.Tent for CPOs and Sailors WT.120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.</u></p> <p><u>GENERAL SPECIFICATION - cins observation and annex b is enclosed as document a.Tent for CPOs and Sailors WT.120 LBs along with complete accessories. B. Details specifications/Technical data/ Testing acceptance criteria be mentioned: Tent Proof: made out of 450/G M2 cotton canvas which is rot proof, water proof, vat dyed canvas. Tent wall: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Inner Lining: Made out of 400/G M2 cotton canvas which is rot proof and water proof. Complete packing of tent along with accessories c. CoC: CoC is also required/compliance by seller.</u></p> |           |

| S. No | LPR No   | PART NO              | NSN / Description   | P/Equipment     | QTY / DENO       | Model                     | SR NO OF PR | MANUF ADO | Availability | Tender Remarks                 | TECH / GEN SPECS  | Dimension |
|-------|----------|----------------------|---|-----------------|------------------|---------------------------|-------------|-----------|--------------|--------------------------------|---|-----------|
| 87    | DGP61253 | TOSHIBA E-STUDIO 282 | 3610705118256 / PLAIN PAPER COPIER HEAVY DUTY (PHOTO STATE MACHINE) F-8 |                 | 1 / EACH/NUMBER  | "E-STUDIO-2528A (25 CPM)" |             |           |              | delivery required at islamabad | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 88    | DGP64436 |                      | 0051500001082 / FORM F (NL)22 LEAVE TICKET                              |                 | 1720 / BOOK      |                           |             |           |              |                                | TECHNICAL SPECIFICATION - LENGTH 8" WIDTH 7" 60 GSM ± 5% White Color Paper printed With Black Ink 100 Pages (Book)<br>GENERAL SPECIFICATION - LENGTH 8" WIDTH 7" 60 GSM ± 5% White Color Paper printed With Black Ink 100 Pages (Book)  |           |
| 89    | DGP65528 |                      | 7490705055906 / SPIRAL BINDING MACHINE                                  | BINDING MACHINE | 1 / EACH/NUMBER  |                           |             |           |              |                                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 90    | DGP57845 |                      | 7510701005039 / UV Flexo Ink (Black Colour)                             |                 | 100 / KILOGRAMME |                           |             |           |              |                                | TECHNICAL SPECIFICATION - MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4. silian brand ink<br>PROPERTIES/CHARACTERISTICS: 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR. |           |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|--------|---------|-------------------|-------------|------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |        |         |                   |             |            |       |             |           |              |                | <p>DENOMINATION : PACKING TO BE PROVIDED IN LOWEST DENOMINATION OF KGS AS INK GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP. <u>GENERAL SPECIFICATION -</u> MANUFACTURED/ SOURCE: 1. TOYO INK CO, JAPAN/ EUROPE. 2. DAIHAN INK, KOREA. 3. PEONY PRINTING INK, CHINA. 4.silian brand ink</p> <p>PROPERTIES/CHARACTERISTICS: 1. UV OFFSET INK IS USED IN OFFSET PRINTING MACHINES I.E. STERAFLEX INK. 2. USED IN HIGH SPEED FLEXO PRESS MACHINES WITH GOOD FLOW PROPERTIES. 3. BRINGS SPEED, EFFICIENCY AND ECONOMY TO FLEXO PRINTING OPERATIONS. 4. STERO FLEX INK MATERIAL ALLOWS FLEXO PRINTERS TO ENHANCE CAPABILITIES OF HIGH RESOLUTION ANILOX AND COLOR INTENSITY. 5. EXCELLENT PRINTABILITY, FAST CURING, GOOD GLOSS, HIGH COLOR STRENGTH, VISCOSITY PROPERTIES FIT TO FLEXO PRINTING AND LOW ODOUR.</p> <p>DENOMINATION : PACKING TO BE PROVIDED IN LOWEST DENOMINATION OF KGS AS INK GETS DRIED UPON ONCE PACKING IS OPENED. CONDITION BY PN CENTRAL PRINTING PRESS: 1. PREFERABLY, UV</p> |           |

| S. No | LPR No   | PART NO                              | NSN / Description   | P/Equipment | QTY / DENO      | Model                          | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|--------------------------------------|---|-------------|-----------------|--------------------------------|-------------|-----------|---------------|----------------|--|-----------|
|       |          |                                      |   |             |                 |                                |             |           |               |                | FLEXO / STERAFLEX INK OF TOYO INK CO TO BE PURCHASED FOR BETTER RESULTS. 2. INK WILL BE ACCEPTED AFTER USING IN OFFSET PRINTING PRESS MACHINES AT PNCPP.   |           |
| 91    | DNF65723 | SMT3000I C/SURTD3 000XLI/30 00VA APC | 613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES. | SELF        | 1 / EACH/NUMBER | MODEL ESP-808 (E) /SYSTEK PVT. |             |           |               |                | <u>TECHNICAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u><br><u>GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES.CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL</u> |           |
| 92    | DGP65716 | NO DATA AVAILAB LE                   | 005050000009 7 / PAPER DUPLICATING  |             | 300 / REAM      | NO DATA AVAILAB LE             |             |           |               |                | <u>TECHNICAL SPECIFICATION - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u><br><u>GENERAL SPECIFICATION - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON</u>   |           |
| 93    | DGP65633 | NO DATA AVAILAB LE                   | 005050000009 7 / PAPER DUPLICATING  |             | 380 / REAM      | NO DATA AVAILAB LE             |             |           |               |                | <u>TECHNICAL SPECIFICATION - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70%</u>   |           |

| S. No | LPR No   | PART NO               | NSN / Description                         | P/Equipment | QTY / DENO    | Model                    | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------------|---|-------------|---------------|--------------------------|-------------|-----------|--------------|----------------|---|-----------|
|       |          |                       |   |             |               |                          |             |           |              |                | MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON  |           |
| 94    | DGP65738 | NO DATA AVAILAB<br>LE | 005050000009<br>7 / PAPER<br>DUPLICATING  |             | 360 /<br>REAM | NO DATA<br>AVAILAB<br>LE |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - Length: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: 70% MECH NATURAL COLOUR GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON |           |
| 95    | DGP65741 | NO DATA AVAILAB<br>LE | 0050500000022<br>3 / PAPER<br>DUPLICATING |             | 425 /<br>REAM | NO DATA<br>AVAILAB<br>LE |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON                                     |           |
| 96    | DGP65717 | NO DATA AVAILAB<br>LE | 0050500000022<br>3 / PAPER<br>DUPLICATING |             | 400 /<br>REAM | NO DATA<br>AVAILAB<br>LE |             |           |              |                | <u>TECHNICAL SPECIFICATION</u> - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING: 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON <u>GENERAL SPECIFICATION</u> - LENGTH: 11.69 INCH WIDTH: 8.27 INCH (A-4) PAPER COLOUR: WHITE GSM: 75 + 5% PACKING:  |           |

| S. No | LPR No   | PART NO       | NSN / Description  | P/Equipment | QTY / DENO        | Model              | SR NO OF PR | MANUF ADO | Availabilty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|---------------|--|-------------|-------------------|--------------------|-------------|-----------|-------------|----------------|---|-----------|
|       |          |               |  |             |                   |                    |             |           |             |                | 500 SHEET EACH REAM AND 06 REAM IN EACH CARTON  |           |
| 97    | DPK57386 | RENDER AR 100 | 8010745175628 / FOOD GRADE RENDER AR100 (Solventfree epoxy) (30kg packing) Brand = MAXPERLES |             | 18 / KILOGRAMME   | NO DATA AVAILAB LE |             |           |             |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |           |
| 98    | DCD49590 |               | 8455703901848 / BADGE ARM BLUE OD-II YARD CONSTRUCTION (C)                                   |             | 500 / EACH/NUMBER |                    |             |           |             |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |           |
| 99    | DRG60723 | SBA-185046150 | 6115705141589 / ALTERNATOR ASSY  |             | 1 / EACH/NUMBER   | NO DATA AVAILAB LE |             |           |             |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |           |
| 100   | DCD65697 |               | 8455703901766 / BADGE ARM MEDICAL OT MT-I RED EMBROIDRY                                      |             | 300 / EACH/NUMBER |                    |             |           |             |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |           |
| 101   | DGP65744 | nil           | 7520705259580 / PERSONEL FOLDER FOR RECORD KEEPING OF of pn civilians                        |             | 300 / EACH/NUMBER | nil                |             |           |             |                | <u>TECHNICAL SPECIFICATION - 1. SIZE OF FOLDER A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F.</u> |           |

| S. No | LPR No | PART NO | NSN / Description | P/Equipment | QTY / DENO | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|--------|---------|-------------------|-------------|------------|-------|-------------|-----------|--------------|----------------|--|-----------|
|       |        |         |                   |             |            |       |             |           |              |                | <p>FILE FASTNER INNER LINING:<br/> CARD BOARD THICK 2.5 MM ± 0.1 MM G. EYELETS: BLACK<br/> ALUMINIUM H. TAG COTTON:<br/> LENGTH 260 MM ALONG WITH IRON TIP WITH BLACK ENAMEL 3.<br/> NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I.<br/> FOR NAME TALLEY: 40 MM 65 MM I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUEGENERAL SPECIFICATION - 1. SIZE OF FOLDER A. LENGTH: 365 MM ± 1 MM B. WIDTH: 260 MM ± 1 MM C. WIDTH OF FOLDING PORTION: 35 MM ± 1 MM 2. MATERIAL: A. OUTER AND INNER COVER: TEXTURED RAXIN BEST QUALITY (NOT COMMERCIAL QUALITY) THICK 1 MM B. POCKETS: TRANSPARENT POLYTHENE THICK 0.1 MM C. INNER LINING OF BACK SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM ± 0.2 MM D. INNER LINING OF FRONT SIDE OF COVER: CARD BOARD HARD THICK 4.5 MM± 0.2 MM E. FILE FASTNER COVER WITH LINING: TEXTURED REXIN THICK 1 MM F. FILE FASTNER INNER LINING: CARD BOARD THICK 2.5 MM ± 0.1 MM G. EYELETS: BLACK</p> |           |



| S. No | LPR No   | PART NO      | NSN / Description                                     | P/Equipment | QTY / DENO        | Model | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension                                  |
|-------|----------|--------------|---|-------------|-------------------|-------|-------------|-----------|--------------|----------------|--|--|
|       |          |              |   |             |                   |       |             |           |              |                | ALUMINIUM H. TAG COTTON: LENGTH 260 MM ALONG WITH IRON TIP WITH BLACK ENAMEL 3. NO OF POCKETS: A. FRONT SIDE 02 POCKET: LENGTH WIDTH I. FOR NAME TALLEY: 40 MM 65 MM I. FOR PHOTOGRAPH: 70 MM 65 MM B. INNER POCKET LEFT HAND SIDE: 215 MM 260 MM C. INNER POCKET RIGHT HAND SIDE: 130 MM 260 MM D. BACK SIDE POCKET: 340 MM 260 MM E. SIDE POCKET ON FOLDING PORTION: 65 MM 35 MM 4. STITCHES BY : BY HEAT MACHINE 5. PRINTING I. PRINTING BY: BY FOIL PRINTING II. PRINTING COLOUR, WORD TITLE AND LOGO : AS PER APPROVAL BY CIVILIAN AUTHORITY 6. COLOUR OF REXIN : NAVY BLUE |  |
| 102   | DCC53088 |              | 8440501201024 / LANYARD PISTOL KHAKI                  |             | 100 / EACH/NUMBER |       |             |           |              |                | TECHNICAL SPECIFICATION - LANYARD PISTOL KHAKI<br>GENERAL SPECIFICATION - LANYARD PISTOL KHAKI   | The item is procured against stock sample. |
| 103   | DNF62194 | DS-6701HFHIV | 5895270684391 / HD ENDCODER (VIDEO COMPRATION DEVICE) |             | 3 / EACH/NUMBER   | N/A   |             |           |              |                | TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM   |  |

| S. No | LPR No   | PART NO                     | NSN / Description   | P/Equipment | QTY / DENO               | Model                    | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-----------------------------|---|-------------|--------------------------|--------------------------|-------------|-----------|---------------|----------------|---|-----------|
|       |          |                             |   |             |                          |                          |             |           |               |                | 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.   |           |
| 104   | DCD65733 |                             | 845570390177<br>1 / BADGE<br>ARM MEDICAL<br>PHYSIO LMT<br>RED<br>EMBROIDRY            |             | 300 /<br>EACH/N<br>UMBER |                          |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>null <u>GENERAL SPECIFICATION -</u><br>null   |           |
| 105   | SRP52808 | S737<br>(PACKING<br>2.5 LI) | 681099224562<br>8 / ALCOHOL<br>ISOPROPYLE<br>(ISOPROPANO<br>L) AR GRADE               |             | 100 /<br>LITER           | NO DATA<br>AVAILAB<br>LE |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>BRITSH APPROVED BS.1595, US<br>EQUIVALENT TT-I-735A GRADE B,<br>FRENCH EQUIVALENT TI<br>AIR3660/A, JOINT SERVICE<br>DESIGNATION AL-11 NATO CODE<br>S-737 <u>GENERAL SPECIFICATION -</u><br>BRITSH APPROVED BS.1595, US<br>EQUIVALENT TT-I-735A GRADE B,<br>FRENCH EQUIVALENT TI<br>AIR3660/A, JOINT SERVICE<br>DESIGNATION AL-11 NATO CODE<br>S-737 |           |
| 106   | DCD44994 |                             | 845550070046<br>7 / BADGE<br>SHOULDER<br>CRESCENT<br>AND STAR<br>FOR MCPO<br>dress 03 |             | 700 /<br>PAIR            |                          |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>BADGE SHOULDER CRESCENT<br>AND STAR FOR MCPO DRESS<br>03 <u>GENERAL SPECIFICATION -</u><br>BADGE SHOULDER CRESCENT<br>AND STAR FOR MCPO DRESS 03  |           |
| 107   | DCD57442 |                             | 845550070046<br>7 / BADGE<br>SHOULDER<br>CRESCENT<br>AND STAR<br>FOR MCPO<br>dress 03 |             | 700 /<br>PAIR            |                          |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>BADGE SHOULDER CRESCENT<br>AND STAR FOR MCPO DRESS<br>03 <u>GENERAL SPECIFICATION -</u><br>BADGE SHOULDER CRESCENT<br>AND STAR FOR MCPO DRESS 03  |           |
| 108   | DCD27013 |                             | 845570390181<br>0 / BADGE<br>ARM MEDICAL<br>PHY MT-ii<br>VELCRO BASE                  |             | 300 /<br>EACH/N<br>UMBER |                          |             |           |               |                | <u>TECHNICAL SPECIFICATION -</u><br>null <u>GENERAL SPECIFICATION -</u><br>null   |           |

| S. No | LPR No    | PART NO          | NSN / Description   | P/Equipment | QTY / DENO        | Model | SR NO OF PR | MANUF ADO | Availabili ty | Tender Remarks | TECH / GEN SPECS   | Dimension                                  |
|-------|-----------|------------------|---|-------------|-------------------|-------|-------------|-----------|---------------|----------------|--|--|
|       |           |                  | WITH PLAIN GREY BASE CLOTH AND BLACK EMBROIDERY   |             |                   |       |             |           |               |                |  |  |
| 109   | DNC594 11 | TM-C-S02         | 252073523768<br>2 / CARDAN SHAFT  |             | 2 / EACH/NUMBER   | HJ322 |             |           |               |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |  |
| 110   | DCD657 34 |                  | 845570390177<br>2 / BADGE ARM MEDICAL PHYSIO ARTIFICER RED EMBROIDRY  |             | 300 / EACH/NUMBER |       |             |           |               |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |  |
| 111   | DNH574 81 | 65605003         | 422073528084<br>8 / 4TH STAGE CYLINDER  |             | 1 / EACH/NUMBER   | NA    |             |           |               |                | TECHNICAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosed<br>GENERAL SPECIFICATION - HOLUGT-SAUER , BREATHING AIR COMPRESSOR, MODEL HL 500-600, HOLLAND as per enclosed   |  |
| 112   | DCD495 84 |                  | 845570390185<br>8 / BADGE ARM YARD LDG ELECTRICAL (L) VELCRO BASE WITH PLAIN GREY BASE CLOTH AND BLACK EMBROIDERY |             | 500 / EACH/NUMBER |       |             |           |               |                | TECHNICAL SPECIFICATION - MATERIAL 100% COTTON COUNT OF YARN WARP 20+2 (29.5+2 TEX) WEFT 16+2 (37 + 2 TEX) COLOR SHADE PANTON SHADE BLACK EMBROIDERY<br>GENERAL SPECIFICATION - MATERIAL 100% COTTON COUNT OF YARN WARP 20+2 (29.5+2 TEX) WEFT 16+2 (37 + 2 TEX) COLOR SHADE PANTON SHADE BLACK EMBROIDERY |  |
| 113   | DCC512 36 |                  | 844070329138<br>4 / GLOVES FIRE RETARDANT SIZE LARGE  |             | 200 / PAIR        |       |             |           |               |                | TECHNICAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE LARGE<br>GENERAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE LARGE   | the item is procured against stock sample. |
| 114   | DRG607 39 | SA10929 (287548) | 294001484134<br>4 / AIR CLEANER ELEMENT   |             | 4 / EACH/NUMBER   | 0     |             |           |               |                | TECHNICAL SPECIFICATION - AS PER PUBLICATION<br>GENERAL SPECIFICATION - AS PER PUBLICATION   |  |

| S. No | LPR No   | PART NO            | NSN / Description   | P/Equipment | QTY / DENO        | Model             | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|--------------------|---|-------------|-------------------|-------------------|-------------|-----------|--------------|----------------|---|-----------|
|       |          |                    | HOBERT GPU  |             |                   |                   |             |           |              |                |   |           |
| 115   | DRG59991 | T400268 (2873K621) | 6105715159630 / STARTER MOTOR                                   |             | 1 / EACH/NUMBER   | 0                 |             |           |              |                | TECHNICAL SPECIFICATION - AS PER PUBLICATION GENERAL SPECIFICATION - AS PER PUBLICATION   |           |
| 116   | DCD65696 |                    | 8455703901765 / BADGE ARM MEDICAL OT MT-II RED EMBROIDRY        |             | 300 / EACH/NUMBER |                   |             |           |              |                | TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null  |           |
| 117   | DCD65731 |                    | 8455703901769 / BADGE ARM MEDICAL PHYSIO MT-II RED EMBROIDRY    |             | 300 / EACH/NUMBER |                   |             |           |              |                | TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null  |           |
| 118   | DNF64871 | 03-00-0623-00      | 6350715300703 / DAS BOARD 3.2                                   |             | 1 / EACH/NUMBER   | 1.2 XIS-6545      |             |           |              |                | TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null  |           |
| 119   | DCD65698 |                    | 8455703901767 / BADGE ARM MEDICAL OT LMT RED EMBROIDRY          |             | 300 / EACH/NUMBER |                   |             |           |              |                | TECHNICAL SPECIFICATION - nullGENERAL SPECIFICATION - null  |           |
| 120   | DGD55632 | pp-01              | 7320705269666 / POTATO PEELER                                   |             | 2 / EACH/NUMBER   | pp-01             |             |           |              |                | TECHNICAL SPECIFICATION - capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor GENERAL SPECIFICATION - capacity: 15kg, power: 1500w, voltage: 220v/50hz, net weight: 62kg, dimension: 18x30x26 inch, heavy duty full load 1.5hp motor |           |
| 121   | DRG60015 | 4036335 (4766127)  | 6105ZO6574044 / ALTERNATOR (FIAT AGRICULTURE TRACTOR MODEL 640) |             | 1 / EACH/NUMBER   | NO DATA AVAILABLE |             |           |              |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 122   | SNH56812 | 244862             | 5330785283914 / PACKING VEE,                                    |             | 10 / PACKET       | 70:1              |             |           |              |                | TECHNICAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO   |           |

| S. No | LPR No   | PART NO       | NSN / Description   | P/Equipment | QTY / DENO        | Model                        | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS   | Dimension |
|-------|----------|---------------|---|-------------|-------------------|------------------------------|-------------|-----------|--------------|----------------|--|-----------|
|       |          |               | TUFFSTACK (PISTON)  |             |                   |                              |             |           |              |                | PREVENT/STOP LEAKAGE OF LUBRICANTS<br>GENERAL SPECIFICATION - CARBON FILLED PTFE. VEE PACKING USED TO PREVENT/STOP LEAKAGE OF LUBRICANTS |           |
| 123   | DRG60651 | 1036735-P5    | 6115016037416 / ALTERNATOR (GENERATOR SET DIESEL ENGINE) CAGE50036    |             | 2 / EACH/NUMBER   | N/A                          |             |           |              |                | TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -  |           |
| 124   | DNZ65782 | bv650i-msx    | 6150ZO5248793 / apc ups 650 va  |             | 7 / EACH/NUMBER   | apc ups 650 va<br>bv650i-msx |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |
| 125   | DRG60742 | ZO6568002     | 4720ZO6568002 / NYLON HOSE WITH APPROPRIATE FITTING 1/4 INCH          |             | 2 / EACH/NUMBER   | LENAAR DO                    |             |           |              |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE   |           |
| 126   | DRG60738 | SBA-185086141 | 6105ZO6567828 / MOTOR ASSY STARTING COMPLETE                          |             | 1 / EACH/NUMBER   | NO DATA AVAILABLE            |             |           |              |                | TECHNICAL SPECIFICATION - ALLIED AGRICULTURAL TRACTOR MODEL 1910<br>GENERAL SPECIFICATION - ALLIED AGRICULTURAL TRACTOR MODEL 1910       |           |
| 127   | DNF57499 | rm 10-hf      | 5810735248460 / modem-1/ RM10 Wideband SDM - WBHF Modem (MS-188-110C) |             | 1 / EACH/NUMBER   | RM 10-HF                     |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |
| 128   | DCD65732 |               | 8455703901770 / BADGE ARM MEDICAL PHYSIO MT-I RED EMBROIDRY           |             | 300 / EACH/NUMBER |                              |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |
| 129   | DNQ64387 | 334 series    | 4240715269613 / 3m safety goggles                                     |             | 40 / EACH/NUMBER  | 334 series                   |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null   |           |

| S. No | LPR No   | PART NO           | NSN / Description  | P/Equipment | QTY / DENO       | Model             | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension |
|-------|----------|-------------------|--|-------------|------------------|-------------------|-------------|-----------|--------------|----------------|---|-----------|
| 130   | DRG59988 | 7208223 (4737755) | 2920151013165 / STARTER MOTOR  |             | 1 / EACH/NUMBER  | NO DATA AVAILABLE |             |           |              |                | TECHNICAL SPECIFICATION - NO DATA AVAILABLE<br>GENERAL SPECIFICATION - NO DATA AVAILABLE  |           |
| 131   | DNF61606 | dem-310gt         | 5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT) |             | 2 / EACH/NUMBER  | dgs-1510-28x      |             |           |              |                | TECHNICAL SPECIFICATION - null<br>GENERAL SPECIFICATION - null  |           |
| 132   | DGD55619 | d-523             | 7310705269679 / CUTTING BOARD  |             | 50 / EACH/NUMBER | d-523             |             |           |              |                | TECHNICAL SPECIFICATION - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2" GENERAL SPECIFICATION - hard polypropylene material, thickness: 2cm Dimension of Item: 26"x13"x 1/2"   |           |
| 133   | DNF63319 | ub500 / SA300     | 6350785246359 / WALK THROUGH GATE WITH MONITOR & FACE CAPTURE CAMERA model no: ub500   |             | 1 / EACH/NUMBER  | ub500             |             |           |              |                | TECHNICAL SPECIFICATION - ITEM PROCURE P/NO. SA300 VIDE CONT.2220159/R-2301/310590 DT22-6-24 OEM, SECURINA DETECTION SYSTEM CO LTD. SHENZHEN CHINA.<br>GENERAL SPECIFICATION - ITEM PROCURE P/NO. SA300 VIDE CONT. 2220159/R-2301/310590 DT22-6-24 OEM, SECURINA DETECTION SYSTEM CO LTD. SHENZHEN CHINA. |           |
| 134   | DCD65671 |                   | 8455500700468 / BADGE SHOULDER TWO STAR FOR FCPO DRESS 03  |             | 500 / PAIR       |                   |             |           |              |                | TECHNICAL SPECIFICATION - BADGE SHOULDER TWO STAR FOR FCPO DRESS 03<br>GENERAL SPECIFICATION - BADGE SHOULDER TWO STAR FOR FCPO DRESS 03  |           |

| S. No | LPR No   | PART NO   | NSN / Description  | P/Equipment | QTY / DENO        | Model       | SR NO OF PR | MANUF ADO | Availability | Tender Remarks | TECH / GEN SPECS  | Dimension                                  |
|-------|----------|-----------|--|-------------|-------------------|-------------|-------------|-----------|--------------|----------------|---|--|
| 135   | DCD65699 |           | 8455703901768 / BADGE ARM MEDICAL OT ARTIFICER RED EMBROIDRY |             | 300 / EACH/NUMBER |             |             |           |              |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |  |
| 136   | DNM53865 | 29010560  | 4710735281473 / HYDRAULIC PIPE L=564                         |             | 2 / EACH/NUMBER   | KESLA 204T  |             |           |              |                | <u>TECHNICAL SPECIFICATION - null</u><br><u>GENERAL SPECIFICATION - null</u>  |  |
| 137   | DNF59086 | 8237-1177 | 2815735289116 / TURNER PCB CONTROL UNIT (733 CONTROL)        |             | 1 / EACH/NUMBER   | 733-CONTROL |             |           |              |                | <u>TECHNICAL SPECIFICATION - 733 control containing TECS software reference as 733-LS) i. Temperature range -40°C to 100°C ii. Voltage input 18 V to 32 V DC, Nominal) iii. Input power 20 watt maximum continuous Main function: i. Speed synchronization ii. Load sharing</u><br><u>GENERAL SPECIFICATION -733 control containing TECS software reference as 733-LS) i. Temperature range -40°C to 100°C ii. Voltage input 18 V to 32 V DC, Nominal) iii. Input power 20 watt maximum continuous Main function: i. Speed synchronization ii. Load sharing</u> |  |
| 138   | DCC51235 |           | 8440703291385 / GLOVES FIRE RETARDANT SIZE MEDIUM            |             | 100 / PAIR        |             |             |           |              |                | <u>TECHNICAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE MEDIUM</u><br><u>GENERAL SPECIFICATION - GLOVES FIRE RETARDANT SIZE MEDIUM</u>  | the item is procured against stock sample. |
| 139   | DPC59036 |           | 0474504740012 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)          |             | 10 / EACH/NUMBER  |             |             |           |              |                | <u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u><br><u>GENERAL SPECIFICATION - NO DATA AVAILABLE</u>  |  |