OPENING ON 17-09-2024 ARF/1169/T/PC-002/LOG/2024-25 DATED 02-09-2024 Organization Pakistan Aeronautical Complex Name AIRCRAFT REBUILD FACTORY PAC Address Kamra City 051-90992442 Tel No. 1. Quotations will be opened on 17 September, 2024 at 10:30 Hrs by the committee in the presence of the interested bidders, or their authorized representatives. 2. Quotation must be typed, hand written, Photocopies, E-mail & Conditional quotation will not be accepted. 3. Separate sealed technical quotes and Commercial quotes both must be deposited in 2 separate envelopes. Rates should be quoted both in words and figures clearly at commercial quotes with unit price. 4. All quotations (Category wise) must be put in separate sealed envelope. There should be no mixing of rates and quotations (Technical quotations with Commercial quotations). More than one quotation in one envelop will be rejected. 5. Technical offers should be without prices and contain all relevant essential specification along with literatures / brochures. Tender number, date of opening and word (Technical offer) should be clearly marked on the face of envelopes. Commercial offers should indicate prices of quoted items and confirmation to the terms and condition of our tender inquiry. Tender No. and words "Commercial offer" be marked on the face of envelope. 6. Income tax, sales tax and professional tax certificates duly attested by the concerned authority must be attached with quotations. 7. All the rates must be valid till 30 June, 2025 otherwise quotation will not be entertained. Only one offer can be made in relevant currency for same item. Multiple rates, if quoted, will be rejected. Taxes will be imposed as per GOVT: policy and directive issued from time to time. 8. All items/chemicals should be provided with COC (Certificate of Conformance), MSDS (Material Safety Data Sheet) and TDS (Technical Data Sheet) and within expiry life of minimum 02 Years. Terms & Conditions The bidder must have a branch office with valid Telephone and fax facility. Sample must be presented before technical opening. 11. Tender detail is available in the office of O i/c Local Purchase and can be collected during working days from 0900-1200 hours. 12. The bidder must be the manufacturer of the products. The ordered stores will be accepted by concerned technical user and our quality department along with warranty 13. The quantities are estimated and may increase/decrease with respect to the requirements. 14. The procuring agency may reject all bids/proposals or bid/proposal pertaining to a specific supplier at any time prior to tender opening. The procuring agency upon request of Supplier / Vendor / Contractor will communicate the reason for rejection of quotations.

- 15. Payment on delivery will be made through cheque against sales tax invoice only.
- 16. Tenders are to be addressed to Director Logistics, Aircraft Rebuild Factory PAC Kamra. The quoted prices must be without GST and envelope must be marked with "TENDER FOR PROCURMENT of "Category-01 to Category-09". Tenders received through fax shall not be accepted.
- 17. The Earnest money @ 5% (not exceeding 0.150 M) will be deposited by all firms irrespective of registration status in favour of Managing Director ARF in the form of CDR at the time of opening tenders in, separate envelope. Earnest money will remain deposited till the finalization of commercial quotes. It will be returned to unsuccessful bidders immediately after finalization of commercial quotes. Quotation without earnest money will be rejected.
- Delivery period should not be more than two weeks.
- 19. Firm should be on ATL of FBR and will provide proof with quotation. Order should be placed and subsequently payment would be released to the firm which is on ATL of FBR.
- 20. All matters connected with this inquiry and subsequent actions arising thereafter fall within the scope of the Pakistan Official Secret Act 1923 which forbid providing contractual information to unauthorized / unconcerned person/organization. The firm is therefore, requested to ensure complete secrecy regarding documents and stores concerned with the inquiry to limit the number of employees having access to this information.

×	(a)There is deviation from any (b)Offers are found conditional (c)Multiple rates are quoted at (d)Manufacturer relevant brook (e)Offer received later than application of the specifications different from the (g)Offer subject to restriction (h)Over writing /erasing in prick (j)Validity of offer is not quoted (k)Earnest money not provide 22.TERMS AND CONDITION (a) Items to be delivered at A (b) Store must be of latest prick (a) (c) Multiple (c) (d) (d) (d) (d) (d) (d) (d) (d) (d) (d	chure is not attached (in case of equipment or major assemblies of equipment). Depointed time and date. Onfirming to the offer. In case of equipment/ major assemblies manufacturer's brochunose given in tender. Of Export License. Des. If as required in IT or made subject to confirmation letter. If as required in IT or made subject to confirmation letter. If as required in IT or made subject to confirmation letter. If an "FOR" Kamra basis. Oduction series (FN).			g es A/R A/R A/R A/R
	transportation.	ould be adequately done with absolute resistant material so as to avoid from any dam- accordance with standard specification provided in the Published Tender at consigner and quality inspector. kimum OEM warranty.		uring mises I Qty A/R A/R	
Closing Time	10:00:00 am				
Opening Time	10:30:00 am				
Bid Validity	30/06/2025				
Remarks	ARF PAC KAMRA				
		ARF/1169/1/T/PC-002			
S No	Part No	Noun	U/	I Q	ty
CATEGORY-01 CH	HEMICAL STORE				
1	5850-68-900-0233	PAINT MIXER Specifications:- Blairtornadoic: Portable, .5400 Twin arm 1 gal shaker or Equalient	EA	. A	R
CATEGORY-02 CR	ISES CONTROL CENTRE (SRT)				_
1	7430-68-900-0852	UPS WITH 1.5 HRS BATTERY BACKUP FOR CONTROL ROOM Specifications:- UPS 5KVA: Output power capacity: 4.0 Kwatts / 5.0 KVA, Input, voltage 160 to 240 V, Nominal Output Voltage: 220 to 230V, Output Voltage Distortion: Less than 5% at full load, Output Frequency (sync to mains): 47-53 Hz for 50 Hz nominal, 57-63 Hz for 60 Hz, nominal, Online, Pure sine wave, LCD display, 1.5 Hrs Backup with maintenance free batteries.	EA	A/F	R
2	5805-68-900-0090	UPS 1KVA Specifications:- Output power capacity 700 watt input voltage 150 to 220 VAC, Normal output voltage 220 to 230 VAC. Output voltage distortion less than 5% at full load, Output Frequency (sync to main) 47 to 53 Hz, for 50 HZ nominal, 57-60 Hz for 60 HZ, nominal online pure sine wave LCD display built in AVR, with 1* 150AH maintenance free battery.	EA	AVF	₹
3	5805-68-900-0160	NVR 64 CHANNEL	EA	A/F	1
CATEGORY-03 AIR	FRAME ACCESSORY SHOP I (AA)				
1	YF105-AGSC3	VERTEX FLOW METER	EA	A/R	
CATEGORY-04 MAG	GNETIC PARTICLE INSPECTION (ME	اراح			-
1	MR-502K	MAG RUBBER	EA	A/R	
CATEGORY-05 PRO	OVOST SQUADRON				1
1	HEDD1	EXPLOSIVE DETETOR	EA	A/R	1
2	9999-68-400-0043	ARMORED GUARD POST Specifications: 1. Length (with AC): 1.46M (4'-7")(55') 2. Length (with out AC width: 1.47M (7') (84") 3. Ballistic protection: 7.2mm NATO (B-6/B-7 level) 4. Weight: 1400-1700 Kgs 5. Firing Ports: Sliding Two on each wall 6. Rifle Rack: Provided (for 7.62mm)	EA	A/R	

1	FO1VIO8954VS05	PRO POWER MATE MIXER (DYNACORD 1800 WATTX2)	EA	A/F
ATEGORY-07 CO	MM CENTER			
1	6145-600-900-0158	UNDER GROUND CABLE 30 PAIR .6MM ARMOURED Specifications: Copper Conductor: 0.6MM Armored, Insulation: Colour High Molecular Weigh Solid High-Density Polyethylene (HDPE), Suitable Applications: For telecommunications system, Colour Coding: Cables should be fully colour coded in accordance with PIC even count colour code, Pairing twisted: Two coloured insulated conductors should be uniformly, Filling Compound: Water resistant filling compound should be applied, Core Covering: A Non-hygroscopic and dielectric heat resistant Polyester Tape and water blocking should be applied helically having a suitable overtap, Flood Compound: Sufficient Flooding compound should be applied between core wrap and shield, Moisture Barrier Inner Sheath: An Aluminum tape with co-polymer coating should be applied over the cable core and sheath with black Polyethylene compound, Armour: A Tin coated corrugated steel tape should be applied longitudinally directly over te Inner sheath with suitable flooding compound.	MTR	A/R
CATEGORY-08 HM	& RC (HS)			
1	55A1131-24-9/96/93-9	WIRE	MTR	A/R
ATEGORY-09 FIR	E FLIGHT			
Ä	21-F/797	"CO2 Trolly Wheel mounted (02x7Kg) Specifications: 1. Co2 Gas Trolley Wheel Mounted (02x06/07 Kg Co2 Cylinder): PAF Standard 2. Co2 Cylinders: Qty-02x06/07 Kg each 3. Body: Made of seamless drawn steel 4. Testing Pressure: 230 Bar 5. Bursting Pressure: 476 Bar 6. Valves Assembly: Controlled wheel type release valves for Co2 Cylinders 7. Carriage MK-II: From fabricated M.S Flat bar thickness 3/08"" with metal covered 8. Wheel Nylon 12"": Qty-02 complete with C.I plate fitted both side with 02 seated 9. High Pressure Hose: Six feet double wire breaded bore 5/16"" complete with both stainless steel fitting / coupling is to provide 10. Manifold discharge: Complete manufactured from solid bar of stainless steel 11. Tube Applicator: Complete manufactured from seamless stainless steel tube in 03 parts with breather hole 12. Empty weight of Co2 Cylinders: As per OEM standard 13. Co2 Gas weight: 06/07 Kg each 14. Total Weight: Empty + Co2 Gas weight 15. Hydrostatic: Both Co2 cylinders should be hydrostatically tested (Testing year engraved on cylinder body) 16. Hydrostatic Test Certificate: Hydrostatic Test Certificate is also required 17. Marking as per British standard: BS- 5423/87, manufacturing month/year, Testing/Bursting pressure, empty and total weight of cylinder should be engraved on cylinder body 18. Colour: Red, 19. Material: As pe BS-5045/7, 20. Discharged Horn: It is constructed of metal and fitted with tube applicator."	EA	A/R