

DATE & TIME 9/30/24 10:18 AM

INVITATION TO TENDER TO BE OPENED ON 10/14/ 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.

2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.

3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	PI Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	SNF51953	0102-034009-226	592578515447 8 / SINGLE POLE BREAKER 4AMP 220V AC	L/PAC	120 / EACH/NUMBER	CHNT-C4 CHNT SINGLE POLE	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674. SPEC.COIL VOLTAGE 220V AC.GENERAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674. SPEC.COIL VOLTAGE 220V AC.	
2	DNO47401	545-9773	294077526649 7 / CIRCUIT BREAKER (20- AMPERE,2- POLE)		5 / EACH/NUMBER	3516E					TECHNICAL SPECIFICATION - CIRCUIT BREAKER (20- AMPERE,2- POLE)GENERAL SPECIFICATION - CIRCUIT BREAKER (20- AMPERE 2- POLE)	
3	DNZ63244	3050944	533001496433 8 / FLANGE GASKET	Cummins QSK 38 OM Main Engine	1 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
4	DNF59977	0103-034021-249	608578515449 7 / THERMOCOUPLE 6M	H/PAC	10 / EACH/NUMBER	FKE 6M		ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674	CHINA		TECHNICAL SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY:ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674. GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY ALPINE INDUSTRIAL CON PVT LTD 365/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042- 6852313,6862490 FAX:92- 426553674	
5	DPK83854	SAE 75W-90	915001363119 2 / LUBRICANT OIL MOBIL 1 SHC (TRANSMISSION OIL) (Packing 20 Liters Drum)	ENGINE	120 / LITER	NO DATA AVAILABLE		US		M/S MOBILE OIL CORPORATION & GOVERNMENT SALES DIVISION 3225 GALLOWSD RD FAIR FAX VA USA 22037- 4090 TEL 703-846- 4090 IDNS: 00129483 4	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
6	SGB47306		055470522134 7 / CARBON STEEL ELECTRODE ZODIAN E- 6013 SIZE 2.5 MM	WELDING RECTIFIER YPK1511611 LINDE	200 / KILOGRAMME	AWS A/SFA 5.1-91. E 6013	R3R 5001	Linde Pakistan Ltd PO BOX N4845 Dockyard Road west wharf KARACHI 74000 PAKISTAN TEL 021111267725 FAX NO +922132312968 E-Mail:customerservice. pk@linde.com		LINDE PVT LTD	TECHNICAL SPECIFICATION - DIA: 2.5 MM, SPECS: AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-500 N/mm2 Yield Power: 380 N/mm2, Elongation: 24.0%, Charpy V impact values at 0 degrees Celsius: minimum 47 (joules) Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to 0.40 %, S 0.03 Max. P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range acidic and type of DCEP/DCEN, Welding all on	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
											positions. Welding arc, Spatter, Flow of welding, Penetration, Finishing of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013	
											GENERAL SPECIFICATION - DIA 2.5 MM, SPECS. AWS A/SFA 5.1-91, E 6013, Type: Rutile-cellulosic electrode AC, DCEP or DCEN, OEM: PAKISTAN OXYGEN Tensile strength: 470-600 N/mm ² , Yield Power: 380 N/mm ² , Elongation: 24.0%, Charpy V impact values at 0 degree Celsius: minimum 47 (joules). Chemical Composition: C 0.04 to 0.10 %, Mn 0.30 to 0.60 %, Si 0.20 to 0.40 %, S 0.03 Max, P 0.03 Max. Acceptance Criteria: Electrode diameter and length, Welding current range acidic and type of DCEP/DCEN, Welding all on positions, Welding arc, Spatter, Flow of welding, Penetration, Finishing of welding bead/ line, Removal of slag, Band test, Availability of data sheet/ OEM certificate. AWS A/SFA 5.1-91, E 6013	
7	SNM55104	215-9509	473001579602 5 / FITTING (QUICK DISCONNECT MALE)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1/ EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 810 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> <u>GENERAL SPECIFICATION -</u>	
8	SNM59318	61-0593	530671522854 6 / BOLT (M10X1.5X30- MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	1/ EACH/N UMBER	N/A	E3S01292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE,ENGINE DIVISION MOSSVILLE BLDG AC P.O.BOX 810 MOSSVILLE,ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		<u>TECHNICAL SPECIFICATION -</u> Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.15 Thread: Coarse Thread Size (in - TPI) (in): M10-1.5 Hex Size (in): 0.51 Material Description: Steel <u>GENERAL SPECIFICATION -</u> Bolt Length (in): 1.18 Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in):	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
9	SNM69313	7K-1181	281501053471 2 / STRAP-CABLE	CATTER PILLER GENSET 3512B USA	1 / EACH/NUMBER	3512B	BS500558 BS500559	CATTER PILLER INC 100 N. E ADAMS STREET PEORIA IL 61628 USA	CATTER PILLER USA		0.15 Thread: Coarse Thread Size (in - TP) (in). M10-1.5 Hex Size (in). 0.51 Material Description: Steel <u>TECHNICAL SPECIFICATION -</u> STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): 19 - 4.00 <u>GENERAL SPECIFICATION -</u> STANDARD COLOR: NATURAL STRAP WIDTH (IN): 0.3 NOTES: OVERALL LENGTH: 387 HEAD TYPE: STANDARD BUNDLE DIAMETER RANGE (IN): 19 - 4.00	
10	DGE58384	11-1-3957-3	402001338330 9 / FAST ROPE ASSEMBLY, INSERTION AND EXTRACTION (LENGTH 120 FT)		7 / ROLL	NO DATA AVAILABLE		US	ELITE TACTICAL SOURCE INC-106 ANGEL LINE DRIVE, NC 2873, SERVICE @ ELITETACTICAL SOURCE.COM		<u>TECHNICAL SPECIFICATION -</u> 1. SPEC: MIL-F-44422 2. Length: 120 Ft, White Extraction Loops Rope, 3. Material: Nylon, 4. Dia: 0.562 inch, 5. Breaking Strength: 35,000 LBS, 6. Shelf Life: 10 YRS, 7. Country Of Origin: USA 8. OEM COC: Required, 9. Lloyd's/BSI Test Certificate is Required, 10. OEM Address: United States Department of the DBA, US Army, Natick Soldier System, Div Natick Soldier Research, Development and Engineering Center, USAGENERAL <u>SPECIFICATION -</u> 1. SPEC: MIL-F-44422 2. Length: 120 Ft, White Extraction Loops Rope, 3. Material: Nylon, 4. Dia: 0.562 Inch, 5. Breaking Strength: 35,000 LBS, 6. Shelf Life: 10 YRS, 7. Country Of Origin: USA 8. OEM COC: Required, 9. Lloyd's/BSI Test Certificate is Required, 10. OEM Address: United States Department of the DBA, US Army, Natick Soldier System, Div Natick Soldier Research, Development and Engineering Center, USA	
11	DNF57816	121488/5P X300 QIRTNQ2/	619072517108 1 / UPS 3 KVA	N/A	2 / EACH/NUMBER	MLM-203 /DH2024		GERMANY	GERMANY		<u>TECHNICAL SPECIFICATION -</u> MODEL MLM-203 /DH2024 BACK UP REQUIREMENT <= 8 HOURS	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / QEND	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		MLM-203 /DH2024									POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT GENERAL SPECIFICATION - MODEL MLM-203 /DH2024 BACK UP REQUIREMENT 4-8 HOURS POWER SUPPLY 220/230/240 VOLT PLUS MINUS 10 PERCENT	
12	SNM585 48	067-8085	281579522955 6 / ROD	33KVA CATERPILLER DG DEO33EO LK	12 / EACH/NUMBER	DEO33EO	E3G0423 9/E3G042 38/E3G04 237/E3G0 4236	CATTERPILLER SAREL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT		CATTERPILLER U. K	TECHNICAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel GENERAL SPECIFICATION - Weight: 0.2 lbs (0.1 kg) Length: 14 in (35.56 cm) Height: 3 in (7.62 cm) Width: 0.5 in (1.27 cm) Material: Alloy Steel	
13	DNS654 53	976039	533014547743 5 / O-RING	VOLVO PENTA SSDG D9A2A MG HE SWEDEN	10 / EACH/NUMBER	D9A MG HE	SEE GEN SPECS	AB Volvo Penta SE-405 08 Göteborg, Sweden Tel: +46 31 23 54 60		AB Volvo Penta Sweden	TECHNICAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT) GENERAL SPECIFICATION - MADADGAR 1009155503(STBD) 1009155425(PORT) RASADGAR 1009161287(STBD) 1009161290 (PORT)	
14	SPK5906 1		815073515984 5 / GREASE MOBILUX 3 (PACKING 16 OR 18 KG)	GREASE	48 / KILOGRAMME			WARTSILA FINLAND OY, SHIP POWER PH NO- 358107090000		MARELLI MOTOR) SPA	TECHNICAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER PH NO- 358107090000 GENERAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER PH NO-358107090000	
15	SNF5212 0	DCC/HFB M/HW/119	705070521567 7 / HDMI CABLE 25MTR FIBER OPTIC	OPERATOR CONSOLE DCC-2016 PAKISTAN	5 / EACH/NUMBER	NA	NA	Commercially Of The Shelf (COTS)/Local Market		COTS	TECHNICAL SPECIFICATION - DISPLAY CABLE GENERAL SPECIFICATION - DISPLAY CABLE	
16	SGB494 09		027770277004 1 / SPANNER FIXED DOUBLE ENDED OPEN JAW 18MM & 19MM	PAK PATTERN (GENERAL USE)	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	Pr/Equipment	QTY / DENO	Modal	SR NO OF PR	MANLIF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
17	SNM49684	7961447	130879489002 3 / FILTER-ELEMENT		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
18	SNM52398	4L-9852	294000074358 4 / AIR FILTER ELEMENT	CATER PILLER D/G (USA)	11 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
19	DNH67371	319-950882	343173505776 9 / WELDING RECTIFIER, W/CART. WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT	USED WELDING SHOP DOCKYARD	3 / EACH/NUMBER	LINC 635-SA					TECHNICAL SPECIFICATION - WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /360 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At 35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 GENERAL SPECIFICATION - WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /360 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At 35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 A	
20	DNH67432	319-950882	343173505776 9 / WELDING RECTIFIER, W/CART. WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT	USED WELDING SHOP DOCKYARD	1 / EACH/NUMBER	LINC 635-SA					TECHNICAL SPECIFICATION - WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /360 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 A</p> <p>AGENERAL SPECIFICATION:- WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /380 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At 35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 A</p>	
21	DNH670 12	319- 950882	343173505778 9 / WELDING RECTIFIER, W/CART, WITH 5 METER MAINS CABLE & 500AMP/30M/5 0 SQ MM STICK WELDING KIT	USED WELDING SHOP DOCKYARD	1/ EACH/N UMBER	LINC 835- SA					<p>TECHNICAL SPECIFICATION:- WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /380 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At 35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 A</p> <p>AGENERAL SPECIFICATION:- WELDING RECTIFIER, W/CART, I/P 380/440V/3P/50/60HZ, O/P 600AMP/35% WITH 5 METER MAINS CABLE & 500AMP/30M/50 SQ MM STICK WELDING KIT TECHNICAL SPECIFICATION Description Range a. Input Current Type: 220 /380 /400 /415 V 3 Phase 50/60 Hz b. Rated Output: 1. At 44 V RANGE: 600 A 35 % Duty cycle 2. At 35 V RANGE: 375 A 10 % Duty cycle c. Current Range: 50-625 A</p>	
22	DGP671 71	G2102560 EU	361070509130 4 / SHREDDING MACHINE		1/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION:- TECHNICAL SPECS/FEATURES/BENEFITS: 1 SHRED SIZE 4 x45mm Confetti</p>	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GBC DUO (SHRED MASTER)								<p>Cut. 2. SHRED SPEED: 2.5/M MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs</p> <p><u>GENERAL SPECIFICATION - TECHNICAL SPECS/FEATURES/BENEFITS:</u> 1. SHRED SIZE: 4 x 45mm Confetti Cut, 2. SHRED SPEED: 2.5/M MIN, 3. DIN Security Level S3 for medium security, 4. DIMENSIONS (HXWXD): 400X365X257MM, 5. WORKING WIDTH: 220MM, 6. Maximum 11 sheets (70g) of paper in a single pass, 7. Compact size for use under desk, 8. Bin window alerts user when bin needs emptying, 9. Shred staples, paper clips, credit cards and CDs.</p>	
23	SGB43666	NO DATA AVAILABE	5310PK508589 5 / NUT SZ-16MM A/F-24MM HIGHT 13MM		150 / EACH NUMBER						<p><u>TECHNICAL SPECIFICATION - MATERIAL STAINLESS STEEL 316</u></p> <p><u>GENERAL SPECIFICATION - MATERIAL STAINLESS STEEL 316</u></p>	
24	SNF53945	A.G.M	6230PK507309 6 / SEARCH LIGHT 500W 220V COMPLETE WITH ACCESSORIES COMMERCIAL	ELECTRICAL USE	7 / EACH NUMBER						<p><u>TECHNICAL SPECIFICATION - Search Light 500W/220V 50/60Hz/PP>0.9/CCT 6500k/IP 66</u></p> <p><u>GENERAL SPECIFICATION - Search Light 500W/220V 50/60Hz/PP>0.9/CCT 6500k/IP 66</u></p>	
25	SPK59082	Mobilux EP2	961170017039 6 / Mobilux Grease EP2 (16 OR 18 Kg Packing)		48 / KILOGRAMME						<p><u>TECHNICAL SPECIFICATION - null</u></p> <p><u>GENERAL SPECIFICATION - null</u></p>	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
26	DGE585-02		834070508791 3 / TENT 40 POUND ARMY PATT = FLY & FOLD DOUBLE = L7W 6FT (JUNGLE GREEN)	GENERAL PERPOSE	15/ EACH/N UMBER						<p><u>TECHNICAL SPECIFICATION - a.</u> Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs, QUANTITY 40, Length 2.5 ft each 10. Hammer, QUANTITY 02, LENGTH 2.5 FT EACH 11. Gunny Bags, QUANTITY 150, LENGTH 2.5 FT EACH b. Testing/Acceptance Criteria</p> <p><u>CINS/END USER GENERAL SPECIFICATION - a.</u> Tent 40 Pounds Army Pattern 1. Double fly tent having one outer fly with weather hood on both sides made of two folds of cotton sheeting cloth. 2. On inner fly with curtains on sides and walls fitted with pockets 3. The inner fly wall and curtains are made of two folds of cotton sheeting cloth both sides of the tent open with lacing from top to bottom. The walls 53 CMs (1'-9") high will be in continuation of the fly. 4. ACCESSORIES: BAMBOO POLES, IRON PEGS, HAMMER, GUNNY BAGS 5. Size 213 CMs (7'-0") length 6. Inside 183 CMs (6'-0") 7. Bamboos, quantity 50, Length 20 ft each 8. Rope, QUANTITY 50, Length 20 ft each 9. Iron pegs, QUANTITY</p>	

S. No.	LPR No	PART NO.	NSN / Description	#/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											40. Length 2.5 ft each 10. Hammer. QUANTITY 02. LENGTH 2.5 FT EACH 11. Gunny Bags. QUANTITY 150. LENGTH 2.5 FT EACH 6. Testing/Acceptance Criteria: CINS/END USER	
27	DGES85 01		834070508791 5 / HIGH QUALITY KUWAITI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	27 EACH/N LUMBER						<u>TECHNICAL SPECIFICATION -</u> Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/8 Ozs perm2) Accessories All accessories are required with Tent & Iron Poles (, Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT & INCH DETACHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN <u>GENERAL SPECIFICATION -</u> Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/8 Ozs perm2) Accessories All accessories are required with Tent &	

S No	LPR No	PART NO	NSN / Description	R/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
28	DGE61553		834070508791 5 / HIGH QUALITY KUWATI DELUXE TENT 23 X 15 FT	GENERAL PURPOSE	2 / EACH IN UMBER						<p>Iron Poles (Centre & Ride) √ Iron Hammer √ Iron Stick for walls √ Iron pins √ Iron pegs √ Repair Kit √ P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF. UV FLAME RESISTANT USAGE OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN</p> <p>TECHNICAL SPECIFICATION:- Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner Fold made of colored sheeting of 150 G/M2 (5/6 Ozs perm2) Accessories All accessories are required with Tent √ Iron Poles (Centre & Ride) √ Iron Hammer √ Iron Stick for walls √ Iron pins √ Iron pegs √ Repair Kit √ P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF. UV FLAME RESISTANT USAGE OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN</p> <p>GENERAL SPECIFICATION - Length: 8 Meter Width: 5 Meter Height of Tent: 3.00 Meter Height of Walls: 1.80 Meter Fabric Material: Outer Fold: First fold of 20 Ozs per m2 waterproof, rot proof & fungus proof cotton canvas</p>	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DEMO	Model	SR NO OF PR.	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											natural gray color. Middle: Fold made of black dyed cotton sheeting for prevention of sun rays, weight 3/4 Ozs per m2. Inner: Inner.Fold made of colored sheeting of 150 G/M2 (5/6 Ozs per m2) Accessories All accessories are required with Tent & Iron Poles (Centre & Ride) & Iron Hammer & Iron Stick for walls & Iron pins & Iron pegs & Repair Kit & P.E Ground Sheet of 180-200 Gsm SIZE: 23 X 15 FT FLY & FOLD WALL HEIGHT: 5 FT 8 INCH DETATCHABLE. MATERIAL: DOUBLE COTTON CANVAS, JUNGLE GREEN, WATERPROOF, UV FLAME RESISTANT USAGE: OUTDOOR OEM COC AND AUTHORIZED DEALER COUNTRY OF ORIGIN: PAKISTAN	
29	DGP61611		743570512646 2 / LAMINATION MACHINE	LAMINATION MACHINE	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
30	DGE62505	NO DATA AVAILABLE	041350000019 0 / TUBING PLASTIC TRANSPARENT(G/USE) O/D 32MM I/D 27MM TH.2.5 MM, LENGTH (MIN) 50 METER. MATERIAL: PLASTIC GRADE-1		1610 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Size: Wall Thick: 2.5mm. Length of Tube: 50ft Spec: 5039 pg 99 s. P.P. INV.1991 GENERAL SPECIFICATION - Size: Wall Thick: 2.5mm. Length of Tube: 50ft Spec: 5039 pg 99 s. P.P. INV.1991	
31	DPC61631	NO DATA AVAILABLE	685078503110 4 / CONTACT CLEANER SPRAYER ELECTRONIC PERO 857/PHILIPS 200ML CLEANER	REQUIREMENT FOR PNS NASR	230 / EACH/NUMBER						TECHNICAL SPECIFICATION - MAKE: AEROSOL MODEL: 390 363/0 0 NON OILY GRADE : DEGREASER CLEANER OEM. PHILIPS SOURCE OF AVAILABILITY VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15 B-8520 KUIJNE BELGIUM TEL: -	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			R(UNIVERSAL DEGREASER) (OEM = PERFECTS								0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>GENERAL SPECIFICATION-</u> MAKE: AEROSOL MODEL: 300 353/0 0 NON OILY GRADE DEGREASER CLEANER OEM. PHILIPS SOURCE OF AVAILABILITY: VOLCK AEROSOL COMPANY, INDUSTRIELAAN 15-B-8520 KUURNE BELGIUM TEL: 0032/56351723 FAX: 0032/56353069 VIDE PNS RAH NAWARD LETTER 300/NWD/1111 DATED 9 DEC 13. <u>TECHNICAL SPECIFICATION-</u> Color of Toner/ Cartridge for printer CP5225dn hp color laser jet printer: a. Black Cartridge: CE740A b. Cyan Cartridge: CE741A c. Magenta Cartridge: CE743A d. Yellow Cartridge: CE742A <u>GENERAL SPECIFICATION-</u> Color of Toner/ Cartridge for printer CP5225dn hp color laser jet printer: a. Black Cartridge: CE740A b. Cyan Cartridge: CE741A c. Magenta Cartridge: CE743A d. Yellow Cartridge: CE742A	
32	DGP63232	NIL	751070510204 3 / COLOR TONER CARTRIDGE FOR PRINTER 4500/HP4025/ CP5225DN HP	PRINTER 4500/HP4025	1 / SET							
33	DPC59351	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	
34	DPC5957e	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE	CP AIR COMP	160 / LITER						<u>TECHNICAL SPECIFICATION - TDS & IPC Enclosed</u> <u>GENERAL SPECIFICATION - TDS & IPC Enclosed</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)									
35	DPC58270	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
36	DPC64187	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	280 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
37	DPC57413	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	150 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
38	DPC62294	CAT ELC TM	681070508453 2 / CAT ELC	CP AIR COMP	300 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		(2056612 or 2056611)	TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)								SPECIFICATION - TDS & IPC Enclosed	
39	DPC58525	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
40	DGP05021	F(MD)-73	7530PK507335 7 / MEDICAL RECORD BOOK F(MD)-73 GSM OF PAPER 60 ± 5%	MEDICAL RECORD BOOK F(MD) 73	2500 / BOOK						TECHNICAL SPECIFICATION - Item Specification : F(MD)-73 MEDICAL RECORD BOOK GENERAL SPECIFICATION - Item Specification : F(MD)-73 MEDICAL RECORD BOOK	
41	DNM06131	04-8/105900	282072512106 8 / PACKING RING 60X58X1 (C-CU)	DIESEL DRIVEN COMPRESSOR W-30	2 / EACH/NUMBER	HATLAPA GMBH & EQUIPMENT CO (GERMANY) (W30/40)					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
42	DGD04535		003550000045 7 / UTENSIL COOKING ALUMINUM ALLOY WITH COVER (O/D 20", HEIGHT 10.25"		18 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (Pb) AND CADMIUM (Cd), ALUMINUM GRADE 3003, NO BREAKAGE/BENT GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (Pb) AND CADMIUM (Cd), ALUMINUM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			THICKNESS 9 SWG								GRADE 3003, NO BREAKAGE/BENT.	
43	DGD64538		0035500000520 / UTENSILS COOKING ALUMINUM WITHOUT COVER (O/D 25.50", HEIGHT 14", TH 10 SWG)		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD). ALUMINUM GRADE 3003, NO BREAKAGE/BENT. GENERAL SPECIFICATION - FOOD GRADE ALUMINUM ALLOY 100% FREE FROM LEAD (PB) AND CADMIUM (CD). ALUMINUM GRADE 3003, NO BREAKAGE/BENT.	
44	DNS65326	73632	5331171027165 / O RING (SEE COMD F8)	ALPHA LEVEL	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE. GENERAL SPECIFICATION - NO DATA AVAILABLE.	
45	DNF63098	T-1501	5996705249070 / Mixer Pre-amplifier, 5 mic Input, 3aux, AC 230V and DC 24V		1 / EACH/NUMBER	ITC					TECHNICAL SPECIFICATION - null. GENERAL SPECIFICATION - null.	
46	DNF60951	WINXP (SP3 ONWARD 5) / VIST/WIN 7 / WIN8 WIN10/ MAC/ LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		5 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLE. GENERAL SPECIFICATION - 4G DATA WINGLE.	
47	SNZ65961	3050944	5330014964338 / FLANGE GASKET	Cummins QSK 38 DM Main Engine	2 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins		TECHNICAL SPECIFICATION - N/A. GENERAL SPECIFICATION - N/A.	
48	DNF55953	0103-034021-249	6885785154487 / THERMOCOUPLE 8M	HIPAC	5 / EACH/NUMBER	FKE 8M		ALPINE INDUSTRIAL CON PVT LTD, 305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE 042-6852313, 6862490 FAX 02-426553674	CHINA		TECHNICAL SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY: ALPINE INDUSTRIAL CON PVT LTD, 305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE 042-6852313, 6862490 FAX 02-426553674. GENERAL SPECIFICATION - MAKE/BRAND: ALPINE SOURCE OF AVAILABILITY: ALPINE INDUSTRIAL	

S No	LPR No	PART NO	NSN / Description	Equipment	QTY / GENO	Model	SR NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CON PVT LTD 305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674	
49	DNF53510	E2C250 H3200	592573517778 0 / 160A CIRCUIT BREAKER	PORTAL CRANE	4/ EACH/N UMBER			ISTANBUL AVRUPA VINC GEMI EKIMANLARI SAN. VETIC.LTD.STI, Guzelyali Mah. Mandiye Sok. No:15/2 Pendik/Istanbul/TURKIYE, Tel: +90(216) 392 25 51, +90(216)392 29 83	SCHNEIDER		TECHNICAL SPECIFICATION - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER GENERAL SPECIFICATION - 400VAC 50HZ 3PHASE 160A CIRCUIT BREAKER	
50	DNF62212	BP 5-12	614073513101 1 / BATTERY 12V /5AH(DRY LED ACID)	UPS 5KVA	15/ EACH/N UMBER	NO DATA AVAILAB LE		KO	M/S VISION KORIAN		TECHNICAL SPECIFICATION - 12V 5AH 4"X3.5"X2.7" GENERAL SPECIFICATION - 12V 5AH 4"X3.5" X2.7"	
51	DNF63592	AC-5000	752073515092 3 / RFID MACHINE (OUTDOOR IP65 FINGERPRINT TERMINAL)	SECURITY EQUIPMENT	3/ EACH/N UMBER	AC-5000		Union Community Co.Ltd 3F, Hyundai Topic bldg., 44-3, Bangi-dong, Songpa-gu, Seoul, 138- 050, Korea Tel: +82-2-6488-3000 Fax: +82-2-6488-3099 WEB: www.virditech.com	VIRDI KOREA		TECHNICAL SPECIFICATION - IP- 65 STANDARD, 2.8" TFT COLOR SCREEN, MEMORY CAPACITY FOR 20,000USERS / 61,000LOGS, 32MB FLASH RAM, 304X344 PIXEL (FINGER PRINT SENSOR) GENERAL SPECIFICATION - IP-65 STANDARD, 2.8" TFT COLOR SCREEN, MEMORY CAPACITY FOR 20,000USERS / 61,000LOGS, 32MB FLASH RAM, 304X344 PIXEL (FINGER PRINT SENSOR)	
52	DNF62291	8-FMX- 100B/cmbt -c-12-150	614078522124 9/ MAINTENANC E FREE BATTERIES 12 VOLT 90- 100 AH	Microwave	3/ EACH/N UMBER	Crown Micro		WAREHOUSE NO.CA02, Near R/A08, Jebel Ali Freezone, Dubai, UAE Phone:(INTERNATIONAL) +971-4-883-9373 AX +971- 4-883 9756	CROWN MICRO AGM CHINA		TECHNICAL SPECIFICATION - required for backup supply for microwave GENERAL SPECIFICATION - required for backup supply for microwave	
53	ONA49890	34235	633070518433 4 / KIT VALVE	SEA WATER PUMP	2/ EACH/N UMBER	3535		DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051- 9060 3-9 FAX: 051- 9280502 90602104	DESTO ISLAMAB AD		TECHNICAL SPECIFICATION - make: Rochem (Germany) DEFENCE SCIENCE AND TECHONOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051- 9060 3-9 FAX: 051-9280502 90602104 GENERAL SPECIFICATION - make: Rochem	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF RR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(Germany) DEFENCE SCIENCE AND TECHNOLOGY ORGANISATION CHATTAR ISLAMABAD PH: 051-9080 5-5 FAX: 051-9280502 90602104	
54	DNO550 92	3808616-VOLVO	299027044164 8 / SENSOR	VOLVO PENTA ENGINE	2 / EACH/NUMBER	NO DATA AVAILAB LE			27	M/S AB VOLVO PENTA CITY GOTEBO RG SWEDEN GOTEBO RG	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
55	DNO552 81	3808616-VOLVO	299027044164 8 / SENSOR	VOLVO PENTA ENGINE	1 / EACH/NUMBER	NO DATA AVAILAB LE			27	M/S AB VOLVO PENTA CITY GOTEBO RG SWEDEN GOTEBO RG	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
56	DNZ5589 7	95602.140	533101415917 8 / O RING	MAIN AIR COMPRESSO R	6 / EACH/NUMBER	NO DATA AVAILAB LE			UK	COMPAIR UK LTD	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
57	DNZ5589 6	D102008 50 / D66376 50	431001416457 2 / PISTON ASSEMBLY	MAIN AIR COMPRESSO R	1 / EACH/NUMBER	NO DATA AVAILAB LE			UK	COMPAIR UK LTD	TECHNICAL SPECIFICATION -- GENERAL SPECIFICATION --	
58	DNS060 25	MRN-102-051/ CODE257 CODE 269	4510FT100869 9 / Muslim Shower	MRN Shower Wet Unit (with Wall Model Vacuum Toilet)	12 / EACH/NUMBER	MERCAN MRN Shower Wet Unit	0	DERI ORGANIZE SANAYI BOLGESI 7. YOL F 7 PARSEL TUZLA		MERCAN GEMICILIK SAN. VE TIC. A.S.	TECHNICAL SPECIFICATION - likely supplier. SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-3240447 GENERAL SPECIFICATION - likely supplier. SULEMAN Hardware, Shop # 2, Near Badami Masjid, Aja Mouj Street, Bhora Pir Electric Market, Karachi. Mob# 0346-2120960, 0312-2633855, 0321-3240447	
59	DNF6023 2	S4600-28P-S1 /CSS326	702514583778 9 / Switch Unit 24 PORT WITH	Local Area Network (LAN) (Intranet)	1 / EACH/NUMBER		0	1 AV DU CANADA LES ULIS LES ULIS		HEWLET T-PACKAR	TECHNICAL SPECIFICATION - DCN S4600-28P-S1 LAYER-2 24 PORT WITH 4SFP GENERAL	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		24G-2SRMJ9775A	4SFP with Accessories						D CENTRE COMPET ENCE FRANCE		SPECIFICATION:- DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP	
60	DNF55788	S4600-28P-SI /CSS326-24G-2SRMJ9775A	702514583778 9 / Switch Unit 24 PORT WITH 4SFP with Accessories	Local Area Network (LAN) (Intranet)	1/ EACH/N UMBER		0	1 AV DU CANADA LES ULIS LES ULIS	HEWLET T- PACKAR D CENTRE COMPET ENCE FRANCE		TECHNICAL SPECIFICATION:- DCN S4600-28P-SI LAYER-2 24 PORT WITH 4SFP GENERAL SPECIFICATION:-DCN S4600-28P- SI LAYER-2 24 PORT WITH 4SFP	
61	DNF58635	SRVPM3K/LSMT3000	613070513726 4 / UPS 3.KVA	UPS	2/ EACH/N UMBER	APC SRVPM3 KIL		PK	PAKISTA N		TECHNICAL SPECIFICATION:- BACK UP TIME: 20 MINUTES GENERAL SPECIFICATION:-BACK UP TIME: 20 MINUTES	
62	DNFB1993	DRS-120 /105D31R/DLS 120	613575518439 0 / DRY BATTERY SOLITE MARINE AND CARAVAN 12V 90AH	350 HP OBM ENGINE YAMAHA	3/ EACH/N UMBER	drs- 120/DLS 120		SUNGWOO AUTOMOTIVE CO LTD KOREA	SUNGWOO AUTOMO TIVE CO LTD KOREA		TECHNICAL SPECIFICATION:- GENERAL SPECIFICATION:-	
63	DNF52515	BSS-1104 TIM DIN	592578516079 8 / MCB 2 POLE 220 V 30AMPS	CONVERSION OF BOATSWAIN INTO MRO/BEHR KUSHA	5/ EACH/N UMBER	BSS-1104 TIM DIN		M/S DIGI TECH SHOP NO2 NEW MEMON CHAMMBER ALTA HUSSAIN ROAD DENS HALL KARACHI-7400 ,TEL: 2639514&2638482	M/S DIGI TECH SHOP NO2 NEW MEMON		TECHNICAL SPECIFICATION:- ruff GENERAL SPECIFICATION:- ruff	
64	DNF59940	CAT-6A U-FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE- 0.35MM 4/U- FTP PVC/LSZH-0.5 MM AQUA/BLUE/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	993 / FOOT	CAT-6A U-FTP	NA	No. 1199 Bin'an road Binjiang District, Hangzhou, China. 310053 Tel: +86- 571-67688883	CHINA		TECHNICAL SPECIFICATION:- qem, contact solution USA, www. CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U- FTP Cable jacket type PVC/LSZH Insulation material type PE 0.35mm capacitance unbalance max 1000 dc resistance: 95 GENERAL SPECIFICATION:-qem, contech solution USA, www.CONTECH SOLUTION.COM Conductor size 23AWG SOLID BORE COPPER, No of pairs 4/U-FTP Cable jacket type	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
65	DNF61135	CAT-6A U-FTP	599578520785 0 / CABLE NETWORK CAT-6A U-FTP 23AWG PE-0.36MM 4/U-FTP PVC/LSZH-0.5MM AQUA/BLEU/G RAY7.47MM	CCTV System CAT-6A U-FTP CHINA	230 / FOOT	CAT-6A U-FTP	NA	No. 1189 Bin'an road, Binjiang District, Hangzhou, China. 310053 Tel: +86-571-87688883	CHINA		PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>TECHNICAL SPECIFICATION - oem, contech solution USA. www.CONTECH SOLUTION.COM</u> Conductor size 23AWG SOLID BORE COPPER. No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95 <u>GENERAL SPECIFICATION - oem, contech solution USA. www.CONTECH SOLUTION.COM</u> Conductor size 23AWG SOLID BORE COPPER. No of pairs 4/U-FTP Cable jacket type PVC/LSZH Insulation material type PE 0.36mm capacitance unvalance max 1600 dc resistance 95	
66	SNF18351	SSX4106-7	592512353527 6 / MCB- SINGLE POLE 6A	DIG	2 / EACH/NUMBER	NO DATA AVAILABLE			SIEMEN PAKISTAN ENGINEERING CO LTD AUTOMATION&DRIVE DIVISION BU SMALL&LARGE B-72ESTATE AVNEUE SITE PO BOX 7158PHW 92(021) 2574910-19 KARACHI 75700		<u>TECHNICAL SPECIFICATION - -</u> <u>GENERAL SPECIFICATION - -</u>	
67	DNS654	3838406	533173515946	VOLVO PENTA 3 /		D9A2A-		WARSILA FINLAND OY.	WARSKA		<u>TECHNICAL SPECIFICATION -</u>	

S. No	LPR No	PART NO	NSN / Description	Fit/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	51		8 / O-RING	SSDG (STUS)	EACH/NUMBER	MG		SHIP POWER P.O BOX 252 FIN-65101 VAASA FINLAND	FINLAND		WARSILA FINLAND OY, SHIP POWER P.O BOX 252 FIN-65101 VAASA FINLAND GENERAL SPECIFICATION - WARSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 VAASA FINLAND	
68	DNS46873	196-013	482073517061 1/ THERMOSTATIC VALVE FOR HT WATER	MAIN ENGINE	2/ EACH/NUMBER			WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	WARTSILA PAKISTAN		TECHNICAL SPECIFICATION - OEM - WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821 GENERAL SPECIFICATION - OEM - WARTSILA FINLAND OY WARTSILA PAKISTAN (PVT) LTD F-8 KDA SCHEME 1 TIPPU SULATAN ROAD KARACHI PAKISTAN TEL +92-213437 5824-30 FAX +92 2134375821	
69	DNF58531		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	2/ EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
70	DNF58245		607070522982 1 / 24 JOINT BOX	PSS SYSTEM	4/ EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
71	DNF58185	APC BRAND / P-0154000 / APC SRT8KXLI	613078516675 3 / UPS 6KVA-2H O/P 220V/6000VA	PSS (CCTV SYS)	1/ EACH/NUMBER	APC BRAND		M/s CETC Mansion, No. 5 Wulitong North Street, Xicheng District, Beijing, China	M/s CETC International CO., LTD	LATEST MODEL REQUIREMENT	TECHNICAL SPECIFICATION - OEM & SOA/M/S CETC Mansion, NO.5 Wulitong North Street, Xicheng District, Beijing, China - BACKUP TIME 30-35 MINS GENERAL SPECIFICATION - OEM & SOA/M/S CETC Mansion, NO.5 Wulitong North Street, Xicheng District, Beijing, China - BACKUP TIME: 30-35 MINS	
72	DNF58634	APC BRAND /	613078516675 3 / UPS 6KVA-	PSS (CCTV SYS)	2/ EACH/NUMBER	APC BRAND		M/s CETC Mansion, No. 5 Wulitong North Street,	M/s CETC International		TECHNICAL SPECIFICATION - OEM & SOA/M/S CETC Mansion,	

S. No	LPR No	PART NO	SN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		P-0154000 / APC SRT6KXL1	2H O/P 220V 6000VA		NUMBER			Xicheng District, Beijing, China		net CO., LTD	NO.5 Wulitong North Street, Xicheng District, Beijing, China. BACKUP TIME: 30-35 MINS. GENERAL SPECIFICATION: OEM & SOA. MIS GETC Mansion, NO.5 Wulitong North Street, Xicheng District, Beijing, China. BACKUP TIME: 30-35 MINS.	
73	DNS48164	165 052	533173518547 1 / SEALING SET FOR INJECTION PUMP	WARTSILA MAIN ENGINE 9L20C3 FINLAND	18 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantie 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tlx 74251 wa sf Fax (Service) ,358 6 358 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	TECHNICAL SPECIFICATION - DOCUMENT NUMBER 54292 SPECIFICATIONS 231205, 231206 OEM: WARTSILA MAKE: FINLAND MODEL: 9L20 GENERAL SPECIFICATION - DOCUMENT NUMBER 54292 SPECIFICATIONS 231205, 231206 OEM: WARTSILA MAKE: FINLAND MODEL: 9L20	
74	DNS47937	167 013	281573518588 5 / PUSH ROD	WARTSILA MAIN ENGINE 9L20C3 FINLAND	18 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084 242 RASDPA AE084243 PAAE084 244	Wartsila Finland Oy Vaasa Factory Tarhaajantie 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tlx 74251 wa sf Fax (Service) ,358 6 358 7355 Fax (Spare parts) +358 10 709 1380		Wartsila Finland Oy	TECHNICAL SPECIFICATION - TP GENERAL SPECIFICATION - TP	
75	DNF62872	03-00-0201-00 / 02-00-0159-00	635071519445 4 / PCB, DCI	Luggage Scanning Machine size (40)	1 / EACH/NUMBER	XIS-100X	ASTVC18 0LL740	ASTROPHYSICS INC CTR UNITED STATES TEL 9085985488 FAX 9085985548		Astrophysics Manufacturing	TECHNICAL SPECIFICATION - Security Equipment 40"X40" 6350-01-615-5690 GENERAL SPECIFICATION - Security Equipment 40"X40" 6350-01-615-5690	
76	DNS55418	3CA80-5.0-S	482077518808 3 / CHECK VALUE	WARTSILA STERN THRUSTER PROP CS250-SWG-K HOLLAND	1 / EACH/NUMBER	WART-LCT-CS250-SWG-K	MADD MP/00675 M2T12 RASD MP/00675 M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 88 Drunen The Netherlands Phone : +31 416 389424 propulsion.service@wartsila.com http://www.wartsila.com		Wartsila Propulsion Netherlands B.V	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
77	DNF46953	US/CHINA BRAND/ P-	603078518498	PSE / CCTV SYS)	100 / METER			GETC MANSION NO-5 WULITONG NORTH		MIS-GETC	TECHNICAL SPECIFICATION -	

S. No	PR No	PART NO	NSN / Description	P/Equipment	QTY / DEMD	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		0003	3 / PREMIERE / PTCL OPTICAL FIBRE 6-CORE CABLE					STREET, XICHENG DISTRICT, BEIJING, CHINA, 100120	INTERNATIONAL CO LTD		DIAMETER 7.5MM Make: PREMIERE/PTCL cables GENERAL SPECIFICATION - DIAMETER 7.5 MM Make: PREMIERE/PTCL cables	
78	DNF45814	US/CHINA BRAND/P-0003	803078516496 3 / PREMIERE / PTCL OPTICAL FIBRE 6-CORE CABLE	PSS (CCTV SYS)	1700 / METER			CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA, 100120	M/S CETC INTERNATIONAL CO LTD		TECHNICAL SPECIFICATION - DIAMETER 7.5MM Make: PREMIERE/PTCL cables GENERAL SPECIFICATION - DIAMETER 7.5 MM Make: PREMIERE/PTCL cables	
79	DNJ58845	99005-45292 /31135-94900	538076522241 6 / SPRING	SUZUKI DF300AP 300 HP OBM	4 / EACH/NUMBER	SUZUKI DF300AP 300 HP OBM	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
80	DNJ58842	15411-93J10	534076522162 8 / CAP, FUEL FILTER	SUZUKI DF300AP 300 HP OBM	1 / EACH/NUMBER	SUZUKI DF300AP	30002P-712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
81	DNF85385	APC Smart-UPS VT 40KVA	613071520703 7 / APC Smart-UPS VT 40KVA	UFFAQ	1 / EACH/NUMBER	APC Smart-UPS VT 40KVA		132 fairgrounds round west kingston, R1 02892, United States; call 401-789-5735 Web: www.apc.com	APC, UK		TECHNICAL SPECIFICATION - As Attached OEM: China/Saima Trade Tower, A910, II Chundngar Road, Saddar Karachi (021) 32213399 GENERAL SPECIFICATION - As Attached OEM: China/Saima Trade Tower, A910, II Chundngar Road Saddar Karachi (021) 32213399	
82	DNF85387	Symmetra LX-16KVA-UPS	613071520703 8 / APC UPS Symmetra LX 16 KVA	UFFAQ	1 / EACH/NUMBER	Symmetra LX		132 fairgrounds round west kingston, R1 02892, United States; call 401-789-5735 Web: www.apc.com	APC, UK		TECHNICAL SPECIFICATION - As Attached LOCAL SOURCE, M/S DELTA TRADERS KARACHI TEL: 0307-3925152 E-MAIL: deltatradrs2001@gmail.com Standard Backup Time GENERAL SPECIFICATION - As Attached LOCAL SOURCE, M/S DELTA TRADERS KARACHI TEL: 0307-3925152 E-MAIL: deltatradrs2001@gmail.com Standard Backup Time	
83	DNF64728	000-133-495	592078520972 9 / FUSE LITHIUM BATTERY CR2450-F2 ST2	Furuno Echo Sounder FE-700 Japan	50 / EACH/NUMBER	N/A	2260-7323	FURUNO ELECTRIC CO. LTD 9-52 ASHIMURA-CHO, NISHINOMIYA, 662-6580, JAPAN Tele No. +81 798 85-2111	FURUNO ELECTRIC CO. LTD		TECHNICAL SPECIFICATION - AS PER CATALOGUE GENERAL SPECIFICATION - AS PER CATALOGUE	

S. No.	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									Fax: +81 798 65-4200			
84	DNZ66405	4988506 / 4988522	598378521722 6 / ELECTRONIC CONTROL MODULE WIRING HARNESS	Cummins QSK38 DM Main Engine	1 / EACH NUMBER	QSK38-DM	33170174	Cummins, Engine Co. Ltd	Cummins		TECHNICAL SPECIFICATION - Harness 1 QSK38-50 T2Marine FF Harness GENERAL SPECIFICATION _Harness 1 QSK38-50 T2Marine FF Harness	
85	DNF61145	DCC/HFB M/EL/007	596070521438 3 / LOW NOISE AMPLIFIER (LNA)	SM RACK 100C22L PAK	7 / EACH NUMBER	100C22L	NA	Data Communication and Control Pvt. Ltd, 409 Clifton Center, Block 5 Clifton, KHI 021-35363212	DCC	OEM - MS DCC (DATA COMMUNICATION & CONTROL)	TECHNICAL SPECIFICATION - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Ω GENERAL SPECIFICATION - It amplifies the received signals with a constant gain of +25 dB Fixed Gain: 25 dB Frequency Range: 0.05 ? 500 MHz Operating Temperature: -55 C to 100 C Supply Voltage: 12V ? 16V Supply Current: 80mA Input Connector Type: SMA-Female Output Connector Type: SMA-Female Input Impedance: 50Ω	
86	DNF65039	DCC/HFB M/IRW/114	705070521587 3 / TOUCH INPUT DISPLAY (TID)	OPERATOR CONTROL DCC-2016 PAKISTAN	3 / EACH NUMBER	NA	NA	Commercially Of The Shelf (COTS)/Local Market	COTS		TECHNICAL SPECIFICATION - INPUT DEVICE 10" installed in HF DF System GENERAL SPECIFICATION - INPUT DEVICE 10" installed in HF DF System	
87	DNO65092	3808616-VOLVO	299027044164 6 / SENSOR	VOLVO PENTA ENGINE	2 / EACH NUMBER	NO DATA AVAILABLE		AB VALVO PENTA SE 405 08 GÖTHENBURG SWEDEN	VALVO PENTA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
88	DNO55281	3808616-VOLVO	299027044164 6 / SENSOR	VOLVO PENTA ENGINE	1 / EACH NUMBER	NO DATA AVAILABLE		AB VALVO PENTA SE 405 08 GÖTHENBURG SWEDEN	VALVO PENTA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
89	DNF58123	BP 4185 (PANELS)	611750514525 2 / SOLAR PANELS (SILICON NITRIDE MONO	SOLAR PANEL SYSTEM	6 / EACH NUMBER	NO DATA AVAILABLE		CH	MS SUNRISE SOLAR TECH CO LTD ZONE		TECHNICAL SPECIFICATION - ON-M572-320WW Maximum Power (Pmax): 320 W Rated voltage (Vmp): 35.66 V Rated Current (Imp): 8.41 A Open Circuit voltage (Voc): 45.10 V Short-Circuit Current	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CRYSTAL SILICON CELLS 165W 24V/300 W 24 V WITH STAND						CHANGZ HOU 213023 JIANGSU CHINA TEL: 0086-519-83906509 FAX: 0086-519-83906538		(isc) 9 A Fire rating: CLASS C Structural load: 5400 Pa Maximum series Fuse: 20 A Maximum System Voltage: DC 1000 V GENERAL SPECIFICATION - ON-M072-320WW Maximum Power (Pmax): 320 W Rated voltage (Vmpp): 35.68 V Rated Current (Impp): 8.41 A Open Circuit voltage (Voc): 45.10 V Short Circuit Current (Isc): 9 A Fire rating: CLASS C Structural load: 5400 Pa Maximum series Fuse: 20 A Maximum System Voltage: DC 1000 V	
90	DNF60415	T-130	705078520482 8 / SERVER DELL POWER EDGE MODEL T-130 WITH 1 TB SSD HARD DISK AND 16 GB RAM	Call Centre T130	1 / UNIT	T130		2nd floor entrance A, Block 3, Crown Technology Park Yairan 9th Rd#21 Chegongmao Futian, Shenzhen China	DELL CHINA		TECHNICAL SPECIFICATION - Extra Spec: 1Tb SSD and with 16 GB RAM GENERAL SPECIFICATION - Extra Spec: 1Tb SSD and with 16 GB RAM	
91	DNS47929	120021	280573515161 1 / Valve seat Insert Inlet	WARTSILA MAIN ENGINE 9L20C3 FINLAND	72 / EACH/NUMBER	9L20C3		Wartsila Finland Oy Vaasa Factory Tietoaajantie 2, FIN-65101 Vaasa, Finland Tel: +358 10 708 0000, Fax: +358 10 708 74251 w a s i Fax (Service): +358 6 356 7355 Fax (Spare parts): +358 10 708 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DNF61364	TMT-50124C	613014504756 3 / AC TO DC POWER SUPPLY 24VDC 2300MA	NIXS	1 / EACH/NUMBER	TMT-50124C		TRACO POWER SUPPLY - SWITZERLAND	TRACO POWER SUPPLY SWITZERLAND		TECHNICAL SPECIFICATION - AC TO DC POWER SUPPLY GENERAL SPECIFICATION - AC TO DC POWER SUPPLY	
93	DNC64291	8M5002465	2910MB002042 7 / INJECTOR ASSEMBLY FUEL	PETROL MAIN ENGINE	6 / EACH/NUMBER	VERADO 350 HP	28814987 28812137 29819494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
94	DNC646	8M5002465	2910MB002042	PETROL MAIN	12 /	VERADO	29814987	MERCURY MARINE	MERCURY		TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	12	5	7 / INJECTOR ASSEMBLY FUEL	ENGINE	EACH / NUMBER	350 HP	28612137 28619494 28614987	SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122 MERCURY MARINE	Y MARINE		no/GENERAL SPECIFICATION - null	
95	DNC54871	8M5002465	2910MB002042 7 / INJECTOR ASSEMBLY FUEL	PETROL MAIN ENGINE	6 / EACH / NUMBER	VERADO 350 HP	28612137 28619494	SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY Y MARINE		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
96	DPC62994	G-1200	047550220561 3 / RTV SILICON SEALANT (PACKING 310 ML TUBE)		36 / TUBE						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DNF56669	DEF107A 822996 62-2PT2	058379910503 3 / TORCH HAND ELECT WATERPROOF R/A HEAD SPARE LAMP SZ 187X43MM		27 / EACH / NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DNF81359	JPN-8840	058379942788 5 / TORCH-HAND-ELECT		6 / EACH / NUMBER	SOGO HUNTER					TECHNICAL SPECIFICATION - INPUT 220-240V 50/60Hz RANGE: 1000M BATTERY: 6V 4Ah OUTPUT: 15W Rechargeable time : 20-24hrs Dimension: 190x122x127mm. GENERAL SPECIFICATION - INPUT 220-240V 50/60Hz RANGE: 1000M BATTERY: 6V 4Ah OUTPUT: 15W Rechargeable time : 20-24Hrs Dimension: 190x122x127mm.	
99	DNF82396	4371187	056579437118 7 / DRILL MACHINE ELECT 220V 5A 50HZ SIZE 23MM 530RPM		1 / EACH / NUMBER	4371187					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
100	DNF66272		056173439325 2 / WIRE WINDING COPPER ELECT COND DIA 1.400MM O/A DIA 1.506	MOTOR WINDING	70 / KILOGRAMME						TECHNICAL SPECIFICATION - BS EN 60317-8 purity of copper 99.9% min required temperature index 180 c NOMINAL DIA: 1.400MM OVERALL DIA: 1.506MM GENERAL SPECIFICATION - BS EN 60317-8: purity of copper 99.9% min required	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			MM (CLASS-180) GRADE 2								temperature index 180 c NOMINAL DIA : 1.400MM OVERALL DIA : 1.500 MM	
101	DNF63335	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	058278562000 6 / BATTERY LEAD ACID 12V 200AH	DG-USED	3 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
102	DNJ45894	533210300 (TEM NO. 1900-5)	299076501215 6 / CONNECTING ROD BERING BUSH 6MG16X-A	NIIGATA DIESEL ENGINE MOD 6L(MG)16X-A	12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
103	DNA44334	0400-2998	299072500691 0 / STOP RING DEUTZ BA12H716 0400-2998	DEUTZ DIESEL GENERATOR 350kW	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
104	DNZ55501	7308	311078503704 9 / BEARING BALL ANGULAR 040X090X23MM	CARGO F/W PUMP 2FDDV-65B NASR	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
105	DNG54894	5149571	533021893157 7 / GASKIT MAJOR OVERHAUL	GM DETROIT ENGINE 149 SERIES	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
106	DNF48704	J9627A	593073511469 1 / 48 Port 10/100 Layer 2 Managed Switch	AT-8300 SERIES	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch GENERAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product: Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch	
107	DNF54093	1106	582570511832 3 / BATTERY CHARGER		1 / EACH/NUMBER	GZL30A-6/48V					TECHNICAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			IP220V 50HZ 1PH O/P 48V (12X4) 20A WITH ACCE								Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC; OEM: Nanchang Shuguang Electric Equipment Factory GENERAL SPECIFICATION - Picture of equipment is enclosed. Input: 220 Volt AC Single Phase 50 Hz Output: 12V/ 24V/ 36V/ 48V and 30A I/P Voltage Range: 90-280V AC OEM: Nanchang Shuguang Electric Equipment Factory	
108	DNF62012	158-51010	595199558030 7 / DIODE 25AMPS 600VOLT	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	DNF62013	158-51020	595199558031 4 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAH)	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DNF62166	158-51020	595199558031 4 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAH)	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
111	DNF63452	6-242-01	613099742767 0 / CHARGER PANEL LIGHT, TYPE 10-MODIFIED 110/130V AND 200/250V 50/60HZ	PANNEL LIGHT	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - country of origin uk GENERAL SPECIFICATION - country of origin uk	
112	DNF64377	PP3, 6F22, (6135-00-900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGIZ 047X25 75X017MM	AVO METER	14 / EACH/NUMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25 75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25 75X017MM OEM RS COMPONENTS LIMITED.	
113	DNF58512		595576501670 1 / MICROPHONE ON/OFF SWITCHABLE MODEL 3049	SRE SYSTEM	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO QF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
114	DNFB5003	WPW5-12 / RM12-7.2 / WPS5-12	814079508929 8 / BATTERY 12VDC 5AH LEAD ACID FOR UPS	SONAR TRAINERS UPS	128 / EACH/N UMBER	WPW5- 12/GES20 3H					TECHNICAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE: 10X9.8X10CM,MODEL: RM12- 7.2. GENERAL SPECIFICATION - BATTERY 12VDC 5AH LEAD ACID, SIZE: 10X9.8X10CM,MODEL:RM12- 7.2.	
115	DNFB4032	LCIR127R 2PG1(SEE P8 FOR L/ADDRES	814578509185 7 / SEALED LEAD ACID BATTERY 7.2 AH/20HR12V S25 7"X3.5"X2. 3"L.H.W	UPS APC ASIS SYSTEM	48 / EACH/N UMBER						TECHNICAL SPECIFICATION - DESCRIPTION: a. Sealed lead Acid Dry battery 12 Volt 7.0 AH b. Sealed lead Acid Dry battery 12 Volt 7.0 AH c. Sealed lead Acid Dry battery 12 Volt 7.2 AH MAKE/MODEL A. Ebaam 12HD7.0 b. Leoch DJW 12- 7.0 c. VOLTA NP-7-12 oem: a. eBAAM USA B. LEOCH CHINA C. VOLTA PAKISTAN GENERAL SPECIFICATION - DESCRIPTION: a. Sealed lead Acid Dry battery 12 Volt 7.0 AH b. Sealed lead Acid Dry battery 12 Volt 7.0 AH c. Sealed lead Acid Dry battery 12 Volt 7.2 AH MAKE/MODEL A. Ebaam 12HD7.0 b. Leoch DJW 12-7.0 c. VOLTA NP- 7-12 oem: a. eBAAM USA B. LEOCH CHINA C. VOLTA PAKISTAN	
116	DNFB6085	HI-PE MULTI- ZONE / PD6500	635071509551 4 / WALKTHROU GH GATE METAL DETECTOR C/W ACCESORIES	SECURITY DETECTION (OEM CEIA ITALY)	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DNFB55502	HI-PE MULTI- ZONE / PD6500	635071509551 4 / WALKTHROU GH GATE METAL DETECTOR C/W ACCESORIES	SECURITY DETECTION (OEM CEIA ITALY)	3 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
118	DNFB4524	PHILIPS/C RC/PERFE CT/C	7810PK508541 9 / ELECTRO SPRAY	PCB CLEAN MATERIAL	15 / CAN						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CONTRACT CLEANER (200ML)								AVAILABLE	
119	DNF61899	390DCS/2	80307750163107 DEGREASER CLEANER, SOLVENT NON OILY (200ML)	PCB CLEAN MATERIAL (M/S PERFECT BELGIUM)	2 / EACH NUMBER	390DCS/20					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
120	DNF48082	525502	66501215795507 BINOCULAR 7X50B/7X50c	BINOCULAR 7X50B OEM: ZEISS CARL POB 1380	9 / EACH NUMBER	7x50b/7X50c					TECHNICAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany GENERAL SPECIFICATION - BINOCULAR 7X50B OEM: STEINER POTIK GMBH germany	
121	DNF5315	MODEL NO MPK TRV1	6780765085706 / MARINE PACK FOR HANDY CAM (VIDEO CAMERA RECORDER) TRV1 SONY	VIDEO CAMERA RECORDER	1 / EACH NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DPC68135	AEROSIL® 200	6810705009686 / POWDER AEROSIL 200 (packing 10/15/20 kg)	EXPOSED DECKS	20 / KILOGRAMME						TECHNICAL SPECIFICATION - REQUIREMENT ... FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA (m2 /g) = 175-225 LSS ON DRYING [wt.%] = 1.5 ph VALUE = 3.7-4.5 GENERAL SPECIFICATION - REQUIREMENT ... FUMED SILICA AEROSIL® GRADES = AEROSIL® 200 BET SURFACE AREA (m2 /g) = 175-225 LSS ON DRYING [wt.%] = 1.5 ph VALUE = 3.7-4.5	
123	DNF64847	KFAE-55C	8105705044236 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	EXHAUST BLOWER STEERING COMPART	1 / EACH NUMBER						TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE	
124	DNF58377	KFAE-55C	8105705044236 / BLOWER	EXHAUST BLOWER	6 / EACH NUMBER						TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	STEERING COMPART	UMBER						50HZ 3 PHASE GENERAL SPECIFICATION:- 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE	
125	DNF61619	ep-1000v/blazer vista 1000	703570505982 7 / UPS 1KVA WITH BATTERY BACKUP 10 MINUTES (AS PER APPROVAL)	BV8S-2	3 / EACH / UMBER	BLAZER VISTA 1000/Aurora					TECHNICAL SPECIFICATION:- backup time: 10 minutes Product Name: AURORA Input: 220V AC GENERAL SPECIFICATION:- backup time: 10 minutes Product Name: AURORA Input: 220V AC	
126	DNF65723	SMT3000 C/SURTD3000XL/3000VA APC	613071506382 3 / UPS 3KVA APC/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH / UMBER	MODEL ESP-808 (E) / SYSTEK PVT.					TECHNICAL SPECIFICATION:- APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION:- APC SMART-UPS, 2700 WATTS/3000 VA, INPUT 230V, OUTPUT 230 V, INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
127	DNF63426	DPSI 8-16X40	055278000024 5 / BINOCULAR WITH CASE	SELF & USE	6 / EACH / UMBER	DPSI OLYMPUS					TECHNICAL SPECIFICATION:- PART NO.8-16X40 MAKE OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES, R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI, OLYMPUS KOREA CO LTD 9H HYUNDAI	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	Tech / GEN SPECS	Dimension
											MARINE BLDG 846 YEOKSAM, DONG KANGNAMGU SEOUL 135-080.TEL 080-777-3200 OR 3201 (TOLL FREE) GENERAL SPECIFICATION - PART NO. 8-16X40 MAKE OLYMPUS MODEL DPSI OEM-KOREA SOURCE OF AVAILABILITY-BS ENTERPRISES, R-429 MOZZANINE FLOOR SHAH ARCADE GULSHAN IQBAL 13-D/1 BLOCK KARACHI. OLYMPUS KOREA CO LTD.9/HYUNDAI MARINE BLDG,846 YEOKSAM, DONG KANGNAMGU SEOUL 135-080.TEL 080-777-3200 OR 3201 (TOLL FREE)	
128	DNF50090	D790-5M	611071528082 5 / Gauge Dust element transducer ALONG WITH Icmd-316 5B CABLE		2 / EACH NUMBER	d 790-sm					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
129	DNZ63593	HUBA CONTROL type 520	668577530069 3 / pressure transmitter		1 / EACH NUMBER	huba					TECHNICAL SPECIFICATION - HP SAEFTY OF MAIN AC PLANT GENERAL SPECIFICATION - HP SAEFTY OF MAIN AC PLANT	
130	DNF59256	DS-6701HFH1-V	589527068439 1 / HD ENCODER (VIDEO COMPRATION DEVICE)		1 / EACH NUMBER	N/A					TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.	
131	DNF63606	DS-6701HFHV	589527068439 1 / HD ENCODER (VIDEO COMPRATION DEVICE)		1 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE.	
132	DNF62320	s115 sport camera backpack	678071523545 3 / bag with trolley large pelican s115 sport camera backpack		1 / EACH/NUMBER	S115 SPORT CAMERA BACKPACK					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
133	DNF60425	HTS-MC100CM	591570524870 4 / MEDIA CONVERTER (1 PAIR)		2 / EACH/NUMBER	MC100CM					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
134	DNF5002	WINXP	599870527758		6 /	NA					TECHNICAL SPECIFICATION - 4G	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	5	(SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		EACH/NUMBER						DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
135	DNF56990	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		28 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
136	DNF55958	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		6 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
137	DNF58586	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		2 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
138	DNF61083	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA C/LINUX	599870527756 7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		8 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	
139	DNF58670	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MA	599870527756 7 / SVAS SECURE 4G DATA WINGLES(jazz (DEVICE)		4 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLEGENERAL SPECIFICATION - 4G DATA WINGLE	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO QF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
CILINUX												
140	DNJ50367	952188	531576523859 1 / Pin Dowel		8 / EACH/NUMBER	E40XMHL					TECHNICAL SPECIFICATION - Make/ Model: Mercury/ E40XMHL a. Length 11.50mm b. Dia 5.87 mm GENERAL SPECIFICATION - Make/ Model: Mercury/ E40XMHL a. Length 11.50mm b. Dia 5.87mm	
141	DNF62321	aol-pll-01	585076529308 3 / led aviation mast light 110- 240V AC 4WATT (RED COLOR)		30 / EACH/NUMBER	PLL-01					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
142	DNF63451	8052-188 / 852188000 8882	599970523829 1 / battery ABSORBENT GLASS MAT (AGM) 12v. 75 ah OPTIMA BT DC 5.5		4 / EACH/NUMBER	bold31m OPTIMA					TECHNICAL SPECIFICATION - NSN 6140015024405 OEM, OPTIMA BATTERIES USA GENERAL SPECIFICATION - NSN 6140015024405 OEM, OPTIMA BATTERIES USA	
143	DN055014	7620.740.0 13.5 / FIL230912	2815FP303039 3 / FUEL DUPLEX FILTER		19 / EACH/NUMBER	TBD620V 12					TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps GENERAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps	
144	DNF46855	9FN066- 008	702501599383 2 / SEAGATE HDD 15K.7 NCC/NMS SERVER DB SERVER		3 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
145	DNF63095	J9776A18 n88a	703571524883 2 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)				RUIE BRAND	TECHNICAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH GENERAL SPECIFICATION - HP ARUBA 24 PORT NETWORK SWITCH	
146	DN0648	hr1234w	614001618242		5 /	8GSYBTU					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / QENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	50	12/ WP 1236W-LONG	1 / BATTERY, RECHARGABLE (12V, 34W)		EACH/NUMBER						nu GENERAL SPECIFICATION - null	
147	DNF52283	NCB-FS09D-LCSC-5	599570524635 5 / D-LINK SC-LC SINGLEMODE ON2 DUPLEX PATCH CORD 5M		5 / EACH/NUMBER	NCB-FS09D-LCSC-5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
148	DNZ58523	CXH3-101P-01/200-011	621072000608 5 / MAST HEAD LIGHT (WHITE)		1 / EACH/NUMBER	3NM 225 VERTICAL MOUNT				OEM/COC CERTIFICATE REQUIRED	TECHNICAL SPECIFICATION - INPUT SUPPLY 24 VOLT DC VISIBILITY 3NM MAST HEAD LIGHT (WHITE) GENERAL SPECIFICATION - INPUT SUPPLY 24 VOLT DC VISIBILITY 3NM MAST HEAD LIGHT (WHITE)	
149	SNM47326	3P0649	533000367565 2 / SEAL O RING	3516, CATERPILLAR D/G USA (JNB)	10 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM: CATERPILLAR DGGENERAL SPECIFICATION - OEM: CATERPILLAR DG	
150	SNM45582	9M4849	533000847435 1 / SEAL	3304PC, CATERPILLAR D/GEN USA	22 / EACH/NUMBER						TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	
151	DNM27494	BS1608	533000437875 2 / GASKET CORK JOINT OF 11 HOLE WD-9X12MM HOLE DIA-9MM TH-03MM	3304PC, CATERPILLAR D/GEN USA	1 / EACH/NUMBER	3304 SSDG					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDGGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR CATERPILLAR (USA) 3304 SSDG	
152	SNM45761	5S-6348	531000557939 9 / NUT	CATERPILLAR DIESEL GENERATOR (USA)	12 / EACH/NUMBER	7N3277 (3304 PC)					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
153	SNM45573	1P1255	533001367572 4 / GASKET JOINT WD-25MM LG-70MM TH-1MM HOLE DIA-11MM	FOR CATERPILLAR DIESEL GENERATOR (USA)	4 / EACH/NUMBER	3304B					TECHNICAL SPECIFICATION - OEM & MAKE: CATERPILLARGENERAL SPECIFICATION - OEM & MAKE: CATERPILLAR	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
154	DNM59938	050307	536512191242 7 / SPACER RING 3RD STAGE	HP AIR COMPRESSOR R-150-BAR (GERMANY)	16 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
155	DNM60755	050307	536512191242 7 / SPACER RING 3RD STAGE	HP AIR COMPRESSOR R-150-BAR (GERMANY)	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
156	DNH87132	NO DATA AVAILABLE	411075053010 6 / REFRIGERATOR 10 CUFT 220V AC 50HZ		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
157	DPC61828	NO DATA AVAILABLE	684070505711 1 / INSECTICIDE K-OTHRINE dc 15 (01 LITER PACKING) (OEM M/S: Bayer Environmental Sciences)	TO CONTROL INSECT PASTS COCKROACHES BUGS	20 / LITER						TECHNICAL SPECIFICATION - Specification: Active Ingredient (A.1) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label. GENERAL SPECIFICATION - Specification: Active Ingredient (A.1) Deltamethrine 15 EC W/V (15g/ltr) Packing: 01x Ltr sealed plastic packing with registered label.	
158	DPC60089	R-5002	801070511103 7 / PIGMENT (BRILLIANT WHITE)	GRP WORK M/S ZAIN SONS. KARCHI, PH. 7731541	60 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
159	DPC61816	NO DATA AVAILABLE	684070505663 4 / Insecticide Heptachlor-32-1-EC/AgEnds 25 Percent EC	FOR INSECT KILLING	15 / LITER						TECHNICAL SPECIFICATION - ACTIVE INGREDIENT (A.1) FIPRONIL 25 % EC W/V GROUP. PHENYL PYRAZOLE PACKING: 01 Ltr bottle PLASTIC WITH REGISTERED LABEL GENERAL SPECIFICATION - ACTIVE INGREDIENT (A.1) FIPRONIL 25 % EC W/V GROUP. PHENYL PYRAZOLE PACKING: 01 Ltr bottle PLASTIC WITH REGISTERED LABEL	
160	DPC57383	NO DATA AVAILABLE	918071501838 8 / COMPOUND HONEY WAX MQLD, D. RLSE	BEST TRADE PRODUCT.	32 / TIN						TECHNICAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP GENERAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			(Packing 140Z Tin)									
181	DPC55296	NO DATA AVAILABLE	916071501638 8 / COMPOUND HONEY WAX MOULD RLSE (Packing 140Z Tin)	BEST TRADE PRODUCT.	27 / TIN						TECHNICAL SPECIFICATION : WAX HIGH CLASS PASTE FOR USE AS A GRP GENERAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP	
182	DPC57943	NO DATA AVAILABLE	916071501638 8 / COMPOUND HONEY WAX MOULD RLSE (Packing 140Z Tin)	BEST TRADE PRODUCT.	5 / TIN						TECHNICAL SPECIFICATION : WAX HIGH CLASS PASTE FOR USE AS A GRP GENERAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP	
183	DPK64232	XG-279, G-403 (DEFSTAN 91-27 ISSUE 2 OF 2011)	915099220241 8 / GREASE AUTOMOTIVE & ARTILLERY XG-279 (G-403) (Packing 3KG TIN)		21 / KILOGRAMME						TECHNICAL SPECIFICATION - Composition: low viscosity mineral OIL and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TINGENERAL SPECIFICATION - Composition: low viscosity mineral OIL and water insoluble calcium soap DEFSTAN 91-27 Issue of 2003 03 LTR TIN	
184	DPK60138	ROCOL AEROSPE C 300 (XG291)	915099638180 8 / GREASE MULTIPURPOSE HEAVY DUTY XG-291 (G-421) 3 KG PACK	GENERAL GREASE	69 / KILOGRAMME						TECHNICAL SPECIFICATION - 1. Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of Manufacturing & ExpiryGENERAL SPECIFICATION - 1. Product is to be listed in TAPL 2. DEFSTAN 91-105/2 3. Valid product Conformity Certificate (PCC) required as per TAPL in accordance with DEFSTAN 01-5 Issue-17 4. OEM COC 5. OEM LAB Test Report indicating Batch Number, Date of Manufacturing & Expiry	
185	DPK64222	G-32	915079502411 9 / SHELL	REFRIGERANT	209 / LITER						TECHNICAL SPECIFICATION - REFRIGERATOR OIL GROUP DIN	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			HIGH QUALITY REFRIGRATOR OIL S2FR-A46	COMPRESSOR OIL							51503.KAA.KC GENERAL SPECIFICATION - REFRIGERATOR OIL GROUP: DIN 51503.KAA.KC	
166	SPK58339	SPIRAX S2 ATF D2 (9150-17-107-6129)	815070505210 0 / SHELL SPIRAX S2 ATF D2 (AUTOMATIC TRANSMISSION FLUID) UK STASCO SHELL (packing 209 ltrs drum)	FOR VBBS BOAT	209 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
167	DPC63465	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
168	DPC63538	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF CATERPILLAR (Packing 20 LITER or 05 Liter Can)	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	
169	SNMS6577	CV20747	688599301365 7 / THERMOSTAT E	SGA120283, PERKINS D/G 800 KVA UK	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG GENERAL SPECIFICATION - WIDTH: 85MM HEIGHT: 95MM DEPTH: 80MM WEIGHT: 0.21 KG	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
170	DNM674 36	757-10191	668572509520 6 / OIL PRESSURE GAUGE (RANGE 0 TO 5 BAR)	GAUGES & METERS LPWT4	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - RANGE 0 TO 5 BAR GENERAL SPECIFICATION - RANGE 0 TO 5 BAR	
171	DNM651 43	04- 8/105900	282072512106 6 / PACKING RING-60X68X1 (C-CU)	DIESEL DRIVEN COMPRESSO R W-30	2 / EACH/N UMBER	HATLAPA GMBH & EQUIPME NT CO (GERMA NY) (W30/40)					TECHNICAL SPECIFICATION - nil GENERAL SPECIFICATION - nil	
172	DNM670 17	7167-973D	432079512011 7 / CAM RING OF FUEL INJECTION PUMP (D/G)	FUEL INJECTION PUMP D/G	1 / EACH/N UMBER	6BT 5.9					TECHNICAL SPECIFICATION - Make Cummins (USA) OR DELPHI Model 6BT 5.9 GENERAL SPECIFICATION - Make Cummins (USA) OR DELPHI Model 6BT 5.9	
173	DNM653 25	260104-91	533101326290 4 / O RING (SEE COMD F8)	ALPHA LEVEL	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
174	DNM618 59	3805762	662073512650 7 / VALVE PLATE ASSY	COMPRESSO R D6SHI-350X AWMD	2 / EACH/N UMBER	D6SHI- 350X AWMD BELGIUM					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
175	DPK5735 5	OENOPER L	801074517562 7 / FOOD GRADE RESIN (OENOPERL 'cold applied' solventfree epoxy) (204KG packing) BRAND= MAXPERLES	COLD/COL ROOM	90 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
176	DPK5603 5		9150FP002000 2 / GREASE SHELL GADUS S2 V 100 2 (18 KG Packing)		108 / KILOGR AMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
177	SNM472 33	7E9658	471071512627 8 / CONTACTOR (WATER	D/G	2 / EACH/N UMBER						TECHNICAL SPECIFICATION - cert: caterpillar GENERAL SPECIFICATION - cert: caterpillar	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TEMPERATURE									
178	DPC88132	BS 627 (F-8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	10 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
179	DPC65931	BS 627 (F-8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	25 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
180	DPC67732	QG2684/D GA045	801017129654 8 / INTERTHANE 870 LIGHT GREY		100 / LITER	INTERTHANE870 LIGHT GRAY					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
181	SPC61290	407A	683079529301 8 / REFRIGERANT GAS 407A (in non returnable cylinder of 40 kg net)		40 / KILOGRAMME	407A					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
182	DNM64834	4573219	590578529161 5 / MAGNETIC CONTACTOR 32A		1 / EACH NUMBER	NXC-32					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
183	SNM61068	4573219	590578529161 5 / MAGNETIC CONTACTOR 32A		1 / EACH NUMBER	NXC-32					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
184	SNM55743	2W7585	312001212474 0 / THRUST WASHER		4 / EACH NUMBER	3512 TA					TECHNICAL SPECIFICATION - THRUST WASHER GENERAL SPECIFICATION - THRUST WASHER	
185	DNH59073	SV-82/ 320L LARGE LAUNDRY CART	351073528463 8 / WASCATOR WOODEN LAUNDRY TROLLEY (4 SECTION)		1 / EACH NUMBER	SV-82/ 320L LARGE LAUNDRY CART					TECHNICAL SPECIFICATION - Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape Square Number of Compartment: 04 Included Component: Wheel Handle Mounting Type: Floor Mount GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	%Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape: Square Number of Compartment: 04 included Component: Wheel, Handle Mounting Type: Floor Mount	
186	DPK57623	Castrol Radicool NF premix	293070528878 7 / Engine Coolant		450 / LITER	radiocool NF					TECHNICAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT GENERAL SPECIFICATION - SPEC DETAILS IS ATTACHED AS DOCUMENT	
187	DNM54011	0102-1543	533001573493 2 / joint-ump to cylinder block assembly (1 pair) / GASKET OIL BASE		2 / EACH/NUMBER	c22 d5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
188	SNM47246	8T-4132	531001413876 4 / NUT plain hexagon (M16X2-THD)		16 / EACH/NUMBER	C7.1					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
189	SPK58342	50053 0658 kz	915070524050 6 / avia syntofluid pe-b10 (hydraulic fluid) 1 LTR PACKING		5 / LITER	HYDRAULIC FLUID FOR THE RESCUE CAGE LEVELLING SYSTEM					TECHNICAL SPECIFICATION - OEM FUCHS GENERAL SPECIFICATION - OEM FUCHS	
190	DNM54252	932-060	294070526431 6 / OIL FITER		10 / EACH/NUMBER	C110D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
191	DNM67202	cwpac-212/ASCN-120D	412070517975 5 / A/C PLANT 10 TON	A/C plant	1 / EACH/NUMBER	CWPAC-212/ASCN-120D		SABRO TECHNOLOGIES (PVT).LTD PLOT # 270 INDUSTRIAL TRIANGLE KAHUTA ROAD ISLAMABAD PHONE NO +92-51-4490905 4490905 4490993	SABRO TECHNOLOGIES		TECHNICAL SPECIFICATION - COOLING CAPACITY 10 Ton CFM 3600 MOTOR CAPACITY 2 HP MOTOR RPM 1400 EVAP MOTOR FLA 3.3Amp COMPRESSOR FLA 10.9 Amp COND MOTOR FLA 1.4 Amp BELT TYPE B39(Grooved) AREA 8.5 sqft CONDENSOR 813MM X 1067MM GENERAL SPECIFICATION - COOLING	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tendor Remarks	TECH / GEN SPECS	Dimension
											CAPACITY 10 Ton CFM 3600 MOTOR CAPACITY 2 HP MOTOR RPM 1400 EVAP MOTOR FLA 3.3 Amp COMPRESSOR FLA 10.9 Amp COND MOTOR FLA 1.4 Amp BELT TYPE B39(Grooved) AREA 5.5 sqft CONDENSOR 813MM X 1067MM	
192	SPC58308	11528	793022258248 9 / DRY SAND 2 MM TO 2.6 MM	RO PLANT F- 22P SHIP SWRO- 1020PT3	1500 / KILOGR AMME	LOCAL		KNICKBERG 1G, D-21077 HAMBURGCONTACT NO 040/7038577-OFAX NO 040/7038577- 155INFO@ROCHEM DEFAX NO 040/7038577- 155INFO@ROCHEM.DE3		ROCHEM RO- WASSER BEHAND- LUNG GMBH, GERMAN Y	TECHNICAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUSTGENERAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUST	
193	DNM69501	1R-0749	533071516838 8 / FUEL FILTER	MAIN ENGINE CATERPILLAR	1/ EACH/N UMBER	C 18	T2P01336	3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905		CATTER PILLAR	TECHNICAL SPECIFICATION - CATERPILLAR ENGINE C 18 SEAL VALVE COVER 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905GENERAL SPECIFICATION - CATERPILLAR ENGINE C 18 SEAL VALVE COVER 3701 STATE ROAD 26 EAST TOWN LAFA VETTE IN POST CODE 47905	
194	DNM61393	060759	433071518528 0 / FLANGED TYPE OIL- REFRIGERAN T SEPARATOR	MAIN AC PLANT(STUS)	1/ EACH/N UMBER	A F 58889		ALCO CONTROLS P O BOX 1270011911 ADIE ROAD ST LOUIS USA Ph(314)569-4500 FAX (314)569-4593		ALCO CONTRO LS	TECHNICAL SPECIFICATION - DOUBLE CONECTION WITH SOLID COPPERGENERAL SPECIFICATION - DOUBLE CONECTION WITH SOLID COPPER	
195	DNM59587	213-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3/ EACH/N UMBER	Marine Genset C 4.4	CAT00C7 15GT00 677	CATERPILLAR INC PEORIAL IL 61629 US		CATERPI LLAR USA	TECHNICAL SPECIFICATION - MAKE: CATERPILLARGENERAL SPECIFICATION - MAKE: CATERPILLAR	
196	DPC61885	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-5 PARTIAL 25- 200 (2/lb)	DECK COVERING FOR CONCRETE SURFACE	20/ BAG			OEM ORIGINAL COLOR CHIPS.A DIVISION OF NORKAN INC. 26200 GROESBECK HWY. WARREN,MI.48089 PHONE:586-771- 6500/FAX:586-771-6501.		DRIGNAL COLOR CHIPS,A DIVISION	TECHNICAL SPECIFICATION - OEM ORIGINAL COLOR CHIPS.A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI. 48089 PHONE:586-771-6500/FAX 586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS RESINOUS FLOORING SYS GENERAL SPECIFICATION - OEM ORIGINAL COLOR CHIPS.A DIVISION OF	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											NORKAN INC. 28200 GROESBECK HWY, WARREN MI 48088 PHONE: 586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS, RESINOUS FLOORING SYS.	
197	DPK65773	PP 47-32 / P-903SW220-5TTL	4310FM045000 1 / POLYESTER OIL CARRIER COMPRESSOR (5 LTRS PACKING)	CHILL WATER UNIT	30 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE	CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE		TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE GENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE	
198	DPK62173	PP 47-32 / P-903SW220-5TTL	4310FM045000 1 / POLYESTER OIL CARRIER COMPRESSOR (5 LTRS PACKING)	CHILL WATER UNIT	45 / LITER	CARRIER		CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE	CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE		TECHNICAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE GENERAL SPECIFICATION - CARRIER CORP 1419 N MARKEET ST. SACRAMENTO, CA. UNITED SATE	
199	DNM80919	267-8398	294073522550 4 / FILTER ELEMENT AS-AIR (PRIMARY)	GENERATOR CATERPILLAR 33 KVA	1 / ASSEMBLY	DE33E0	E3G04236-39	CATERPILLAR INC. 108A CATERPILLAR DIV. GOVERNMENTAL AND DEFENSE PRODUCTS, MOSSVILLE, UNITED STATES. TEL:3095782353, FAX:3095783739	CATERPILLAR SARL		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR USED IN 33 KVA CATERPILLAR DG OF LLADR TO PURIFY THE AIR FOR COMBUSTION. AND FILTER REPLACED AFTER EVERY 500 SERVICE HOURS OR ONE YEAR. GENERAL SPECIFICATION - MAKE: CATERPILLAR USED IN 33 KVA CATERPILLAR DG OF LLADR TO PURIFY THE AIR FOR COMBUSTION. AND FILTER REPLACED AFTER EVERY 500 SERVICE HOURS OR ONE YEAR.	
200	DNM86319	3393041/4 334439	533071517706 1 / RING WEAR	MAIN ENGINE KTA50M2	1 / EACH IN LUMBER			CUMMINS INC. SOUTH CAROLINA USA	CUMMINS USA		TECHNICAL SPECIFICATION - RING WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE GENERAL SPECIFICATION - RING WEAR IS A PART OF SEA WATER PUMP FOR MAIN ENGINE	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											CUMMINS KTA50M2 16 CYL	
201	SNM45562	156595	5330009318048 / GASKET	3304PC CATERPILLER	15 / EACH/NUMBER		3512TA CATERPILLER	3512TA CATERPILLER	USA		TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR	
202	DNM66312	3393042/4334440	2930715177054 / IMPELLER	MAIN ENGINE CUMMINS KTA50M2	1 / EACH/NUMBER			CUMMINS Inc SOUTH CAROLINA, USA.	CUMMINS USA		TECHNICAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL GENERAL SPECIFICATION - Semi open impeller Fins/ Vanes 5 Dia 7" Height 2.15" IMPELLER FOR SEA WATER PUMP OF MAIN ENGINE CUMMINS KTA50M2 16 CYL	
203	DNM85910	0193-0468	2810715231058 / SENDER, LOW COOLANT	DIESEL GENREATOR C350 D5 UK	1 / UNIT	C350 D5	A13K447525	MANSTON COLUMBUS AVENUE RAMSGATE KENT ENGLAND CT125BS	MANSTON COLUMBUS UK		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
204	DNM54459	H43850	4720715179216 / XTREME DUTY AIR LESS HOSE	AIR LESS	1 / EACH/NUMBER			GRACO FLUID EQUIPMENT (SHANGHAI) CO. LTD. ROOM 118 1ST FLOOR NO2 XIN YUAN BUILDING NO 509, CAO BAO ROAD, SHANGHAI, P.R CHINA 200233	GRACO		TECHNICAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M) GENERAL SPECIFICATION - 3/8 IN X 50 FT (9.5 MM X 15 M)	
205	DNM59874	06414	4730715173026 / COP NYLON QUICK COUPLING	ABRASIVE BLAST CLEANING MACHINE	10 / EACH/NUMBER			CLEMCO INDUSTRIES CORP. USA WWW.CLEMCOINDUSTRIES.COM	CLEMCO		TECHNICAL SPECIFICATION - JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING GENERAL SPECIFICATION - JOIN 1-1/4 INCH HOSE (INTERNAL DIAMETER) x 2-3/32 INCH (OUTER DIAMETER, FIBER REINFORCED NYLON MATERIAL, BUILT IN LOCK SPRING	
206	SNM50735	214-7588	5331015135210 / SEAL O RING	MAIN ENGINE	64 / EACH/NUMBER	C-18 ACERT	T2P01491	CATERPILLAR USA	CATERPILLAR		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR PDPNMIT LETTER NO PNMIT/400/1201 DT 1.1 DEC 12 DAMEN SHIPYARDS P.O BOX 1-4200 A A GORINCHEM	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											HOLLAND TEL: 31 (0) 183-639811 31 (0) 183-632189 GENERAL SPECIFICATION - MAKE CATERPILLAR PDPNMIT LETTER NO PNMIT400/1201 DT 11 DEC 12 DAMEN SHIPYARDS P O BOX 1 4200 A A GORINCHEM HOLLAND TEL: 31 (0) 183-639911 31 (0) 183-632189	
207	SNM538 31	100-4461	530801524030 3 / BOLT (M10X1.5X50- MM)	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	20 / EACH/N UMBER	N/A	E3601292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE ENGINE DIVISION MOSSVILLE BLDG AC P.O. BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
208	SNM538 56	7W-6249	292001391834 7 / RELAY- SOLENOID ENGINE STARTER, ELECTRICAL	50KVA ALLIED CAT DG 400 VOLTS 3 PHASE 50 HZ	2 / EACH/N UMBER	N/A	E3601292	CATERPILLAR INC MANAGER, CUSTOMER SERVICE ENGINE DIVISION MOSSVILLE BLDG AC P.O. BOX 610 MOSSVILLE, ILLINOIS 61552-0610 COUNTRY USA	ALLIED CAT		TECHNICAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6 GENERAL SPECIFICATION - WIDTH (IN): 1 HEIGHT (IN): 0.85 LENGTH (IN): 2.6	
209	SNM434 56	6L1650	533100869657 4 / SEAL 'O' RING	CATERPILLAR MAIN ENGINE C-18?	10 / EACH/N UMBER		T2P01406	USA	CATER PILLAR		TECHNICAL SPECIFICATION - MAKE CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
210	DNM664 89	423-8521	281071522305 9 / FILTER G P. WATER SEP AND FUEL	caterpillar C-13 USA	1 / EACH/N UMBER	NA	NA	CATERPILLAR DIESEL GENERATOR SET Electric power North America Attr: Product support Manager AC 6109 Mossville, ILLinois 61552	CATER PILLER		TECHNICAL SPECIFICATION - OEM: CATERPILLAR GENERAL SPECIFICATION - OEM: CATERPILLAR	
211	SNM657 47	9L-6647	303014583534 2 / V BELT	MAIN ENGINE C-18 ACERT T2P1UP USA	2 / EACH/N UMBER	C-18 ACERT T2P1UP	1	3701 STATE ROAD 20 BAST TOWN ALFA VETTE IN POST CODE 47905 USA	CATERPI LLER USA		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
212	SNM613 57	124-3815	530870522957 5 / BOLT (M8X1.25X16- MM)	33KVA CATER PILLER DG DE033E0 UK	24 / EACH/N UMBER	DE033E 0	EJG0423 9/E3G042 38/E3G04 237/E3G0 4236	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATTERP ILLER U. K		TECHNICAL SPECIFICATION - Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.12 Thread: Coarse Thread Size (in - TPI) (in): M8-1.25 Material Description: Dimensions, tolerances.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											material, and quality requirements for hexagon flange head bolts. Metric-ISO 4162 Hexagon Bolts with Flange Inch- ASME B 15.2.1 Hex Flange Head Screws Notes: Thread Length (mm)3.125 Hole Thread Pitch: 1.25 <u>GENERAL SPECIFICATION</u> - Bolt Type: Hex Flange Head Coating: Zinc Plated Grip Length (in): 0.12 Thread: Coarse Thread Size (in - TP1) (lb): MS-1.25 Material Description: Dimensions, tolerances, material, and quality requirements for hexagon flange head bolts. Metric-ISO 4162 Hexagon Bolts with Flange Inch- ASME B 15.2.1 Hex Flange Head Screws Notes: Thread Length (mm)3.125 Hole Thread Pitch: 1.25	
213	DNM53028	CMPU-08	593078521157 7 / LOW PRESSURE SWITCH	5 TON AC CWFSC-8+CWCU-108 CHINA	8 / EACH/NUMBER	LPL-2545	NA	XIAN CHAUNG CHINA TSUEN WAN OFFICE YUEN SANG WATCH INDUSTRIES LIMITED 1ST FLOOR 100 TEXACO ROAD TSUEN WAN		XIAN HOUANG CHINA	<u>TECHNICAL SPECIFICATION</u> - null <u>GENERAL SPECIFICATION</u> - null	
214	DNM47835	2355057	433071518666 9 / FILTER ELEMENT FUEL	D/G CATERPILLAR C2.2	10 / EACH/NUMBER		JAW00494	USA		CATERPILLAR	<u>TECHNICAL SPECIFICATION</u> - oem caterpillar <u>GENERAL SPECIFICATION</u> - oem : caterpillar	
215	SNM57284	1542427	533089845029 5 / GASKET EXHAUST	D/G CATERPILLAR C2.2	1 / EACH/NUMBER		JAW00494	USA		CATERPILLAR	<u>TECHNICAL SPECIFICATION</u> - ITEM REQUIRED FOR TOH / MOH OF DG <u>GENERAL SPECIFICATION</u> - ITEM REQUIRED FOR TOH / MOH OF DG	
216	DPK88599	185-6727	284071518331 2 / LUB OIL SHELL RIMULA R6 M10W-40	D/G ENGINE	360 / LITER		31072013 12020714 D	CUMMINS ONAN USA		CUMMINS ONAN	<u>TECHNICAL SPECIFICATION</u> - LUB OIL SHELL REMULA R6 M10W-40- CUMMINS DIESEL GENERATOR ENGINE <u>GENERAL SPECIFICATION</u> - LUB OIL SHELL REMULA R6 M10W-40- CUMMINS DIESEL GENERATOR ENGINE	
217	DPK88877	FCW NIMA	915076522310 7 / SUZUKI/ADOL MARINE 4 STROKE	ENGINE OIL SUZUKI	350 / LITER	NA		SUZUKI THAILAND		CBM SUZUKI THAILAND	<u>TECHNICAL SPECIFICATION</u> - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ENGINE OIL 10W-40								manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5 GENERAL SPECIFICATION - SUZUKI MARINE ENGINE OIL 4 STROKE 10W40 CHARACTERISTICS PRODUCT NAME 10W40 Country of manufacturer Thailand Manufacturer Nippon oil Packaging Plastic canister Standard of compliance API SG Volume 5	
218	DPC572 26	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tail ship	40 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flaxborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN		TECHNICAL SPECIFICATION - undercoat primer white GENERAL SPECIFICATION - undercoat primer white	
219	DPC634 21	PILOT-II	801079517183 9 / MAMMUT PRIMER WHITE	Tail ship	80 / LITER			Jotun Paints (Europe) Ltd. Stather Road Flaxborough, Scunthorpe North Lincolnshire DN15 8RR England Tel: +44 17 24 40 00 00 Fax: +44 17 24 40 01 00 SDSJotun@jotun.com	JOTUN		TECHNICAL SPECIFICATION - undercoat primer white GENERAL SPECIFICATION - undercoat primer white	
220	DNM547 27	385720510	590599871629 1 / WATER TEMPERATURE SENSOR	COOLING SYSTEM	1 / UNIT	SDG15PS	00151403 045	S. M. JAFFER & CO, JAFFER HOUSE 17, TIMBER POND, KEAMARI (P. O. BOX No. 4488), KARACHI UAN: 0092-21-111-765-765 FAX: 0092-21-32851162 & 32850080 E-Mail: info@smjaffer.com	PERKINS		TECHNICAL SPECIFICATION - PART NO: 385720510 WATER TEMPERATURE SENSOR GENERAL SPECIFICATION - PART NO: 385720510 WATER TEMPERATURE SENSOR	
221	SPK5833 7	ARCTIC 32/146264	915079517025 6 / MOBIL EAL ARCTIC 32 (1 LITRE PACKING)	COMPRESSOR	40 / LITER		65703502	Mobil Oil Company Limited Acting as Agent for Mobil Lubricants UK Limited ExxonMobil House, Emryn Way Leatherhead, Surrey, KT22	Mobil Oil Company Limited		TECHNICAL SPECIFICATION - MOBIL EAL ARCTIC 32 GENERAL SPECIFICATION - MOBIL EAL ARCTIC 32	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								BUX Telephone: 01372-22-2000 ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728853				
222	DNM60591	435-6493	433071522487 7 / FUEL FILTER	Caterpillar DG DE200EUSA	12 / EACH / UMBER	CAT C 7.1	CAT00C7 1LECW03 124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728853	Caterpillar USA		TECHNICAL SPECIFICATION - OEM: CATERPILLAR DG GENERAL SPECIFICATION - OEM: CATERPILLAR DG	
223	DNM56296	435-6493	433071522487 7 / FUEL FILTER	Caterpillar DG DE200EUSA	20 / EACH / UMBER	CAT C 7.1	CAT00C7 1LECW03 124	ENERCON ASIA LTD 7 MANDAI LINK MANDAI CONNECTION #09-18/19 SINGAPORE 728853	Caterpillar USA		TECHNICAL SPECIFICATION - OEM: CATERPILLAR DG GENERAL SPECIFICATION - OEM: CATERPILLAR DG	
224	DNM54093	FF9011	294001523005 0 / Fuel Filter	CUMMINS 200 KVA DG	2 / EACH / UMBER	6CTA8.3	78515443	Cummins Americas Inc. 3350 SW 148 AVENUE SUITE 205 Miramar, FL 33027 USA Toll (1-954) 431-5511 Fax (1-954)433- 6797	USA		TECHNICAL SPECIFICATION - MAKE: CUMMINS USAGENERAL SPECIFICATION - MAKE: CUMMINS USA	
225	DPC57474	TUFF- BOND HANGER ADHESIVE	804001009800 1 / ADHESIVE, TUFF BOND	BULKHEAD AND DECKS LAGGING	8 / GALLO N			MOORE GOODLOE E INC DBA GEMCO 1019 GRIGGS ST DANVILLE IL UNITED STATES PSC: 61832-4116 TEL: 217-446-7900 DN: DUNS 001744697	MOORE GOODLO E E INC		TECHNICAL SPECIFICATION - Material RUBBER SYNTHETIC FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS GENERAL SPECIFICATION - Material RUBBER SYNTHETIC FOR BONDING METAL AND NYLON INSULATION HANGERS AND CLIPS	
226	DNM54821	943478	472099833298 7 / HOSE CLAMP (CHARGE AIR COOLER)	AIR COOLER	6 / UNIT	D6-3700- E	NA	AS VOLVO PENTA SE.406 08 GOTHENBURG SWEDEN	SWEDEN		TECHNICAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER GENERAL SPECIFICATION - MAKE: VOLVO PENTA , CHARGE AIR COOLER	
227	DPK81874	TEXAMATI C 1888 SAE DEXRON- III	915001487853 0 / STEERING LUB OIL (PETROL/DIES EL ENGINE MT VEHICLES) (01 ltrs packing)	MT VEHICLE	110 / BOTTLE			GENERAL MOTORS CORP 3044 W GRAND BLVD DETROIT MI UNITED STATES PSC: 48202-3991 TEL: 248-857-2576	GENERA L MOTORS CORP		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
228	DNM57290	2010TM- OR	291001353854 0 / 10 MICRON ELEMENT W/SEALS	DIESEL GENERATOR QSB7DM	3 / EACH / UMBER	500FG		PARKER HANNIFIN CORPORATION	PARKER HANNIFI N		TECHNICAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL GENERATOR CUMMINS QSB7DM 6 CYL GENERAL SPECIFICATION - 10 micron Element w/Seals FOR DIESEL	

S. No.	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											GENERATOR CUMMINS QS87DM 6 CYL	
229	DNM86798	450-9606/5034411	252015003511 2 / EMCP 4.2 (Engine Control Panel)	CATERPILLAR GENSET D3512B (YBB1) USA	1/ EACH/ NUMBER	NA	CAT3512 BEY8800 583	CATERPILLAR INC 100 N.E. ADAMS STREET PEORIA, IL 61629 USA	CATERPILLAR USA		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION - 0	
230	DNM58413	3067129	281578520786 0 / Assembly, fuel pump	320 KVA DG	1/ EACH/ NUMBER	NT-855- G8	11518	CUMMINS POWER GENERATION COLUMBUS AVENUE MANSTON PARK MANSTON RAMSGATE KENT CT12 5BF UNITED KINGDOM	CUMMIN S		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
231	DNM48034	1105326	294001468513 2/ FILTERELEMENT AS - AIR (PRIMARY)	80 KVA DG CAT USA	2/ EACH/ NUMBER	DE88EO	ZRE0132 3	CATERPILLAR INCI CATERPILLAR PRECISION SEALS 517 INDUSTRIAL PARK RD FRANKLIN, NC, USA TEL: 828-348-8400	CATERPI LAR USA		TECHNICAL SPECIFICATION - DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24 CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH GENERAL SPECIFICATION - DIESEL GENSET AT 88 KVA/70.4 KW STANDBY, 0.8 POWER FACTOR, 3 PHASE, 50 HERTZ, 400/230 VOLTS, 1500 RPM, PNAEL TYPE EMCP 4.1 PRIME POWER ISO RATING DRIVEN RADIATOR WITH CONTROL PANEL 50MM 24 CORE CABLE FOR 80 KVA DG HAVING LENGTH OF 30 FEET EACH	
232	DNM59587	233-5182	294001534870 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	3 / EACH/ NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. OBA CATERPI LLAR DIV GOVERN MENTAL AND DEFENS E PRODUJ		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
									TS			
233	DPK6385 8	SAPHIRE LO TEMP 2	815022309160 7 / LUBRICANT GREASE (ROCOL SAPHIRE LO TEMP 2) (18KG packing)	LLADR ANTENA	20 / KILOGR AMME			ITW CHEMICAL PRODUCTS SCANDINAVIA APS FORMELY: KEMA A/S ST1 PRIORSVEJ 36 CIT. SILKEBORG CTR DENMARK PSC: 8000 TEL: 86826444 FAX: 86826464	WUHAN BIN HU ELECTO NICS CO. CHINA		TECHNICAL SPECIFICATION - LUBRICATING GREASE GENERAL SPECIFICATION - LUBRICATING GREASE	
234	DNH648 54	NIL LOCAL	732070816380 7 / ELECTRIC ROTI PLANT 1000 CHAPATI MRS	ROTI PLANT	1 / EACH/N UMBER	Automatic Electric Roti Plant		M/S SHARIF ENGINEERING WORKS BAZAR KHARADAN GUJRANWALA	M/S SHARIF ENGINEE RING WORKS BAZAR KHARAD AN GUJRAN		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
235	DPC660 57	X0006938 5	681072523242 5 / COOLANT CS 10/90 CORROSION INHIBITOR PREMIX (PACKING 200 OR 20 LITER)	All MTU Engines	160 / LITER	CS 10/90	Various	MTU Friedrichshafen GmbH, Friedrichshafen Germany Website: www. mtu-online.com	MTU Friedrichs hafen GmbH		TECHNICAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added quality water 10% Coolant and 90% Water Manufactured by MTU GENERAL SPECIFICATION - CS 10/90 Corrosion inhibitor Pre Mix Pre diluted coolant with OEM added quality water 10% Coolant and 90% Water Manufactured by MTU	
236	DNM581 15	imp/gp/str/ 001	201071522103 3 / STERN TUBE FOR 50 MM SHAFT DIA	SHAFTING ARRANGEME NT.	3 / EACH/N NA UMBER			CUMMINS ENGINE CO. 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL: 843-745-1483	CUMMIN S USA		TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS, INCLUDING RUBBER GRP BEARING (WATER LUBRICATING), MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											50MM INCLUDING 2 RUBBER WALLED ENDS INCLUDING RUBBER GRP BEARING (WATER LUBRICATING). MACHINED TO ACCEPT TIDES MARINE SURE SEAL. FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
237	DNM56823	Imp/gp/stb/101	201071522103 3 / STERN TUBE FOR 50 MM SHAFT DIA	SHAFTING ARRANGEMENT	4 / EACH NUMBER	NA		CUMMINS ENGINE CO 4500 LEEDS AVENUE SUITE 500 NORTH CHARLESTON SC, USA TEL. 843-745-1483		CUMMINS USA	TECHNICAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS, INCLUDING RUBBER GRP BEARING (WATER LUBRICATING), MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED GENERAL SPECIFICATION - STEEL STERN TUBE, TO BE WELDED FOR SHAFT 50MM, DIMENSIONS, DIA 50MM INCLUDING 2 RUBBER WALLED ENDS, INCLUDING RUBBER GRP BEARING (WATER LUBRICATING), MACHINED TO ACCEPT TIDES MARINE SURE SEAL, FIRM'S QUOTATION ALONGWITH TECHNICAL SPECS IS ATTACHED	
238	DPC67392		047350473014 6 / ZINC OXIDE WHITE	FWT TAKE OFF DR.	20 / KILOGRAMME						TECHNICAL SPECIFICATION - DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX503R GRADE.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS</p> <p>REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) (IGNITED BASIS 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D4078 CADMIUM (CD) 0.002MAX 0.0003 ASTM D4078 IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER(CU) 0.001MAX 0.0001 ASTM D4075Q LOSS AT 110°C (MOISTURE) 0.25 MAX 0.15 ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2.500 LB NET WT PALLET, OR 2.000 LB FIBC. (PACKING 25 KG BAG) GENERAL SPECIFICATION - DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE I.I.C 800XL, KADOX</p>	

Sr No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF AID	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>930, AND KADOX XX503R GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES: THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS</p> <p>REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) IGNITED BASIS 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D4075 CADMIUM (CD) * 0.002 MAX 0.0003 ASTM D4075 IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER (CU) 0.001 MAX 0.0001 ASTM D4075 LOSS AT 110°C (MOISTURE) 0.25 MAX 0.15 ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2.500 LB NET WT PALLET, OR 2.000 LB FIBC. (PACKING 25 KG BAG)</p> <p>TECHNICAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING 01 KG PACKET) GENERAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100%</p>	
230	DPC585 54		047350473004 0 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGR AMME							

S No	EPR No	PART NO	NSN / Description	Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
240	DPC618 26		047350473004 0 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGR AMME						TECHNICAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET) GENERAL SPECIFICATION - MOLECULAR FORMULA: Zn3 P2 MOLECULAR WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)	
241	DPK6151 9	DEFSTAN 01-5	047550220234 8 / BRAKE FLUID DOT-4 AUTOMOTIVE BRAKE OIL OX-8 NATO CODE H-542 (01 LTR)		380 / LITER						TECHNICAL SPECIFICATION - SPECIFICATIONS: SAE J1704 Rev Sep 2006 (DEFSTAN 01-5/17) GENERAL SPECIFICATION - SPECIFICATIONS: SAE J1704 Rev Sep 2006 (DEFSTAN 01-5/17)	
242	DPC684 31		044250442004 8 / PAINT FOR INTERIOR (PALE GREEN)	FINISHING INTERIOR	500 / LITER						TECHNICAL SPECIFICATION - To be tested against DEFSTAN: 80-78/2 of 1995. Stage Inspection Prescribed Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. 4. NSIP/002 of Apr 2013 (Revised) Except for Packing GENERAL SPECIFICATION - To be tested against DEFSTAN: 80- 78/2 of 1995. Stage Inspection Prescribed, Colour Shade No 216 (EAU-DE-NIL) to BS: 381-C of 1996. 4. NSIP/002 of Apr 2013 (Revised) Except for Packing	
243	SPC5485 0	NO DATA AVAILABL E	044250442015 1 / PAINT ZINC RICH EPOXY HARDENER (Component B)	BUXLY/BERGE R/ICM/KOSAR GRP-A VIDE NHQ LT	100 / LITER						TECHNICAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY WITHIN 1 HRS (B)	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TACK FREE WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ. METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUPLY THINNER EP-TH- 10 (xi) % OF ZINC IN AGENT 70% MIN GENERAL SPECIFICATION - (i) TYPE TWO PACK (ii) MIXING RATIO COMPONENT 'B' 1 PART MIX ONLY THE QUANTITY WHICH CAN BE CONSUMED WITHIN 1-2 HOURS (iii) DRYING TIME (A) SURFACE DRY WITHIN 1 HRS (B) TACK FREE WITHIN 6 HRS RECOAT: MIX 24 HRS MIX 04 HRS (iv) CONSISTENCY THIXOTROPIC (v) COLOUR GREY (vi) GLOSS MATT TO EGG SHELL (vii) SPREADING RATE 4-6 SQ. METERS PER LITER PER COAT (viii) FLASH POINT (BELOW) 23 DEGREE C (ix) COATING RECOMMENDED 1-2 COATS (x) THINNER BUPLY THINNER EP-TH- 10 (xi) % OF ZINC IN AGENT 70% MIN	
244	SPC6123 4		047450474001 2 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		70 / EACH IN UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
245	DPC590 36		047450474001 2 / DEOXIDISING TUBE (1 TUBE =25 GRAMS)		10 / EACH IN UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
246	DPK6352 6		047450910052 4 / GREASE NAVAL	XG-460	111 / KILOGR. AMME						TECHNICAL SPECIFICATION - TECHNICAL DATA (TYPICAL VALUES) APPEARANCE = FIBROUS	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
			GRAPHITE XG-460 3 KG PACK								<p>GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)</p> <p>GENERAL SPECIFICATION:- TECHNICAL DATA (TYPICAL VALUES) APPEARANCE =FIBROUS GREASE COLOUR = BLACK NLGI CLASSIFICATION = UNWORKED PENETRATION (IP50) =400-430 WORKED PENETRATION (IP50) = 400-430 BASE OIL VISCOSITY (IP71) @ 400C CST = 600 @ 1000C CST =34 FOUR BALL (IP 239) WELD LOAD KGS =315 TIMKEN OK LOAD IBS =45 OPERATING TEMPERATURE RANGE = -25 TO + 1000C DEFSTAN 1-5 (XG-460)</p> <p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE.GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
247	SNM523 79	AF-1811	294001435547 5 / AIR FILTER (AF1811-1)	3512.CATER PILLAR ME USA	4 / EACH/NUMBER	3512					TECHNICAL SPECIFICATION - NO DATA AVAILABLE.GENERAL SPECIFICATION - NO DATA AVAILABLE	
248	DNM268 76	4W07891 05-2506	291501202589 3 / PUMP (PRIMARY FUEL PUMP/HAND PUMP)	3306.FUEL SYS. CATERPILLAR D/G USA	1 / EACH/NUMBER	3306 & 3304B					<p>TECHNICAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : ALIX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA) 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</p> <p>GENERAL SPECIFICATION - (a) NSN NO : 2915-01-202-5893 (b) SHIP : ALIX MEEZAN (c) ENGINE S NO : 18668 (d) MAKE/ MODEL : CAT (USA) 3304 PC (e) PARENT EQUIPMENT : CATERPILLAR 3304 PC</p>	
249	DNM654 90	5N9359 (3040-01-203-0160)	304071503513 0 / SHAFT, SHOULDERED	INDUSTRIEL MARINE CATER	1 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Spine Empty</p> <p>GENERAL</p>	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CA-LG168MM-COLLAR-DIA34.8MM SPLINED ENDED	PILLER DG							SPECIFICATION - Collar-Dia34.8mm Shaft 168 mm Splined Ended	
250	DNM64501	5N9360 (4320-01-201-2865)	432071503513 1 / IMPELLER ASSY (D18M07Y13P472) ID25 O/D60MM 12FINS RUBBER INNER SLEEVE BRASS	INDUSTRIEL MARINE CATERPILLER ENGINE	1 / EACH/NUMBER	5n-9360					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
251	DNM67481	NO DATA AVAILABLE	461071508959 0 / WATER FILTRATION SYSTEM MABZI - THREE STAGES		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER) QUANTITY 01 GENERAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER) QUANTITY 01	
252	DNH61499	DV-200N	431079511348 5 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
253	DNH69337	LS-R126AAL	412070509931 7 / AIR CONDITIONER (SPLIT WALL MOUNTED 01 TON)	AIR COND OEM LG ELECTRONIC S.NEW ALLIED	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
254	SNM43738	OS1594	530800260450 8 / BOLT	3304PC. CATERPILLER D/GEN USA	20 / EACH/NUMBER	3304PC. 3304					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
255	SPC67813	11528	793022258248 9 / DRY SAND 2 MM TO 2.6 MM	RO PLANT F- 22F SHIP SWRO-1020PT3	1750 / KILOGRAMME	LOCAL		KNICKBERG 1G, D-21077 HAMBURG CONTACT NO 040/7038577-0 FAX NO 040/7038577-155 INFO@ROCHEM. DEFAX NO 040/7038577-155 INFO@ROCHEM.DE3	ROCHEM RO-WASSER BEHANDLUNG GMBH GERMANY		TECHNICAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUST GENERAL SPECIFICATION - SAND MUST BE DRY AND 100 % FREE OF DUST	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
256	DNM538 65	29010560	471073528147 3 / HYDRAULIC PIPE L=564		2 / EACH / UMBER	KESLA 204T					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
257	SNM593 14	233-5182	294001534670 9 / Filter Element As-Air (Primary)	Caterpillar Emergency DG Marine Genset C 4.4 USA	10 / EACH / UMBER	Marine Genset C 4.4	CAT00C7 15GTY00 677	CATERPILLAR INC PEORIAL IL 61629 US	CATERPI LLAR USA		TECHNICAL SPECIFICATION - MAKE CATERPILLAR GENERAL SPECIFICATION - MAKE CATERPILLAR	
258	SNM624 93	00530 / 0 62774	291012342781 7 / SWK 2000/05 UMK SEPARATOR FILTER ELEMENT	MAIN ENGINE	10 / EACH / UMBER		T2P01336	WILLI BRORD LOSING FILTER TECHNIK g-k 45517 HATTINGEN GERMANY	GERMAN Y		TECHNICAL SPECIFICATION - Swk 2000/05 Umk SEPARATOR FILTER ELEMENT CATERPILLAR INC. 3701 STATE ROAD 26 EAST LAFAYETTE IN POSTCODE 47005 USA information details is attached as document GENERAL SPECIFICATION - Swk 2000/05 Umk SEPARATOR FILTER ELEMENT CATERPILLAR INC. 3701 STATE ROAD 26 EAST LAFAYETTE IN POSTCODE 47005 USA information details is attached as document	
259	DNF6853 3	2H1A4AS / VIEWSONI C VX2753M H-LED	582071516381 2 / LED MONITOR 27 INCHES	HARPOON INTERACTIVE (HITS)	3 / EACH / UMBER			M/S VIEW SONIC AMERCA WORD HQ 381 BREA CANYON ROAD WALNUT, CA 91789-0708 USA TEL +1 909 444 8888 FAX +1 909 466 1240.	M/S VIEW SONIC AMERCA WORD HQ 381 BREA		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
260	DNF6857 1	DH-IPC- HFV2231 T-ZS-S2 / ZKIP370	583678517105 9 / IP FIXED CAMERA WITH HOUSING & MOUNTING	N/A	3 / EACH / UMBER	ZKIP370		CHINA	CHINA		TECHNICAL SPECIFICATION - MODEL ZKIP 370 IMAGE RESOLUTION 1280*720 POWER SUPPLY POE 802 3af Gross weight 66 Kg GENERAL SPECIFICATION - MODEL ZKIP 370 IMAGE RESOLUTION 1280*720 POWER SUPPLY POE 802 3af Gross weight 66 Kg	
261	SNM680 20	261-8744	533000567797 8 / GASKET	DG CAT7.1 USA	5 / UNIT	CAT7.1	NA	CATERPILLAR INC PEORIAL IL 61629 USA	CATERPI LLAR USA		TECHNICAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA CATERPILLAR DG GENERAL SPECIFICATION - ITEM IS CRITICALLY REQUIRED FOR MAINTENANCE OF 150 KVA	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / GENO	Model	SR NO OF PR	MANUF ADD	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
											CATERPILLAR DGs	
282	SNM60091	3B-4505	5310795229944 / LOCKWASHER	33KVA CATERPILLER DG DEO33E0 UK	12 / EACH/NUMBER	DEO33E0	E3G0423 9/E3G042 38/E3G04 237/E3G0 4238	CATTERPILLER SARL C/O EAME Power System, Building 21 Millennium Springvale Business Park Belfast BT	CATERPILLER UK		TECHNICAL SPECIFICATION - PART MANUAL C3.3 DE33E0 GENERATOR SET GENERAL SPECIFICATION - PART MANUAL C3.3 DE33E0 GENERATOR SET	
263	DNC68418	WBCL002301/023x1471	4130745133149 / BI-FLOW FILTER/DRYER 1/2 FOR CHILLER-42 T050 MONO	A/C SYSTEM PNS KARRAR	2 / EACH/NUMBER	NO DATA AVAILAB LE		FR	WEBAST O MARINE COMFORT FRANCE	OEM: DANFOSS	TECHNICAL SPECIFICATION - oem: Danfoss source of availability YONK-ONUKJV GENERAL SPECIFICATION - oem: Danfoss source of availability YONK-ONUKJV	
264	DNS68891	191 051	3100735186042 / BALL BEARING	WARTSILA MAIN ENGINE BL20C3 FINLAND	4 / EACH/NUMBER	BL20C3	MADPAA E084245, PAAE084242 RASDPA AE084243 PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantie 2, FIN-65101 Vaasa, Finland Tel: +358 10 708 0000; Tlx 74251 wa sf Fax (Service) .358 6 358 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TP GENERAL SPECIFICATION - TP	
265	SNM59314	233-5182	2940015348709 / Filter Element As-Air (Primary)	Caterpillar, Emergency DG Marine Genset C 4.4 USA	10 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		TECHNICAL SPECIFICATION - MAKE: CATERPILLAR GENERAL SPECIFICATION - MAKE: CATERPILLAR	
266	SNM68995	10000-05598	5120795198973 / OIL FILTER	PERKINS P-200-3 UK	1 / EACH/NUMBER	P-200-3	PR83167 R007382 A	F.G.WILSON (ENGINEERING) LTD CHURCH ROAD WHITE HOUSE NEWTOWNABEY, BELFAST BT36 7LN NORTHERN IRELAND, UK	PERKIN UK		TECHNICAL SPECIFICATION - ITEM USED IN LUBRICATION SYSTEM GENERAL SPECIFICATION - ITEM USED IN LUBRICATION SYSTEM	
267	DNF68674	PS12260NB	6135715141490 / RECHARGEAB	LPS	24 / EACH/NUMBER	NO DATA AVAILAB LE		US	M/S POWER SONIC		TECHNICAL SPECIFICATION - OEM: M/S POWER SONIC CORPORATION 7550 PANASONIC	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			LE DRY BATTERY 12V 26AMP/HR SIZE W,16.5 CM H,12.5CM L,17.5CM						CORPORATION 7550 PANASONIC WAY SANDIEGO CALIFORNIA USA		WAY SANDIEGO CALIFORNIA USA GENERAL SPECIFICATION - OEM M/S POWER SONIC CORPORATION 7550 PANASONIC WAY SANDIEGO CALIFORNIA USA	
268	DPC691 51	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE - GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
269	DPC690 98	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable cylinder with protection cap/color. Each Cylinder containing 5-7 Cum Acetylene		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE - GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	
270	DPC689 70	0443-443003	044350224043 9 / GAS ACETYLENE TECHNICAL (96.6% Purity) in buYer/supPliEr returnable		138 / CUBIC METER						TECHNICAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE - GENERAL SPECIFICATION - CGA G1.1 OF 1990 GRADE-H OF TABLE-I	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimensions
			cylinder with protection cap/collar. Each Cylinder containing 5-7 Gum Acetylene									
271	SNM659 57	HL003446	431072505541 8 / SPRING PIN(STEEL) SIZE LG28MM TH4MM	HATALPA ELECTRICAL AIR COMPRESSO R	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
272	SNM660 15	HL020030	431072505542 5 / DISTANCE RING (STEEL) SIZE LG15. 2MM TH8MM ID5.5MM	HATALPA ELECTRICAL AIR COMPRESSO R	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
273	DNHB48 31		414070504164 0 / DESERT AIR COOLER 220/240V AC SINGLE PHASE FULL SIZE	DESERT AIR COOLED 220/240VAC	5 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
274	DNM600 38	050307	536512191242 7 / SPACER RING 3RD STAGE	HP AIR COMPRESSO R-150-BAR (GERMANY)	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
275	SNM624 99	5P-0840	533101317950 2 / SEAL O RING	3512TA, CATERPILLER USA	51 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
276	DNF6878 1	TOA / A- 1512	583576510188 6 / AMPLIFIER 120 WATT, 120VAC,50HZ	SRE SYSTEM, TOA JAPAN	3 / EACH/N UMBER					OEM TOA JAPAN	TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
277	DNF6828 3	AMV PTCU/ 1077183	597571506375 3 / LINE CORD TELEPHON CABLE 18/38 (100M ROLL)	LIQUID DI- ELECT.TEST SET LD-80 OEM/TEC	2 / ROLL						TECHNICAL SPECIFICATION - length per roll 100 mtr oem, PTCL CABLES PAKISTAN TELEPHONE CABLES LIMITEDGENERAL SPECIFICATION - length per roll 100 mtr oem, PTCL CABLES PAKISTAN TELEPHONE CABLES LIMITED	
278	DNF6866 7	RL2400L	614070505487 5 / BATTERY		1 / SET	RL2400L					TECHNICAL SPECIFICATION - (NARDAR)PHONIX	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEMO	Model	SR NO OF PR	MANUFACTO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SECONDARY 8V 400AH LEAD ACID (4CELLS FOR 01 BATTERY)								KOREA GENERAL SPECIFICATION - (MARDAR) PHONIX KOREA	
279	DNF6878 4	DL-108	624078503086 7 / TUBE LIGHT FLOURESCEN T 220/230V 30W SIZE 894X32.5MM	LIGHTING SYSTEM	80 / EACH / N UMBER	DL-108					TECHNICAL SPECIFICATION - 220/230V 30W SIZE 894X32.5MM oem: philips pakistan GENERAL SPECIFICATION - 220/230V 30W SIZE 894X32.5MM oem: philips pakistan	
280	DPC584 09	NO DATA AVAILABL E	916071501638 8 / COMPOUND HONEY WAX MOULD RLSE (Packing 14OZ Tin)	BEST TRADE PRODUCT	12 / TIN						TECHNICAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP GENERAL SPECIFICATION - WAX HIGH CLASS PASTE FOR USE AS A GRP	
281	DNF6842 2	6KP	583073512485 1 / INTERCOM SYSTEM WITH JUNCTION BOX & ACCESSORIE S	INTERCOM SYSTEM 6KP KOREA	1 / EACH / N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
282	DNF6878 2	MCTX- CAT6	591570524871 0 / CAT 6 networking cable		400 / METER	MCTX- CAT6					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
283	DNF6867 3	6701-537	613573527071 2 / LUMINAL CELL (PACK OF 6 CELLS)		1 / EACH / N UMBER	NA					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
284	SNM659 91	350-2375	473071523833 3 / tube asSEMBLY		1 / EACH / N UMBER	C7-1502- 117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
285	SNM659 94	281-7040	533001567776 2 / GASKET		1 / EACH / N UMBER	C7.1					TECHNICAL SPECIFICATION - NOT KNOWN GENERAL SPECIFICATION - NOT KNOWN	
286	SNM660 19	277-2925	471001567798 8 / connection as		1 / EACH / N UMBER	C7-1502- 117					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
287	DNF6772 1	EW-AL16 / JVA-N751	612070524905 6 / JVA 1.6mm		3 / ROLL	namtek EW-AL16					TECHNICAL SPECIFICATION - OUTDOOR ACCESSORIES of	

S. No	LPR No	PART NO	NSN / Description	#/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ALUMINIUM Alloy Fence Wire (p/roll 1000M)								efence rod. oem nembak & jva ltd. MATERIAL: ALUMINIUM, ALLOY SOLID, TENSILE: 1.6MM 60-70 RESISTANCE: 1.6MM 27OHM/KM ELONGATION: 10-11% GENERAL SPECIFICATION - OUTDOOR ACCESSORIES of efence rod. oem nembak & jva ltd. MATERIAL: ALUMINIUM, ALLOY SOLID, TENSILE: 1.6MM 60-70 RESISTANCE: 1.6MM 27OHM/KM ELONGATION: 10-11%	
288	SNM593 17	UK211D1	312078528191 7 / BALL BEARING UK211D1		2 / EACH/UMBER	uk211					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
289	SNM669 90	0147-0921	473001573499 9 / NOZZLE & HOLDER ASSY (C17 D5, C22 D5, C28 D5)		3 / EACH/UMBER	C22 D5					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
290	SNM669 91	UPRK0005	252099216194 9 / PISTON RING KIT		2 / EACH/UMBER	1103C-33T DG323036					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
291	SNM538 38	367-5789	471071526910 1 / TUBE		4 / EACH/UMBER	DE110E2					TECHNICAL SPECIFICATION - TUBE GENERAL SPECIFICATION - TUBE	
292	SNM624 92	2654408	294070524659 6 / lubricating oil filter		10 / EACH/UMBER	3-2500					TECHNICAL SPECIFICATION - MAKE: PERKINS GENERAL SPECIFICATION - MAKE: PERKINS	
293	SNM659 93	458-5183	294071523833 9 / line as		1 / EACH/UMBER	C7-1502-117					TECHNICAL SPECIFICATION - DETAILED ATTACHED IN DOCUMENT GENERAL SPECIFICATION - DETAILED ATTACHED IN DOCUMENT	
294	DNF6877 1	RSFD-II	813578528471 7 / EXTERNAL & INTERNAL LIGHT LIFERAFT BATTERY		6 / EACH/UMBER	RSFD-II					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
295	SNM669 94	3908615/L F3959	294001280841 9 / CARTRIDGE	Cummins SSDG (Englis)	28 / EACH/UMBER			500 JACKSON ST, COLUMBUS	CUMMIN		TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NG OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
		(LF0334900)	LUB OIL FILTER ELEMENT D/G LF3349FLEET GUARD	68T5.9-GM83 USA	UMBER			812-377-3920 FAX NO 812-377-1715 STEVE.A. HEWITT@CUMMINS.COM FAX NO 812-377-1715 STEVE.A. HEWITT@CUMMINS.COM	ENGINE COMPANY, INC		SPECIFICATION - NO DATA AVAILABLE	