

## TENDER BULLETIN

DATE & TIME 9/5/24 9:47 AM

INVITATION TO TENDER TO BE OPENED ON 9/23/2 10:00 AM

AND ITEM REQ BY

**CONDITIONS**

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF4890 1	0102-034002-226	611078515447 1 / MAIN CONTACTOR 95 AMP COIL VOLTAGE 220V AC	L/PAC	1 / EACH/NUMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC;COIL VOLTAGE 220V AC RATING 95A.	
2	DNF4867 3	HY5005E	613071520490 0 / DC POWER SUPPLY DUAL 50V VARIABLE	Dr.Meter HY5005E USA	3 / EACH/NUMBER	HY5005E		33442 Western Ave, Union City, CA 94587, USA Phone: +1-888-530-9912 E-Mail: support@hisgadget.com Web: http://www.hisgadget.com Twitter: https://twitter.com/Hisgadget	hisgadget		TECHNICAL SPECIFICATION - Display Switching Dual DC Power Supply, Variable Dual Output 0-50V @ 0-5A.GENERAL SPECIFICATION - Display Switching Dual DC Power Supply, Variable Dual Output 0-50V @ 0-5A	
3	DNF6784 0	NIKON 850 DSLR	635076522555 5 / NIKON 850 DSLR CAMERA ALONG WITH LENS 24-120 MM	STILL CAMERA	1 / EACH/NUMBER	NIKON 850 DSLR	NA	NIKON JAPAN	NIKON		TECHNICAL SPECIFICATION - HARD COPY IS ATTACHED.GENERAL SPECIFICATION - HARD COPY IS ATTACHED	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
4	DGE65935	Art 38600	8430725198427 / SHOES ARROW CLOG WHITE ESD (SIZE 44)	All ESD GERMANY	15 / PAIR	NIL	NIL	Abeba Spezial schuhausstatter GmbH Schlackenbergrasse 5 6638 St. Ingbert +49 06894-3103-100	M/s Abeba		<p><b>TECHNICAL SPECIFICATION</b> - Size 44 CE, EN ISO 20347:2012, OB, A, FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining</p> <p><b>GENERAL SPECIFICATION</b> - Size 44 CE, EN ISO 20347:2012, OB, A, FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining</p>	
5	DGE65792	Art 38600	8430725198427 / SHOES ARROW CLOG WHITE ESD (SIZE 44)	All ESD GERMANY	15 / PAIR	NIL	NIL	Abeba Spezial schuhausstatter GmbH Schlackenbergrasse 5 6638 St. Ingbert +49 06894-3103-100	M/s Abeba		<p><b>TECHNICAL SPECIFICATION</b> - Size 44 CE, EN ISO 20347:2012, OB, A, FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining</p> <p><b>GENERAL SPECIFICATION</b> - Size 44 CE, EN ISO 20347:2012, OB, A, FO, SRA Smooth leather, perforated, white Leather heel patch Heel strap non-foldable, adjustable instep area padded with elastic band Velcro fastening Non-slip PU walking sole Sanitized treated ESD dissipative as per DIN EN 61340 Leather lining</p>	
6	DNF67713	P. 0143000-A /YT-100B	5660785172597 / COMPOSITE MATERIALS E-FENCE ROD S.S POLE SQUARE TUBE ANGLED TYPE, BLACK	PSS	380 / EACH/NUMBER	YT-100B E-Fence Controller		M/s CETC International Co. Ltd. CETC Mansion, No.5 Wulotong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		<p><b>TECHNICAL SPECIFICATION</b> - Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1.6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			PODER COATED & HOT DIP GALVANISED WITH ACCESSORIE S.								(100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICP/8885791 DT. 05-6-24 GENERAL SPECIFICATION -Material: Square tube Materials E-Type: Angled Fence Rods Dimension: 20 x 20 x 1,6mm Finish: Black Powder Coated and Hot Dip Galvanised with following accessories: (1) Shield Insulator - Black (2) Jurassic Screw (3) Warning Sign (4) Ferrules - 6mm Aluminum (100 Pack) (5) Spring (6) Tensioner (7) Spring Hook (8) RAWAL BOLTS (9) POLE CAP (10) NUT BOLTS 11) SS SUPPORT 12) SIREN 12VDC15W (ES-626) nsn-6350785308363 13) E-FENCE LIGHT(SR-FL/TL/G) nsn-6230735308362 NOTE: ITEM S.NO. 12,13 IS NOT ACCESS. OF E-FENCE ROD BY NEMTEK imfo to GMPMSUR VIDE CICP/8885791 DT. 05-6-24	
7	SNF5464 6	BSB-1104 TIM DIN	592576516079 6 / MCB 2 POLE 220 V 30AMPS	CONVERSION OF BOATSWAIN INTO MRO/BEHR KUSHA	10 / EACH/N UMBER	BSB-1104 TIM DIN		M/S DIGI TECH SHOP NO2 NEW MEMON CHAMBER ALTAF HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL 2639514&2638482		M/S DIGI TECH SHOP NO2 NEW MEMON	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
8	SNF1835 1	5SX4106-7	592512353527 6 / MCB- SINGLE POLE 6A	D/G	2 / EACH/N UMBER	NO DATA AVAILAB LE		PK		SIEMEN PAKISTA N ENGINEE RING CO LTD AUTOMA TION&DR	TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	--------------	----------------	------------------	-----------

IVE  
DIVISION  
BU  
SMALL&L  
ARGE B-  
72ESTAT  
E  
AVNEUE  
SITE PO  
BOX  
7158PH#  
92(021)  
2574910-  
19  
KARACHI  
75700

9	DNF60716	P-0190000	5140785167178 / EQUIPMENT BOX (650*750*250) MM PORTABLE MATERIAL, Stainless Steel, grade 316L	PSS	1 / EACH/NUMBER			M/s CETC International Co., Ltd. CETC Mansion, No.5 Wululong North Street, Xicheng District, Beijing, China 100120.	M/s CETC International Co., Ltd.		TECHNICAL SPECIFICATION - EQUIPMENT BOX METAL (650*750*250) MM PORTABLE material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wululong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer GENERAL SPECIFICATION - EQUIPMENT BOX METAL (650*750*250) MM PORTABLE material: STAINLESS STEEL GRADE: 316L M/s CETC International Co., Ltd. CETC Mansion, No.5 Wululong North Street, Xicheng District, Beijing, China 100120. Box: DP Box for Energizer	
10	DNF58531		6070705229821 / 24 JOINT BOX	PSS SYSTEM	2 / EACH/NUMBER	24 JOINT BOX	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		TECHNICAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type GENERAL SPECIFICATION - 1. Water proof 2. 24 core optical fiber splice box horizontal type	
11	DNF56272	SC/UPC-SC/UPC	6099705229819 / PATCH CHORDS FIBER (1.5	PSS SYSTEM	1 / EACH/NUMBER	SM-SC-LC	NIL	LTE LUB THATOO, ABBOTABAD ROAD, HASANABDAL, PAKISTAN	LTE		TECHNICAL SPECIFICATION - PATCH CHORDS FIBER (1.5 MTR) SC - LC GENERAL SPECIFICATION - PATCH CHORDS FIBER (1.5 MTR)	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			MTR) SC - LC								SC - LC	
12	DNF67715	P-0018	6145785164976 / BVR1*8MM (YELLOW&GREEN)/POWER CABLE	PSS	1800 / METER	BVR1*6mm (Yellow&Green)		CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA. 100120	M/S CETC INTERNATIONAL CO LTD		TECHNICAL SPECIFICATION - OEM M/S CETC INTERNATIONAL CO. LTD DIAMETER 6mm Yellow&Green 1-Core GENERAL SPECIFICATION - OEM M/S CETC INTERNATIONAL CO. LTD DIAMETER 6mm Yellow&Green 1-Core	
13	SNF51754	ACC2425BB-3	5925725129139 / CIRCUIT BREAKER 24VDC, 25AMPS(F8)	CUMMUNICAT ION SYSTEM	2 / EACH/NUMBER			GR		DIGI TECH DENSO HALL KARACHI	TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
14	DNF60627	DCC/HFB M/EL/004	5995705214358 / DAFS UNIT	DF RACK 100C2ZL PAK	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, KHI 021-35363212		DCC	TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
15	DNF67025	N1537	6110705155260 / ENERGY SAVER 220V-240V ,11W. (screw type)	SELF, FOR DISTRIBUTION SYS.	264 / EACH/NUMBER			SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI.		PHILIPS CO LTD.	TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE-RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi GENERAL SPECIFICATION - SOURCE OF AVAILABILITY: PHILIPS CO LTD, ROSHAN ELECTRIC STORE JUPLTER MARKET SERAI ROAD DENSO HALL KARACHI. PRICE-RS140 PKR. REQ:1000. FOR GENERAL LIGHTING. SPECS:220-240V 11W. OEM: Pierlite OEM Email: www. Pierlite.com Country of Origin: China. 2. Philips Pakistan Address: K-2/I, 11 Main Ch Khaleeq Uz Zaman Road Gizri Karachi	
16	DNF64020	DH-PFM900-E/IPC	5820735231645 / ALMIGHTY IPC TESTER	CCTV VIGIL SYSTEM	1 / EACH/NUMBER	IPC9300S ACT		M/S OPENPINOY PHILPINE TELL NO. (02) 8722-0909.FAX NO. (02)		M/S OPENPINOY	TECHNICAL SPECIFICATION - BROUCHER ATTACHGENERAL SPECIFICATION - BROUCHER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
-------	--------	---------	-------------------	-------------	------------	-------	-------------	-----------	-------------	----------------	------------------	-----------

		9800ADH Plus IPC9300S	FOR CCTV CAMERA VIGIL SYSTEM				8570-0909				ATTACH	
--	--	-----------------------	------------------------------	--	--	--	-----------	--	--	--	--------	--

17	DGE664 79	NO DATA	035059571311 NYLON, 8 / ROPE HAWSERLAD, 3-STRD, CIRC: 5/8"(0.625"), DIA: 3/16" (0.1875"), (5MM)		240 / FATHO M	NO DATA					TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004. 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
18	DGE575 93	035059571312 8 / ROPE NYLON, HAWSERLAD, 3-STRAND, 2-LAY, NOM DIA: 20MM, (13/16"), CIRC: 2.50 INCH, TYPE-1			780 / FATHO M						TECHNICAL SPECIFICATION - 1. STANDARD FOR NYLON EN ISO 1140 OF 2004, ISO 2307 OF 2005 & ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM PER COIL. 3. Function Binding, Climbing, Rescue, Pulling-GENERAL SPECIFICATION - Pulling-GENERAL SPECIFICATION - CERTIFICATE OF CONFORMITY AND OEM I CERTIFICATE SUPPLY 2. 120 FATHOM PER COIL. 3. Function Binding, Climbing, Rescue, Pulling	
19	DGE629 32	035059571323 0 / ROPE			400 / FATHO						TECHNICAL SPECIFICATION - Characteristics: Excellent resistance	

S. No	LPR No	PART NO	NSN / Description	P:Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SISAL HAWSERLAID, 3-STRAND, DIA: 12MM		M						to sunlight, little stretch and good knot – holding ability Purpose : Used for rope and twine ,rope swings and barrier ropes Safeties: Sisal rope must be stored dry to avoid mildew , and chemical will cause it to deteriorate Minimum Braking Strength and Safe Load : 7.56 Kn dimension: 35 x 35 x 30 CM PACKING: 220 meter coil BRAND: GLOBAL INTERNATIONAL 1. min breaking force: 0.95 ton, 2. AS PER ISO SPEC: 1181 OF 2004 MIN B.S 9.86 KN 3. length per coil: 120 FATHOM, 4. STANDARD EN 1181 OF 2004, BS-2052/65, 6 TABLE-1, ISO 9554, 2005 & ISO 2307, 2005GENERAL SPECIFICATION - Characteristics: Excellent resistance to sunlight, little stretch and good knot – holding ability Purpose : Used for rope and twine ,rope swings and barrier ropes Safeties: Sisal rope must be stored dry to avoid mildew , and chemical will cause it to deteriorate Minimum Braking Strength and Safe Load : 7.56 Kn dimension: 35 x 35 x 30 CM PACKING: 220 meter coil BRAND: GLOBAL INTERNATIONAL 1. min breaking force: 0.95 ton, 2. AS PER ISO SPEC: 1181 OF 2004 MIN B.S 9.86 KN 3. length per coil: 120 FATHOM, 4. STANDARD EN 1181 OF 2004, BS-2052/65, 6 TABLE-1, ISO 9554, 2005 & ISO 2307, 2005	
20	DGT66794	NO DATA AVAILABE	0100501000118 / PLY WOOD MARINE ALL SHESHAM GD-II (CORE INNER & OUTER PLYS OF SHESHAM WOOD) 7 PLY		224 / SQ FEET						TECHNICAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			TYPE OF BOND WBP TREATED WITH PRESERVATIVE								13mmGENERAL SPECIFICATION - SPECIFICATION: BS-1088, part BS-4079 type: wbp preservation by on of the following wb-1 mark w1/3 WB-1 MARK W1/4 WB-2 MARK W2/3 WB-2 MARK W2/4 SIZE: LENGTH= 8 FT, WIDTH= 4 FT , THICKNESS =12MM (±1MM) thickness tolerance of subject item is 12mm to 13mm	
21	DGB64451	SKF N 312	0269799502091 / BEARING PARALLEL ROLLER SKF N 312 060X130X31MM		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
22	DGE67162	NIL	0350599237126 / ROPE NYLON CIRC 2", DIA 16MM, HAWSERLAID, 3 STRAND, Z LAY, 120 FM PER COIL,	STRENGTH 5.200 TONS UNIT OF AVAILABILITY	740 / FATHOM						TECHNICAL SPECIFICATION - STANDARD EN ISO 1140 OF 2004 (E), ISO 9554:2005 & ISO 2307:2005 WITH C/C AND OEM   CERTIFICATE Special Instructions Attached for SPI Only OEM: M/S COTESI UKGENERAL SPECIFICATION - STANDARD EN ISO 1140 OF 2004 (E), ISO 9554:2005 & ISO 2307:2005 WITH C/C AND OEM   CERTIFICATE Special Instructions Attached for SPI Only OEM: M/S COTESI UK	
23	DGE66927	NIL	0350599237129 / ROPE NYLON, HAWSERLAID, 3-STRANDS, CIRC 3", NOM DIA: 24MM, Z-LAY, TYPE-1, MINIMUM BREAKING LOAD: 12 TONS	STRENGTH 11,800 TONS UNIT OF AVAILABILIT	475 / FATHOM						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005, 4. LENGTH: PER COIL: 120 FATHOM, 5. OEM COC REQUIRED. 6. BS4982GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH	



S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. 6. BS4982	
24	DGB64453	SKF 30207A	0269599500550 / BEARING TAPERED ROLLER SKF 30207A 030X072X18.25		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
25	DNH67831	NO DATA AVAILABLE	1308500530116 / AIR CONDITIONER 1.5 TON WINDOW TYPE		2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
26	DNF66603	PAK / GFC/MILL AT/EQUIVALENT	0565700000048 / FAN PADESTAL-230VAC-24INCH 50CYCLES (PAK FAN)	END USE SELF	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
27	DNF66799	N250 PLUS EXIDE / OSAKA OR EQUIVALENT	0562795620006 / BATTERY LEAD ACID 12V 200AH	DG USED	2 / EACH/NUMBER	N250 PLUS EXIDE / OSAKA					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA GENERAL SPECIFICATION - BATTERY LEAD ACID 12V 200AH EXIDE / OSAKA	
28	DGE65811	4220505101929 / LIFE JACKET	FOR PERSONAL SAFETY,PNS QASIM,PRIZE ENT		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - (1) Buoyancy: 7.5kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester oxford cloth (4) Buoyancy material: EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003 GENERAL SPECIFICATION - (1) Buoyancy: 7.5 kg (2) Size: One size, adjustable (suitable 76 – 132 cm/2.49 – 4.33" bust) (3) Material: 240D Polyester	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											oxford cloth (4) Buoyancy material. EPE (5) Accessories: Whistle, Florescent Ribbons as per attached DRAWING NO TD-1688/2003	
29	DNF4870 4	J9627A	593073511469 1 / 48 Port 10/100 Layer 2 Managed Switch	AT-8300 SERIES	1 / EACH/N UMBER						TECHNICAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch GENERAL SPECIFICATION - Brand: HP Product: Family ProCurve Product: Series E2620 Product Name 2620-48-PoE+ Product Code / Part No: J9627A Category: Network Switch	
30	DNF6681 4	A-500 APC	614076507617 4 / BATTERY 12V 18AH MODEL A-500	DMG	4 / EACH/N UMBER	LONG WP18- 12SHR					TECHNICAL SPECIFICATION - A. POWER RATING 12V,18AH B. MAKE/OEM YUASA BATTERIES C. TYPE VALVE REGULATED LEAD ACID D. DIMENSIONS ( W X D X H) 181 X 76 167 (MM) E. TERMINAL TYPE FP TERMINAL F. WEIGHT 6.2 KG GENERAL SPECIFICATION - A. POWER RATING 12V,18AH B. MAKE/OEM YUASA BATTERIES C. TYPE VALVE REGULATED LEAD ACID D. DIMENSIONS ( W X D X H) 181 X 76 167 (MM) E. TERMINAL TYPE FP TERMINAL F. WEIGHT 6.2 KG	
31	DNF6687 3	EVP20- 12FR/0319 061023.	614012172188 9 / BATTERY SECONDARY LEAD ACID M/FREE 12V 20AH(6.6X6. 2X4.8INCH)	GYRO	1 / EACH/N UMBER	EVP20- 12FR					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
32	DNF6769 3	SMT3000I C/SURTD3 000XL/30 00VA APC	613071506382 3 / UPS 3KVA APCI/P220V O/P220V W/BATTERY BACKUP 25 MINUTES.	SELF	1 / EACH/N UMBER	MODEL ESP-808 (E) /SYSTEK PVT.					TECHNICAL SPECIFICATION - APC SMART-UPS. 2700 WATTS/3000 VA. INPUT 230V. OUTPUT 230 V. INTERFACE PORT DB-9 RS-232. USB. SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL GENERAL SPECIFICATION - APC SMART-UPS, 2700 WATTS/3000 VA. INPUT 230V, OUTPUT 230 V. INTERFCE PORT DB-9 RS-232, USB, SMARTSLOT LINE INTERACTIVE PURE SINE WAVE WITH POWER CHUTE SOFTWARE PART NO. SUA300041 INCLUDES CD WITH SOFTWARE, SMART UPS SIGNALLING RS-232 CABLE, USB CABLE, USER MANUAL	
33	DNF54933	02 CORE KAUDIO	5995765120716 / SPEAKER STEREO cable Electro voice	PA SYSTEM (TOA)	150 / METER						TECHNICAL SPECIFICATION - EV 2C X 14 AWG Pro Speaker Cable SSC-910, 2 X 1.5MM 2 Speaker cable OD 7.2MM (100 Mtr Roll) GENERAL SPECIFICATION - EV 2C X 14 AWG Pro Speaker Cable SSC-910, 2 X 1.5MM 2 Speaker cable OD 7.2MM (100 Mtr Roll)	
34	DNF47195	AS PER SPECIFICATION	6145755120718 / pro shielded 2 core micwire electro-voice	PA SYSTEM	300 / METER	3935X50					TECHNICAL SPECIFICATION - 1 Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll) GENERAL SPECIFICATION - 1 Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 6.55mm (100 Mtr Roll)	
35	DNF54939	TS50P SAMSON	7720735120714 / speaker stand samson (for ELX115	PA SYSTEM	4 / EACH/NUMBER	TS50P SAMSON					TECHNICAL SPECIFICATION - Professional Speaker stand, SAMSON TS50P for microphone, Ultra light weight collapsible tripod.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			speakers)								Weight metal base for stability. Non reflecting black finish. GENERAL SPECIFICATION - Professional Speaker stand, SAMSON TS50P for microphone. Ultra light weight collapsible tripod. Weight metal base for stability. Non reflecting black finish.	
36	DCW67455		8430500400923 / SHOES JOGGERS FOR CPO/SAILORS SIZE-8		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-8 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-8	ITEM REQUIRED AS PER specification
37	DCF66252		8345595714697 / FLAG NATIONAL FRANCE 4 BD FITTED SZ 4.50X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL FRANCE 4 BD FITTED SZ 4.50X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL FRANCE 4 BD FITTED SZ 4.50X3.00FT	
38	DCW67456		8430500400924 / SHOES JOGGERS FOR CPO/SAILORS SIZE-9		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-9 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-9	ITEM REQUIRED AS PER specification
39	DCF66713		8345595714810 / FLAG NATIONAL STATE OF KUWAIT 4 BD FITTED SZ 6.00X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL STATE OF KUWAIT 4 BD FITTED SZ 6.00X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL STATE OF KUWAIT 4 BD FITTED SZ 6.00X3.00FT	
40	DCW67457		8430500400925 / SHOES JOGGERS FOR CPO/SAILORS SIZE-10		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-10 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-10	ITEM REQUIRED AS PER specification
41	DCF66691		8345595714180 / FLAG ENSIGN PAKISTAN 6 BD FITTED SZ 9.00X4.50FT		63 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG ENSIGN PAKISTAN 6 BD FITTED SZ 9.00X4.50FT GENERAL SPECIFICATION - FLAG ENSIGN PAKISTAN 6 BD FITTED SZ 9.00X4.50FT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
42	DCW67191		8430500100532 / BOOT ANTI SKID BLACK SIZE 06		60 / PAIR						TECHNICAL SPECIFICATION:- BOOT ANTI SKID BLACK SIZE 06 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 06	Item per required as specification
43	DNF49162	YYS-OP60N	6650785240913 / OPTICAL POWER METER WITH VFL		1 / EACH/NUMBER	YYS-OP60N					TECHNICAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 $\mu$ +10dBm 60NC:-50 $\mu$ +26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 $\mu$ 30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 $\mu$ 60C, 90%RH p. Operating TEMPERATURE : -10 $\mu$ 50, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db tc/sc/st interface supported GENERAL SPECIFICATION - a. Power meter interface: 2.5 mm GPI b. Wavelength range : 700-1700 nm c. Power detector type: INGaAs d. Calibration WAVELENGTH : 850/1300/1310/1490/1550/1625nm e. Measurement range 60NT: -70 $\mu$ +10dBm 60NC:-50 $\mu$ +26dBm f. Accuracy: + 0.2 dB g. Red light source INTERFACE : 2.5mm GPI h. Output power LIGHT SOURCE of red : 1 $\mu$ 30mW j. Flashlight Torch: YES k. Network Cable DETECTION INTERFACE: RJ45 l. Data Interface : USB m. Battery: Built – in lithium battery (rechargeable) n. Storage Temperature: -20 $\mu$ 60C, 90%RH p. Operating TEMPERATURE : -10	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>250, 90%RH q. Weight: 100g r. Dimension: 104mm*60mm*26mm s. Dynamic Range: 80db + 0.2db fs/sc/st interface supported</p>	
44	DCW67454		843050040092 2 / SHOES JOGGERS FOR CPO/SAILORS SIZE-7		150 / PAIR						<p>TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-7 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-7</p>	ITEM REQUIRED AS PER specification
45	DCF66716		834550000079 0 / FLAG NATIONAL MALTA 4BD		5 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - FLAG NATIONAL MALTA 4BD GENERAL SPECIFICATION - FLAG NATIONAL MALTA 4BD</p>	
46	DNF62194	DS-6701HFH1-V	589527068439 1 / HD ENCODER (VIDEO COMPRATION DEVICE)		3 / EACH/NUMBER	N/A					<p>TECHNICAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE GENERAL SPECIFICATION - 1-CH 1080P H.264 DVS H.264/M-JPEG ENCODING FORMATS AVAILABLE INDEPENDENT CONFIGURATION OF ENCODING FORMATS FOR MAIN STREAM AND SUB STREAM 1-CH CH HDMI OR VGA VIDEO INPUT AND 1-CH VGA VIDEO LOOP OUT PROVIDED ENCODING AT HD RESOLUTION OF 1080P/720P/UXGA, ETC. UP TO 128G MICRO SD CARD AVAILABLE</p>	
47	DCW67193		843050010069 8 / BOOT ANTI SKID BLACK SIZE 8		60 / PAIR						<p>TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 8</p>	ITEM PER REQUIRED AS SPECIFICATION

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
48	DNF63560	LD004	6230785289113 / CSM Life raft - Lithium cell & Canopy light		10 / NO	LD004					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
49	DNF66954	WINXP (SP3 ONWARD S) / VIST/WIN7 / WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLES/jazz (DEVICE)		1 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLE GENERAL SPECIFICATION - 4G DATA WINGLE	
50	DCW67459		8430500400967 / SHOES JOGGERS FOR CPO/SAILORS SIZE-13		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-13 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-13	ITEM REQUIRED AS PER specification
51	DCD66176		8455501300437 / PAK MARINE INSIGNIA CPOs / SAILORS		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - PAK MARINE INSIGNIA CPOs / SAILORS GENERAL SPECIFICATION - PAK MARINE INSIGNIA CPOs / SAILORS	
52	DCF66712		8345595022193 / FLAG NATIONAL KENYA 4 BD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL KENYA 4 BD GENERAL SPECIFICATION - FLAG NATIONAL KENYA 4 BD	
53	DCD66181		8455703901779 / BADGE ARM MEDICAL X-RAY LMT RED EMBROIDRY		300 / EACH/NUMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
54	DCF66258		8345500000762 / FLAG NaTional JORDAN 4-BD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NaTional JORDAN 4-BD GENERAL SPECIFICATION - FLAG NaTional JORDAN 4-BD	
55	DCF66253		8345596714708 / FLAG NATIONAL GERMANY 4 BD FTD SZ 4.50X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL GERMANY 4 BD FTD SZ 4.50X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL GERMANY 4 BD FTD SZ 4.50X3.00FT	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
56	DCW67201		843050010096 1 / BOOT ANTI SKID BLACK SIZE-14		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-14 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-14	item per requird as specification
57	DCW67192		843050010069 7 / BOOT ANTI SKID BLACK SIZE 7		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 7 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 7	ITEM PER REQUIRED AS SPECIFICATION
58	DCC66478		844550000032 2 / DUPATTA WHITE MALMAL LG. 2X1 MTR.		1000 / EACH/NUMBER						TECHNICAL SPECIFICATION - DUPATTA WHITE MALMAL LG.2X1 MTR. GENERAL SPECIFICATION - DUPATTA WHITE MALMAL LG.2X1 MTR.	
59	DNF48088	SUN-SC-10M-SC-SM SX-3P	704578524964 4 / Patch cords SC-SC (10 Meter) Simplex SC/UPC - simplex SC/UPC connector; Length: 10Meter (Tolerance:0-0.1M); SM, G652D; Simplex cable; 3.0mm PVC jacket		8 / EACH/NUMBER	SUN-SC-10M-SC-SM SX-3P					TECHNICAL SPECIFICATION - Complete Details regarding OFC Patchcord are available in the attached Brochure named "Fiber Optic Patchcord and pigtails" GENERAL SPECIFICATION - Complete Details regarding OFC Patchcord are available in the attached Brochure named "Fiber Optic Patchcord and pigtails"	
60	DCF66722		834559571495 5 / FLAG NATIONAL SAUDI ARABIA 4 BD FITTED SZ 4.00X3.00FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL SAUDI ARABIA 4 BD FITTED SZ 4.00X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL SAUDI ARABIA 4 BD FITTED SZ 4.00X3.00FT	
61	DCF66714		834550000079 2 / FLAG NATIONAL KOREA 4BD		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL KOREA 4BD GENERAL SPECIFICATION - FLAG NATIONAL KOREA 4BD	
62	SNF48719	04070916	591578527938 7 / hdmi usb slave cable		8 / EACH/NUMBER	D14581-01-03					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	



S No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			(otg) cable									
63	DCF66257		834559571479 0 / FLAG NATIONAL JAPAN 4 BD FITTED SZ 4.50X3.00FT		5 / EACH/ UMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL JAPAN 4 BD FITTED SZ 4.50X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL JAPAN 4 BD FITTED SZ 4.50X3. 00FT	
64	DCW67200		843050010096 0 / BOOT ANTI SKID BLACK SIZE-13		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-13 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE-13	ITEM PER REQUIRED AS SPECIFICA TION
65	DCW67460		843050040069 8 / SHOES JOGGERS FOR CPO/SAILORs SIZE-14		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs SIZE-14 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORs SIZE-14	8430500400 698
66	DCF66715		834559571483 0 / FLAG NATIONAL LIBYA 4 BD FITTED SZ 4.50X3.00FT		5 / EACH/ UMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL LIBYA 4 BD FITTED SZ 4.50X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL LIBYA 4 BD FITTED SZ 4.50X3. 00FT	
67	DNF63007	410048	590573526869 2 / SET OF NVD COLLIMATOR ADAPTERS AND APPARTURE		1 / EACH/ UMBER	MS380PN 2A					TECHNICAL SPECIFICATION - SET OF NVD COLLIMATOR ADAPTERSGENERAL SPECIFICATION - SET OF NVD COLLIMATOR ADAPTERS	
68	DCF66259		834559571493 0 / FLAG NATIONAL QATAR 4 BD FITTED SZ 7.50X3.00FT		5 / EACH/ UMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL QATAR 4 BD FITTED SZ 7.50X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL QATAR 4 BD FITTED SZ 7.50X3. 00FT	
69	DCF66254		834559571476 5 / FLAG NATIONAL IRAN 4 BD FITTED SZ 9.00X3.00FT		5 / EACH/ UMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL IRAN 4 BD FITTED SZ 9.00X3.00FT GENERAL SPECIFICATION - FLAG NATIONAL IRAN 4 BD FITTED SZ 9.00X3.00FT	
70	DCF6626		834559571418		33 /						TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	0		1 / FLAG ENSIGN PAKISTAN 8 BD FITTED SZ12.00X6.00FT		EACH/NUMBER						L=145" W =72" colour (green 107" white 38") moon size 152" w10: star size 13" aS PER STOCK SAMPLE GENERAL SPECIFICATION - L=145" W =72" colour (green 107" white 38") moon size 152" w10: star size 13" aS PER STOCK SAMPLE	
71	DCW67199		843050010053 1 / BOOT ANTISKID BLACK SIZE 12		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12 GENERAL SPECIFICATION - BOOT ANTISKID BLACK SIZE 12	ITEM PER REQUIRED AS SPECIFICATION
72	DNF63006	410005	599973526869 5 / NVD STAND		1 / EACH/NUMBER	MS380PN2A					TECHNICAL SPECIFICATION - NVD STAND GENERAL SPECIFICATION - NVD STAND	
73	DCF66720		834550000170 1 / FLAG NATIONAL MAURITANIA 4 BD FITTED SZ 4.00X2.75FT		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL MAURITANIA 4 BD FITTED SZ 4.00X2.75FT GENERAL SPECIFICATION - FLAG NATIONAL MAURITANIA 4 BD FITTED SZ 4.00X2.75FT	
74	DCF66717		834559571417 9 / FLAG ENSIGN PAKISTAN 4 BD FITTED SZ 6.00X3.00FT		62 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG ENSIGN PAKISTAN 4 BD FITTED SZ 6.00X3.00FT GENERAL SPECIFICATION - FLAG ENSIGN PAKISTAN 4 BD FITTED SZ 6.00X3.00FT	
75	DCF66711		834550000048 6 / FLAG 4BD FOR KAZAKHISTAN		5 / EACH/NUMBER						TECHNICAL SPECIFICATION - FLAG 4BD FOR KAZAKHISTAN GENERAL SPECIFICATION - FLAG 4BD FOR KAZAKHISTAN	
76	DCW67194		843050010069 9 / BOOT ANTI SKID BLACK SIZE 9		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 9	ITEM PER REQUIRED AS SPECIFICATION
77	DCW67198		843050010053 3 / BOOT ANTI SKID BLACK SIZE 11		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 11	ITEM PER REQUIRED AS SPECIFICATION
78	DCW67455		843050040092 7 / SHOES JOGGERS FOR		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-12 GENERAL SPECIFICATION - SHOES	ITEM REQUIRED AS PER specification

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CPO/SAILORS SIZE-12								JOGGERS FOR CPO/SAILORS SIZE-12	
79	DCD66176		845570390177 7 / BADGE ARM MEDICAL X-RAY MT-II RED EMBROIDRY		300 / EACH/N UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
80	DCW67196		843050010070 0 / BOOT ANTI SKID BLACK SIZE 10		60 / PAIR						TECHNICAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 10 GENERAL SPECIFICATION - BOOT ANTI SKID BLACK SIZE 10	ITEM PER REQUIRED AS SPECIFICA TION
81	DCC66476		841050000024 5 / DRESS WHITE AYA LARGE		200 / PAIR						TECHNICAL SPECIFICATION - DRESS WHITE AYA LARGE GENERAL SPECIFICATION - DRESS WHITE AYA LARGE	
82	DCW67453		843050040092 1 / SHOES JOGGERS FOR CPO/SAILORS SIZE-6		150 / PAIR						TECHNICAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-6 GENERAL SPECIFICATION - SHOES JOGGERS FOR CPO/SAILORS SIZE-6	ITEM REQUIRED AS PER specification
83	DCF66721		834559571460 9 / FLAG NATIONAL SRILANKA (CEYLON) 4 BD FTD SZ 6.00X3.00FT		5 / EACH/N UMBER						TECHNICAL SPECIFICATION - FLAG NATIONAL SRILANKA (CEYLON) 4 BD FTD SZ 6.00X3. 00FT GENERAL SPECIFICATION - FLAG NATIONAL SRILANKA (CEYLON) 4 BD FTD SZ 6.00X3. 00FT	
84	DNF58978	ADZBQ7421	534074529221 6 / key SOFTWARE USB of wecdis		1 / EACH/N UMBER	PRO 325- 61 (ADZBQ 7421)					TECHNICAL SPECIFICATION - The subject USB should be based on HASP Language Technology. Moreover, the Key Software USB is to be compatible with already held WECDIS system software (i.e. GECDIS 0062, Version 5.1.3) GENERAL SPECIFICATION - The subject USB should be based on HASP Language Technology. Moreover, the Key Software USB is to be compatible with already held WECDIS system software (i.e. GECDIS 0062, Version 5.1.3)	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF.ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
85	DPC67949	QG2684/OGA046	8010171296548 / INTERTHANE 870 LIGHT GREY		100 / LITER	INTERTHANE870 LIGHT GRAY					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
86	DNF53391	2810019	6160735244928 / battery 12v 170 ah		2 / EACH/ NUMBER	CLASSIC V					TECHNICAL SPECIFICATION - DRY BATTERY Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KGGENERAL SPECIFICATION - DRY BATTERY Volt: 12 Amp: 170 AH DIMENSION: Length 21.5" Width 4.5" Height 11" APPROX WEIGHT: 30-40 KG	
87	DRG57531	725231	3670ZO5196637 / PRINTED CIRCUIT BOARD		1 / EACH/ NUMBER	0					TECHNICAL SPECIFICATION - SUNTEST SYSTEM BV CHAMBER OF COMMERCE HRB HILVERSUM NETHERLAND GENERAL SPECIFICATION - SUNTEST SYSTEM BV CHAMBER OF COMMERCE HRB HILVERSUM NETHERLAND	
88	DNH59073	SV-82/ 320L LARGE LAUNDRY CART	3510735284638 / WASCATOR WOODEN LAUNDRY TROLLEY (4 SECTION)		1 / EACH/ NUMBER	SV-82/ 320L LARGE LAUNDRY CART					TECHNICAL SPECIFICATION - Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape: Square Number of Compartment: 04 Included Component: Wheel, Handle Mounting Type: Floor Mount GENERAL SPECIFICATION - Product Dimension: 36 x 12 x 35 inches Item Weight: 8.80 pounds (3.96 KG) Capacity: 320 Liters Material: Metal Style: Casual Shape: Square Number of Compartment: 04 Included Component: Wheel, Handle Mounting Type: Floor Mount	
89	DNH65740	NO DATA AVAILABLE	1308500530116 / AIR CONDITIONER 1.5 TON WINDOW TYPE		1 / EACH/ NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
90	DNH61499	DV-200N	4310795113455 / VACUUM PUMP	VACUUM PUMP	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DNF63773	100AH	6140705054203 / 12 VOLTS LEAD ACID 97AH BATTERY	TX-R-PK/PRC 786	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
92	DGE68164		0451594510094 / MATTRESS FOAM RUBBER WITH COVER 82" X38"X4" (WARRANTY 10 YEARS)		35 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM. GENERAL SPECIFICATION - 1. ACCEPTABLE BRAND OF; a. DIAMOND SUPREME A-1 b. MASTER MOLTY FOAM.	
93	DRG60312	N150/N185 OR N-200 170AH	6140Z06541599 / BATTERY LEAD ACID		2 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - V=12 VOLT,I=170 AH,L=50.2CM. W=22.2CM,H=25.2CM, EXIDE N150/N185 GENERAL SPECIFICATION - V=12 VOLT,I=170 AH,L=50.2CM.W=22.2CM,H=25.2CM, EXIDE N150/N185	
94	SRP52808	S737 (PACKING 2.5 LI)	6810992245628 / ALCOHOL ISOPROPYLE (ISOPROPANO L) AR GRADE		100 / LITER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - BRITSH APPROVED BS.1595, US EQUIVALENT TT-I-735A GRADE B, FRENCH EQUIVALENT TI AIR3660/A, JOINT SERVICE DESIGNATION AL-11 NATO CODE S-737 GENERAL SPECIFICATION - BRITSH APPROVED BS.1595, US EQUIVALENT TT-I-735A GRADE B, FRENCH EQUIVALENT TI AIR3660/A, JOINT SERVICE DESIGNATION AL-11 NATO CODE S-737	
95	SNZ66982	3026423	5330014964336 / GASKET, AFTERCOOLE R COVER		10 / EACH/NUMBER	K-38-M					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
98	DNF68047	MCTX-UVSS-CAM/MV-PD-03-	6720705249123 / UVSS Camera		2 / EACH/NUMBER	Mechatro nix/HIKVI SION					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
		0001-01/02										
97	DRG607 24	NS100/ N130P	6140ZO652918 3 / BATTERY LEAD		6 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE:367MMX173X228(LXWXH) MADE IN PAKISTAN.	
98	DRG483 34	NS100/ N130P	6140ZO652918 3 / BATTERY LEAD		1 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE; 367MMX173X228(LXWXH)MADE IN PAKISTAN. GENERAL SPECIFICATION - BATTERY LEAD ACID 12 V 110 AH EXIDE NS-100 SIZE:367MMX173X228(LXWXH) MADE IN PAKISTAN.	
99	DRG494 01	ZO656089 1	2610ZO656089 1 / WHEEL ASSY COMPLETE WITH HUB, RIM,TYRE + TUBE		10 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Complete wheel (including tube, hub and rim) of tube dimension 2.50 x 18 (2.50 width in millimetre of tyre cross section and 18 inches diameter of the wheel that tyre is designed to fit). DATE OF MANUFACTURING: DOM TO BE EMBOSSED ON TYRE GENERAL SPECIFICATION - Complete wheel (including tube, hub and rim) of tube dimension 2.50 x 18 (2.50 width in millimetre of tyre cross section and 18 inches diameter of the wheel that tyre is designed to fit). DATE OF MANUFACTURING: DOM TO BE EMBOSSED ON TYRE	
100	DRG608 91	(1) N80 (N88) (N70A/N80 A) / (2) N- 80 new no n-85 12 v65ah 11 plates	6140ZO651014 2 / BATTERY LEAD ACID		18 / EACH/N UMBER	N80					TECHNICAL SPECIFICATION - TYPE: LEAD ACID BATTERY, MODEL: N80, VOLTS - 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-258 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE. EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET</p> <p><u>GENERAL SPECIFICATION - TYPE:</u> LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET</p> <p><u>TECHNICAL SPECIFICATION - TYPE:</u> LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET</p> <p><u>GENERAL SPECIFICATION - TYPE:</u> LEAD ACID BATTERY, MODEL: N80, VOLTS : 12, PLATES: 11 PLATES PER CELL, AMPERE : 65AH, SIZE IN MM: L-259 X W-172 XH-224 (+/- 5MM), POLARITY RIGHT THICK POLE, EQUIVALENT AGS BATTERY MODEL GL85 13 PLATES 70AH, OEM/COUNTRY OF ORIGIN: EXIDE PAKISTAN LTD, OEM COC/AUTHORIZED DEALER CERTIFICATE: N/A, ITEM AVAILABLE IN LOCAL MARKET</p> <p><u>TECHNICAL SPECIFICATION -</u> NSX-FHYJ-HZ3 1.6 MPa DN40 OD =</p>	
101	DRG60741	(1) N80 (N88) (N70A/N80 A) / (2) N-80 new no n-85 12 v65ah 11 plates	6140Z0651014 2 / BATTERY LEAD ACID		2 / EACH/NUMBER	N80						
102	DN067942	CSA-40-SEW/FFF1	534078527963 8 / ISOMETRIC		13 / EACH/NUMBER	CLH80-50-6.5(Z)						

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		2	COMPOSITE SACRIFICAL ANODE (40 OD = 74 Ømm, ID = 41.5 Ømm)		UMBER						74 (Ømm), ID = 41.5 (Ømm), Length of sleeve = 40 (mm) GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.6 MPa DN40 OD = 74 (Ømm), ID = 41.5 (Ømm), Length of sleeve = 40 (mm)	
103	DNQ63199	MM308R	4220795300637 / TORCH BATTERY		15 / EACH/NUMBER	n/a					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
104	DRG60739	SA10929 (287548)	2940014841344 / AIR CLEANER ELEMENT HOBERT GPU		4 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - AS PER PUBLICATION GENERAL SPECIFICATION - AS PER PUBLICATION	
105	DN057945	CSA-80-SEW/FFF7	5340785279635 / ISOMETRIC COMPOSITE SACRIFICAL ANODE (80 OD = 118 Ømm, ID = 84 Ømm)		30 / EACH/NUMBER	215ZF907-12-0					TECHNICAL SPECIFICATION - NSX-FHJYJ-HZ3 1.0 MPa DN80 OD = 118 (Ømm), ID = 84 (Ømm), Length of sleeve = 40 (mm) GENERAL SPECIFICATION - NSX-FHJYJ-HZ3 1.0 MPa DN80 OD = 118 (Ømm), ID = 84 (Ømm), Length of sleeve = 40 (mm)	
106	DRG49404	1730ZO6549721 / TRESTLE AFT			5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE 30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel Binch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color) GENERAL SPECIFICATION - 1. HEIGHT: 9.5FT 2. WIDTH: 4FT 3. LENGTH: 8FT 4. Aluminium Section: 40x40 5. Aluminium Checker Plate: 4mm Thick (Stairs) 6. Aluminium Checker Plate 4mm Thick Platform (900x900) 7. Section Fitting (Customize) 8. MS PIPE	



S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											30X30X2MM FOR STAIRS (900MM LENGTH) 8. MS Railing Pipe 50mm round 2mm thick 9. Side Rigger (Screw and Floding Type) 10. Wheel 8inch (2revolving 2 fix) alongwith brake Hardware 11. Paint Powder Coating (Only MS Material Yellow color)	
107	DRG59991	T400268 (2873K621)	6105715159630 / STARTER MOTOR		1 / EACH/NUMBER	0					TECHNICAL SPECIFICATION - AS PER PUBLICATION GENERAL SPECIFICATION - AS PER PUBLICATION	
108	DN067943	CSA-50-SEW/FFF11	5340785279637 / ISOMETRIC COMPOSITE SACRI FICIAL ANODE (50 OD = 84 Ømm, ID = 54 Ømm)		4 / EACH/NUMBER	CLH80-50-6.5(Z)					TECHNICAL SPECIFICATION - NSX-FHYJ-HZ3 1.6 MPa DN50 OD = 84 (Ømm), ID = 54 (Ømm), Length of sleeve = 40 (mm)GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.6 MPa DN50 OD = 84 (Ømm), ID = 54 (Ømm), Length of sleeve = 40 (mm)	
109	DRG60043	401R5532 V4-1B	5998745152046 / SUPERVISING BOARD (400HZ)		3 / EACH/NUMBER	GA100V14BC1200					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
110	DRG49909	23332	5120Z06528505 / GUN SPRAY		10 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Paint spray gun suction (bottom fed) Tank capacity 1 Litre Air flow 200-250 Lit/min Operating pressure 6-8 bar Air connection 1/4 inch dia GENERAL SPECIFICATION - Paint spray gun suction (bottom fed) Tank capacity 1 Litre Air flow 200-250 Lit/min Operating pressure 6-8 bar Air connection 1/4 inch dia	
111	DRG57347	23332	5120Z06528505 / GUN SPRAY		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Paint spray gun suction (bottom fed) Tank capacity 1 Litre Air flow 200-250 Lit/min Operating pressure 6-8 bar Air connection 1/4 inch dia GENERAL SPECIFICATION - Paint spray gun suction (bottom fed) Tank capacity 1 Litre Air flow 200-250 Lit/min Operating pressure 6-8 bar Air connection 1/4 inch dia	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabil ty	Tender Remarks	TECH / GEN SPECS	Dimension
112	DN067941	CSA-32-SEW/FFF13	5340785279639 / ISOMETRIC COMPOSITE SACRI FICIAL ANODE (32 OD = 64 Ømm, ID = 34 Ømm)		11 / EACH/NUMBER	CM-FST-1-20					TECHNICAL SPECIFICATION - NSX-FHYJ-HZ3 1.6 MPa DN32 OD = 64 (Ømm), ID = 34 (Ømm), Length of sleeve = 40 (mm)GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.6 MPa DN32 OD = 64 (Ømm), ID = 34 (Ømm), Length of sleeve = 40 (mm)	
113	DRG49400	ZO6510148	2630ZO6510148 / WHEEL TROLLEY SIZE 8 INCH		10 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Metallic/ rubber wheel with dia of 8 inches √ Wheel Diameter 8 inches (20.32 cm) √ Load Capacity approx. 300 lbs √ Bearing Type Ball Bearing √ Mounting Type Plate Mount √ Swivel Type 360-degree movement Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle. GENERAL SPECIFICATION - Metallic/ rubber wheel with dia of 8 inches √ Wheel Diameter 8 inches (20.32 cm) √ Load Capacity approx. 300 lbs √ Bearing Type Ball Bearing √ Mounting Type Plate Mount √ Swivel Type 360-degree movement Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle.	
114	DNF67720	E-DURID28LCD	5805785276744 / PULSE GENERATOR NEMTEK 02 ZONE ENERGIZER		6 / EACH/NUMBER	E-DURID28LCD					TECHNICAL SPECIFICATION - Enclosure size 400(L) x 270(W) x 125(D)mm Weight 5.7kg excluding battery (7AH) 8.0kg including battery (7AH) IP rating IPx4 Operating temperature -10°C to 50°C Operating humidity 80% non-condensing Electrical supply voltage 240V Typical power consumption 18VA (normal operating conditions) Standby Time 24hrs (fully charged battery) Energy output 3.7 Joule per zone (500 Ohms load) Open circuit voltage 9000VGENERAL SPECIFICATION - Enclosure size	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											400(L) x 270(W) x 125(D)mm Weight 5.7kg excluding battery (7AH) 8.0kg including battery (7AH) IP rating IPx4 Operating temperature -10°C to 50°C Operating humidity 80% non-condensing Electrical supply voltage 240V Typical power consumption 18VA (normal operating conditions) Standby Time 24hrs (fully charged battery) Energy output 3.7 Joule per zone (500 Ohms load) Open circuit voltage 9000V	
115	DRG47266	BARREL JP	4320Z06531217 / BARREL EMPTY FUEL JP1/JP4 EPOXY COATED REUSABLE		14 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - CAPACITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXY COATED, TO BE USED FOR AVN FUEL GENERAL SPECIFICATION - CAPACITY 210 LIT (40/45 IMPERIAL GALLON), SPECIAL PURPOSE EPOXY COATED, TO BE USED FOR AVN FUEL	
116	SRG22518	RILG-416-0	5970143040395 / RYLSO SLEEVE (SLEEVING ELECTRICAL)		150 / FOOT	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DRG60015	4036335 (4766127)	6105Z06574044 / ALTERNATOR (FIAT AGRICULTURE TRACTOR MODEL 640)		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
118	DN067944	CSA-65-SEW/FFF9	5340785279636 / ISOMETRIC COMPOSITE SACRIFICAL ANODE (65 OD = 104 Ømm, ID = 72 Ømm)		10 / EACH/NUMBER	CLH80-50-6.5(Z)					TECHNICAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN65 OD = 104 (Ømm), ID = 72 (Ømm), Length of sleeve = 40 (mm) GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN65 OD = 104 (Ømm), ID = 72 (Ømm), Length of sleeve = 40 (mm)	
119	DN067947	CSA-125-SEW/FFF3	5340785279633 / ISOMETRIC COMPOSITE		24 / EACH/NUMBER	CLS-350					TECHNICAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN 125 OD = 164 (Ømm), ID = 127 (Ømm),	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			SACRIFICAL ANODE (125 OD = 164 Ømm, ID = 127 Ømm)								Length of sleeve = 50 (mm) GENERAL SPECIFICATION - NSX-FHYJ-HZ3 1.0 MPa DN 125 OD = 164 (Ømm), ID = 127 (Ømm), Length of sleeve = 50 (mm)	
120	DNM67023	359-7563	5925715269086 / CIRCUIT BREAKER (100 -AMPERE , 4 POLE)		1 / EACH/NUMBER	DE110E2					TECHNICAL SPECIFICATION - CIRCUIT BREAKER (100 -AMPERE , 4 POLE)GENERAL SPECIFICATION - CIRCUIT BREAKER (100 -AMPERE , 4 POLE)	
121	DRG60651	1036735-P5	8115016037415 / ALTERNATOR (GENERATOR SET DIESEL ENGINE) CAGE50036		2 / EACH/NUMBER	N/A					TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
122	DRG60742	ZO6568002	4720ZO6568002 / NYLON HOSE WITH APPROPRIATE FITTING 1/4 INCH		2 / EACH/NUMBER	LENAAR DO					TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
123	DRG60738	SBA-185086141	6105ZO6567828 / MOTOR ASSY STARTING COMPLETE		1 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - ALLIED AGRICULTURAL TRACTOR MODEL 1910 GENERAL SPECIFICATION - ALLIED AGRICULTURAL TRACTOR MODEL 1910	
124	DRG49399	ZO6567572	1560ZO6567572 / WHEEL		20 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tire Diameter 535 mm Tire Ply Rating 4 ply Hub Type Locally Made Load Capacity Varies (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub GENERAL SPECIFICATION - Trolley wheel of tyre dia 535 mm (4 ply) with local made hub Tire Diameter 535 mm Tire Ply Rating 4 ply Hub Type Locally	

S No	LPR No	PART NO	NSN / Description	R/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Made Load Capacity Vanes (e.g. 500 kg) Bearing Type Ball Bearing Mounting Type Plate Mount Swivel Type 360-degree movement Wheel Type Pneumatic Trolley wheel of tyre dia 535 mm (4 ply) with local made hub	
125	DRG60892	6X120 (6X15)	6140Z06538698 / BATTERY LEAD ACID 12 VOLTS,105 AH		4 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH: 367MM W: 173MM HIGHT: 228MM LEAD ACID 12V,105AH, EXIDE 6X15 GENERAL SPECIFICATION - LENGTH: 367MM W: 173MM HIGHT: 228MM LEAD ACID 12V,105AH,EXIDE 6X15	
126	DRG59988	7208223 (4737755)	2920151013165 / STARTER MOTOR		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
127	DRG57646	ZW91100H001101	1730785150870 / MECHANICAL TOW BAR		1 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - LENGTH OF TOW BAR=2750 MM WIDTH OF NOSE WHEELS=457.2 MM DIAMETER OF NOSE WHEEL=330 MM GROUND CLEARANCE FROM STRUCTURE = 533.4 MM GROUND CLEARANCE FROM PITOT TUBE= 457.2MM. Technical specification is enclosed wherein, breaking strength of shear pin was mentioned as 9.5 -10.5 kN. Towing Bar must be capable to drag the aircraft weight of 4100 Kg with 1.5 safety margin. Tow bar is being linked with Helicopter at nose landing gear and it moves the aircraft through towing tractor.GENERAL SPECIFICATION - LENGTH OF TOW BAR=2750 MM WIDTH OF NOSE WHEELS=457.2 MM DIAMETER OF NOSE WHEEL=330 MM GROUND CLEARANCE FROM STRUCTURE = 533.4 MM GROUND CLEARANCE FROM PITOT TUBE= 457.2MM. Technical specification is enclosed wherein, breaking strength of shear pin was mentioned as 9.5	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											-10.5 kN. Towing Bar must be capable to drag the aircraft weight of 4100 Kg with 1.5 safety margin. Tow bar is being linked with Helicopter at nose landing gear and it moves the aircraft through towing tractor.	
128	SRP64310	FC-577 (SOFT 99)	6850Z06511199 / VINYL CLEANER FOAM SPRAY, 400ML		100 / BOTTLE	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY. VINYL.CARPETS PART NO FC-577 (WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT: 400ML/22 OZ/623 GMS GENERAL SPECIFICATION - ABRO.CLEAN ALL FOAM CLEANERS FOR UPHOLSTERY.VINYL.CARPETS PART NO FC-577 (WWW.ABRO.COM).OEM: ABRO INDUSTRIES INC.PO BOX 1174.IN 46624 USA MAKE NET WT:400ML/22 OZ/623 GMS	
129	DRG49402	WHEEL DIA 6"	2630Z06510147 / TROLLEY WHEEL 6"DIA		30 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Metal/ rubber wheel with 360 degree movement and dia of 6 inches 1 Wheel Diameter 6 inches (15.24 cm) 2 Load Capacity approx. 300 lbs 3 Bearing Type Ball Bearing 4 Mounting Type Plate Mount 5 Swivel Type 360-degree movement 6 Wheel Type Solid Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with metallic core) with 360 degree movement for trestle. GENERAL SPECIFICATION - Metal/ rubber wheel with 360 degree movement and dia of 6 inches 1 Wheel Diameter 6 inches (15.24 cm) 2 Load Capacity approx. 300 lbs 3 Bearing Type Ball Bearing 4 Mounting Type Plate Mount 5 Swivel Type 360-degree movement 6 Wheel Type Solid Rubber outer with metallic core (aluminium or steel) Wheel (outer rubber layer with	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											metallic core) with 360 degree movement for trestle.	
130	DRG61633	I-8000T CC-6000 OR I-633MMTB	291570515008 8 / COALESCER ELEMENT ASSY		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
131	DRQ54941	H7A	6710Z0651054 6 / EAR MUFF		16 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - BILSOM VIKING 2421/H7A(EN 3521-1:1992 0121 CE) MAKE: USA/EU/SWEDEN/3M STOCKIST:7, ADNAN CENTRE, OFF: NICOL ROAD, PH:2416012 GENERAL SPECIFICATION - BILSOM VIKING 2421/H7A(EN 3521-1:1992 0121 CE) MAKE: USA/EU/SWEDEN/3M STOCKIST:7, ADNAN CENTRE, OFF: NICOL ROAD, PH:2416012	
132	DN067946	CSA-100- SEW/FFF5	534078527963 4 / ISOMETRIC COMPOSITE SACRI FICAL ANODE (100 OD = 138 Ømm, ID = 103 Ømm)		29 / EACH/N UMBER	BC2×518 4-4.9L					TECHNICAL SPECIFICATION - NSX-1-1 FHYJ- HZ3 1.0 MPa DN 100 OD = 138 (Ømm), ID = 103 (Ømm), Length of sleeve = 50 (mm) GENERAL SPECIFICATION - NSX-1-1 FHYJ- HZ3 1.0 MPa DN 100 OD = 138 (Ømm), ID = 103 (Ømm), Length of sleeve = 50 (mm)	
133	DNF67790	0102- 034006- 226	599978515447 5 / OVER IOAD SS3-120 (0-120 AMP) Range 01 – 120 Amp (Adjustable)	L/PAC	10 / EACH/N UMBER		100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD,305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042- 6852313,6862490 FAX:92- 426553674	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAL CON PVT LTD,305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674. SPEC: COIL VOLTAGE 220V AC. MAKE: MAC OPR ( MAC ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR (	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY:ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042-6852313,6862490 FAX;92-426553674. SPEC.COIL VOLTAGE 220V AC. MAKE: MAC OPR ( MAC ELECTRIC) OF CHINA ORIGIN RANGE 01 – 120 AMP (ADJUSTABLE) MODEL: NOT APPLICABLE. EQUIVALENT: NOT KNOWN. new specification a. General purpose Over Load utilized in multi type machinery controls system. b. Range 01 – 120 Amp (Adjustable) c. Already in use against captioned NSN with satisfactory performance. d. Make: MAC OPR ( MAC Electric) of China origin e. Model: Not Applicable. f. Equivalent: Not Known.	
134	SNM669 94	3908615/L F3959 (LF033490 0)	294001280841 9 / CARTRIGE LUB OIL FILTER ELEMENT D/G LF3349FLEET GUARD	Cummins SSDG (Engine) 6BT5.9-GM83 USA	28 / EACH/N UMBER			500 JACKSON ST, COLUMBUSCONTACT NO 812-377-3920FAX NO 812- 377-1715STEVE.A. HEWITT@CUMMINS. COMFAX NO 812-377- 1715STEVE.A. HEWITT@CUMMINS. COM3	CUMMIN S ENGINE COMPAN Y, INC		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
135	DNFG779 1	K0-399 0102- 034022- 226	662678515446 6 / AIR TEMPERATUR E CONTROLLER RANGE 0-300 C volt100-240V AC	MOBILE LPAC (AC UNIT ALPINE	10 / EACH/N UMBER	OMRON E5C4-R	100-125 PSI	ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674.	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE;042- 6852313,6862490 FAX;92- 426553674GENERAL SPECIFICATION - SOURCE OF AVAILABILITY;ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE	



S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											PAKISTAN PHONE:042-6852313,6862490 FAX,92-426553674	
135	DNM57955	ZP385KCE-TWD-251	4310715208540 / COMPRESSOR (COPELAND SCROLL)	AIR COOLED CHILLER 85 TON ZP385KCE-TWD 251 USA	1 / EACH/NUMBER	ZP385KCE-TWD 251	SNVM797270	SCHNEIDER ELECTRIC COMPANY C ZECH REPUBLIC USA	USA		TECHNICAL SPECIFICATION - 161KW R410A R410A PS46BAR/MWP 667 PSIG GENERAL SPECIFICATION - 161KW R410A R410A PS46BAR/MWP 667 PSIG	
137	DNM68016	ZP385KCE-TWD-251	4310715208540 / COMPRESSOR (COPELAND SCROLL)	AIR COOLED CHILLER 85 TON ZP385KCE-TWD 251 USA	1 / EACH/NUMBER	ZP385KCE-TWD 251	SNVM797270	SCHNEIDER ELECTRIC COMPANY C ZECH REPUBLIC USA	USA		TECHNICAL SPECIFICATION - 161KW R410A R410A PS46BAR/MWP 667 PSIG GENERAL SPECIFICATION - 161KW R410A R410A PS46BAR/MWP 667 PSIG	
138	DNQ57215	17-2879003	6350735226057 / SMOKE & HEAT DETECTOR FOR ALARM SYSTEM	MAB	1 / EACH/NUMBER	TSD-1	NIL	SATEL sp. z o.o. ul. Schuberta 79 80-172 Gdansk POLSKA Tel : 58 320 94 00 info@satel.pl / www.satel.pl	SATEL POLAND		TECHNICAL SPECIFICATION - 9.5 V -30V DC Class A1& A1R GENERAL SPECIFICATION - 9.5V -30V DC Class A1& A1R	
139	DNF67483	Intellilite COMAP MRS 16	6110735229231 / CONTROLLER	DIESEL GENERATOR	2 / EACH/NUMBER	MRS 16	NIL	Manufacturer: ComAp, spol. s r.o. Czech Republic Phone: +420 266 790 611 Fax: +420 266 316 647 E-mail: info@comap.cz Internet: www.comap.cz	ComAp		TECHNICAL SPECIFICATION - SAFTY PANEL OF DIESEL GENERATOR FOR STATR , STOP THE GENERATOR , ALL PARAMATER AND WARNING GENERAL SPECIFICATION - SAFTY PANEL OF DIESEL GENERATOR FOR STATR , STOP THE GENERATOR , ALL PARAMATER AND WARNING	
140	DNA48897	31040	5330705164333 / KIT SEAL (INCLUDES 97,106,112,127,155,156,158,159)	SEA WATER PUMP	1 / EACH/NUMBER	CAT - 3531/3535		DEFENCE SCIENCE AND TECHNOLOGY ORGNISATION CHATTAR ISLAMABAD PH: 051-9060,5-9 FAX: 051-9280502 90602104	DESTO ISLAMABAD		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
141	DNF67918	SRV6KI	6130715194943 / 06 KVA ON LINE UPS	SMART-UPS ON-LINES	1 / EACH/NUMBER	Smart-UPS On-Line SRC 230 V		Schneider Electric Industries SAS USA www.schneider-electric.com 998-1269702 US + 971 4 7099333 USA	APC by Schneider Electric		TECHNICAL SPECIFICATION - Power Rating : 06KVA/3500 W Nominal Output Voltage : 220 Vac single-phase UPS Nominal Input Voltage : 220/230 Vac single-phase UPS Input Frequency Range : 40 ? 70 Hz Output Frequency : 50/60 Hz	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES.GENERAL SPECIFICATION - Power Rating : 06KVA/3500 W Nominal Output Voltage : 220 Vac singe-phase UPS Nominal Input Voltage : 220/230 Vac singe-phase UPS Input Frequency Range : 40 ? 70 Hz Output Frequency : 50/60 Hz Topology : Double-conversion Online Backup time : MINIMUM OF 05 MINUTES AND MAXIMUM FOR 15 MINUTES.</p>	
142	DNO67839	GREEN TRIDENT	623001563775 6 / LIGHT, HEAD, GENERAL PURPOSE	DC & FF	6 / EACH/NUMBER			STREAMLIGHT INC 30 EAGLEVILLE UNITED STATES CAGE CODE 56654	STREAM LIGHT INC 30		<p>TECHNICAL SPECIFICATION - DEPTH 2.53 IN; OVERALL 2.55 IN; POWERED BY 3 AAA BATTERIESGENERAL SPECIFICATION - DEPTH 2.53 IN; OVERALL 2.55 IN; POWERED BY 3 AAA BATTERIES</p>	
143	DNF67936	SURT 6000 XLI/ELENAS 6KVA	613070514291 8 / UPS 6KVA	OFFICE MACHINERY EQUIP	1 / EACH/NUMBER	EP-H 01		PK	M/S MANSOOR & SONS (PVT) LTD, MEZZANINE FLOOR, PLOT NO. 11-C, STREET NO.28, TAUHEED COMMERCIAL AREA, PHASE V, DHA KARACHI 75500 TEL: 92-21-		<p>TECHNICAL SPECIFICATION - BAKCUP TIME ONE AND HALF TO TWO HOURS. GENERAL SPECIFICATION - BAKCUP TIME ONE AND HALF TO TWO HOURS.</p>	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
									35862134 3583525 5 FAX:92-21-35861671 3583518 5 E.MAIL: SHANZ			
144	DNV18896	2080/G-1/2080/g	599875523182 9 / MOTHER BOARD PCB SMART LOOP 2L	FIRE ALARM 2080/G-1 ITALY	1 / EACH/NUMBER	2080/G-1	NA	INZM ELECTRONICS 9001:2008 REGD. COMPANY VIA FOSSO ANTICO LOC. CENTOBULCHI 83076 MONTEPRANDONE(AP) ITALY TEL:+39 0735 705007 FAX:+39 0735 704912	INIM ELECTRONICS		TECHNICAL SPECIFICATION - INPUT:220V/ 110VAC & 24VDC GENERAL SPECIFICATION - INPUT:220V/ 110VAC & 24VDC	
145	DNS47933	113 010	2815580002120 / GUDGEON PIN	WARTSILA MAIN ENGINE 9L20C3 FINLAND	9 / EACH/NUMBER	9L20C3	MADPAA E084245, PAAE084242 RASDPA AE084243 PAAE084244	Wartsila Finland Oy Vaasa Factory Tarhaajantie 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tlx 74251 waf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - TPI GENERAL SPECIFICATION - TPI	
146	DNS62478	3837393-2	4270735159555 / HAND PUMP	FUEL CLEANER/WATER SEPARATOR, TWIN.	1 / EACH/NUMBER	D5-D16		WARTSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 FINLAND	WARSILA FINLAND		TECHNICAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER P.O.BOX 252 FIN-65101 FINLAND GENERAL SPECIFICATION - WARTSILA FINLAND OY, SHIP POWER P.O. BOX 252 FIN-65101 FINLAND	
147	DNS56368	ITL22L6B	4810775187938 / INTERNAL PARTS CHECK VALVE	WARTSILA STERN THRUSTER PROP CS250-S/WO-K HOLLAND	1 / EACH/NUMBER	WART-LCT-CS250-S/WO-K	MADD MP/00675 .M2T12 RASD MP/00675 .M2T11	Wartsila Propulsion Netherlands B.V. Marine Propulsion Systems P.O. Box 6 5150 BB Drunen The Netherlands Phone : +31 416 388424 propulsion.service@wartsila.com http://www.wartsila.com	Wartsila Propulsion Netherlands B.V.		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
148	DNF67725	02G-P4-2651-KR	9999735212304 / GRAPHIC CARD( EVGA GEFORCE GTX 650 2GB)	CIWS T5600 CANADA	1 / EACH/NUMBER	T5600	NA	USN/Lockheed Martin CANADA WWW.EVGA.COM/teamevga	EVGA/NVIDIA		TECHNICAL SPECIFICATION - GRAPHIC CARD( EVGA GEFORCE GTX 650 2GB)GENERAL SPECIFICATION - GRAPHIC CARD( EVGA GEFORCE GTX 650 2GB)	
149	SNS55047	329-6655	2815FT1019208 / insert-Valve Seat	Caterpillar Emergency DG Marine Genset C 4.4 USA	8 / EACH/NUMBER	Marine Genset C 4.4	N/A	14009 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPILLAR INC. DBA CATERPILLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	
150	DNS47929	120021	2805735151611 / Valve seat Insert Inlet	WARTSILA MAIN ENGINE 9L20C3 FINLAND	72 / EACH/NUMBER	9L20C3		Wartsila Finland Oy Vaasa Factory Tarhaajantie 2, FIN-65101 Vaasa, Finland Tel. +358 10 708 0000, Tlx 74251 wa sf Fax (Service) ,358 6 356 7355 Fax (Spare parts) +358 10 709 1380	Wartsila Finland Oy		TECHNICAL SPECIFICATION - NO DATA AVAILABLEGENERAL SPECIFICATION - NO DATA AVAILABLE	
151	DNC56246	8806621	3410MB0020689 / BEARING	PETROL MAIN ENGINE	2 / EACH/NUMBER	350		2B614987 2B612137 2B619494	MERCURY MARINE SINGAPORE PTE LTD 11 CHANGI SOUTH STREET 3, #01-02 SINGAPORE 486122	MERCURY MARINE	TECHNICAL SPECIFICATION - BEARINGGENERAL SPECIFICATION - BEARING	
152	DNZ67038	4000714	5330785216992 / AFTERCOOLER COVER GASKET	Cummins QSK 38 DM Main Engine	4 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co, Ltd	Cummins		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
153	DNZ67487	4000714	5330785216992 / AFTERCOOLER COVER GASKET	Cummins QSK 38 DM Main Engine	4 / EACH/NUMBER	QSK38-DM	33170174	Cummins, Engine Co, Ltd	Cummins		TECHNICAL SPECIFICATION - N/AGENERAL SPECIFICATION - N/A	
154	SNM66995	10000-05598	5120795198973 / OIL FILTER	PERKINS P-200-3 UK	1 / EACH/NUMBER	P-200-3	PR83167 R007362	F.G WILSON (ENGINEERING) LTD	PERKINS UK		TECHNICAL SPECIFICATION - ITEM USED IN LUBRICATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO. OF PR.	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
					UMBER		A	CHURCH ROAD WHITE HOUSE NEWTOWNABBEY, BELFAST BT36 7LN NORTHERN IRELAND, UK			SYSTEM GENERAL SPECIFICATION - ITEM USED IN LUBRICATION SYSTEM.	
155	DGE314 88	202-GNFG	047659000775 8 / GLOVES SEAMLESS DIPPED RUBBER I.R. SIZE 9.		150 / PAIR	202- GNFG					TECHNICAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who involve / Deal with high voltage electricity GENERAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who involve / Deal with high voltage electricity	
156	SGB568 78		027670910659 2 / VICE ENGINEERS WIDTH OF	JAW 3-1/4" PARALLEL, QUICK RELEASE	30 / EACH/N UMBER						TECHNICAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			JAW 4.5", NOM OPENING 5-1/2".								GENERAL SPECIFICATION - Jaw Opening: 5.5 Inch Depth of Jaw: 3 Inch Weight with stationary base: 91.1 kg Make/ Model: England	
157	SNQ37530	BS876 (5120-99-255-7816)	0274709104652 / HAMMER HAND ENGINEER 2.000LBS LG 16.000IN IL31ENGS PEIN		30 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
158	SGB52777		0274599104700 / HAMMER HAND SLEDGE 10.00 LBS LG 36.00 IN STRAIGHT PEIN		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: Mild Steel Length of wooden handle: 3 feet Diameter of wooden handle: 1.5 Inch GENERAL SPECIFICATION - Material: Mild Steel Length of wooden handle: 3 feet Diameter of wooden handle: 1.5 Inch	
159	SGB51720		0214590130818 / BOLT MACHINE STEEL BSF HEX HD SZ 0.500X4.500X1.000 IN		10 / TEN						TECHNICAL SPECIFICATION - Material: ferrous Grade: EN4140, DGS 8060 class 1(a) (as per BR-320d) GENERAL SPECIFICATION - Material: ferrous Grade: EN4140, DGS 8060 class 1(a) (as per BR-320d)	
160	SGB51518		0263594149636 / THIMBLE-ROPE-OPEN-TYPE-STEEL-2.500" (LOCAL)		24 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
161	DNQ63433		0243591295634 / FIRE EXTINGUISHER CO2 (CARBON DIOXIDE) 2 1/2LB C/W DISCHARGE HORN ASSM	FOR FIRE FIGHTING	79 / EACH/NUMBER						TECHNICAL SPECIFICATION - BS EN -3 GENERAL SPECIFICATION - BS EN -3	
162	DNF66191	BS EN 60317-8	0561705253677 / WIRE, WINDING COPPER	WINDING FOR MOTOR	30 / KILOGRAMME						TECHNICAL SPECIFICATION - ideally upto 99.95 % purity of copper wire is required to ensure optimal electrical conductivity with heat	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DEND	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			ELECT COND DIA=1.120MM, O/A DIA=1.217 (CLASS-180)								resistance above 180°C and item is general in nature and easily available at local market. Purity of copper wire is required to be upto: 99.95% COND DIA 1.120 mm & O/A DIA 1.217 class 180 (SWG 18.5). BS EN ,60317-22 OF 2004 <u>GENERAL SPECIFICATION</u> - ideally upto 99.95 % purity of copper wire is required to ensure optimal electrical conductivity with heat resistance above 180°C and item is general in nature and easily available at local market. Purity of copper wire is required to be upto: 99.95% COND DIA 1.120 mm & O/A DIA 1.217 class 180 (SWG 18.5). BS EN ,60317-22 OF 2004	
163	DNF65313	BS EN 60317-8	056179525357 7 / WIRE, WINDING COPPER ELECT COND DIA=1.120MM, O/A DIA=1.217 (CLASS-180)	WINDING FOR MOTOR	60 / KILOGRAMME						<u>TECHNICAL SPECIFICATION</u> - ideally upto 99.95 % purity of copper wire is required to ensure optimal electrical conductivity with heat resistance above 180°C and item is general in nature and easily available at local market. Purity of copper wire is required to be upto: 99.95% COND DIA 1.120 mm & O/A DIA 1.217 class 180 (SWG 18.5). BS EN ,60317-22 OF 2004 <u>GENERAL SPECIFICATION</u> - ideally upto 99.95 % purity of copper wire is required to ensure optimal electrical conductivity with heat resistance above 180°C and item is general in nature and easily available at local market. Purity of copper wire is required to be upto: 99.95% COND DIA 1.120 mm & O/A DIA 1.217 class 180 (SWG 18.5). BS EN ,60317-22 OF 2004	
164	DNF67954	N150/ N140,125, EXIDE	056279900465 3 / BATTERY 12V 115-125 AH SEC ACID TYPE	GENERAL USE	1 / EACH/NUMBER	N140, N125 EXIDE					<u>TECHNICAL SPECIFICATION</u> - oem exide karachi pakistan <u>GENERAL SPECIFICATION</u> - oem exide karachi pakistan	
165	DNJ45838	63313190 C	281576502288 6 / MAIN		1 / SET						<u>TECHNICAL SPECIFICATION</u> - NO DATA AVAILABLE <u>GENERAL</u>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
			METAL (ITEM NO 1300-5)								SPECIFICATION - NO DATA AVAILABLE	
166	DNG679 11	576139/FS P-0008-12	432000368318 6 / PUMP UNIT CENTRIFUGAL	SELF	2 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - a. Model: 777D - Bronze 777H - Aluminum b. Motor Rating: HP - 5 Phase - 3 Cycle - 60 RPM - 3450 Voltage - 115,220,440 Ac g. Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHOF - 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 Total Head: gallons per minutes Operating speed at rated capacity: 50.000 feet/110.000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow centrifugal pump impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYPE DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING</p>	



S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in horizontal or any midway position</p> <p>GENERAL SPECIFICATION - a. Model: 777D - Bronze 777H - Aluminum b. Motor Rating: HP - 5 Phase - 3 Cycle - 60 RPM - 3450 Voltage - 115,220,440 Ac g. Capacity: 140 GPM at 70 ft Total Head 200 GPM at 50 ft Total Head i. Cable: 45 feet of Conductor Type PHCF - 9 (9030 cm) j. Fresh Water Temperature: 1300 f k. Sea Water Temperature: 1300 f Specification: Maximum discharge flow rate: 180.0 Total Head: gallons per minutes Operating speed at rated capacity: 50,000 feet/110,000 FEET media for which designed: water, salt pumping element operating position: vertical centrifugal pump design: OEM/MANUFACTURERS/CODE: 83590/ STAR ENGINEERING WORKS radial flow centrifugal pump impeller quantity: 1 centrifugal pump impeller suction type: single stage quantity: 1 pump quantity: 1 intake connection quantity: 1 intake connection type: threaded internal INTAKE CONNECTION THREAD SIZE AND SERIES/TYP DESIGNATOR: 2.500-7 1/2 nh DISCHARGE CONNECTION QUANTITY: 1 DISCHARGE CONNECTION TYPE: threaded internal/PIN LOCK SYSTEM DISCHARGE CONNECTION THREAD SIZE AND SERIES/TYP DESIGNATOR: 2.500-7 1/2 NH/2.5" PRIME MOVER TYPES: electric motor PRIME MOVER COOLING</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											MEDIUM: air/WATER PRIME MOVER QUANTITY: 1 CURRENT TYPE: ac VOLTAGE IN VOLTS: 440 FREQUENCY IN HERTZ: 50/60 HZ PHASE: three CURRENT RATING IN AMPS: 7.5 INCLOSURE TYPE: fully inclosed ENVIRONMENTAL PROTECTION: submersible COOLING METHOD: self ventilated SPECIAL FEATURES: controller has magnetic casing, unit will operate in horizontal or any midway position	
167	DNM67481	NO DATA AVAILABLE	4610715089590 / WATER FILTRATION SYSTEM MABZI-THREE STAGES		1 / EACH/NUMBER						TECHNICAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER) QUANTITY 01 GENERAL SPECIFICATION - PRE-FILTER (SEDIMENT FILTER) QUANTITY 01	
168	SGB66988	10N47 (WELDCRAFT (USA) or equivalent)	3439701004654 / CERAMIC SHEILD HI-AMP CUPS SIZE-7, O/A LG 47,4 I/D 9,10 MM		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet. GENERAL SPECIFICATION - Ceramic Shield (Cup) Size No. 7, Part No 10N47, Make: WELDCRAFT (USA) or equivalent, Packing: 10 Pieces/ Packet.	
169	DNQ46497	318RCR-FD4-SEW / 647000283	3120725094066 / BEARING CARRIER	DOCK BILGE PP ZVZ 400/300 FD-IV OEM.	7 / EACH/NUMBER	ZVZ 400/300					TECHNICAL SPECIFICATION - Material = Gun Metal TECHNICAL DATA , Drawing No. D001 MArTERIAL/ GRADE, BS-1400 (LG2/LG4) PRODUCTION METHOD, DRAWN FROM CASTING. GENERAL SPECIFICATION - Material = Gun Metal TECHNICAL DATA , Drawing No. D001 MArTERIAL/ GRADE, BS-1400 (LG2/LG4) PRODUCTION METHOD, DRAWN FROM CASTING	
170	DNM67691	214-925	4940795061949 / SWIVEL STEEL LG-72MM O/D-	AIR POWERED PORTABLE AIRLESS	2 / EACH/NUMBER	GRACO					TECHNICAL SPECIFICATION - MAKE/MODEL: GRACO GENERAL SPECIFICATION - MAKE/MODEL: GRACO	

S No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			26/20 T.P.-16	HYDRA SPRAY								
171	DNQ66744	00779	473099533296 1 / CLAMP HOSE WORM DRIVE TY STEEL ZINC PLATED W13MM BAND 65/226	LUB OIL PURIFIER OEM.ALFA LAVAL ENGG. UK	43 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
172	SGB66985		531099124047 4 / NUT PLAIN HEX 3/8INBSW AF0.600THK0. 312		32 / TEN						TECHNICAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C) GENERAL SPECIFICATION - PD 970 Material Grade 605 M(36) (EN16C)	
173	DNZ60333	501	533078502778 9 / GLAND PACKING CARBONIZED FIBER (NSD/CSG- II/2/132 DT30- 04-2002	M/E PISTON COOLING PUMP TOMG- 125 NASR	2 / METER						TECHNICAL SPECIFICATION - Material: Carbonized fibre GENERAL SPECIFICATION - Material: Carbonized fibre	
174	DNF62013	158-51020	596199558031 4 / REVERSE DIODE	D/GENERATO R(PNS RAJSHAHI)	3 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
175	DNF67995	PP3 6F22. (6135-00- 900-2139)	613570100411 8 / BATTERY DRY FOR MULTIMETER 09V EVER/ENERGI Z 047X25. 75X017MM	A/VO METER	10 / EACH/ UMBER						TECHNICAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED. GENERAL SPECIFICATION - 09V EVER/ENERGIZ 047X25.75X017MM OEM RS COMPONENTS LIMITED.	
176	DNF67912	A-500 APC	614076507817 4 / BATTERY 12V 18AH MODEL A-500	DMG	32 / EACH/ UMBER	LONG WP18- 12SHR					TECHNICAL SPECIFICATION - A. POWER RATING 12V,18AH B. MAKE/OEM YUASA BATTERIES C. TYPE VALVE REGULATED LEAD ACID D. DIMENSIONS ( W X D X H ) 181 X 76 167 (MM) E. TERMINAL TYPE FP TERMINAL F. WEIGHT 6.2 KG GENERAL SPECIFICATION - A. POWER RATING 12V,18AH B. MAKE/OEM YUASA BATTERIES C.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											TYPE VALVE REGULATED LEAD ACID D. DIMENSIONS ( W X D X H) 181 X 76 167 (MM) E. TERMINAL TYPE FP TERMINAL F. WEIGHT 6.2 KG	
177	DNF6793 8	NS240 PLUS /6JC-180	6140785032200 / BATTERY LEAD ACID 12V 180AH SIZE L495MM, W215MM, B203MM	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	2 / EACH/NUMBER	NS 240 PLUS					TECHNICAL SPECIFICATION - Local EXIDE: NS 240 PLUS 12V 180AH GENERAL SPECIFICATION - Local EXIDE: NS 240 PLUS 12V 180AH	
178	SNF5993 2	LRD16 OLD P/N LR2-D1316	594514453607 7 / THERMAL RELAY 9-13AMPS	STARTER (JOSHILA/DEL AIR)	4 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
179	DNF6743 5	6KP	583073512465 1 / INTERCOM SYSTEM WITH JUNCTION BOX & ACCESSORIES	INTERCOM SYSTEM 6KP KOREA	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
180	DNF6769 2	KFAE-55C	610570504423 6 / BLOWER EXHAUST 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3PHASE	EXHAUST BLOWER STEERING COMPART	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1.5 KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE GENERAL SPECIFICATION - 1.5KW 380-420V 5AMP RPM 2950 50HZ 3 PHASE	
181	DNM674 36	757-10191	668572509520 6 / OIL PRESSURE GAUGE (RANGE 0 TO 5 BAR)	GAUGES & METERS LPWT4	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - RANGE 0 TO 5 BAR. GENERAL SPECIFICATION - RANGE 0 TO 5 BAR.	
182	SPC6698 3		047354600470 3 / SODA CAUSTIC (PACKING 25 KG)		200 / KILOGRAMME						TECHNICAL SPECIFICATION - Soda Caustic (chemical nomenclature: SODIUM HYDROXIDE) Chemical formula: NaOH+H2O • Other name of material: Lye, caustic soda water solution • Molecular mass: 40 • Hazard identification number: 80 • UN number: 1824 • Appearance:	