

TENDER BULLETIN

DATE & TIME 9/9/24 11:23 AM

INVITATION TO TENDER TO BE OPENED ON 9/24/2 10:00 AM

AND ITEM REQ BY

CONDITIONS

1. NON REGISTERED FIRMS/SUPPLIERS ARE REQUIRED TO FORWARD BANK DRAFT/PAY ORDER EQUAL TO 5% TOTAL VALUE OF QUOTATION IN FAVOUR OF COMMANDER LOCAL PURCHASE DIVISION ALONGWITH THEIR BIDS.
2. FOR ANY AMPLIFIED DETAILS INTERESTED FIRM MAY CONTACT LOCAL PURCHASE DIVISION IN PERSON OR THROUGH TELEPHONE. DELIVERY TIME OF LOCALLY AVAILABLE ITEMS IS 15 DAYS AND 45 DAYS FOR IMPORTED ITEMS.
3. LAB TESTING CHARGES IF ANY WILL BE BORNE BY FIRM.

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
1	DNF55941	0103-034021-248	593078515451 2 / SELECTOR SWITCH 250V AC 3A	H/PAC	15 / EACH/NUMBER	PNC EB2		ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674	CHINA		TECHNICAL SPECIFICATION - SOURCE OF AVAILABILITY,ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674. GENERAL SPECIFICATION - SOURCE OF AVAILABILITY,ALPINE INDUSTRIAL CON PVT LTD.305/2 GT ROAD BUGHBAN PURA LAHORE PAKISTAN PHONE:042-6852313,6862490 FAX:92-426553674.	
2	DNF65029	ATV31HU75N4A	662573522921 5 / VFD (VARIABLE FREQUENCY DRIVE)	CONTROL SYSTEM	1 / UNIT	SVO55FP5-4	1261600029/30	Wider RoadWali Hing Building, Huaide Nanzing, Fuyong, Baon District Shenzhen, Guangdong, China 518100 Tel: (86755) 29608571 Ext: 612 Fax: (86755) 29608109	CARRIER		TECHNICAL SPECIFICATION - Model: SV055FP5-4 INPUT: 380-480V 3 Phase 17.5A 50/60 Hz OUTPUT: 0-Input V 3 Phase 12.0A 0.1-400 Hz 9.1 KVA/7.5 KW Ser No 55034160366GENERAL SPECIFICATION - Model: SV055FP5-4 INPUT: 380-480V 3 Phase 17.5A 50/60 Hz OUTPUT: 0-Input V 3 Phase 12.0A 0.1-400 Hz 9.1 KVA/7.5 KW Ser No 55034160366	
3	DPC63537	100	534071516068 8 / CHIPS WHITE (SIZE 1/8" FULL 4-6 PARTIAL 25-200 R2/b)	DECK COVERING FOR CONCRETE SURFACE	25 / BAG			OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY, WARREN,MI 48089 PHONE:586-771-	ORIGNAL COLOR CHIPS,A DIVISION		TECHNICAL SPECIFICATION - OEM:ORIGNAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE:586-771-6500/FAX: 586-771-6501. CHIPS WHITE ARE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
								6500/FAX:586-771-6501.			COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS:RESINOUS FLOORING SYS.GENERAL SPECIFICATION - OEM:ORIGINAL COLOR CHIPS,A DIVISION OF NORKAN INC. 26200 GROESBECK HWY,WARREN,MI 48089 PHONE: 586-771-6500/FAX:586-771-6501. CHIPS WHITE ARE COLOURED/FLAKES USE FOR DECORATIVE APPLICATION INCLUDING SEAMLESS:RESINOUS FLOORING SYS.	
4	DNJ64016	8M0078858/B17275A08	2930015618292 / REPAIR KIT WATER PUMP UPPER	MERCURY 300 HP OBM USA	6 / EACH/NUMBER	F300BET X	28469929	MERCURY Marine W6250 Pioneer Road Fond du Lac Wisconsin USA	MERCURY Marine USA		TECHNICAL SPECIFICATION - GEAR HOISING DRIVESHAFT, 4.80 TORPEDO REPAIR KIT WATER PUMP UPPER.GENERAL SPECIFICATION - GEAR HOISING DRIVESHAFT, 4.80 TORPEDO REPAIR KIT WATER PUMP UPPER.	
5	DNF64512	RCU-014	6110015304087 / CONTROL-INDICATOR SUBASSEMBLY	FURUNO	1 / UNIT	2010		FURUNO ELECTRIC CO LTD 9-52 ASHIMURA CHR, NISHINOMIYA,JAPAN	FURUNO ELECTRIC CO LTD		TECHNICAL SPECIFICATION - FURUNO Control Unit GENERAL SPECIFICATION - FURUNO Control Unit	
6	DNM65454	949841-VOLVO	5330270363930 / O-RING	VOLVO PENTA ENGINE	6 / EACH/NUMBER	NO DATA AVAILABLE		27	M/S AB VOLVO PENTA, CITY: GOTEBO RG SWEDEN GOTEBO RG		TECHNICAL SPECIFICATION - - GENERAL SPECIFICATION - -	
7	DPK63936	841GB	9150795160135 / DEKS OLJE D.2 FLEXIBLE HIGH GLOSS FINISH (01 LITER Pack) OEM = OWATROL	SHIP WOODEN STRUCTURE, HULL	30 / LITER			MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL +33(0) 160 86 48 70,FAX: +38 (0) 160 88 84 84-LEQAL	OWATROL-DURIEU GROUP-BP75-		TECHNICAL SPECIFICATION - MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-FRANCE-TELL +33(0) 160 86 48 70, FAX:+38 (0) 160 88 84 84-LEGALGENERAL SPECIFICATION -MANUFACTURE ADDRESS: OWATROL-DURIEU GROUP-BP75-91072 BONDOUFLE CEDEX-	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											FRANCE-TELL:+33(0) 160 86 46 70, FAX:+38 (0) 160 88 84 84-LEOAL	
8	DNF52515	RSB-1104 TIM DIN	592578516079 8 / MCB 2 POLE 220 V 30AMPS	CONVERSION OF BOATSWAIN INTO MRO/BEHR KUSHA	5 / EACH/N UMBER	RSB-1104 TIM DIN		M/S DIGI TECH SHOP NO2 NEW MEMON CHAMBER ALTA HUSSAIN ROAD DENSO HALL KARACHI-7400 ,TEL. 2639514&2638482	M/S DIGI TECH SHOP NO2 NEW MEMON		TECHNICAL SPECIFICATION : null GENERAL SPECIFICATION : null	
9	DPC62751	DERAKAN E 8084	803073514178 9 / EPOXY VINYL ESTER RESIN	MRT338VBS S BOATS	50 / KILOGR AMME	NO DATA AVAILAB LE	OC		1. ASHLAN D CHEMICA L HISPANIA .S.L PARTIDA POVET 37 APDO CORREO S 26, BENICAR LO, CASTELL ON 12580, SPAIN, TEL#*349 64467393 FAX#*34 96447411 7. 2. M/S YONCA- ONUK JV, TERSAN ELER CADDESI 50/3 34,940 TUZLA ISTAN		TECHNICAL SPECIFICATION : SOURCE OF AVAILABILITY-2 ASHLAND CHEMICAL HISPANIA,S. L.PARTIDA POVET 37,APDO CORREOS 26 BENICARLO, CASTELLON 12580,SPAIN.TEL#*34 964 46 7393,FAX#*34 964 47 4117GENERAL SPECIFICATION - SOURCE OF AVAILABILITY-2: ASHLAND CHEMICAL HISPANIA,S. L.PARTIDA POVET 37,APDO CORREOS 26 BENICARLO, CASTELLON 12580,SPAIN.TEL#*34 964 46 7393,FAX#*34 964 47 4117	
10	DNQ63339	SOLO A10-001	129073522627 0 / SOLO A10 150ML (SMOKE	SMOKE DETECTOR	2 / EACH/N UMBER	SOLO A10	NIL	EDISON HOUSE 163 DIXONS HILL ROAD WELHAM GREEN HERTFORDSHIRE AL9 7JE UNITED KINGDOM.	NO CLIMB PRODUC TS LTD		TECHNICAL SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			DETECTOR TESTER)								SPECIFICATION - IPC ATTACHED, MODEL SOLO A10, NON FLAMMABLE AND SILICON FREE SOLUTION	
11	DNQ63438	PHY32.C	4630705212408 / RUBBER DIAPHRAGM FOR FIXED 700 L BOTTLE	AFFF FOAM BOTTLE	2 / EACH/NUMBER	RUBBER DIAPHRAGM FOR PHY32.C	J20552/B7482	ZHENDAN FIRE EQUIPMENT WORKS CHINA. POC IS M/S CSTC CHINA. ITEM IS LOCALLY AVAILABLE AT M/S LONGMAN MILLS LAHORE	ZHENDAN FIRE EQUIPMENT WORKS		TECHNICAL SPECIFICATION - SIZE 1080X1125X2150 MM GENERAL SPECIFICATION - SIZE 1080X1125X2150 MM	
12	DNQ58905	NIL	8415998696940 / SURCOAT WHITE WITH RED CROSS (COTTON/NO MAX MATERIAL)	STOCKING SHIPS FF	4 / EACH/NUMBER	NO DATA AVAILABLE		UK	UK		TECHNICAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0) 2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12. GENERAL SPECIFICATION - OEM M/S COONEEN GROUP UK 23 COONEEN ROAD FIVEMILETOWN COUNTRY TYRONE NORTHERN IRELAND BT75 ONE UK T: +44(0) 2889521401 F: +44(0)2889521488 LOCAL SOURCE GSA TRADERS KARACHI 021-35873927 VIDE DP (N) LETTER 340731/P-34 DATED 28 FEB 12.	
13	DPK55980	92-8m0133951/82-8M0133949	9150715229211 / POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC	300 HP OBM	50 / QUART	1300V24LD	28550466	MERCURY MARINE W6250 PIONEER ROAD FOND DU LAC, WI 54936-1939 TEL NO 920-929-5000	USA		TECHNICAL SPECIFICATION - POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCURY OBMs 300. IPC OF THE SAME AND SPECIFICATION ENCLOSED. GENERAL SPECIFICATION - POWER STEERING FLUID SAE0W-30 FULL SYNTHETIC HYDRAULIC FLUID USED IN MERCURY OBMs 300. IPC OF THE SAME AND SPECIFICATION ENCLOSED.	
14	DNF5080	SWTG DS.6.3	6300705220323 / SMART	SWTG	2 / EACH/NUMBER	DS-6.3		DEFENCE SCIENCE AND TECHNOLOGY		DESTD	TECHNICAL SPECIFICATION - DIMENSIONS HEIGHT 2210MM	

S. No	LPR No	PART NO	NSN / Description	Pr/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WALK THROUGH GATE		UMBER			ORGANIZATION CHAKLALA CANTT RAWALPINDI			WIDTH 810MM DEPTH 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD RECHARGEABLE BATTERY 12 MONTHS LIFE GENERAL SPECIFICATION - DIMENSIONS HEIGHT 2210MM WIDTH 810MM DEPTH 605MM OPERATING VOLTAGE AC 200-230V/DC 12V POWER CONSUPTION 35 WATT WORK ENVIRONMENT -5c-50c NO OF ZONES 06 DISPLAY TYPE LCD RECHARGEABLE BATTERY 12 MONTHS LIFE	
15	DNQ62660	ITEM INDINEGO US DEVELOP	8415595160246 / SURCOAT BLUE	FIRE FIGHTING EQUIPMENT	6 / EACH/UMBER			LOCALLY AVAIL ABLE/IND DEVELOP.	LOCALLY AVAIL ABLE/IND DEVELOP.		TECHNICAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP.GENERAL SPECIFICATION - LOCALLY AVAIL ABLE/IND DEVELOP.	
16	SGE56531	FRS-560G/W	4130705218303 / ROLL FILTER MEDIA	Air less Spray Machine pakistan	2 / ROLL	FRS-560G/W	NA	Pan Weld Enterprise, office # 604-a, Block-A, 6th Floor, Saima Trade Tower, I/I Chundrigar Road, Karachi, Pakistan, Tel: 92-21-227-2221, 92-21-262-7640, e-mail: panweld@cyber.net.pk_	GUANGDONG FRESH FILTER CO.LTD		TECHNICAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER EN 779 CLASS F5 FINAL RESISTANCE = 400 PA TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120CGENERAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER EN 779 CLASS F5 FINAL RESISTANCE = 400 PA TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120C	
17	SGE49534	FRS-560G/W	4130705218303 / ROLL FILTER MEDIA	Air less Spray Machine pakistan	2 / ROLL	FRS-560G/W	NA	Pan Weld Enterprise, office # 604-a, Block-A, 6th Floor, Saima Trade Tower, I/I Chundrigar Road, Karachi, Pakistan, Tel: 92-21-227-2221, 92-21-262-7640, e-mail: panweld@cyber.net.pk_	GUANGDONG FRESH FILTER CO.LTD		TECHNICAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER EN 779 CLASS F5 FINAL RESISTANCE = 400 PA TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120CGENERAL SPECIFICATION - TYPE = ROLL SIZE MEDIA = SYNTHETIC FIBER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											EN 779 CLASS F5 FINAL RESISTANCE = 400 PA TEMPERATURE RESISTANCE = 100C INSTANT TEMPERATURE = 120C	
18	DGE585 04	096-0240-004C	402079515298 7 / ROPE NAVY FLEX 24 MM BROWN 3 STRAND POLYPROPYL ENE (HAWSERLAID)	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL: +4589111213 FAX; +4589111212 E-MAIL: RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL:+4589111213 FAX; +4589111212 E-MAIL:RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS:TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE. GENERAL SPECIFICATION - ISO 1346,9554 & 2307 ANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL:+4589111213 FAX; +4589111212 E-MAIL:RANDERS-ROPE@RANDERS-REB.DK. PARENT/SYS:TALL SHIP SAILING RIG Special Instructions Attached for SPI Only OEM: M/S COTESI UK MANUFACTURED STANDARDS EN ISO 1346 OF 2004, 2307 OF 2005 AND ISO 9554 OF 2005 WITH CERTIFICATE OF CONFORMITY AND OEM TEST CERTIFICATE.	
19	DGE571 14	HEN00300 7	801079520819 8 / FABRIC 1300 GSM MILITARY GREY (HYPALONE)	RHIB BOAT	33 / METER	HENSHA W UK	NIL	HENSHAW INFLATABLES LTD, SOUTHGATE ROAD, WINCANTON,SOMERSET, BA9 9RX, TEL*01963 33237, FAX 01963 34573, EMAIL karen@henshaw.co.uk, www.henshaw.co.uk	HENSHA W INFLATA BLES LTD		TECHNICAL SPECIFICATION - 1. FOR HIGH END PRODUCTS IN MARINE INDUSTRY OUTER LAYER: CSM HYPALONEIS EASY TO BOND, EXTERNAL COATING: CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE) INTERNAL COATING: CR (NEOPRENE) TENSILE STRENGTH: >=350 DAN/GCM TEAR RESISTANCE: >=15 DAN WEIGHT: 1300 (+/- 100G)	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>G/M2 2. Complete item/store description: Fabric 1300 GSM Military Grey Hypalon Packing Detail: Roll 3. Detailed Specification / Technical data / Testing / Acceptance Criteria: Base Fabric: Polyester (high tenacity 1100 dtex-990 deniers) External coating: CSM (Chlorosulfonated Polyethylene) over layer of CR (Neoprene) Internal Coating: CR (Neoprene) Tensile Strength: >=350 daN/gcm Tear Resistance: >=16 daN Weight: 1300 (+/- 100g) g/m2 Marine Standard, resistant to UV rays, abrasion, hydrocarbons and extreme temperatures, fire and heat resistant, air light, flexible and easy to bond to many materials 4. MAKE: HENSHAW UK OEM Country of Origin/ Manufacture: HENSHAW Company, United Kingdom GENERAL SPECIFICATION - 1. FOR HIGH END PRODUCTS IN MARINE INDUSTRY OUTER LAYER: CSM HYPALONEIS EASY TO BOND. EXTERNAL COATING: CSM (CHLOROSULFONATED POLYETHYLENE) OVER LAYER OF CR (NEOPRENE) INTERNAL COATING: CR (NEOPRENE) TENSILE STRENGTH: >=350 DAN/GCM TEAR RESISTANCE: >=16 DAN WEIGHT: 1300 (+/- 100G)</p> <p>G/M2 2. Complete item/store description: Fabric 1300 GSM Military Grey Hypalon Packing Detail: Roll 3. Detailed Specification / Technical data / Testing / Acceptance Criteria: Base Fabric: Polyester (high tenacity 1100 dtex-990 deniers) External coating: CSM (Chlorosulfonated Polyethylene) over layer of CR (Neoprene) Internal Coating: CR (Neoprene) Tensile Strength: >=350 daN/gcm Tear Resistance: >=16 daN</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Weight: 1300 (+/- 100g) g/m2 Marine Standard, resistant to UV rays, abrasion, hydrocarbons and extreme temperatures, fire and heat resistant, air tight, flexible and easy to bond to many materials 4. MAKE: HENSHAW UK OEM Country of Origin/ Manufacture: HENSHAW Company, United Kingdom	
20	DGE58503	006-0320-004C	402079515298 9 / ROPE NAVY FLEX 32 MM BROWN 3- STRAND POLYPROPYL ENE	TALL SHIP SAILING RIG	120 / METER			RANDERS REB A/S VINKELVEJ 10 DK 8900 RANDERS.TEL: +4589111213 FAX: +4589111212 E-MAIL: RANDERS- ROPE@RANDERS-REB. DK.	UK		TECHNICAL SPECIFICATION - 1. MANUFACTURED TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9654:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR GENERAL SPECIFICATION - 1. MANUFACTURED TO STANDARD EN ISO 1346 OF 2004, 2. ISO: 2307: 2005 & ISO: 9654:2005 WITH CERTIFICATE OF CONFORMITY AND OEM CERTIFICATE FOR NAVY FLEX. 3. LENGTH PER COIL: 220 MTR	
21	DNF57849	US/CHINA BRAND/ P- D003	603078516496 3 / PREMIERE / PTCL OPTICAL FIBRE 6-CORE CABLE	PSS (CCTV SYS)	500 / METER			CETC MANSION NO 5 WOLUTONG NORTH STREET, XICHENG DISTRICT, BEIJING, CHINA. 100120	M/S CETC INTERNATIONAL CO LTD		TECHNICAL SPECIFICATION - DIAMETER 7.5MM Make: PREMIERE/PTCL cables GENERAL SPECIFICATION - DIAMETER 7.5 MM Make: PREMIERE/PTCL cables	
22	DNQ65131	B1 PRENEC	597099522452 6 / TAPE INSULATING 30MM	TAPE INSULATING (FF)	2 / ROLL	NO DATA AVAILAB LE		UK	UK ENGLAN D		TECHNICAL SPECIFICATION - NMA6 K4723 M/S DUNLOP GREENGATE (STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL: 01204 466 74. FAX 01204 861 333 EMA lesley.minton@john- holden.com www www.JOHN- HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL GENERAL SPECIFICATION - NMA6 K4723 M/S DUNLOP GREENGATE	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DEMO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											(STROMPROFING LTD) MOSS ROSE MILL, SPRINGFIELD ROAD KERSLEY, BOLTON UNITED KINGDOM BL4 8JW TEL 01204 466 74, FAX 01204 861 333 EMA lesley.minton@john-holden.com www www.JOHN-HOLDEN.COM ITEMS REQUIRED ON VALID PART NUMBER AS PER NMCRL	
23	SGE49515	2058691	841514555760 7 / HAND GLOVES ALUMINIZED WITH PALM LEATHER HEAT	GLOVE	30 / PAIR	NIL	NA	HONEYWELL INTERNATIONAL INS 115 TABOR ROAD MORRIS PLAINS NJ 07950 USA NEW JERSEY	UK		<p>TECHNICAL SPECIFICATION - DESCRIPTION CE CATEGORY: II INTERMEDIARY RISKS IN ACCORDANCE WITH STANDARDS: EN 420-2003 BASIC standards EN 388-2003 MECHANICAL HAZARDS EN 407-2004 HEAT HAZARDS EN 12 477-2000 TYPE A PROTECTION FOR WELDERS</p> <p>CHARACTERISTICS : COWHIDE SPLIT LEATHER GLOVE. GUNN CUT. WINGED THUMB. GAUNTLET TYPE. ALUMINISED KEVLAR BACK OF THE HAND WITH COTTON FLEECE LINER. HEAT RESISTANT SPLIT LEATHER PALM WITH COTTON FLEECE LINING. SPLIT LEATHER CUFF WITH COTTON FLEECE LINER ON PALM SIDE. ALUMINISED KELVAR CUFF WITH COTTON FLEECE LINER ON BACK SIDE. PRODUCT TECHNOLOGY: cut and sewn length: 35,5 cm thickness: leather only 1,1/1,3 mm harmlessness: in conformity with the european standards.</p> <p>GENERAL SPECIFICATION - DESCRIPTION CE CATEGORY: II INTERMEDIARY RISKS IN ACCORDANCE WITH STANDARDS: EN 420-2003 BASIC standards EN 388-2003 MECHANICAL HAZARDS EN 407-2004 HEAT HAZARDS EN 12 477-2000 TYPE A PROTECTION FOR WELDERS CHARACTERISTICS : COWHIDE SPLIT LEATHER</p>	

S. No	LPR No	PART NO	NSN / Description	PIEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											GLOVE. GUNN CUT, WINGED THUMB, GAUNTLET TYPE. ALUMINISED KEVLAR BACK OF THE HAND WITH COTTON FLEECE LINER. HEAT RESISTANT SPLIT LEATHER PALM WITH COTTON FLEECE LINING. SPLIT LEATHER CUFF WITH COTTON FLEECE LINER ON PALM SIDE. ALUMINISED KEVLAR CUFF WITH COTTON FLEECE LINER ON BACK SIDE. PRODUCT TECHNOLOGY: cut and sewn length: 35.5 cm thickness: leather only 1.1/1.3 mm harmlessness: in conformity with the european standards.	
24	DNJ5864 2	15411- 93J10	534076522162 8 / CAP. FUEL FILTER	SUZUKI DF300AP 300 HP OBM	1 / EACH/IN UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - NIL GENERAL SPECIFICATION - NIL	
25	DNQ600 53	08279009	621079517576 2 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	15 / EACH/IN UMBER	UK (RFD BEAUFO RT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFO RT LTD (UK)		TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
26	DNQ626 29	08279009	621079517576 2 / LIFE RAFT INTERNAL LIGHT & BATTERY	UK RFD	6 / EACH/IN UMBER	UK (RFD BEAUFO RT)	08279009	RFD BEAUFORT LTD (UK)	RFD BEAUFO RT LTD (UK)		TECHNICAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK) GENERAL SPECIFICATION - LIFE RAFT INTERNAL LIGHT & BATTERY, RFD BEAUFORT LTD (UK)	
27	DNJ6183 4	25141- 93L00-0EP / 25141- 93L01- 0EP / 25141- 93L00- YAY	534076522193 7 / HOUSING, SHIFT ROD GUIDE (BLACK)	SUZUKI DF300AP 300 HP OBM	1 / EACH/IN UMBER	DF300AP	30002P- 712896	SUZUKI MOTOR CO LTD JAPAN	SUZUKI JAPAN		TECHNICAL SPECIFICATION - ENGINE MODEL DF300AP GENERAL SPECIFICATION - ENGINE MODEL DF300AP	
28	SNS5506 4	8T-0337	530501430027 7 / Screw- Machine (MAX) 0.7X12	Caterpillar Emergency DG Marine Genset C 4.4 USA	5 / EACH/IN UMBER	Marine Genset C 4.4	N/A	14000 OLD GALENA RD TC-A, MOSSVILLE, IL, 61552-7547, U.S.A	CATERPI LLAR INC. OBA CATERPI		TECHNICAL SPECIFICATION - GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			rim)						LLAR DIV GOVERNMENTAL AND DEFENSE PRODUCTS			
29	DNF59979	DCC/HFB MEL/004	5995705214358 / DAFS UNIT	DF RACK 100C2ZL PAK	1 / EACH/NUMBER	100C2ZL	NA	Data Communication and Control Pvt. Ltd. 409 Clifton Center, Block 5 Clifton, KHI 021-35363212	DCC		TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
30	SNF57086	7429766	5930735218570 / PRESSURE SWITCH OIL 17 BAR 230Vac/dc 10AMP	Azimuth Thruster	1 / EACH/NUMBER	7429766	66925,669226	Rolls Royce OY Ab PO BOX 220, FIN-26101 Roma Finland Phone + 358283791. FAX NO + 358283794804 Azimuth Thruster/Propulsion Aftermarket Fax + 358283794804 Home Page: ww.rolls ? Royce.com	Rolls Royce OY Ab, Rauma, Finland		TECHNICAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR. GENERAL SPECIFICATION - PRESSURE SWITCH FITTED WITH STEERING AND LUBRICATION HYDRAULICS SYSTEM AND SEND ALARM WHEN PRESSURE DECREASING BELOW 17 BAR.	
31	DPK64112	N28355-1	9150123772290 / OIL SYNTHETIC/LUBRICATING OIL HYDRAULIC (VDL100) OEM = BAUER	HPAC	45 / LITER	NO DATA AVAILABLE		GR	SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORD HERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENT		TECHNICAL SPECIFICATION - SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORD HERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDY NAMICS.COM WWW. SMITHSDETECTION.COM GENERAL SPECIFICATION - SMITHS DETECTION-WATFORD LIMITED 459 PARK AVENUE BUSHEY, WATFORD HERTFORDSHIRE UNITED KINGDOM WD23 2BW 01923 658185 01923 221361COMMENTS@GRASEBYDY NAMICS.COM WWW. SMITHSDETECTION.COM	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
									S@GRAS EBYDYN AMICS. COM WWW. SMITHSD ETECTIO N.COM			
32	DNF5617 0	KR40KVA / NST- 5400040	613070523223 8 / 40 KVA UPS WITH 60 MINUTES BACKUP TIME	40 KVA UPS WITH 60 MINUTES	1 / EACH / NUMBER	KR40KVA / NST- 5400040	NIL	ADVANCE ENGINEERING GROUP 72H BLOCK2, P.E.C.H.S NEAR NOOR MASJID KASHMIR KARACHI PAKISTAN	ADVANC E ENGINEE RING GROUP		TECHNICAL SPECIFICATION - SPECIFICATION: UPS ONLINE DOUBLE CONVERSION SINE WAVE. BRAND: ABLEREX MODEL: KR40KVA ORIGIN: ITALY 3 PHASE IN/OUT 50HZ BACKUP TIME: 60 MINUTES ON 100-120 COMPUTER SYSTEM WITH EXTERNAL BATTERIES BATTER BRAND: SPRINTER EXIDE BATTERY RATING: 12V 41AH X 40 PSC BATTERY ORIGIN: PORTUGAL WARRANTY: 02 YEARS COMPREHENSIVE REPLACEMENT WARRANTY WILL BE OFFERED INCLUDING BATTERIES GENERAL SPECIFICATION - SPECIFICATION: UPS ONLINE DOUBLE CONVERSION SINE WAVE. BRAND: ABLEREX MODEL: KR40KVA ORIGIN: ITALY 3 PHASE IN/OUT 50HZ BACKUP TIME: 60 MINUTES ON 100-120 COMPUTER SYSTEM WITH EXTERNAL BATTERIES BATTER BRAND: SPRINTER EXIDE BATTERY RATING: 12V 41AH X 40 PSC BATTERY ORIGIN: PORTUGAL WARRANTY: 02 YEARS COMPREHENSIVE REPLACEMENT WARRANTY WILL BE OFFERED INCLUDING BATTERIES	
33	DPC590 38		647450220171 1 / SOAP TYPE B SOAP SCRUBBING ALKALINE	SKF COUPLING	500 / KILOGR AMME						TECHNICAL SPECIFICATION - BS 1913 of 1990 TYPE B USED FOR GENERAL CLEANING PURPOSE GENERAL SPECIFICATION - BS 1913 of 1990	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			JELLY 10KG DRUM								TYPE B USED FOR GENERAL CLEANING PURPOSE	
34	SGE483 61	TIGER BRAND	046159000776 7 / SCREEN HAND FOR ELECTRIC WELDING WITH GLASS BLACK.		30 / EACH/ UMBER						TECHNICAL SPECIFICATION - Material: High Density Polyethylene HDPE Size: 9 x 6 inch or any suitable size Color: BLACK Style: FULL FACE GENERAL SPECIFICATION - Material: High Density Polyethylene HDPE Size: 9 x 6 inch or any suitable size Color: BLACK Style: FULL FACE	
35	SGE561 41		046159220367 8 / PAPER, ABRASIVE 9" X11" (OROCUS) MATERIAL EMERY GRADE 4/0		1800 / SHEET						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
36	DGE641 50	319- SIVLER- DE	047659000003 1 / BRUSH STEEL WIRE SURFACE CLEANING SMALL		448 / EACH/ UMBER	319- SILVER- DE					TECHNICAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: Grams 7. PRODUCT DIMENSION: L- 200mm, W-25mm, T- 8mm, Brush Dimension: L- 78mm x W-22mm x 15mm 8. MODEL: Wooden handled Brass/ Steel Wire Brush- 6 inches/ Can be customized as per user requirement GENERAL SPECIFICATION - 1. ITEM WEIGHT: 4.9 OUNCES 2. SIZE: LARGE 3. COLOR/MATERIAL: STAINLESS STEEL 4. GRIT DESCRIPTION: FINE 5. ADDITIONAL INFO: ASIN B07RP9X98J 6. ITEM WEIGHT: Grams 7. PRODUCT DIMENSION: L- 200mm, W-25mm, T- 8mm, Brush Dimension: L- 78mm x W-22mm x 15mm 8. MODEL: Wooden handled Brass/ Steel Wire Brush- 6 inches/ Can be customized as per user	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											requirement	
37	DGE62618		0350595713034 / ROPE COIR, HAWSERLAID, 3-STRAND, CIRC: 3-INCH, DIA: 1-INCH (24MM)		400 / FATHOM						TECHNICAL SPECIFICATION - LENGTH PER COIL: 120 FATHOM, OEM COC REQUIRED.GENERAL SPECIFICATION - LENGTH PER COIL: 120 FATHOM, OEM COC REQUIRED.	
38	DGE64305		0462502201803 / TUBING PLASTIC POLYETHYLENE LAY FLAT WD.48	DC/FF	705 / KILOGRAMME						TECHNICAL SPECIFICATION: 0.0002" for single ply, T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317GENERAL SPECIFICATION - 0.0002" for single ply, T-64 BR 320D of 1976, Weight per Roll 96Lbs, Length per Roll 500 foot, Thick of Plastic 0.010inch. Spec: DEF 1317	
39	SGE56515	202-GNFG	0475590007758 / GLOVES SEAMLESS DIPPED RUBBER I.R. SIZE 9		780 / PAIR	202-GNFG					TECHNICAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who involve / Deal with high voltage electricity GENERAL SPECIFICATION - a. Product Code: GL 897 Black Nitrile Gloves b. Thickness: 2.3 mil c. Size: AVAILABLE SIZES STANDARD SIZE (FIT TO ALL) d. 13g/ 15g polyester & nylon liners Nitrile smooth finish full coated e. Specification 13g/ 15g polyester &	

S. No	LPR No	PART NO	NSI / Description	PEquipment	QTY / DENO	Model	SR NO Cf PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											nylon liners Nitrile smooth finish full coated f. Application Paints, Oils, Gases, Metal etc g. Detailed Specifications/ Technical Data: Gloves Seamless Dipped Rubber (as per sample) are essentially required for safety of personnel deployed at Machine Shop, Metal Treatment Shop and for other who involve / Deal with high voltage electricity.	
40	SPC51403		0473504730146 / ZINC OXIDE WHITE	FWT TAKE OFF DR	100 / KILOGRAMME						<p>TECHNICAL SPECIFICATION- DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX503R. GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES : THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS. REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZNO) IGNITED BASIS 99.8 MM 99.9 SUPPLIER (CALCULATION) LEAD</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabili ty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>(PB) * 0.003 MAX 0.002 ASTM D407S CADMIUM (CD)* 0.002MAX 0.0003 ASTM 0407S IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER(CU) 0.001MAX 0.0001 ASTMND40750 LOSS AT 110°C (MOISTURE) 0.25 MAX 0.1S ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2.000 TO 2.500 LB NET WT PALLET, OR 2.000 LB FIBC. (PACKING 25 KG BAG)GENERAL SPECIFICATION- DESCRIPTION : OUR ZINC OXIDE PRODUCT IS A BRILLIANT WHITE POWDER MANUFACTURED BY THE FRENCH (INDIRECT) PROCESS. GRADE 103 OFFERS VERY HIGH PURITY, LARGE PARTICLE SIZE, AND THE LOWEST M2/G SURFACE AREA ("SA") AVAILABLE IN HIGH QUALITY FRENCH PROCESS PRODUCT. GRADE 103 REPLACES GRADES ZINC OXIDE LLC 800XL, KADOX 930, AND KADOX XX503R GRADE 103 IS ALSO A DROP IN SUBSTITUTE FOR AMERICAN (DIRECT) PROCESS ZINC OXIDE IN MOST APPLICATIONS. USES : THIS GRADE IS USED WHERE A VERY LOW IMPURITY LARGE PARTICLE SIZE ZINC OXIDE IS REQUIRED SUCH AS IN ELECTRONIC SOFT FERRITES, VARISTORS, CERAMICS, AND PAINT AND COATINGS. THIS PRODUCT IS ALSO AVAILABLE IN PELLETTED FORM (GRADE 103P), AND WITH AROUND UP TO 0.1% PROCESSING AID/SURFACE TREATMENT (GRADE 103T) FOR SOME RUBBER MIXERS REPRESENTATIVE CHEMICAL PROPERTIES: ZINC OXIDE (ZnO) (GNITED BASIS: 99.8 MM 99.9</p>	

S. No	LPR No	PART NO	NSN / Description	PI/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SUPPLIER (CALCULATION) LEAD (PB) * 0.003 MAX 0.002 ASTM D4075 CADMIUM (CD) * 0.002 MAX 0.0003 ASTM D4075 IRON (RE) 0.002 MAX 0.0003 ASTM D4075 COPPER(CU) 0.001 MAX 0.0001 ASTM D4075 LOSS AT 110°C (MOISTURE) 0.25 MAX 0.15 ASTM D280 STANDARD PACKAGING: 50 LB. KRAFT PAPER BAGS ON 2,000 TO 2,500 LB NET WT PALLET, OR 2,000 LB FIBC. (PACKING 25 KG BAG)	
41	DPK64099	0474-7021 (0475-99-224-2137)	0474502242137 / TALLOW WHITE (GREASE) (200 KG DRUM)		50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
42	SGE52938		0462590005989 / TUBING PLASTIC POLYTHYNE LAY FLAT 0.005"TH.WD. 27"WEIGHT PER		220 / KILOGRAMME						TECHNICAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE) GENERAL SPECIFICATION - TUBING PLASTIC POLYTHYNE LAY FLAT KILOGRAM 0.005"TH. WD.27" WIEGHT PER. DIAMETER: 27 INCHES. Diametre: 27 Inches thickness: 0.005 inches (DOUBLE SIDE)	
43	DPC58654		0473504730040 / ZINC PHOSPHIDE (RAT POISON)		1 / KILOGRAMME						TECHNICAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER:1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG PACKET)GENERAL SPECIFICATION - MOLECULER FORMULA: Zn3 P2 MOLECULER WEIGHT: 268.08 CAS NUMBER: 1314-84-7 PERCENTAGE: 100% BOILING POINT: 2012 F MELTING POINT: 788F (PACKING: 01 KG	

S. No	LPR No	PART NO	NSN / Description	Pl/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
44	DGE562 87		047450474012 6 / SHAMIANA COMPLETE SZ. 18.00X36. 00 FT.		8 / EACH/N UMBER						PACKET) TECHNICAL SPECIFICATION - MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)GENERAL SPECIFICATION: MATERIAL: 100% COTTON, BAMBO OF MATURE STEM, SOUND,REASONABLY STRAIGHT & FREE FROM100% BORER OR INSECT HOLES (GHOON),SPLIT AND PRESERVED. Color: Item is required in multicolor i e (yellow, green)	
45	DGE541 85		046159000405 8 / HEAD SCREEN FOR ELECTRIC WELDING WITH GLASS BLACK.		31 / EACH/N UMBER						TECHNICAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11). Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dini protection. standards: en166, en169, en175, & ce make : delta plus, franco / uaeGENERAL SPECIFICATION - Specifications: ANSI Z87.1 - 2003 also EN 175 Min Shade (6 upto 11). Min lens th (2mm) Likely Source: Lincoln, Miller, Weldline, SACIT, Hobart etc. are all welding helmet manufactures. casuod3 headband welding shield for all type of welding that require shade dini protection. standards: en166, en169, en175, & ce make : delta plus, franco / uae	
46	DGE540 18		035059571313 0 / ROPE NYLON HAWSERLAID, 3-STRAND.	TOWING & BERTHING ROPE	620 / METER						TECHNICAL SPECIFICATION:- 1- type: polypropylene-3 strand , 2. max breaking strength: 7.5 tonnes-3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I/E ISO 1140 OF	

S No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN. SPECS	Dimension
			CIRC: 3-1/2 INCH, NOM DIA: 28MM, (1-1/8"), TYPE-1,								2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.GENERAL SPECIFICATION - 1. type: polypropylene 3 strand , 2. max breaking strength: 7.6 tonnes 3. 220 MTR PER COIL, 4. GENERAL SPECIFICATION I.E ISO 1140 OF 2004 & ISO 2307 OF 2005 5. CERTIFICATION: VALID LLOYD'S TEST CERTIFICATE REQUIRED INDICATING BATCH/LOT NUMBER OR IDENTIFICATION AND WORKING/ BREAKING STRENGTH OF STORES.	
47	DGE44803		0421599244635 / CHAIR-PEDESTAL		25 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
48	DGE58431		0421599425637 / FILING CABINET SIZE, 4-DRAWERS W/LOCK combination AND COMPRESSOR PLATES GREY GAUGE SWG-22 SIZE; W18 INCH		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - GAUGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH, HEIGHT:52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user GENERAL SPECIFICATION - GAUGE SWG:22 SIZE; Width:18 INCH. Dia:24 1/2 INCH. HEIGHT:52 INCH. MPBW CODE: 01-18-114 REQUIRED MATERIAL STEEL REQUIREMENT OF LOCK 01 LOCK WITH OVERALL 4 DRAWERS Item locally available and accepted by end user	
49	DGE64477	0415-9061	0415599231419 / SAFETY WALK THREAD NONMETALIC,		1050 / EACH/NUMBER						TECHNICAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed; Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated ; Anti-	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NON-SKID, LENGTH= 2- FEET, WIDTH= 6-INCH,								Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-FEET, Width 6-INCH GENERAL SPECIFICATION - 1. Make / Model / Brand / Equivalent be endorsed. Local 2. OEM / country of Origin / Manufacture : Pakistan 3. Parent equipment be indicated : Anti-Skid Safety Walk Used Over Stairs, 4. Detailed specifications / Technical data Testing : Safety Walk Thread Nonmetallic Nonskid SIZE: Length 2-FEET, Width 6-INCH	
50	SGB39775	FLUXITE PASTE	0283595711610 / FLUX SOLDERING PASTE FORM FLUXITE TYPE 4509 TIN (500GRAM TIN)		40 / TIN						TECHNICAL SPECIFICATION - Multi-purpose paste flux Well established product Quick and clean to use WRAS Approved Product Suitable for lead free and lead containing solder alloys Effective and reliable soldering flux broushers attached as document GENERAL SPECIFICATION - Multi-purpose paste flux Well established product Quick and clean to use WRAS Approved Product Suitable for lead free and lead containing solder alloys Effective and reliable soldering flux broushers attached as document	
51	DPC63466	NO DATA AVAILABLE	0444500010551 / SOLUTION FOR SCALE REMOVING packing 20 or 25 lit		50 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
52	DGB62643		0283595711457 / ROD NAVAL BRASS RO DIA 2.25" WT PER FT 14.73(LB)		12 / METER						TECHNICAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade 712 (M), Running Length (Min): 02 meter GENERAL SPECIFICATION - Specifications: BSEN 12163 of 1998 Grade 712 (M), Running Length (Min): 02 meter	
53	DGB62641		0283595711465 / ROD		2 / METER						TECHNICAL SPECIFICATION - BSEN 12163/2011, GRADE	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO Cf. PR	MANUF ALID	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			NAVAL BRASS ROUND (DIA 4.125", WT/MTR49.90 lb/ft								CW712R (CZ112) RUNNING LENGTH: 1.5 METER authority: as per br 320d GENERAL SPECIFICATION - BSEN 12163/2011, GRADE: CW712R (CZ112) RUNNING LENGTH: 1.5 METER authority: as per br 320d	
54	DGE58533		0413705063244 / ANTI SKID DOTTED RUBBER FLOORING COLOUR GREY 15"X36" X0.17".		100 / EACH/NUMBER						TECHNICAL SPECIFICATION - ANTI SKID DOTTED RUBBER FLOORING COLOUR GREY size: 15"X36"X0.17". Rubber Specs: Nitrile rubber Equivalent (Hyper V Oil Resistant Type) Thickness: 4mm Fabric: 1Ply, 2 PlyGENERAL SPECIFICATION - ANTI SKID DOTTED RUBBER FLOORING COLOUR GREY size: 15"X36"X0.17". Rubber Specs: Nitrile rubber Equivalent (Hyper V Oil Resistant Type) Thickness: 4mm Fabric: 1Ply, 2 Ply	
55	SGE49098	0414-5162	0414699230935 / ASBESTOS SHEET COMPRESSE D, LENGTH: 63-INCH, WIDTH: 54-INCH, THICKNESS: 0.125 INCH	GENERAL PERPOSE	90 / KILOGRAMME						TECHNICAL SPECIFICATION - Dimension/Size: LENGTH: 63 INCH, WIDTH: 54 INCH, THICKNESS: 0.125 INCH COLOUR: RED, MATERIAL: ASBESTOS BS-2815GENERAL SPECIFICATION - Dimension/Size: LENGTH: 63 INCH, WIDTH: 54 INCH, THICKNESS: 0.125 INCH COLOUR: RED, MATERIAL: ASBESTOS BS-2815	
56	SGE49522	NIL	0413599238936 / RUBBER STRIP WIDTH 0.375"HEIGHT 0.375".		115 / METER						TECHNICAL SPECIFICATION - SPECSIFICATIONS: BS-1155 MATERIAL: NATURAL, HARDNESS RATING: 42.0 MINIMUM AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, FABRICATION METHOD: SOLID, COLOUR: WHITE, CROSS SECTIONAL SHAPE STYLE: SQUARE, CROSS SECTIONAL WIDTH: 0.375 INCHES, CROSS SECTIONAL HEIGHT: 0.375 INCHES.GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATIONS: BS-1155 MATERIAL: NATURAL. HARDNESS RATING: 42.0 MINIMUM AND 50.0 MAXIMUM INTERNATIONAL RUBBER HARDNESS DEGREE SCALE, FABRICATION METHOD: SOLID, COLOUR: WHITE, CROSS SECTIONAL SHAPE STYLE: SQUARE, CROSS SECTIONAL WIDTH: 0.375 INCHES, CROSS SECTIONAL HEIGHT: 0.375 INCHES.	
57	DGB522 12		021259571070 5 / BAR STEEL CORROSION RESISTING H/R RD 03' WT PER FT24. 030LBS	MAT IDEN SYMBLO. L42H35 18% CHROM	6 / METER						TECHNICAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 8 meter GENERAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter	
58	SGB490 55		021259571070 5 / BAR STEEL CORROSION RESISTING H/R RD 03' WT PER FT24. 030LBS	MAT IDEN SYMBLO. L42H35 18% CHROM	2 / METER						TECHNICAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter GENERAL SPECIFICATION - BS 970, Material Grade SS 316S16, Running Length: 6 meter	
59	SGB487 39		021259571069 9 / BAR STEEL CORROSION RESISTING H/R RD 0.50		100 / METER						TECHNICAL SPECIFICATION - material grade: SS316L GENERAL SPECIFICATION - material grade: SS316L	
60	DGB573 12		026659000039 0 / HAND CUFFS BRIGHT STEEL LARGE SIZE WITH KEY		64 / PAIR						TECHNICAL SPECIFICATION - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg GENERAL SPECIFICATION - made of iron steel coated total length approx: 5 1/2 feet inner opening for the wrist approx: 65x50 mm chain length approx : 5 feet the key is approx: 76 mm long weigh approx : 1.370 kg	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
61	DGB545 82		026759923532 9 / UNION PIPE BLACK BORE 3/4"		24 / EACH/ UMBER						TECHNICAL SPECIFICATION - bs1740 table: 20 finish: black GENERAL SPECIFICATION - bs1740 table: 20 finish: black	
62	SGB449 45		026759923533 6 / TEE PIPE GALVANISED SIZE 15MM BORE 1/2"		150 / EACH/ UMBER						TECHNICAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE 1/2 INCH, GENERAL SPECIFICATION - Internal Dia: 18.5mm, External Dia: 27mm, Wall Thickness: 4.5mm, Galvanization Thickness: 0.5 - 1mm, SPECIFICATIONS: BS 1740/71, MATERIAL: STEEL/ FERROUS ALLOY, DIMENSION: 15 MM, NOMINAL BORE 1/2 INCH.	
63	SGB102 57		026759923533 7 / TEE PIPE EQUAL GALVANISED		200 / EACH/ UMBER						TECHNICAL SPECIFICATION - SIZE: 3/4, THICKNESS: 5MM, runing length: 850mm, Material Grade: Mild Steel with Galvanization of 2.5 mm GENERAL SPECIFICATION - SIZE: 3/4, THICKNESS: 5MM, runing length: 850mm, Material Grade: Mild Steel with Galvanization of 2.5mm	
64	SGB561 64		021259571068 1 / BAR- STEEL-HOT- ROLLED-RD- 0.31 INCH		3 / METER						TECHNICAL SPECIFICATION - Specification PD- 970 Material grade 605 M(36) running length : 10 ft GENERAL SPECIFICATION - Specification PD- 970 Material grade 605 M(36) running length : 10 ft	
65	DGB568 81		026859000146 7 / WEIGHING- MACHINE- WITH-HOOK-1- TO-30-POUND		3 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABEGENERAL SPECIFICATION - NO DATA AVAILABLE	
66	DGB514 16	0267- 10598	026759923534 7 / TEE PIPE EQUAL GALVANISED NOM BORE SZ 2.50		60 / EACH/ UMBER						TECHNICAL SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENINGS, NOMINAL BORE SIZE: 2.5" (65MM), PROTECTION: GALVANIZEDGENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - SPECS: BS 1740, SHAPE: TEE EQUAL OPENINGS, NOMINAL BORE SIZE: 2.5" (65MM), PROTECTION: GALVANIZED	
67	DGB54585		026759923534 9 / TEE PIPE EQUAL (GALVANISED) 03.00IN		50 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5 mm GENERAL SPECIFICATION - Material: G.I Inner Dia: 85mm Outer Dia: 98mm Wall Thickness: 6.5mm	
68	SGB31386		021459033070 8 / STUD-PLAIN-BSW-THREA-D-0.43-INCH-LENGTH-2-INCH		95 / TEN						TECHNICAL SPECIFICATION - THREAD SIZE: 0.43 INCH, LENGTH OF THREAD: 2 INCH, MATERIAL END: 7/16 INCH, NUT END: 7/8 INCH, AUTHORITY: AS PER BR 320D SPECS PD970:2005, GRADE 708M40/42CRM04 OEM COC/MTC REQUIRED GENERAL SPECIFICATION - THREAD SIZE: 0.43 INCH, LENGTH OF THREAD: 2 INCH, MATERIAL END: 7/16 INCH, NUT END: 7/8 INCH, AUTHORITY: AS PER BR 320D SPECS PD970:2005, GRADE 708M40/42CRM04 OEM COC/MTC REQUIRED	
69	SGB58592		021459013101 5 / BOLT MACHINE STEEL BSF HEX HD SZ 0.625X3.750X1.250 INCH		40 / EACH/NUMBER						TECHNICAL SPECIFICATION - Material: MS, Grade AISI 4140, BS 708M40, DIN 42CrM04 is also acceptable. GENERAL SPECIFICATION - Material: MS, Grade AISI 4140, BS 708M40, DIN 42CrM04 is also acceptable.	
70	SGB44852		021459033101 0 / Stud Plain (Ends threaded unequal LENGTH), THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END:		600 / EACH/NUMBER						TECHNICAL SPECIFICATION - DGS.8060 A CLASS-1, EN 4140 DGS 8060 Class 1(B), BS 970, Material Grade EN16 (605 M36) or EN 100 (945 M38), Condition: R LENGTH), THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END 1 1/4" GENERAL SPECIFICATION - DGS.8060 A CLASS-1, EN 4140 DGS 8060 Class 1(B), BS 970, Material Grade EN 16,	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			1 1/4"								(605 M38) or EN 100 (945 M38). Condition: R LENGTH). THREAD SIZE: 5/8", LENGTH: 2 1/2", LENGTH OF THREAD: METAL END: 5/8", NUT END 1 1/4"	
71	SGB102 60	SPEC BSS 2674 CZ 112 M	028370571144 9 / ROD NAVAL BRASS RD DIA 1.25" WT PER FT 4.58LB		7 / METER						TECHNICAL SPECIFICATION - SPECIFICATION: BSEN/2/63 OF 1998 MATERIAL GRADE: CW712R GENERAL SPECIFICATION - SPECIFICATION: BSEN/2/63 OF 1998 MATERIAL GRADE: CW712R	
72	DGE612 30	DEFSTAN 40-3	033059571325 3 / TWINE HEMP 3- STRAND, MIN BKG STRENGTH 810 LBS, DIA: 7mm		17 / EACH/ UMBER						TECHNICAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM Material: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT: CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557, CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS GENERAL SPECIFICATION - APPROX CIRC 7/8" DIA 7MM Material: Jute Process : Twist Colour Natural: Brown Diameter: 10 mm Weight: 8-10 kg SURFACE TREATMENT CLEANING: FIBER END (BURR TRIM) T-4 ALSO KNOWN AS FISHING LINE SPECIFICATION BS 2019 C-1557. CONSTRUCTION STYLE: 3 PLY/ 3 STRANDS	
73	DGE561 99	NIL	035059823713 0 / ROPE NYLON, HAWSERLAID, 3-STRND, Z- LAY, NOM DIA: 28 MM, CIRC: 3.50 INCH, TYPE-1, MIN BRKG STRENGTH 15.500 TONS	MIN BRKG STRENGTH 15.500 TONS UNIT OF	920 / METER						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. GENERAL SPECIFICATION - 1. TO BE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
74	DGE585 29	NIL	035059923713 0 / ROPE NYLON, HAWSERLAID, 3-STRND, Z- LAY, NOM DIA: 28 MM, CIRC: 3.50 INCH, TYPE-1, MIN BRKG STRENGTH 15.500 TONS	MIN BRKG STRENGTH 15.500 TONS UNIT OF	440 / METER						TECHNICAL SPECIFICATION:- 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED. GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E). 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005. 4. LENGTH: PER COIL: 120 FATHOM. 5. OEM COC REQUIRED.	
75	SGB316 54		021470053083 8 / NUT PLAIN HEX BSF SIZE 3/4"X1.20"X0. 687 INCH		700 / EACH/N UMBER						TECHNICAL SPECIFICATION:- SPECS PD 970.2005, GRADE 708M40/42CRM04, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75 INCHES, 12 TPI), NOMINAL LENGTH: 5/8 (0.625 INCHES), THICKNESS: (1 1/8" (1.125 INCHES) GENERAL SPECIFICATION:- SPECS PD 970.2005, GRADE 708M40/42CRM04, MATERIAL: FERROUS THREAD SIZE: 3/4 (0.75 INCHES, 12 TPI), NOMINAL LENGTH: 5/8 (0.625 INCHES).	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENC	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											THICKNESS: (1 1/8" (1.125 INCHES)	
76	DGB540 16		027679910587 0 / SCREW DRIVER RATCH, DOUBLE SPIRAL AUTO RETURN, 250MM LG.3 BITS		57 / EACH/NUMBER						TECHNICAL SPECIFICATION - Detail specification: Screw Driver Ratch, Double Spiral, Auto Return Technical data: Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER Made in China GENERAL SPECIFICATION - Detail specification: Screw Driver Ratch, Double Spiral, Auto Return Technical data: Screw Driver Set Flexible 215MM, 30 Accessories by HOLZER, Made in China	
77	SGB314 87	BS 1769 (5306-99- 941-0015)	021459941001 5 / BOLT MACHINE THD UNC CLASS 2A, HEX HD TPI 11 SZ 0.625X2X1.5"		300 / EACH/NUMBER						TECHNICAL SPECIFICATION - METRIAL GRADE EN 4140 steel grade aisi 4140(pd 970:2005 grade 708m40/42cm40 oem coc required GENERAL SPECIFICATION _METRIAL GRADE EN 4140 steel grade aisi 4140(pd 970:2005 grade 708m40/42cm40 oem coc required	
78	SGB615 74		026659001803 0 / WASHER FLAT ROUND MILD STEEL 0.625X0. 687X1.375X0. 128IN	O/D 34.925 INCH THK 0.128 INCH SPEC=BS- 1769	190 / KILOGRAMME						TECHNICAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925MM), THICKNESS 0.128" INCH (3.25MM), NO TEMPER REQUIREMENT IS REQUIRED GENERAL SPECIFICATION - SPEC=BS1769, MILD STEEL GRADE EN4140, BORE 0.687" INCH (17.45MM), DIAMETER 1.375" INCH (34.925 MM), THICKNESS 0.128" INCH (3.25 MM), NO TEMPER REQUIREMENT IS REQUIRED	
79	DGB485 57	0246-4028 (BRAND- NICH) / c 21-1	024679463385 4 / HOIST CHAIN STEEL GEARED HAND OPERATED SWIVEL HOOKS,	SHIP 76,LOAD CHAIN 1,MAX. DIST.HOOK TO	3 / EACH/NUMBER	HE-50A					TECHNICAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76,LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up). Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model:	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CAPACITY 01 TON								NITCHE HH5010A (OR) Equivalent mtc required, table 40 a is enclosed GENERAL SPECIFICATION - MAKE: ELEPHANT CHAIN BLOCK MADE IN JAPAN SHIP 76.LOAD CHAIN 1,MAX.DIST.HOOK TO MAXIMUM DISTANCE: 16 INCH (Hook to Hook when drawn up), Height of Lift: 10 ft, Maximum Working Load: 3240 LBS, Model: NITCHE HH5010A (OR) Equivalent mtc required, table 40 a is enclosed	
80	DNQ614 21	BS - EN - 3	024359129583 3 / FIRE EXTINGUISHER CO2 5.5 KGS RED	FIRE FIGHTING EQUIPMENT	141 / EACH/NUMBER						TECHNICAL SPECIFICATION - SPECS: BS - EN - 3 NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150-160mm CYLINDER HIGH (mm): 800-840mm CYLINDER WEIGHT (Kg) 6-8KG EXTINGUISHER WEIGHT(kg) 11-13kg GENERAL SPECIFICATION - SPECS: BS - EN - 3 NOTE: ADVANCE SAMPLE IS TO BE SUBMITTED BY THE FIRM TO CINS FOR APPROVAL PRIOR ORDERING/OFFERING COMPLETE STORE FOR INSPECTION UL/FM, BSI/KITE MARK LPCB APPROVED SHOULD COMPLY WITH PROVISIONS OF EN-3-7, 3-9 & 3-10 BS 5045-7:2000 PRODUCT NAME : CO2 EXTINGUISHER 5KG OUT DIAMETER (mm) 150-160mm CYLINDER HIGH (mm): 800-840mm CYLINDER WEIGHT (Kg) 6-8KG EXTINGUISHER WEIGHT (kg) 11-13kg	

S. No	LPR No	PART NO	NSN / Description	R/Equipment	QTY / DENO	Moort	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
81	DNO5552	G4A1H0121CMOD	0243995318927 / FIRE HOSE DURALINE/GO MTEX ID2 LENGTH: 40 FEET (1+1M) /FEMALE COUPLING	FOR FIRE FIGHTING EQUIPMENT	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - length: 40 feet (1+1m)/female coupling GENERAL SPECIFICATION - length: 40 feet (1+1m)/female coupling	
82	SGB49060	0285-111	0265594233195 / NAIL STEEL WIRE ROUND, CHEQUERED HD, SWG 9 LG 3.0 IN (LOCAL)		300 / KILOGRAMME	local					TECHNICAL SPECIFICATION - nail steel wire round 3 inch GENERAL SPECIFICATION - nail steel wire round 3 inch	
83	DGB54102		0251704119609 / CLIP FLAG SWIVEL EYE MFR DGS 002503348/01 OF 01		1620 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
84	DGB54583	NO EACH PKT)	0251704119610 / CLIP-FLAG-FIXED-EYE W/O SWIVEL DGS 002503348/01-OF 01 (10 IN	FOR FLAG FITTING	1620 / EACH/NUMBER						TECHNICAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material GENERAL SPECIFICATION - dimension / size: Length = 50mm Width = 25mm Depth = 05mm Upper Hole = 15mm Lower Hole = 15mm Spec: Brass material	
85	DGB52219	NO DATA AVAILABLE	0212595710028 / BAR-STEEL-CARBON, ROUND -4 INCH WEIGHT PER FT (LB) 42.73		8 / METER						TECHNICAL SPECIFICATION - STANDARD SPECIFICATION; DNC/S2A/ BS 970 070M20 (en3a) RUNNING LENGTH OF ITEM IS 15 TO 16 FT AS PER BR 320 D. GENERAL SPECIFICATION - STANDARD SPECIFICATION; DNC/S2A/ BS 970 070M20 (en3a) RUNNING LENGTH OF ITEM IS 15 TO 16 FT AS PER BR 320 D.	
86	SGB54863		0212700000440 / BAR-STEEL-HEXAGONAL-0.75-INCH		5 / METER						TECHNICAL SPECIFICATION - Material Grade SS 316, Running Length: 1 meter GENERAL SPECIFICATION - Material Grade SS 316, Running Length: 1 meter	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
87	DGB54028	0251-14505	025170411973 7 / FERRULE- WIRE-ROPE 1.5 INCH (12mm)		500 / EACH/ NUMBER						TECHNICAL SPECIFICATION:- ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA:27.2 MM ferrule length: 45 mm GENERAL SPECIFICATION:- ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA: 27.2 MM ferrule length: 45 mm	
88	DGB54595	0251-14505	025170411973 7 / FERRULE- WIRE-ROPE 1.5 INCH (12mm)		339 / EACH/ NUMBER						TECHNICAL SPECIFICATION:- ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA:27.2 MM ferrule length: 45 mm GENERAL SPECIFICATION:- ferrule 1.5 inch (12mm) aluminum alloy ferrule outer: dia:38.1 mm FERRULE inner: DIA: 27.2 MM ferrule length: 45 mm	
89	SGE49300		2040PK310105 2 / RUBBER SHEET SIZE WEIGHT: 10- KG, LENGTH: 7-FT, WIDTH: 1- FT, THICKNESS: 3/8-INCH	FENDER	100 / KILOGR AMME						TECHNICAL SPECIFICATION:- MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50*±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-80 SPECS AS PER BS-1154 SIZES OF ITEM: WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN: MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN KAISER SAHTTI 0321- 2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720962GENERAL SPECIFICATION:- MATERIAL: NATURAL RUBBER COLOUR OF RUBBER: BLACK COMPOUND: NR DARDNESS (SHORE A): 50*±5 DENSITY: 1.15 G/CM2 TENSILE STRENGTH: 17 MPA ELONGATION	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / GENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											AT BREAK: 500% ABRASION RESISTANCE: 115 MM2 WORKING TEMP RANGE: -20°C TO +70°C HARDNESS OF RUBBER: 50-60 SPECS AS PER BS-1154 SIZES OF ITEM WEIGHT: 10 KGS LENGTH: 7 FT WIDTH: 1 FT THICKNESS: 3/8 INCH OEM/ COUNTRY OF ORIGIN/ MANUFACTURE: (1) ADD GIBSUN CORP GIBSUN@LIVE.COM (2) LONGMAN QAISER BAHTTI 0321-2490174 (3) SALOGI MANSION JAMEELA ST. MA JINNAH ROAD KARACHI 021-32720552	
90	DNF50669	DEF107A B22996 , 62-2PT2	058379910503 3 / TORCH HAND ELECT WATERPROO F R/A HEAD SPARE LAMP SZ 187X43MM		27 / EACH/N UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
91	DGE64180	NO DATA AVAILAB LE	047259523774 4 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	84 / EACH/N UMBER						TECHNICAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM - Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating:181N. GENERAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM - Internal dia 44.5 CM Thickness 11.5 CM Buoyancy Rating:181N.	
92	DGE64577	NO DATA AVAILAB LE	047259523774 4 / Life Bouy Ring (Orange) with SOLAS Reflective Tape	FOR SHIPS/BOATS	8 / EACH/N UMBER						TECHNICAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM - Internal dia 44.5 CM Thickness 11.5CM Buoyancy Rating:181N. GENERAL SPECIFICATION - DGS-DNC 10/566 K-7355 EX597 2.5 Kg SOLAS Life Bouy Ring with Reflective Tape. 30" Diameter External dia 74.5 CM -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Internal dia 44.5 CM Thickness 11.5 CM Buoyancy Rating:181N.	
93	DPC85049	0474-7041	047450224264 2 / CEMENT PORTLAND (50 KG BAG)		350 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
94	DGE58385		047450474001 9 / TENT MK 4 COMPLETE WITH ACCESSORIES W/O JHALER WT.180 LBS	CAPACITY 5 MAN, INNER PLY 5 OZ+9 OZ, UPPER	7 / EACH IN LUMBER						TECHNICAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS: 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03 GENERAL SPECIFICATION - Length: 5.00 Meter Width: 5.00 Meter Central Height: 3.60 Meter Flies: 02 Folds: 02 Wall Height: 1.80 Meter Tent Roof & Tent Wall: Made out of 400 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) Inner Lining: Made out of 150 gm/m2 cotton canvas which is rot proof, waterproof and fireproof (Dyed Canvas) All accessories are required with Tent Iron Poles (01 x Centre & 02 x Ride) Iron Hammer (05 kg) Iron Stick for walls Iron pins Iron pegs Repair Kit P. E Ground Sheet of 180-200 Gsm Mill	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENO	Model	SR NO OF PR	MANUF. ACO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Test Certificate / Lab Report ISO 9001, ISO 14001 OUTER/UPPERFLY CANVAS 100% COTTON ROTPROOF & WATER PROOF. LIST OF ACCESSORIES: IRON PIG X 22 ROPE X 22 BAMBOO (STAND POLE) X 03	
95	DNJ60347	Z565003700	2990785027157 / GASKET COPPER ID 27MM O/D 35MM THICKNESS 1MM L0063	DAIHATSU DIESEL GENERATOR 6PSH-TD-26 NSR	6 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
96	DGB51177	NO DATA AVAILABLE	3110715058603 / ROLLER BEARING NU 232 M/C3 SIZE 160X290X48 MM	D/G SET 800K/W 450V 60HZ	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
97	DNJ62761	E225800010B	2815765047759 / EXHAUST VALVE STEEL LG 300MM SEAT 71MM TH 16MM		12 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
98	DNZ60369	R21410	2815765038394 / JOINT RING STEEL ON CYLINDER LINER 610MM O/D 758 MM ID 26M-CF005	MAIN ENGINE 8RLB 66 NASR	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
99	DGE48675	530300/T 41114/RC5 56000	4220505084569 / KNIFE DIVERS (SEAHWK/ AQUALUNG KNIFE) WITH LEG CLASP BLADE LENGTH APPROX)		17 / EACH/NUMBER	/Cressi orca, black					TECHNICAL SPECIFICATION - BRAND: AQUA LUNG 7 1/2" POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE: BLACK CONTOURED RUBBER HANDLE. GENERAL SPECIFICATION - BRAND: AQUA LUNG 7 1/2" POLISHED BLADE WITH 6" SCALE AND SERRATED SAW EDGE. HANDLE: BLACK	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			180MM/ SEAHWK/ AQUAL UNG KNIFE								CONTOURED RUBBER HANDLE.	
100	DNZ65134	MXS-60115-SEW/520	4320765060507 / MECHANICAL SEAL Inner DIA 60mm, length 115mm	CARGO FRESH WATER PUMP	2 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. DIMENSION INNER DIA Bore 60 mm b. Length 115 mm c. M/seal outer dia 80 mm d. Stationary dia 82 mm GENERAL SPECIFICATION - a. DIMENSION INNER DIA Bore 60 mm b. Length 115 mm c. M/seal outer dia 80 mm d. Stationary dia 82 mm	
101	DNQ58138	ACG-72019	4210785088910 / SPRING HOLDER FOR FIRE EXTINGUISHER	FOR FIRE EXTINGUISHER ALL TYPES	265 / EACH/NUMBER						TECHNICAL SPECIFICATION - Hold the syphon tube of fire extinguisher GENERAL SPECIFICATION - HOLD the syphon tube of fire extinguisher	
102	DNQ63203	ACG-72019	4210785088910 / SPRING HOLDER FOR FIRE EXTINGUISHER	FOR FIRE EXTINGUISHER ALL TYPES	722 / EACH/NUMBER						TECHNICAL SPECIFICATION - Hold the syphon tube of fire extinguisher GENERAL SPECIFICATION - HOLD the syphon tube of fire extinguisher	
103	DGE50755	NIL	4020999237121 / ROPE NYLON, HAWSERLAID, 3-STRO, CIR 1.00" DIA 0.3125" (8MM)	NGTH 1.330 TONS UNIT OF AVAILABILITY	780 / FATHOM						TECHNICAL SPECIFICATION - SPECS: BS: 4928/74 PART-2 TABLE1, BS: EN-696 ISO: 1140 OF 2004 120 FAHTAM PER COIL REQUIRED. GENERAL SPECIFICATION - SPECS: BS: 4928/74 PART-2 TABLE1, BS: EN-696 ISO: 1140 OF 2004 120 FAHTAM PER COIL REQUIRED.	
104	DGE52795	NIL	4020999237133 / ROPE NYLON, CIRCUMFERE NCE: 5 INCH, DIA: 40MM, 2-LAY, 3-STRAND,		480 / METER						TECHNICAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005, 4. LENGTH: PER COIL, 120 FATHOM, 5. OEM COC REQUIRED, 6.	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECS: BS4928 GENERAL SPECIFICATION - 1. TO BE COMPLY WITH THE SPECIFICATION OF ISO 1140-2004, 2. TO BE MANUFACTURED/ MARKING AND LABELING OF THE ROPES IN ACCORDANCE WITH ISO 9554: 2005(E), 3. ROPE ARE REQUIRED TO BE TESTED AS PER ISO 2307 OF 2005, 4 LENGTH: PER COIL: 120 FATHOM, 5. OEM COC REQUIRED. 6. SPECS: BS4928	
105	SGB570 63	A1226-1-0	311000227327 6 / BEARING BALL ANNULAR SZ 40.00X90. 00MMX1.4375 IN		10 / EACH/ UMBER						TECHNICAL SPECIFICATION - OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required GENERAL SPECIFICATION - OEM Timken, Country of origin USA OEM COC/ Authorized Dealership Certificate Required	
106	DNG631 93		512000017284 4 / POP RIVETING MACHINE		2 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
107	DGB393 96	MODEL P- 40	513076501639 4 / ELECTRIC PORTABLE PLANNER AND GROOVERS (C/W/D 136 MAX-C/D 3MM)	GENERAL USE	5 / EACH/ UMBER						TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
108	SGB566 25		512070505656 8 / SCREW DRIVER PHILIPS 8" LENGTH SMALL	FOR GENERAL USE	15 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
109	SGB566 22		512070505657 3 / SCREW DRIVER FLAT BLADE 8 1/4" TIP WIDTH	FOR GENERAL USE	15 / EACH/ UMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
110	DNG63601	NO DATA AVAILABLE	4730001892614 / UNION STEEL		4 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - MATERIAL STEEL 250PSI WOG NOM SIZE=6MM(1/4 INCHES) LENGTH MIN=39.37MM(1.555 INCHES) NPT=1/4-18 DASH NO: 22TA COUNTRY: USA</p> <p>GENERAL SPECIFICATION - MATERIAL STEEL 250PSI WOG NOM SIZE=6MM(1/4 INCHES) LENGTH MIN=39.37MM(1.555 INCHES) NPT=1/4-18 DASH NO:22TA COUNTRY: USA</p>	
111	SGB51521	FLG02-SEW/gd1152 / 1001357	4730995253347 / FLANGE PIPE ROUND	FOR GENERAL USE	10 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - Inner dia 1 1/4 inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness 1/2 inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn8%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches</p> <p>GENERAL SPECIFICATION - Inner dia 1 1/4 inch Pitch circle dia 3 7/16 inch Outer dia 4 3/4 inch 04 x holes of 11/16 inch Thickness 1/2 inch Material Leaded Gunmetal LG2 or LG4 (both are acceptable) Material Composition: cu 85%, zn 4%, sn6%, pb 3% Size: (1dxodxth) 1.250 inch x 4.755inchs x 0.438 inches</p>	
112	SGB51525		4730995311398 / FLANGE PIPE STEEL ROUND SIZE 4.0X8.50X0.50 INCH	GENERAL USE	100 / EACH/NUMBER						<p>TECHNICAL SPECIFICATION - SPECIFICATION : BS10 AS PER BR-320D NOMINAL SIZE: 100 MM, NOMINAL BORE: 4 INCH, FLANGE OD: 8-1/2 INCH, FLANGE THICKNESS: 1/2 INCH, BOLT HOLES SIZE: 11/16 INCH, NO. OF BOLT HOLES: 4 (DATA SHEET FROM CATALOG OF NAVAL STORES IS ENCLOSED)GENERAL SPECIFICATION - SPECIFICATION : BS10 AS PER BR-320D NOMINAL SIZE: 100 MM, NOMINAL BORE: 4 INCH, FLANGE OD: 8-1/2 INCH, FLANGE THICKNESS: 1/2 INCH.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											BOLT HOLES SIZE: 11/16 INCH. NO. OF BOLT HOLES: 4 (DATA SHEET FROM CATALOG OF NAVAL STORES IS ENCLOSED)	
113	SG854698	BR3013-SHEET3.1.2	473099531137 8 / FLANGE PIPE STEEL ROUND 2		10 / EACH/NUMBER						TECHNICAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch, b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm, GENERAL SPECIFICATION - a. Specification: flange pipe steel round 2, bore 2 inch, b. Dimension: Inner Dia 2 inch (51 mm), c. Outer Dia: 5 inch (125 mm) and d. thickness: 13 mm.	
114	SNZ5858	ATX71110 0 DHS	481078502661 3 / VALVE THERMAL EXPANSION REFRIGERANT R-22 CAPACITY 17.8TON	AIR CONDITIONER PLANT MODEL 6C75-EB NASR	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
115	DNZ60301	306	530678503913 7 / COUPL BOLT WITH NUT&S. WASHER STEELU-352 SZ 53.00 00X14.00MM	AIR CONDITION SEA WATER PUMP PNS NASR	16 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL: SSGENERAL SPECIFICATION - MATERIAL: SS	
116	DNZ60360	R27429	533078503432 3 / O,RING FOR STARTING AIR VALVE HOUSING ID135.87X7MM CF-122	MAIN ENGINE 8RLB-66 NASR	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
117	DNZ60361	R27231	533078503433 7 / O RING RUBBER 29X3.50MM CF-121	MAIN ENGINE 8RLB 66 NASR	8 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
118	DNZ60366	R21411/R27127	533078503450 6 / O RING FOR CYLINDER LINER AND COVER 850X9MM RUBBER CF-113	DALIAN SULZER DIESEL ENGINE -8 RLB60	16 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
119	SGE47953	FP6F3	564000237482 8 / INSULATION SLEEVING TUBE		25 / EACH/NUMBER						TECHNICAL SPECIFICATION - SLEEVE SIZES: LENGTH: 06 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPECS/PICT ARE ATTACHED WITH WIMS NOTE: LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGASINT FOREIGN NSN OEM: FORTE PAKISTN GENERAL SPECIFICATION - SLEEVE SIZES: LENGTH: 06 FEET, INNER DIA: 03 INCH (76MM), THICKNESS: 3/4 INCH (19MM). TDS/SPECS/PICT ARE ATTACHED WITH WIMS NOTE: LOCAL STORE IS REQUIRED/ACCEPTED BY END USER AGASINT FOREIGN NSN OEM: FORTE PAKISTN	
120	DNF62012	158-51010	596199558030 7 / DIODE 25AMPS 600VOLT.	MAIN RECTIFIER ASSY	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
121	DNF61502	158-51020	596199558031 4 / REVERSE DIODE	D/GENERATOR (PNS RAJSHAH)	3 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
122	DNF39769	6X120 EXIDE/ 6X15/ exide n-140 plus	614070502360 7 / BATTERY SECONDARY 105AH 12V SZ 367X173X228. MM EXIDE		2 / EACH/NUMBER	6X120EXIDE/ EXIDE N-140 PLUS local					TECHNICAL SPECIFICATION - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS GENERAL SPECIFICATION - 12 V, Volt 12 V DC Amp 105 AH OEM Exide/ AGS	
123	DNZ59351	DH5-1	622078100498 6 / MAST LIGHT FITTING RED	LIGHTING SYSTEM TURKEY	29 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / DENG	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GLASS DH5-1 105/M									
124	DN283605	DH5-1	822078100498 6 / MAST LIGHT FITTING RED GLASS DH5-1 105/M	LIGHTING SYSTEM TURKEY	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
125	DGB33333	MATERIAL GRADE EN4140	026859003333 3 / SCREW MACHINE STEEL BSW HEX HD F/THRD SZ 1.00X0.375IN TPI 16		100 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material grade EN4140 GENERAL SPECIFICATION - material grade EN4140	
126	SGB47556	CH50-10	024650000106 5 / BLOCK CHAIN 5 TON 5 METER CHAIN (ORIGINAL ELEPHANT JAPAN)		1 / EACH/NUMBER	CH50-10					TECHNICAL SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10, 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn), Maximum working load is 05 Ton, Height of lift is 40' GENERAL SPECIFICATION - MADE /Brand: Elephant Japan Model: CH50-10, 5 Tons, Shipping Weight: 84.0 Lbs, Test load: 7.5 Tons, Load Chain size: 3.54 INCH, Weight: 84 Lbs, Type: Manual, Acceptance Criteria: Lifting of 5 Tons Load Maximum distance from Hook to Hook is 45' (when drawn), Maximum working load is 05 Ton, Height of lift is 40'	
127	DGE63731	NO DATA AVAILABLE	033050000013 8 / CALICO CLOTH BLEACHED WIDTH 36 LENGTH 15 FT	GENERAL USE	685 / KILOGRAMME	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/50 MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX) GENERAL	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											SPECIFICATION - material: Polyester Cotton WIDTH: 91.4 CM ± 1CM (36") WT/SQ MTR: 115 TO 130 GRAM THREAD/CM: WARP = 24/25 , WEFT=17/18 COUNT OF YARN: 20/21S SHRINKAGE: 2% (MAX) SCOURING LOSS: 1% (MAX)	
126	DGE64147	NO DATA AVAILABLE	0340500000010 / CANVAS COVER WATER PROOF		5 / EACH/NUMBER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - Water Proof. In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand) GENERAL SPECIFICATION - Water Proof. In single sheet Size: 30 x 30 feet Colour: Olive Green Usage: Multipurpose use for NA Stores Weight: 60 + 5 KG Material: 100% Cotton Canvas Cloth Thickness: As per sample OEM: Local Manufacturer (Pakistan) Stock Sample / Reference Sample Material as per sample (enclosed by hand)	
129	SGE49383	NO DATA AVAILABLE	0413500000132 / EAR DEFENDER-SMALL SIZE		1000 / PAIR	NO DATA AVAILABLE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
130	SGE49353	NO DATA AVAILABLE	0413500000133 / EAR DEFENDER		18 / PAIR	PELTOR H10A/OPTIME 105					TECHNICAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained Technical data provided in EN 352-2. Reduces noise levels by ~ 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model: pletor h10a/OPTIME 105 3M Ear Defender Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip) GENERAL SPECIFICATION - acceptance on delivery or at the time of inspection may be obtained	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Technical data provided in EN 352-2. Reduces noise levels by + 20-30 dB. a. Ear defender medium size (Pic of packing and ear defenders are enclosed) b. Make: PELTOR Model: pletor n10a/OPTIME 105 3M Ear Defender-Bilsom Viking Medium Size (HAC Hardwar & Industrial Safety Equip)	
131	DNF81332	AGFA-G335	6750PK506905 1 / AGFA FIXER G335- FOR RADIO FILM	X-RAY MACHINE SMART 225	40 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
132	SGE49297	NO DATA AVAILABL E	046150000008 6 / GOGGLE CHIPPING		1700 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Acceptance criteria: Physically Inspection usage: Chipping and grinding work OEM: PAKISTAN GENERAL SPECIFICATION - Acceptance criteria: Physically Inspection usage: Chipping and grinding work OEM: PAKISTAN	
133	SPC54158	R-5002	801070511103 7 / PIGMENT (BRIANT WHITE)	GRP WORK, M/S ZAIN SONS. KARCHI.PH, 7731541	80 / KILOGR AMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
134	SGE49530		813570506488 2 / TAPE TRANSPAREN T ADHESIVE WATER PROOFED WD.12 MM LG 68 MTR.	GENERAL USE.	180 / ROLL						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
135	DNF61699	390DCS/2	803077501631 0 / DEGREASER CLEANER, SOLVENT NON OILY (200ML)	PCB CLEAN MATERIAL (M/S PERFECT BELGIUM)	2 / EACH/N UMBER	390DCS/0 0					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
136	DGE53951		031050000000 4 / CANVAS COTTON		1179 / METER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - SIZE: WIDTH 24" WEIGHT 24 OZ PER SQ YD. ROT PROOF & WATER	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			GREY (WD: 24")								PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance GENERAL SPECIFICATION- SIZE: WIDTH 24" WEIGHT 24 OZ PER SQ YD ROT PROOF & WATER PROOF MIN TENSILE STRENGTH ON 5X20 CM STRIPS- Specification PS-319 OF 1986 VARIETY NO 7 advance sample will provided to cins for acceptance	
137	SGE56506	NO DATA AVAILABLE	0310500000006 / CANVAS COTTON NATURAL GREY (WD: 36 INCH)		600 / METER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION- SPECIFICATION: WATER PROOF AND ROT PROOF WIDTH: 36 INCH WEIGHT: 12 OZ PER SQ YARD COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY. GENERAL SPECIFICATION- SPECIFICATION: WATER PROOF AND ROT PROOF WIDTH: 36 INCH WEIGHT: 12 OZ PER SQ YARD COLOUR: NATURAL GREY GEN SPECS: 1. PS-319 OF 1986 VARIETY NO 2 TABLE 1 2. ADVANCE SAMPLE TO BE APPROVED BY CINS PRIOR BULK SUPPLY.	
138	DGE02006	NO DATA AVAILABLE	8340505039261 / SHAMIANA SIZE 18 X 36 COMPLETE WITH ALL ACCESSORIES 3 IN NO		5 / EACH IN NUMBER						TECHNICAL SPECIFICATION-: 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. Colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-191, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative)	

S No	LPR No	PART NO	NSN / Description	Pr Equipment	QTY / DENO	Modul	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Length 12 feet min with 02 spare . 7. Hammer: 05 Lbe with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759. Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbe with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p>	
139	DGE60011	NO DATA AVAILABL E	834050503926 1 / SHAMIANA SIZE 18.X 36. COMPLETE WITH ALL ACCESSORIE S-3 IN NO		5/ EACH/N UMBER						<p>TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759.</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos GENERAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare . 7. Hammer: 05 Lbs with handle. qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhaler : 06 in Nos Ropes : 05 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p>TECHNICAL SPECIFICATION - 1. Material: Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in</p>	
140	DGE625 31	NO DATA AVAILABL E	834050503926 1 / SHAMIANA SIZE 18 X 36. COMPLETE WITH ALL ACCESSORIE		5/ EACH/N UMBER							

S. No	LIFE No	PART NO	NSN / Description	Equipment	QTY / GENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			S 3 IN NO								<p>Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle, qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhalar : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p><u>GENERAL SPECIFICATION - 1 Material:</u> Specification PSG-248, 100% Cotton Cloth. 2. colour: Cedar Green BCC 80. 3. Print: White. (Suitable Print) 4. Rope: PSG-101, 100% Cotton, dia 1 inch Qty 08 in Number Length 25 feet. 5. Iron Pin: 08 in Number, Length 18 inch, dia 1 1/4 inch. 6. Bamboo: PSG-758 & 759, Qty 06 in Number, Min dia at bottom 3.5 & at top 2.5 inch should be Rot proofed (treated with Preservative) Length 12 feet min with 02 spare. 7. Hammer: 05 Lbs with handle, qty 01 8. Handle material: Kahoo/Sissoo or Teak wood of 2.5 feet length, 9. Eyelets brass: PSG-283 10. Leather: PSG-9 (b) Vegetable tanned Leather Piece insert in between (EYE PIECE) the all Caps for Strengthening. 11. COMPLETE ACCESSORIES: Jhalar : 06 in Nos Ropes : 06 in Nos Nails: 06 in Nos Hammer: 01 in Nos Bamboo: 06 in Nos</p> <p><u>TECHNICAL SPECIFICATION - NO DATA AVAILABLE</u> <u>GENERAL SPECIFICATION - NO DATA</u></p>	
141	SGE479 52	4800	831099139716 0 / GLASS SEWING	E&H VOL BELLOWS	6 / EACH/N UMBER							

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
			THREAD 03 STRAND WEIGHT PER REEL 0.5 KG (UK MADE)								AVAILABLE	
142	SGE51704	NO DATA AVAILAB L E	045150000002 1 / CLOTH TIKEN BLUE STRIPS WIDTH 58 INCHES		150 / METER	NO DATA AVAILAB L E					TECHNICAL SPECIFICATION - a. WIDTH:58 INCH(1.473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT2/206 e. SHRINKAGE- WARP: 2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS) GENERAL SPECIFICATION - a. WIDTH:58 INCH(1.473MTR) b. WT/SQ MTR(GM);200 ± 05 c.NO OF THREAD/INCH=WARP:40 WEFT:40 d.COUNT OF YARN WARP:2/206 WEFT2/206 e. SHRINKAGE- WARP: 2%(MAX) WEFT:2%(MAX) f.DYE FASTNESS TO WASHING TEST NO.3 (FOR BLUE STRIPS)	
143	DPK63939	H 572	915099220346 8 / OIL OM 85 (Packing = 05 liters)	30MM GUN	428 / LITER						TECHNICAL SPECIFICATION - bs-4475 of 2000 grade cs 88 defstan 01-5/issue 17 mar 11 200 Ltr drum GENERAL SPECIFICATION - bs-4475 of 2000 grade cs 88 defstan 01-5/issue 17 mar 11 200 Ltr drum	
144	DPK64527	H 572	915099220346 8 / OIL OM 85 (Packing = 05 liters)	30MM GUN	330 / LITER						TECHNICAL SPECIFICATION - bs-4475 of 2000 grade cs 88 defstan 01-5/issue 17 mar 11 200 Ltr drum GENERAL SPECIFICATION - bs-4475 of 2000 grade cs 88 defstan 01-5/issue 17 mar 11 200 Ltr drum	
145	SGE38542	NO DATA AVAILAB L E	932070505898 4 / RUBBER STRIP (FOAM TYPE) SIZE 30 X 20 INCH	GENERAL USE	140 / METER						TECHNICAL SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPDM) GENERAL SPECIFICATION - Rubber Type: Ethylene-Propylene Rubber (EPDM)	
146	SGE49351		933099224809 0 / PLASTIC SHEET LAMINATED COLOUR	GENERAL USE	75 / SHEET						TECHNICAL SPECIFICATION - Size: L : 8mm, w : 4mm, Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794 GENERAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			WHITE B.X4. X0.80 to 0.70 MM								Size: L: 8mm, w: 4mm. Tolerance in Thickness: 0.60mm to 0.70mm (FORMICA) SPEC: BS 3794	
147	SGB521 28		02755000002 6 / MEASURING TAPE STEEL 1/2" x 300'		3 / EACH/N UMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - Crescent Lufkin 1/2" x 300' Pro Series Engineers Ny-Clad Steel Tape Measure - Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable- steel blade under normal working condition GENERAL SPECIFICATION - Crescent Lufkin 1/2" x 300' Pro Series Engineers Ny- Clad Steel Tape Measure - Part No. PS1809DN OEM: Lufkin USA Length: 300 Feet Acceptance Criteria: Nylon Coated Alloy Steel Tape, Un-stretchable steel blade under normal working condition	
148	DGB313 51	XK- 1000/Exec el-40C	667078511607 2 / DIGITAL WEIGHING SCALE FOR RATIONS WEIGHING		1 / EACH/N UMBER						TECHNICAL SPECIFICATION - model: Any Model oem: As per procured model end user: VSD usage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx. 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter, ii. Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration GENERAL SPECIFICATION - model: Any Model oem: As per procured model end user: VSD usage: digital weighing scale required to weight of ration approx. 1000 Kg Base weighing plate minimum size shall be approx. 4ft x 4ft Testing may please be carried out at VSD/CINS as OEM CoC: Authorized dealer certificate product list: i. Digital calibration meter, ii.	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Electrical panel iii. Main body with grill iv. Size if weighing plate 4ft x 4 ft The item is to used for weighing of ration	
149	DPC569 50	TS10268/ ZOK 27	685099225402 0 / COMPRESSO R CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSO R G.T.E.TYPE 21	150 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
150	DPC627 52	TS10268/ ZOK 27	685099225402 0 / COMPRESSO R CLEANING INHABITING FLUID (CCIF) P/NO ZOK 27	CLEANING FLUID COMPRESSO R G.T.E.TYPE 21	150 / LITER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
151	SPC5212 4	P-21	681070508042 0 / DE- SCALLING COMPOUND ARCOBURAG (DEM ARCO PACKING 20 TO 25 KG)	A/C PLANT CHILLER WATER CONDENSER SHEEL	150 / KILOGR AMME						TECHNICAL SPECIFICATION - >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning. GENERAL SPECIFICATION - >ARCOBURAG P-21 is a powder, full strength scale remover containing acid inhibitors, color indicators & wetting agents. >Dissolves scale, algae and bacteria thereby increasing water handling efficiency. >Lowers surface tension, accelerates penetration and ensures complete cleaning.	
152	DPC594 51	CAT ELC TM (2056612 or 2056611)	681070508453 2 / CAT ELC TM EXTENDED LIFE COOLANT FOR RADIATOR OF	CP AIR COMP	200 / LITER						TECHNICAL SPECIFICATION - TDS & IPC Enclosed GENERAL SPECIFICATION - TDS & IPC Enclosed	

S. No	LPR No	PART NO	NSN / Description	PrEquipment	QTY / GENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			CATERPILLAR (Packing 20 LITER or 05 Liter Can)									
153	DNF53774	ATLAS	6625715110586 / NETWORK ANALYSER MODEL ATLAS CABLE TESTER IT PEAK	CABLE TEST. M/S MAKKAYS 40T/3 BLK/ PECHS	1 / EACH/NUMBER						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
154	SG848516	NO DATA AVAILABE	5310705126321 / HEX NUT STAINLESS STEEL SIZE INNER DIA 1/2 OUTER DIA 3/4 INNER THREAD 12 T. P. BSW	FITTING OF QSB 6.9 CUMMINS ENGINE FOUNDATION PLATES WITH BOAT HULL	400 / EACH/NUMBER						TECHNICAL SPECIFICATION - MATERIAL: SS 316 GENERAL SPECIFICATION - MATERIAL: SS 316	
155	DNJ62760		2340715127947 / WATER SCOOTER WITH STOWAGE TROLLEY AND RAIN PROTECTING COVER	WATER SCOOTER VX-1100 SPORTS	1 / EACH/NUMBER	VX1050E-A / VX-1100 SPORTS					TECHNICAL SPECIFICATION - COLOR: CYAN WITH BLACK LENGTH: 3.37 M WIDTH: 1.24 M HEIGHT: 1.20 DRY WEIGHT: 310 ENGINE TYPE: 3-CYLINDER, 4 STROKE TR-1 HIGH OUTPUT YAMAHA MARINE ENGINE DISPLACEMENT: 1049 CC BORE x STROKE(mm): 82 x 66.2 COMPRESSION RATIO: 11.0 : 1 COOLING SYSTEM : WATER COOLED PUMP TYPE : 155MM AXIAL FLOW FUEL TYPE RECOMMENDED : REGULAR UNLEADED FUEL SUPPLY SYSTEM: ELECTRONIC FUEL INJECTION FUEL CAPACITY (LITER): 70 LUBRICATION SYSTEM: DRY SUMP TOTAL OIL CAPACITY (LITER) : 3.5 STORAGE CAPACITY (LITER): 113.9 RIDER CAPACITY: 1-3 PERSONS MODEL YEAR : 2024 DISPLACEMENT: 1049 CC, 4 STROKE GENERAL SPECIFICATION - COLOR: CYAN	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>WITH BLACK LENGTH: 3.37 M WIDH: 1.24 M HEIGHT: 1.20 DRY WEIGHT: 310 ENGINE TYPE: 3- CYLINDER,4 STROKE TR-1 HIGH OUTPUT YAMAHA MARINE ENGINE DISPLACMENT: 1049 CC BORE x STROKE(mm): 82 x 66.2 COMPRESSION RATIO:11.0 :1 COOLING SYSTEM : WATER COOLED PUMP TYPE : 155MM AXIAL FLOW FUEL TYPE RECOMMENDED : REGULAR UNLEADED FUEL SUPPLY SYSTEM. ELECTRONIC FUEL INJECTION FUEL CAPACITY (LITER): 70 LUBRICATION SYSTEM. DRY SUMP TOTAL OIL CAPACITY (LITER) : 3.5 STORAGE CAPACITY (LITER): 113.9 RIDER CAPACITY: 1-3 PERSONS MODEL YEAR :2024 DISPLACMENT:1049 CC,4 STROKE</p>	
156	DGE486 54	2822-025- 00051	802017101264 4 / SOFT BRUSH		30 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE</p>	
157	SGB494 16		534070512426 1 / CABINET LOCK	WOODEN CABINET	160 / EACH/N UMBER						<p>TECHNICAL SPECIFICATION - material specifications grade: cp (metal key) length: 22mm dia of lock: 19mm make: khas GENERAL SPECIFICATION - material specifications grade: cp (metal key) length: 22mm dia of lock: 19mm make: khas</p>	
158	DNE5874 8	AS PER SPECIFIC ATION	614575512071 8 / pro shielded 2 core microwire electro-voice	FA SYSTEM	300 / METER	3935X30					<p>TECHNICAL SPECIFICATION - 1 Conductor Material: Pure Copper 2 Area Conductor CSA: 0.22mm square 3 External Diameter: 5.15 mm 4 Impedence: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC- 710BK, OD 6.55mm (100 Mtr Roll) GENERAL SPECIFICATION - 1 Conductor Material: Pure Copper 2</p>	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Area Conductor CSA/ 0.22mm square 3 External Diameter: 5.15 mm 4 Impedance: 75 ohm 5 Cable Type: 02 core pro shielded 6 Insulation Material: PVC (7) EV 2 core shielded Mic Wire 2C X 18 or AWG SMC-710BK, OD 8.55mm (100 Mt. Roll)	
159	DPK59581	ARDROX6345-5L	685014445180 4 / GAS TURBINE CLEANING SOLVENT PACKING 25 LITERS		20 / LITER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
160	DPK57387	LP 100/512 COATING	801074517562 9 / FOOD GRADE TOP COAT SOLVENT FREE EPOXY (60KG packing) BRAND MAXPERLES		110 / KILOGRAMME	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
161	DGE64709	IACD42106 or CITEX H-1140	424099527598 5 / SAFETY HARNESS (100% POLYESTER WITH BUCKLES & D-RING	PPE	72 / EACH/NUMBER	NO DATA AVAILAB LE					TECHNICAL SPECIFICATION - MATERIAL: 100% POLYESTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS, COLOR: GREEN/RED or CUSTOMIZED, CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH: >=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mail Shalimar Link Road Lahore Pakistan Email: info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASHI Enterprises in Sep 18. Specification may be endorsed to avoid	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max impact force of 6 KN. GENERAL SPECIFICATION - MATERIAL: 100% POLYESTER, TYPE: SAFETY HARNESS FOR GENERAL CLIMBING APPLICATIONS. COLOR: GREEN/RED or CUSTOMIZED. CERTIFICATE: CE/ISO9001 OR EN-361, STRENGTH:>=23KN, SPARE PARTS: BUCKLE, D-RING, WEBBING WIDTH: 45MM, WEBBING LENGTH: 6M, NET WEIGHT: 1 KG Safety Harness (100% Polyester with Buckles and D-Ring) in normal standard packing. a. M/S Abdullah fire Protection Pakistan Office C1 2nd Floor, Red Mall Shalimar Link Road Lahore Pakistan Email: Info@abdullahfireprotection.com.pk b. Last Procurement data through registered supplier M/S ASH Enterprises in Sep 18. Specifcation may be endorsed to avoid</p> <p>complication at later stage a. Safety Harness (100% Polyester with Buckles), Part No IACD42106. b. Standard of article should be as per EN361, EN1497, 2007. Polyester webbing should be water repellent and UV resistant for a long service. Fall arrest indicator with Rescue strop. c. Article should be 1.4 kg in weight, User weight 150 Kg including Tools and equipment with max</p>	

S. No	LFR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											Impact force of 5 KN.	
162	DPC62765	BS 627 (F-8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
163	SPC58340	BS 627 (F-8) (R 5123)	801070512876 4 / PIGMENT (LIGHT CRAFT GREY-BS627) (F8)	PIGMENT IS USED TO ACHIEVE DERIVED COLOUR	50 / KILOGRAMME						TECHNICAL SPECIFICATION - NO DATA AVAILABLE GENERAL SPECIFICATION - NO DATA AVAILABLE	
164	DG962931	WORKING 100PSIG MAX FLANGE CONN-	024154600193 4 / GATE VALVE 1.5" PRESSURE 100PSI		8 / EACH/NUMBER						TECHNICAL SPECIFICATION - Specifications: Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves Make : Kurtak Vana Sanayi VE Ticaret Ltd, STI, connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb GENERAL SPECIFICATION - Specifications: Gate Valve (Non-Rising Stem) with indicator, Flanged, 1.5", Pressure 100 PSI Testing/ Acceptance Criteria: Relevant ISO standards for sea water valves Make : Kurtak Vana Sanayi VE Ticaret Ltd, STI, connection type: flange flange Standard: din 3202-f4 working temperature: +180 c body material: g-cusn5znpb	
165	SNF52839	MCTX-4PRT-SWITCH	593070524871 2 / 4 PORT SWITCH		10 / EACH/NUMBER	MCTX-4PRT-SWITCH					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
166	DNO61551	GOMTEX Ø 30310003800	473070526970 9 / hose assy rubber duraline/ gometex lg 100 ft id 1-1/2"		4 / EACH/NUMBER	HOSE ASSY RUBBER DURALINE/ GOMETE X LG 100 FT ID 1-1/2"					TECHNICAL SPECIFICATION - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availabilty	Tender Remarks	TECH / GEN SPECS	Dimension
											<p>specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. GENERAL SPECIFICATION - Dia: 1½ inch (32 mm) Length: 100 feet (30 meters) Coupling: on both side as per BS 336:2010 compatible British instantaneous type coupling of Bronze/ Gun Metal material. Working pressure: 20 bar Test pressure: 40 bar Applicable Standards: hose shall meet BS 6391:2009 Type-3</p> <p>specification. Only Kite marked / BSI / UL/ FM/ VdS approved products are to be acceptable. SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE.</p> <p>TECHNICAL SPECIFICATION - VGA , HDMI H265/264 codec decoding max 200Mbps incoming bandwidth. Upto 16 IP Camera inputs. UPnP, upto 8MP resolution for preview and playback, 16 Poe ports. HDMI/ VGA simultaneous video output, note you must have 4K monitor to display 4k image via HDMI port. Memory : 6 TB HDD: 6 TB No of Channels: 16 GENERAL SPECIFICATION - VGA , HDMI H265/264 codec decoding max 200Mbps incoming bandwidth. Upto 16 IP Camera inputs UPnP, upto 8MP resolution for preview and playback, 16 Poe ports. HDMI/ VGA simultaneous video output, note you</p>	
167	DNF53768	DH-XVR5116H S-13/ DH-XVR5116H S-12	599978624886 2 / 16 CHANNEL DVR COMPLETE WITH ACCESSORIES		1 / EACH NUMBER	DH-XVR5116HS-12						

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / GENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											must have 4k monitor to display 4k image via HDMI port. Memory : 6 TB HDD: 6 TB No of Channels: 16	
168	DNF55968	WINXP (SP3 ONWARD S) /VIST/WIN 7/ WIN8 WIN10/MAC/LINUX	5998705277567 / SVAS SECURE 4G DATA WINGLESjazz (DEVICE)		6 / EACH/NUMBER	NA					TECHNICAL SPECIFICATION - 4G DATA WINGLE GENERAL SPECIFICATION - 4G DATA WINGLE	
169	DGE64951	CTLBS12202003	5340735267409 / BASE 4' (1220 X 200 X 3MM)		96 / FOOT RUN	BASE 4' CTLBS12202003					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1220 X 200 X 3MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
170	DGE64931	CTLCB10008025	5340735267410 / CANTILEVER BRACKET 3' (1000 X 80 X 2.5MM)		72 / EACH/NUMBER	CANTILEVER BARACKET 3' CTLCB10008025					TECHNICAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: CHANNEL SECTION: 1000 X 80 X 2.5MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	
171	DPK64152	Polysulphide GG	8030705287063 / SIKA Polysulphide GG sealant (2.5 LITERS COMP. A / 4.0 LITERS COMP. B)		100 / LITER	POLYSULPHIDE GG					TECHNICAL SPECIFICATION - DENSITY -1.58 KG./L. SOLID CONTENT 100% GENERAL SPECIFICATION - DENSITY -1.58 KG./L. SOLID CONTENT 100%	
172	DNC64749	TM-C-S02	2520735237682 / CARDAN SHAFT		4 / EACH/NUMBER	HJ322					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
173	SRG42524	170377	2930705141605 / RADIATOR		2 / EACH/NUMBER	FIAT 640					TECHNICAL SPECIFICATION - MAKE/MODEL FIAT 640 PARENT EQUIPMENT FIAT 640 TRACTOR	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											OEM COC/DEALER CERTIFICATE YES (IF APPLICABLE) GENERAL SPECIFICATION - MAKE/MODEL FIAT 640 PARENT EQUIPMENT FIAT 640 TRACTOR OEM COC/DEALER CERTIFICATE YES (IF APPLICABLE)	
174	DG852491	8004	534070524680 9 / perforated ss ladder steps fitted onboard f22ps 12-swg gR.304		75 / EACH/NUMBER	na					TECHNICAL SPECIFICATION - S No Measurement Value Remarks a. Length: 600mm - b. Width : 180mm - c. Depth(lengthwise) 40mm With slight bend towards inner side d. Depth (Widthwise) 30mm With slight bend towards inner side e. Thickness 2mm - f. Distance between TWO HOLES FOR BOLTS: 120MM (AT WIDTH SIDE) size: Step with L= 180mm, W= 600mm Step with L= 180mm, W= 500mm GENERAL SPECIFICATION - S No Measurement Value Remarks a. Length: 600mm - b. Width : 180mm - c. Depth(lengthwise) 40mm With slight bend towards inner side d. Depth (Widthwise) 30mm With slight bend towards inner side e. Thickness 2mm - f. Distance between TWO HOLES FOR BOLTS: 120MM (AT WIDTH SIDE) size: Step with L= 180mm, W= 600mm Step with L= 180mm, W= 500mm	
175	DN055014	7620.740.0 13.5 / FIL230912	2815FP303039 3 / FUEL DUPLEX FILTER		19 / EACH/NUMBER	TBD620V 12					TECHNICAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps GENERAL SPECIFICATION - FUEL DUPLEX FILTER Item Name: Lead Acid Battery (Maintenance Free) Make: Power Sonic Model: PG - 12V 22 B Technical Detail: 12V, 22Amps	
176	BNF5394E	VE/3 Pin S. Socket/FP	593050523486 4 / 3 Pins switch socket		50 / BOX	VE/3 PIN S. SOCKET					TECHNICAL SPECIFICATION - OEM, VISION ENG, AGHAR COLONY KARACHI 21-75385382	

S. No	LPR No	PART NO	NSN / Description	PEquipment	QTY / DENO	Model	SR NO OF PR	MANUF ADD	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
		1020	250 volt 10 amps			FP.1020					INFO@VISION-ENGG.COM TECH-SPECCS, 220-250V, 10AMP, MARINE INDUSTRIAL, BRASS MATERIAL IP56, DIN89262GENERAL SPECIFICATION - DEM, VISION ENG, AKHTAR COLONY KARACHI 21-35385382 INFO@VISION-ENGG.COM TECH-SPECCS, 220-250V, 10AMP, MARINE INDUSTRIAL, BRASS MATERIAL IP56, DIN89262	
177	DNQ63358	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		3 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMETEX LG 100 FT ID 2"					TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usaGENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
178	DNQ61650	GOMTEX Ø 30310005000	473070526970 8 / hose assy rubber duraline /gometex lg 100 ft id 2"		4 / HUNDRED FT	HOSE ASSY RUBBER DURALINE /GOMETEX LG 100 FT ID 2"					TECHNICAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usaGENERAL SPECIFICATION - SPECIALLY FORMULATED RUBBER, I EXTRUDED THROUGH A CIRCULAR WOVEN. LOW PRESSURE DROP THANKS TO ITS SMOOTH INNER WALL, HIGH THERMAL RESISTANCE. oem/country of origin GOMTEX/ usa	
179	DNFB457	A074A915	599879528498		1 /	A074A905					TECHNICAL SPECIFICATION -	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
	4		7 / LCD CONTROL BOARD		EACH/NUMBER						Power Supply: 14 V 3.5 Amp AC GENERAL SPECIFICATION:- Power Supply: 14 V 3.5 Amp AC	
180	DPK63551	TELLUS S2 MX 46	2590715148513/ HYDRAULIC OIL (SHELL TELLUS S2 MX 46)		200 / LITER	NO DATA AVAILABLE					TECHNICAL SPECIFICATION:- SHELL TELLUS S2 MX 46 ISO FLUID TYPE = HM GENERAL SPECIFICATION:- SHELL TELLUS S2 MX 46 ISO FLUID TYPE = HM	
181	DNQ63331	BP002	4220785289108 / CSM Life raft - Firstaid kit		15 / BAG	BP002					TECHNICAL SPECIFICATION:- null GENERAL SPECIFICATION:- null	
182	DNQ64387	334 series	4240715269613 / 3m safety goggles		40 / EACH/NUMBER	334 series					TECHNICAL SPECIFICATION:- null GENERAL SPECIFICATION:- null	
183	DNZ58916	E-02-14	4810785277589 / SECONDARY INTAKE VALVE		1 / EACH/NUMBER	MCH18-Standard Super silent breathing air compressor.					TECHNICAL SPECIFICATION:- null GENERAL SPECIFICATION:- null	
184	DNF63005	J9776A/r8n88a	7035715248832 / HP ARUBA 2530 24G network switch		2 / EACH/NUMBER	ARUBA 2530 24G (J9776A)					TECHNICAL SPECIFICATION:-HP ARUBA 24 PORT NETWORK SWITCH GENERAL SPECIFICATION:- HP ARUBA 24 PORT NETWORK SWITCH	
185	DNF54578	DGS-1510-28X_DEM-310GT.	5930705246333 / D-LINK 24 PORTS 10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & DEM-310GT)		2 / EACH/NUMBER	dgs-1510-28x_DEM-310GT.					TECHNICAL SPECIFICATION:- null GENERAL SPECIFICATION:- null	
186	DNF55115	DGS-1510-28X_DEM-310GT.	5930705246333 / D-LINK 24 PORTS		5 / EACH/NUMBER	dgs-1510-28x_DEM-310GT.					TECHNICAL SPECIFICATION:- null GENERAL SPECIFICATION:- null	

S. No	LPR No	PART NO	NSN / Description	Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ACC	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
			10/100/1000 MBPS+4 10G SFP+PORTS SMARTPRO SWITCH, (EU PLUG) WITH 4 X K-LINK 1-P LX SM SFP (DGS-1510-28X & OEM-310GT)									
187	DNF5691 1	CPU RT-700	598875527093 7 / cpu RT-700 for surface grinding machine		1 / EACH/NUMBER	rt-700					TECHNICAL SPECIFICATION - null GENERAL SPECIFICATION - null	
188	DGE612 20	IND/FRM/2 2	719570526740 4 / FIRE RETARDANT FOAM Mattress (length 6', width 2', height 4")		41 / EACH/NUMBER	IND/FRM/22					TECHNICAL SPECIFICATION - Fire retardancy of mattress: Cover of Foam Mattress is Fire retardant only LENGTH: 6FT WIDTH: 2FT THICKNESS: 4INCH GENERAL SPECIFICATION - Fire retardancy of mattress: Cover of Foam Mattress is Fire retardant only LENGTH: 6FT WIDTH: 2FT THICKNESS: 4INCH	
189	DNF6377 5	253-PVM	594599317822 2 / RELAY UNDER VOLTAGE 253-PVM		2 / EACH/NUMBER	253 PVM					TECHNICAL SPECIFICATION - Used in ssdd 125 kw in control system for protection of under voltage SPECIFICATION OF UNDER VOLTAGE RELAY NORMAL VOLTAGE 100V - 440V AC SYSTEM FREQUENCY 45/65HZ TRIP LEVEL ADJUSTMENT UNDER VOLTAGE 75 TO 100% OVER VOLTAGE 100 TO 125% OF NORMAL INPUT VOLTAGE TIME DELAY FACTORY PRE SET UP TO 30 SECONDS GENERAL SPECIFICATION - Used in ssdd 125 kw in control system for protection of under voltage SPECIFICATION OF UNDER VOLTAGE RELAY NORMAL VOLTAGE 100V - 440V AC SYSTEM FREQUENCY 45/65HZ TRIP LEVEL ADJUSTMENT UNDER VOLTAGE	

S. No	LPR No	PART NO	NSN / Description	P/Equipment	QTY / DENO	Model	SR NO OF PR	MANUF ADO	Availability	Tender Remarks	TECH / GEN SPECS	Dimension
											75 TO 100% OVER VOLTAGE 100 TO 125% OF NORMAL INPUT VOLTAGE TIME DELAY FACTORY PRE SET UP TO 30 SECONDS	
190	DGE649 21	CTLCS150 11016	534073526741 2 / CROSS (1500 X 1100 X 1.6MM)		40 / EACH/N UMBER	CROSS CTLCS15 011016					TECHNICAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS GENERAL SPECIFICATION - PROFILE: SQUARE SECTION: 1500 X 1100 X 1.6MM MATERIAL: HR GRADE: Q-235 SURFACE FINISH: POWDER COATED 60 MICRONS	